

APPARATUS AND METHOD FOR PROCESSING FLUIDS FROM A WELL

CROSS REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to Great Britain Provisional Patent Application No. GB0625526.9, entitled "Apparatus and Method", filed on December 18, 2006, which is herein incorporated by reference.

FIELD OF THE INVENTION

[0002] The present invention relates to apparatus and methods for processing well fluids. Embodiments of the invention can be used for recovery and injection of well fluids. Some embodiments relate especially but not exclusively to recovery and injection, into either the same, or a different well.

BACKGROUND

[0003] This section is intended to introduce the reader to various aspects of art that may be related to various aspects of the present invention, which are described and/or claimed below. This discussion is believed to be helpful in providing the reader with background information to facilitate a better understanding of the various aspects of the present invention. Accordingly, it should be understood that these statements are to be read in this light, and not as admissions of prior art.

[0004] As will be appreciated, oil and natural gas have a profound effect on modern economies and societies. In order to meet the demand for such natural resources, numerous companies invest significant amounts of time and money in searching for and extracting oil, natural gas, and other subterranean resources from the earth. Particularly, once a desired resource is discovered below the surface of the earth, drilling and production systems are employed to access and extract the resource. These systems can be located onshore or offshore depending on the location of a desired resource. Further, such systems generally include a wellhead assembly through which

the resource is extracted. These wellhead assemblies generally include a wide variety of components and/or conduits, such as a christmas tree (tree), various control lines, casings, valves, and the like, that control drilling and/or extraction operations.

[0005] Subsea manifolds such as trees (sometimes called christmas trees) are well known in the art of oil and gas wells, and generally comprise an assembly of pipes, valves and fittings installed in a wellhead after completion of drilling and installation of the production tubing to control the flow of oil and gas from the well. Subsea trees typically have at least two bores one of which communicates with the production tubing (the production bore), and the other of which communicates with the annulus (the annulus bore).

[0006] Typical designs of conventional trees may have a side outlet (a production wing branch) to the production bore closed by a production wing valve for removal of production fluids from the production bore. The annulus bore also typically has an annulus wing branch with a respective annulus wing valve. The top of the production bore and the top of the annulus bore are usually capped by a tree cap which typically seals off the various bores in the tree, and provides hydraulic channels for operation of the various valves in the tree by means of intervention equipment, or remotely from an offshore installation.

[0007] Wells and trees are often active for a long time, and wells from a decade ago may still be in use today. However, technology has progressed a great deal during this time, for example, subsea processing of fluids is now desirable. Such processing can involve adding chemicals, separating water and sand from the hydrocarbons, etc.

[0008] Conventional treatment methods involve conveying the fluids over long distances for remote treatment, and some methods and apparatus include localized treatment of well fluids, by using pumps to boost the flow rates of the well fluids, chemical dosing apparatus, flow meters and other types of treatment apparatus.

[0009] One problem with locating the treatment apparatus locally on the tree is that the treatment apparatus can be bulky and can obstruct the bore of

the well. Therefore, intervention operations requiring access to the wellbore can require removal of the treatment apparatus before access to the well can be gained.

SUMMARY OF THE INVENTION

[0010] According to a first aspect of the present invention there is provided an apparatus for the processing of fluids from an oil or gas well, the apparatus comprising a processing device, and a wellbore extension conduit.

[0011] Typically the apparatus is modular and the wellbore extension conduit extends through the module. The wellbore extension conduit typically comprises sealed tubing that optionally extends at least partially through a central axis of the apparatus, and the processing device is arranged around the central axis, spaced from the wellbore extension conduit.

[0012] The apparatus can be built in modules, with a first part of the module, for example, a lower surface, being adapted to attach to an interface of a manifold such as a tree, and a second part, for example an upper surface, being adapted to attach to a further module. The second part (e.g. the upper surface) can typically be arranged in the same manner as the manifold interface, so that further modules can be attached to the first module, which typically has the same connections and footprint of the manifold interface. Thus, modules adapted to connect to the manifold interface in the same manner as the first module can connect instead to the first or to subsequent modules in the same manner, allowing stacking of separate modules on the manifold, each one connecting to the module below as if it were connecting to the manifold interface.

[0013] The wellbore extension conduit is typically straight and is aligned with the wellbore, although some embodiments of the invention incorporate versions in which the wellbore extension conduit is deviated from the axis of the wellbore itself. Embodiments with straight extension conduits in axial alignment with the wellbore have the advantage that the wellbore can be accessed in a straight line, and plugs or other items in the wellbore, perhaps below the tree, can be pulled through the modules via the extension conduits

without removing or adjusting the modules. Embodiments in which the wellbore extension conduit is deviated from the axis of the wellbore tend to be more compact and adaptable to large pieces of processing equipment. The wellbore can be the production bore, or a production flowline.

[0014] The upper surface of the module will typically have fluid and/or power conduit connectors in the same locations as the respective connectors are disposed in the lower surface, but typically, the upper surface connectors will be adapted to mate with the lower surface connectors, so that the upper surface connectors can mate with the lower surface connectors on the lower surface of the module above. Therefore, where the upper surface has a male connector, the lower surface can typically have a female connector, or vice versa.

[0015] Typically the module can have support structures such as posts that are adapted to transfer loads across the module to the hard points on the manifold. In certain embodiments, the weight of the processing modules can be borne by the wellbore mandrel.

[0016] In some embodiments, the processing device can connect directly into the wellbore mandrel. For example, conduits connecting directly to the mandrel can route fluids to be processed to the processing device. The processing device can optionally connect to a branch of the manifold, typically to a wing branch on a tree. The processing device can typically have an inlet that draws production fluids from a diverter insert located in a choke conduit of the branch of the manifold, and can return the fluids to the diverter insert via an outlet, after processing.

[0017] The diverter insert can have a flow diverter to divide the choke conduit into two separate fluid flowpaths within the choke conduit, for example the choke body, and the flow diverter can be arranged to control the flow of fluids through the choke body so that the fluids from the well to be processed are diverted through one flowpath and are recovered through another, for transfer to a flowline, or optionally back into the well. Optionally the flow diverter has a separator to divide the branch bore into two separate regions.

[0018] The oil or gas well is typically a subsea well but the invention is equally applicable to topside wells. The manifold may be a gathering manifold at the junction of several flow lines carrying production fluids from, or conveying injection fluids to, a number of different wells. Alternatively, the manifold may be dedicated to a single well; for example, the manifold may comprise a christmas tree.

[0019] By “branch” we mean any branch of the manifold, other than a production bore of a tree. The wing branch is typically a lateral branch of the tree, and can be a production or an annulus wing branch connected to a production bore or an annulus bore respectively.

[0020] Optionally, the flow diverter is attached to a choke body. “Choke body” can mean the housing which remains after the manifold’s standard choke has been removed. The choke may be a choke of a tree, or a choke of any other kind of manifold.

[0021] The flow diverter could be located in a branch of the manifold (or a branch extension) in series with a choke. For example, in an embodiment where the manifold comprises a tree, the flow diverter could be located between the choke and the production wing valve or between the choke and the branch outlet. Further alternative embodiments could have the flow diverter located in pipework coupled to the manifold, instead of within the manifold itself. Such embodiments allow the flow diverter to be used in addition to a choke, instead of replacing the choke.

[0022] Embodiments where the flow diverter is adapted to connect to a branch of a tree means that the tree cap does not have to be removed to fit the flow diverter. Embodiments of the invention can be easily retro-fitted to existing trees. Preferably, the flow diverter is locatable within a bore in the branch of the manifold. Optionally, an internal passage of the flow diverter is in communication with the interior of the choke body, or other part of the manifold branch.

[0023] The invention provides the advantage that fluids can be diverted from their usual path between the well bore and the outlet of the wing branch. The fluids may be produced fluids being recovered and traveling from the well

bore to the outlet of a tree. Alternatively, the fluids may be injection fluids traveling in the reverse direction into the well bore. As the choke is standard equipment, there are well-known and safe techniques of removing and replacing the choke as it wears out. The same tried and tested techniques can be used to remove the choke from the choke body and to clamp the flow diverter onto the choke body, without the risk of leaking well fluids into the ocean. This enables new pipework to be connected to the choke body and hence enables safe re-routing of the produced fluids, without having to undertake the considerable risk of disconnecting and reconnecting any of the existing pipes (e.g. the outlet header).

[0024] Some embodiments allow fluid communication between the well bore and the flow diverter. Other embodiments allow the wellbore to be separated from a region of the flow diverter. The choke body may be a production choke body or an annulus choke body. Preferably, a first end of the flow diverter is provided with a clamp for attachment to a choke body or other part of the manifold branch. Optionally, the flow diverter has a housing that is cylindrical and typically the internal passage extends axially through the housing between opposite ends of the housing. Alternatively, one end of the internal passage is in a side of the housing.

[0025] Typically, the flow diverter includes separation means to provide two separate regions within the flow diverter. Typically, each of these regions has a respective inlet and outlet so that fluid can flow through both of these regions independently. Optionally, the housing includes an axial insert portion.

[0026] Typically, the axial insert portion is in the form of a conduit. Typically, the end of the conduit extends beyond the end of the housing. Preferably, the conduit divides the internal passage into a first region comprising the bore of the conduit and a second region comprising the annulus between the housing and the conduit. Optionally, the conduit is adapted to seal within the inside of the branch (e.g. inside the choke body) to prevent fluid communication between the annulus and the bore of the conduit.

[0027] Alternatively, the axial insert portion is in the form of a stem. Optionally, the axial insert portion is provided with a plug adapted to block an

outlet of the christmas tree, or other kind of manifold. Preferably, the plug is adapted to fit within and seal inside a passage leading to an outlet of a branch of the manifold. Optionally, the diverter assembly provides means for diverting fluids from a first portion of a first flowpath to a second flowpath, and means for diverting the fluids from a second flowpath to a second portion of a first flowpath. Preferably, at least a part of the first flowpath comprises a branch of the manifold. The first and second portions of the first flowpath could comprise the bore and the annulus of a conduit.

[0028] The diverter insert is optional and in certain embodiments the processing device can take fluids from a bore of the well and return them to the same or a different bore, or to a branch, without involving a flow diverter having more than one flowpath. For example, the fluids could be taken through a plain single bore conduit from one hub on a tree into the processing apparatus, and back into a second hub on the same or a different tree, through a plain single bore conduit.

[0029] According to a second aspect of the present invention there is provided a manifold having apparatus according to the first aspect of the invention. Typically, the processing device is chosen from at least one of: a pump; a process fluid turbine; injection apparatus for injecting gas or steam; chemical injection apparatus; a chemical reaction vessel; pressure regulation apparatus; a fluid riser; measurement apparatus; temperature measurement apparatus; flow rate measurement apparatus; constitution measurement apparatus; consistency measurement apparatus; gas separation apparatus; water separation apparatus; solids separation apparatus; and hydrocarbon separation apparatus.

[0030] Optionally, the flow diverter provides a barrier to separate a branch outlet from a branch inlet. The barrier may separate a branch outlet from a production bore of a tree. Optionally, the barrier comprises a plug, which is typically located inside the choke body (or other part of the manifold branch) to block the branch outlet. Optionally, the plug is attached to the housing by a stem which extends axially through the internal passage of the housing.

[0031] Alternatively, the barrier comprises a conduit of the diverter assembly which is engaged within the choke body or other part of the branch. Optionally, the manifold is provided with a conduit connecting the first and second regions. Optionally, a first set of fluids are recovered from a first well via a first diverter assembly and combined with other fluids in a communal conduit, and the combined fluids are then diverted into an export line via a second diverter assembly connected to a second well.

[0032] According to a fourth aspect of the present invention, there is provided a method of processing wellbore fluids, the method comprising the steps of: connecting a processing apparatus to a manifold, wherein the processing apparatus has a processing device and a wellbore extension conduit, and wherein the wellbore extension conduit is connected to the wellbore of the manifold; diverting the fluids from a first part of the wellbore of the manifold to the processing device; processing the fluids in the processing device; and returning the processed fluids to a second part of the wellbore of the manifold.

[0033] Typically, the method is for recovering fluids from a well, and includes the final step of diverting fluids to an outlet of the first flowpath for recovery therefrom. Alternatively or additionally, the method is for injecting fluids into a well. The fluids may be passed in either direction through the diverter assembly.

BRIEF DESCRIPTION OF THE DRAWINGS

[0034] Various features, aspects, and advantages of the present invention will become better understood when the following detailed description is read with reference to the accompanying figures in which like characters represent like parts throughout the figures, wherein:

[0035] FIG. 1 is a plan view of a typical horizontal production tree;

[0036] FIG. 2 is a side view of the FIG. 1 tree;

[0037] FIG. 3 is a plan view of FIG. 1 tree with a first fluid processing module in place;

- [0038] FIG. 4 is a side view of the FIG. 3 arrangement;
- [0039] FIG. 5 is a side view of the FIG. 3 arrangement with a further fluid processing module in place;
- [0040] FIG. 6 is a plan view of a typical vertical production tree;
- [0041] FIG. 7 is a side view of the FIG. 6 tree;
- [0042] FIG. 8 is a side view of FIG. 6 tree with first and second fluid processing modules in place;
- [0043] FIG. 9 is a schematic diagram showing the flowpaths of the FIG. 5 arrangement;
- [0044] FIG. 10 is a schematic diagram showing the flowpaths of the FIG. 8 arrangement;
- [0045] FIG. 11 shows a plan view of a further design of wellhead;
- [0046] FIG. 12 shows a side view of the FIG. 11 wellhead, with a processing module; and
- [0047] FIG. 13 shows a front facing view of the FIG. 11 wellhead.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

[0048] One or more specific embodiments of the present invention will be described below. These described embodiments are only exemplary of the present invention. Additionally, in an effort to provide a concise description of these exemplary embodiments, all features of an actual implementation may not be described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

[0049] Referring now to the drawings, a typical production manifold on an offshore oil or gas wellhead comprises a christmas tree with a production bore 1 leading from production tubing (not shown) and carrying production fluids from a perforated region of the production casing in a reservoir (not shown). An annulus bore 2 (see FIG. 9) leads to the annulus between the casing and the production tubing. A tree cap typically seals off the production bore 1, and provides a number of hydraulic control channels by which a remote platform or intervention vessel can communicate with and operate valves in the christmas tree. The cap is removable from the christmas tree in order to expose the production bore in the event that intervention is required and tools need to be inserted into the wellbore. In the modern horizontal trees shown in FIGS.1-5, a large diameter production bore 1 is provided to feed production fluids directly to a production wing branch 10 from which they are recovered.

[0050] The flow of fluids through the production and annulus bores is governed by various valves shown in the schematic arrangements of FIG. 9 and 10. The production bore 1 has a branch 10 which is closed by a production wing valve PWV. A production swab valve PSV closes the production bore 1 above the branch 10, and a production master valve PMV closes the production bore 1 below the branch 10.

[0051] The annulus bore 2 is closed by an annulus master valve AMV below an annulus outlet controlled by an annulus wing valve AWV. An annulus swab valve ASV closes the upper end of the annulus bore 2.

[0052] All valves in the tree are typically hydraulically controlled by means of hydraulic control channels passing through the cap and the body of the apparatus or via hoses as required, in response to signals generated from the surface or from an intervention vessel.

[0053] When production fluids are to be recovered from the production bore 1, PMV is opened, PSV is closed, and PWV is opened to open the branch 10 which leads to a production flowline or pipeline 20. PSV and ASV are generally only opened if intervention is required.

[0054] The wing branch 10 has a choke body 15a in which a production choke 16 is disposed, to control the flow of fluids through the choke body and out through production flowline 20.

[0055] The manifold on the production bore 1 typically comprises a first plate 25a and a second plate 25b spaced apart in vertical relationship to one another by support posts 14a, so that the second plate 25b is supported by the posts 14a directly above the first plate 25a. The space between the first plate 25a and the second plate 25b is occupied by the fluid conduits of the wing branch 10, and by the choke body 15a. The choke body 15a is usually mounted on the first plate 25a, and above it, the second plate 25b will usually have a cut-out section to facilitate access to the choke 16 in use.

[0056] The first plate 25a and the second plate 25b each have central apertures that are axially aligned with one another and with the production bore 1 for allowing passage of the central mandrel 5 of the wellbore, which protrudes between the plates 25 and extends through the upper surface of the second plate to permit access to the wellbore from above the wellhead for intervention purposes. The upper end of the central mandrel is optionally capped with the tree cap or a debris cover (removed in drawings) to seal off the wellbore in normal operation.

[0057] Referring now to FIGS. 3 and 4, the conventional choke 16 has been removed from the choke body 15a, and has been replaced by a fluid diverter that takes fluids from the wing branch 10 and diverts them through an annulus of the choke body to a conduit 18a that feeds them to a first processing module 35b. The second plate 25b can optionally act as a platform for mounting the first processing module 35b. A second set of posts 14b are mounted on the second plate 25b directly above the first set of posts 14a, and the second posts 14b support a third plate 25c above the second plate 25b in the same manner as the first posts 14a support the second plate 25b above the first plate 25a. Optionally, the first processing module 35b disposed on the second plate 25b has a base that rests on feet set directly in line with the posts 14 in order to transfer loads efficiently to the hard points of the tree. Optionally, loads can be routed through the mandrel of the wellbore, and the posts and feet can be omitted.

[0058] The first processing module contains a processing device for processing the production fluids from the wing branch 10. Many different types of processing devices could be used here. For example, the processing device could comprise a pump or process fluid turbine, for boosting the pressure of the production fluids. Alternatively, or additionally, the processing apparatus could inject gas, steam, sea water, or other material into the fluids. The fluids pass from the conduit 18a into the first processing module 35b and after treatment or processing, they are passed through a second choke body 15b which is blanked off with a cap, and which returns the processed production fluids to the first choke body 15a via a return conduit 19a. The processed production fluids pass through the central axial conduit of the fluid diverter in the choke body 15a, and leave it via the production flowpath 20. After the processed fluids have left the choke body 15a, they can be recovered through a normal pipeline back to the surface, or re-injected into a well, or can be handled or further processed in any other way desirable.

[0059] The injection of gas could be advantageous, as it would give the fluids "lift". The addition of steam has the effect of adding energy to the fluids.

[0060] Injecting sea water into a well could be useful to boost the formation pressure for recovery of hydrocarbons from the well, and to maintain the pressure in the underground formation against collapse. Also, injecting waste gases or drill cuttings etc into a well obviates the need to dispose of these at the surface, which can prove expensive and environmentally damaging.

[0061] The processing device could also enable chemicals to be added to the fluids, e.g. viscosity moderators, which thin out the fluids, making them easier to pump, or pipe skin friction moderators, which minimize the friction between the fluids and the pipes. Further examples of chemicals which could be injected are surfactants, refrigerants, and well fracturing chemicals. Processing device could also comprise injection water electrolysis equipment. The chemicals/injected materials could be added via one or more additional input conduits.

[0062] The processing device could also comprise a fluid riser, which could provide an alternative route between the well bore and the surface. This could be very useful if, for example, the branch 10 becomes blocked.

[0063] Alternatively, processing device could comprise separation equipment e.g. for separating gas, water, sand/debris and/or hydrocarbons. The separated component(s) could be siphoned off via one or more additional processes.

[0064] The processing device could alternatively or additionally include measurement apparatus, e.g. for measuring the temperature/ flow rate/ constitution/ consistency, etc. The temperature could then be compared to temperature readings taken from the bottom of the well to calculate the temperature change in produced fluids. Furthermore, the processing device could include injection water electrolysis equipment.

[0065] Alternative embodiments of the invention can be used for both recovery of production fluids and injection of fluids, and the type of processing apparatus can be selected as appropriate.

[0066] A suitable fluid diverter for use in the choke body 15a in the FIG. 4 embodiment is described in application WO/2005/047646, the disclosure of which is incorporated herein by reference.

[0067] The processing device(s) is built into the shaded areas of the processing module 35b as shown in the plan view of FIG. 3, and a central axial area is clear from processing devices, and houses a first mandrel extension conduit 5b. At its lower end near to the second plate 25b, the first mandrel extension conduit 5b has a socket to receive the male end of the wellbore mandrel 5 that extends through the upper surface of the second plate 25b as shown in FIG. 2. The socket has connection devices to seal the extension conduit 5b to the mandrel 5, and the socket is stepped at the inner surface of the mandrel extension conduit 5b, so that the inner bore of the mandrel 5 is continuous with the inner bore of the mandrel extension conduit 5b and is sealed thereto. When the mandrel extension conduit 5b is connected to the mandrel 5, it effectively extends the bore of the mandrel 5

upwards through the upper surface of the third plate 25c to the same extent as the mandrel 5 extends through the second plate 25b as shown in FIG. 2.

[0068] The upper surface of the third plate 25c though which the first mandrel extension conduit 5b protrudes, as shown in FIG. 4, has, therefore, the same profile (as regards the wellbore mandrel) as the basic tree shown in FIG. 1. The mandrel extension conduit 5b can be plugged. The other features of the upper surface of the third plate 35c are also arranged as they are on the basic tree, for example, the hard points for weight bearing are provided by the posts 14, and other fluid connections that may be required (for example hydraulic signal conduits at the upper face of the second plate 25b that are needed to operate instruments on the tree) can have continuous conduits that provide an interface between the third plate 25c and the second 25b.

[0069] The third plate 25c has a cut out section to allow access to the second choke body 15b, but this can be spaced apart from the first choke body 15a, and does not need to be directly above. This illustrates that while it is advantageous in certain circumstances for the conduit adapting to the basic tree to be in the same place on the upper surface as its corresponding feature is located on the lower plate, it is not absolutely necessary, and linking conduits (such as conduits 18 and 19) can be routed around the processing devices as desired.

[0070] The guide posts 14 can optionally be arranged as stab posts 14' extending upward from the upper surface of the plates, and mating with downwardly-facing sockets 14'' on the base of the processing module above them, as shown in FIG. 4. In either event, it is advantageous (but not essential) that the support posts on a lower module are directly beneath those on an upper module, to enhance the weight bearing characteristics of the apparatus. A control panel 34b can be provided for the control of the processing module 35b. In the example shown in FIG. 4, the processing module comprises a pump.

[0071] Referring now to FIG. 5, a second processing module 35c has been installed on the upper surface of the third plate 25c. The blank cap in the

second choke body 15b has been replaced with a fluid diverter 17b similar to the diverter now occupying the first choke body 15a. The diverter 17b is provided with fluid conduits 18b and 19b to send fluids to the second processing module 35c and to return them therefrom, via a further blanked choke body 15c, for transfer back to the first choke body 15a, and further treatment, recovery or injection as previously described.

[0072] Above the second processing module 35c is a fourth plate 25d, which has the same footprint as the second and third plates, with guide posts 14" and fluid connectors etc in the same locations. The second processing module 35c, which may incorporate a different processing device from the first module 35b, for example a chemical dosing device, is also built around a second central mandrel extension conduit 5c, which is axially aligned with the mandrel bore 5 and the first extension 5b. It has sockets and seals in order to connect to the first mandrel extension conduit just as the first extension conduit 5b connects to the mandrel 5, so the mandrel effectively extends continuously through the two processing units 35b and 35c and has the same top profile as the basic wellhead, thereby facilitating intervention using conventional equipment without having to remove the processing units.

[0073] Processing units can be arranged in parallel or in series. FIGS. 6-8 show a further embodiment of a vertical tree. Like parts between the two embodiments have been allocated the same reference numbers, but the second embodiment's reference numbers have been increased by 100.

[0074] In the embodiment shown in FIGS. 6-8, the vertical tree has a central mandrel 100 with a production bore 101 and an annulus bore 102 (see FIG. 6). The production bore 101 feeds a production choke 116p in a production choke body 115p through a production wing branch 110, and the annulus bore 102 feeds an annulus choke 116a in an annulus choke body 115a through an annulus wing branch 111. The tree has a cap 106 to seal off the mandrel and the production and annulus bores, located on top of a second plate 125b disposed directly above a lower first plate 125a as previously described. The second plate 125b is supported by tubular posts 114a, and guide posts 114' extend from the upper surface of the second plate

125b. ROV controls are provided on a control panel 134 as with the first embodiment.

[0075] FIG. 8 shows a first processing module 135b disposed on the top of the second plate 125b as previously described. The first processing module 135b has a central axial space for the first mandrel extension conduit 105b, with the processing devices therein (e.g. a pump) displaced from the central axis as previously described. A second processing module 135c is located on top of the first, in the same manner as described with reference to the FIG. 5 embodiment. The second processing module 135c also has a central axial space for the second mandrel extension conduit 105c, with the processing devices packed into the second processing module 135c being displaced from the central axis as previously described. The second processing module 135c can comprise a chemical injection device. The second mandrel extension conduit 105c connects to the first 105b as previously described for the first embodiment.

[0076] The production fluids are routed from the production choke body 115p by a fluid diverter 117p as previously described through tubing 118p and 119p to the first processing module 135b, and back to the choke body 115p for onward transmission through the flowline 120. Optionally the treated fluids can be passed through other treatment modules arranged in series with the first module, and stacked on top of the second module, as previously described.

[0077] The fluids flowing up the annulus are routed from the annulus choke body 115a by a fluid diverter 117a as previously described through tubing 118a and 119a to the second processing module 135c, and back to the choke body 115a for onward transmission. Optionally the treated fluids can be passed through other treatment modules arranged in series with the second module, and stacked on top of the second or further modules, as previously described.

[0078] FIGS. 11-13 show an alternative embodiment, in which the wellhead has stacked processing modules as previously described, but in which the specialized dual bore diverter 17 insert in the choke body 15 has been

replaced by a single bore jumper system. In the modified embodiment shown in these figures, the same numbering has been used, but with 200 added to the reference numbers. The production fluids rise up through the production bore 201, and pass through the wing branch 211 but instead of passing from there to the choke body 215, they are diverted into a single bore jumper bypass 218 and pass from there to the process module 235. After being processed, the fluids flow from the process module through a single bore return line 219 to the choke body 215, where they pass through the conventional choke 216 and leave through the choke body outlet 220. This embodiment illustrates the application of the invention to manifolds without dual concentric bore flow diverters in the choke bodies.

[0079] Embodiments of the invention provide intervention access to trees or other manifolds with treatment modules in the same way as one would access trees or other manifolds that have no such treatment modules. The upper surfaces of the topmost module of embodiments of the invention are arranged to have the same footprint as the basic tree or manifold, so that intervention equipment can land on top of the modules, and connect directly to the bore of the manifold without spending any time removing or re-arranging the modules, thereby saving time and costs.

[0080] Modifications and improvements may be incorporated without departing from the scope of the invention. For example the assembly could be attached to an annulus bore, instead of to a production bore.

[0081] Any of the embodiments which are shown connected to a production wing branch could instead be connected to an annulus wing branch, or another branch of the tree, or to another manifold. Certain embodiments could be connected to other parts of the wing branch, and are not necessarily attached to a choke body. For example, these embodiments could be located in series with a choke, at a different point in the wing branch.

[0082] While the invention may be susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and have been described in detail herein. However, it should be understood that the invention is not intended to be limited to the particular

forms disclosed. Rather, the invention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the following appended claims.

CLAIMS

1. A system, comprising:
 - a first module configured to process fluid from a well, wherein the first module comprises:
 - an extension conduit having a connection that is coupleable to a central mandrel of a manifold;
 - a processing device arranged in a region surrounding the extension conduit;
 - a processing input; and
 - a processing output.
2. The system of claim 1, wherein the manifold comprises a christmas tree.
3. The system of claim 1, wherein the processing device comprises a pump, a process fluid turbine, an injection apparatus for injecting gas or steam, a chemical injection apparatus, a chemical reaction vessel, a pressure regulation apparatus, a fluid riser, a measurement apparatus, a temperature measurement apparatus, a flow rate measurement apparatus, a constitution measurement apparatus, a consistency measurement apparatus, a gas separation apparatus, a water separation apparatus, a solids separation apparatus, a hydrocarbon separation apparatus, or a combination thereof.
4. The system of claim 1, wherein the processing input comprises a first flowpath extending between a bore of the manifold and the processing device, and wherein the processing output comprises a second flowpath extending between an output of the processing device and a production output.
5. The system of claim 1, wherein the first module is configured to couple to a second module configured to process fluid from the well.

6. The system of claim 5, wherein the second module is connected in series with the first module.
7. The system of claim 6, wherein the first module comprises a second processing input and a second processing output, each comprising a flowpath configured to couple to the second module.
8. The system of claim 1, comprising:
 - a lower interface, comprising the extension conduit; and
 - a rigid structure, comprising:
 - an upper surface; and
 - a lower surface;wherein the processing device is contained between the upper surface and the lower surface.
9. The system of claim 8, wherein the first module is stackable with a second module.
10. The system of claim 9, wherein the first module comprises an upper interface that is coupleable to a lower interface of the second module.
11. The system of claim 9, wherein the first module comprises a first diverter configured to mate with a second diverter of the second module.
12. A diverter, comprising:
 - a first flow path, comprising:
 - a first input coupleable to a bore of a manifold; and
 - a first output coupleable to a processing input of a processing module, wherein the processing module is configured to process fluids from a well and is coupleable to a central mandrel of the manifold; and
 - a second flowpath, comprising:
 - a second input coupleable to a production output of the processing module;
 - a second output coupleable to a production output.

13. The diverter of claim 12, wherein the diverter is configured to mount in a branch of the manifold.
14. The diverter of claim 12, wherein the manifold comprises a tree.
15. The diverter of claim 14, wherein the diverter is configured to be disposed in a choke body of the tree.
16. The diverter of claim 15, wherein the second output is in communication with a production output of the choke body.
17. The diverter of claim 12, wherein the diverter comprises a first flow path in communication with the first output, and a second flowpath between the second input and the second output.
18. A modular well system, comprising:
 - a diverter comprising a first flow path and a second flowpath; and
 - a processing module configured to be coupled to a central mandrel of a manifold, wherein the processing module is in fluid communication with the first flow path and the second flowpath.
19. The modular well system of claim 18, comprising the manifold comprising the central mandrel having a bore in fluid communication with the first flowpath.
20. The modular well system of claim 19, wherein fluid is configured to flow from the bore to the processing module via the first flow path and the fluid is configured to be directed to an output via the second flow path.
21. The modular well system of claim 19, wherein fluid is configured to flow into the processing module via the second flow path and is directed into the bore via the first flow path.

22. A method of processing well fluids, comprising:
diverting fluids from a bore of a manifold to a processing module,
wherein the processing module is coupled to a mandrel of the manifold;
processing the fluids in the processing module; and
returning the fluids to a flowpath for recovery.
23. The method of claim 22, wherein processing comprises passing the fluids into a pump, a process fluid turbine, an injection apparatus for injecting gas or steam, a chemical injection apparatus, a chemical reaction vessel, a pressure regulation apparatus, a fluid riser, a measurement apparatus, a temperature measurement apparatus, a flow rate measurement apparatus, a constitution measurement apparatus, a consistency measurement apparatus, a gas separation apparatus, a water separation apparatus, a solids separation apparatus, a hydrocarbon separation apparatus, or a combination thereof.
24. A well system, comprising:
a processing module configured to couple directly to a top of a manifold of a well, the processing module comprising an input configured to be in fluid communication with a bore of the manifold and an output configured to be in fluid communication with a fluid output of the manifold.
25. The well system of claim 24, wherein the processing module comprises a conduit extension, wherein the processing module is configured to couple to the top of the manifold via the conduit extension, and wherein the conduit extension comprises a bore that is configured to align with a bore of the manifold.