

SEMICONDUCTOR STRUCTURE AND METHOD FOR MANUFACTURING SEMICONDUCTOR STRUCTURE, MEMORY CHIP AND ELECTRONIC DEVICE

CROSS-REFERENCE TO RELATED APPLICATION

[0001] The present application claims priority to Chinese Patent Application No. 202210723121.3, filed on June 21, 2022 and entitled "SEMICONDUCTOR STRUCTURE AND METHOD FOR MANUFACTURING SAME, MEMORY CHIP AND ELECTRONIC DEVICE", the disclosure of which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] The embodiments of the disclosure belong to the field of semiconductors and particularly relate to a semiconductor structure and a method for manufacturing the semiconductor structure, a memory chip and an electronic device.

BACKGROUND

[0003] A semiconductor structure includes a plurality of memory cells, and the memory cells are connected to a peripheral circuit to execute a storage function. With an improvement of an integration level of the semiconductor structure, the number of the memory cells capable of being accommodated in the semiconductor structure increases and the performance of the semiconductor structure gets better. However, many spaces in the current semiconductor structure are wasted. Besides, under the limit of factors of physical properties, the volume of the memory cell has reached a scaling limit. Under the limit of process factors, it is also difficult to increase the number of stacked layers of the memory cell.

[0004] Therefore, it is urgent to provide a semiconductor structure in a new architecture, so as to improve the integration level of the semiconductor structure.

SUMMARY

[0005] The embodiments of the disclosure provide a semiconductor structure and a method for manufacturing a semiconductor structure, a memory chip and an electronic device, to improve an integration level of the semiconductor structure.

[0006] An aspect of the embodiments of the disclosure provides a semiconductor structure. The semiconductor structure includes a substrate on which a stacked structure is provided. The stacked structure includes a plurality of memory cell groups arranged in a first direction, and each of the memory cell groups includes multiple layers of memory cells arranged in a second direction. The semiconductor structure includes a plurality of leading wire posts. At least two leading wire posts are respectively in contact with different layers of memory cells of in different memory cell groups.

[0007] Another aspect of the embodiments of the disclosure provides a method for manufacturing a semiconductor structure. The method includes: providing a substrate on which a stacked structure is provided. The stacked structure includes a plurality of memory cell groups arranged in a first direction, and each of the memory cell groups includes multiple layers of memory cells arranged in a second direction. The method further includes forming a plurality of leading wire posts. At least two leading wire posts are respectively in contact with different layers of memory cells in different memory cell groups.

[0008] Another aspect of the embodiments of the disclosure provides a semiconductor structure. The semiconductor structure includes a substrate on which a stacked structure is provided. The stacked structure includes a plurality of memory cell groups arranged in a first direction, and each of the memory cell groups includes multiple layers of memory cells arranged in a second direction. The semiconductor structure includes a plurality of leading wire posts. At least two leading wire posts are in contact with different memory cells in same memory cell group.

[0009] Another aspect of the embodiments of the disclosure further provides a memory chip including the aforementioned semiconductor structure.

[0010] Another aspect of the embodiments of the disclosure further provides an electronic device including the aforementioned memory chip.

[0011] Technical solutions provided by the embodiments of the disclosure at least have the following advantages.

[0012] In the semiconductor structure provided by the embodiments of the disclosure, at least two leading wire posts are in contact with different layers of memory cells in the memory cell group. That is, at least two leading wire posts are directly in contact with the memory cells. Therefore, the number of stairs is reduced or it is no longer to arrange a separate staircase, thereby improving an integration level of the semiconductor structure.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments conforming to the disclosure and, together with the description, serve to explain the principles of the disclosure. It is apparent that the accompanying drawings described below merely show some embodiments of the disclosure, and those of ordinary skill in the art can further obtain other drawings according to those accompanying drawings without making creative efforts.

[0014] FIG. 1 illustrates a top view of a semiconductor structure.

[0015] FIG. 2 illustrates an enlarged partial view of FIG. 1.

[0016] FIG. 3 illustrates a sectional view along a direction A-A1 of FIG. 2.

[0017] FIG. 4 illustrates a schematic diagram of a stacked structure provided by an embodiment of the disclosure.

[0018] FIG. 5 to FIG. 11 respectively illustrate partial plan views of seven different semiconductor structures provided by the embodiments of the disclosure.

- [0019] FIG. 12 illustrates a schematic diagram of a memory cell group provided by an embodiment of the disclosure.
- [0020] FIG. 13 illustrates a schematic partial side view of a semiconductor structure provided by an embodiment of the disclosure.
- [0021] FIG. 14 illustrates a schematic diagram of another memory cell group provided by an embodiment of the disclosure.
- [0022] FIG. 15 illustrates a schematic partial side view of another memory cell group provided by the embodiment of the disclosure.
- [0023] FIG. 16 illustrates a schematic diagram of another memory cell group provided by an embodiment of the disclosure.
- [0024] FIG. 17 illustrates a schematic partial side view of another semiconductor structure provided by an embodiment of the disclosure.
- [0025] FIG. 18 to FIG. 21 respectively illustrate schematic diagrams of four memory cell groups provided by the embodiments of the disclosure.
- [0026] FIG. 22 shows a schematic diagram of a structure module provided by an embodiment of the disclosure.
- [0027] FIG. 23 to FIG. 31 illustrate schematic structural diagrams corresponding to stairs in a method for manufacturing a semiconductor structure provided by the embodiments of the disclosure.
- [0028] FIG. 32 to FIG. 35 illustrate schematic structural diagrams corresponding to stairs in another method for manufacturing a semiconductor structure provided by the embodiments of the disclosure.
- [0029] FIG. 36 illustrates a schematic diagram of another memory cell group provided by an embodiment of the disclosure.
- [0030] FIG. 37 to FIG. 38 respectively illustrate partial top views of two different semiconductor structures provided by the embodiments of the disclosure.

DETAILED DESCRIPTION

[0031] FIG. 1 is a top view of a semiconductor structure. FIG. 2 is an enlarged view of a stair in a dotted line circle in FIG. 1. FIG. 3 is a sectional view along a direction A-A1 in FIG. 2. Referring to FIG. 1 to FIG. 3, the semiconductor structure includes a memory cell area 100 and a staircase 200. Multiple layers of memory cells are provided in the memory cell area 100. Multiple stairs are arranged in the staircase 200, and the stairs and the multiple layers of memory cells are arranged in one-to-one correspondences. A connecting layer (not shown FIG. 1 to FIG. 3) can be arranged in the stair, a leading wire post 300 can be arranged on the stair, and the leading wire post 300 is electrically connected to the memory cell through the connecting layer in the stair to lead out the memory cell, to connect the memory cell to a peripheral circuit. However, with an increase of the number of stacked layers of the memory cells, the area occupied by the staircase 200 is getting large. For example, if there are totally 64 layers of memory cells, 64 stairs are needed correspondingly, and the lower the stair is, the larger the area of the stair is. If the area of the topmost stair is $0.25\mu\text{m}^2$, the stair of the bottommost stair is $64*0.25=16\mu\text{m}^2$. Referring to FIG. 3, the connecting layer below each stair is only used for support and electric connection, so that the bottom space is wasted. Therefore, the integration level of the semiconductor structure is to be further improved.

[0032] An embodiment of the disclosure provides a semiconductor structure. In the semiconductor structure, at least two leading wire posts of the plurality of leading wire posts are in contact with the different layers of memory cells in different memory cell groups. That is, at least two leading wire posts directly contact with to the memory cells, to reduce the number of stairs or it is no longer to arrange a separate staircase, thereby improving a spatial utilization ratio, and improving an integration level of the semiconductor structure.

[0033] The embodiments of the disclosure are described below in detail in combination with the drawings. However, those of ordinary skill in the art may understand that many technical details are provided to better understand the embodiments of the disclosure. However, the technical solutions claimed by the disclosure may also be

implemented based on various changes and modifications of the following embodiments without these technical details.

[0034] As shown in FIG. 4 to FIG. 22, an embodiment of the disclosure provides a semiconductor structure. The semiconductor structure includes: a substrate 11 (referring to FIG. 23) on which a stacked structure is provided. The stacked structure includes multiple memory cell groups TC0 arranged in a first direction X, and the memory cell group TC0 includes multiple layers of memory cells TC arranged in a second direction Z. The semiconductor structure further includes multiple leading wire posts 5. At least two leading wire posts 5 are respectively in contact with different layers of memory cells TC in different memory cell groups TC0.

[0035] That is, the memory cells TC are stacked in multiple layers, and at least two leading wire posts 5 are directly in contact with the memory cells TC, to reduce the number of stairs. In a case that all the leading wire posts 5 are directly in contact with the memory cells TC, it is not required to arrange the separate staircase. That is, orthographic projections of the leading wire post 5 in contact with the memory cell TC on a surface of the substrate 11 are within orthographic projection of the stacked structure on the surface of the substrate 11, which can improve a utilization degree of the surface of the substrate 11, and further improve an integration level of the semiconductor structure. In addition, at least two leading wire posts 5 are in contact with different layers of memory cells TC in different memory cell groups TC0. This indicates that at least two leading wire posts 5 may utilize the space of different memory cell groups TC0.

[0036] The semiconductor structure is described below in detail in combination with the drawings.

[0037] In some embodiments, referring to FIG.4 to FIG.5 and FIG. 8 to FIG. 22, all the memory cells TC in the same memory cell group TC0 are in contact with no more than one leading wire post 5. That is, only one contact position of the leading wire post 5 to the memory cell TC is arranged in each memory cell group TC0. Since the contact position in the same memory cell group TC0 is few, connection modes in different memory cell groups TC0 are relatively unified. Therefore, the connection process between different leading wire posts 5 and memory cells TC can be unified, thereby

lowering the production cost. It is to be noted that in order to make the leading wire post 5 contact with different layers of memory cells TC, a part of structure in the memory cell TC can be removed, so that at least a part of leading wire post 5 penetrate through at least one memory cell TC, and the leading wire post 5 may be arranged on a side wall of the memory cell TC and do not penetrate through the memory cell TC.

[0038] In some other embodiments, referring to FIG.6 to FIG. 7, the memory cells TC in contact with at least two leading wire posts 5 are located in the same memory cell group TC0. That is, multiple contact positions of the leading wire post 5 to the memory cell TC can be arranged in each memory cell group TC0. It is to be noted that in order to make the leading wire post 5 be in contact with the memory cell TC, a part of structure in the memory cell TC is removed, so as to provide space needed by the leading wire post 5. After the part of structure in the memory cell TC is removed, the memory cell TC may no longer execute the storage function. In a case that the multiple leading wire posts 5 are arranged in the same memory cell group TC0, the number of the invalid memory cells TC can be reduced, to improve a spatial utilization ratio in the semiconductor structure, thereby improving the integration level.

[0039] Specifically, the memory cells TC in the same memory cell group TC0 in contact with at least two leading wire posts 5 includes the following two conditions. At least two leading wire posts 5 in the same memory cell group TC0 are in contact with the same layer of memory cells TC, and at least two leading wire posts 5 in the same memory cell group TC0 are in contact with the different layers of memory cells TC.

[0040] Referring to FIG. 6, at least two leading wire posts 5 in the same memory cell group TC0 may be arranged along the first direction X. Referring to FIG. 7, at least two leading wire posts 5 in the same memory cell group TC0 may be arranged along the third direction Y.

[0041] In some embodiments, referring to FIG. 4, the number of the leading wire posts 5 is equal to or greater than the number of layers of the memory cells TC, and each of the layers at least includes one memory cell TC in contact with the leading wire post 5. That is, the memory cell TC in each layer may be directly in contact with the leading wire post 5, and the separate staircase is not required. In addition, the memory cell TC in

each layer may be led out through one or more leading wire posts 5. In a case that the memory cell TC in each layer is led out through one leading wire post 5, process manufacturing is simplified. In a case that the memory cell TC in each layer is led out through the plurality of leading wire posts 5, the contact area is increased, thereby reducing the contact resistance.

[0042] It is to be noted that the memory cell group TC0 includes various different structures inside. Therefore, in a case that there are too many leading wire posts 5 connected to the same memory cell group TC0, the space needed by the leading wire posts 5 is large. Different leading wire posts 5 may be connected to different structures in the memory cell group TC0. Different connection processes are adopted for different structures. In some embodiments, the number of the leading wire posts 5 connected to the same memory cell group TC0 is smaller than the number of layers of the memory cells TC in the memory cell group TC0. By controlling the number of the leading wire posts 5 connected to the same memory cell group TC0 to be kept in a reasonable range, the connection processes between the leading wire posts 5 and the memory cells TC is simplified.

[0043] In some embodiments, referring to FIG. 6 and FIG.8 to FIG.9, the leading wire posts 5 are arranged along the first direction X. That is, the plurality of leading wire posts 5 are substantially aligned in the first direction X, so that the plurality of leading wire posts 5 can be connected to the same structure in the memory cell TC, which unifies processes of connecting the leading wire posts 5 to the memory cells TC, and thus lowers the production cost.

[0044] For example, referring to FIG. 8, the leading wire posts 5 are lined up along the first direction X. In other words, the leading wire posts 5 are arranged in a straight line, and two ends of the plurality of leading wire posts 5 are aligned in the first direction X, which simplifies the process and improves the uniformity of the semiconductor structure. In addition, referring to FIG. 9, the leading wire posts 5 may further be slightly staggered, that is, two ends of the plurality of leading wire posts 5 are not aligned in the first direction X, to reduce the area of a directly facing region between the leading wire posts 5, thereby reducing parasitic capacitance between adjacent leading wire posts 5.

[0045] Referring to FIG. 4 and FIG.12 to FIG. 22, the at least one leading wire post 5 extends in the second direction Z and penetrates through at least one memory cell TC in the memory cell group TC0. In this case, the orthographic projection of the at least one leading wire post 5 on the surface of the substrate 11 is within the orthographic projection of the memory cell TC on the surface of the substrate 11. It will be described below in detail. In order to facilitate understanding, the leading wire post 5 is divided into a contact portion 51 and an extension portion 52 arranged in a stacked manner. The contact portion 51 is in contact with the memory cell TC, and the memory cell TC in contact with the contact portion 51 is called as the memory cell TC of a corresponding layer.

[0046] Specifically, at least two leading wire posts 5 are respectively in contact with different layers of memory cells TC in different memory cell groups TC0, which indicates that at least one leading wire post 5 is in contact with the memory cell TC of the non-top layer. The leading wire post 5 in contact with the memory cell TC of a non-top layer occupies a spatial position of the memory cell TC above the corresponding layer, in addition to spatial position of the memory cell TC of the corresponding layer. For example, referring to FIG. 12, FIG. 14 and FIG. 16, in a case that a secondary top layer is taken as the corresponding layer, the contact portion 51 of the leading wire post 5 is in contact with the memory cell TC of the secondary top layer, and the extension portion 52 of the leading wire post 5 penetrates through the memory cell TC of the top layer. The memory cell TC which is penetrated and the memory cell TC which is in contact with the leading wire post no longer have the storage function. In other words, a part of structure of the memory cell TC above the corresponding layer may be directly removed, to provide a spatial position to the extension portion 52 of the leading wire post 5, thereby simplifying the production process.

[0047] It is to be noted that in some other embodiments, the extension portion 52 of the leading wire post 5 may not occupy the spatial position of the memory cell TC above the corresponding layer but occupies a spatial position between the adjacent memory cells TC. Specifically, referring to FIG. 10, a part of contact portion 51 of the leading wire post 5 protrudes from the memory cell TC of the corresponding layer and is arranged in a space between the adjacent memory cells TC, so that the extension portion

52 of the leading wire post 5 may be led out upwards from a gap between the adjacent memory cells TC without penetrating through the memory cell TC above the corresponding layer, thereby decreasing the number of the invalid memory cells TC. Alternately, referring to FIG. 11, the contact portion 51 and the extension portion 52 of the leading wire post 5 are arranged in the space between the adjacent memory cells TC, and the contact portion 51 is in contact with the side wall of the memory cell TC of the corresponding layer, so that the extension portion 52 of the leading wire post 5 may be led out upwards from the gap between the adjacent memory cells TC without penetrating through the memory cell TC above the corresponding layer, thereby decreasing the number of the invalid memory cells TC.

[0048] Referring to FIG. 4, the leading wire post 5 in contact with the memory cell TC of the top layer only utilizes a spatial position of the memory cell TC of the corresponding layer rather than spatial positions of the other memory cells TC. Therefore, the leading wire post does not need penetrating through the memory cells TC of a layer rather than the corresponding layer.

[0049] It is to be noted that in some embodiments, referring to FIG. 4 and FIG. 12 to FIG. 13, the leading wire post 5 may further penetrate through the memory cell TC of the corresponding layer, that is, a part of structure of the memory cell TC of the corresponding layer is removed to provide a spatial position to the contact portion 51 of the leading wire post 5. At the time, at least a part of side surface of the leading wire post 5 is in contact with the memory cell TC.

[0050] In some other embodiments, the leading wire post 5 may not penetrate through the memory cell TC of the corresponding layer. For example, referring to FIG. 14 to FIG. 15, the leading wire post 5 is embedded into the memory cell TC of the corresponding layer. In this case, a bottom surface and a part of a side surface of the leading wire post 5 are in contact with the memory cell TC. In addition, referring to FIG. 16 to FIG. 17, the bottom surface of the leading wire post 5 is in contact with a top surface of the memory cell TC of the corresponding layer.

[0051] Referring to FIG. 4, FIG. 13, FIG. 15 and FIG. 17, the numbers of the memory cells which at least two leading wire posts 5 penetrate through are different. That is, at

least two leading wire posts 5 are in contact with different layers of memory cells TC, so as to lead out different layers of memory cells TC. In this way, at least two stairs may be decreased, so as to reduce the volume of the semiconductor structure.

[0052] Referring to FIG. 12, FIG. 14, FIG. 16 and FIG. 18 to FIG. 21, the semiconductor structure further includes a dielectric layer 6 arranged between the leading wire post 5 and the penetrated memory cell TC. The dielectric layer 6 may isolate the leading wire post 5 from the memory cell TC above the corresponding layer. It is to be noted that in a case that the leading wire post 5 further penetrates through the memory cell TC of the corresponding layer, the dielectric layer 6 is arranged between the leading wire post 5 and the memory cell TC above the corresponding layer, and a side of the leading wire post 5 located in the memory cell TC of the corresponding layer is exposed, so that the leading wire post 5 is in contact with the memory cell TC of the corresponding layer through the side wall.

[0053] Referring to FIG. 4, the two adjacent leading wire posts 5 are at least spaced by one memory cell group TC0. That is, the adjacent two leading wire posts 5 are not in contact with the adjacent memory cell groups TC0, to increase a distance between the adjacent leading wire posts 5, thereby reducing the parasitic capacitance.

[0054] Specifically, in some examples, the number of the memory cell groups TC0 between adjacent two leading wire posts 5 is fixed, that is, a distance between the adjacent leading wire posts 5 is fixed, thereby improving the uniformity of the semiconductor structure. In some other examples, the area of a directly facing region between the two adjacent leading wire posts 5 are directly proportional to the number of the memory cell groups TC0 between the two adjacent leading wire posts 5. It may be understood that the parasitic capacitance between the adjacent leading wire posts 5 is related to the area of a directly facing region between the two adjacent leading wire posts 5. With an increase of the area of a directly facing region between the two adjacent leading wire posts 5, the number of the memory cell groups TC0 between the two adjacent leading wire posts 5 may be correspondingly increased to increase the distance between the two adjacent leading wire posts 5, so as to reduce the parasitic capacitance. Exemplarily, two leading wire posts 5 in contact with the memory cells TC of the bottom

layer and the secondary bottom layer are adjacently arranged, and five memory cell groups TC0 are arranged between the two leading wire posts 5. Two leading wire posts 5 in contact with the memory cells TC of the top layer and the secondary top layer are adjacently arranged, and one memory cell group TC0 is arranged between the two leading wire posts 5.

[0055] In some other embodiments, referring to FIG.8 to FIG. 9, the adjacent two leading wire posts 5 may further be arranged on the adjacent memory cell groups TC0, and there is no memory cell group TC0 between the adjacent two leading wire posts 5.

[0056] The stacked structure is specifically described below.

[0057] Referring to FIG. 4, the semiconductor structure has the first direction X, the second direction Z and the third direction Y inside. The first direction X is parallel to the surface of the substrate 11, the second direction Z is perpendicular to the surface of the substrate 11, and the third direction Y is parallel to the surface of the substrate 11. The third direction Y is different from the first direction X. Exemplarily, the third direction Y is perpendicular to the first direction X.

[0058] Continuously referring to FIG. 4, the stacked structure further includes a plurality of horizontal signal lines 3 and a plurality of vertical signal lines 4. The plurality of horizontal signal lines 3 are arranged in the second direction Z and extend along the first direction X, and are in contact with one layer of the memory cells TC. The vertical signal lines 4 extend along the second direction Z and are in contact with the multiple layers of memory cells TC of the same memory cell group TC0. The leading wire posts 5 are electrically in contact with the horizontal signal lines 3.

[0059] That is, the horizontal signal lines 3 are arranged in a stacked manner on the substrate 11 and are led out through the leading wire posts 5, so as to facilitate subsequent electric connection between the horizontal signal lines 3 and the peripheral circuit. The vertical signal lines 4 are arranged perpendicular to the substrate 11, and thus are not required to be lead out through the leading wire posts 5. In some embodiments, the leading wire posts 5 may be directly in contact with the horizontal signal lines 3, so as to realize electric connection of the leading wire posts 5 and the horizontal signal lines

3. In some other embodiments, the leading wire posts 5 may be electrically connected to the horizontal signal lines 3 through conductive structures in the memory cells TC, which is described in detail subsequently.

[0060] Referring to FIG.4 to FIG. 22, in some embodiments, the memory cell TC may include a transistor T and a capacitor C arranged in the third direction Y. The horizontal signal lines 3 and the vertical signal lines 4 are connected to the transistor T. Exemplarily, in a Dynamic Random Access Memory (DRAM), the memory cell TC includes a transistor T and a capacitor C. In some other embodiments, the memory cell TC may include only the transistor T. For example, in a Static Random-Access Memory (SRAM), the memory cell is composed of six transistors T. For another example, a Capacitor-less Double Gate Quantum Well Single Transistor (1T DRAM), the memory cell is composed of one double gate transistor T.

[0061] The transistor includes a channel region 22 and a source/drain doped region 21 arranged in the third direction Y, and the source/drain doped region 21 is located at two sides of the channel region 22. One of the horizontal signal line 3 and the vertical signal line 4 is a bit line (BL), and the other one is a word line (WL). The bit line BL is connected to the source/drain doped region 21, and the word line WL is connected to the channel region 22. Exemplarily, the source/drain doped region 21 includes a first source/drain doped region 211 and a second source/drain doped region 212, the first source/drain doped region 211 is located between the BL and the channel region 22 and the second source/drain doped region 212 is located on a side of the channel region 22 deviating away from the first source/drain doped region 211. The first source/drain doped region 211 and the second source/drain doped region 212 may respectively serve as a source and a drain of the transistor T. In addition, the second source/drain doped region 21 may further include a light doped drain structure arranged between the channel region and the drain electrode.

[0062] A position relation among the leading wire post 5 and the memory cell TC and the horizontal signal line 3 is described below in detail.

[0063] In a case that the horizontal signal line 3 is BL and the vertical signal line 4 is WL, the position relation among the leading wire post 5 and the memory cell TC and the

horizontal signal line 3 is described as follows.

[0064] In a first example, referring to FIG. 4 and FIG. 12 to FIG. 17, a bottom surface of at least one leading wire post 5 is located in the source/drain doped region 21. That is, the orthographic projection of the leading wire post 5 on the surface of the substrate 11 is overlapped with the orthographic projection of the source/drain doped region 21 on the surface of the substrate 11, and the leading wire post 5 may be electrically in contact with the BL by utilizing a spatial position of the source/drain doped region 21. It is to be noted that FIG. 13, FIG. 15 and FIG. 17 are all schematic partially side view, and do not show the channel region, the vertical signal lines and the capacitors.

[0065] Specifically, at least one leading wire post 5 is in contact with the first source/drain doped region 211 of the corresponding layer. Since the first source/drain doped region 211 is closer to the BL than the second source/drain doped region 212, a distance between the leading wire post 5 and the BL may be shortened when the leading wire post 5 and the BL are electrically connected by utilizing the spatial position of the first source/drain doped region 211, thereby reducing resistance, and simplifies the production process. In a case that the leading wire post 5 and the BL are electrically connected by utilizing a spatial position of the second source/drain doped region 212, conducting processing may be performed on the channel region 22 and the first source/drain doped region 211, to reduce resistance of the channel region 22 and the first source/drain doped region 211.

[0066] In some embodiments, referring to FIG. 4 and FIG. 12 to FIG. 13, at least one leading wire post 5 penetrates through the source/drain doped region 21 in at least one memory cell TC. The orthographic projection of the leading wire post 5 on the surface of the substrate is at least partially overlapped with the orthographic projection of the memory cell TC, for example, the first source/drain doped region 211, on the surface of the substrate. Specifically, at least one leading wire post 5 penetrates through the source/drain doped region 21 of the corresponding layer. For example, the leading wire post 5 may penetrate through the first source/drain doped region 211 of the memory cell TC of the corresponding layer. In this case, the leading wire post 5 may be directly in contact with to the BL through the side wall.

[0067] In some other embodiments, referring to FIG. 14 to FIG. 15, a bottom surface of the leading wire post 5 is embedded into the source/drain doped region 21. That is, a bottom end of the leading wire post 5 is located in the source/drain doped region 21 and does not penetrate through the source/drain doped region 21 completely. In this case, the leading wire post 5 may not only be directly in contact with the BL, but also be electrically connected to the BL through the source/drain doped region 21.

[0068] In some other embodiments, referring to FIG. 16 to FIG. 17, a bottom surface of the leading wire post 5 is located on a top surface of the source/drain doped region 21. For example, the bottom surface of the leading wire post 5 is located on the top surface of the first source/drain doped region 211. In this case, the leading wire post 5 is not directly in contact with the BL, but is electrically connected to the BL through the source/drain doped region 21. In order to reduce the resistance of the source/drain doped region 21, conducting processing may be performed on the source/drain doped region 21. For example, a metal silicide is formed in the source/drain doped region 21 by adopting a metal silicification process. Alternately, heavy doping treatment is performed in the source/drain doped region 21.

[0069] It is to be noted that the leading wire post 5 in contact with the memory cell TC of the non-top layer may penetrate through the source/drain doped region 21 above the corresponding layer. The leading wire post 5 in contact with the memory cell TC of the top layer does not penetrate through other source/drain doped region 21 of a layer rather than the corresponding layer.

[0070] In a second example, referring to FIG. 18, the memory cell TC further includes a bit line contact area 23. The bit line contact area 23 connects the BL to the source/drain doped region 21. The bit line contact area 23 may reduce a contact resistance between the BL and the source/drain doped region 21. Exemplarily, the bit line contact area 23 may be a heavily doped polycrystalline silicon or metal silicide.

[0071] A bottom surface of at least one leading wire post 5 is located in the bit line contact area 23. That is, the leading wire post 5 may further be electrically connected to the BL by utilizing the bit line contact area 23. For example, at least one leading wire post 5 penetrates through the bit line contact area 23 in a memory cell TC. Alternatively,

the at least one leading wire post 5 is embedded into the bit line contact area 23 of the corresponding layer. Alternately, the bottom surface of the at least one leading wire post 5 is in contact with a top surface of the bit line contact area 23 of the corresponding layer.

[0072] In a case that the horizontal signal line 3 is the WL and the vertical signal line 4 is the BL, a position relation between the leading wire post 5 and the memory cell TC and the horizontal signal line 3 is described as follows.

[0073] In a first example, referring to FIG. 19, a bottom surface of at least one leading wire post 5 is located in the channel region 22. That is, the orthographic projection of the leading wire post 5 on the surface of the substrate 11 is overlapped with the orthographic projection of the channel region 22 on the surface of the substrate 11, and the leading wire post 5 may be electrically connected to the word line WL by utilizing a spatial position of the channel region 22.

[0074] It is to be noted that there are various position relations between the word line WL and the channel region 22. For example, the word line WL may cover the entire channel region 22. Alternatively, the word line WL may be connected to a top surface and/or a bottom surface of the channel region 22.

[0075] A position relation between the leading wire post 5 and the word line WL is described below by taking a case that the word line WL at least covers the top surface of the channel region 22 as an example.

[0076] Referring to FIG. 19, in a case that the leading wire post 5 is in contact with the memory cell TC of the non-top layer, the leading wire post 5 is electrically connected to the word line WL on the memory cell TC of the corresponding layer and penetrates through the channel region 22 and the word line WL located above the corresponding layer. The orthographic projection of the leading wire post 5 on the surface of the substrate is at least partially overlapped with the orthographic projection of the channel region 22 in the memory cell TC on the surface of the substrate. It is to be noted that although the leading wire post 5 penetrates through the word line WL, the leading wire post 5 does not completely truncate the word line WL. For example, the leading wire post 5 penetrates through the center of the word line WL. The dielectric layer 6 exists between

the leading wire post 5 and the word line WL above the corresponding layer, to prevent electrical connection between the leading wire post 5 and the word line WL above the corresponding layer.

[0077] In a case that the leading wire post 5 is in contact with the memory cell TC of the top layer, the leading wire post 5 may be electrically connected to the word line WL of the top layer without penetrating through any word line WL and the channel region 22.

[0078] Since the semiconductor structure at least includes two leading wire posts 5 in contact with the memory cells TC of different layers, at least one leading wire post 5 is in contact with the memory cell TC of the non-top layer. Therefore, the at least one leading wire post 5 penetrates through the channel region 22 in at least one memory cell TC.

[0079] It is to be noted that in a case that the word line WL does not cover the top surface of the channel region 22 but covers the bottom surface of the channel region 22, the leading wire post 5 in contact with the memory cell TC of the top layer at least penetrates through one channel region 22, so as to be connected to the WL on the bottom surface of the channel region 22.

[0080] In a second example, referring to FIG. 20 to FIG. 21, the bottom surface of the at least one leading wire post 5 is located in the source/drain doped region 21, and a part of a side surface of the leading wire post 5 is connected to the WL of the corresponding layer. In addition, the word line WL further penetrates through the source/drain doped region 21 above the corresponding layer. That is, the leading wire post 5 may further be electrically connected to the word line WL by utilizing the source/drain doped region 21. Specifically, referring to FIG. 20, a bottom surface of the at least one leading wire post 5 is located in the first source/drain doped region 211 and a part of a side surface of the leading wire post 5 is connected to the WL of the corresponding layer, and the orthographic projection of the leading wire post 5 on the surface of the substrate is at least partially overlapped with the orthographic projection of the first source/drain doped region 211 in the memory cell TC on the surface of the substrate. Referring to FIG. 21, the bottom surface of the at least one leading wire post 5 is located in the second source/drain doped region 212 and a part of the side surface of the leading wire post 5 is connected to the word line WL of the corresponding layer, and the orthographic

projection of the leading wire post 5 on the surface of the substrate is at least partially overlapped with the orthographic projection of the second source/drain doped region 212 in the memory cell TC on the surface of the substrate.

[0081] It is to be noted that the bottom surface of the leading wire post 5 is located in the source/drain doped region 21 but is electrically isolated from the source/drain doped region 21. For example, the bottom surface of the leading wire post 5 may form an isolation layer (not shown in FIG. 20 and FIG. 21). Alternatively, before the leading wire post 5 is formed, passivation treatment is performed on the surface of the source/drain doped region 21 of the corresponding layer.

[0082] The structure module is described below in detail.

[0083] Referring to FIG. 22, there are a plurality of stacked structures, the plurality of horizontal signal lines 3 of the same stacked structure includes first to N-th horizontal signal lines successively arranged in the second direction Z, and N being a positive integer greater than 1.

[0084] Two stacked structures constitute a structure module. The structure module further includes a plurality of wires 7, and the wire 7 connects two leading wire posts 5 connected to different stacked structures. In other words, two leading wire posts 5 located in different stacked structures are connected by one wire 7, and a sum of sequence numbers of two horizontal signal lines 3 electrically connected to the two leading wire posts 5 is (N+1).

[0085] That is, the two horizontal signal lines 3 with the sum of sequence numbers being (N+1) may be electrically connected by the wire 7 through the leading wire posts 5. The two horizontal signal lines 3 electrically connected may form a horizontal signal line group. As a result of same potential, the two horizontal signal lines 3 of the horizontal signal line group may further be regarded as one horizontal signal line 3.

[0086] Exemplarily, the horizontal signal lines 3 include first to fifth horizontal signal lines, and the first horizontal signal line of a stacked structure is connected to the fifth horizontal signal line of another stacked structure. The second horizontal signal line of a stacked structure is connected to the fourth horizontal signal line of another stacked

structure. The third horizontal signal line of a stacked structure is connected to the third horizontal signal line of another stacked structure. The first horizontal signal line is located in the top layer, and the fifth horizontal signal line is located in the bottom layer.

[0087] It is to be noted that since the leading wire post 5 penetrates through the memory cell TC, the penetrated memory cell TC no longer executes the storage function. Since the leading wire posts 5 are in contact with the memory cells TC of different layers, the numbers of available memory cells TC of different layers in the semiconductor structure are different. For example, there are totally five layers of memory cells TC. The first layer as the top layer is lack of five memory cells TC. The second layer is lack of four memory cells TC. The third layer is lack of three memory cells TC. The fourth layer is lack of two memory cells TC. The fifth layer, as the bottom layer, is lack of one memory cell TC. Under the action of the wire 7, the numbers of the memory cells TC connected to different horizontal signal line groups are identical.

[0088] In addition, since the leading wire posts 5 in contact with the memory cells TC of different layers have different lengths, different resistances are generated. Based on an RC delayed effect, delay times of different memory cells TC are different. Under the action of the wire 7, the leading wire posts 5 in pairs form a group, and the total lengths of the leading wire posts 5 in each group are substantially identical, thereby unifying the delay time, so as to improve the performance of the semiconductor structure.

[0089] In addition, the contact areas between the memory cells TC of different layers and the leading wire post 5 may be kept consistent, so as to obtain consistent contact resistance, thereby preventing generation of different delay times. For example, the contact areas between the memory cells TC of different layers and the leading wire post 5 all are $0.036\text{-}0.054\ \mu\text{m}^2$.

[0090] In some embodiments, two leading wire posts 5 connected by the wire 7 are arranged directly opposite, and an extension direction of the wire 7 is perpendicular to the first direction X, to shorten the distance between the two leading wire posts 5, and reduce the length of the wire. Since the length of the wire is reduced, the resistance is reduced, the power consumption is reduced, and the delay time is shortened. In some other embodiments, referring to FIG. 22, the two leading wire posts 5 connected by the

wire 7 may be staggered to each other.

[0091] In the same structure module, the transistor T of one stacked structure is arranged facing to the transistor T of the other stacked structure. That is, the capacitor C of a stacked structure has two opposite sides arranged in the third direction Y. A side of the capacitor facing the another stacked structure is an inner side, and a side of the capacitor opposite to the other stacked structure is an outer side. The transistors T are arranged facing to each other, indicating that the two transistors T both are arranged on the inner sides of the stacked structures where the transistors are arranged, to shorten the distance between the two transistors T, and further shorten the distance between the two leading wire posts 5, so as to reduce the lengths of the wire 7.

[0092] As shown in FIG. 22, in some other embodiments, in the same structure module, the transistor T of a stacked structure is arranged in a same direction as the transistor T of the other stacked structure. Alternatively, in the same structure module, the transistor T of a stacked structure is arranged opposite to the transistor T of the other stacked structure. The transistors T are arranged in a same direction, indicating that the transistor T of a stacked structure is located on the inner side of the capacitor C and the transistor T of the other stacked structure is located on the outer side of the capacitor C. The transistors T are arranged oppositely, indicating that the transistors T of the two stacked structures both are arranged on the outer side of the capacitor C.

[0093] In conclusion, in the embodiments of the disclosure, at least two leading wire posts 5 are integrated, from the staircase, into an area where the memory cells TC are arranged, thereby improving a utilization ratio of the surface area of the substrate 11. In a case that all the leading wire posts 5 are arranged in the area where the memory cells TC are arranged, it is unnecessary to arrange the separate staircase, thereby improving the integration level of the semiconductor structure, and increasing the number of the memory cells TC.

[0094] As shown in FIG. 23 to FIG. 35, another embodiment of the disclosure further provides a method for manufacturing a semiconductor structure. The method may be used for manufacturing the semiconductor structure provided by the aforementioned embodiment, and regarding the detailed description about the semiconductor structure,

reference may be made to the aforementioned embodiment. It is to be noted that in order to conveniently describe and clearly illustrate operations of the method for manufacturing the semiconductor structure, FIG. 23 to FIG. 35 all are schematic partially structural diagrams of semiconductor structure. FIG. 23, FIG. 25, FIG. 26 and FIG. 28 to FIG. 30 are schematic partial side view, in which the channel regions, the vertical signal lines and the capacitors are not shown. FIG. 24, FIG. 27 and FIG. 31 are partial side views in which an insulating layer 12 is not shown. FIG. 32 and FIG. 34 are sectional views in the first direction X and FIG. 33 and FIG. 34 are partial top views, in which the insulating layer 12 is not shown.

[0095] Referring to FIG. 23, the substrate 11 is provided. A stacked structure is formed on the substrate 11, the stacked structure includes a plurality of memory cell groups TC0 (referring to FIG. 1) arranged in a first direction X, each of the memory cell groups TC0 includes multiple layers of memory cells TC arranged in the second direction Z. The plurality of memory cells TC of the same memory cell group TC0 include the first memory cell to the N-th memory cell successively arranged. The first memory cell is located in the top layer, and the N-th memory cell is located in the bottom layer.

[0096] Exemplarily, the memory cell TC may include a transistor T and a capacitor C.

[0097] Specifically, the operation that the transistor T is formed may include operations as follows. Multiple active layers are arranged at an interval, and each of the active layers includes a plurality of active structures. Doping treatment is performed on the active structure, to form a source/drain doped region 21 and a channel region 22. A gate dielectric layer is formed on a surface of the channel region 22. That is, the memory cell TC includes a channel region 22 and a source/drain doped region 21 arranged in the third direction Y. The source/drain doped region 21 is located on two sides of the channel region 22. The third direction Y is parallel to the surface of the substrate 11.

[0098] In addition, an insulating layer 12 is arranged between the transistors T of adjacent layers, so as to isolate the adjacent transistors T.

[0099] The operation that the capacitor C is formed may include an operation. A capacitor supporting layer and a capacitor hole located in the capacitor supporting layer

are formed. A lower electrode is formed on an inner wall of the capacitor hole. A capacitor dielectric layer is formed on a surface of the lower electrode, and an upper electrode is formed on the surface of the capacitor dielectric layer. The lower electrode, the capacitor dielectric layer and the upper electrode form the capacitor C.

[00100] The method further includes operations as follows. A plurality of horizontal signal lines 3 and a plurality of vertical signal lines 4 (referring to FIG. 4) are formed. The plurality of horizontal signal lines 3 are arranged in the second direction Z and extend along the first direction X. Each of the horizontal signal lines 3 is connected to the memory cells TC of one layer. The vertical signal lines 4 extend along the second direction Z and are connected to the multiple layers of memory cells TC of the same memory cell group TC0. The first direction X is parallel to the surface of the substrate 11, and the second direction Z is perpendicular to the surface of the substrate 11.

[00101] One of the horizontal signal line 4 and the vertical signal line 3 is a bit line (BL), and the other one is a word line (WL). The bit line BL is connected to the source/drain doped region 21, and the word line WL, as a gate, is connected to the channel region 22.

[00102] A method for forming the vertical signal line 4 may include operations as follows. An isolation structure is formed, and the isolation structure is etched to form a filling hole in the isolation structure. The filling hole extends in the second direction Z. A conductive material is deposited in the filling hole, to form the vertical signal line 4.

[00103] The operation that the horizontal signal line 3 is formed may include operations as follows. A conductive material is deposited on the surface of the active structure, to enable the conductive material to wrap the active structure of the same layer. Hereafter, an isolation structure is formed between the adjacent horizontal signal lines 3.

[00104] Referring to FIG. 23 to FIG. 35, a plurality of leading wire posts 5 are formed, where at least two leading wire posts 5 are respectively in contact with different layers of memory cells TC in different memory cell groups TC0.

[00105] The operation that the leading wire post 5 is formed is described below in detail.

[00106] In a case that the horizontal signal lines 3 are bit lines BL and the vertical signal lines 4 are word lines WL, the operation that the leading wire post 5 is formed include the following operations.

[00107] First, it is to be noted that the plurality of source/drain doped regions 21 of the same memory cell group TC0 include the first layer of source/drain doped region to the N-th layer of source/drain doped region which are successively arranged, N being a positive integer. The first layer source/drain doped region is located in the top layer, and the N-th layer of source/drain doped region is located in the bottom layer.

[00108] Referring to FIG. 23 to FIG. 24, a mask layer 71 is formed, and the mask layer 71 has N openings 72, N being a positive integer. The openings 72 are located above the source/drain doped region 21. For example, the openings are located above the first source/drain doped region 211. Exemplarily, the mask layer 71 may be a photoresist layer, and the photoresist layer is photo-etched to form the openings 72. Alternatively, the mask layer 71 may further be a hard mask layer and a photoresist layer arranged in an overlapped manner, and after the photoresist layer is photo-etched, the hard mask layer is then etched, to form the openings 72.

[00109] Referring to FIG. 25, the first memory cell is etched along the openings 72 to form a plurality of first sub-through holes 811. One of the first sub-through holes 811 is taken as a first through hole 81. Specifically, the source/drain doped region 21 is etched along the openings 72. In addition, before the first memory cell is etched, the insulating layer 12 located above the first memory cell is etched.

[00110] Referring to FIG. 26 to FIG. 27, a sacrificial layer 73 filling the first sub-through holes 8 is formed. Exemplarily, a low dielectric constant material such as silicon oxide is deposited in the first sub-through holes 8 to serve as the sacrificial layer 73.

[00111] Continuously referring to FIG. 26 to FIG. 27, the mask layer 71 is patterned to enable the mask layer 71 to have the (N-1) openings 72. Specifically, the photoresist layer may be spin-coated again, and the photoresist layer is photo-etched to form the openings 72.

[00112] Referring to FIG. 28, the sacrificial layer 73 and the second memory cell are etched along the openings 72 to form (N-1) second sub-through holes 821. One of the second sub-through holes 821 serves as a second through hole 82. After the sacrificial layer 73 is etched, the insulating layer 72 located on the second memory cell is etched.

[00113] Referring to FIG. 29, the operations of forming the sacrificial layer 73, patterning the mask layer 71 and etching are repeated till the N-th memory cell is penetrated, that is, the N-th source/drain doped region is penetrated. In some other embodiments, the operations of forming the sacrificial layer, patterning the mask layer 71 and etching are repeated till the (N-1)-th memory cell is penetrated, and the N-th memory cell is exposed. Alternatively, the (N-1)-th memory cell is penetrated, and the N-th memory cell of partial thickness is removed.

[00114] At this point, based on FIG. 23 to FIG. 29, the through hole 8 may be formed, and the through hole 8 includes the first through hole to the N-th through hole. Exemplarily, referring to FIG. 29, the first through hole 81, the second through hole 82, the third through hole 83, the fourth through hole 84 and the fifth through hole 85 may be formed. In some embodiments, the first through hole 81 may penetrate through the first layer of source/drain doped region, and the N-th through hole may penetrate through the first layer of source/drain doped region to the N-th layer of source/drain doped region 21. In some other embodiments, the first layer of source/drain doped region 21 is exposed in the first through hole 8, and the N-th through hole penetrates through the first layer of source/drain doped region to the (N-1)-th layer of source/drain doped region 21, and exposes the N-th layer of source/drain doped region 21. In some other embodiments, the first layer of source/drain doped region 21 is embedded onto the bottom of the first through hole 8, the N-th through hole penetrates through the first layer of source/drain doped region to the (N-1)-th layer of source/drain doped region, and the N-th layer of source/drain doped region is embedded onto the bottom of the N-th through hole. It is to be noted that depths of the first through hole 81, the second through hole 82, the third through hole 83, the fourth through hole 84 and the fifth through hole 85 arranged successively increase progressively in the first direction X. In other embodiments, depths of the first through hole 81, the second through hole 82, the third through hole 83, the fourth through hole 84 and the fifth through hole 85 arranged successively may not

increase or decrease progressively in the first direction X, but the depths of the through holes are alternated, so as to avoid too large parasitic capacitance between the leading wire posts 5 with large depths among the subsequently formed leading wire posts 5.

[00115] Referring to FIG. 30 to FIG. 31, the dielectric layer 6 covering a side wall of the through hole 8 is formed, and the leading wire post 5 filling the through hole 8 is formed, and the leading wire post 5 contacts with the corresponding source/drain doped region 21.

[00116] Specifically, in a case that the N-th through hole penetrates the N-th layer of source/drain doped region 21, or the N-th through hole penetrates the (N-1)-th layer of source/drain doped region 21 and the bottom of N-th through hole is embedded into the N-th layer of source/drain doped region 21, the operation that the dielectric layer 6 and the leading wire post 5 are formed may include the following operations.

[00117] The contact portion 51 is formed in the bottom of the through hole 8, and the contact portion 51 is in contact with the memory cell TC of the corresponding layer. After the contact portion 51 is formed, the dielectric layer 6 is formed on the side wall of the through hole 8. Exemplarily, an initial dielectric layer is formed on the side wall of the through hole 8 and a surface of the contact portion 51 through a chemical vapor deposition process. The initial dielectric layer on the surface of the contact portion 51 is removed, and the initial dielectric layer located on the side wall of the through hole 8 is taken as the dielectric layer 6. After the dielectric layer 6 is formed, an extension portion 52 filling the through hole 8 is formed. The extension portion 52 and the contact portion 51 form the leading wire post 5.

[00118] In a case that the N-th through hole 8 penetrates the (N-1)-th layer of source/drain doped region, and the N-th layer of source/drain doped region is exposed, the operation that the dielectric layer 6 and the leading wire post 5 are formed may include operations as follows. The dielectric layer 6 is formed on an inner wall of the through hole 8, and after the dielectric layer 6 is formed, the leading wire post 5 filling the through hole 8 is then formed. In this case, a metal silicide may be formed in the source/drain doped region 21 of the corresponding layer by adopting a metal silicification process, to reduce the contact resistance. Specifically, a metal layer is deposited on the

inner wall of the through hole 8, and thermal treatment is performed so that the metal layer is reacted with the source/drain doped region 21. Hereafter, an unreacted metal layer is removed, and the unreacted metal layer is mainly located on the side wall of the through hole 8. Then, the dielectric layer 6 and the leading wire post 5 are formed.

[00119] In a case that the horizontal signal lines 3 are the bit lines BL and the vertical signal lines 4 are word lines WL, the operation that the leading wire post 5 is formed include the following operations.

[00120] First, it is to be noted that the plurality of channel regions 22 of the same memory cell group TC0 include the first channel region to the N-th channel region successively arranged, N being a positive integer. The first channel region is located in the top layer, and the N-th channel region is located in the bottom layer.

[00121] Referring to FIG. 32 to FIG. 33, the through hole 8 is formed, the through hole 8 includes the first through hole 81 to the N-th through hole. The word line WL connected to the first channel region is exposed in the first through hole 8, and the N-th through hole 8 penetrates through the first channel region 22 to the (N-1)-th channel region and exposes the WL connected to the N-th channel region. The operation that the through hole 8 is formed may refer to aforementioned detailed description.

[00122] Referring to FIG. 34 to FIG. 35, a dielectric layer 6 covering the side wall of the through hole 8 is formed. Specifically, an initial dielectric layer is formed on an inside wall of the through hole 8. The initial dielectric layer located on the bottom wall of the through hole 8 is removed to expose the word line WL of the corresponding layer, and the initial dielectric layer located on the side wall of the through hole 8 is taken as the dielectric layer 6.

[00123] Continuously referring to FIG. 34 to FIG. 35, the leading wire post 5 filling the through hole 8 is formed, the leading wire post 5 is in contact with the corresponding word line WL. Exemplarily, metals such as copper, aluminum, titanium or tungsten are deposited in the through hole 8 as the leading wire post 5.

[00124] It is to be noted that the abovementioned method for forming the leading wire post 5 is merely exemplary described but is not limited thereto. The method for forming

the leading wire post 5 may be adjusted according to a specific structure of the leading wire post 5.

[00125] In conclusion, in the embodiments of the disclosure, the memory cell TC is etched to form the through hole 8, and the dielectric layer and the leading wire post 5 filling the through hole 8 is formed. Therefore, the leading wire post 5 may be electrically connected to the memory cell TC directly by utilizing a spatial position of the memory cell TC, to reduce the number of stairs without forming the independent staircase, thereby improving the integration level of the semiconductor structure.

[00126] Referring to FIG. 36 to FIG. 38, another embodiment of the disclosure further provides a semiconductor structure. The semiconductor structure is substantially same with the semiconductor structure in the aforementioned embodiments. The main difference lies in that at least two leading wire posts 5 of this semiconductor structure are in contact with different memory cells TC in the same memory cell group TC0. Regarding the parts of the semiconductor structure same as or similar to the semiconductor structure in the aforementioned embodiments, reference can be made to detailed description in the aforementioned embodiments, which is not described in detail herein.

[00127] The semiconductor includes a substrate 11 (referring to FIG. 34) on which the a stacked structure is provided. The stacked structure includes a plurality of memory cell groups TC0 arranged in a first direction X, and each of the memory cell groups TC0 includes multiple layers of memory cells TC arranged in a second direction Z. The semiconductor further includes a plurality of leading wire posts 5. At least two leading wire posts 5 are in contact with different memory cells TC in the same memory cell group TC0.

[00128] Compared with a case that different leading wire posts 5 are located in different memory cell groups TC0, at least two leading wire posts 5 may utilize the spatial position of the same memory cell group TC0, thereby improving the spatial utilization ratio of the same memory cell group TC0 and further increasing the number of the available memory cells TC. For example, in a case that two leading wire posts 5 are respectively connected to the memory cell TC of the top layer and the memory cell TC of

the secondary top layer, when the memory cell TC of the top layer and the memory cell TC of the secondary top layer are located in different memory cell group TC0, three memory cells TC are invalid. When the memory cell TC of the top layer and the memory cell TC of the secondary top layer are located in the same memory cell group TC0, two memory cells TC are invalid.

[00129] It is to be noted that in the same semiconductor structure, the abovementioned two solutions may further be combined. For example, the semiconductor structure includes at least four leading wire posts 5. At least two leading wire posts 5 are respectively connected to different layers of memory cells TC in different memory cell groups TC0, and at least two leading wire posts 5 are respectively connected to different layers of memory cells TC in the same memory cell group TC0.

[00130] Continuously referring to FIG. 36 to FIG. 38, at least two leading wire posts 5 in contact with different memory cells TC in the same memory cell group TC0 are arranged along the first direction X, to unify a contact position between the leading wire posts 5 and the memory cells TC, thereby simplifying the connection process.

[00131] In some embodiments, the stacked structure further includes a plurality of horizontal signal lines 3 and a plurality of vertical signal lines 4. The plurality of horizontal signal lines 3 are arranged in the second direction Z and extend along the first direction X, and are connected to one layer of the memory cells TC. The vertical signal lines 4 extend along the second direction Z and are connected to the multiple layers of memory cells TC of the same memory cell group TC0. The leading wire posts 5 are electrically connected to the horizontal signal lines 3.

[00132] In some embodiments, the leading wire posts 5 in contact with different memory cells TC in the same memory cell group TC0 are lined up along the first direction X. That is, the leading wire posts 5 are substantially aligned in the first direction X. Therefore, the distances of the plurality of leading wire posts 5 in relative to the horizontal signal lines 3 are substantially identical, thereby unifying the contact resistance between the plurality of leading wire posts 5 and the horizontal signal lines 3. In addition, the process is simplified and the uniformity of the semiconductor structure is improved. For example, referring to FIG. 37, two ends of the plurality of leading wire

posts 5 are aligned in the first direction X, thereby simplifying the process. Referring to FIG. 38, two ends of the plurality of leading wire posts 5 are slightly staggered in the first direction X, to reduce the area of a directly facing region, thereby reducing parasitic capacitance.

[00133] In conclusion, in the embodiments of the disclosure, at least two leading wire posts 5 are integrated, from the staircase, into an area where the memory cells TC are arranged, thereby improving a utilization ratio of the surface area of the substrate 11. In addition, at least two leading wire posts 5 are in contact with different layers of memory cells C in same memory cell group TC0, indicating that at least two leading wire posts 5 may utilize the spatial space of the same memory cell group TC0, to decrease the number of the invalid memory cells TC, thereby improving the integration level of the semiconductor structure.

[00134] The embodiments of the disclosure further provide a memory chip, including the semiconductor structure provided by the aforementioned embodiments.

[00135] The memory chip is a memory part for storing programs and various data information. Exemplarily, the memory chip may be a random access memory chip or a read-only memory chip. For example, the random access memory chip may include a Dynamic Random Access Memory (DRAM) or a Static Random Access Memory (SRAM). Since the integration level of the aforementioned semiconductor structure is high, it contributes to realizing microminiaturization of the memory chip.

[00136] The embodiments of the disclosure further provide an electronic device, including the memory chip provided by the aforementioned embodiments.

[00137] Exemplarily, the electronic device may be a device such as a television, a computer, a mobile phone or a tablet computer. The electronic device may include a circuit board and a package structure, and the memory chip may be welded to the circuit board and is protected by the package structure. In addition, the electronic device may further include a power supply for providing a working voltage to the memory chip.

[00138] In the description of the specification, the description with reference to the terms “some embodiments”, “exemplarily”, and the like means that specific features,

structures, materials, or features described in connection with the embodiments or examples are included in at least one embodiment or example of the disclosure. In the description, schematic expressions of the terms do not have to mean same embodiments or exemplary embodiments. Furthermore, specific features, structures, materials or characteristics described can be combined in any one or more embodiments or exemplary embodiments in proper manners. In addition, under a condition without mutual contradiction, those skilled in the art can integrate or combine different embodiments or examples with features of different embodiments or examples described in the description.

[00139] Although the embodiments of the disclosure have been shown and described above, it can be understood that the above embodiments are exemplary and cannot be construed as limitation to the disclosure. Those of ordinary skill in the art can make changes, modification, replacement and transformation on the embodiments within the scope of the present disclosure. Changes and modifications made according to claims and description of the disclosure shall fall into the scope of the disclosure.

CLAIMS

1. A semiconductor structure, comprising:

a substrate on which at least one stacked structure is provided, the stacked structure comprising a plurality of memory cell groups arranged in a first direction, each of the memory cell groups comprising multiple layers of memory cells arranged in a second direction; and

a plurality of leading wire posts, wherein each of the leading wire posts is in direct contact with one layer of memory cells in one memory cell group, and at least two of leading wire posts respectively are in direct contact with different layers of memory cells in different memory cell groups.

2. The semiconductor structure according to claim 1, wherein

the leading wire posts are arranged along the first direction, and

the leading wire posts are lined up along the first direction.

3. The semiconductor structure according to claim 1, wherein

all the memory cells in a same memory cell group are in contact with at most one leading wire post of the plurality of leading wire posts.

4. The semiconductor structure according to claim 1, wherein

the number of the plurality of leading wire posts is equal to or greater than the number of layers of the memory cells, and each layer of memory cells at least comprises one memory cell in contact with the leading wire post.

5. The semiconductor structure according to claim 1, wherein

the number of leading wire posts in contact with one of the memory cell groups is less than the number of layers of the memory cells in the one memory cell group.

6. The semiconductor structure according to claim 1, wherein the first direction is parallel to a surface of the substrate, and the second direction is perpendicular to the surface of the substrate;

the stacked structure further comprises a plurality of horizontal signal lines and a plurality of vertical signal lines, wherein the plurality of horizontal signal lines are arranged in the second direction and extend along the first direction, and each of the horizontal signal lines is connected to one layer of memory cells, and the vertical signal lines extend along the second direction and are connected to multiple layers of memory cells in a same memory cell group; and

the leading wire posts are electrically connected to the horizontal signal lines.

7. The semiconductor structure according to claim 6, wherein

each of the memory cells comprises a channel region and a source/drain doped region arranged in a third direction, the source/drain doped region is arranged at two sides of the channel region, and the third direction is parallel to the surface of the substrate.

8. The semiconductor structure according to claim 7, wherein

each of the plurality of horizontal signal lines is a bit line, and each of the plurality of vertical signal lines is a word line,

the bit line is connected to the source/drain doped region, and the word line is connected to the channel region; and

at least one of the plurality of leading wire posts penetrates through the source/drain doped region in at least one of the memory cells, wherein

the source/drain doped region comprise a first source/drain doped region and a second source/drain doped region, the first source/drain doped region is located between the bit line and the channel region, and the second source/drain doped region

is located at a side of the channel region deviating away from the first source/drain doped region; and

the leading wire post penetrates through the first source/drain doped region.

9. The semiconductor structure according to claim 7, wherein

each of the plurality of horizontal signal lines is a word line, and each of the plurality of vertical signal lines is a bit line,

the bit line is connected to the source/drain doped region, and the word line is connected to the channel region; and

at least one of the plurality of leading wire posts penetrates through the channel region in at least one of the memory cells.

10. The semiconductor structure according to claim 7, wherein the memory cell further comprises a bit line contact area, the bit line contact area connecting the bit line to the source/drain doped region, wherein at least one of the plurality of leading wire posts penetrates through the bit line contact area in one of the memory cells.

11. The semiconductor structure according to claim 1, wherein

the numbers of memory cells which the at least two leading wire posts penetrate through are different from each other.

12. The semiconductor structure according to claim 1, wherein

two adjacent leading wire posts of the plurality of leading wire posts are at least spaced by one of the plurality of memory cell groups, wherein

the number of memory cells between the two adjacent leading wire posts is fixed, or

the area of a directly facing region between the two adjacent leading wire posts

is directly proportional to the number of memory cell groups between the two adjacent leading wire posts.

13. The semiconductor structure according to claim 6, wherein

the number of stacked structures is greater than one, the plurality of horizontal signal lines of a same stacked structure comprises a first horizontal signal line to N-th horizontal signal line successively arranged in the second direction, N being a positive integer greater than 1; and

two stacked structures of the stacked structures constitute a structure module, the structural module further comprises a plurality of wires, the wire connects two leading wire posts, which are in contact with different stacked structures of the stacked structures, of the plurality of leading wire posts, and a sum of sequence numbers of the two horizontal signal lines electrically connected to the two leading wire posts being $N+1$.

14. The semiconductor structure according to claim 13, wherein

the two leading wire posts connected by the wire are arranged to be faced directly, and an extension direction of the wire is perpendicular to the first direction.

15. The semiconductor structure according to claim 13, wherein the memory cell comprises a transistor and a capacitor arranged in a third direction,

in a same structure module, the transistor of one stacked structure in the structure module is arranged facing to the transistor of another stacked structure in the structure module; or

in a same structure module, the transistor of one stacked structure in the structure module is arranged in a same direction as the transistor of another stacked structure in the structure module; or

in a same structure module, the transistor of one stacked structure in the

structure module is arranged in an opposite direction to the transistor of another stacked structure in the structure module.

16. The semiconductor structure according to claim 1, wherein at least one of the plurality of leading wire posts extends in the second direction and penetrates through at least one memory cell in the memory cell group,

the semiconductor structure further comprises a dielectric layer arranged between the leading wire post and the memory cell through which the leading wire post penetrates.

17. The semiconductor structure according to claim 16, wherein a bottom surface of the leading wire post is in contact with the memory cell, or at least a part of a side surface of the leading wire post is in contact with the memory cell.

18. The semiconductor structure according to claim 1, wherein the memory cells in contact with the at least two of the plurality of leading wire posts are arranged in a same memory cell group.

19. A method for manufacturing a semiconductor structure, comprising:

providing a substrate,

forming at least one stacked structure on the substrate, the stacked structure comprising a plurality of memory cell groups arranged in a first direction, each of the memory cell groups comprising multiple layers of memory cells arranged in a second direction; and

forming a plurality of leading wire posts, wherein each of the leading wire posts is in direct contact with one layer of memory cells in one memory cell group, and at least two of leading wire posts respectively are in direct contact with different layers of memory cells in different memory cell groups.

20. A semiconductor structure, comprising:

a substrate on which at least one stacked structure is provided, the stacked structure comprising a plurality of memory cell groups arranged in a first direction, each of the memory cell groups comprising multiple layers of memory cells arranged in a second direction; and

a plurality of leading wire posts, wherein each of the leading wire posts is in direct contact with one layer of memory cells in one memory cell group, and at least two leading wire posts are in direct contact with different layers of memory cells in a same memory cell group.