

SYSTEM AND METHOD FOR SECURE RECORD PROTOCOL USING SHARED KNOWLEDGE OF MOBILE USER CREDENTIALS

5

[0001] The present disclosure relates generally to secure record protocols, and in particular to secure record protocols for communications between a client and a server.

10 **[0002]** Secure communications are important when sending many types of information between a client and server. For example, financial information, health information, electronic mail, among others need to be protected, both by ensuring data authenticity and integrity, and through encryption of the data.

15 **[0003]** Various solutions exist to provide such secure communications. One example involves the use of client and server certificates. However, as will be appreciated by those skilled in the art, it is difficult for a domain owner such as carrier or enterprise to manage client certificates on a client device, especially when the client device is a mobile device. Further, the installation of these client certificates on a mobile device involves challenging logistics.

20

[0004] Alternative solutions include the use of a shared secret where the shared secret or part of it flows over the air between a client and server prior to the establishment of the secured channel. As will be appreciated, this over the air transfer of shared secrets could result in data integrity being compromised.

25

GENERAL

[0005] The present system and method may provide a lightweight security model for the establishment of a secure, authenticated record protocol between a device client and a generic mobile server. The method may be based on shared
30 knowledge of mobile user credentials such as a user password or any other secure parameters provided off-line at device or mobile user registration.

[0006] The system may involve a client key generator (CKG) that uses predefined security algorithms to generate public and private keys from an input token in a
35 single key pair encryption methodology, or to generate device client public and

private keys and a server public key from the input token in a dual key pairs solution. It should be noted that the server private key generated as a part of the sequence to produce the server public key is NOT exposed to the client runtime environment.

5

[0007] The system may further include a server key generator (SKG) that uses a matching security algorithm to that of the client key generator to generate a public and private key from the input token in a single key pair solution and a server public key, a server private key and a device client public key from the input token in an dual key pair solution. It should be noted that the client private key generated as a part of the sequence to produce the client public key is NOT exposed to the server runtime environment.

[0008] The present disclosure therefore may provide a method for secure record protocol in a system with a server and a client, comprising the steps of: utilizing a mobile user credential as an input to a key generator, said mobile user credential being known to both said server and said client; generating one or two public key-private key pairs based on said mobile user credential input; and sending a message signed with a private key.

20

[0009] The present disclosure may further provide a system for secure record protocol using a mobile user credential, comprising: a client, said client having: a communications subsystem; a processor adapted to communicate with said communications subsystem; a memory adapted to store an input created from said mobile user credential; a client key generator, said client key generator being provided with the input and adapted to generate one or two public key-private key pairs; and an signing/verification module, said signing/verification module adapted to sign a message with a private key generated by said client key generator; and a server, said server having: a communications subsystem adapted to communicate with said client communications subsystem; a processor adapted to communicate with said communications subsystem; a memory adapted to store an input created from said mobile user credential; a server key generator, said server key generator being provided with the input and adapted to

25
30

generate one or two public key-private key pairs; and an signing/verification module, said signing/verification module adapted to sign a message with a private key generated by said server key generator, wherein said client key generator and said server key generator are adapted to produce identical private key-public key pairs for an identical input.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The present disclosure will be better understood with reference to the drawings in which:

10 **Figure 1** is a block diagram of an exemplary device showing a single key pair solution utilizing a client key generator and a server key generator;

Figure 2 is a block diagram of an exemplary device showing a dual key pair solution utilizing a client key generator and a server key generator;

Figure 3 is a dataflow diagram of sample data flows between a client and server for the activation of a session;

Figure 4 is a dataflow diagram of sample data flows between a client and server for the activation of a session; and

Figure 5 is a block diagram of an exemplary mobile device.

20 DESCRIPTION OF PREFERRED EMBODIMENTS

[0011] Reference is made to **Figure 1**. **Figure 1** illustrates a block diagram of a simplified server and client adapted to be used in a single key pair encryption scheme. The system includes a server **110** and a client **150**. Server **110** includes a communications subsystem **112** adapted to communicate over a network with a client **150**, and in particular with a communications subsystem **152** on client **150**. As will be appreciated by those skilled in the art, the network over which communication occurs can be any network, included wired or wireless network. In one example, communications subsystem **152** is adapted to communicate through a wireless network such as a cellular network or a wireless local area network (WLAN) with a base station or an access point, which then connects through a series of system components such as a packet data serving node, through the internet to server **110**. Other examples of communications would be

known to those skilled in the art and the present application is not meant to be limited to any particular mode of communications.

5 [0012] Server **110** further includes a processor **114** adapted to communicate with the communications subsystem **112**.

[0013] Processor **114** also communicates with a memory **116** that is used to store various applications and data. Memory **116** could include any form of memory applied to computer systems and devices.

10

[0014] Processor **114** further communicates with a signing/verification module **120**. In the system of **Figure 1**, signing/verification module **120** is a single key pair signing/verification module.

15 [0015] A server key generator **125** is adapted to provide signing/verification module **120** with the signing/verification key necessary to either sign an outgoing message or verify an incoming message. The server key generator (SKG) **125** is further adapted to communicate with memory **116** in order to receive an input token from memory **116**.

20

[0016] The input token for SKG **125** comprises a mobile user credential that is known to both the server and the client. This could include credentials such as a user password or a secure code provided offline at device registration. Other examples of mobile user credentials would be known to those in the art.

25

[0017] SKG **125** utilizes input token from memory **116** to create both a public and a private key in a preferred embodiment. The private key is used for decrypting incoming messages and the public key is used for encrypting outgoing messages in the preferred embodiment.

30

[0018] SKG **125** further preferably includes domain owner parameters built into it. A wireless domain owner such as the carrier or the enterprise sets these domain owner parameters prior to deployment of SKG. SKG **125** combines the domain

owner parameters **127** with the input token received from memory **116** in order to generate the public key **130** and the private key **132**.

[0019] The combination of input token and domain owner parameters increases entropy and improves security. There are different ways of mixing these parameters. One is the generation of parameters from the domain owner parameters using, for example, DSA (Digital Signature Algorithm) keys. A DSA key generation mechanism can be found on the wikipedia web site under "Digital_Signature_Algorithm".

[0020] As described in the article above, (p, q, g, y) is a public key and (x) is a private key where:

p is order of a cyclic group Z_p^*
 q is order of a cyclic subgroup Z_q^* of Z_p^* (q divides p)
 g is a generator of cyclic subgroup Z_q^*
 y is an element in Z_q^* such that $g^x = y$.

[0021] As will be appreciated, p , q , and g define algorithm parameters, and y is what defines public key.

[0022] Normally, p , q , and g are public. However, in the above, p , q , and g can be a secret algorithm parameters set derived from domain owner credentials. Then x (private key) will be derived from subscriber password, and y will be calculated as $y = g^x$. Note that p , q , and g should be the same on both sides.

[0023] In another example, a 2-phase process could be used within the CKG and SKG, where at the first phase the process applies a transformation to the input token using a key derived from domain owner parameters. Again, this key can be setup in CKGs securely prior to their deployment onto devices. Using this approach at the 1st phase the process generates a new input key (with better entropy) and will feed this key to key pair generation in the second phase.

[0024] As will be appreciated by those in the art, other possible scenarios exist.

[0025] On the client side, client **150** includes a communication subsystem **152** as described above. Client **150** further includes a processor **154**. Processor **154** is adapted to send communications over communication subsystem **152** and further interacts with a memory **156**.

5

[0026] A signing/verification module **160** is utilized for signing outgoing messages and verifying incoming messages. Signing/verification module **160** communicates with a client key generator **165**, which is adapted to create a key. In particular, in a preferred embodiment, a public key **170** and a private key **172** are generated.

10 Public key **170** should be identical to public key **130** and private key **172** should be identical to private key **132**.

[0027] In operation, an input token stored in memory **156** is input to the CKG **165**. Preferably the domain owner parameters **167** are combined with the input token
15 from memory **156** and client key generator **165** creates a key based on these two parameters. This could be done, as with the above, in a number of ways.

[0028] Also, one or both of SKG **125** and signing/verification module **120** could be
20 part of processor **114**. In the alternative, these components can be separate from processor **114** on server **110**.

[0029] Similarly, CKG **165** could form part of processor **154** and
signing/verification module **160** could also form part of processor **154**. In the
25 alternative, one or both the SKG **165** and signing/verification module **160** could be separate components on client device **150**.

[0030] To provide better protection to the embodiment of **Figure 1**, a dual key pair system could be used. Reference is now made to **Figure 2**. **Figure 2** illustrates
30 an exemplary client/server system with a server **210** and a client **250**.

[0031] As with the system of **Figure 1**, server **210** includes a communications subsystem **212** which is adapted to communicate over a network with client **250** and in particular with a communication subsystem **252** on client **250**.

5 [0032] Server **210** further includes a processor **214** adapted to send and receive communications over communications subsystem **212** and further communicates with a memory **216** and a signing/verification module **220**. Memory **216** stores an input token that comprises a shared credential, and memory **216** could be any form of memory.

10

[0033] In the system of **Figure 2**, signing/verification module **220** is an asymmetric signing/verification module. In other words, on server **210**, the client private key is used to sign outgoing messages and a server public key is used to verify messages received from the client. As described below, the client public key
15 could also be used for encryption, and the server private key used for verification.

[0034] A server key generator **225** is adapted to receive the input token from memory **216**. Preferably, SKG **225** further includes algorithm parameters **227** which combine with the input token from memory **216** to the input for the server
20 key generator **225**.

[0035] SKG **225** produces a server public key **230**, a server private key **232**, a client public key **234** and a client private key (not shown). It is expected that the SKG **225** does not provide the ability to output the device client private key.

25

[0036] Similarly, client device **250** includes a communications subsystem **252** as described above. Further, client **250** includes a processor **254** adapted to send and receive communications over communications subsystem **252** and is adapted to communicate with memory **256**. An asymmetric signing/verification module
30 **260** communicates with the processor and communications subsystem **252** and further receives keys from a client key generator (CKG) **265**.

[0037] CKG 265 receives a shared credential from memory 256 and in a preferred embodiment also uses algorithm parameters 267 to create an input token to generate keys. CKG 265 generates a client public key 270, a client private key 272, a server public key 274 and a server private key (not shown). It is expected that the CKG does not provide the ability to output the server private key.

[0038] The above system therefore involves a client key generator 265 that uses a predefined security algorithm to generate device client public and private keys 270 and 272 respectively and further a server public key 274 from the input token. The above further involves a server key generator 225 that uses a matching security algorithm to generate a server public and private key 230 and 232 respectively, as well as a device client public key 234 based on the input token. When identical input tokens are used, the CKG 265 and the SKG 225 should satisfy the following conditions:

- a) The server public key generated by CKG 265 should be identical to the server public key generated by SKG 225 and match the server private key 232 generated by SKG 225; and
- b) The device client public key 234 generated by SKG 225 should be identical to client public key 270 generated by CKG 265 and match the client private key 272 generated by CKG 265.

[0039] The input parameters for algorithms used in SKG 225 and CKG 265 are confidential and managed by the domain owner. In a wireless domain, this could be the carrier or the enterprise. The SKG 225 and CKG 265 modules should offer a domain owner the ability to set up domain owner credentials prior to the deployment of these modules on servers 210 and devices 250. These domain owner credentials are a protected secret of the domain owner and provide additional security if client credentials are jeopardized. In one embodiment these parameters could be auto-generated using the domain owner private key.

30

[0040] Reference is now made to **Figure 3**. **Figure 3** shows a dataflow diagram in accordance with a preferred method. A client 310 communicates with a server 320. Client 310, upon version negotiation sends an activation message at step

322, the activation message providing a mobile user identity. A nonce could be provided with the activation message.

5 **[0041]** In an alternative flow, a client **310** could instead send a client activation message in step **342** and receive a challenge that may include a nonce in step **344**. The client **310** would then send a challenge response **346** in which the mobile user identity is optionally hashed with the nonce from step **344**.

10 **[0042]** Server **320** retrieves the mobile user identity from the message in **346** and uses the server key generator (SKG **225** from **Figure 2**) to generate a server private and public key pair as well as a client public key using the mobile user's password as an input token. Optionally, the input token for SKG **225** could be created using the password hashed with a secure hash function with a nonce if a client provided nonce in the activation message. In a further alternative, any
15 password transformation using parameters shared by the client and server could be performed.

20 **[0043]** The server can then send an activation confirmation response message signed with the server private key in step **352**.

25 **[0044]** In step **354**, the client key generator generates a server public key and a client private/public key pair using mobile user password as the input token. Optionally, the input token for the CKG could be created using the password hashed with a secure hash function with a nonce if a nonce was sent in the activation message, or any password transformation using parameters shared by both the client and the server.

30 **[0045]** The client **310** next verifies the message in step **356** with the server public key and optionally decrypts it with the client private key.

[0046] Subsequent messages between the client and the server use parts of their private/public keys for the record protocol to sign and encrypt messages.

[0047] With a more simple activation, the client activation message **322** includes the mobile user identifier and optionally a nonce.

5 [0048] In step **324**, the server **320** gets the keys from the SKG based on the mobile user identifier. As indicated above, the server retrieves the mobile user password and uses the server key generator to generate a server private/public key pair and client/public key using the mobile user password as an input token. Optionally, the input token for SKG could be created using a password hashed with the nonce if the client provided a nonce in the activation message, or using
10 any password transformation using parameters shared by both the client and the server.

[0049] The server **320** then sends a client activation message **328** that is signed with the server's private key and could also be encrypted with the client's public
15 key if needed. The message in step **328** preferably includes the session identifier as well as any other parameters required by client **310**.

[0050] Client **310** uses the client key generator to generate a server public key and a client public/private key pair using the mobile user password as an input
20 token. Optionally, the input token for the CKG could be created using passwords hashed with the nonce if a nonce was sent in the activation message or any password transformation using secret parameters shared by the client and the server. This is performed in step **330**.

25 [0051] In step **332** the client verifies the digital signature of the message with the server public key and optionally decrypts it with the client private key.

[0052] For any subsequent message, the client and server use their pairs of private/public keys for the record protocol to sign and encrypt messages.

30

[0053] Reference is now made to **Figure 4**. **Figure 4** shows an alternative data flow diagram.

[0054] Client **410** communicates with a server **420**. As seen in **Figure 4**, various flows are possible for communications. Client **410** in a first flow creates a client's activation message at step **422**, the message including a mobile user identifier and optionally a nonce.

5

[0055] In step **424**, the server **420** receives the client activation message and the server retrieves the mobile user password and uses a server key generator to generate the private/public key pair and the client public key using the mobile user password as an input token. Optionally, the input token for the SKG could be
10 created using a password hashed with a nonce if the client provided a nonce in the activation message, or with any password transformation using parameters shared by both the client and the server.

[0056] The server then generates a unique session identifier and creates a new
15 shared secret based on a predefined combination of the mobile user password, nonce from the activation message if any, and optionally the generated session ID. This is performed in step **428**.

[0057] Server **420** then sends a message in step **430** indicating activation
20 confirmation and includes the generated session ID signed with the server private key.

[0058] The client in step **432** uses the client key generator to generate a server
25 public key using the mobile user password and input token. Further, the client key generator could be used to generate a client public/private key pair. Again, optionally, the input token for the CKG could be created using a password hashed with a nonce if a nonce was sent in the activation message or any password transformation using parameters shared by the client and the server. If the message is encrypted, the client should use the CKG to generate a client private
30 key to decrypt the message.

[0059] The process then verifies the message in step **434** with the server public key. The client optionally decrypts the message with the client private key, and retrieves the session ID.

- 5 **[0060]** In step **436**, the client creates a shared secret identical to the server's shared secret based on the predefined combination of the mobile user password, nonce from the activation message, if any, and the generated session ID.

- 10 **[0061]** The client uses a CKG to generate a server public key and a client private public key pair based on the shared secret.

[0062] The server in step **438** uses the same information to generate a client public key and a server public private key pair based on the shared secret.

- 15 **[0063]** Next the client and the server use their pairs of public keys and private keys for the record protocol to sign and encrypt messages.

- 20 **[0064]** As will be appreciated by those skilled in the art, the benefit of the above approach is that the password-derived keys never travel over the air. The problem with keys traveling over the air is trusting the keys. Since keys are generated independently by each party, they will be trusted, so no certificates are required for public key verification.

- 25 **[0065]** As will further be appreciated by those skilled in the art, the above could be deployed on any client device. However, in one embodiment the above is deployed on wireless data devices. An enterprise or carrier can manage the CKG modules by provisioning the modules on to every device that is sold. The solution is therefore lightweight because it is easy to deploy. Further, because the modules are added to the device, nothing else needs to be done and the adding
30 of the module can be done during device provisioning.

[0066] With reference to **Figures 3 and 4**, as will be appreciated by those skilled in the art, a single key pair could be used as an option for a simplified model in which a single key pair scheme is used.

5 [0067] The above further provides for non-repudiation constrained by CKG implementation security. The algorithm parameters are known only to one party since they are set by carrier or domain and combined with the password or other credential to create the public/private key pairs.

10 [0068] Reference is now made to **Figure 5**. **Figure 5** shows a more detailed block diagram of an exemplary mobile device that can be used in association with the present method and system. The apparatus of **Figure 5** is not meant to be limiting, and is meant only as an example of the type of device that can be used.

15 [0069] **Figure 5** is a block diagram illustrating a mobile device apt to be used with preferred embodiments of the apparatus and method of the present application. Mobile device **500** is preferably a two-way wireless communication device having at least voice and data communication capabilities. Mobile device **500** preferably has the capability to communicate with other computer systems on the Internet.

20 Depending on the exact functionality provided, the wireless device may be referred to as a data messaging device, a two-way pager, a wireless e-mail device, a cellular telephone with data messaging capabilities, a wireless Internet appliance, or a data communication device, as examples.

25 [0070] Where mobile device **500** is enabled for two-way communication, it will incorporate a communication subsystem **511**, including both a receiver **512** and a transmitter **514**, as well as associated components such as one or more, preferably embedded or internal, antenna elements **516** and **518**, local oscillators (LOs) **513**, and a processing module such as a digital signal processor (DSP)
30 **520**. As will be apparent to those skilled in the field of communications, the particular design of the communication subsystem **511** will be dependent upon the communication network in which the device is intended to operate.

[0071] Network access requirements will also vary depending upon the type of network **519**. In some CDMA networks, for example, network access is associated with a subscriber or user of mobile device **500**. A CDMA mobile device may require a removable user identity module (RUIM) or a subscriber identity module (SIM) card in order to operate on a CDMA network. The SIM/RUIM interface **544** is normally similar to a card-slot into which a SIM/RUIM card can be inserted and ejected like a diskette or PCMCIA card. The SIM/RUIM card can have approximately 64K of memory and hold many key configuration **551**, and other information **553** such as identification, and subscriber related information.

[0072] When required network registration or activation procedures have been completed, mobile device **500** may send and receive communication signals over the network **519**. As illustrated in **Figure 5**, network **519** can consist of multiple base stations communicating with the mobile device. For example, in a hybrid CDMA 1x EVDO system, a CDMA base station and an EVDO base station communicate with the mobile device and the mobile device is connected to both simultaneously. The EVDO and CDMA 1x base stations use different paging slots to communicate with the mobile device.

[0073] Signals received by antenna **516** through communication network **519** are input to receiver **512**, which may perform such common receiver functions as signal amplification, frequency down conversion, filtering, channel selection and the like, and in the example system shown in **Figure 5**, analog to digital (A/D) conversion. A/D conversion of a received signal allows more complex communication functions such as demodulation and decoding to be performed in the DSP **520**. In a similar manner, signals to be transmitted are processed, including modulation and encoding for example, by DSP **520** and input to transmitter **514** for digital to analog conversion, frequency up conversion, filtering, amplification and transmission over the communication network **519** via antenna **518**. DSP **520** not only processes communication signals, but also provides for receiver and transmitter control. For example, the gains applied to

communication signals in receiver **512** and transmitter **514** may be adaptively controlled through automatic gain control algorithms implemented in DSP **520**.

[0074] Mobile device **500** preferably includes a microprocessor **538** which controls the overall operation of the device. Communication functions, including at least data and voice communications, are performed through communication subsystem **511**. Microprocessor **538** also interacts with further device subsystems such as the display **522**, flash memory **524**, random access memory (RAM) **526**, auxiliary input/output (I/O) subsystems **528**, serial port **530**, one or more keyboards or keypads **532**, speaker **534**, microphone **536**, other communication subsystem **540** such as a short-range communications subsystem and any other device subsystems generally designated as **542**. Serial port **530** could include a USB port or other port known to those in the art.

[0075] Some of the subsystems shown in **Figure 5** perform communication-related functions, whereas other subsystems may provide “resident” or on-device functions. Notably, some subsystems, such as keyboard **532** and display **522**, for example, may be used for both communication-related functions, such as entering a text message for transmission over a communication network, and device-resident functions such as a calculator or task list.

[0076] Operating system software used by the microprocessor **538** is preferably stored in a persistent store such as flash memory **524**, which may instead be a read-only memory (ROM) or similar storage element (not shown). Those skilled in the art will appreciate that the operating system, specific device applications, or parts thereof, may be temporarily loaded into a volatile memory such as RAM **526**. Received communication signals may also be stored in RAM **526**.

[0077] As shown, flash memory **524** can be segregated into different areas for both computer programs **558** and program data storage **550**, **552**, **554** and **556**. These different storage types indicate that each program can allocate a portion of flash memory **524** for their own data storage requirements. Microprocessor **538**, in addition to its operating system functions, preferably enables execution of

software applications on the mobile device. A predetermined set of applications that control basic operations, including at least data and voice communication applications for example, will normally be installed on mobile device **500** during manufacturing. Other applications could be installed subsequently or dynamically.

5

[0078] A preferred software application may be a personal information manager (PIM) application having the ability to organize and manage data items relating to the user of the mobile device such as, but not limited to, e-mail, calendar events, voice mails, appointments, and task items. Naturally, one or more memory stores
 10 would be available on the mobile device to facilitate storage of PIM data items. Such PIM application would preferably have the ability to send and receive data items, via the wireless network **519**. In a preferred embodiment, the PIM data items are seamlessly integrated, synchronized and updated, via the wireless network **519**, with the mobile device user's corresponding data items stored or
 15 associated with a host computer system. Further applications may also be loaded onto the mobile device **500** through the network **519**, an auxiliary I/O subsystem **528**, serial port **530**, short-range communications subsystem **540** or any other suitable subsystem **542**, and installed by a user in the RAM **526** or preferably a non-volatile store (not shown) for execution by the microprocessor **538**. Such
 20 flexibility in application installation increases the functionality of the device and may provide enhanced on-device functions, communication-related functions, or both. For example, secure communication applications may enable electronic commerce functions and other such financial transactions to be performed using the mobile device **500**.

25

[0079] In a data communication mode, a received signal such as a text message or web page download will be processed by the communication subsystem **511** and input to the microprocessor **538**, which preferably further processes the received signal for output to the display **522**, or alternatively to an auxiliary I/O
 30 device **528**.

[0080] A client key generator **560**, which could be equivalent to CKG **165** and CKG **265** keys to the microprocessor **538**.

[0081] A user of mobile device **500** may also compose data items such as email messages for example, using the keyboard **532**, which is preferably a complete alphanumeric keyboard or telephone-type keypad, in conjunction with the display **522** and possibly an auxiliary I/O device **528**. Such composed items may then be transmitted over a communication network through the communication subsystem **511**.

[0082] For voice communications, overall operation of mobile device **500** is similar, except that received signals would preferably be output to a speaker **534** and signals for transmission would be generated by a microphone **536**. Alternative voice or audio I/O subsystems, such as a voice message recording subsystem, may also be implemented on mobile device **500**. Although voice or audio signal output is preferably accomplished primarily through the speaker **534**, display **522** may also be used to provide an indication of the identity of a calling party, the duration of a voice call, or other voice call related information for example.

[0083] Serial port **530** in **Figure 5**, would normally be implemented in a personal digital assistant (PDA)-type mobile device for which synchronization with a user's desktop computer (not shown) may be desirable, but is an optional device component. Such a port **530** would enable a user to set preferences through an external device or software application and would extend the capabilities of mobile device **500** by providing for information or software downloads to mobile device **500** other than through a wireless communication network. The alternate download path may for example be used to load an encryption key onto the device through a direct and thus reliable and trusted connection to thereby enable secure device communication. As will be appreciated by those skilled in the art, serial port **530** can further be used to connect the mobile device to a computer to act as a modem.

[0084] Other communications subsystems **540**, such as a short-range communications subsystem, is a further optional component which may provide

for communication between mobile device **500** and different systems or devices, which need not necessarily be similar devices. For example, the subsystem **540** may include an infrared device and associated circuits and components or a Bluetooth™ communication module to provide for communication with similarly
5 enabled systems and devices.

[0085] The embodiments described herein are examples of structures, systems or methods having elements corresponding to elements of the techniques of this application. This written description may enable those skilled in the art to make
10 and use embodiments having alternative elements that likewise correspond to the elements of the techniques of this application. The intended scope of the techniques of this application thus includes other structures, systems or methods that do not differ from the techniques of this application as described herein, and further includes other structures, systems or methods with insubstantial
15 differences from the techniques of this application as described herein.

Claims:

1. A method for secure record protocol in a system with a server (110; 210) having a server key generator (125; 225) and a client device (150; 250) having a client device key generator (165; 265), comprising the steps of:
 - 5 utilizing a mobile user credential as an input to said server key generator (125;225) and said client device key generator (165; 265), said mobile user credential being known to both said server (110; 210) and said client device (150; 250);
 - utilizing said server key generator (125; 225) to generate one or two public key-private key pairs based on said mobile user credential input;
 - 10 utilizing said client device key generator (165;265) to generate one or two public key-private key pairs based on said mobile user credential input; and
 - sending a message signed with one of said private keys from the client device to the server or from the server to the client device,
 - wherein said client device key generator and said server key generator are
 - 15 adapted to provide identical private key-public key pairs for an identical input.
2. The method of claim 1, wherein the mobile user credential is a password.
3. The method of claim 1 or claim 2, wherein the input is a password hashed, using
20 a secure hash function, with a nonce.
4. The method of any one of claims 1 to 3, wherein the input is a password transformation using a parameter shared by the client device and the server.
- 25 5. The method of any one of claims 1 to 4, wherein said server key generator (125; 225) and said client device key generator (165; 265) generate only one public key-private key pair.
6. The method of any one of claims 1 to 4, wherein said server key generator (125; 225) and said client device key generator (165; 265) generate a client device public key-private key pair and a server public-key private key pair.
30
7. The method of claim 6, wherein said server key generator (125; 225) and said client device key generator (165; 265) hide the client device private key or the server
35 private key.

8. The method of any one of claims 1 to 7 wherein the sending step further encrypts the message with one of said public keys.
- 5 9. The method of any one of claims 1 to 8, wherein utilizing identical inputs, said generating step, when performed on said client device (150; 250), generates identical public-private key pairs to said generating step, when performed on said server (110;210).
- 10 10. The method of any one of claims 1 to 9, wherein said utilizing step further incorporates a session identifier to create an input.
11. The method of any one of claims 1 to 10, wherein said generating step further comprises parameters provided by a domain owner.
- 15 12. The method of claim 11, wherein the parameters provided by the domain owner are auto-generated using a private key of the domain owner.
13. The method of any one of claims 1 to 12, wherein said client device is a
20 wireless device.
14. A system for secure record protocol using a mobile user credential, comprising:
a client device (150; 250), said client device having:
25 a communications subsystem (152;252) ;
a processor (154; 254) adapted to communicate with said communications subsystem (152; 252);
a memory (156; 256) adapted to store an input created from said mobile user credential;
30 a client device key generator (165; 265), said client device key generator being provided with the input and adapted to generate one or two public key-private key pairs; and

a signing/verification module (160;260), said signing/verification module adapted to sign a message with one of said private keys generated by said client device key generator(165; 265); and

a server (110; 210), said server having:

5 a communications subsystem (112; 212) adapted to communicate with said client device communications subsystem (152; 252), said signed messages being sent from said client device to said server or from said server to said client device utilizing said communications subsystem of said client device and said communications subsystem of said server;

10 a processor (114;214) adapted to communicate with said server communications subsystem;

a memory (116; 216) adapted to store an input created from said mobile user credential;

a server key generator (125; 225), said server key generator being
15 provided with the input and adapted to generate one or two public key-private key pairs; and

a signing/verification module (120; 220), said signing/verification module adapted to sign a message with one of said private keys generated by said server key generator,

20 wherein said client device key generator and said server key generator are adapted to produce identical private key-public key pairs for an identical input.

15. The system of claim 14, wherein the mobile user credential comprises a password

25

16. The system of claim 14 or claim 15, wherein the input at the server and the input at the client device comprises a password hashed with a nonce.

17. The system of any one of claims 14 to 16, wherein the input at the server and the
30 input at the client device comprises a password transformation using a parameter shared by the client device and the server.

18. The system of any one of claims 14 to 16, wherein the client device key
35 generator (165; 265) and server key generator (125; 225) are adapted to generate an identical single public key-private key pair.

19. The system of any one of claims 14 to 17, wherein the client device key generator (165; 265) and server key generator (125; 225) are adapted to generate both a client public key-private key pair and a server public-key private key pair.
- 5 20. The system of claim 19, wherein said client device key generator (165; 265) hides the server private key and said server key generator (125; 225) hides said client device private key.
21. The system of any one of claims 14 to 20 wherein the client device
10 signing/verification module further encrypts the message with one of said public keys.
22. The system of any one of claims 14 to 21 wherein the server
15 signing/verification module further encrypts the message with one of said public keys.
23. The system of any one of claims 14 to 22, wherein said input comprises a session identifier.
- 20 24. The system of any one of claims 14 to 23, wherein client device key generator (165; 265) and said server key generator (125; 225) are adapted to utilize parameters provided by a domain owner in combination with the input.
- 25 25. The system of claim 24, wherein the parameters provided by the domain owner are auto-generated using a private key of the domain owner.
26. The system of any one of claims 14 to 25, wherein said client device is a wireless device.
- 30 27. A computer readable medium storing program code for use by a processor of a computing device or system to cause said computing device or system to perform the method of any one of claims 1 to 13.

28. The system of any one of claims 14 to 26 in which a plurality of client devices are adapted to communicate with the server.