

Process and contrivance for the coking of coal mixtures with high swelling pressure characteristics in a “non-recovery” or “heat-recovery” coke oven

[0001] The present invention concerns a process for the coking of coal with high swelling pressure characteristics in a “non-recovery” or “heat-recovery” coke oven whereby a coke oven bank composed of coke oven chambers arranged in a row is used for the cyclical coking of coal and a quantity of coal pre-heated to a specific temperature is introduced into the coke chamber to be filled at such a load height as to allow the swelling pressure arising due to coking to be released into the gas compartment over the coke cake, so that the coke oven chamber walls surrounding the coke oven chamber can be relieved of the swelling pressure arising during coking. The invention also concerns a device with which this process can be executed.

[0002] During the coking of coal, substantial pressure known as swelling pressure arises. This is exerted on the coke oven chamber walls, subjecting the coke oven chamber walls to substantial mechanical stress. Coke oven chamber walls are frequently fitted with an elaborate cross-anchoring system consisting of anchor stands, wall shields, chamber frames, bias springs and anchors. An example of a cross-anchoring system for coke oven chamber walls can be found in WO 2009141086 A1.

[0003] Swelling pressure arises during the coking of coal in the so-called plastic zone of the coke cake due to the splitting of the volatile coal components and tar, and tar seam formation arising from the meeting of plastic zones. Swelling pressure is caused by what is known as internal gas pressure, which arises in connection with the dilation and contraction of the coal. The internal gas pressure is exerted on the coke oven chamber walls via the already coked coal, as the coke first forms near the walls due to the hot coke oven chamber walls. During the coking of coal, swelling pressure can arise that is high enough to damage the coke oven chamber walls. Experience has shown that maximum swelling pressure is reached at approximately 75% of operating time, defined as the period between two loadings. As the bias springs of the cross-anchoring system serve to absorb the swelling pressures, they must be pre-stressed to a high degree, and often precisely adjusted in order to prevent damage of the coke oven chamber walls by the swelling pressure.

[0004] This entails considerable economic expense. Furthermore the coke oven chamber walls must be repaired frequently due to the influence of swelling pressure if the cross-anchoring system is improperly adjusted or has not been maintained throughout the life of an oven. Because the amount of swelling pressure depends primarily on the type of

coal or mixture of types of coal used, severe limitations are often placed on the type of coal that can be used for coking. Therefore, from the very beginning such coals cannot be used for coking that are particularly well-suited for the intended use. It is also possible to reduce the swelling pressure by introducing additives to the coal to be coked. Examples of these are coke breeze with a high content of volatile components and inert dull coal. However, introducing additives is not always desirable as they may also have an undesirable effect on the utilisation processes. Finally, the coking speed also depends on the moisture content, the content of volatile coal components, the height of the load and the load weight.

[0005] At the same time, during loading the coal that is fed in must always be levelled after loading with a mechanical levelling bar to convert the conical load into an oven load with a uniform height. This homogenises the coking process. The levelling bar is introduced into the oven laterally through levelling holes in the oven door. This entails a complex design and construction.

[0006] Thus the present task is to develop a process for the coking of coal with high swelling pressure characteristics whereby the type of coal to be used can be freely selected without the need to avoid excessive swelling pressure. The moisture content, the content of volatile coal components, the load weight, the layer height, the type of coal, the maceral group of the type of coal being used and the choice of coking conditions should play no role in coking. At the same time the design and construction of intricate parts such as levelling doors and cross anchoring should become unnecessary in order to make the coking process more economical.

[0007] The invention solves this task with a process for coking coal with high swelling pressure characteristics in a “non-recovery” or “heat-recovery” coke oven bank whereby

- a coke oven bank composed of coke oven chambers arranged in a row is used for the cyclical coking of coal,
- the coke oven chambers are loaded from a coal hopper from which the coal can be loaded into the coke oven chamber with appropriate transport equipment,
- the coal is brought to an elevated temperature of 100 to 400 °C under an inert gas, and the coal is loaded under an inert gas into the coke oven chamber,
- the pre-warmed quantity of coal is put into the coke oven chamber to be filled at a constant loading height without additional levelling so that the swelling pressure of the coking can escape into the gas compartment over the coke cake, and

- the coal is converted to coke in the designated coke oven chamber during the course of a coking cycle.

[0008] Loading the coke oven chamber with pre-heated coal, whereby the coal is initially heated to a temperature of 100 to 400 °C, allows for a situation where part of the volatile components has been outgassed already and the heating takes place in a hermetically sealed environment so that no coal is lost through combustion. Furthermore, because the pre-heated coal is filled using a means of transportation through the coke oven cover in a “heat-recovery” or “non-recovery” coke oven bank, whereby a specific load height is maintained, the swelling pressure can escape into the gas compartment over the coke cake.

[0009] At the elevated temperature of 100 °C to 400 °C the coal attains a quasi-fluid state that is characterised by fluid-like flow characteristics so that the coke oven banks can be filled in a particularly efficient and homogenous manner. This simplifies the management of the coking process and substantially improves the quality of the coke.

[0010] At the same time, the operating time necessary to coke the coal in a “heat-recovery” or “non-recovery” coke oven is substantially reduced, as a large share of the volatile coal components have already been released in an external unit even before the oven is loaded. This measure thus enhances the cost-effectiveness of the “heat-recovery” or “non-recovery” coking process.

[0011] Moreover, during loading the elaborate design and construction of the levelling door openings and the cross anchoring is unnecessary, substantially enhancing the cost-effectiveness of the process.

[0012] “Heat-recovery” or “non-recovery” coke oven banks are suitable for this process because their method of construction allows for a gas compartment over the coke cake that is intended for partial combustion of coking gas in the typical method of construction of this design. Coking ovens that are not of this design have no compartment or only a very small compartment for offgassing, so the swelling pressure cannot be immediately released. A list and explanation of examples of coke ovens in the “heat-recovery” or “non-recovery” designs are found in patent specifications US 4344820 A, US 4287024 A, US 5114542 A, GB 1555400 A or CA 2052177 C. The heating also causes the water contained in the coal to outgas. Thus the coking can begin directly after loading and heating.

[0013] Warming coal for heat recovery and in order to improve the coking process is already known. DE 4204578 C2 describes processes for drying and pre-heating the feed

coal through heat recovery from hot raw gas, which is characterised in that wet feed coal is brought by means of a counterflow into direct contact with raw gas that is cooled from an operating temperature of 700 to 900 °C to an outlet temperature of approximately 550 °C. This process serves primarily to improve the energy effectiveness of the horizontal chamber coking, whereby the sensible heat is extracted from the coke and the raw gas as far as possible, and reintroduced into the process via the coal. The coal is initially pre-dried and then pre-heated according to the state and moisture content of the coal. Thus the degree of pre-drying and pre-heating can be set within broad limits.

[0014] DE 2706026 A1 describes a process for conveying pre-warmed feed coal into coking chambers and a system for conducting the process whereby the feed coal is pneumatically loaded above the middle of the coking chambers using a pressurized, neutral carrier medium, such as nitrogen, from one or several metering storage vessels, where the carrier medium is separated from the feed coal in an outgassing distributor and then distributed through gravity into one or more pipe chutes and into the coking chambers. The temperature of the pre-warmed coal can be 100 to 280 °C, depending on the state of the art.

[0015] However, the process makes no mention of the use of “heat-recovery” or “non-recovery” coke oven banks in which coal could be loaded under inert gas at an elevated temperature. Neither does it describe how swelling pressure can be counteracted by the use of pre-heated coal. Pipe chutes are named as the exclusive transportation medium to be used. For the current invention, however, it is theoretically possible to use any means of transportation for pre-heated coal in which it can be loaded into coke oven chambers in a hermetically sealed environment.

[0016] It is important for the execution of the present invention process for the coal to reach a quasi-fluid state, depending on the type of coal, so that homogenous loading is possible. Also, the moisture content, the content of volatile coal components, the load weight, the height of the layer, the type of coal, the maceral group of the coal and the coking speed through pre-heating and homogenous loading no longer play a role.

[0017] In the process, the pre-heated coal can be produced in various ways. The coal is taken from one of the coal hoppers assigned to one of the coke oven banks in a preferred embodiment of the invention. Pre-heating can then take place, for instance, in an intermediate container. This can be in the form of a hopper, box or cone. Pipes for transporting hot solids are sufficiently known in the state of the art. In one embodiment of the invention, the coke oven chambers are loaded with the pre-heated coal from a coal hopper

through pipes under inert gas. The coal can also be advantageously supplied through pre-heating in the pipe. In this process, the heating takes place under the inert gas, whereby the pipe is equipped with devices to allow for heating the coal. Degassers or distributors can be situated at any location in the pipes. These can be equipped with shutoff devices; for instance, valves or slides are suitable for this.

[0018] The coke oven chamber can also be filled with pre-heated coal from a coal hopper via conveyer belts under inert gas. The pre-heating can take place, for instance, in an intermediate container. This can be in the form of a hopper, box, or cone. Conveyer belts used to transport hot solids are sufficiently known in the state of the art. The coal can also be pre-heated on the conveyer belt. The conveyer belt or the housing of the conveyer belt are equipped with devices, according to this embodiment of the process, that allow for the coal to be heated. In one possible embodiment of the invention, the housing is equipped with a connection for introducing an inert gas.

[0019] The pre-heated coal can also be supplied from a coal hopper or coal container in which the coal is pre-heated. To this end the coal hopper, or a container that can also be designed as an intermediate container, is equipped with a device to heat the coal. For example the coal in the coal hopper or container can be heated by heat coils through which hot mediums flow, such as steam, exhaust or heated air.

[0020] The heating coils can be of any type; for instance, pipelines or radiators could be considered. Hot transfer mediums flow through the heating coils. They can be of any type and flow through the heating coils at a high temperature. The temperature can be at any level. In an advantageous embodiment of the invention, the temperature is over 200°C.

[0021] In one embodiment of the invention, the filling of the coke oven chamber with pre-heated coal from the coal hopper or a container is effected by a coal charging car under inert gas. For this, the coal can be heated either in the coal hopper or container or in the coal charging car. For instance, the pre-heated coal can be supplied from a coal charging car under inert gas, whereby the coal is heated in the coal charging car. If the heating takes place in the coal charging car, then the coal charging car is equipped with devices for the heating of the coal. These can be located in any part of the coal charging car. The coal charging car is equipped with loading devices and emptying connections for filling the coke oven chambers. Coal charging cars for filling coke oven chambers are sufficiently known in the state of the art. An example of a coal charging car with a device for lifting covers from filling hole frames in the furnace roof of a coke oven is found in WO 2009097984 A2.

[0022] In a typical embodiment of the invention, the coke oven chamber is filled with the pre-heated coal from a coal charging car, whereby the charging car establishes a canal-like connection between a pipeline carrying coal under inert gas or a conveyer belt and the oven fill hole to be filled.

5 **[0023]** In one design of the invention, a fluidised bed is used to warm the coal. In this process, fluidising is by means of either a heated, inert gas or low-oxygen gas from a downcomer of an end oven after it has been cooled down to 400°C. Such a gas can be subsequently transferred back to the lower oven or the upper oven of the end oven. It is also possible to use heat coils within the fluid bed.

10 **[0024]** The inert gas can be nitrogen, helium or argon. The coal or coke is heated here under inert gas. This is necessary to avoid combustion of the coal during heating. Handling the coal under inert gas is only necessary if the coal is heated. In the process, handling under inert gas is understood to mean adding the coal and covering the coal with the inert gas in such a quantity as to hinder the combustion or excessive reaction of the coal with air.

15 **[0025]** The coal can be heated in any of the above-mentioned transfer or storage mediums in any way. It is therefore possible to use burners or a hot gas. The hot gas can heat the coal either directly or in an indirect heat exchange. For instance, the coal can also be heated through induction, microwave or arc heating. These types of heating are suitably known in the state of the art. Examples of this are found in patent specifications DE 2812520
20 A1, GB 1089092 A, US 4389283 A. The coal is pre-heated to a temperature of 100 to 400°C.

[0026] Loading of the coke oven chambers with the hot coal takes place in one embodiment of the invention through 1 to 4 fill holes in the coke oven cover. In the process, the coal charging car travels along the cover of the coke oven chambers and enables the coke oven chambers to be filled while covering the coal with the inert gas. Loading or
25 transporting the heated coal can be temporary or permanent. This typically occurs according to a pre-determined plan of operation.

[0027] In one embodiment of the invention, the coke oven chamber is filled with the hot coal through 1 to 4 fill holes in the coke oven chamber cover. The coke oven charging car travels along the cover of the coke oven chambers and enables the coke oven chambers to
30 be filled by establishing only a connecting pipeline between the pipeline carrying the coal and the fill holes to be filled, without an inert gas atmosphere. To this end at least two slides or other fittings are activated. The heated coal can be loaded or transported temporarily or permanently. This is typically undertaken according to a predetermined plan of operation.

[0028] In one embodiment of the invention the medium serving to heat the coal is taken from end ovens 1 to 6 of a coke oven bank near the coal tower and transferred back to an oven after it has been cooled.

[0029] The task of the invention is also solved with a device for coking coal with high swelling pressure characteristics in a “non-recovery” or “heat-recovery” coke oven bank with the use of a process according to one of the previous claims, including

- a coke oven bank or coke oven battery with a number of coke oven chambers which must be loaded through the coke oven chamber covers,
- a coal charging car that can travel along the top of the cover of a coke oven bank or battery and can fill at least one coke oven chamber,
- a coal hopper with which the coal charging car can be filled with coal, whereby
- the coal charging car can be filled, using suitable devices, with an inert gas whereby the coal charging car is equipped with coal loading connections that enable the combustion-free loading of the coke oven chambers without any air entering, and
- the coal charging car is equipped with a device to heat the coal

[0030] One embodiment of the device provides for the coal charging car to be equipped with a sealable supply container for the inert gas.

[0031] One further embodiment of the device provides for the coke oven chamber to be filled with the pre-heated coal from a coal charging car, whereby the charging car is equipped with a canal-like connection between the pipeline carrying the coal with inert gas or the conveyer belt, and the oven fill hole to be filled, and the connection between the conveyer belt and the charging car and the fill hole is detachable with at least two sealable fittings such as slides, valves, bucket conveyers, screw conveyers or other fittings.

[0032] The coal charging car is equipped with a device for heating. This can be a more simple device according to the state of the art, such as burners or feed connections for hot gas. This can also be done through induction, microwave or arc heating in the coal charging car. The coal charging car can be equipped with at least one sealable feed connection for the inert gas. The coal charging car can also be equipped with a sealable supply container for the inert gas.

[0033] The invention has the advantage of effecting the loading of coke oven chambers in a manner that avoids an increase in swelling pressure in a coke oven chamber during coking. This enables the coking process to be made more cost-effective. In addition, disadvantages are avoided that are caused by excessive moisture content and disadvantageous content of volatile components of the coal.

[0034] The advantages of the invention are:

- The operating time between two loading processes is substantially reduced, leading to an increase in equipment revenue and thus greater cost-effectiveness.
- Types of coal with high swelling pressure characteristics that cannot be used in conventional horizontal chamber ovens and are thus less expensive to acquire can be used without any danger of damage being caused.
- Design and construction complexity is reduced because the need for an expensive cross-anchoring system is obviated.
- An otherwise necessary, expensive levelling system is also rendered unnecessary.

[0035] The present invention device is explained more precisely using two figures, whereby these depict only possible embodiments of the invention. FIG. 1 shows a coke oven bank with the coal charging car for loading according to the present invention. FIG. 2 shows the coal charging car according to the present invention.

[0036] FIG. 1 shows a coke oven bank (1) consisting by way of example of a total of eight coke oven chambers (2) of the "heat-recovery" or "non-recovery" type. The coke oven chambers (2) are loaded through the filling holes (3) in the coke oven cover (4). Two of the coke oven chambers (2) are depicted in an open position after the emptying of the previous load, whereby the raised coke oven chamber door (5) is located above the coke oven chamber opening (6). The coke oven chambers (2) are loaded by the coal charging car (7), which travels along the cover (4) of the coke oven bank (1) on a guide rail (8), is positioned over the coke oven chamber to be filled (2) and loads the coke oven chamber to be filled (2) via a discharge nozzle with hot, pre-heated coal (9). The coke is heated in the coal charging car (7), which is equipped with a heating device (10). The coal charging car (7) is loaded from a coal hopper (11) situated above the level of the coal charging car. Loading takes place under an inert gas (12) that also surrounds the coal (13) in the coal hopper (11). The

coal charging car (7) can also be placed under inert gas (12), so that the coal (9) can be transported to the coke oven chamber to be filled (2) without combustion.

[0037] FIG. 2 shows a coal charging car (7) equipped with an opening for filling (14) and two heating devices (10a,10b) with which the coal (9) can be pre-heated. Underneath the coal charging car (7) there is a discharge nozzle (15) through which the hot, pre-heated coal (9) can be loaded into the coke oven chamber to be filled (2). The coal charging car (7) is equipped with a supply container for inert gas (16) so that the hot, pre-heated coal (9) can be transported without combustion. The guide wheels (17) enable the car to travel along the guide rails (8).

10 **[0038]** Reference symbol list

- 1 Coke oven bank
- 2 Coke oven chamber
- 3 Fill holes
- 4 Coke oven chamber cover
- 5 Coke oven chamber door
- 6 Coke oven chamber opening
- 7 Coal charging car
- 8 Guide rails
- 9 Hot, pre-heated coal
- 10 Upper heating device
- 10a Lower heating device
- 10b Heating device
- 11 Coal hopper
- 12 Inert gas
- 13 Coal
- 14 Opening for loading the coke car
- 15 Discharge nozzle for the coal charging car
- 16 Supply container for inert gas
- 17 Guide wheels

Patent claims

1. The process for coking coals (13) with high swelling pressure characteristics in a “non-recovery” or “heat-recovery” coke oven bank (1), whereby
 - a coke oven bank (1) composed of coke oven chambers (2) arranged in a row is used for the cyclical coking of coal (9) and
 - the coke oven chambers (2) are loaded from a coal hopper (11) from which the coal (13) can be loaded using suitable transport equipment into the coke oven chamber (2),

is characterised in that

 - the coal (9) is brought to an elevated temperature of 100 to 400°C under an inert gas (12) and the quantity of coal (9) is loaded under inert gas (12) into the coke oven chamber to be filled (2),
 - the pre-heated coal (9), at a constant fill height without additional levelling, is introduced into the coke oven chamber to be filled (2) in such a way that the swelling pressure of the coking can escape into the gas compartment over the coke cake and
 - the coal (9) can be converted to coke in the designated coke oven chamber (2) during a coking cycle.
2. The process according to claim 1 is **characterised in that** the loading of the coke oven chamber (2) takes place with the pre-heated coal (9) from a coal hopper (11) via pipelines under inert gas (12).
3. The process according to claim 2 is **characterised in that** the pre-heated coal (9) is supplied through pre-heating in the pipeline.
4. The process according to claim 1 is **characterised in that** the loading of the coke oven chamber (2) with the pre-heated coal (9) takes place from a coal hopper (11) via conveyer belts under inert gas (12).
5. The process according to claim 4 is **characterised in that** the pre-heated coal (9) is supplied through pre-heating on the conveyor belt.

6. The process according to claim 1 is **characterised in that** the pre-heated coal (9) is supplied through pre-heating in a fluidised bed.
7. The process according to claim 1 is **characterised in that** the pre-heated coal (9) is supplied from a coal container (11) in which the coal (13) is pre-heated.
- 5 8. The process according to claim 7 is **characterised in that** the coal (13) is heated in the coal container (11) via heat coils through which hot mediums flow such as steam, exhaust, raw coke oven gas, heated air or mixtures of these mediums.
- 10 9. The process according to one of the claims 1 to 8 is **characterised in that** the medium serving to heat the coal is taken from ovens 1 to 6 near the coal tower of a coke oven bank (1) and after it has been cooled is transferred back to an oven (2).
- 15 10. The process according to claim 1 is **characterised in that** the coke oven chamber (2) is filled with the pre-heated coal (9) from a coal charging car (11) under inert gas (12).
- 20 11. The process according to one of the previous claims 1 to 10 **is characterised in that** the coke oven chamber (2) is loaded with the pre-heated coal (9) from a coal charging car (7) whereby the charging car (7) establishes a canal-like connection (14,15) between a pipeline carrying coal (13) under inert gas (12) or a conveyer belt and the oven fill hole to be filled (3).
12. The process according to claim 10 **is characterised in that** the pre-heated coal (9) from a coal charging car (7) is supplied under inert gas (12) whereby the coal (13) is heated in the coal charging car (7).
- 25 13. The process according to one of the claims 1 to 11 **is characterised in that** the inert gas (12) is nitrogen, helium or argon.
14. The process according to one of the claims 1 to 11 **is characterised in that** the coal (13) is heated by induction, microwave or arc heating.
15. The process according to one of the claims 1 to 14 **is characterised in that** the coal (13) is heated to a temperature of 100 to 400 °C.

16. The process according to one of the claims 1 to 15 **is characterised in that** the coke oven chambers (2) are filled with the hot coal (9) via 1 to 4 fill holes (3) in the coke oven cover (4).
17. Device for coking coal (13) with high swelling pressure characteristics in a “non-recovery” or “heat-recovery” coke oven bank (1) using a process according to one of the previous claims, including
- a coke oven bank (1) or coke oven battery (1) with a number of coke oven chambers (2) that are to be loaded through the coke oven chamber cover (4),
 - a coal charging car (7) that can travel along the cover (4) of the coke oven bank (1) or battery (1) and with which at least one coke oven chamber (2) can be loaded,
 - a coal hopper (11) from which the coal charging car (7) can be loaded with coal (13),
- characterised in that**
- the coal charging car (7) can be loaded via suitable devices (16) with an inert gas (12), whereby the coal charging car (7) is equipped with coal feed connections (16) that allow for loading the coke oven chambers (2) without combustion in a hermetically sealed environment, and
 - the coal charging car (7) is equipped with a device for heating coal (9).
18. The device according to claim 17 **is characterised in that** the coal charging car (7) is equipped with a sealable supply container (16) for the inert gas (12).
19. The device according to claim 17 **is characterised in that** the coke oven chamber (2) is loaded with the pre-heated coal (9) from a coal charging car (7) whereby the charging car (7) establishes a canal-like connection (14,15) between a pipeline carrying coal (13) under inert gas (12) or the conveyer belt and the oven fill hole to be filled (3) and the connection (14,15) between the conveyer belt and charging car (7) and fill hole (3) can be detached via at least two sealable fittings.