

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
9 October 2003 (09.10.2003)

PCT

(10) International Publication Number
WO 03/082450 A1

(51) International Patent Classification⁷: **B01D 65/08**

(21) International Application Number: PCT/US03/01209

(22) International Filing Date: 15 January 2003 (15.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/109,260 28 March 2002 (28.03.2002) US

(71) Applicant: **ONDEO NALCO COMPANY** [US/US]; On-
deo Nalco Center, Naperville, IL 60563-1198 (US).

(72) Inventors: **ZEIHER, E., H., Kelle**; 213 Benton Avenue,
Naperville, IL 60540 (US). **HO, Bosco, P.**; 46 Rossini
Court, Wheaton, IL 60187 (US). **HOOTS, John, E.**; 1430
Lancaster Avenue, Saint Charles, IL 60174 (US).

(74) Agent: **KEEFER, Timothy, J.**; Wildman, Harrold, Allen
& Dixon, 225 Wacker Drive, Suite 2800, Chicago, IL
60606 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC,
VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF MONITORING MEMBRANE SEPARATION PROCESSES

(57) Abstract: Methods and systems for monitoring and/or controlling membrane separation systems or processes are provided. The present invention utilizes measurable amounts of inert fluorescent tracers and tagged fluorescent agents added to a feed stream to evaluate and/or control one or more parameters specific to membrane separation such that performance thereof can be optimized. The methods and systems of the present invention can be utilized in a variety of different industrial applications including raw water processing and waste water processing.



WO 03/082450 A1