

SPECIFICATION

TITLE OF THE INVENTION

TRANSMITTER AND RECEIVER

5

TECHNICAL FIELD

The present invention relates to a technical field of radio communications. More particularly, the present invention relates to a transmission apparatus and a reception apparatus used in a downlink.

10

BACKGROUND ART

In a next generation radio access scheme for which research and development are currently being conducted, it is required to perform communication more efficiently compared with conventional schemes. In the downlink, speed-up and increase of capacity for communication are especially required. Thus, radio access schemes of a multicarrier scheme such as orthogonal frequency division multiplexing (OFDM) are highly expected. On the other hand, the uplink is different from the downlink in that speed-up and large capacity are not so strongly required for the uplink as the downlink and that transmission power of a mobile station is considerably limited compared with that of the base station and the like. Thus, the multicarrier scheme in which there is a fear that peak to average power ratio (PAPR) becomes large is not a proper scheme for the uplink. Rather, from the viewpoint of suppressing PAPR and increasing coverage of a cell, it is desirable to adopt a single carrier scheme for the uplink.

15

20

25

30

By the way, there are data channels, control channels and pilot channels and the like as channels to be transmitted on the uplink, and the

channels include various types of channels having different functions. For example, as to the pilot channels, in addition to a pilot channel for channel compensation for assigned radio resources, there is
5 a pilot channel for channel compensation for unassigned radio resources. In addition, the control channel may include information such as transmission confirmation information (ACK/NACK) of a previously received downlink data channel and the
10 like in addition to information (for example, information indicating a modulation scheme and a channel coding rate and the like) used for demodulating an uplink data channel. For example, the patent document 1 describes types and properties
15 of the uplink channels.
[Non-patent document 1]3GPP, TR25.814, "Physical Layer Aspects for Evolved UTRA"

DISCLOSURE OF THE INVENTION

20 PROBLEM TO BE SOLVED BY THE INVENTION

However, a proper uplink frame considering properties of the above-mentioned various uplink channels has not yet been established. In addition, in the next generation radio access scheme, wide
25 range of system frequency bands are prepared and it is assumed that mobile stations perform communications using the whole or a part of the bands. However, an uplink frame suitable for use in various wide and narrow bands has not yet been
30 established.

The present invention is contrived for addressing at least one of the problems, and the object is to provide a transmission apparatus and a reception apparatus for realizing a proper uplink
35 frame for transmitting various uplink channels.

MEANS FOR SOLVING THE PROBLEM

In the present invention, a transmission
5 apparatus used in a mobile communication system
adopting a single carrier scheme in an uplink is
used. The transmission apparatus includes:
multiplexing means configured to multiplex a pilot
channel, a control channel, and a data channel; and
10 transmission means configured to transmit a
transmission symbol including at least the pilot
channel and the control channel using the uplink.
The pilot channel includes a first pilot channel
used for a reception apparatus to measure channel
15 state of the uplink and a second pilot channel for
compensating for a channel transmitted by the uplink.
The data channel is transmitted using one or more
resource blocks. The first pilot channel is
transmitted using a frequency band over a plurality
20 of resource blocks. The second pilot channel is
transmitted by a resource block assigned to the
transmission apparatus. Control channels of the
transmission apparatus and the apparatus other than
the transmission apparatus are orthogonalized with
25 each other by a frequency division multiplexing
(FDM) scheme.

EFFECT OF THE INVENTION

According to the present invention, a
30 proper uplink frame for transmitting various uplink
channels can be realized.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig.1 is a schematic block diagram of a
35 transmitter according to an embodiment of the
present invention;

Fig.2 is a schematic block diagram of a

receiver according to an embodiment of the present invention;

Fig.3 shows a detailed diagram of the shared control channel generation unit;

5 Fig.4 is a diagram showing an example of bands used in a system;

Fig.5A is a diagram showing a manner in which information of a user A and information of a user B are multiplexed by the distributed FDM;

10 Fig.5B is a diagram showing a manner in which information of a user A and information of a user B are multiplexed by CDM and the distributed FDM;

15 Fig.5C is a diagram showing a manner in which information of a user A and information of a user B are multiplexed by the localized FDM;

Fig.6A is a diagram showing a mapping example of a pilot channel, a control channel, and a data channel;

20 Fig.6B is a diagram showing a mapping example of a pilot channel, a control channel, and a data channel;

Fig.7 is a diagram showing a mapping example of a pilot channel, a control channel, and a data channel;

25 Fig.8 is a diagram showing a mapping example of a pilot channel, a control channel, and a data channel; and

30 Fig.9 is a diagram showing a mapping example of a pilot channel, a control channel, and a data channel.

Description of reference signs

- 231 pilot channel generation unit
- 35 233 shared control channel generation unit
- 235 shared data channel generation unit
- 236, 241 discrete Fourier transform unit

- 237, 242 mapping unit
- 238, 243 inverse fast Fourier transform unit
- 244 demultiplexing unit
- 251-253 switch
- 5 255-258 modulation and coding unit
- 259 multiplexing unit

PREFERRED EMBODIMENTS FOR CARRYING OUT THE INVENTION

According to an embodiment of the present
10 invention, a first pilot channel used for a
reception apparatus to measure channel state of the
uplink is transmitted by a wide band, and a second
pilot channel for compensating for a channel
transmitted by the uplink is transmitted by a
15 resource block assigned to the user apparatus. Thus,
quality measurement for each resource block can be
properly performed, and channel compensation and the
like for assigned resource blocks can be also
properly performed.

20 In addition to obtaining frequency
diversity effect, in view of obtaining orthogonality
easily and with reliability, control channels of the
transmission apparatus and the apparatus other than
the transmission apparatus may be orthogonalized with
25 each other by a distributed FDM scheme.

From the viewpoint of transmitting a
control channel by a resource block in a good
channel state, it is desirable that the control
channel of the transmission apparatus is also
30 transmitted in a resource block assigned for data
channel of the transmission apparatus.

From the viewpoint of especially expecting
frequency diversity effect, the control channel of
the transmission apparatus may be transmitted using
35 not only the resource block for the data channel but
also a wide band equal to or greater than the
resource block assigned for the data channel of the

transmission apparatus.

From the viewpoint of improving throughput considering superiority and inferiority of channel state of each user, the control channel of the
5 transmission apparatus may be transmitted using a frequency band of one or several number of resource blocks.

Data channels of the transmission apparatus and the apparatus other than the
10 transmission apparatus may be orthogonalized with each other by the FDM scheme, and pilot channels of the transmission apparatus and the apparatus other than the transmission apparatus may be orthogonalized with each other by the CDM scheme.

15 [Embodiment 1]

Before describing the apparatus configuration and the operation according to an embodiment of the present invention, it can be considered meaningful to explain the outline of
20 various types of channels transmitted on the uplink. Uplink channels are broadly divided into (A) Contention-based channels, (B) Contention non-permitted channels and (C) Pilot channels. The contention-based channel is a channel for which
25 scheduling is not required in a base station before transmission, and the contention non-permitted channel is a channel (scheduled channel) for which scheduling is required in a base station before transmission. The contention-based channel includes
30 one or more of (A1) High speed access channel, (A2) Reservation channel and (A3) Uplink synchronization channel. The contention non-permitted channel includes one or more of (B1) uplink shared data channel and (B2) uplink shared control channel.

35 (A) [Contention-based channel]

The contention-based channel to be transmitted from the mobile station without

scheduling in the base station can be transmitted at any time by a mobile station (more generally, user apparatus (UE : user equipment) that includes a fixed station). It is desirable that the
5 contention-based channel is transmitted over a wide band. By doing that, transmission time can be decreased. In addition, since the band is wide, frequency diversity effect can be obtained. Thus, even though signal quality deteriorates very much in
10 a part of frequencies, power amplification (power ramping) and the like for compensating for the deterioration is not essential. Although contention may occur between users for the contention-based channel, high speed communication is available
15 easily by the channel. Although time division multiplexing scheme (TDM) is used in the same way as the current UTRA, frequency division multiplexing and/or code division multiplexing (CDM) is performed in the present embodiment from the viewpoint of
20 reducing contention with other users as much as possible. However, when contention against other user occurs, these users may transmit the contention-based channel again as necessary.

(A1) Fast access channel

25 The fast access channel may include a control message of a small data size, may include traffic data of a small data size, or may include both of them. One reason for limiting the data size to be small is for reducing transmission delay. For
30 example, the control message may include information on layer 3 handover, for example. The traffic data of the small size may include an e-mail of a small information amount, a command of a game and the like. Since the user apparatus can transmit the fast
35 access channel to the base station without any prior reservation, process time required for transmission can be small. The fast access channel is

transmitted by one or more frequency chunks assigned beforehand. Which chunk is to be used in a plurality of frequency chunks may be reported from the base station to the user apparatus by a
5 broadcast channel of a downlink. The content of the report may indicate that only a particular frequency chunk can be used or may indicate any one (or any number) of a plurality of particular frequency chunks can be used. The latter one is advantageous
10 in that probability for contention between users is less than that of the former one.

(A2) Reservation channel

The reservation channel includes information for requesting scheduling of a
15 contention non-permitted channel. The information may include identification information for identifying a user apparatus, traffic data type (voice, image, and the like), data size, required quality information (QoS and the like), and
20 transmission power of the user apparatus and the like. The reservation channel is also transmitted by a frequency chunk assigned beforehand. Which chunk is to be used in a plurality of frequency chunks may be reported from the base station to the
25 user apparatus by a broadcast channel of a downlink.

(A3) Uplink Synchronization Channel

In the present embodiment, signal transmission of an uplink is performed using a single carrier scheme, and equalization is performed
30 for suppressing multipath interference. For performing effective equalization, it is desirable to maintain synchronization such that reception timing for reception from various users fall within a period of a predetermined guard interval. For
35 maintaining the synchronization, uplink synchronization channel is used.

By the way, maintaining synchronization

can be also realized by the after-mentioned pilot channel. Therefore, it is not essential to prepare both of the synchronization channel and the pilot channel.

5 (B) [Contention non-permitted channel]

The contention non-permitted channel is transmitted from the user apparatus according to scheduling performed in the base station.

(B1) Uplink Shared Data Channel

10 The uplink shared data channel includes both or one of traffic data and a control message of layer 3. The control message may include information on handover, information necessary for retransmission control and the like. The uplink
15 shared data channel is assigned one or more resource blocks (or chunks) according to scheduling in time domain or both of time and frequency domains. In this case, resource assignment is scheduled in the base station such that a user related to a better
20 transmission route (channel) in the time domain or in both of the time and frequency domains can transmit packet in priority. The number of resource blocks to be assigned is determined depending on a data rate and a data size and the like to be
25 transmitted by the user apparatus. When there are a plurality of users requesting only a relatively low data rate, one resource block may be shared by a plurality of users. However, when a traffic size of a user exceeds a predetermined size, one user may
30 use the whole of the resource block. In addition, one user may use a plurality of resource blocks. When one resource block is shared by a plurality of users, multiplexing in some manner is performed such that channels of a plurality of users become
35 orthogonal in the resource block. For example, localized FDM or distributed FDM may be performed in the resource block.

(B2) Uplink Shared Control Channel

Uplink shared control channel transmits a physical control message and a layer 2 control message (FFS). As to the uplink shared data channel, resource assignment is scheduled in the base station such that a user related to a better transmission route (channel) can transmit a packet in priority. However, as to the uplink shared control channel, scheduling depending on superiority or inferiority of channel state is not essential (however, some link adaptation may be performed for the shared control channel). The base station assigns resource blocks to each user apparatus to perform scheduling to avoid contention of shared control channels. As to the uplink shared control channel, the base station performs scheduling depending on the number of users. In order to maintain packet error rate to be low, it is desirable to perform transmission power control with high precision. In addition, it is desirable to obtain frequency diversity effect by transmitting the uplink shared control channel over a wide range of frequencies so as to increase quality of reception packets.

More particularly, the uplink shared control channel includes one or more of:

- (1) control information related to a scheduled uplink shared data channel;
- (2) control information related to a scheduled downlink shared data channel;
- (3) control information for changing content of scheduling of the uplink shared data channel; and
- (4) control information for performing scheduling of a downlink shared data channel.

In these types of control information, (1) includes control information essential for demodulating the uplink shared data channel, and is

essential control information that should associated with the uplink shared data channel. On the other hand, as to (2) and (4), it is not essential that they are associated with the uplink shared data
5 channel, and they are control information (control information different from the essential control information) that are not necessarily associated with the uplink shared data channel. According to such classification method, the control information
10 (3) related to change of scheduling content may be included in the essential control information, or may be included in control information different from the essential control information.

(1) The control information (essential
15 control information) related to scheduled uplink shared data channel is transmitted being associated with an uplink shared data channel only when the uplink shared data channel is transmitted. This control information is also called an associated
20 control channel, and may include information necessary for demodulating shared data channel (modulation scheme, channel coding rate and the like), transmission block size, information related to retransmission control, and the like, and may be
25 represented with information amount of about 14 bits, for example. For example, the retransmission control information may include information indicating whether a packet transmitted by the uplink shared data channel is a retransmission
30 packet or a new packet, information indicating use method of the retransmission packet, and the like. For example, data of the retransmission packet is the same as data of a previously transmitted packet (initial transmission data, for example) in a first
35 use method, and data of the retransmission packet may be different from data of a previously transmitted packet in a second use method. In the

latter case, packet combining can be performed with redundancy information of error correcting coding.

(2) The control information associated with the scheduled downlink shared data channel is transmitted to the base station only when a downlink shared data channel is transmitted from the base station and the downlink shared data channel is received by the user apparatus. This control information represents transmission confirmation information, that is, whether the packet is properly received on the downlink (ACK/NACK), and it can be represented by 1 bit in a simplest case.

(3) The control information for changing content of scheduling of the uplink shared data channel is transmitted for reporting a buffer size and/or transmission power of the user apparatus to the base station. This control information may be transmitted periodically or irregularly. For example, it may be transmitted from the user apparatus at a time when the buffer size and/or the transmission power change. The base station may change the scheduling content according to such a status change of the user apparatus. The status of the buffer size and the transmission power may be represented using an information amount of about 10 bits, for example.

(4) Control information for performing scheduling for the downlink shared data channel is transmitted for reporting channel quality information (CQI: channel quality indicator) of the downlink to the base station. The CQI may be reception SIR measured by the user apparatus, for example. This information may be transmitted periodically or irregularly. For example, this information may be reported to the base station when the channel quality changes. This control information may be represented using an information

amount of 5 bits, for example.

(C) [Pilot channel]

The pilot channel is a signal having a pattern that is known beforehand in the transmission side and in the reception side, and it can also be referred to as a reference signal, a known signal, a training signal and the like.

The pilot channel can be transmitted from the user apparatus using the time division multiplexing (TDM), the frequency division multiplexing (FDM), code division multiplexing (CDM), or a combination of these. However, from the viewpoint of decreasing peak-to-average power ratio (PAPR), it is desirable to use a TDM scheme. By orthogonalizing a pilot channel and a data channel using the TDM scheme, the pilot channel can be correctly separated in the reception side, so that it contributes to improvement of channel estimation accuracy.

The pilot channel includes a first pilot channel for CQI measurement for every resource block that has a chance to be assigned to the user apparatus in the future, and includes a second pilot channel for channel compensation of a channel transmitted by a resource block that is currently assigned to the user apparatus. As mentioned later, the first pilot channel is transmitted by a wide band including all resource blocks and the second pilot channel is transmitted only by a particular resource block assigned to the user apparatus.

Fig.1 is a schematic block diagram of a transmitter according to an embodiment of the present invention. The transmitter shown in the figure is typically provided in a user apparatus. Fig.1 shows a pilot channel generation unit 231, a shared control channel generation unit 233, a shared data channel generation unit 234, a multiplexing

unit 235, a discrete Fourier transform unit (DFT) 236, a mapping unit 237 and an inverse fast Fourier transform unit 238.

The pilot channel generation unit 231
5 generates a pilot channel used in the uplink. The pilot channel includes the above-mentioned first and the second pilot channels at least.

The shared control channel generation unit
233 generates a shared control channel that may
10 include various control information. The shared control channel generation unit 233 is described with reference to Fig.3 later.

The shared data channel generation unit
234 generates a shared data channel transmitted by
15 the uplink.

The multiplexing unit 235 multiplexes and outputs one or more channels. It is not essential to multiplex all of the channels shown in the figure, and one or more channels are multiplexed as
20 necessary. In the example shown in the figure, processing of time division multiplexing is performed by the multiplexing unit 235, and processing of assuagement to frequency components is performed by the mapping unit 237. Since scheduling
25 for the time division multiplexed signal is performed based on an instruction by the base station, the signal is classified to the contention non-permitted channel.

Actually, a contention-based channel is
30 also generated and is multiplexed and transmitted as necessary. But, for the sake of simplicity of explanation, this is not shown.

The discrete Fourier transform unit (DFT) 236 performs Fourier transform on a signal (signal
35 after being multiplexed in the example shown in the figure) input to the unit. In this stage of the signal processing, since the signal is discrete

digital values, discrete Fourier transform is performed. By doing that, a sequence of signals arranged in order of time is represented in the frequency domain.

5 The mapping unit 237 maps each signal component after Fourier transform to a predetermined subcarrier on the frequency domain. The frequency division multiplexing (FDM) scheme in this case may be a localized FDM scheme for assigning one
10 continuous narrow band to one user or may be a distributed FDMA scheme for giving a spectrum in which a plurality of frequency components are arranged by being distributed at predetermined frequency intervals. The predetermined frequency
15 intervals are regular intervals generally, but the predetermined frequency intervals may be irregular intervals. The mapping unit 237 performs mapping on the frequency axis by the localized FDM or by the distributed FDM.

20 The inverse fast Fourier transform unit 238 performs inverse fast Fourier transform on the signal components after mapping so as to output a sequence of signals arranged in order of time.

By the way, the distributed FDM may be
25 realized by Variable Spreading and Chip Repetition Factors - CDM (VSCRF-CDM) scheme and the like.

Fig.2 shows a schematic block diagram of a receiver according to an embodiment of the present invention. The receiver shown in the figure is
30 provided in a base station typically. Fig.2 shows a discrete Fourier transform unit (DFT) 241, a mapping unit 242, an inverse fast Fourier transform unit 243 and a multiplexing unit 244.

The discrete Fourier transform unit (DFT)
35 241 performs Fourier transform on a signal (reception signal in the example shown in the figure) input to the unit. Accordingly, a sequence

of signals arranged in order of time can be represented in the frequency domain.

The mapping unit 242 extracts predetermined subcarrier components from signals after Fourier transform. Accordingly, signals that are multiplexed by the localized FDM or the distributed FDM are separated, for example.

The inverse fast Fourier transform unit 242 performs inverse fast Fourier transform on signal components after being separated to output a sequence of signals arranged in order of time.

The demultiplexing unit 244 separates one or more channels to output them. In the example shown in the figure, signals mapped to the frequency components are restored to signals before mapping by the demapping unit 242, and the separation of the time multiplexed signal is performed by the demultiplexing unit 244.

One or more channels generated in the generation unit of each channel are time-multiplexed (properly switched) by the multiplexing unit 235, and the multiplexed signal is input to the DFT 236 so that the signal is transformed to a signal in the frequency domain. The signal after transform is properly mapped to the frequency component by the mapping unit 237, and input to the IFFT 238 so as to be converted to time series signals. After that, the signal is transmitted by radio via process elements such as the RF unit 14 shown in Fig.1. This signal is received by the receiver shown in Fig.2. The reception signal is input to the DFT 241, and is transformed into a signal in the frequency domain. The transformed signal is a signal mapped to the frequency component, and separated by the demapping unit 242 to a signal before mapping. The separated signal is transformed to time series signals, and the time-multiplexed signal sequence is

properly demultiplexed by the demultiplexing unit 244, and further demodulation process and the like is performed by process elements not shown in the figure.

5 Fig.3 shows a detailed diagram of the shared control channel generation unit 233. Fig.3 shows switches 251, 252 and 253, modulation and coding units 255, 256, 257 and 258, and a multiplexing unit 259. Each switch provides each
10 channel that is input to one end (left side of the figure) to another end according to an instruction signal (not shown in the figure) on the shared control channel. The content of the instruction signal determines how to configure the shared
15 control channel, that is, which control information is included in the shared control channel. In the example shown in the figure, the figure shows (1) essential control information, (2) transmission confirmation information of downlink channel
20 (information indicating acknowledgement (ACK) and negative acknowledgement (NACK)), (3) information for changing content of scheduling and (4) channel state information (CQI) indicating reception quality of downlink pilot channel.

25 Each of the modulation and coding unit performs data modulation on a channel input to the unit using an instructed modulation scheme, and performs channel coding using an instructed coding scheme. The modulation scheme and the coding scheme
30 used for each channel may be different or same schemes may be used for more than one channel. The modulation scheme or the coding scheme may be fixedly set so as to be unchanged.

35 The multiplexing unit 259 multiplexes each channel to generate and output the shared control channel.

 In transmission of the shared control

channel in the conventional technique, the modulation scheme and the coding scheme are fixed, and it is intended to obtain required quality by controlling transmission power control. However, in
5 view of increasing quality of channel and effective use of resources, it is desirable to perform further link adaptation on transmission of the shared control channel. As a method for performing link adaptation, there are adaptive modulation and coding
10 (AMC), and transmission power control (TPC).

Fig.4 shows frequency bands used in the communication system. The frequency band provided to the system (to be also referred to as whole frequency band or system band) includes a plurality
15 of system frequency blocks, so that the user apparatus can perform communication using one or more of resource blocks included in the system frequency blocks. The resource block is also called a chunk or a frequency chunk. In general, one chunk
20 may include one or more carriers (to be also referred to as a subcarrier). But, in an embodiment of the present invention, a single carrier scheme is adopted so that one chunk includes only one carrier.

In the example shown in Fig.4, the system
25 band is 10 MHz, the system frequency block is 5 MHz, and the system band includes two system frequency blocks. For the sake of simplicity of drawing, the system frequency band 2 is not shown. The resource block is 1.25 MHz, and one system frequency block
30 includes four resource blocks. Which can be used in the two system frequency blocks by the user apparatus is determined by the base station based on a bandwidth by which the user apparatus can perform communication and a number of users performing
35 communication in the system. The bandwidth of the system frequency block is designed as a band by which every user apparatus that may perform

communication in the system can perform communication. In other words, the bandwidth of the system frequency block is determined as a maximum transmission bandwidth of a user apparatus of a
5 minimum grade that can be assumed. Therefore, a user apparatus that can only perform communication using the band of 5 MHz is assigned only one of the system frequency blocks, but, a user apparatus that
10 be assigned a band such that the user apparatus can use both of the system frequency blocks. In the present embodiment, although a subframe may be called a transmission time interval (TTI) such as 0.5ms, for example, any proper interval may be used.
15 These value examples are merely an example, and any proper values may be used.

The user apparatus transmits an uplink pilot channel to the base station. The base station determines (performs scheduling) one or more
20 resource blocks to be used for the user apparatus to transmit the shared data channel based on the reception quality of the uplink pilot channel. The content of the scheduling (scheduling information) is reported to the user apparatus using an downlink
25 shared control channel or other channel. The user apparatus transmits an uplink shared data channel using an assigned resource block. In this case, the shared control channel (shared control channel including essential control information) associated
30 with the uplink shared data channel is transmitted using the same resource block. As mentioned above, the uplink shared control channel may include control information other than the essential control information.

35 Resource blocks assigned to a user may change as time advances. The resource blocks assigned to the user may comply with a frequency

hopping pattern. The content of the hopping pattern may be known before start of communication between the base station and the user apparatus, and may be reported to the user apparatus from the base station
5 as necessary. From the viewpoint for maintaining average signal quality of the uplink channel, it is desirable to use not only a particular resource block but also various resource blocks.

Figs.5A-5C show detailed concrete examples
10 how information of a user A and a user B are multiplexed in a subframe. In the example shown in Fig.5A, pilot channels and data channels are time-multiplexed. Information of the user A and the user B are multiplexed using the distributed FDM. In the
15 example of Fig.5B, pilot channels and data channels are time-multiplexed and the data channels of the user A and the user B are multiplexed using the distributed FDM similarly to Fig.5A, but the pilot channels of the user A and the user B are
20 multiplexed by CDM. In the example of Fig.5C, pilot channels and the data channels are time-multiplexed, and the data channels of the user A and the user B are multiplexed by the localized FDM.

Fig.6A shows a mapping example of
25 information of each user according to an embodiment of the present invention. Although the range shown in the figure is the whole frequency band and one subframe, the range in the frequency axis direction may be within a range of one system frequency block.
30 For the sake of description, a period in a subframe is divided into first - fourth time slots in order of elapse of time. In the first time slot, first pilot channels from all users are multiplexed and transmitted. The all users include all of users
35 that may transmit some channels in the future in addition to users transmitting the uplink data channel and users transmitting the uplink control

channel. As mentioned above, the first pilot
channel is a pilot channel for measuring CQI for all
resource blocks having a chance to be assigned to
the user apparatus in the future. Multiplexing of
5 the first pilot channels for all users may be
performed by FDM, CDM or both of them.

Control channels are mapped to the second
time slot. Control channels of each user are
orthogonalized with each other by the distributed
10 FDM. As mentioned above, as information included in
the shared control channel, there are essential
control information essential for demodulating the
shared data channel and control information (control
information other than the essential control
15 information) other than that. In the example shown
in the figure, users B, C and D transmit control
channels including control information other than
essential control information. Like the first pilot
channel, the users B, C and D distribute the control
20 channels over the whole frequency band (or the whole
of the system frequency block) to transmit them to
the base station. It is assumed that the users B, C
and D do not transmit a data channel in any resource
block in this subframe. The user A is assigned one
25 resource block, and the user A transmits a data
channel in the third time slot using the resource
block. A control channel (including essential
control information and control information other
than that) of the user A is transmitted using
30 frequencies in the resource block assigned to the
user A. The control channel of the user A and
control channels of other users are orthogonalized
with each other using the distributed FDM.

In the fourth time slot, the second pilot
35 channel is mapped. As mentioned above, the second
pilot channel is a pilot channel for channel
compensation for a channel to be transmitted by a

resource block that is currently assigned to the user apparatus. Also in this fourth time slot, first pilot channels transmitted over wide band for CQI measurement may be multiplexed and transmitted
5 by a plurality of users. Also in this case, it is possible to perform channel compensation for a channel transmitted using the resource block currently assigned to the user apparatus by using a part of the first pilot channel transmitted over the
10 wide band.

By the way, for the sake of simplicity of the drawing, although any data channel of users other than the user A is not shown, data channels and the like of some sort of users (other than the
15 users B, C and D) are mapped to resource blocks other than the resource block assigned to the user A in actuality.

As to an uplink channel received from the user A, the base station estimates the channel state
20 of the resource block based on the second pilot channel, and determines compensation content (phase rotation amount and power and the like) to be performed on the control channel and the data channel so as to perform the compensation. In
25 addition, it is determined which resource block becomes high quality for the user A in later subframes based on the first pilot channel. The base station performs retransmission control and the like based on uplink channels (control information
30 other than the essential control information) received from the users B, C and D. In addition, when resource assignment request of an uplink has been received, the base station determines which resource block becomes high quality for the user B,
35 C or D based on the received first pilot channel.

From the viewpoint that the base station determines superiority or inferiority of the channel

state of each user for each resource block, it is desirable that the first pilot channel is transmitted using a wide band. From the viewpoint of maintaining minimum reception quality in the base station by increasing frequency diversity effect, it is desirable that control channels of the users B, C and D for which any particular resource block is not assigned are distributed to a wide band like the example shown in the figure. From the viewpoint of transmitting a control channel in a good channel state as much as possible, it is desirable that the control channel of the user A to which a particular resource block is assigned is transmitted by the assigned resource block as the example shown in the figure. In this case, the second pilot channel transmitted by the assigned resource block can be also used for demodulation of the control channel of the user A.

Fig.6B shows a mapping example of information of each user according to an embodiment of the present invention. Expedient time slots are divided to five that are first to fifth slots. The first, second, fourth and fifth time slots are the same as the first to fourth time slots of Fig.6A. However, in Fig.6B, a control channel that includes control information other than the essential control information of user A is transmitted in the third time slot (before the data channel of the user A is transmitted). In the example shown in the figure, in control channels of the user A, the essential control information is transmitted by the second time slot, and control information other than the essential control information is transmitted by the third time slot. Such a scheme is advantageous when information amount of control information other than the essential control information is large (for example, when control information other than the

essential control information is large to a degree in which it is difficult to transmit using the scheme shown in Fig.6A).

Fig.7 shows a mapping example of
5 information of each user according to an embodiment of the present invention. Generally, although this example is similar to the example shown in Fig.6A, this example is deferent in that each of the control
10 channels (including only control information other than essential control information) transmitted by the users B, C and D falls within a range of a resource block instead of being distributed over the whole frequency band. When a channel state on a
15 particular resource block is relatively good, it is desirable that the control channel is transmitted by a particular resource block as shown in Fig.7.

Fig.8 shows a mapping example of
information of each user according to an embodiment of the present invention. Generally, although this
20 example is similar to the example shown in Fig.6A, this example is deferent in that not only the control channels (including only control information other than essential control information) transmitted by the users B, C and D but also the
25 control channel of the user A are distributed over the whole frequency band.

Fig.9 shows a mapping example of
information of each user according to an embodiment of the present invention. Although only the data
30 channel of user A is shown in the mapping examples of Figs.6A-8, data channels of other users are shown in Fig.9. Fig.9 shows a mapping example for two subframes. As shown in the figure, mapping methods may change variously as time advances.

35 The present international application claims priority based on Japanese patent application No.2006-127996, filed in the JPO on May 1, 2006 and

the entire contents of the Japanese patent application No.2006-127996 is incorporated herein by reference.

5

10

15

20

25

30

35

CLAIMS

1. A user apparatus for use in a mobile communication system in which a single carrier scheme is adopted in an uplink and a system band is divided by a plurality of resource blocks, the user apparatus comprising:

a mapping unit configured to map a data channel, a first pilot channel which is not related to the data channel and a second pilot channel which is related to the data channel to predetermined resource blocks; and a transmission unit configured to transmit the data channel, the first pilot channel and the second pilot channel which are mapped by the mapping unit, wherein the mapping unit maps the first pilot channel to a plurality of resource blocks, and the mapping unit maps the second pilot channel to a resource block to which the data channel is mapped.

20

2. The user apparatus as claimed in claim 1, wherein the first pilot channel mapped by the mapping unit is used for measurement, and the second pilot channel is used for demodulation of the data channel.

25

3. The user apparatus as claimed in claim 1 or 2, wherein the mapping unit multiplexes the data channel, the first pilot channel and the second pilot channel in a time division manner.

30

4. The user apparatus as claimed in any one of claims 1 - 3, wherein the mapping unit maps a control channel to one resource block or several resource blocks.

35

5. The user apparatus as claimed in any one of claims 1 - 4, wherein a control channel is transmitted by using a resource block to which the data channel transmitted by the transmission unit is mapped.

5

6. A transmission method for use in a user apparatus of a mobile communication system in which a single carrier scheme is adopted in an uplink and a system band is divided by a plurality of resource blocks, the transmission method comprising the steps of:

10 mapping a data channel, a first pilot channel which is not related to the data channel and a second pilot channel which is related to the data channel to predetermined resource blocks; and
15 transmitting the data channel, the first pilot channel and the second pilot channel which are mapped, wherein the step of mapping includes mapping the first pilot channel to a plurality of resource blocks, and mapping the second pilot channel to a resource block
20 to which the data channel is mapped.

7. The transmission method as claimed in claim 6, wherein the first pilot channel mapped in the step of mapping is used for measurement, and the second pilot channel is used for demodulation of the data channel.

30 8. The transmission method as claimed in claim 6 or 7, wherein the step of mapping includes multiplexing the data channel, the first pilot channel and the second pilot channel in a time division manner.

35

9. The transmission method as claimed in any one of claims 6 - 8, wherein the step of mapping includes

mapping a control channel to one resource block or several resource blocks.

5 10. The transmission method as claimed in any one of claims 6 - 9, wherein a control channel is transmitted by using a resource block to which the data channel transmitted in the step of transmitting is mapped.

10

 11. A mobile communication system in which a single carrier scheme is adopted in an uplink and a system band is divided by a plurality of resource blocks, the mobile communication system comprising:

15 a user apparatus configured to transmit a data channel, a first pilot channel which is not related to the data channel and a second pilot channel; and

 a base station configured to receive the data channel, the first pilot channel and the second pilot
20 channel from the user apparatus,

 wherein the user apparatus maps the first pilot channel to a plurality of resource blocks, and the user apparatus maps the second pilot channel to a resource block to which the data channel is mapped.

25