

CLAIMS

What is claimed is:

1. A functional wall module for at least partially forming an individual space in a building and for positioning and selectively repositioning one or more objects within the individual space, the functional wall module comprising:
 - a frame comprising one or more vertical frame supports and one or more horizontal frame supports, the frame defining an interior space;
 - one or more interior supports disposed within the interior space, the one or more interior supports comprising:
 - one or more interior vertical supports connected to at least one of the one or more horizontal frame supports, such that the one or more interior vertical supports are spaced apart from the one or more vertical frame supports; or
 - one or more interior horizontal supports connected to at least one of the one or more vertical frame supports, such that the one or more interior horizontal supports are spaced apart from the one or more horizontal frame supports;
 - a bracket associated with at least one of the one or more interior supports, the bracket comprising one or more bracket arms extending away from the interior space and from the one or more interior supports,
 - wherein the one or more bracket arms are configured to support or couple to one or more movable platforms; and
 - wherein the one or more bracket arms comprise at least a lower bracket arm and an upper bracket arm, wherein each of the lower bracket arm and the upper bracket arm further comprise a vertical attachment surface and one or more of a horizontal attachment surface or a movable receptacle attachment surface; and
 - a positioning mechanism positioned within the interior space and connected to the bracket, wherein the positioning mechanism is operable to selectively reposition the bracket.
2. The functional wall module as recited in claim 1, further comprising at least one panel connected to the frame in a manner that at least partially conceals the interior space.
3. The functional wall module as recited in claim 2, wherein the at least one panel comprises one or more bracket slots aligned with the one or more bracket arms such that at least a portion of the one or more bracket arms extends through the one or more bracket slots.

4. The functional wall module as recited in claim 3, wherein at least one of the one or more bracket slots is elongate and disposed about a path that one of the one or more bracket arms is configured to transit during repositioning of the bracket by the positioning mechanism.

5. The functional wall module of claim 1, wherein the one or more bracket arms further comprise one or more attachment surfaces.

6. The functional wall module of claim 5, wherein the one or more bracket arms are configured to support or couple to the one or more movable platforms via the one or more attachment surfaces.

7. The functional wall module of claim 6, wherein the one or more attachment surfaces comprise one or more of a horizontal attachment surface, a vertical attachment surface, or a movable platform attachment surface.

8. The functional wall module of claim 1, wherein the one or more movable platforms comprises one or more of a shelf, a cabinet, a work surface, or a monitor.

9. The functional wall module of claim 1, wherein the one or more interior supports further comprises a guide member operable to stabilize the bracket.

10. The functional wall module of claim 9, wherein the guide member further comprises a track and wherein the bracket is associated with one or more roller bearings or wheels configured to roll within the track.

11. A modular wall for creating an individual space and positioning and repositioning one or more objects within the individual space, the modular wall comprising:

- one or more wall modules selectively and detachably connected together, the one or more wall modules including a functional wall module comprising:

- a frame defining an interior space of the functional wall module;

- a positioning mechanism disposed within the interior space;

- at least one panel connected to the frame, the at least one panel comprising one or more bracket slots;

- a bracket associated with the positioning mechanism and comprising a lower bracket arm and an upper bracket arm, wherein each of the lower bracket arm and the upper bracket arm passes through one of the one or more bracket slots and extends away from the interior space and from the frame, and wherein the positioning mechanism is operable to reposition the bracket;

- a first movable platform connected to the lower bracket arm; and

- a second movable platform connected to the upper bracket arm, wherein the upper bracket arm comprises an attachment surface that is substantially parallel

to a vertical plane that is parallel to the frame of the functional wall module, the attachment surface comprising a flange having one or more mounting holes.

12. The modular wall as recited in claim 11, wherein the upper and lower bracket arms are fixedly associated with the bracket such that the upper and lower bracket arms remain equidistant during repositioning of the bracket.

13. The modular wall as recited in claim 12, wherein the one or more bracket slots are sized and shaped to permit at least a portion of the upper and lower bracket arms to transit the one or more bracket slots during repositioning of the bracket.

14. The modular wall as recited in claim 13, wherein the first movable platform comprises a work surface, and wherein the second movable platform comprises a cabinet.

15. A method for installing a functional wall module, comprising:

securing one or more interior supports to a frame having one or more horizontal frame supports and one or more vertical frame supports, such that the one or more interior supports are disposed within an interior space defined by the one or more horizontal frame supports and the one or more vertical frame supports;

securing a positioning mechanism within the interior space;

securing a panel to the frame, such that the panel at least partially conceals the interior space, the panel having one or more bracket slots; and

securing one or more bracket arms to the one or more interior supports after the panel has been secured to the frame,

wherein a first portion of each bracket arm passes through one of the one or more bracket slots and is secured to one of the one or more interior supports, and a second portion of each bracket arm has at least one dimension or shape that prevents the second portion from passing through the bracket slot through which the corresponding first portion passes, such that the second portion of each bracket arm remains outside of the interior space of the frame when the corresponding first portion is secured to one of the one or more interior supports, and

wherein the one or more bracket arms comprise at least a lower bracket arm and an upper bracket arm, wherein each of the lower bracket arm and the upper bracket arm further comprise a vertical attachment surface and one or more of a horizontal attachment surface or a movable receptacle attachment surface.

16. The method as recited in claim 15, wherein securing the one or more interior supports to the frame further comprises at least one of:

securing one or more interior vertical supports to at least one of the one or more horizontal frame supports, such that the one or more interior vertical supports are spaced apart from the one or more vertical frame supports; or

securing one or more interior horizontal supports to at least one of the one or more vertical frame supports, such that the one or more interior horizontal supports are spaced apart from the one or more horizontal frame supports.

17. The method as recited in claim 15, wherein the one or more interior supports further comprises one or more guide members operable to stabilize the one or more bracket arms, the one or more guide members each comprising a track and wherein the one or more bracket arms are associated with one or more roller bearings configured to roll within the track.

18. The method as recited in claim 15, wherein installing the functional wall module comprises converting an existing non-functional wall module into a functional wall module by securing the one or more interior supports to the frame of the existing non-functional wall module.