2078594

STAPLE CARTRIDGE FOR SURGICAL STAPLING INSTRUMENT.

This invention relates to a staple cartridge for use in an instrument for use in applying surgical fasteners such as staple, clips and the like to living tissue.

Typically, a surgical stapling instrument for use in forming a plurality of laterally spaced rows of staples in an internal body organ comprises a pair of cooperating elongate jaw members, one of which in use carries a staple cartridge with at least two laterally spaced rows of staples and the other of which carries an anvil with staple-closing depressions aligned with the rows of staples in the cartridge. A pusher bar and knife assembly is provided which is moved longitudinally along the jaws to sequentially eject staples from the cartridge by a camming action, through the agency of staple pushers carried by the cartridge in association with the individual staples, and to close the staples against the anvil thereby forming laterally spaced lines of staples in tissue gripped between the jaws, while the knife, which trails the pusher bars, cuts the tissue along a line between the staple rows. One instrument of this type is disclosed, for example, in the specification of British Patent No. 1,210,522.

With instruments of the above type, the staple cartridges and associated anvils, pusher bars and knife assemblies have commonly been made of disposable plastics and low cost metal stampings while the frames, namely the

basic instruments, have more generally been constructed for repeated usage necessitating continual sterilization of these elements between each use. In recent years, in order to obviate the need for such repeated sterilization of instruments, the tendency in the surgical field has been towards the introduction of fully self-contained disposable instruments which are used for only a single operation and then discarded. Obviously, therefore in the design of such disposable instruments, economics is a factor and it is desirable to design such instruments to utilize readily available economic materials of minimum material weight and to employ production techniques of optimum economy.

With stapling instruments of the type described, relatively large forces are involved in clamping the tissue to be fastened and in ejecting the individual staples, causing these to penetrate the gripped tissue and to be closed against the anvil. Such forces tend both to separate the jaws vertically and to laterally distort the jaws thereby hindering accurate stapling. This problem is of course accentuated if relatively light-weight disposable materials are to be used for manufacture of the jaw frames.

In our copending patent application No. 8103084 from which the present application is divided we claim in a surgical stapling instrument having first and second cooperating frames each provided with an elongate jaw, one of said jaws being adapted to receive at least two laterally spaced longitudinal rows of staples, an elongate pusher bar and knife assembly slidable longitudinally relative to said jaws for sequentially ejecting staples from said one of said jaws and shaping the staples against anvil means

provided on the other of said jaws to form a pair of laterally spaced staple rows in tissue gripped between said jaws and for cutting the tissue along a line between said staple rows, said assembly including a pair of laterally spaced pusher bars each having a forward end portion including a pusher bar cam and a knife carrier having a knife blade located between said pusher bars, jaw support means carried by the pusher bar and knife assembly and cooperating with said jaws, for locally supporting both of said jaws in the region of the pusher bar cams as the cams move along the jaws, for resisting forces tending to deflect said jaws during ejection and shaping of the individual staples.

In accordance with the present invention there is provided a staple cartridge for use with a surgical stapling instrument, said cartridge comprising a nose portion, a pair of substantially parallel elongate limbs extending from said nose portion, said limbs defining an uninterrupted slit therebetween extending the entire length and height of said limbs, seating means in each of said limbs for at least one longitudinally extending row of surgical staples and longitudinal passage means in each of said limbs for receiving a travelling pusher means operative sequentially to expel staples from said seating means.

Preferably the cartridge includes a series of individual staple pushers in each of said passage means, said staple pushers having camming surfaces for cooperating with said pusher means to expel staples from said seating means.

Preferably, also, the seating means in each of said limbs includes means for accommodating two mutually staggered rows of staples.

According to another aspect of the invention there is provided a staple cartridge for use with a surgical stapler of the type having a first jaw adapted to carry a staple cartridge, using a pusher bar to eject staples sequentially from a cartridge carried on the first jaw, and having a second jaw facing the first jaw for closing staples ejected from a cartridge on the first jaw; said staple cartridge comprising: a body containing at least one longitudinally extending row of surgical staples and having a first longitudinal passage for receiving a pusher bar of a surgical stapler; camming means for cooperating with a pusher bar to eject said surgical staples from said body; and a slot extending through the entire thickness of said body for receiving jaw support means for supporting the stapler jaws.

Yet another aspect of the invention provides a disposable cartridge for use with a surgical stapler of the type having a first jaw adapted to support a staple holder, and a second jaw facing the first jaw to close staples ejected from the staple holder, and using a pusher bar to eject staples sequentially from the staple holder; said disposable cartridge comprising: a staple holder containing a longitudinal row of staples; pusher bar means; and camming means contained in said staple holder for cooperating with said pusher bar means for ejecting said staples from said staple holder sequentially; said pusher bar means having a forward end that is received in said staple holder and being movable forward farther into said staple holder to eject said staples in cooperation with said camming means.

The invention will be further described by way of example, with reference to the accompanying drawings, wherein:

Figure 1 is a side view of a surgical stapling instrument in the assembled and closed condition;

Figure 2 is a side view of the instrument in an open condition;

Figure 3 is an exploded view of the instrument;

Figure 4 is a side view of a pusher bar and knife assembly;

Figure 5 is an underneath plan view of the pusher bar and knife assembly;

Figure 6 is a section on line 6-6 of Figure 1;

Figure 7 is a section on line 7-7 of Fgure 1; with parts of the instrument removed;

Figure 8 is an underneath view of a disposable staple cartridge;

Figure 9 is a side view of the cartridge;

Figure 10 is a section on line 10-10 of Figure 9;

Figure 11 is a top view of an elongate anvil member;

Figure 12 is a side view of the anvil member;

Figure 13 is a section on line 13-13 of Figure 12; and

Figure 14 is a section on line 14-14 of Figure 1.

Best Mode for Carrying Out the Invention

It is to be noted that the general construction and principle of operation of the illustrated instrument is similar to the instrument described in British Patent No. 1,210,522, previously referred to. Accordingly, the following description will only deal in detail with modified features of the instrument and for a fuller understanding of the principles and operation of the instrument, reference

may be made to the above patent, the disclosure of which is incorporated herein by reference.

The present instrument, generally indicated by reference 10 includes an upper frame 12 and a lower frame 14. The forward end portion of upper frame 12 defines an elongate upper jaw 16 while the forward end portion of the lower frame 14 defines an elongate lower jaw 20. The portion of lower frame 14 rearward of jaw 20 fits into a channel-shaped handle member 22 having a pivot bar 24 at its rear end which is received in notches 28 at the rear end of upper frame member 12. Intermediate its length, upper frame member 12 has laterally projecting lugs 13 whch fit in complimentary openings 15 formed in a bifurcated locking handle 26. The handle 26 can be used to open and close the frames about the pivot means 24, 28 between the open condition shown in Figure 2 and the locked condition shown in Figure 1. To this end, handle 26 has slots 17 providing camming surfaces 19 which cooperate with laterally projecting lugs 21 on handle member 22. The instrument further includes a sliding pusher bar and knife assembly 30 comprising a central knife carrier 32 and laterally spaced pusher bars 34 and 36 on either side the knife carrier, the pusher bars terminating at their forward ends in inclined pusher bar cams 38 and 40, respectively, and the knife carrier including an inclined knife 42 situated just to the rear of the pusher bar cams.

In use, a disposable staple cartridge 44, containing four laterally spaced longitudinal rows of staples, is inserted into the lower jaw 20 while two anvil members 72 having staple shaping depressions in their outer surfaces, complimentary to the positioning of the individual staples in the staple

cartridge, are placed on the upper jaw 16. The instrument is inserted into a patients body and manipulated such that tissue to be cut and sutured is inserted between the jaws, an incision to receive one of the jaws having previously been made in the tissue, if required. The jaws are then closed and locked by handle 26 to firmly grip the tissue between the opposing staple cartridge and anvil surfaces. The pusher bar and knife assembly which is initially in a rearward position relative to the jaws, is then pushed forwardly causing the pusher bar cams to enter longitudinal slits in the staple cartridge, in which slits are accommodated rows of individual staple pushers. The pusher bar cams cooperate sequentially with camming surfaces on the individual staple pushers to force the staples successively from the cartridge, through the gripped tissue and into engagement with the anvil depressions which thereby, in conjunction with the cams, produce staple-closing forces. The design of the cartridge is such that each slit carries two mutually staggered rows of staples so that in all, four staple rows are formed in the gripped tissue. The knife 42 which trails the pusher bars cams slightly and rides in central longitudinal slits in the cartridge and anvil, cuts the gripped tissue along a line between the two pairs of staple rows.

To provide lateral support for the jaws and to resist forces tending to vertically open the jaws during stapling, each jaw is provided with a longitudinal passageway and the knife blade carrier 32 which is a relatively rigid member, preferably of metal, carries upper and lower laterally aligned shoes which ride in these passageways and provide the required local support to the jaws in the region

of the pusher bar cams and knife blade as these elements travel along the staple cartridge.

Thus, it will be seen, particularly in Figures 6, 7 and 14 that the lower frame 14 is formed with a cartridge-receiving channel 46 and an outer longitudinal passageway 48 of generally T-shaped cross-section extending from the base of the channel 46. Upper frame 12 has inwardly directed longitudinally extending shoulders 50 for mounting the anvils as will be described, the construction of the upper frame being such that a longitudinally extending passageway 52 of generally rectangular section is formed beneath the shoulders.

The pusher bar and knife assembly 30, see particularly Figures 3, 4 and 5, has conventional-type laterally spaced pusher bars 34 and 36 terminating in slightly offset inclined pusher bar cams 38 and 40. The central knife carrier 32, as indicated, has an inclined knife 42 just to the rear of the pusher bar cams and the knife carrier is extended vertically above and below the pusher bars. On upper and lower terminal portions of the knife carrier which project forwardly of the knife, are situated lower and upper shoes 54 and 56, respectively, the vertical spacing between the shoes corresponding to the vertical spacing between the passageways 48 and 52 in the lower and upper frames when the frames are locked together. The lower shoe 54 has a substantially T-shaped cross section corresponding to the cross-sectional shape of passageway 48 so that this shoe fits in passageway 48 with minimal clearance to allow substantially friction-free passage of the shoe along the passageway, and upper shoe 56 is likewise shaped to fit in passageway 52 with minimal clearance to provide substantially

friction-free passage. It will be noted that the shoes 52 and 54 are longitudinally located in proximity to the pusher bar cams 38 and 40 so as to in use, provide support for the jaws 16 and 20 in the region of the cams substantially at points where the forces created by cooperation of the pusher bar cams and the individual staple pushers in the cartridge approach a maximum. Further, by locating the shoes both laterally and vertically in the respective passageways, both lateral alignment of the jaws and resistance to vertical jaw opening during stapling is obtained.

At the rear end of assembly 30, the pusher bars and knife carrier are mounted in known manner in a suitable carrying block 31 having an operating knob 33 or the like.

The staple cartridge 44 as shown in Figures 8, 9 and 10 is generally of similar character to the known type as described in the aforementioned British Patent No. 1,210,522 insofar as the number of staple rows, and design and location of the individual staple pushers is concerned. For a fuller description of these elements and the manner in which staple ejection is effected by interaction of the pusher bar cams and the individual staple pushers, reference may therefore be made to this patent. In the present case, the cartridge 44 has a solid nose portion 58 and a pair of longitudinal ribs 60 and 62 extending rearwardly from the nose portion and defining a slit 64 therebetween right through the cartridge for passage of the knife carrier 32. The inner facing surfaces of the ribs 60 and 62 again have bumps 66 to laterally locate the knife carrier and the ribs are themselves longitudinally slit to accommodate the staple pushers and the opposed,

staggered rows of staples. Friction pieces 68 are again provided to inhibit inadvertent forward motion of the pusher bars. Thus, the significant difference between the present cartridge and that described in British Patent No. 1,210,522 is that in the present case slit 64 extends right through the cartridge (to the rear of the nose portion) to allow passage of the vertically extended knife carrier. In use, as indicated, the cartridge 44 sits in the cartridge receiving channel 46 of the lower jaw with the nose portion 58 projecting forwardly of the jaw and positive longitudinal location of the cartridge being effected by means of a projecting cartridge lug 70 and a complimentary cut-out in one of the side walls of channel 46.

The anvil means in the present instance, see Figures 11, 12 and 13, comprises a pair of like individual elongate anvils 72 which sit with a friction fit on the shoulders 50 of the upper jaw, as seen in Figures 1, 3 and 14, whereby a slit is provided between the anvils allowing passage for the vertically extended knife carrier. Each individual anvil comprises an anvil surface 76 with staple-shaping depressions 78, an outer wall 80 and a shorter inner wall 82. The inner and outer walls are slightly inwardly tapered to provide the friction fit on shoulders 50 and the outer walls each have depressions 51 aligning with complimentary depressions

in the side walls of the lower jaw for longitudinally locating the individual anvils and accurately aligning the staple shaping depressions with the individual staples in cartridge 44.

While the instrument as described includes separate anvils 72 which fit on the shoulders 50 of upper jaw 16, it is also possible, particularly in the manufacture of a low-cost disposable instrument, to dispense with the anvils themselves and form the staple shaping depressions, directly in the undersurfaces of shoulders 50 of the upper jaw.

Assembly of the various components of the instrument is effected in the following manner with particular reference to Figures 1 to 3. Initially, with a cartridge 44 correctly positioned on jaw 20 of lower frame 14, the forward end of pusher assembly 30 is inserted from the back into lower frame 14, with lower shoe 54 fitting in passageway 48, and assembly 30 is moved forwardly along frame 14 until the pusher bars enter the lontitudinally slit ribs 60 and 62 of cartridge 44 and are arrested by the friction pieces 68. This position of pusher assembly 30 relative to frame 14 is shown in Figures 1 and 2. Frame 14 with the inserted pusher assembly 30 is then fitted into handle member 22, suitable complimentary locating means (not shown) being provided on the frame and handle member to longitudinally align these elements and prevent forward movement of frame 14 in member 22 during staple ejection.

Anvils 72 are fitted on jaw 16 and lugs 13 of frame 12 are fitted into openings 15 of handle 26. Then with handle 26 tilted upwardly, as shown in Figure 2, notches 28 are engaged with pivot bar 24 to complete the assembly of the instrument.

In use, the instrument in the assembled open condition, substantially as shown in Figure 2, is inserted into a body cavity, so that tissue to be stapled is accepted between jaws 16 and 20 and the instrument is then locked by manipulation of handle 26 and cooperation of camming surfaces 19 with lugs 21. It will be noted that openings 55 (see Figure 3) are provided in shoulders 50 of the upper frame 12 which allow shoes 56 to enter channel 52 as the instrument is closed. With tissue gripped between the jaws and the instrument in the condition as shown in Figure 1, stapling is effected in the manner described in the aforementioned patent by pushing forwarding on knob 33.

When stapling is completed, the pusher assembly 30 is retracted to the initial positon, allowing shoes 56 to be removed from channel 52 through openings 55, so that the instrument can be opened.

It will be appreciated, since the shoes 54 and 56 are accurately laterally aligned and carried by a relatively rigid member, that during stapling, as the shoes move along the passageways 48 and 52 with minimal clearance, they provide adequate localized support to the jaws in the region of operation of the pusher bar cams and the particular individual staple pushers being actuated. Due to the cross-sectional shape of the shoes and passage-ways, such support resists forces tending both laterally to distort the jaws and to open the jaws vertically and accordingly the present construction lends itself to manufacturing the jaws in relatively light weight disposable materials. It is to be understood however that the construction can also be used in instruments manufactured from more conventional materials.

While only a single preferred embodiment of the invention has been described in detail, it is to be understood that the invention is not limited to its specific features and modifications are possible within the scope of the attached claims. Thus, while the invention has been particularly described in relation to its application in a surgical stapling instrument, the invention is not limited to this application. The invention may be applied to other fastening instruments having opposed jaws which require stabilization while fastening means are applied to living tissue gripped between the jaws. For example, the invention may be applied to instruments for applying certain types of surgical clips or instruments for applying surgical fastening devices of the type set out in U.S. Patent No. 4,060,089.

CLAIMS

1. A staple cartridge for use with a surgical stapling instrument, said cartridge comprising a nose portion, a pair of substantially parallel elongate limbs extending from said nose portion, said limbs defining an uninterrupted slit therebetween extending the entire length and height of said limbs, seating means in each of said limbs for at least one longitudinally extending row of surgical staples and longitudinal passage means in each of said limbs for receiving a travelling pusher means operative sequentially to expel staples from said seating means.

2. A staple cartridge as defined in claim 1, including a series of individual staple pushers in each of said passage means, said staple pushers having camming surfaces for cooperating with said pusher means to expel staples from said seating means.

3. A staple cartridge as defined in claim 1 or 2, wherein said seating means in each of said limbs includes means for accommodating two mutually staggered rows of staples.

4. A staple cartridge for use with a surgical stapler of the type having a first jaw adapted to carry a staple cartridge, using a pusher bar to eject staples sequentially from a cartridge carried on the first jaw, and having a second jaw facing the first jaw for closing staples ejected from a cartridge on the first jaw; said staple cartridge comprising: a body containing at least one longitudinally extending row of surgical staples and having a first longitudinal passage for receiving a pusher bar of a surgical stapler; camming means for cooperating with a pusher bar to eject said surgical staples from said body; and a slot extending through the entire thickness of said body for receiving jaw support means for supporting the stapler jaws.

5. A staple cartridge according to claim 4, further comprising jaw support means for supporting the stapler jaws, wherein said jaw support means comprises shoe means slidably movable along said slot in tandem with a pusher bar when a pusher bar of a surgical stapler is received in said first longitudinal passage, said shoe means being adapted to cooperate with a surgical stapler of said type for maintaining the jaws of the surgical stapler substantially stationary relative to each other in the vicinity of said shoe means.

6. A staple cartridge according to claim 5, wherein said shoe means comprises upper and lower shoes rigidly connected to each other.

7. A staple cartridge according to claim 5 or 6, further comprising pusher bar means received in said longitudinal passage for expelling staples from said body sequentially, said pusher bar means being movable in tandem with said shoe means.

8. A staple cartridge according to claim 7, further comprising knife means received in said slot and movable with said pusher bar means for cutting tissue after it has been stapled with staples ejected from said cartridge, said knife means being movable in tandem with said pusher bar means.

9. A disposable cartridge for use with a surgical stapler of the type having a first jaw adapted to support a staple holder, and a second jaw facing the first jaw to close staples ejected from the staple holder, and using a pusher bar to eject staples sequentially from the staple holder; said disposable cartridge comprising: a staple holder containing a longitudinal row of staples; pusher bar means; and camming means contained in said staple holder for cooperating with said pusher bar means for ejecting said staples from said staple holder sequentially; said pusher bar means having a forward end that is received in said staple holder and being movable

forward farther into said staple holder to eject said staples in cooperation with said camming means.

10. A staple cartridge for use with a surgical stapling instrument, such cartridge being constructed and arranged substantially as hereinbefore described with reference to and as illustrated in the accompanying drawings.

The text of the specification has been reproduced by photocopying the applicants original typescript. It may contain a few amendments which are difficult to read. The original typescript containing these amendments may be inspected on the premises of the Patent Office

* C L M S *