

(51) International Patent Classification:
E21B 19/00 (2006.01)(21) International Application Number:
PCT/EP2011/060756(22) International Filing Date:
28 June 2011 (28.06.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20100955 30 June 2010 (30.06.2010) NO(71) Applicant (for all designated States except US): **AKER
MH AS** [NO/NO]; P.O.Box 413, Lundsiden, N-4604 Kris-
tiansand (NO).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **PØHNER, Lars**
[NO/NO]; Trostestien 22, N-3189 Horten (NO).(74) Agents: **LANGAN, H.** et al.; c/o **ONSAGERS AS**,
P.O.BOX 6963, St. Olavs Plass, N-0130 Oslo (NO).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG,
SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ,
UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG,
ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

— before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))(88) Date of publication of the international search report:
7 February 2013

(54) Title: A METHOD AND A SYSTEM FOR CONTROLLING MOVEMENTS OF A FREE-HANGING TUBULAR




FIG. 3

(57) Abstract: An apparatus (1) for controlling movements of a free-hanging tubular (4) suspended via at least a connector element (8) by at least one compensator member (7) which is connected to a buoyant vessel (2), said tubular extending into a body of water below the vessel. The apparatus comprises motion sensing means (36) for sensing movements of the compensator member and thus that of the vessel (2), and position indicator means (21) for sensing the position of the connector element (8), and thus that of an upper region of the tubular, with respect to the compensator member. The apparatus further comprises data processing means (22) for determining one or more parameters regarding the movement between the vessel and the upper region of the tubular; and adjusting means (24a, b, 25, 26, 29, 33a-d) for controlling at least the stiffness and dampening of the compensator member (7); whereby the axial loads which are transferred between the compensator and the tubular may be controlled.