

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G08B 5/22	A1	(11) International Publication Number: WO 97/17681 (43) International Publication Date: 15 May 1997 (15.05.97)
(21) International Application Number: PCT/JP96/03281 (22) International Filing Date: 8 November 1996 (08.11.96) (30) Priority Data: 7/317450 10 November 1995 (10.11.95) JP (71) Applicant (for all designated States except US): CASIO COMPUTER CO., LTD. [JP/JP]: 6-1, Nishi-Shinjuku 2-chome, Shinjuku-ku, Tokyo 160 (JP). (72) Inventors; and (75) Inventors/Applicants (for US only): TAKAHASHI, Oh [JP/JP]: 4-4-4-107, Shibakubo-cho, Tanashi-shi, Tokyo 188 (JP). HIDAKA, Shinji [JP/JP]: 638-510, Ooaza-fussa, Fussa-shi, Tokyo 197 (JP). (74) Agents: SUZUYE, Takehiko et al.; Suzuye & Suzuye, 7-2, Kasumagaseki 3-chome, Chiyoda-ku, Tokyo 100 (JP).		(81) Designated States: AU, CN, KR, SG, US. Published <i>With international search report.</i>

(54) Title: **DATA RECEIVER APPARATUS**

(57) Abstract

When a pager (1) receives message data produced by dial input by a data sender (6), a CPU (15) detects a free word start symbol from the message data. Then, following bit patterns, are by 2, sequentially read so that a corresponding character is instructed and the received message is developed on a display buffer (26). When a control code detector (151) detects a bit pattern corresponding to a control code "2", "4", "6", "8", or "0", the CPU (15) generates a bit pattern corresponding to the control code and a display control code from a bit pattern in front of the bit pattern, and a corresponding contents of control is read from a display control table stored in a display control memory (155). In accordance with the contents of display control, the developed received message is displayed on a display (27).

