

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
02 January 2020 (02.01.2020)



(10) International Publication Number
WO 2020/005141 A1

(51) International Patent Classification:
F16L 5/08 (2006.01) *H02G 3/22* (2006.01)

TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

(21) International Application Number:
PCT/SE2019/050585

Published:
— with international search report (Art. 21(3))

(22) International Filing Date:
19 June 2019 (19.06.2019)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
1850795-4 27 June 2018 (27.06.2018) SE

(71) Applicant: **ROXTEC AB** [SE/SE]; P.O. Box 540, SE-371
23 KARLSKRONA (SE).

(72) Inventor: **STRÄNG, Daniel**; c/o Roxtec AB, P.O. Box
540, 371 23 KARLSKRONA (SE).

(74) Agent: **STRÖM & GULLIKSSON AB**; P.O. Box 4188,
SE-203 13 MALMÖ (SE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP,
KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

(54) Title: A LEAD-THROUGH COMPRISING A SEAL AND AN OUTER DIAMETER EXTENDER




Fig. 3

(57) Abstract: The present invention concerns a lead-through for cables, wires or pipes comprising a cylindrical seal (4) and an outer diameter extender (1). The outer diameter extender (1) is adapted to be mounted on an outer surface of the cylindrical seal (4). The outer diameter extender (1) comprises two parts, wherein each of the two parts has at least one protruding part (2) and at least one recess (3). The at least one protruding part (2) of one of the parts of the outer diameter extender (1) is to be received in the at least one recess (3) of the other part of the outer diameter extender (1).

WO 2020/005141 A1