

DESCRIPTION
SCREW COMPRESSOR

Technical Field

5 [0001]

The present invention relates to a screw compressor, and more particularly to an arrangement structure of a gas cooler in a screw compressor.

10 Background Art

[0002]

The screw compressor is provided with a gas cooler for cooling gas which has high temperature and high pressure by compression.

15 [0003]

Patent Document 1 discloses a compact screw compressor in which a cooler casing and a step-up gear casing are integrally made of a cast material, and a compressor and an electric motor are mounted on the step-up gear casing part of the integrated casings.

20

Prior Art Document

Patent Document

[0004]

Patent Document 1: JP 2002-21759 A

25

Disclosure of the Invention

Problems to be Solved by the Invention

[0005]

The screw compressor mentioned in Patent Document 1 has a casing structure in which the cooler casing part, the step-up gear casing part, and the like are integrally formed of the cast material. Because of this, if any trouble occurs in the cooler casing part, work of removing and replacing the entire integrated casing structure will be required, which is a significant burden.

[0006]

The cooler casing part is regarded as a pressure vessel and needs to be compliant with laws and regulations of each country. Further, the step-up gear casing part integrally formed with the cooler casing part can also be regarded as a pressure vessel, and thus inevitably has the same properties as the pressure vessel. Such a step-up gear casing part is of undue quality, which is more than needed in terms of structure and material. Consequently, the manufacturing cost of the step-up gear casing part increases, which leads to an increase in the manufacturing cost of the screw compressor as well.

[0007]

Therefore, in view of these technical problems to be solved by the present invention, it is an object of the present invention to provide a screw compressor which can easily detach a gas cooler from a step-up gear without compromising compactness and can be

manufactured at low cost.

Means for Solving the Problems

[0008]

5 To solve the above-mentioned technical problems, the present invention provides the following screw compressor.

[0009]

That is, a screw compressor is characterized by including:

a screw compressor main body;

10 a motor for driving the screw compressor main body;

a gearbox interposed between the screw compressor main body and the motor to transmit a driving force of the motor to the screw compressor main body; and

15 a gas cooler positioned below either the screw compressor main body or the motor and attached as a separate body to a side surface of the gearbox.

Effects of the Invention

[0010]

20 With the above-mentioned configuration, the gas cooler is positioned below either the screw compressor main body or the motor and attached as a separate body to a side surface of the gearbox, thereby making it possible to easily remove the gas cooler, though the screw compressor is compact. As the gearbox
25 separately provided from the gas cooler is not regarded as a

pressure vessel, the gearbox can adopt the optimal structure and material required therefor, and the screw compressor can be manufactured at low cost.

5 Brief Description of the Drawings

[0011]

FIG. 1 is a front view of a screw compressor according to an embodiment of the present invention.

FIG. 2 is a plan view of the screw compressor shown in FIG.

10 1.

FIG. 3 is a side view of the screw compressor shown in FIG.

1.

Embodiments of the Invention

15 [0012]

A screw compressor 1 according to an embodiment of the present invention will be described with reference to FIGS. 1 to 3.

[0013]

20 FIG. 1 is a front view of the screw compressor 1 according to an embodiment of the present invention; FIG. 2 is a plan view of the screw compressor; and FIG. 3 is a side view of the screw compressor. The screw compressor 1 shown in FIGS. 1 to 3 includes a motor 10, a screw compressor main body 20, a gearbox 30, a gas
25 cooler 40, and a base plate 7.

[0014]

The screw compressor main body 20 is a two-stage screw compressor that has a first stage compressor main body 22 on a low pressure side and a second stage compressor main body 24 on a high pressure side. The first stage compressor main body 22 is disposed on one side surface of the gearbox 30. The second stage compressor main body 24 is disposed on one side surface of the gearbox 30, which is the same side as the first stage compressor main body 22. The screw compressor main body 20 is connected to one side surface of the gearbox 30 in a state of being positioned at a predetermined location.

[0015]

The first stage compressor main body 22 has a pair of male and female screw rotors that rotate while meshing with each other. The second stage compressor main body 24 has a pair of male and female screw rotors that rotate while meshing with each other. The respective screw rotors of the first stage compressor main body 22 and the second stage compressor main body 24 compress a fluid, such as gas.

[0016]

The motor 10 that supplies a driving force to the first stage compressor main body 22 and the second stage compressor main body 24 is disposed on the other side surface of the gearbox 30. In other words, the gearbox 30 is interposed between the screw compressor main body 20 and the motor 10. The gearbox 30 is

coupled to the first stage compressor main body 22 and the second stage compressor main body 24. The motor 10 is connected to the other side surface of the gearbox 30 via a substantially cylindrical connection casing 15 in a state of being positioned at a predetermined location. That is, a connection flange 16 of the connection casing 15 is connected to a motor-side connection flange 14 of the motor 10, while a coupling flange 17 of the connection casing 15 is connected to a coupling end 18 of the gearbox 30.

[0017]

The gearbox 30 has a substantially rectangular parallelepiped shape that has a long side orthogonal to a motor shaft of the motor 10 or a rotor shaft (hereinafter sometimes simply referred to as a shaft) of the screw compressor main body 20, a short side extending in parallel to the shaft, and a height orthogonal to the shaft. A gear mechanism (any element therein not shown) is accommodated inside the gearbox 30. In the present embodiment, a bull gear, a first pinion gear, and a second pinion gear are accommodated as the gear mechanism. A coupling is accommodated inside the connection casing 15.

[0018]

The motor shaft of the motor 10 is coupled to an input shaft of the gear mechanism via the coupling. The bull gear is attached to the side of the input shaft opposite to the coupling side. The input shaft inputs the driving force of the motor 10 to the gearbox

30. The gear mechanism of the gearbox 30 transmits the driving force of the motor 10 to each of the screw rotors of the first stage compressor main body 22 and the second stage compressor main body 24.

5 [0019]

One rotor shaft of the first stage compressor main body 22 extends within the gearbox 30, and the first pinion gear that meshes with the bull gear is attached to a shaft end part of the rotor shaft. One rotor shaft of the second stage compressor main
10 body 24 extends into the gearbox 30, and the second pinion gear that meshes with the bull gear is attached to a shaft end part of the rotor shaft.

[0020]

The bull gear connected to the input shaft, which is coupled
15 to the motor shaft via the coupling, meshes with the first pinion gear of the first stage compressor main body 22 and the second pinion gear of the second stage compressor main body 24.

Therefore, once the motor 10 is activated, the driving force of the motor 10 is input to the input shaft, transmitted from the
20 bull gear to the first pinion gear and the second pinion gear, and then transmitted to the respective rotor shafts of the first stage compressor main body 22 and the second stage compressor main body 24. Then, the respective screw rotors of the first stage compressor main body 22 and the second stage compressor main body
25 24 rotate to compress the fluid such as gas.

[0021]

The gas cooler 40 configured separately from the gearbox 30 is disposed on one side surface of the gearbox 30 where the screw compressor main body 20 is disposed. An attachment portion 36 of the gas cooler 40 is connected to an attachment portion 35 provided on one side surface of the gearbox 30 in a state of being positioned at a predetermined location. Thus, the gas cooler 40 is detachably attached to the gearbox 30 in a position lower than the screw compressor main body 20. The screw compressor main body 20 on the upper side is connected to the gas cooler 40 on the lower side by piping (not shown). The screw compressor main body 20 and the gas cooler 40 are positioned with respect to the gearbox 30 by using positioning pins so that the gas cooler 40 is arranged below the screw compressor main body 20, which facilitates handling of the piping for connecting both the screw compressor main body 20 and the gas cooler 40 and shortens the length of the piping.

[0022]

The gas cooler 40 is a pressure vessel provided for cooling compressed gas discharged from the screw compressor main body 20. The gas cooler 40 includes an intercooler (first gas cooler) 42 and an aftercooler (second gas cooler) 44, which are integrally formed in a substantially rectangular parallelepiped shape. The intercooler 42 is provided in a gas path between the first stage compressor main body 22 and the second stage compressor main body

24, and the aftercooler 44 is provided in a gas path disposed downstream of the second stage compressor main body 24. The gas cooler 40 may have a substantially rectangular parallelepiped shape that has a long side orthogonal to the shaft, a short side extending in parallel to the shaft, and a height orthogonal to the shaft in order to effectively utilize an installation space.

[0023]

The intercooler 42 is a cooler for lowering the temperature of the compressed gas that has its temperature increased by being compressed in the first stage compressor main body 22. The aftercooler 44 is a cooler for lowering the temperature of the compressed gas that has its temperature increased by being compressed in the second stage compressor main body 24. The gas cooler 40 is, for example, a shell and tube type water-cooled heat exchanger.

[0024]

Within a heat exchange portion through which the compressed gas circulates, a plurality of straight heat exchange pipes is installed side by side. Cooling water (cooling medium) is caused to flow through the inside of the heat exchange pipes. The compressed gas to be cooled circulates around the heat exchange pipes. It is noted that a part where the plurality of heat exchange pipes is installed is called a tube nest portion. The heat exchange pipes are arranged in parallel to each other.

Further, it is noted that piping and the like for inflow or outflow

of the cooling water is not illustrated.

[0025]

A top wall portion 61 of a cooler casing 41 is respectively provided with an inter-inlet port 45 connected to the discharge side of the first stage compressor main body 22, an inter-outlet port 46 connected to the suction side of the second stage compressor main body 24, and an after-inlet port 47 connected to the discharge side of the second stage compressor main body 24. An after-outlet port 48 is provided at the lower side of a sidewall portion 62 located on the side of an aftercooler 50 of the cooler casing 41. Covers 63 are respectively attached to both side ends of the cooler casing 41 to maintain liquid tightness. The tube nest portion is detachable from the cooler casing 41 and thus can be easily replaced by removing the cover 63 in the event of trouble.

[0026]

The compression gas supplied to the first stage compressor main body 22 is compressed by the first stage compressor main body 22, sent from the discharge port on the bottom surface side thereof to the inter-inlet port 45 on the upper surface side of the intercooler 42, cooled by the intercooler 42, and then discharged from the inter-outlet port 46 on the upper surface side of the intercooler 42. Thereafter, the compressed gas is supplied to the second stage compressor main body 24 and further compressed by the second stage compressor main body 24. Subsequently, the compressed gas is sent from the discharge port on the bottom

surface side of the second stage compressor main body 24 to the after-inlet port 47 on the upper surface side of the aftercooler 50, cooled by the aftercooler 50, and then discharged from the after-outlet port 48. It should be noted that since the screw
5 compressor main body 20 and the gas cooler 40 are connected together in a state of being positioned with respect to the gearbox 30, the length of the piping connecting both of them is mechanically determined. Thus, there is no need to provide an error buffering member, such as an expansion pipe joint for
10 buffering an error in the pipe installation length, at some midpoint of the piping. Further, the length of the piping becomes as short as possible by arranging a discharge port on the bottom surface side of the screw compressor main body 20 and arranging an introduction port on the top surface side of the gas cooler
15 40.

[0027]

A support end portion 49 is provided at a position below the cooler casing 41 and away from the gearbox 30. For example, as shown in FIG. 2, the support end portion 49 is arranged at one
20 site located farthest away from the gearbox 30 and substantially at the center of the long side of the cooler casing 41 as shown in FIG. 3. A vibration isolator 53 is interposed between the lower surface of the support end portion 49 and the upper surface of the base plate 7. The vibration isolator 53 is arranged not at
25 one end and the other end of the long side of the cooler casing

41, but substantially at the center of the long side. A connection port for introducing or guiding out the compressed gas, such as the after-outlet port 48, any cooling-water piping, and the like are provided on the side of an end of the long side of the cooler casing 41 shown in FIG. 3 in many cases. Such provision needs consideration not to interrupt a replacement work of the tube nest portion in the gas cooler 40. For this reason, the vibration isolator 53 is preferably provided substantially at the center in the long-side direction (direction orthogonal to the shaft) of the cooler casing 41 rather than on the side of the end of the long side of the cooler casing 41. Therefore, the arrangement of the vibration isolator 53 substantially at the center of the long side of the cooler casing 41 improves flexibility in the configuration of the heat exchange portion in the gas cooler 40, which facilitates the replacement work of the tube nest portion in the gas cooler 40.

[0028]

Support end portions 38 and 39 are provided under the gearbox 30. For example, as shown in FIG. 3, the support end portions 38 and 39 are arranged at one end and the other end of the long side of the gearbox 30, respectively. Vibration isolators 51 and 52 are interposed between the lower surfaces of the support end portions 38 and 39 and the upper surface of the base plate 7, respectively. That is, the two vibration isolators 51 and 52 are arranged spaced apart from each other in the direction of the long

side of the gearbox 30 (the direction orthogonal to the shaft). The side of the gearbox 30 is supported by the minimum necessary vibration isolators 51 and 52, thereby making it possible to reduce the cost.

5 [0029]

The gearbox 30 to which the motor 10 and the screw compressor main body 20 are connected and the gas cooler 40 are placed on the base plate 7 via the vibration isolators 51, 52, and 53. The gearbox 30 and the gas cooler 40 are supported at three points,
10 namely, the vibration isolators 51, 52, and 53, so that the gearbox 30 and the gas cooler 40 can be stably freestanding when placed on the base plate 7 or when detached from the base plate 7 and placed in another position.

[0030]

15 The vibration isolators 51, 52, and 53 have predetermined spring properties and hence have the function of attenuating vibration transmitted from the gearbox 30 and the gas cooler 40 to the base plate 7. Each of the vibration isolators 51, 52, and 53 is, for example, a vibration isolating rubber. The vibration
20 isolators 51, 52, and 53 are preferably made of the same member, i.e., the same material with the same shape. By using the same member in the vibration isolators, the cost can be reduced.

[0031]

In the above-mentioned embodiment, the gas cooler 40 is
25 detachably attached as a separate body to the lower part of one

side surface, on the side of the screw compressor main body 20, of the gearbox 30. Alternatively, in a modification, the gas cooler 40 may be detachably attached to a lower part of the other side surface, on the side of the motor 10, of the gearbox 30.

5 [0032]

As can be seen from the above description, the screw compressor 1 according to the present invention comprises: the screw compressor main body 20; the motor 10 for driving the screw compressor main body 20; the gearbox 30 interposed between the screw compressor main body 20 and the motor 10 to transmit a driving force of the motor 10 to the screw compressor main body 20; and the gas cooler 40 positioned below either the screw compressor main body 20 or the motor 10 and attached as a separate body to a side surface of the gearbox 30.

15 [0033]

With the above-mentioned configuration, the gas cooler 40 is positioned below either the screw compressor main body 20 or the motor 10 and attached as the separate body to the side surface of the gearbox 30, thereby making it possible to easily detach the gas cooler 40, though the screw compressor is compact. As the gearbox 30 separately provided from the gas cooler 40 is not regarded as a pressure vessel, the gearbox 30 can adopt the optimal structure and material required therefor, and the screw compressor 1 can be manufactured at low cost.

25 [0034]

The present invention can have the following features in addition to the features mentioned above.

[0035]

That is, the vibration isolators 51, 52, and 53 are disposed
5 between the base plate 7 on which the gearbox 30 and the gas cooler
40 are placed and the respective support end portions 38, 39, and
49 of the gearbox 30 and the gas cooler 40, respectively. With
this configuration, vibration transmitted from the gearbox 30 and
the gas cooler 40 to the base plate 7 can be attenuated.

10 [0036]

The gearbox 30 and the gas cooler 40 are placed on the base
plate 7 via the two vibration isolators 51 and 52 supporting the
gearbox 30 and the one vibration isolator 53 supporting the gas
cooler 40. With this configuration, the gearbox 30 and the gas
15 cooler 40 can be stably freestanding through three-point support.

[0037]

The only one vibration isolator 53 disposed in the gas cooler
40 is arranged substantially at the center, in the direction
orthogonal to each of shafts of the motor 10 and the screw
20 compressor main body 20, of the gas cooler 40. With this
configuration, the gas cooler 40 has improved flexibility in the
configuration of the heat exchange portion therein, which
facilitates the replacement work of the tube nest portion in the
gas cooler 40.

25 [0038]

Each of the vibration isolators 51 and 52 disposed in the gearbox 30 is arranged in a vicinity of each corresponding end, in the direction orthogonal to each of shafts of the motor 10 and the screw compressor main body 20, of the gearbox 30. With this configuration, the side of the gearbox 30 is supported by the minimum necessary vibration isolators 51 and 52, thereby making it possible to reduce the cost.

Description of Reference Numerals

- 10 [0039]
- 1: Screw compressor
- 7: Base plate
- 10: Motor
- 14: Motor side connection flange
- 15 15: Connection casing
- 16: Connection flange
- 17: Coupling flange
- 18: Coupling end
- 20: Screw compressor main body
- 20 22: First stage compressor main body
- 24: Second stage compressor main body
- 30: Gearbox
- 35, 36: Attachment portion
- 39: Support end portion
- 25 40: Gas cooler

- 41: Cooler casing
- 42: Intercooler (first gas cooler)
- 44: Aftercooler (second gas cooler)
- 45: Inter-inlet port
- 5 46: Inter-outlet port
- 47: After-inlet port
- 48: After-outlet port
- 49: Support end portion
- 51, 52, 53: Vibration isolator
- 10 61: Top wall portion
- 62: Sidewall portion
- 63: Cover

CLAIMS

1. A screw compressor comprising:
 - a screw compressor main body;
 - a motor for driving the screw compressor main body;
 - a gearbox accommodating a gear mechanism therein,interposed between the screw compressor main body and the motor to transmit a driving force of the motor to the screw compressor main body via the gear mechanism; and
 - a gas cooler positioned below either the screw compressor main body or the motor and detachably attached to a side surface of the gearbox.
2. The screw compressor according to claim 1, wherein support end portions are each provided at the gearbox and the gas cooler, the gearbox and the gas cooler are each placed on a base plate and a vibration isolator is disposed between each support end portion and the base plate.
3. The screw compressor according to claim 2, wherein the gearbox and the gas cooler are placed on the base plate via the two vibration isolators supporting the gearbox and the one vibration isolator supporting the gas cooler.
4. The screw compressor according to claim 2 or 3, wherein the only one vibration isolator supporting the gas cooler is

arranged substantially at a center, in a direction orthogonal to each of shafts of the motor and the screw compressor main body, of the gas cooler.

5. The screw compressor according to claim 2 or 3, wherein each of the vibration isolators supporting the gearbox is arranged in a vicinity of each corresponding end, in a direction orthogonal to each of shafts of the motor and the screw compressor main body, of the gearbox.

6. The screw compressor according to claim 4, wherein each of the vibration isolators supporting the gearbox is arranged in a vicinity of each corresponding end, in a direction orthogonal to each of shafts of the motor and the screw compressor main body, of the gearbox.