

Description

The invention relates to a two-step reaction process for converting ethylene oxide with high selectivity into monoethylene glycol.

It is generally known, e.g. from Kirk-Othmer's Encyclopedia of chemical Technology, 3rd Edition vol. 11 (1980), 939, that monoethylene glycol is prepared by reaction of ethylene oxide with water at a temperature between 180 °C and 220 °C, wherein the amount of water is about 10 times the amount of ethylene oxide (by weight). Disadvantages of the process are that large amounts of water must be flashed off and still considerable amounts of diethylene glycol are prepared. The use of a catalyst may lead to a reduction in the amount of water (but not to stoichiometric amount), but the amount of diethylene glycol is hardly diminished.

Applicant has now found a process for the preparation of monoethylene glycol, which process does not have these disadvantages.

It is an object of the invention to prepare monoethylene glycol from ethylene oxide in very high yield.

It is another object of the invention to use as little water as possible.

According to the invention ethylene oxide is converted with high selectivity into monoethylene glycol in a two-step reaction process which comprises firstly reacting ethylene oxide with acetone to 2,2-dimethyl-1,3-dioxolane and secondly hydrolyzing the 2,2-dimethyl-1,3-dioxolane with a substantially stoichiometric amount of water to monoethylene glycol, both steps requiring the presence of a solid acidic catalyst.

In the German "Auslegesschrift" 1,086,241 is disclosed the preparation of 1,3-dioxolanes by reacting epoxy compounds with carbonyl compounds in the presence of acid activated bentonite. The reaction between acetone and ethylene oxide has been mentioned and the yield of this step is 83 per cent. Reactions with other compounds give similar yields. The publication does not teach how the objects of our invention could be fulfilled.

In the UK Patent Application 2,098,985 is disclosed a two-step process whereby an alkylene oxide reacts with carbon dioxide in the presence of a phosphonium halide, there being substantially less than an equimolar amount of water present based on the ethylene oxide, to produce an alkylene carbonate, which latter product is reacted with water in the presence of the same phosphonium halide to a glycol. This two-step process has the disadvantages that rather high temperatures (180 °C) and no solid catalyst is used.

In the Japanese Patent Application (KOKAI) 59-67233 there is disclosed a method for separating ethylene glycol from its mixtures, by reacting it with a ketone such as acetone or methyl ethyl ketone into the corresponding cyclic ketal, which is separated by distillation and subsequently converted with an excess of water and redistilled to give back the ethylene glycol as a distillation residue.

Solid acidic catalysts, to be employed in the process according to the invention are acid activated clays. They are especially suitable for the reaction of ethylene oxide with acetone into 2,2-dimethyl-1,3-dioxolane. Especially important clays are those of the montmorillonite series, such as montmorillonite, beidellite, nontronite, hectorite, saponite and saucanite. Acid activated clays are the clays which have been treated with mineral acids, such as hydrochloric acid or sulphuric acid. The acid activated clays are prepared by mixing crushed raw material with water to form a slurry to which the mineral acid amounting to about 35% of the total dry weight of the clay is added. The mixture is then treated with live steams for 5 to 6 hours, after which the whole mixture is dumped into fresh water and then washed, until it is substantially free of acids.

The mol ratio of acetone to ethylene oxide may range from 1:1 to 5:1, although higher ranges are not excluded.

Since the reaction of acetone with ethylene oxide is exothermic, the temperature is regulated by refluxing the acetone. At a later stage a somewhat higher temperature than the boiling temperature of acetone is suitable. The reaction temperature generally range from 30 °C to 80 °C, preferably from 50 °C to 65 °C.

In the hydrolyzing step either the raw mixture or purified 2,2-dimethyl-1,3-dioxolane may be used. Since 2,2-dimethyl-1,3-dioxolane boils at 92 °C, the compound can be purified by distillation. Hydrolysis of the 2,2-dimethyl-1,3-dioxolane in the second step is done in the presence of a substantially stoichiometric amount of water with the aid of an acid activated clay or an ion-exchange resin. About the stoichiometric amount of water is sufficient to obtain substantial hydrolysis of the 2,2-dimethyl-1,3-dioxolane into monoethylene glycol and acetone. During this reaction the formed acetone is distilled off and any unreacted ketal may be recycled.

EXAMPLES**A. Preparation of the cyclic ketal 2,2-dimethyl-1,3-dioxolane**

For the preparation of the ketal a glass, double walled reactor with a content of 2 litre was used provided with a glass stirrer and four glass joints for placing a thermocouple well, two gas inlet tubes and a reflux condenser. One of the gas inlet tubes was used for a slight nitrogen purge, the other one (both made from glass) being connected via a ball joint connection to the steel exit tube of a syringe pump (type LC-5000 from Isco Inc). containing the stock of liquid ethylene oxide under a pressure of 15-20 bar. Water was circulated around the wall of the glass reactor via a thermostatted bath for heating/cooling purposes.

The reactor was charged with 1695 ml (1340 g, 23.1 mol) of acetone and 34 g of K10 catalyst (acid activated montmorillonite, supplied by Sued-Chemie) and the suspension thus obtained was heated under stirring to 54 °C. At this stage the introduction of liquid ethylene oxide from the syringe pump was started, an amount of 305 ml (269 g, 6.1 mol) being introduced in the course of 45 minutes. By means of a valve in the steel exit tube of the Isco pump a pressure in the latter of 15-20 bar was maintained to keep the ethylene oxide in the liquid form. At 54 °C the formation of the cyclic ketal started immediately, the heat of reaction being removed via refluxing of the excess of acetone; the boiling point of reaction mixture gradually increased over the period of ethylene oxide addition (due to formation of the cyclic ketal, bp. 92 °C) from 56 °C to 62 °C.

After a post reaction of 15 minutes the reaction mixture was cooled and the K10 catalyst allowed to settle after which the supernatant liquid was sucked by slight vacuum from the catalyst layer. Then a new batch of acetone was charged to the reactor and the reaction repeated, the amounts of acetone and ethylene oxide being the same as described above with the original amount of K10 catalyst, which was thus reused.

Twelve batch reactions were carried out according to the procedure described above. The combined product (18.42 kg) in which no ethylene oxide could be detected had the following composition (GC analysis):

acetone	60.7 %w
ketal	38.9 %w
monoethyleneglycol	0.1 %w
diethyleneglycol	0.2 %w
1,4-dioxane	0.1 %w

B. Hydrolysis of the cyclic ketal

Two options were carried out by addition of water and acid catalyst either to the reaction mixture prepared under A or to the ketal isolated prior to the hydrolysis step.

The equipment used was a 10 l distillation flask provided with a fractionating Vigreux column of approx. 6 m length having 15-20 theoretical plates.

1. Hydrolysis of the reaction mixture

Into the distillation flask were present the following components:

reaction mixture prepared according to method under A	6000 g
water	452 g water/ketal mol ratio 1.09
Amberlyst 15	10 g

The acid ion exchange resin catalyst Amberlyst 15 (styrene-divinylbenzene copolymer containing sulphonic acid groups) was wrapped in glass cloth and placed into the distillation flask in order to prevent crushing during boiling of the reaction mixture. The excess of acetone as well as the amount of acetone from the hydrolysis of the ketal was distilled at atmospheric pressure. When the bulk of the ketal had been converted into glycol and acetone the boiling point started to rise sharply but was maintained at 110 °C to protect the catalyst. Further conversion of the ketal was then carried out under a pressure of 250 mbar until

distillation of the acetone stopped. The following mass balance was obtained:

	In (g)	Out (g)
ketal	: 2352 (23.1 mol)	31.8 (0.3 mol)
monoethylene glycol:	17.4 (0.3 mol)	1414.7 (22.8 mol)
total mass	: 6452	6445

Thus, the total mass balance was 99.9% and the mol balance of MEG + ketal 98.7%.

This result points to a catalyst consumption of less than 1% by weight on monoethylene glycol.

2. Hydrolysis of the cyclic ketal isolated from the reaction mixture

An amount of 5212 g of the reaction mixture (prepared according to method under A) was distilled in order to isolate the bulk of the ketal. A distilled fraction of 2036 g containing 89.6 %w ketal (17.88 mol), 10.3 %w acetone and about 0.2 %w 1,4-dioxane was combined with 355 g H₂O (mol ratio H₂O/ketal 1.1) and 20 g of Amberlyst 15 (wrapped in glass cloth). Because the liquid mixture consisted of two phases, it was homogenized at room temperature by a shift of equilibrium before being introduced with the catalyst in the distillation flask.

Equilibration and distillation of the acetone (basically the same procedure as applied in the first hydrolysis under 1) yielded ultimately a residue containing 1091 g monoethylene glycol (17.6 mol) and traces of acetone, unconverted ketal and 1,4-dioxane but no heavy glycols. The mol balance on monoethylene glycol and total unconverted ketal (0.12 mol) was 99%, the same figure being found for the total mass balance.

Claims

1. A two-step reaction process for converting ethylene oxide with high selectivity into monoethylene glycol which comprises firstly reacting ethylene oxide with acetone to 2,2-dimethyl-1,3-dioxolane and secondly hydrolyzing the 2,2-dimethyl-1,3-dioxolane with a substantially stoichiometric amount of water to monoethylene glycol, both steps requiring the presence of a solid acid catalyst.
2. A process as claimed in claim 1, wherein the catalyst used in the first step is an acid activated clay.
3. A process as claimed in claim 1 or 2, wherein the mole ratio of acetone/ethylene oxide ranges from 1:1 to 5:1.
4. A process as claimed in one or more of the claims 1-3, wherein the reaction temperature ranges from 30 °C to 80 °C.
5. A process as claimed in one or more of the claims 1-4, wherein the 2,2-dimethyl-1,3-dioxolane is distilled off.
6. A process as claimed in one or more of the claims 1-5, wherein the 2,2-dimethyl-1,3-dioxolane is hydrolyzed with water in the presence of an ion-exchange resin or an acid activated clay.
7. A process as claimed in claim 6 wherein the acetone is distilled off during the reaction.

Patentansprüche

1. Ein Zweistufen-Reaktionsverfahren zum Umwandeln von Ethylenoxid mit hoher Selektivität in Monoethylenglykol, welches erstens das Umsetzen von Ethylenoxid mit Aceton zu 2,2-Dimethyl-1,3-dioxolan und zweitens das Hydrolysieren des 2,2-Dimethyl-1,3-dioxolans mit einer im wesentlichen stöchiometrischen Menge an Wasser zu Monoethylenglykol umfaßt, wobei für beide Verfahrensstufen die Gegenwart eines festen sauren Katalysators notwendig ist.

distillation of the acetone stopped. The following mass balance was obtained:

	In (g)	Out (g)
ketal	: 2352 (23.1 mol)	31.8 (0.3 mol)
monoethylene glycol:	17.4 (0.3 mol)	1414.7 (22.8 mol)
total mass	: 6452	6445

Thus, the total mass balance was 99.9% and the mol balance of MEG + ketal 98.7%.

This result points to a catalyst consumption of less than 1% by weight on monoethylene glycol.

2. Hydrolysis of the cyclic ketal isolated from the reaction mixture

An amount of 5212 g of the reaction mixture (prepared according to method under A) was distilled in order to isolate the bulk of the ketal. A distilled fraction of 2036 g containing 89.6 %w ketal (17.88 mol), 10.3 %w acetone and about 0.2 %w 1,4-dioxane was combined with 355 g H₂O (mol ratio H₂O/ketal 1.1) and 20 g of Amberlyst 15 (wrapped in glass cloth). Because the liquid mixture consisted of two phases, it was homogenized at room temperature by a shift of equilibrium before being introduced with the catalyst in the distillation flask.

Equilibration and distillation of the acetone (basically the same procedure as applied in the first hydrolysis under 1) yielded ultimately a residue containing 1091 g monoethylene glycol (17.6 mol) and traces of acetone, unconverted ketal and 1,4-dioxane but no heavy glycols. The mol balance on monoethylene glycol and total unconverted ketal (0.12 mol) was 99%, the same figure being found for the total mass balance.

Claims

1. A two-step reaction process for converting ethylene oxide with high selectivity into monoethylene glycol which comprises firstly reacting ethylene oxide with acetone to 2,2-dimethyl-1,3-dioxolane and secondly hydrolyzing the 2,2-dimethyl-1,3-dioxolane with a substantially stoichiometric amount of water to monoethylene glycol, both steps requiring the presence of a solid acid catalyst.
2. A process as claimed in claim 1, wherein the catalyst used in the first step is an acid activated clay.
3. A process as claimed in claim 1 or 2, wherein the mole ratio of acetone/ethylene oxide ranges from 1:1 to 5:1.
4. A process as claimed in one or more of the claims 1-3, wherein the reaction temperature ranges from 30 °C to 80 °C.
5. A process as claimed in one or more of the claims 1-4, wherein the 2,2-dimethyl-1,3-dioxolane is distilled off.
6. A process as claimed in one or more of the claims 1-5, wherein the 2,2-dimethyl-1,3-dioxolane is hydrolyzed with water in the presence of an ion-exchange resin or an acid activated clay.
7. A process as claimed in claim 6 wherein the acetone is distilled off during the reaction.

Patentansprüche

1. Ein Zweistufen-Reaktionsverfahren zum Umwandeln von Ethylenoxid mit hoher Selektivität in Monoethylenglykol, welches erstens das Umsetzen von Ethylenoxid mit Aceton zu 2,2-Dimethyl-1,3-dioxolan und zweitens das Hydrolysieren des 2,2-Dimethyl-1,3-dioxolans mit einer im wesentlichen stöchiometrischen Menge an Wasser zu Monoethylenglykol umfaßt, wobei für beide Verfahrensstufen die Gegenwart eines festen sauren Katalysators notwendig ist.



2. Ein Verfahren, wie in Anspruch 1 beansprucht, in welchem der in der ersten Stufe eingesetzte Katalysator ein saurer aktivierter Ton ist.
3. Ein Verfahren, wie in Anspruch 1 oder 2 beansprucht, in welchem das Molverhältnis von Aceton/Ethylenoxid im Bereich von 1:1 bis 5:1 liegt.
4. Ein Verfahren, wie in einem oder mehreren der Ansprüche 1 bis 3 beansprucht, in welchem die Reaktionstemperatur im Bereich von 30 °C bis 80 °C liegt.
5. Ein Verfahren, wie in einem oder mehreren der Ansprüche 1 bis 4 beansprucht, in welchem das 2,2-Dimethyl-1,3-dioxolan abdestilliert wird.
6. Ein Verfahren, wie in einem oder mehreren der Ansprüche 1 bis 5 beansprucht, in welchem das 2,2-Dimethyl-1,3-dioxolan in Gegenwart eines Ionenaustauscherharzes oder eines sauren aktivierten Tons mit Wasser hydrolysiert wird.
7. Ein Verfahren, wie in Anspruch 6 beansprucht, in welchem das Aceton während der Reaktion abdestilliert wird.

Revendications

1. Un procédé de réaction en deux étapes pour convertir l'oxyde d'éthylène avec un rendement élevé en monoéthylène glycol, procédé selon lequel on fait réagir d'abord de l'oxyde d'éthylène avec de l'acétone pour obtenir du 2,2-diméthyl-1,3-dioxolane et, en second lieu, on fait réagir le 2,2-diméthyl-1,3-dioxolane avec une quantité pratiquement stoechiométrique d'eau pour obtenir le monoéthylène glycol, les deux étapes exigeant la présence d'un catalyseur acide solide.
2. Un procédé tel que revendiqué dans la revendication 1, dans lequel le catalyseur utilisé dans la première étape est une argile acide activée.
3. Un procédé tel que revendiqué dans la revendication 1 ou 2, dans lequel le rapport molaire de l'acétone/oxyde d'éthylène se situe dans la gamme de 1:1 à 5:1.
4. Un procédé tel que revendiqué dans une ou plus d'une des revendications 1 à 3, dans lequel la température de réaction se situe dans la gamme de 30 °C à 80 °C.
5. Un procédé tel que revendiqué dans une ou plus d'une des revendications 1 à 4, dans lequel le 2,2-diméthyl-1,3-dioxolane est chassé par distillation.
6. Un procédé tel que revendiqué dans une ou plus d'une des revendications 1 à 5, dans lequel le 2,2-diméthyl-1,3-dioxolane est hydrolysé avec de l'eau en présence d'une résine échangeuse d'ions ou d'une argile acide activée.
7. Un procédé tel que revendiqué dans la revendication 6, dans lequel l'acétone est chassée par distillation pendant la réaction.

