

Description

This invention relates to a deflection yoke for use with a cathode ray tube.

Magnetic deflection is normally used in cathode ray tubes such as television picture tubes or the like having an electric gun provided to emit electrons toward a fluorescent screen. It is the common practice to deflect an electron beam in a cathode ray tube by a deflection yoke provided around the neck portion of the cathode ray tube. The deflection yoke has a coil portion wound to have a uniform thickness so as to produce a uniform magnetic field deflecting the electron beam in the cathode ray tube. The uniform magnetic field provides a good beam-focusing performance; however, it tends to cause picture distortion at and near the edges of the screen of the cathode ray tube. In order to correct the picture distortion, the deflection yoke has another coil portion wound to have a non-uniform thickness so as to produce a pincushion magnetic field deflecting the electron beam in the cathode ray tube. However, the pincushion magnetic field tends to degrade the beam-focusing performance. Therefore, the conventional beam deflector cannot correct the picture distortion to a sufficient degree without the significant sacrifice of the beam-focusing performance.

JP-A-61 214336 discloses the use of magnetic parts to convert part of the vertical magnetic field into a pincushion magnetic field. JP-A-57-151155 discloses the provision of a convergence-free deflection unit with an auxiliary coil on the screen side to compensate for the fourth vertical distortion. JP-A-2-155151 discloses the use of permanent magnets at the screen side of the yoke for creating a pincushion magnetic field.

Therefore, a main object of the invention is to provide an improved deflection yoke which can correct the picture distortion to a sufficient extent and maintain the beam-focusing performance without significant sacrifice.

There is provided, in accordance with the invention, a deflection yoke for deflecting an electron beam in a cathode ray tube, the deflection yoke having a diverging portion for positioning over a diverging portion of the CRT and diverging forwardly from a neck portion positioned to the rear of said diverging portion for positioning over the neck of the CRT, a deflection coil for producing a deflecting magnetic field and extending from the neck portion forwardly over the diverging portion towards a front end, characterised in that said deflection coil has a first portion wound extending forwardly from the neck portion over the diverging portion to produce a uniform magnetic field and a second portion wound only at said front end to produce a pincushion magnetic field.

The deflection yoke may include horizontal and vertical deflection coils. At least one of said horizontal

and vertical deflection coils has a first portion wound to have a uniform thickness substantially over the full length of the deflection yoke so as to produce a uniform deflecting magnetic field in the neck portion and a second portion wound to have a non-uniform thickness at the front end so as to produce a pincushion deflecting magnetic field.

The deflection yoke may include a bobbin having a deflection coil wound thereon for producing a deflecting magnetic field in the neck portion. The bobbin has a front end close to the screen and a front flange formed at the front end of the bobbin. The deflection coil has a first portion wound to have a uniform thickness on the bobbin except for the front flange so as to produce a uniform magnetic field and a second portion wound to have a non-uniform thickness on the front flange so as to produce a pincushion magnetic field.

This invention will be described by way of example with reference to the following description taken in connection with the accompanying drawings, in which:

Fig. 1 is a partially cutaway perspective view showing an inner wire wound bobbin embodying the invention;

Fig. 2 is a schematic elevational view of the wire wound bobbin of Fig. 1;

Fig. 3 is a schematic side view of the wire wound bobbin of Fig. 1;

Fig. 4 is a sectional view taken along the lines A-A of Fig. 3;

Fig. 5 is a sectional view taken along the lines B-B of Fig. 3

Fig. 6 is an exploded perspective view showing a conventional deflection yoke;

Fig. 7 is a sectional view taken along the lines a-a of Fig. 6;

Fig. 8 is a sectional view taken along the lines b-b of Fig. 6;

Fig. 9 is a diagram showing a deflecting magnetic field produced in the section of Fig. 7; and

Fig. 10 is a diagram showing a deflecting magnetic field produced in the section of Fig. 8.

Prior to the description of the preferred embodiment of the present invention, the prior art deflection yoke of Figs 6-8 is briefly described in order to specifically point out the difficulties attendant thereon.

The prior art deflection yoke 10 of Fig. 6 is of a saddle shape including an inner wire wound bobbin 12 mounted around the neck portion of a cathode ray tube (not shown), an outer wire wound bobbin 14 mounted around the inner wire wound bobbin 12, and a core 16 composed of two core parts 16a and 16b interconnected to cover the outer periphery of the outer wire wound bobbin 12. The inner bobbin 12 is composed of two interconnected bobbin parts 12a and 12b and it has a cylindrical rear portion having a rear opening defined by an annular rear end flange, and

a diverging front portion extending away from the cylindrical rear portion toward the fluorescent screen (not shown) of the cathode ray tube. The diverging front portion has a front opening defined by an annular front end flange. The front opening is greater in diameter than the diameter of the rear opening. A conductor is wound and supported on the inner surface of the inner bobbin 12 to form a horizontal deflection coil 13. The horizontal deflection coil 13 produces a horizontal deflection magnetic field to deflect the electron beam horizontally in the neck portion of the cathode ray tube when energized. Similarly, the outer bobbin 14 is composed of two bobbin parts 14a and 14b interconnected to cover the outer periphery of the inner bobbin 12. A conductor is wound and supported on the inner surface of the outer bobbin 14 to form a vertical deflection coil 15. The vertical deflection coil 15 produces a vertical deflection magnetic field to deflect the electron beam vertically in the neck portion of the cathode ray tube when energized.

The horizontal deflection coil 13 has a first portion wound to have a uniform thickness on the cylindrical rear portion, as shown in Fig. 7. This first portion will produce a uniform magnetic field in the cathode ray tube, as shown in Fig. 9. Although such a uniform magnetic field is effective to provide a good beam-focusing performance, it will cause picture distortion on and near the edge of the screen of the cathode ray tube. In order to correct the picture distortion, the horizontal deflection coil 13 has a second portion wound to have a non-uniform thickness on the diverging front portion, as shown in Fig. 8. This second portion will produce a pincushion magnetic field in the cathode ray tube, as shown in Fig. 10. However, the pincushion magnetic field will produce forces to deform the electron beam into the squeezed shape so as to degrade the beam-focusing performance. For this reason, the prior art deflection yoke cannot correct the picture distortion to a sufficient degree without the significant sacrifice of the beam-focusing performance.

Referring to Figs. 1 to 3, there is shown a deflection yoke embodying the invention. The deflection yoke has an inner wire wound bobbin 20. The inner wire wound bobbin 20 includes two interconnected bobbin parts 20a and 20b. The inner bobbin 20 has a cylindrical rear neck portion 21 and a diverging front portion 23 extending away from the cylindrical rear neck portion 21 toward the fluorescent screen (not shown) of the cathode ray tube. The cylindrical rear portion 21 is formed at its rear end with an annular rear flange 22 which defines a rear opening. The diverging front portion 23 is formed at its front end with a front flange 24 which defines a front opening greater in diameter than the diameter of the rear opening. The front flange 24 is elongated in the x-direction (horizontal direction) to provide a horizontal length longer than the vertical length of the front flange 24,

as best shown in Fig. 2.

A conductor is wound to produce a horizontal deflection coil 25 which has a first portion wound to have a uniform thickness (x-direction) on the inner bobbin 20 to produce a uniform magnetic field in the cathode ray tube when energized. The first portion of the horizontal deflection coil 25 expands substantially over the full length (z-direction) of the inner bobbin 20. That is, the horizontal deflection coil 25 has a uniform thickness substantially over the full length of the cylindrical rear portion 21. Fig. 4 shows the uniform thickness of the horizontal deflection coil 25 in the section taken along the lines A-A of Fig. 3. The horizontal deflection coil 25 has a uniform thickness substantially over the full length of the diverging front portion 23 of the inner bobbin 20. Fig. 5 shows the uniform thickness of the horizontal deflection coil 25 in the section taken along the lines B-B of Fig. 3. The horizontal deflection coil 25 also has a second portion wound to have a non-uniform thickness (x-direction) on the front flange 24 so as to produce a pincushion magnetic field when energized. The thickness, that is, the x-direction length, of the second portion of the horizontal deflection coil 25 decreases as going away from the line at which the inner bobbin parts 20a and 20b are connected.

A number of guide projections 26 are formed in spaced relation to each other on the inner surface of the inner bobbin 20. Each of the guide projections 26 has a rear hook projection 27 formed on the rear surface of the rear flange 22 and a front hook projection 28 formed on the front surface of the front flange 24. A rear annular wall 30 is provided on the rear hook projections 27 to form grooves 31 for receipt of a number of turns of the horizontal deflection coil 25. Similarly, a front wall 32 is provided on the front hook projections 28 to form grooves 33 for receipt of a number of turns of the horizontal deflection coil 25.

The other part of the deflection yoke is substantially the same as described in connection with Fig. 6 and will not be described further.

It is apparent from the foregoing that the deflection yoke of the invention includes a deflection coil 25 which produces a deflecting magnetic field to deflect the electron beam in the cathode ray tube. The deflection coil has a first portion wound to have a uniform thickness substantially over the full length of the deflection coil so as to produce a uniform magnetic field when energized and a second portion wound to have a non-uniform thickness only at the front end of the deflection coil so as to produce a pincushion magnetic field. Thus, the electron beam emitted from the electron gun toward the screen is subject first to the influence of the uniform magnetic field produced by the first portion of the deflection coil and then to the influence of the pincushion magnetic field produced by the second portion of the deflection coil. Under the influence of the uniform magnetic field, the electron

beam is deflected without any shape deformation. The pincushion magnetic field is effective to correct the picture distortion caused by the influence of the uniform magnetic field. The pincushion magnetic field tends to deform the shape of the electron beam. The degree to which the electron beam is deformed is dependent on the distance of the screen from the position at which the electron beam is subject to the influence of the pincushion magnetic field. Since the second portion is positioned only at the front end of the deflection coil, that is, at a position as close to the screen of the cathode ray tube as possible, the deflection coil of the invention is effective to correct the picture distortion to a sufficient extent and maintain the beam-focusing performance without significant sacrifice.

Although the invention has been described in connection with a deflection coil having a second portion extending in the x-direction to have a non-uniform thickness, it is to be understood that the second portion is not limited to this arrangement as long as it can produce a pincushion magnetic field at the front end of the deflection coil. Although the invention has been described in connection with the inner wire wound bobbin of the deflection yoke, it is to be noted the invention is equally applicable to the outer wire wound bobbin of the deflection yoke to correct picture distortion at or near the left and right edges of the screen of the cathode ray tube while maintaining the beam-focusing performance without significant sacrifice.

While the invention has been described in connection with a specific embodiment thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all alternatives, modifications and variations that fall within the scope of the appended claims.

Claims

1. A deflection yoke for deflecting an electron beam in a cathode ray tube (CRT), the deflection yoke having a diverging portion (23) for positioning over a diverging portion of the CRT and diverging forwardly from a neck portion (21) positioned to the rear of said diverging portion (23) for positioning over the neck of the CRT, a deflection coil (25) for producing a deflecting magnetic field and extending from the neck portion (21) forwardly over the diverging portion (23) towards a front end, characterised in that said deflection coil (25) has a first portion wound extending forwardly from the neck portion (21) over the diverging portion (23) to produce a uniform magnetic field and a second portion wound only at said front end to produce a pincushion magnetic field.

2. A deflection yoke according to claim 1, wherein said first portion of the deflection coil (25) does not extend to said front end.
3. A deflection yoke according to claim 1, including horizontal and vertical deflection coils (25) and at least one of said horizontal and vertical deflection coils has said first portion wound to have a uniform thickness substantially over the full length of said deflection yoke so as to produce a uniform deflecting magnetic field in said neck portion (21) and said second portion wound to have a non-uniform thickness at said front end (24,32,33) so as to produce a pincushion deflecting magnetic field.
4. A deflection yoke according to claim 1, 2 or 3, including a bobbin (20) having the deflection coil (25) wound thereon said bobbin (20) having a front flange (24) formed at said front end thereof, said deflection coil (25) having said second portion wound on said front flange (24).
5. A deflection yoke as claimed in claim 4, wherein said bobbin (20) has a diverging front portion (23) formed at said front end with said front flange (24), said front flange (24) being elongated in a horizontal direction to have a horizontal length longer than a vertical length.

Patentansprüche

1. Ablenkjoch zur Ablenkung eines Elektronenstrahls in einer Kathodenstrahlröhre (CRT) aufweisend einen auseinanderlaufenden Abschnitt (23) zur Positionierung über einem auseinanderlaufenden Abschnitt der Kathodenstrahlröhre, der von einem Halsabschnitt (21) am hinteren Teil des auseinanderlaufenden Abschnitts (23) zur Positionierung über dem Hals der Kathodenstrahlröhre nach vorne auseinanderläuft, und eine Ablenkspule (25) zur Erzeugung eines Ablenkmagnetfeldes, die sich von dem Halsabschnitt (21) über den auseinanderlaufenden Abschnitt (23) zu einem vorderen Ende erstreckt, dadurch gekennzeichnet, daß die Ablenkspule (25) einen ersten Abschnitt aufweist, der von dem Halsabschnitt (21) sich über den auseinanderlaufenden Abschnitt (23) erstreckend gewickelt ist, um ein gleichmäßiges Magnetfeld zu erzeugen, und einen zweiten Abschnitt aufweist, der nur an dem vorderen Ende gewickelt ist, um ein kissenförmiges Magnetfeld zu erzeugen.
2. Ablenkjoch nach Anspruch 1, wobei sich der erste Abschnitt der Ablenkspule (25) nicht bis zum vorderen Ende erstreckt.



beam is deflected without any shape deformation. The pincushion magnetic field is effective to correct the picture distortion caused by the influence of the uniform magnetic field. The pincushion magnetic field tends to deform the shape of the electron beam. The degree to which the electron beam is deformed is dependent on the distance of the screen from the position at which the electron beam is subject to the influence of the pincushion magnetic field. Since the second portion is positioned only at the front end of the deflection coil, that is, at a position as close to the screen of the cathode ray tube as possible, the deflection coil of the invention is effective to correct the picture distortion to a sufficient extent and maintain the beam-focusing performance without significant sacrifice.

Although the invention has been described in connection with a deflection coil having a second portion extending in the x-direction to have a non-uniform thickness, it is to be understood that the second portion is not limited to this arrangement as long as it can produce a pincushion magnetic field at the front end of the deflection coil. Although the invention has been described in connection with the inner wire wound bobbin of the deflection yoke, it is to be noted the invention is equally applicable to the outer wire wound bobbin of the deflection yoke to correct picture distortion at or near the left and right edges of the screen of the cathode ray tube while maintaining the beam-focusing performance without significant sacrifice.

While the invention has been described in connection with a specific embodiment thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all alternatives, modifications and variations that fall within the scope of the appended claims.

Claims

1. A deflection yoke for deflecting an electron beam in a cathode ray tube (CRT), the deflection yoke having a diverging portion (23) for positioning over a diverging portion of the CRT and diverging forwardly from a neck portion (21) positioned to the rear of said diverging portion (23) for positioning over the neck of the CRT, a deflection coil (25) for producing a deflecting magnetic field and extending from the neck portion (21) forwardly over the diverging portion (23) towards a front end, characterised in that said deflection coil (25) has a first portion wound extending forwardly from the neck portion (21) over the diverging portion (23) to produce a uniform magnetic field and a second portion wound only at said front end to produce a pincushion magnetic field.

2. A deflection yoke according to claim 1, wherein said first portion of the deflection coil (25) does not extend to said front end.

3. A deflection yoke according to claim 1, including horizontal and vertical deflection coils (25) and at least one of said horizontal and vertical deflection coils has said first portion wound to have a uniform thickness substantially over the full length of said deflection yoke so as to produce a uniform deflecting magnetic field in said neck portion (21) and said second portion wound to have a non-uniform thickness at said front end (24,32,33) so as to produce a pincushion deflecting magnetic field.

4. A deflection yoke according to claim 1, 2 or 3, including a bobbin (20) having the deflection coil (25) wound thereon said bobbin (20) having a front flange (24) formed at said front end thereof, said deflection coil (25) having said second portion wound on said front flange (24).

5. A deflection yoke as claimed in claim 4, wherein said bobbin (20) has a diverging front portion (23) formed at said front end with said front flange (24), said front flange (24) being elongated in a horizontal direction to have a horizontal length longer than a vertical length.

Patentansprüche

1. Ablenkjoch zur Ablenkung eines Elektronenstrahls in einer Kathodenstrahlröhre (CRT) aufweisend einen auseinanderlaufenden Abschnitt (23) zur Positionierung über einem auseinanderlaufenden Abschnitt der Kathodenstrahlröhre, der von einem Halsabschnitt (21) am hinteren Teil des auseinanderlaufenden Abschnitts (23) zur Positionierung über dem Hals der Kathodenstrahlröhre nach vorne auseinanderläuft, und eine Ablenkspule (25) zur Erzeugung eines Ablenkmagnetfeldes, die sich von dem Halsabschnitt (21) über den auseinanderlaufenden Abschnitt (23) zu einem vorderen Ende erstreckt, dadurch gekennzeichnet, daß die Ablenkspule (25) einen ersten Abschnitt aufweist, der von dem Halsabschnitt (21) sich über den auseinanderlaufenden Abschnitt (23) erstreckend gewickelt ist, um ein gleichmäßiges Magnetfeld zu erzeugen, und einen zweiten Abschnitt aufweist, der nur an dem vorderen Ende gewickelt ist, um ein kissenförmiges Magnetfeld zu erzeugen.
2. Ablenkjoch nach Anspruch 1, wobei sich der erste Abschnitt der Ablenkspule (25) nicht bis zum vorderen Ende erstreckt.



3. Ablenkjoch nach Anspruch 1, aufweisend horizontale und vertikale Ablenkspulen (25), wobei der erste Abschnitt wenigstens einer der horizontalen und vertikalen Ablenkspulen so gewickelt ist, daß er eine gleichmäßige Dicke über im wesentlichen die gesamte Länge des Ablenkjochs aufweist, um ein gleichmäßiges Ablenkmagnetfeld im Halsabschnitt (21) zu erzeugen, und der zweite Abschnitt so gewickelt ist, daß er eine ungleichmäßige Dicke am vorderen Ende (24, 32, 33) aufweist, um ein kissenförmiges Ablenkmagnetfeld zu erzeugen.
4. Ablenkjoch nach Anspruch 1, 2 oder 3, aufweisend einen Spulenkörper (20), auf den die Ablenkspule (25) gewickelt ist und einen an dessen vorderem Ende ausgebildeten Vorderflansch (24), auf den der zweite Abschnitt der Ablenkspule (25) gewickelt ist.
5. Ablenkjoch nach Anspruch 4, wobei der Spulenkörper (20) einen am vorderen Ende mit dem Vorderflansch (24) ausgebildeten auseinanderlaufenden Vorderabschnitt (23) aufweist und der Vorderflansch (24) sich in horizontaler Richtung so erstreckt, daß er eine größere horizontale als vertikale Länge aufweist.

5

10

15

20

25

Revendications

30

1. Bobine de déviation pour dévier un faisceau d'électrons dans un tube à rayons cathodiques (CRT), la bobine de déviation possédant une partie divergente (23) en vue d'un positionnement au-dessus d'une partie divergente du CRT et divergeant vers l'avant depuis un col (21) disposé à l'arrière de ladite partie divergente (23) en vue d'un positionnement au-dessus du col du CRT, une bobine de déviation (25) pour créer un champ magnétique de déviation et s'étendant depuis le col (21) vers l'avant au-dessus de la partie divergente (23) vers une extrémité antérieure, caractérisée en ce que ladite bobine de déviation (25) possède une première partie de bobine s'étendant vers l'avant depuis le col (21) sur la partie divergente (23) pour créer un champ magnétique uniforme et une seconde partie bobinée uniquement à ladite extrémité antérieure pour créer un champ magnétique en coussin.
2. Bobine de déviation selon la revendication 1, dans laquelle ladite première partie de la bobine de déviation (25) ne s'étend pas jusqu'à ladite extrémité antérieure.
3. Bobine de déviation selon la revendication 1, comprenant des bobines de déviation horizontale

35

40

45

50

55

5

et verticale (25) et au moins l'une desdites bobines de déviation horizontale et verticale possède ladite première partie bobinée présentant une épaisseur uniforme sensiblement sur toute la longueur de ladite bobine de déviation de manière à créer un champ magnétique de déviation uniforme dans ladite partie de col (21) et ladite seconde partie bobinée présentant une épaisseur non uniforme à ladite extrémité antérieure (24, 32, 33), de manière à créer un champ magnétique de déviation en coussin.

4. Bobine de déviation selon la revendication 1, 2 ou 3, comprenant une carcasse (20) sur laquelle est bobinée la bobine de déviation (25), ladite carcasse (20) ayant un rebord antérieur (24) formé sur ladite extrémité antérieure de celle-ci, ladite bobine de déviation (25) ayant ladite seconde partie bobinée sur ledit rebord antérieur (24).

5. Bobine de déviation selon la revendication 4, dans laquelle ladite carcasse (20) possède une partie antérieure divergente (23) formée à ladite extrémité antérieure avec ledit rebord antérieur (24), ledit rebord antérieur (24) étant allongé dans une direction horizontale pour présenter une longueur horizontale supérieure à une longueur verticale.

