

Title: HIGH INTENSITY DISCHARGE LAMP DEVICE

This invention relates generally to high intensity discharge lamp devices and, more particularly, to a high intensity discharge lamp which has omitted mercury from
5 filled material within an arc tube.

High intensity discharge lamps have been widely and increasingly employed, in addition to the field of illumination, in such further fields of nonillumination as visual, business and office machines and devices,
10 visual projecting apparatus and so on.

Generally, a high intensity discharge lamp device is formed by providing an arc tube within a light transmissive envelope while enclosing in the arc tube mercury, rare gas and metal halides, and providing to
15 both ends of the arc tube a pair of electrodes which are connected preferably through a metal foil to lead wires to which an external circuit is connectable. With such a high intensity discharge lamp device, it is possible to provide a white light source showing high efficiency
20 and high colour rendering. Further, while high intensity lamps have been increasingly utilized in recent types of visual, business and office machines and devices, visual projecting apparatus and so on, in these cases it has been a common prerequisite for such high
25 intensity discharge lamp devices to be excellent in the reproducibility of luminous colour.

There has been a demand, on the other hand, for the discharge lamp to light with the same lamp voltage as that of existing lamps to enable existing light circuits
30 to be utilizable and, for this purpose, there has been a tendency, in the case where the arc tube is small, to

increase the amount of mercury within the arc tube. When the filled mercury amount increases, however, a problem arises in that the luminous colour reproducibility deteriorates.

5 In view of the above, a high intensity discharge lamp expected to be improved in the colour rendering property by omitting mercury has been provided. For example, in U.S. Patent No. 4,810,938 by P. D. Johnson et al, a high intensity discharge lamp employed a metal
10 halide and Xe gas as filling materials in the light transmissive arc discharge tube but omitted mercury therefrom. According to the metal halide discharge lamps of the U.S. patent which employ no mercury, it may be possible to improve the luminous colour
15 reproducibility to some extent because of the absence of mercury, but they still involve a drawback in attaining sufficiently such colour reproducibility that is demanded in the field of nonillumination of visual machines and devices and so on, since although mercury
20 is omitted, there is no intention of remarkably improving the colour reproduction triangle in the chromaticity coordinates.

 A primary aim of the present invention is, therefore, to provide a high intensity discharge lamp
25 device which has eliminated the foregoing drawback, and which can satisfy the luminous colour reproducibility demanded in such nonillumination fields as visual and business or office machines and devices, visual projecting apparatus and so on by sufficiently enlarging
30 the colour reproduction triangle presented in the chromaticity coordinates.

According to one aspect of the present invention, there is provided a high intensity discharge lamp device comprising an arc tube enclosing therein an arc discharge material consisting solely of a rare gas, Li
5 halide and two or more metal halides selected from the group consisting of Tl halide, In halide, Al halide, Sn halide, Na halide and mixtures of said metal halides including said Li halide, in the absence of mercury.

Another aspect of the present invention provides a
10 high intensity discharge lamp device comprising an electrodeless arc tube for enclosing therein an arc discharge material consisting solely of a rare gas, Al halide and two or more metal halides selected from the group consisting of Li halide, Tl halide, In halide, Sn
15 halide, Na halide and mixtures of said metal halides including Al halide, in the absence of mercury.

Said second and third halides will form complex halides with the Li halide.

The invention will now be described in detail, by
20 way of example, with reference to the drawings, in which:-

FIGURE 1 is a vertically sectioned view of one embodiment of a high intensity discharge lamp device according to the present invention;

25 FIG. 2 shows an emission spectrum of the lamp device of FIG. 1 according to the present invention;

FIG. 3 shows an emission spectrum of a device according to a comparative example in which mercury is added to the device of FIG. 1;

30 FIG. 4 is a diagram showing a distribution of spectral transmittance with a red colour filter;

FIG. 5 is a diagram showing a distribution of spectral transmittance with a green colour filter;

FIG. 6 is a diagram showing a distribution of spectral transmittance with a blue colour filter;

5 FIG. 7 is a diagram showing a colour reproduction range of the lamp device of FIG. 1 in comparison with that of a comparative example with mercury employed;

FIG. 8 is an emission spectrum of the high intensity discharge lamp device according to the present
10 invention;

FIG. 9 is a schematic block circuit diagram of a high frequency lamp lighting circuit employed in the present invention; and

FIG. 10 is a schematic block circuit diagram of a
15 high frequency lamp lighting circuit employed in a comparative example.

While the present invention shall now be explained with reference to respective examples described, it should be appreciated that the intention is not to limit
20 the invention only to such examples but rather to cover all alterations, modifications and equivalent arrangements possible within the scope of appended claims.

Example 1:

25 Referring to FIG. 1, it is shown a high intensity discharge lamp device according to the present invention, in which the lamp device 10 comprises an arc tube 11 formed by a quartz glass and provided at both ends with a pair of electrodes 12 and 12a opposing each
30 other. These electrodes 12 and 12a are connected respectively to each of such metal foils 14 and 14a as molybdenum foils, preferably, which are sealed in enclosures 13 and 13a, while the metal foils 14 and 14a are electrically connected to support conductor wires 15

and 15a also functioning as a supporting member for the arc tube 11 so that the tube 11 will be mechanically fixed by the wires 15 and 15a. The support conductor wires 15 and 15a are arranged for connection to an external circuit (not shown) such as a lamp lighting circuit through a capsule 17 fitted to an end of the envelope 16.

Within the arc tube 11, 100 Torr of Xe gas and, as metal halides, LiI (9mg), TlI (1.5mg)-InI (0.5mg) are sealed. An emission spectrum of this Example is shown in FIG. 2, and, as will become clear when compared with FIG. 3 showing an emission spectrum of a lamp device in which several ten Torr of Ar in place of Xe and 40mg of mercury are added, and in which NaI (8mg) is substituted for LiI, it is possible to restrain other emission spectrum than the emission spectrum of Na (main wavelength 589nm; orange), Tl (main wavelength 535nm; green) and In (main wavelength 451nm; blue). Here, colour reproduction triangles of the lamp device according to Example 1 having such emission spectrum as shown in FIG. 2 and the comparative lamp device according to the comparative example having such emission spectrum as in FIG. 3 are given as presented on the chromaticity coordinates of FIG. 7, with vacuum-deposited film filters of red, green and blue of such spectral transmittances as shown in FIGS. 4-6 employed. In FIG. 7, it should be appreciated that a colour reproduction triangle of dotted lines denotes the comparative example, whereas the other colour reproduction triangle of solid lines denotes Example 1 of the present invention, and that the colour reproduction triangle can be remarkably enlarged according to the present invention, that is, the luminous colour reproducibility can be sufficiently improved by the present invention.

It has been also revealed that, while the comparative example requires a power of 250W for obtaining a light output of 18,000lm at white point, Example 1 requires only 230W for obtaining the same
5 light output, so that about 10% power saving can be attained.

It has been possible to attain the same result in the case where 200 Torr of Kr was enclosed instead of Xe.

10 Example 2:

Within the same arc tube 11 as in Example 1, 150 Torr of Xe gas was enclosed together with NaI (8mg), TlI (1.8mg), InI (0.6mg) and $AlCl_3$ (2mg). An emission spectrum of this Example 2 is as shown in FIG. 8 from

which it has been found that, since NaI and AlCl_3 constitute a complex halide, the emission output of Na of 589nm is increased to be 1.5 times as large as that in Example 1 with respect to the same input power.

5 Consequently, it has been found that, in order to attain the same white chromaticity coordinates as in Example 1, only a smaller amount of the input power is required so as to be 200W in contrast to 230W required in Example 1 since tube wall temperature of the arc tube 11 is
10 restrained to be low, and a remarkable power saving can be attained.

The same result could be obtained even when NaCl and NaBr or LiI, LiCl and LiBr were enclosed in the arc tube instead of NaI.

15 It has been also possible to attain the same result in the case where AlI_3 and AlBr_3 or SnCl_2 , SnI_2 and SnBr_2 were enclosed in place of AlCl_3 .

Example 3:

An electrodeless arc tube with the same filling
20 materials as in Example 2 was lit by means of a lighting circuit 20 of high frequency voltage application system as shown in FIG. 9, in which the lighting circuit 20

comprises a power supplying coil 21 wound around the arc tube itself and an impedance matching circuit 24 comprising capacitors 22 and 22a and a coil 23 connected to the power supplying coil 21. A high frequency oscillator 27 is connected to the impedance matching circuit 24 through a power amplifier 25 and a switch 26. For the purpose of comparison with this Example, lighting with a known lighting circuit of the arc tube 11 having the electrodes as in Example 2 of the arrangement of FIG. 1 was carried out, and both arc tubes thus lit were subjected to a measurement of the relationship between the lighting hour and the luminous flux.

Comparative Example 1:

Several ten Torr of Ar as well as Hg (40mg), NaI (8mg), TlI (1.5mg) and InI (0.5mg) were enclosed in the same electrodeless arc tube as in Example 3, and this arc tube was lit by means of the lighting circuit 20 of high frequency voltage application system as shown in FIG. 9. The relationship between the lighting hour and the luminous flux was measured with respect to this arc tube.

Comparative Example 2:

An arc tube having electrodes and the same filling materials therein as those in the foregoing Comparative Example 1 was lit by means of the same lighting circuit as in the foregoing Example 2, and was subjected to the measurement of the relationship between the lighting hour and the luminous flux.

Comparative Example 3:

Several ten Torr of Ar as well as Hg (40mg), NaI (14mg) and ScI_3 (4mg) were enclosed in the same arc tube having the electrodes as in FIG. 1, and this arc tube was subjected to the lighting by means of the known

lighting circuit and to the measurement of the relationship between the lighting hours and the luminous flux.

Comparative Example 4:

5 An electrodeless arc tube with the same filling materials as in Comparative Example 3 was subjected to the lighting by means of the lighting circuit of FIG. 9 employed in the foregoing Example 3 and to the measurement of the relationship between the lighting
10 hours and the luminous flux.

The rate of deterioration in the luminous flux with respect to the lighting hours as measured for the foregoing Examples 2 and 3 as well as Comparative Examples 1 to 4 is shown in the following Table:

15	Lighting Hour (h)			0	100	1,000	3,000	6,000
	Device							
20	Example 2			115	100	80	65	50
	" 3			105	100	95	90	85
	Comp. Example 1			103	100	97	92	87
	" " 2			105	100	95	85	75
	" " 3			110	100	87	70	60
	" " 4			105	100	95	90	85

25 It should be clear from the above Table that an extremely excellent discharge lamp device can be realised when such luminous materials which constitute a complex halide as in Example 3 are enclosed in the electrodeless arc tube and this arc tube is lit by a
30 lighting circuit such as shown in FIG. 9.

It has been found that, generally, the deterioration in the luminous flux occurs less in the lamp device of the electrodeless tube than in the case of a tube having electrodes. This is due to the fact that, in the arc tube having electrodes, a reaction takes place between the metal halide and quartz forming the arc tube to produce SiI , a further reaction of the thus produced SiI with tungsten W forming the electrodes takes place to produce an alloy of Si and W of a low melting point, and this alloy adheres to the tube wall so as to blacken the wall and to lower the light transmissivity. When in particular the luminous materials enclosed in the arc tube constitute the complex halide for improving the luminous efficiency, an intense reaction takes place between chlorine and the electrodes to cause a remarkable blackening to occur. The electrodeless structure of the arc tube is therefore most desirable.

On the other hand, there arises a remarkable difference in circuit simplification of the high frequency voltage application type lighting circuit, between the arc tube having the filling materials according to the present invention and the other arc tube having filling materials which include mercury as in the Comparative Examples. The lighting circuit 30 of FIG. 10 will now be explained. This lighting circuit 30 comprises an impedance matching circuit 34 connected to a power supplying coil 31 wound around the arc tube and having variable capacitors 32 and 32a and a variable inductance coil 33, a circuit 38 for detecting input/output power difference, a power amplifier 35, a switch 36 and a high frequency oscillator 37. A servomotor controlling circuit 39 is connected to the input/output power difference detecting circuit 38, so that servomotors 40, 40a and 40b for regulating the

electrostatic capacity and inductance of the variable capacitors 32 and 32a and a variable inductance coil 33 will be controlled by the circuit 39. Now, as the switch 36 is put in ON state, an electrostatic field is applied across the power supplying coil 31, breakdown is caused by this field to occur in the arc tube, and the lighting is started. As an electric field is generated along the extending direction of the coil 31 in proportion to the time variation ratio of a magnetic field generated by the current fed to the coil 31, therefore as the conductivity within the arc tube increases, the thus generated electric field causes a current to flow in the arc tube and electric power is thereby supplied to the tube. Since the filling materials in the arc tube include mercury in the case of the Comparative Examples, mercury discharge is formed and a weak emission is revealed. Thereafter, with the power consumed within the tube, the temperature of the tube wall rises, and the enclosed mercury or metal halide is gradually evaporated, and such metal emits light.

At the same time, mercury vapour pressure within the arc tube is raised to increase the impedance, and there arises gradually a deviation in the impedance matching between the source side and the arc tube side, so the power supply to the arc tube becomes difficult and the arc sometimes vanishes. In order to prevent these phenomena, the input/output power difference is constantly monitored by the input/output power difference detecting circuit 38 so that, when the detected input/output power difference approaches a level at which the turning-off takes place in the arc tube, the servomotor control circuit 39 drives the servomotors 40, 40a and 40b to regulate the

electrostatic capacity and inductance of the variable capacitors 32 and 32a and variable inductance coil 33, and the input/output power difference can be minimised. However, this circuit apparatus is extremely complicated
5 and costly.

Also in the lighting circuit of FIG. 9 for the arc tube according to the present invention, closing the switch 26 causes an electric field to be generated in proportion to the time variation ratio of the magnetic
10 field generated by a current flowing through the coil 21, and power is supplied to the arc tube with the current made to flow in the tube by the electric field, in the same manner as in the lighting circuit 30 of FIG. 10. In the arc tube according to the present invention,
15 however, the rise in the tube wall temperature causes the vapour pressure of the filling materials in the tube to rise only up to several hundred Torr and never to several thousand Torr as in the case where mercury is included.

20 In this case, too, substantially the same amount of the metal halide required for the emission as that in the presence of mercury is assured. Even when the tube wall temperature rises, the impedance in the arc tube does not vary, and no turning-off due to the impedance
25 mismatching with the power source side takes place. It will be appreciated here that the lighting circuit for the arc tube according to the present invention does not require the input/output power difference detecting circuit, servomotors and their controlling circuit, and
30 that the lighting circuit can be remarkably simplified and reduced in cost, while realising substantially the same level of function and effect as in the foregoing comparative examples.



- 13 -

CLAIMS

1. A high intensity discharge lamp device comprising an arc tube enclosing therein an arc discharge material consisting solely of a rare gas, Li halide and two or more metal halides selected from the group consisting of Tl halide, In halide, Al halide, Sn halide, Na halide and mixtures of said metal halides including said Li halide, in the absence of mercury.
 2. A device according to claim 1 wherein said arc tube is formed by a ceramics.
 3. A device according to claim 1 or claim 2, wherein said arc tube has no electrode.
 4. A high intensity discharge lamp device comprising an electrodeless arc tube for enclosing therein an arc discharge material consisting solely of a rare gas, Al halide and two or more metal halides selected from the group consisting of Li halide, Tl halide, In halide, Sn halide, Na halide and mixtures of said metal halides including Al halide, in the absence of mercury.
 5. A device according to claim 4, wherein said Al halide is AlCl_3 .
 6. A device according to any one of claims 3 to 5, wherein said arc tube is provided for high frequency lighting.
 7. A high intensity discharge lamp device substantially as described herein with reference to the drawings.
-