

TITLE OF THE INVENTION

IMAGE FORMATION APPARATUS

BACKGROUND OF THE INVENTION

The present invention relates to an image
5 formation apparatus for forming an image by printing
dots while feeding a recording medium relatively in the
direction virtually perpendicular to a linear arrange-
ment direction of recording elements of the recording
head.

10 As an example of the image formation apparatus of
this type, conventionally known is an ink-jet type line
printer. Such an ink-jet type line printer has a line
recording head consisting of a plurality of ink
chambers arranged in a main scanning direction (i.e.,
15 a line direction) and ink jet-out ports corresponding
to the ink chambers. To improve image quality, it is
necessary to form the ink jet-out ports in the same
size and shape and arrange them at the same intervals
(itches). However, in practice, it is difficult to
20 form all the ink jet-out ports identical. If the ink
jet-out ports formed in a head manufacturing step
slightly differ in size and shape, the difference in
size and shape has an effect on amounts and directions
of ink jetting out from the ink jet-out ports. The
25 resultant image is non-uniform in concentration and
thus degraded in quality.

As shown, for example, in FIG. 9, in the case

where ink is jetted out from individual ink jet-out ports 2 of the line recording head 1 in the same amount and in the same direction, ink dots 3 jetted out from the ink jet-out ports 2 will be identical.

5 Consequently, pixel dots 5 will be printed in identical size and direction on a recording paper (recording medium) 4. As a whole, the formed image is uniform in concentration.

10 In practice, however, the ink jet-out ports 2 of the line recording head 1 are formed irregularly in size and shape, as shown in FIG. 10. The ink dots 6 jetted out from the ink-jet ports 2 therefore differ in jet out amount and direction. As a result, pixel dots 7 printed on the recording paper 4 differ in size and
15 direction. If such dots are overlapped excessively, a black stripe is formed, whereas if the dots are printed at extremely larger intervals than required, a white stripe is formed. The resultant image is non-uniform in concentration.

20 To suppress image formation non-uniform in concentration as much as possible, known is a control method shown in FIG. 11. In this method, assuming that a line recording head 11 consists of, for example, eight ink-jet ports 12, the line recording head 11 is
25 controlled by moving the line recording head 11 in an arrangement direction of the ink jet-out ports 12 (recording elements) while a recording paper 14 is fed

repeatedly in a direction virtually perpendicular to the arrangement direction of the ink jet-out ports 12, multiple times. In this case, since ink dots 13 jetted out from ink jet-out ports 12 differ in jet-out amount and direction, an image is formed on the recording paper 14 (wound around a drum three times) by printing dots alternately up and down in a staggering manner while controlling movement of the line recording head 11 at every round.

In other words, at a first round of the drum, first to fourth ink jet-out ports 12₅ to 12₈ from the right hand side of the line recording head 11 are used. More specifically, the ink jet-out ports 12₅ and 12₇ are used to print dots of odd lines, whereas the ink jet-out ports 12₆ and 12₈ are used to print dots of even lines. At a second round of the drum, the line recording head 11 is slid rightward by four pitches of the ink jet-out ports. At this time, all ink jet-out ports 12₁ to 12₈ of the line recording head 11 are used. More specifically, dots of odd lines are printed by the ink jet-out ports 12₂, 12₄, 12₆, 12₈, whereas dots of even lines are printed by the ink jet-out ports 12₁, 12₃, 12₅, 12₇. At a final round (third round), the line recording head 11 is slid further rightward by four pitches of ink jet-out ports. In this case, first to fourth ink jet-out ports 12₁-12₄ from the lefthand side are used. That is, the ink jet-out ports 12₁ and

12₃ are used for printing dots of odd lines, whereas the ink jet out-ports 12₂ and 12₄ are used to print dots of even lines.

5 In the recording method of this type, if the ink jet-out ports 12₁-12₈ are irregularly formed in size and shape, the effect of the irregularity in size and shape on the image formed on the recording paper 14 is reduced in half. As a result, the black and white stripes as shown in FIG. 10 are not visible clearly, so
10 that image formation non-uniform in concentration can be suppressed.

Furthermore, another control method is known which is concerned with increasing a resolution. In the control method, the line recording head 11 is slid in
15 the arrangement direction of the ink jet-out ports 12 by L/K (L is an arrangement interval of the ink jet-out ports 12), while the recording paper 14 is repeatedly fed in the direction virtually perpendicular to the arrangement direction of the ink jet-out ports 12,
20 multiple times. In the case where the recording paper 14 is wound around the drum twice, pixel dots 15 (indicated by hatched lines declining rightward in the figure) are printed on the recording paper 14 at a first round of the drum, as shown in FIG. 12. At the
25 second round, the line recording head 11 is slid rightward by L/2 (L is an arrangement interval of the ink jet-out ports 12), and then, recording pixel dots

16 (indicated by hatched lines declining leftward in the figure) are printed on the recording paper 14.

In this manner, the resolution of the formed image is improved twice as high as that of the line recording head 11.

As described, in the image formation method for improving the resolution of the image by controlling the movement of the line recording head 11, if the ink dots jetted out from the ink jet-out ports 12 of the line recording head 11 differ in jet-out amount and direction, the black stripe (which is formed by excessively overlapping dots than required) and the white stripe (which is formed by printing dots at intervals which are excessively far from each other than required) emerge, as shown in FIG. 13. As a result, the obtained image is non-uniform in concentration as a whole.

To overcome this problem, it is considered that the image is formed by two control methods in combination, as shown in FIG. 14. One is a control method in which the line recording head 11 is slid by $L/2$ (L is an arrangement interval of the ink jet-out ports 12) and the other is a control method in which dots are printed on the recording paper 14 alternately up and down in a staggering manner. To be more specific, at a first round of the drum, pixel dots 17 (indicated by a lattice pattern in the figure) are

printed on the recording paper 14. At a second round of the drum, the line recording head 11 is slid rightward by $L/2$, and then, pixel dots 18 (indicated by hatched line declining rightward) are printed on the recording paper 14. At a third round of the drum, the line recording head 11 is slid further rightward by $L/2$, and then, pixel dots 19 (indicated by hatched lines declining leftward) are printed. At a fourth round of the drum, the line recording head 11 is further slid rightward by $L/2$ and then pixel dots 20 (indicated by a white circle in the figure) are printed on the recording paper 14. In this manner, the resolution of the image is improved twice as high as that of the line recording head 11. At the same time, the image formation non-uniform in concentration due to irregular arrangement of the ink jet-out ports can be successively suppressed.

However, the aforementioned controlling manner has a problem in that it takes time to form the image since time required for image formation is doubled compared to the control method only for increasing the resolution.

BRIEF SUMMARY OF THE INVENTION

An object of the present invention is to provide an image formation apparatus capable of improving image quality by suppressing image formation non-uniform in concentration due to irregularity in size and shape

of ink jet-out ports; and capable of reducing time required for image formation.

According to one aspect of the present invention, the image formation apparatus has a recording head having a plurality of recording elements arranged in line. Using the recording head, an image is formed by printing dots on a recording medium while the recording medium is fed relatively in a direction virtually perpendicular to an arrangement direction of the recording elements of the recording head. The present invention is characterized in that dots are printed at pitches smaller than arrangement intervals of the recording elements by feeding the recording medium to the recording head repeatedly multiple times while the recording head is being moved in the arrangement direction of recording elements, and in that the recording head is slid by a moving amount determined so as to correspond to a specific feature of a human visual system every time the feed of the recording medium is repeated to the recording head.

According to the aspect of the present invention, quality of the image can be improved by successively suppressing image formation non-uniform in concentration due to the irregularity of ink jet-out ports in size and shape. Furthermore, time required for image formation can be reduced.

Additional objects and advantages of the invention

will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and
5 obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the invention,
10 and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention.

15 FIG. 1 shows a main portion of an entire structure of a printer according to an embodiment of the present invention;

FIG. 2 is a view showing arrangement of the ink jet-out ports of the ink jet recording head according
20 the embodiment;

FIG. 3 is a view showing the relationship between a moving step amount of the ink-jet recording head and pixel dots printed on the recording paper according to the embodiment;

25 FIG. 4 is a one-dimensional concentration distribution curve showing a Gaussian distribution function curve and a basic concentration function curve

of the ink jet printer;

FIG. 5 is a graph showing the head moving step amount versus the objective evaluation when the resolution is 300 dpi in the embodiment;

5 FIG. 6 is a graph showing the head moving step amount versus the subjective evaluation when the resolution is 300 dpi in the embodiment;

FIG. 7 is a graph showing the head moving step amount and the objective evaluation in the cases
10 where the resolutions are 300 dpi and 600 dpi in the embodiment;

FIG. 8 is a view showing a gist portion of an entire structure of a printer according to another embodiment of the present invention;

15 FIG. 9 of a view showing an ideal image formed by the ink-jet printer;

FIG. 10 is a view showing an image formed by the ink jet printer when the formed image is non-uniform in concentration;

20 FIG. 11 is a view for explaining how to control a conventional ink-jet printer in order to suppress an image formation non-uniform in concentration;

FIG. 12 is a view for explaining how to control a conventional ink jet printer in order to enhance
25 resolution of an image;

FIG. 13 is a view for explaining problems in the case where a conventional ink jet printer is controlled

for improving a resolution of an image; and

FIG. 14 is a view for explaining problems in the case where a conventional ink jet printer is controlled for suppressing image formation non-uniform in concentration and for improving a resolution.

DETAILED DESCRIPTION OF THE INVENTION

Now, an embodiment of the present invention will be explained with reference to FIGS. 1 to 7. In this embodiment, the present invention is applied to an ink-jet type line printer.

FIG. 1 is a view showing a main portion of an entire structure of a printer. The printer has a main case 21 housing a drum 22. The drum is rotated at a constant speed in the direction indicated by an arrow in the figure. A recording paper 25 (recording medium) to be fed through paper feed rollers 23, 24 is wound around the drum 22.

A paper feed cassette 26 is fitted to the bottom portion of the main case 21. Recording paper sheets 25 mounted on the mounting plate 27 of the paper feed cassette 26 is taken out one by one and sent to the paper feed rollers 23, 24. On the other hand, the recording paper sheets 25 can be manually fed through a manual feeding tray 29 which is fitted to an openable side portion of the main case 21. The manually fed recording paper sheet is also sent to the paper feed rollers 23, 24 by a paper feed roller 30. Note that

a paper-feed switching means 31 is responsible for switching the paper feed routes to be controlled by the paper feed roller 28 and by the paper feed roller 30.

5 A charging roller 32 is arranged so as to face the drum 22. The charged roller 32 is responsible for adsorbing the recording paper sheet 25 fed through the paper feed rollers 23, 24, on the drum surface. Furthermore, a printing mechanism 34 is arranged so as to face the drum 22. The printing mechanism 34 has
10 an ink-jet recording head 33 having a plurality of recording elements arranged in lines. The printing mechanism 34 is movable in a recording element arrangement direction (i.e., along a rotation shaft of the drum 22). Therefore, the recording paper 25 is fed
15 in a direction perpendicular to the recording element arrangement direction of the ink-jet recording head 33 by rotation of the drum 22.

The ink-jet recording head 33 has a plurality of ink jet ports 33a (serving as recording elements)
20 arranged at intervals (itches) L. Ink chambers are formed corresponding to ink jet-out ports 13a.

The printing mechanism 34 consists of a reciprocal moving mechanism 35 having the ink jet recording head 33 mounted thereon, a motor unit 36 having a reciprocal
25 moving rod and a linear motor, and a back-and-forth moving means 37. The ink jet recording head 33 is moved back and forth by the back-and-forth moving means

37 with respect to the drum 22; at the same time,
the ink jet recording head 33 is moved reciprocally
in the rotation shaft direction of the drum 22.

The reciprocal movement of the ink-jet recording head
5 33 is controlled by the motor unit 36, which moves the
reciprocal moving mechanism 35 in the rotation-shaft
direction of the drum 22.

The drum 22 has a recording paper detachment means
having a detachment nail 38, which is capable of being
10 inserted between the drum surface and the recording
paper sheet 25. The detachment nail 38 removes the
recording paper sheet 25 and discharges it into a
recording paper sheet discharge means 39. The
recording paper discharge means 39 consists of a belt
15 conveyer 40 which is in contact with a non-recording
surface of the recording paper 25 and a pressing means
41 for pressing the recording paper sheet 25 against
the belt conveyer 40.

The recording paper sheet 25 is conveyed by the
20 belt conveyer 40 to a terminal end of the belt conveyer
40 and then discharged outward through a side face of
the main case 21.

The resolution of the image formed by the
apparatus is set at K-fold (K is an integer of 2 or
25 more) of the resolution of the interval (pitch) L of
ink jet-out ports 33a of the ink jet recording head 33.
The ink jet recording head 33 moves by $T \times L/K$ (T is

a positive integer representing a head moving step amount) in the rotation-shaft direction of the drum 22 when the drum 22 rotates once. The head moving step amount T is determined in consideration of a specific feature of human visualization. To be more specific, a human eye is characterized by a band pass filter which passes only light having frequencies within a certain band zone. Since the eye acts as the band filter as mentioned, the image captured by the human eye slightly differs from the image detected by retina and transmitted to the brain.

For example, the image formed in FIG. 3 has a resolution twice as high as that of the interval (pitch) L of the ink jet-out ports 33a of the ink jet recording head 33. In this case, the ink jet recording head 33 moves by $3 \times L/2$ in the rotation-shaft direction of the drum 22 when the drum 22 rotates once. In other words, the head moving step amount T is set at 3.

In this case, at the first rotation of the drum 22, pixel dots 51 (indicated by an open circle) are printed by jetting out ink from ink jet-out ports 33a of the ink jet recording head 33. At a second rotation of the drum 22, pixel dots 52 (indicated by hatched lines declining leftward) are printed by jetting out ink from ink jet-out ports 33a of the ink jet recording head 33.

If the image formation is formed by printing pixel

dots as mentioned above, it is possible to form an image improved in resolution and in quality which is rated as the most suitable as viewed from human eyes. More specifically, the drum 22 is required to rotate only for improving the resolution but not for suppressing the black and white stripes. It is therefore possible to enhance the resolution and to suppress the image formation non-uniform in concentration due to irregularity of the ink jet-out ports 33a in size and shape by rotating the drum few number of times, with the result that the image quality is improved and the time required for image formation can be reduced.

Now, we will describe how to determine the head moving step amount T.

In general, a figure showing concentration distribution of pixel dots printed by the ink-jet printer can be approximated by means of "Gauss distribution", which is often used in analysis of natural phenomena. In the case where the coordinate in the arrangement direction of ink jet-out ports 33a of the ink jet recording head 33 is represented by x , and the coordinate in the feed direction of the recording paper sheet 25 is represented by y , the concentration distribution function of image data can be given by the following equation (1):

$$d(x-x_0, y-y_0) = D_{\max} \exp \left\{ -2 \left[\left(\frac{x-x_0}{a} \right)^2 + \left(\frac{y-y_0}{b} \right)^2 \right] \right\} \dots (1)$$

Where D_{max} is the maximum concentration value, x_0 and y_0 are off-set positions of a pixel dot; a , b are radii at $1/e^2$ of a spot in the x direction and the y direction, respectively. In this case, if x and y are present within the range of one pixel, the concentration distribution function represented by the
5 aforementioned equation (1) is regarded as a minimum unit for forming an image. Hence, the entire image is formed by synthesizing the concentration distributions
10 of the minimum unit. That is, the minimum unit may be regarded as a basic distribution function for image formation.

For example, in the case where an area-modification ink-jet printer is employed as the ink-jet
15 printer, the basic concentration function depends on D_{max} , a and b (a and b are variable depending upon respective tones). However, since the dot concentration figure actually formed by the ink jet printer slightly differs from that of the Gauss distribution
20 mentioned above, the Equation (2) modified from the Equation (1) may be used. FIG. 4 shows a curve g_1 indicating the Gauss distribution function in comparison with a curve g_2 indicating the basic concentration distribution function for use in
25 simulation in practice. The curve indicates a one-dimensional function in the x direction.

$$d_1(x-x_0, y-y_0) = D_{\max} \exp \left\{ - \left[\left(\frac{x-x_0}{0.9a} \right)^2 + \left(\frac{y-y_0}{0.9b} \right)^2 \right]^{1.5} \right\} \dots (2)$$

The concentration distribution of the synthesized image is determined by synthesizing the basic distribution functions and thus represented by the following equation (3):

$$e(x, y) = \sum_{x=0}^M \sum_{y=0}^N \sum_{i=0}^m \sum_{j=0}^n d_1(x-x_i, y-y_j) \dots (3)$$

where m is the number of pixels in the arrangement direction of the ink-jet ports 33a; n is the number of pixels in the feed direction of the recording paper sheet 25, and M and N are the sampling numbers (corresponding to dividing numbers of each pixel) in the x direction and y direction, respectively.

However, the printing positions of the pixel dots are shifted from right positions in most cases by the irregularity of the ink-jet ports 33a in size and shape which are formed by causes in the head manufacturing step. Therefore, in consideration of error equations $g(x_j)$ and $h(y_j)$ of the pixel dot recording portion in the x direction and y direction, respectively, the pixel dot recording position is represented by the following equation (4):

$$e_1(x, y) = \sum_{x=0}^M \sum_{y=0}^N \sum_{i=0}^m \sum_{j=0}^n d_1(x-(x_i+g(x_i)), y-(y_j+h(y_j))) \dots (4)$$

In the case of analyzing image signals in a frequency space, a two-dimensional frequency analysis is generally employed. If the image signal is treated as a one-dimensional signal for brevity sake, the basic concentration distribution function of an image is
5 represented by the following equation (5):

$$d_2(x-x_0) = D_{\max} \exp \left\{ - \left[\left(\frac{x-x_0}{0.9a} \right)^2 \right]^{1.5} \right\} \quad \dots (5)$$

Furthermore, taking an error of the pixel dot recording position into consideration, the
10 concentration distribution of the synthesized image is represented by the following equation (6):

$$e_2(x) = \sum_{x=0}^M \sum_{i=0}^m d_2(x-(x_i+g(x_i))) \quad \dots (6)$$

15 Since the human visual system can be regarded as a filter passing frequencies within a certain band zone, convolution of the spatial frequency characteristics of the image and of the human visual system must be carried out. The convolution made in the frequency
20 space results in a product of two functions as shown in the following equation (7):

$$G(\mu) = E(\mu)H(\mu) \quad (7)$$

μ : frequency

$H(\mu)$: spatial frequency characteristics of
25 visualization

$E(\mu)$: spatial frequency characteristics of
image

(Fourier transform of $e_2(x)$).

A final evaluation amount is an integration value
5 of $G(\mu)$ in an effective frequency region as given by

$$\text{Evaluation amount} = \int_{\mu} G(\mu) d\mu \quad \dots (8)$$

The larger the evaluation amount represented by
the equation (8), the more sensitive a human eye to the
10 white and black stripes formed by the irregularity of
ink jet-out port 33a in size and shape. In other words,
if the head movement step amount T indicating a low
evaluation amount, is selected, the most preferable
image as viewed from human eyes can be printed.

15 Now, we will explain the evaluation when an image
is actually formed with a resolution of 300 dpi.

FIG. 5 is a graph plotting evaluation amount by
simulation at each of head moving step amounts $T = 1, 3,$
5, and 7 when the image is formed with a resolution of
20 300 dpi by using a recording head having the ink jet-
out ports 33a arranged at intervals of 150 dpi. Curves
 g_3, g_4, g_5 of the graph in the figure respectively show
evaluation amounts in the cases three types of ink jet-
out head different in size and shape of jet out ports
25 are used.

The evaluation amount is the lowest at the head
moving step amount $T = 3$ in any head of $g_3, g_4,$ and g_5 .

In other words, image can be obtained in the most satisfactory quality at the head moving step amount $T=3$ when the image is formed with a resolution of 300 dpi.

To prove it, a subjective evaluation is further made. As the subjective evaluation, one-to-one comparison (alternative evaluation of yes and no) is made by a plurality of panels with respect to a pair of objects. Generally, all combinations: $nC_2:n(n-1)/2$, are checked by changing the order or positions.

The results are shown in the graph of FIG. 6. The graphs g6, g7, g8 respectively show the evaluations when three types of ink jet-out heads having different sizes and shapes of the jet-out ports. Evaluation is made in such a scoring method that two points are given to the image superior in quality and a zero point is given to the image inferior in quality. Accordingly, the image earning a higher score means high in quality. Since the highest evaluation score is given at the head moving step amount $T=3$ in the subjective evaluation, the highest image quality is obtained at $T=3$.

As described above, the subjective evaluation results made by peoples agree with the objective evaluation results calculated by simulation. It is therefore successively proved that the head moving step amount T in accordance with the specific feature of human visualization can be effectively determined.

FIG. 7 shows the head moving step amount T versus

the evaluation amount for two types of images with resolutions of 300 dpi and 600 dpi, respectively.

More specifically, a graph g9 shows an image with a resolution of 300 dpi. A graph g10 shows an image with a resolution of 600 dpi. The lowest evaluation is given at the head moving step amount T of 3 in the case of 300 dpi resolution, and at the head moving step amount T of 5 in the case of 600 dpi.

As described, it is found that the most suitable head moving step amount T varies depending upon the resolution of the formed image. Therefore, if the head moving step amount T is controlled in accordance with the resolution of the printer to be used, the image can be formed in the most preferable quality in consideration of the specific feature of human visualization.

In the foregoing, an example of the ink jet printer was described which has the printing mechanism 34 equipped with an ink jet recording head 33 having a plurality of recording elements arranged in line and being movable in the rotation shaft direction of the drum 22. However, the ink jet printer is not limited thereto. The present invention can be further applied to an ink jet color printer having a printing mechanism 341 equipped with four ink jet recording heads 331, 332, 333, 334 having a plurality of recording elements arranged in line and being movably in the rotation shaft direction of the drum 22, as shown in FIG. 8.

In this case, the ink jet recording head 331 is set at "yellow", the ink jet recording head 332 is set at "Cyan", the ink jet recording head 333 is set at "magenta", and the ink jet recording head 334 is set at black, and then, these recording heads may be driven on the basis of the head moving step amount T which is determined in correspondence to the specific feature of a human visual system, in the same way as in the case of the ink-jet recording head 33. In this case, if the four ink jet recording heads 331-334 are mounted on the reciprocal moving mechanism 35, they can be controlled simultaneously.

In the aforementioned embodiments, we explained the case where the image is formed with resolutions of 300 dpi or 600 dpi by using the recording head having the ink jet out ports arranged at intervals of 150 dpi. The same explanation can be adopted to the cases where the image is formed with a resolution of 2A dpi or 4A dpi by the use of the recording head having ink jet out ports 33a arranged at intervals of A dpi.

Furthermore, an image having a resolution of 400 dpi can be formed by using a recording head having a plurality of recording elements arranged at intervals of 200 dpi if the recording head is moved by the predetermined number of head moving steps which is defined by the method according to the present invention.

Similarly, an image having a resolution of 800 dpi can be formed by using a recording head having a plurality of recording elements arranged at intervals of 200 dpi if the recording head is moved by the
5 predetermined number of head moving steps which is defined by the method according to the present invention.

Similarly, an image having a resolution of 360 dpi can be formed by using a recording head having a
10 plurality of recording elements arranged at intervals of 180 dpi if the recording head is moved by the predetermined number of heat moving steps which is defined by the method according to the present invention.

15 Still similarly, an image having a resolution of 720 dpi can be formed by using a recording head having a plurality of recording elements arranged at intervals of 180 dpi if the recording head is moved by the predetermined number of heat moving steps which is
20 defined by the method according to the present invention.

In the aforementioned embodiments, we described the case in which the recording paper is fed in the direction virtually perpendicular to the arrangement
25 direction of the ink jet-out ports of the ink jet recording head while the recording paper is wound around the drum. However, the present invention is

not limited thereto. For example, the recording paper may be fed by being mounted on a belt conveyer etc.

Alternatively, the recording head may be fed relative to the ink jet recording head by moving the ink jet

5 recording head with respect to a recording paper immobilized.

In the embodiments mentioned above, we described the case in which the present invention is applied to the ink jet printer. However, the present invention
10 is not limited thereto. The present invention may be applied to a printer having an LED recording head having a plurality of LED recording elements arranged in line, a printer having a thermal recording head having a plurality of thermal recording elements
15 arranged in line, and a printer having an edge-emitter recording head having a plurality of EL recording elements arranged in line.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore,
20 the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as
25 defined by the appended claims and their equivalents.



CLAIMS

1. An image formation apparatus comprising:
a recording head having a plurality of recording
elements arranged in line;

5 moving means for moving the recording head in
an arrangement direction of the recording elements;

feed means for feeding a recording medium
relatively in a direction virtually perpendicular to
the arrangement direction of the recording elements of
10 the recording head; and

means for moving the recording head by a moving
amount determined so as to correspond to a specific
feature of a human visual system every time a recording
medium is fed with respect to the recording head while
15 allowing the moving means to move the recording head in
the arrangement direction of the recording elements and
allowing the feed means to feed the recording medium
repeatedly multiple times, thereby printing dots at
pitches smaller than arrangement intervals of the
20 recording elements.

2. The image formation apparatus according to
claim 1, wherein the specific feature of a human visual
system is a specific feature for recognizing difference
in concentration of dots printed on the recording
25 medium, in the moving direction of the recording head.

3. An image formation apparatus comprising:
a recording head having a plurality of recording



elements arranged in line;

moving means for moving the recording head in
an arrangement direction of the recording elements;

feed means for feeding a recording medium
5 relatively in a direction virtually perpendicular to
an arrangement direction of the recording elements of
the recording head; and

means for moving the recording head by a moving
amount, $T \times L/K$ (T is a positive integer representing a
10 head moving step amount) determined so as to correspond
to a specific feature of a human visual system every
time a recording medium is fed with respect to the
recording head while allowing the moving means to move
the recording head in the arrangement direction of the
15 recording elements and allowing the feed means to feed
the recording medium to the recording head repeatedly
multiple times, thereby printing dots at pitches of L/K
(K is an integer of 2 or more) smaller than arrangement
intervals of the recording elements.

20 4. The image formation apparatus according to
claim 3, wherein said head moving step amount T is set
at a minimum step amount which is given by an integra-
tion of products obtained by multiplying a spatial
frequency characteristic of a formed image and a
25 spatial frequency characteristic of visualization.

5. The image formation apparatus according to
claim 4, wherein the spatial frequency characteristic



of a formed image is $E(\mu)$ and the spatial frequency characteristic of visualization is $H(\mu)$.

6. The image formation apparatus comprising:

a recording head having a plurality of recording elements arranged in line at intervals of $1/150$ inch;

moving means for moving the recording head in an arrangement direction of the recording elements;

feed means for feeding a recording medium relatively in a direction virtually perpendicular to the arrangement direction of the recording elements of the recording head; and

means for moving the recording head by a moving amount, $3 \times 1/300$ (a head moving step number $T=3$) every time a recording medium is fed with respect to the recording head, while allowing the moving means to move the recording head in the arrangement direction of the recording elements and allowing the feed means to feed the recording medium to the recording head, repeatedly twice, thereby printing dots at pitches of $1/300$

smaller than intervals $1/150$ of the recording elements.

7. An image formation apparatus comprising:

a recording head having a plurality of recording elements arranged in line at intervals of $1/150$ inch;

moving means for moving the recording head in an arrangement direction of the recording elements of the recording head;

feed means for feeding a recording medium



relatively in a direction virtually perpendicular to an arrangement direction of recording elements of the recording head; and

means for moving the recording head by a moving
5 amount, $5 \times 1/600$ (a head moving step number $T=5$) every
time a recording medium is fed with respect to the
recording head while allowing the moving means to move
the recording head in the arrangement direction of the
recording elements and allowing the feed means to feed
10 the recording medium to the recording head, repeatedly
four times, thereby printing dots at pitches of $1/600$
smaller than arrangement intervals $1/150$ of the
recording elements.

8. An image formation apparatus, substantially as
15 hereinbefore described with reference to FIGS. 1 to 8
of the accompanying drawings.