

SECURED DOCUMENT, SYSTEM FOR MANUFACTURING SAME AND
SYSTEM FOR READING THIS DOCUMENT

The invention relates to a secured document, a process
5 and a system making it possible to manufacture this
document and means making it possible to read it.

It is now relatively easy for forgers to reproduce
conventional documents such as passports, identity
10 card, identification badges.

The object of the invention is to make it difficult, or
even virtually impossible, to reproduce and/or falsify
such documents.

15 Securing documents (identity cards, passports, etc.)
against counterfeiting and falsification is a
fundamental problem which arises with all those
involved in the field.

20 The restrictions which bear on the securing methods are
stringent. This is because these documents must be made
with:

- 25 - a very low production cost (a few tens of
centimes per document)
- a short duration for the process allowed for
the manufacture of each document (a few seconds
per document)
- 30 - a high level of protection against
counterfeiting.

Generally, the object of the invention is to produce,
on the document to be protected, a characteristic
hologram which is difficult to copy and moreover which
35 carries printed data in a conventional manner on the
document. Thus a verifying agent will be able to check
the document by comparing the content of the hologram
with the content of the rest of the document. For

example, the hologram represents an image of the identity photo contained on the document. Comparing the image of the hologram with the image of the photo makes it possible to authenticate the document quickly and easily.

Processes for securing documents, for example by hologram, are known from documents US-A-4 171 864, EP-A-0 283 233, GB-A-2 254 166, US-A-3 894 756 and US-A-5 483 363, but these known processes do not offer strengthened security against counterfeiting.

The invention therefore relates to a document comprising at least one drawing or data, made by deposition or inclusion of pigments or dyes which can be read optically, and a hologram made from a copy of said drawing or of said data, characterized in that the hologram comprises deformations introduced during its recording which makes the copy read from the drawing or said data different.

The invention also relates to a document security system, comprising a prerecorded or electrically controllable optical modulator in which the image of at least part of the document is recorded, said modulator being designed to be combined with a layer of photosensitive material, at least one first light source making it possible to transmit a first reference wave to the layer of photosensitive material and a second incident wave onto said modulator and giving rise to a third object wave which is transmitted to the layer of photosensitive material in order to interfere with the reference wave in this layer, characterized in that it comprises in the path of the first wave or of the second, means inducing scrambling in the hologram recorded in the layer of photosensitive material.

The invention also relates to a system for reading a document comprising a hologram containing an image of part of said document, said image being scrambled, characterized in that it comprises a device for
5 correcting said scramblings, or revealer, said hologram being readable through the revealer.

The various objects and characteristics of the invention will become more clearly apparent in the
10 following description given by way of example and in the appended figures which represent:

- figures 1a and 1b, examples of documents secured according to the invention;
- figures 2 to 4c, examples of hologram recording
15 systems according to the invention;
- figures 5 and 6, recording systems making it possible to induce scramblings in the images recorded in the holograms;
- figures 7 and 8, systems making it possible to
20 read a hologram by removing scramblings contained in the hologram;
- figures 9 and 10, a device for reading a document furnished with a hologram and making it possible to remove scramblings induced in the hologram;
- 25 - figures 11 and 12, documents incorporating special gratings placed against the holograms.

An example of a document secured according to the invention will first of all be described with reference
30 to figure 1a. By way of example, figure 1 shows an identity card 1 comprising data 4 indicating the identity of the possessor of the card, his or her photograph 2 and his or her signature 5. Furthermore, according to the invention, the card comprises a
35 hologram 3 in which one or more elements for personalizing the card have, *inter alia*, been recorded, such as the photograph, the signature, etc. In figure

1, the photograph has been chosen for recording in the hologram. A card of this type would thus be more difficult to falsify since the hologram contains data for personalizing the card, which will change from one
5 card to another.

Figure 1b shows a variant embodiment of figure 1a. According to this variant the hologram 3 contains images which appear in different planes. An image 60
10 may be, for example in the case of an identity card, a copy of the identity photo 2, whilst another image 61 may be either a standard image (logo) or other data from the card such as the copy of the signature 5.

According to another variant (not shown), the hologram
15 may also comprise data printed on its surface.

A first example of the process of recording the hologram will now be described with reference to figure 2.

20 A support element 22 is coated on one of its faces with a layer of photosensitive material 21. An optical modulator 23, such as a transparent photographic support or a controllable modulator such as a liquid-crystal screen, is applied near to or in contact with
25 the layer of photosensitive material.

Preferably, the modulator makes it possible to supply the contents (data or image) of part of the document to be secured. If this involves a prerecorded modulator of
30 the transparency type, this part of the document is recorded in the modulator. If this involves a controllable modulator, the part of the document can be displayed using the control of the modulator.

35 The support element 22 is transparent at the recording wavelength. A mirror 24 is placed on the side opposite the photosensitive layer with respect to the modulator

23. A light beam R supplied by a source S1 and carrying a coherent wave illuminates the support element 22. By way of example, in figure 2, this light beam is perpendicular to the plane of the support element 22 and of the photosensitive layer 21. The beam R passes through the support 22, the holography layer 21. It is modulated by the modulator 23 and is transmitted to the mirror 24. The latter reflects the modulated beam which passes back through the modulator. According to this embodiment, the mirror 24 is perpendicular to the direction of the beam and reflects a beam colinearly with the incident beam. The reflected modulated beam interferes with the beam R in the layer of photosensitive material. The modulation carried by the modulated beam is therefore recorded in the photosensitive layer. Thus, a hologram containing data or an image, which is a copy of data or of an image contained in the document to be secured, has been recorded. If the modulator 23 contains, for example, the photograph of the possessor of the identity card, this photo has therefore been recorded in the hologram.

In this process, it is assumed that T is the transmission coefficient of the modulator and that O is the wave illuminating the hologram on the side opposite the beam R, which we will call reference wave R hereinafter.

The function recorded by the hologram comes from the interference between the reference wave R and the wave $O \sim R^*T$, the object wave from the transparency.

The hologram records $R(R^*T)^*$ i.e. RR^*T^2 .

If the hologram is thick, it will rediffract on reading the recorded image, for specified angles of incidence (Bragg effect) of the illumination wave and of the

viewing direction.

The modulator can integrate a scattering function for improved reading of the hologram and in order to
5 complicate any counterfeiting.

Figure 3 shows another recording process in which two waves illuminating the photosensitive layer are needed. The light modulator 23 is placed against the layer of
10 photosensitive material 21 borne by the support 22.

An illuminating reference wave R supplied by the source S1 is transmitted to the layer of photosensitive material 21 without passing through the modulator. An
15 illumination wave I supplied by the source S2 illuminates the modulator 23 and is transmitted therethrough to the layer of photosensitive material (illumination wave O, $O = IT$). The two waves R and O interfere in the photosensitive material 21.
20 Preferably, the two waves O and R are counterpropagating and are perpendicular to the plane of the layer of photosensitive material 21. Also, preferably, the two waves are coherent plane waves.

25 The function recorded by the hologram comes from interference between R, reference wave, and the object wave coming from the modulator illuminated by the plane wave I: $O = IT$.

30 The hologram records $R^*.I.T$.

The thick hologram reilluminated by a plane wave R will diffract an image proportional to IT , that is to say, the image of the transparency, provided that I is of
35 the plane wave type, like R.

As in figure 2, the modulator 23 of figure 3 can be

integrated into a scattering function. For example, a layer of scattering material will be deposited on the face of the modulator located on the side of the layer of photosensitive material.

5

In the above, the recording of the hologram 21 has been carried out by placing thereagainst an optical modulator. It is also possible to design a recording system in which the modulator is illuminated by a wave I, which is modulated by the modulator and which supplies a wave O, as is shown in figure 4a. An optical device 80 images the modulator in the plane of the hologram. Moreover, a beam-splitter plate 81 placed in the path of the wave O makes it possible to transmit a reference wave R to the photosensitive medium 21. This reference wave interferes with the wave O and makes it possible to record the image supplied by the modulator 23. The rereading of such a hologram requires placing a mirror against the support 22 on the side opposite the hologram 21.

Figures 4b and 4c represent variants of recording systems in which the modulator is not placed against the hologram. As can be seen in figure 4b, the modulator 23 is illuminated by the wave I and is projected by the optic 80, onto the surface of the layer of photosensitive material 21 (wave $O = IT$). Moreover, the layer of photosensitive material is illuminated by a reference wave R incident on this layer from the side opposite the modulator. The two waves O and R interfere in the photosensitive layer in order to record a hologram corresponding to the display of the modulator 23. As is known in the prior art, the waves O and R are preferably coherent.

35

Figure 4c shows the system of figure 4b in which one or more additional light modulators 27, 28 have been

provided. These modulators are not placed in the same plane as the modulator 23. These modulators will make it possible to record, in the photosensitive layer of the holograms which will not appear in the same plane as the image of the modulator 23.

Preferably, the images of the various modulators will be recorded separately. The image of the modulator 23 will be recorded when the modulators 27 and 28 are transparent or in the absence of these modulators. In order to record the image of an additional modulator, 27 for example, the modulator 23 will be made transparent (or removed) possibly together with the modulator 28.

It should be noted that the various holograms recorded using the various modulators can be recorded using different wavelengths insofar as the nature of the photosensitive layer 21 allows it. These holograms will then be reread using these various wavelengths.

The variant of figure 4c making it possible to record visible holograms in different planes is also applicable to the systems of figures 2 and 3 by also providing one or more additional modulators on the path of one of the waves I or R.

These additional modulators will make it possible to display either a specific motif (logo) or data (a signature for example) of the document to be secured.

In order to induce a scattering effect and/or aberrations in the hologram, the means inducing the scattering and/or the aberration can be placed either in the path of the wave O or in the path of the wave R.

Figures 5 and 6 show variants of the systems of figures

2 and 3, respectively, in which optical aberrator devices are provided.

Thus, in figure 5, an aberrator 25 is positioned, for example, on the reference wave R. An aberrator introduces a local phase ϕ into the wave R, that is to say, it transforms it into $R.e^{i\phi}$.

The modulator is also illuminated by $R.e^{i\phi}$ and the object wave O is $O = R^*.e^{-i\phi}T^2$. The hologram records $R(.R^*.e^{i\phi}T^2)^*$, i.e. $RRe^{2i\phi}T^2$.

In reading mode, illuminated by R^* , it diffracts a wave $e^{2i\phi}RT^2$ deformed with respect to RT^2 . The image appears scrambled to the observer. The observer can read normally only a deformed image. The deformation undergone by the image is twice that coming from the aberrator.

If the aberrator 25 is located on the modulator side with respect to the layer of photosensitive material, the hologram records $R^*.R.T^2.e^{2i\phi}$. This case is similar to the case of recording 2 waves treated below.

In figure 6, the system is illuminated by two distinct waves I and R supplied by sources S1 and S2 as in figure 3.

The aberrator is positioned, for example, in the path of the wave R. The aberrator introduces a local phase ϕ into the wave R, that is to say, it transforms it into $R.e^{i\phi}$.

The transparency is illuminated by a plane wave I. We therefore have $O = IT$.

The hologram records $R^*.e^{i\phi} IT$.

In reading, reilluminated by R , it diffracts a wave $e^{i\phi}$ IT deformed with respect to IT. The image appears scrambled to the observer, as above.

5

The deformation undergone by the image is the same as that coming from the aberrator.

Under these conditions, in order to be able to reread
10 the images recorded using the systems of figures 5 and 6, it is necessary to correct the aberrations introduced by the aberrator.

For this purpose, according to the invention, an
15 aberration-correcting device 27, which we will call a revealer 27, is placed (figure 7) in front of the hologram thus recorded, through which it is possible to read the hologram corrected of the aberrations.

20 The revealer induces a phase function the inverse of that of the aberrator, that is $e^{-i\phi}$, on the read wave.

The wave incident on the hologram is $Re^{-i\phi}$. Since the hologram has recorded $R.Re^{2i\phi}T^2$, it diffracts a wave
25 proportional to $T^2.e^{i\phi}$ then passes back through the revealer which again induces $e^{-i\phi}$ and thus the light wave coming from the revealer is proportional to T , that is to say corresponds to the undeformed image.

30 Therefore, with a recording such as that of figure 6, (aberrator on the reference wave side), the aberrator induces ϕ , the revealer must induce $-\phi$.

Where the aberrator has been positioned on the
35 modulator side, the revealer is determined as in the two-wave case described below.

According to figure 8, the revealer induces a phase function of $e^{-i\phi/2}$ on the read wave.

5 The wave incident on the hologram is $R.e^{i\phi/2}$. Since the hologram has recorded $R^*ie^{i\phi}T$, it diffracts a wave proportional to $T.e^{i\phi/2}$ then passes back through the revealer which again induces $e^{-i\phi/2}$ and thus the light wave coming from the revealer is proportional to IT , that is to say it corresponds to the undeformed image.

10

Therefore with 2 wave recording: the aberrator induces ϕ and the revealer must induce $-\phi/2$.

15 In order that the positioning of the revealer is not too critical, the aberrator must be chosen so as to noticeably modify the view of the image but with phase defect spatial frequencies on the scale of the positioning accuracy tolerated.

20 1°/ 1 or 2 wave recording can be carried out with any incident waves. The benefit is, *inter alia*, to separate the direction of observing the recorded image from the specular reflection. This configuration substantially improves the image contrast.

25

2°/ In figure 2, a nonspecular mirror can be used in recording so as to modify the angle of incidence of the object wave with respect to that of the reference wave, namely to separate the direction of observing the photo
30 from the specular reflection.

3°/ The aberrator and the revealer are two different phase functions. It is possible to use the same component for both functions by reilluminating the
35 hologram not with R but with R^* . In this case, the phase function recorded in the hologram is transformed

11a

into its conjugate by diffraction and self-corrects by passing through this same phase law. This is the principle of phase conjugation.

5 A hologram of this sort is thus made difficult to counterfeit by the presence of the aberrator during recording:

- knowledge of the correct aberration function to be used is not easy to acquire. This analysis
10 can be made difficult by superimposing a scattering function on the diffracted function;
- on the assumption that the aberrant function to be used during recording has been determined, the practical construction of a known phase law
15 aberrator is not easy.

Figure 9 shows a device for reading a document furnished with a hologram recorded with aberrations. This device comprises a revealer 27 which must be
20 accurately positioned with respect to the hologram in order to allow sufficient correction of the aberrations. According to figure 8, the document which bears the hologram or the hologram support comprises positioning means such as notches 30 to 33. The read
25 device comprises lugs or pads 40 to 43, the complement of the notches, so that the document is placed correctly in front of the revealer.

According to a variant embodiment (figure 10), instead
30 of notches, the document may comprise optical marks 34 to 37 visible through the read device 27. The latter

also comprises optical marks 44 to 47. Making the marks 34 to 37 coincide with the marks 44 to 47 enables the hologram to be placed correctly in front of the revealer 27.

5

To improve the protection against counterfeiting, it is proposed to use a variant of the photosensitive protection of a volume which consists of the superposition of several photosensitive functions, one
10 of which contains the photo-type personalized data.

By way of example, the following combination is proposed:

- 15 - a photo-type hologram (HP) operating in reflection providing the personalization;
- a grating-type coding function (HS) operating in transmission providing the security;

In the case which is described in figure 11
20 illustrating this principle, the function (HP) has been recorded in the holographic layer 21 with an object wave obtained with the modulator 23 by means similar to the Lipmann process and with a reference wave which is the sum of the waves transmitted by the component HS.
25 In figure 11, the component HS is, for example, a diffraction grating supplying two waves $A_{s,R}^*$ and $A_{s,o}$.

To be visible, the photo contained in the component 21 requires the presence of the coding function of the
30 component HS.

The grating function HS may simply be of the grating type with a fixed pitch or contain specific but not personalized data: it will therefore be identical for
35 all the cards.

The benefit of the HS coding function resides in the fact that it endows the personalized hologram with specific optical properties colorimetry, multiple

angular ranges of visibility as a function, for example, of the grating order number, etc.

The combination of the two components, photosensitive
 5 layer and grating HS (figure 12) by "anti-peel" bonding means does not enable the two optical functions to be separated and consequently makes counterfeiting complex insofar as it requires knowledge of the amplitude and phase data of each of the reference and object waves
 10 for each of the two components to be recorded. Analysis of the wave diffracted by the assembly gives access to a product of all these complex waves;

- if $A_{S,R}$ and $A_{S,O}$ are the reference and object
 15 recording waves, respectively, of the grating HS and A_ℓ the wave incident on HS to record the component 21, then the recording waves of the hologram 21 are $[A_{S,R} \cdot A_{S,O} + A_{S,R}^* \cdot A_{S,O}] A_\ell$ and $A_{P,O}$.

20 The image recorded in the hologram 21 will be observed without distortion if the whole (21 + HS) is illuminated by the wave A_ℓ .

Outside these observation conditions, the holographic
 25 image will change color with the appearance of distortions or will disappear depending on its geometrical characteristics (thickness and index variation), a simple Lipmann hologram does not show such distortions.

30

According to a variant of the system of figure 11, the safety function may contain data which will be highlighted by the continuous component reflected by the photosensitive component. To increase the
 35 visibility of the data reread by the continuous component, it is possible to add, on the rear face of the hologram, a high index treatment or a treatment with narrow spectral reflectivity.

- 14 -

The relative positions of the hologram functions and of the grating HS can be exchanged as well as their kind and type of transmission or reflection.

5 Where transmission functions are combined, it is possible to add a high index treatment or a narrow spectral band reflector (which may or may not be photosensitive) to increase the readability of the data.

10

It should be noted that in the above, the photosensitive functions may be monochrome, dichrome or trichrome, etc., it is possible to adjust the colorimetry of the image for authentication with a
15 given light source (natural, neon or other light) or code the data stored in one and the same layer in different colors.

The use of photosensitive material with swelling that
20 can be spatially controlled by post-treatment makes it possible either to color-code a given motif superimposed on the personalized hologram, or to include another high-resolution function which can be seen with an additional source.

25

In addition, the hologram may be transparent to allow the reading of data located under the hologram, on the document.

30 The hologram can be read either by natural light, or by normal illumination, or using a lamp with a particular range of wavelengths.

It will generally be recalled that:

35 - if the hologram is thick, it only diffracts the recorded image with light incident at a particular angle (Bragg effect) and that the recorded image is only visible from a viewing

- 15 -

angle determined with respect to the direction of the incident light;

- the illuminating waves R and O are preferably plane but that is not compulsory;
- 5 - the illuminating waves R and O may be counterpropagating but that is not compulsory;
- the illuminating waves R and O are preferably mutually coherent;
- the hologram can be recorded with a single
10 wavelength or by using several wavelengths, or
 else by using three wavelengths (red, green,
 blue) so as to diffract white light.

CLAIMS

1. A document comprising at least one drawing or data produced by deposition or inclusion of pigments or dyes which can be read optically, and a hologram made from a copy of said drawing or said data, characterized in that the hologram comprises deformations introduced during its recording which make the copy read from the drawing or from said data different.
2. The document as claimed in claim 1, characterized in that the deformations are aberrations.
3. The document as claimed in claim 1 or 2, characterized in that the deformations are scattering effects.
4. The document as claimed in one of the preceding claims, characterized in that the hologram is superimposed onto at least one photosensitive layer with a coding function (HS).
5. The document as claimed in claim 4, characterized in that said photosensitive layer is a diffraction grating.
6. The document as claimed in claim 4 or 5, characterized in that said photosensitive layer contains specific but not personalized data, identical for all documents of the same type.
7. The document as claimed in one of claims 4 to 6, characterized in that the coding function comprises at least one of the following optical properties: colorimetry with multiple angular ranges of visibility, high-resolution visible with an additional source.

8. The document as claimed in one of claims 4 to 7, characterized in that the man [sic] and the photosensitive layer are combined by "anti-peel" bonding means.
- 5
9. The document as claimed in one of the preceding claims, characterized in that the hologram is transparent so that data located under it, on the document, can be read.
- 10
10. The document as claimed in one of the preceding claims, characterized in that the hologram can be read only under lighting of certain wavelengths.
- 15
11. The document as claimed in one of the preceding claims, characterized in that the hologram can be read at different wavelengths from different angles.
- 20
12. The document as claimed in one of the preceding claims, characterized in that the hologram is combined with a reflector with narrow band reflectivity.
- 25
13. The document as claimed in one of the preceding claims, characterized in that the hologram represents at least one other image appearing in a plane different to that of said deformed copy.
- 30
14. The document as claimed in claim 13, characterized in that said image can be read at a wavelength different from that of said deformed copy.
- 35
15. Document according to one of the preceding claims, characterized in that the hologram comprises data printed on its surface.

16. A document security system, comprising a prerecorded or electrically controllable optical modulator (23) in which the image of at least part of the document is recorded, said modulator being
5 designed to be combined with a layer of photosensitive material (21), at least one first light source making it possible to transmit a first reference wave (R) to the layer of photosensitive material and a second incident wave
10 (I) onto said modulator (23) and giving rise to a third object wave (O) which is transmitted to the layer of photosensitive material in order to interfere with the reference wave (R) in this layer, characterized in that it comprises in the
15 path of the first wave or of the second of means (25) inducing scrambling in the hologram recorded in the layer of photosensitive material.
17. The system as claimed in claim 16, characterized
20 in that it comprises a mirror (24) placed on the side opposite the layer of photosensitive material (21) with respect to the modulator, this mirror receiving the reference wave (R) after passing through the layer of photosensitive material and
25 the modulator and reflecting this wave in order to give rise to the second wave (I) which illuminates the modulator which transmits the third wave (O) to the layer of photosensitive material, the reference (R) and object (O) waves being
30 counterpropagating and perpendicular to the planes of the modulator and of the photosensitive layer.
18. The system as claimed in claim 16, characterized
35 in that it comprises a second source which is coherent like the first source and emitting the second wave (I), the first and the second source being located on each side of the modulator

assembly and layer of photosensitive material.

19. The system as claimed in claim 16, characterized
in that it comprises, between the modulator (23)
5 and the layer of photosensitive material (21), an
optical device (80) making it possible to image
the modulator (23) in the plane of the layer of
photosensitive material (21).
- 10 20. The system as claimed in claim 19, characterized
in that it comprises a beam-splitter plate (81),
the first source supplying the first reference
wave (R) to the beam-splitter plate which
retransmits this first wave to the layer of
15 holographic material, a second source supplying
the second wave (I), coherent with the first,
toward the modulator which retransmits the third
wave (A) to the layer of holographic material
through the optical device (80) and the beam-
20 splitter plate (81).
21. The system as claimed in either of claims 16 to
19, characterized in that it comprises at least
one additional spatial light modulator (27, 28)
25 not located in the plane of said optical modulator
(23) and making it possible to record, in the
hologram, at least one additional image appearing,
on reading, in a plane different from said image
of the part of the document.
- 30 22. The system as claimed in claim 21, characterized
in that the additional image and the image of the
part of the document are recorded at different
wavelengths and/or different angles of incidence
35 of the recording beams.
23. The system as claimed in one of claims 16 to 19,

characterized in that the first reference wave (R) and the third object wave (O) are plane, coherent and collinear waves.

24. The system as claimed in one of claims 16 to 23,
5 characterized in that said means inducing scrambling are placed against or almost against the layer of photosensitive material.

25. The system for reading a document comprising a
10 hologram containing an image of part of said document, said image being scrambled, characterized in that it comprises a device for correcting said scramblings, or revealer (27), said hologram being readable through the revealer.

15 26. The system as claimed in claim 25, characterized in that it comprises a marking device making it possible to position the hologram to be read facing the revealer (27).

20 27. The system as claimed in claim 26, characterized in that it comprises lugs intended to accommodate notches from the document.

25 28. The system as claimed in claim 25, characterized in that the revealer comprises optical markers intended to be made to coincide with the markers of the document.