

TWIN LIFTING MACHINERY FOR TWO 40 FEET CONTAINER SHORE CRANE

Field of invention

The invention generally relates to cranes, more particularly, relates to a twin lifting machinery for two 40 feet container shore crane.

Background of invention

The increasing requirements of container transportation in the world and the continuous increment of the handling capacity of the container port put forward new and increased demands on the technical equipment for loading and unloading containers, and an urgent need for the design and development of high efficient bank-run container load and unload systems to meet the demand of the lifter productivity needed by the larger ships.

The main lifting machinery of the crane of the prior art carries out the lifting and lowering operation of one hanger tool only, hence only one 40 feet container or two 20 feet containers can be lifted at a time so that limits the production efficiency and does not meet the market requirement.

Summary of invention

It is an object of the invention to provide a twin lifting machinery for two 40 feet container shore crane.

According to the present invention, a twin lifting machinery for two 40 feet container shore crane is provided, said lifting machinery comprises: motors, high speed brakes, reducers, multiple-project rope reels, and reel brakes connecting to each multiple-project rope reel respectively; wherein two or four motors are provided according to the power requirement; two reducers having high speed input shafts and low speed output shafts are provided; said high speed brakes are provided on one of the input shafts of the reducers respectively; said each one of the multiple-project rope reels is provided on one of the low speed output shafts of the reducers respectively; said reel brakes are provided on corresponding multiple-project rope reels respectively.

According to an embodiment of the present invention, said two reducers provided on the output ends of the motors have a land side output and a sea side output; said land side output connects to the land side multiple-project rope reel which has four project ropes connecting to a hanger tool; said sea side output connects to the sea side multiple-project rope reel which has four project ropes connecting to another hanger tool.

According to an embodiment of the present invention, two motors are provided as motors; the output end of the motor connects to the input shaft of the reducer, and a high speed brake is provided on the input shaft of the reducer; the output end of the motor connects to the input shaft of the reducer, and a high speed brake is provided on the input shaft of the reducer.

According to an embodiment of the present invention, four motors are provided as motors; each output ends of the two motors connects to one of the input shafts of the reducers respectively, and a high speed brake is provided on the input shaft of the reducer; each output ends of the two motors connects to one of the input shafts of the reducers respectively, and a high speed brake is provided on the input shaft of the reducer.

According to an embodiment of the present invention, reel brakes are provided on said four-project rope reel of the land side; and reel brakes are provided on said four-project rope reel of the sea side.

According to an embodiment of the present invention, reel brakes are provided on each one of the two two-project rope reels of the land side respectively; and reel brakes are provided on each one of the two two-project rope reels of the sea side respectively.

Compared with the prior art, the twin lifting machinery for the two 40 feet container shore crane of the present invention has the following advantages and active effects:

Since two reducers and at least two motors have been used in the present invention, both the synchronous operation and the individual operation of two sets of the lifting machineries in the twin lifting machinery under the electric control can be

carried out. The twin lifting machinery can carry out lifting and lowering of two hanger tools of the sea side and the land side, either the synchronous operation of two hanger tools or the individual operation of a single hanger tool is possible, so that the loading and unloading efficiency of the container crane may be increased by more than 60%.

Brief description of drawings

The object, concrete structure, features and advantages of the invention may be further understood from the following description of the embodiments of the twin lifting machinery for two 40 feet container shore crane according to the invention referring to the appended drawings in which:

Figure 1 is the schematic structure view of the first embodiment of the twin lifting machinery with two motors driving two four-project rope reels for two 40 feet container shore crane according to the invention;

Figure 2 is the schematic structure view of the second embodiment of the twin lifting machinery with two motors driving two four-project rope reels for two 40 feet container shore crane according to the invention;

Figure 3 is the schematic structure view of the third embodiment of the twin lifting machinery with two motors driving two four-project rope reels for two 40 feet container shore crane according to the invention;

Figure 4 is the schematic structure view of the fourth embodiment of the twin lifting machinery with two motors driving two four-project rope reels for two 40 feet container shore crane according to the invention.

Detailed description of preferred embodiments

Referring to figure 1, 2, 3 and 4, the twin lifting machinery for two 40 feet container shore crane according to the present invention (taking two 40 feet containers for example) includes: motors 10, reducers 20 connecting to the motors 10, a plurality of high speed shaft brakes 50 provided on the input ends of the reducers 20, a plurality of project rope reels 30 provided on the output ends of the reducers, and a plurality of reel brakes connecting to each project rope reel respectively.

Two or four motors 10 may be provided according to the motor power, two reducers are provided so that four two-project rope reels 30 may be driven by the two motors 10 through the two reducer 20, four two-project rope reels 30 may be driven by the four motors through the two reducers 20, or two four-project rope reels 30 be driven by the two motors through the two reducers 20, or two four-project rope reels 30 may be driven by the four motors through the two reducer 20.

The first embodiment

Refer to figure 1.

According to the embodiment, the twin lifting machinerys with two motors driving two four-project rope reels for two 40 feet container shore crane includes: motors 10, high speed brakes 50, two reducers 20, two four-project rope reels 30, and reel brakes 40 connecting to the four-project rope reels 30 respectively;

Two motors are provided as motors 10;

The input ends of the two reducers 20 connect to one of the output ends of the motors 10 respectively.

The input ends of the two reducers 20 are provided on one of the high speed brakes 50 respectively;

The four-project rope reels 30 are provided on one of the output ends of the two reducers 20 respectively;

The reel brakes 40 are provided on each four-project rope reel 30 respectively;

The (land side) reducer 21 has an output end 25, the output end 25 connects to a four-project rope reel 31, the four-project rope reel 31 has four project ropes connecting to a hanger tool;

The (sea side) reducer 22 has an output end 26, the output end 26 connects to a four-project rope reel 32, the four-project rope reel 32 has four project ropes connecting to another tool.

The reel brakes 41 are provided on a four-project rope reel 31 of the land side, the reel brakes 42 are provided on a four-project rope reel 32 of the sea side.

The second embodiment

Refer to figure 2.

According to the embodiment, the twin lifting machinery for two 40 feet container shore crane has four motors driving two four-project rope reels , the twin lifting machinery includes: motors 10, high speed brakes 50, two reducers 20, two four-project rope reels 30, and reel brakes 40 connecting to the four-project rope reels 30 respectively;

Four motors are provided as the motor 10;

Each one of the input ends of said two reducers 20 connect to one of the output ends of the motors 10 respectively.

Each one of the input ends of said two reducers 20 are provided on one of the high speed brakes 50 respectively;

The four-project rope reels 30 are provided on one of the output ends of said two reducers 20 respectively;

The reel brakes 40 are provided on said each four-project rope reel 30 respectively;

The (land side) reductor 21 has an output end 25, the output end 25 connects to a four-project rope reel 31, and the four-project rope reel 31 has four project ropes connecting to a hanger tool;

The (sea side) reductor 22 has an output end 26, the output end 26 connects to a four-project rope reel 32, and the four-project rope reel 32 has four project ropes connecting to another tool.

The reel brakes 41 are provided on a four-project rope reel 31 of the land side, and the reel brakes 42 are provided on a four-project rope reel 32 of the sea side.

The third embodiment

Refer to figure 3.

According to the embodiment, the twin lifting machinery for two 40 feet container shore crane having two motors driving four two-project rope reels , said twin lifting machinery includes: motors 10, high speed brakes 50, two reducers 20, four

two-project rope reels 30, and reel brakes 40 connecting to the four two-project rope reels 30 respectively;

Two motors are provided as motors 10;

Each one of the input ends of said two reducers 20 connect to one of the output ends of the motors 10 respectively.

Each one of the input ends of said two reducers 20 are provided on one of the high speed brakes 50 respectively;

The two-project rope reels 30 are provided on one of the output ends of the two reducers 20 respectively;

The reel brakes 40 are provided on each one of the two-project rope reel 30 respectively;

The (land side) reductor 21 has an output end 25, the output end 25 connects to two two-project rope reels 31, the two two-project rope reels 31 have four project ropes connecting to a hanger tool;

The (sea side) reductor 22 has an output end 26, the output end 26 connects to two two-project rope reels 32, the two two-project rope reels 32 have four project ropes connecting to another tool.

The reel brakes 41 are provided on two two-project rope reels 31 of the land side, and the reel brakes 42 are provided on two two-project rope reels 32 of the sea side.

The fourth embodiment

Refer to figure 4.

According to the embodiment, the twin lifting machinery for two 40 feet container shore crane having four motors driving four two-project rope reels, said twin lifting machinery includes: motors 10, high speed brakes 50, two reducers 20, four two-project rope reels 30, and reel brakes 40 connecting to the four two-project rope reels 30 respectively;

Two motors are provided as motors 10;

Each one of the input ends of said two reducers 20 connect to one of the output ends of the motors 10 respectively.

Each one of the input ends of said two reducers 20 are provided on one of the high speed brakes 50 respectively;

The two-project rope reels 30 are provided on one of the output ends of said two reducers 20 respectively;

The reel brakes 40 are provided on said each two-project rope reel 30 respectively;

The (land side) reductor 21 has an output end 25, the output end 25 connects to two two-project rope reels 31, the two two-project rope reels 31 have four project ropes connecting to a hanger tool;

The (sea side) reductor 22 has an output end 26, the output end 26 connects to two two-project rope reels 32, the two two-project rope reels 32 have four project ropes connecting to another hanger tool.

The reel brakes 41 are provided on two two-project rope reels 31 of the land side, and the reel brakes 42 are provided on two two-project rope reels 32 of the sea side.

The twin lifting machinery for two 40 feet container shore crane of the invention uses two or four motors and two reducers, four two-project rope reels may be driven by two motors through two reducers, or four two-project rope reels may be driven by four motors through two reducers, or two four-project rope reels may be driven by two motors through two reducers, or two four-project rope reels may be driven by four motors through two reducers. Thus the synchronous operation or individual operation of two sets of lifting machineries under electrical control can be carried out, achieving the lifting and lowering operation of two hanger tools of sea side or land side. The twin lifting machinery can carry out both synchronous operation of two hanger tools and individual operation of a single hanger tool, increasing the loading and unloading efficiency of the container crane by more than 60%.

CLAIMS

1. A twin lifting machinery for two 40 feet container shore crane, comprising:
motors (10);
high speed brakes (50);
reducers (20);
multiple-project rope reels (30);and
reel brakes (40) connecting to each multiple-project rope reel (30) respectively;
wherein,
two or four motors are provided according to the power requirement;
two reducers having high speed input shafts and low speed output shafts are provided;
said high speed brakes (50) are provided on one of the input shafts (23,24) of the reducers (20) respectively;
said each one of the multiple-project rope reels (30) is provided on one of the low speed output shafts of the reducers respectively;
said reel brakes (40) are provided on corresponding multiple-project rope reels (30) respectively.
2. The twin lifting machinery of claim 1 wherein:
said two reducers (20) provided on the output ends of the motors (10) have a land side output (25) and a sea side output (26);
said land side output (25) connects to the land side multiple-project rope reel (31) which has four project ropes connecting to a hanger tool;
said sea side output (26) connects to the sea side multiple-project rope reel (32) which has four project ropes connecting to another hanger tool.
3. The twin lifting machinery of claim 1 wherein,
two motors (11,12) are provided as motors (10);
the output end of the motor (11) connects to the input shaft (23) of the reductor

(21), and a high speed brake (51) is provided on the input shaft (23) of the reductor (21);

the output end of the motor (12) connects to the input shaft (24) of the reductor (22), and a high speed brake (52) is provided on the input shaft (24) of the reductor (22).

4.The twin lifting machinery of claim 1 wherein,

four motors (two motors 11 and two motors 12) are provided as motors (10);

each output ends of the two motors (11) connects to one of the input shafts (23) of the reductors (21) respectively, and a high speed brake (51) is provided on the input shaft (23) of the reductor (21);

each output ends of the two motors (12) connects to one of the input shafts (24) of the reductors (22) respectively, and a high speed brake (52) is provided on the input shaft (24) of the reductor(22).

5.The twin lifting machinery of claim 1 or 2 wherein,

reel brakes (41) are provided on said four-project rope reel (31) of the land side; and reel brakes (42) are provided on said four-project rope reel (32) of the sea side.

6.The twin lifting machinery of claim 1 or 2 wherein,

reel brakes (41) are provided on each one of the two two-project rope reels (31) of the land side respectively; and reel brakes (42) are provided on each one of the two two-project rope reels (32) of the sea side respectively.