

DESCRIPTION

INFORMATION STORAGE DEVICE, REMOVABLE DEVICE, DEVELOPER
CONTAINER, AND IMAGE FORMING APPARATUS

5

TECHNICAL FIELD

The present invention relates to an image forming
apparatus such as a copying machine, a printer, a facsimile,
or a multi-function peripheral (MFP), a removable device
10 and a developer container that are removably installed
therein, and an information storage device installed
therein.

BACKGROUND ART

15 Conventionally, in an image forming apparatus such as
a copying machine, a technique of removably installing a
removable device such as a developer container (a toner
bottle, a toner storage container, or an ink cartridge) or
a process cartridge on an image forming apparatus body has
20 been usually used (for example, Patent Literature 1:
Japanese Patent Application Laid-open No. 2009-69417,
Patent Literature 2: Japanese Patent Application Laid-open
No. 2006-209060, and Patent Literature 3: Japanese Patent
Application Laid-open No. 2002-196629).

25 In the removable device, an information storage device
(an information recording unit or a non-volatile memory)
such as an ID chip storing information to be exchanged with
the image forming apparatus body is installed. In a state
in which the removable device is set to the image forming
30 apparatus body, information (for example, information such
as manufacturing year, month, and date of the removable
device, a manufacturing lot number, or a color of toner, or
a kind of toner) stored in the information storage device

is transmitted to a control unit of the image forming apparatus body, or information (information such as a use history of the image forming apparatus) is transmitted from the image forming apparatus body to the information storage device, so that fulfilling quality control of the image forming apparatus body and the removable device is performed.

Patent Literature 1 discloses a contact-type information storage device (an information recording unit). Specifically, in the contact-type information storage device (an ID chip), when the removable device (a toner storage container) is set to the image forming apparatus body, a metal pad (a terminal) comes in contact with a body side terminal of a connector installed in the image forming apparatus body. As a result, information can be exchanged between the information storage device of the removable device and the control unit (the body side information recording unit) of the image forming apparatus.

Further, a feeding opening for allowing the stored toner to flow out to the outside is installed in the developer container. The opening needs remain closed until it is loaded onto a developing device so as to prevent the toner from being scattered or leaking.

As a configuration for achieving the above desire, there has been suggested a configuration in which a shutter for opening/closing the opening installed in the developer container is installed. Further, as a configuration of the shutter, there has been suggested a configuration in which a flat plate-like shutter that is movable in a direction traversing the toner and an outlet is installed (For example, Patent Literature 4: Japanese Patent Application Laid-open No. 2010-066638).

However, the conventional techniques described above

have the following problems.

As a first problem, the conventional contact-type information storage device may electrically get damaged since an electric circuit of the information storage device is not sufficiently earthed and so becomes an electrically floating state when the removable device is attached to or removed from the device body.

The present invention is made to solve the first problem described above and provides an information storage device, a removable device, a developer container, and an image forming apparatus in which electrical damage is difficult to occur in the information storage device even when the contact-type information storage device is installed in the removable device removably installed in the image forming apparatus body.

As a second problem, in the conventional contact-type information storage device, there may occur a problem in that contact sections thereof are misaligned (a contact failure) due to wrong positioning of the terminal (metal pad) installed in the information storage device and the terminal of the image forming apparatus body. Particularly, when the terminal of the information storage device is small, the problem becomes important.

The present invention is made to solve the second problem described above and provides a removable device, a developer container, and an image forming apparatus in which a contact failure caused by a positioning failure with the body side terminal of the connector of the image forming apparatus body is difficult to occur even when the contact-type information storage device is installed in the removable device removably installed in the image forming apparatus body.

A third problem is as follows. In recent years, toner

having a small particle diameter has been used so as to improve the resolution. Improving a filter function so as to cope with using the toner may increase the material or processing cost. That is, when a foamable material is used, it is necessary to prescribe mesh fineness that does not let the toner through, a so-call foaming degree, but as mesh fineness increases, flexibility tends to decrease. This tendency may be difficult to go along with movement of the shutter, and a sealing characteristic may get worse.

10 The present invention has an improved invention of a shutter mechanism of the conventional toner feeding device. The improved invention provides a developer storage container and an image forming apparatus which have a configuration capable of reliably preventing the toner from leaking from the developer storage container that is replaced by an attaching/detaching operation at a low cost.

DISCLOSURE OF INVENTION

20 In the present invention, a "process cartridge" is defined as a removable device that is configured such that at least one of a charging unit for charging an image carrier, a developing unit (a developing device) for developing a latent image formed on the image carrier, and a cleaning unit for cleaning the surface of the image carrier is integrally formed with the image carrier and that is installed removably on the image forming apparatus body.

30 Further, in the present invention, a "nearly rectangular metallic plate" is defined to include a nearly rectangular one as well as a rectangular one. Thus, one in which all or part of an angular section of the rectangular metallic plate is chamfered and an R-shaped one are also included in the "nearly rectangular metallic plate."

The effect of the present invention on the first problem is as follows. The present invention can provide an information storage device, a removable device, a developer container, and an image forming apparatus in which electrical damage is difficult to occur in the information storage device even when the contact-type information storage device is installed in the removable device removably installed on the image forming apparatus body since an earth terminal engaged with a body side earth terminal formed in a protruding section of the image forming apparatus body is formed in a hole or a notch formed in a substrate of the information storage device.

The effect of the present invention on the second problem is as follows. In the present invention, the contact-type information storage device is held on a holding section to be movable on a virtual plane that is substantially orthogonal to a movement direction in which a terminal approaches and comes in contact with a body side terminal. Thus, the present invention can provide a removable device, a developer container, and an image forming apparatus in which a contact failure caused by a positioning failure with the body side terminal of the connector of the image forming apparatus body is difficult to occur even when the contact-type information storage device is installed in the removable device removably installed in the image forming apparatus body.

The effect of the present invention on the third problem is as follows. According to the present invention, by causing riding-up when hitting against a rib disposed on a circumferential edge of an ejecting opening, adhesion can be secured.

Thus, by using a shutter that is an existing component used for opening/closing the ejecting opening, a toner leak

from the ejecting opening can be reliably prevented without adding a special structure.

BRIEF DESCRIPTION OF DRAWINGS

5 Fig. 1 is an overall configuration view illustrating an image forming apparatus according to an embodiment;

 Fig. 2 is a cross sectional view illustrating an image forming unit;

 Fig. 3 is a schematic view illustrating a state in
10 which a toner container is installed in a toner feeding device;

 Fig. 4 is a schematic perspective view illustrating a state in which four toner containers are installed in a toner container storage unit;

15 Fig. 5 is a schematic perspective view illustrating a state in which one toner container is installed in a toner container storage unit;

 Fig. 6 is a side view illustrating a state in which a toner container is installed in a toner container storage
20 unit;

 Fig. 7 is a cross sectional view illustrating a state in which a cap section is installed in a cap receiving section;

 Fig. 8 is a perspective view illustrating a cap
25 receiving section of a toner container storage unit;

 Fig. 9 is an enlarged perspective view illustrating a neighborhood of a leading end section of a bottle receiving section;

 Fig. 10 is a back view illustrating a state in which a
30 cap section is set to a bottle receiving section in a regular toner container;

 Fig. 11 is a back view illustrating a state in which a cap section is set to a bottle receiving section in a non-

regular toner container;

Fig. 12 is a perspective view illustrating a cap receiving section to which a cap section is set;

Fig. 13 is a front view illustrating a cap receiving
5 section in a state in which a cap section is set;

Fig. 14A is a back view illustrating a cap receiving section, and Fig. 14B is a partial enlarged view illustrating a neighborhood of a contacted groove encircled by a dotted line in a cap receiving section of Fig. 14A;

10 Fig. 15 is a perspective view illustrating a cap receiving section from obliquely below;

Fig. 16 is a perspective view illustrating a connector;

Fig. 17 is a schematic view illustrating a state in
15 which an information storage device of a cap section is set to a connector of a cap receiving section;

Fig. 18 is a perspective view illustrating a toner container from obliquely below;

Fig. 19 is a side view illustrating a toner container;

20 Fig. 20 is a perspective view illustrating a cap section side of a toner container from obliquely below;

Fig. 21 is a front view illustrating a toner container from a cap section side;

Fig. 22 is a perspective view illustrating a state in
25 which a shutter member of a toner container closes a toner discharge opening;

Fig. 23 is a perspective view illustrating a state in which a shutter member of a toner container opens a toner discharge opening;

30 Figs. 24A to 24C are schematic views illustrating an opening operation of a shutter member that is in conjunction with a mounting operation of a toner container on a toner container storage unit;

Fig. 25 is a perspective view illustrating a shutter member;

Fig. 26 is another perspective view illustrating a shutter member;

5 Fig. 27 is a perspective view illustrating a state in which an information storage device is extracted;

Fig. 28 is a six-plane view illustrating a holding member of an information storage device;

10 Fig. 29 is a three-plane view illustrating an information storage device;

Fig. 30 is a cross sectional view illustrating a neighborhood of a cap section of a toner container;

15 Fig. 31 is a schematic cross sectional view illustrating a toner container according to a second embodiment;

Fig. 32 is a back view illustrating a cap section in the toner container of Fig. 31;

Fig. 33 is a perspective view illustrating a holding cover engaged with a holding member;

20 Fig. 34 is a schematic view illustrating a state in which an information storage device of a toner container according to a third embodiment is set to a connector of a cap receiving section;

25 Fig. 35 is a three-plane view illustrating a substrate of an information storage device according to a fourth embodiment;

Fig. 36 is a three-plane view illustrating a substrate of an information storage device according to a fifth embodiment;

30 Fig. 37 is a perspective view illustrating an information storage device, a holding member, and a connector;

Fig. 38 is a perspective view illustrating a state in

which an information storage device is engaged with a connector;

Figs. 39A and 39B are schematic views illustrating an electric circuit of an information storage device and an electric circuit of a connector;

Figs. 40A and 40B are front views illustrating an information storage device;

Fig. 41 is a view illustrating an information storage device in an inspection process;

Figs. 42A and 42B are perspective views illustrating a toner container according to a sixth embodiment;

Fig. 43 is a front view illustrating a toner container in which a face plate is not installed;

Fig. 44 is a cross sectional view illustrating a toner container in which an information storage device and a face plate are installed;

Fig. 45 is a view illustrating a state in which an information storage device is being inserted into a connector;

Figs. 46A and 46B are perspective views illustrating a toner container of another form;

Figs. 47A to 47C are views illustrating a toner container of another form;

Fig. 48 is an exploded perspective view illustrating a toner container according to a seventh embodiment;

Fig. 49 is a cross sectional view illustrating the toner container of Fig. 48;

Fig. 50 is a perspective view illustrating an image forming apparatus according to an eighth embodiment;

Figs. 51A and 51B illustrate toner cartridges installed in the image forming apparatus of Fig. 50, Fig. 51A is a cross sectional view, and Fig. 51B is a bottom view;

Fig. 52 is a perspective view illustrating an image forming apparatus according to a ninth embodiment;

Fig. 53 is a schematic view illustrating a state in which a connector is connected to an information storage device in the image forming apparatus of Fig. 52;

Fig. 54 is a perspective view illustrating an ink cartridge according a tenth embodiment;

Fig. 55 is a top view illustrating an image forming apparatus in which the ink cartridge of Fig. 54 is installed;

Fig. 56 is a perspective view illustrating a connector of an image forming apparatus according to the tenth embodiment;

Fig. 57 is a three-plan view illustrating an information storage device that comes in contact with the connector of Fig. 56;

Fig. 58 is a three-plane view illustrating an information storage device of another form;

Fig. 59 is a perspective view illustrating a toner container according to a twelfth embodiment;

Fig. 60 is an enlarged perspective view illustrating configurations of an information storage device and a holding member according to the twelfth embodiment;

Fig. 61 is an exploded perspective view illustrating the configurations of the information storage device and the holding member according to the twelfth embodiment;

Fig. 62 is an enlarged perspective view illustrating a fixing state between the information storage device and the holding member according to the twelfth embodiment;

Fig. 63 is an enlarged perspective view illustrating a fixing state between an information storage device and a holding member according to a thirteenth embodiment;

Fig. 64 is an enlarged perspective view illustrating

configurations of the information storage device and the holding member according to the thirteenth embodiment;

Fig. 65 an enlarged perspective view illustrating a fixing state between an information storage device and a holding member according to a fourteenth embodiment;

Fig. 66 is an enlarged perspective view illustrating configurations of the information storage device and the holding member according to the fourteenth embodiment;

Fig. 67 is a cross sectional view illustrating a cap section illustrated in Fig. 18;

Fig. 68 is a perspective view, viewed from a bottom surface of a shutter, for explaining a configuration of a shutter used in a cap section illustrated in Fig. 18;

Figs. 69A and 69B are views, corresponding to Fig. 18, for explaining an opening/closing state of a shutter illustrated in Figs. 69A and 69B;

Figs. 70A to 70C are views for explaining a configuration of the shutter illustrated in Figs. 69A and 69B;

Figs. 71A to 71C are views illustrating an opening state of the shutter illustrated in Figs. 70A to 70C and a cross section of the state;

Fig. 72 is a plane view for explaining a relation between a body side shutter closing mechanism and a shutter;

Fig. 73 is a plane view illustrating a state of the body side shutter closing mechanism illustrated in Fig. 72;

Fig. 74 is a plane view illustrating a state of the body side shutter closing mechanism that has changed from the state illustrated in Fig. 73;

Figs. 75A to 75D are views for explaining a positional relation between a toner discharge opening and a shutter and a sealing state of a seal material;

Figs. 76A and 76B are views illustrating a configuration of an information storage device used in a sixteenth embodiment;

Fig. 77 is a perspective view of a cap receiving side that becomes part of an electrical connection section with an information storage device;

Fig. 78 is a perspective view illustrating a common electronic substrate including a shutter connected with an information storage device;

Fig. 79 is a view for explaining a connection state between the information storage device used in the sixteenth embodiment and a connector at a cap receiving section side;

Fig. 80 is a perspective view, viewed from a front right side in an insertion direction of a cap in the state in which a shutter is closed, for explaining a modification related to a configuration of a cap section according to a seventeenth embodiment;

Fig. 81 is a perspective view viewed from a front left side in an insertion direction of the cap illustrated in Fig. 80;

Fig. 82 is an exploded perspective view of the cap section illustrated in Fig. 80;

Fig. 83 is a perspective view illustrating a modification of a main part of the cap section illustrated in Fig. 80;

Fig. 84 is a plane view for explaining an aspect of a body side shutter closing mechanism targeting on the cap section illustrated in Fig. 80;

Fig. 85 is a plane view illustrating the body side shutter closing mechanism illustrated in Fig. 84;

Fig. 86 is a plane view illustrating a state of the body side shutter closing mechanism that has changed from

the state illustrated in Fig. 85;

Fig. 87 is a three-plane view illustrating an alternative of the substrate illustrated in Fig. 36; and

Figs. 88A to 88C are plane views illustrating further
5 alternatives of the substrate illustrated in Fig. 36.

BEST MODE(S) FOR CARRYING OUT THE INVENTION

Hereinafter, embodiments of the present invention will be described in detail with reference to the accompanying
10 drawings. In the drawings, the same or corresponding parts are denoted by the same reference numerals, and thus a duplicated description thereof will be appropriately simplified or omitted.

15 First Embodiment

A first embodiment of the present invention will be described in detail with reference to Figs. 1 to 30.

First, a configuration and operation of the entire image forming apparatus will be described.

20 As illustrated in Fig. 1, in a toner container storage unit 70 above an image forming apparatus body 100, toner containers 32Y, 32M, 32C, and 32K (developer containers) are removably (replaceably) installed as four removable devices corresponding to respective colors (yellow, magenta,
25 cyan, and black) (also see Figs. 3 to 5).

An intermediate transfer unit 15 is disposed below the toner container storage unit 70. Image forming units 6Y, 6M, 6C, and 6K corresponding to respective colors (yellow, magenta, cyan, and black) are disposed in line to face an
30 intermediate transfer belt 8 of the intermediate transfer unit 15.

Toner feeding devices 60Y, 60M, 60C, and 60K are disposed below the toner containers 32Y, 32M, 32C, and 32K

as the removable devices (developer containers), respectively. The toners stored in the toner containers 32Y, 32M, 32C, and 32K are supplied (fed) to the inside of the developing devices of the image forming units 6Y, 6M, 5 6C, and 6K by the toner feeding devices 60Y, 60M, 60C, and 60K, respectively.

Referring to Fig. 2, the image forming unit 6Y corresponding to yellow includes a photosensitive drum 1Y, a charging unit 4Y disposed around the photosensitive drum 10 1Y, a developing device 5Y (a developing section), a cleaning unit 2Y, a neutralizing unit (not shown), or the like. An image forming process (a charging process, an exposure process, a developing process, a transfer process, and a cleaning process) is performed on the photosensitive 15 drum 1Y, and so a yellow image is formed on the photosensitive drum 1Y.

The remaining three image forming units 6M, 6C, and 6K have almost the same configuration as the image forming unit 6Y corresponding to yellow except that colors of used 20 toner are different. Hereinafter, a description of the remaining three image forming units 6M, 6C, and 6K will be appropriately omitted, and a description will be made in connection with the image forming unit 6Y corresponding to yellow.

25 Referring to Fig. 2, the photosensitive drum 1Y is rotationally driven clockwise in Fig. 2 by a driving motor (not shown). The surface of the photosensitive drum 1Y is uniformly charged at the position of the charging unit 4Y (the charging process).

30 Thereafter, the surface of the photosensitive drum 1Y reaches an irradiation position of laser light L emitted from an exposure unit 7 (see Fig. 1), and an electrostatic latent image corresponding to yellow is formed by exposure

scanning at this position (the exposure process).

Then, the surface of the photosensitive drum 1Y reaches the position facing the developing device 5Y, and the electrostatic latent image is developed at this
5 position, so that a yellow toner image is formed (the developing process).

Next, the surface of the photosensitive drum 1Y reaches the position facing the intermediate transfer belt 8 and a primary transfer bias roller 9Y, and the toner
10 image on the photosensitive drum 1Y is transferred onto the intermediate transfer belt 8 at this position (a primary transfer process). At this time, a slight amount of non-transfer toner remains on the photosensitive drum 1Y.

Thereafter, the surface of the photosensitive drum 1Y
15 reaches the position facing the cleaning unit 2Y, and the non-transfer toner remaining on the photosensitive drum 1Y is mechanically collected by a cleaning blade 2a at this position (the cleaning process).

Finally, the surface of the photosensitive drum 1Y
20 reaches the position facing the neutralizing unit (not shown), and residual potential on the photosensitive drum 1Y is removed at this position.

Thus, a series of image forming processes performed on the photosensitive drum 1Y are finished.

25 The above described image forming process is performed even in the other image forming units 6M, 6C, and 6K in the same manner as in the yellow image forming unit 6Y. That is, the laser light L based on image information is irradiated from the exposure unit 7 disposed below the
30 image forming units onto the photosensitive drums of the image forming units 6M, 6C, and 6K. Specifically, the exposure unit 7 emits the laser light L from a light source and irradiates the laser light L onto the photosensitive

drum through a plurality of optical elements while scanning the laser light L by a polygon mirror that is rotationally driven.

Thereafter, toner images of respective colors formed
5 on the respective photosensitive drums through the developing process are transferred onto the intermediate transfer belt 8 in a superimposed manner. As a result, a color image is formed on the intermediate transfer belt 8.

Referring to Fig. 1, the intermediate transfer unit 15
10 includes the intermediate transfer belt 8, four primary transfer bias rollers 9Y, 9M, 9C, and 9K, a secondary transfer bias roller 12, a plurality of tension rollers, an intermediate transfer cleaning unit, and the like. The intermediate transfer belt 8 is stretched over and
15 supported by a plurality of roller members and endlessly moves in a direction of an arrow in Fig. 1 as one roller member 12 is rotationally driven.

The four primary transfer bias rollers 9Y, 9M, 9C, and 9K sandwich the intermediate transfer belt 8 together with
20 the photosensitive drums 1Y, 1M, 1C, and 1K, respectively, to form primary transfer nips. A transfer bias reverse to a polarity of the toner is applied to the primary transfer bias rollers 9Y, 9M, 9C, and 9K.

The intermediate transfer belt 8 moves in a direction
25 of an arrow and sequentially passes through the primary transfer nips of the primary transfer bias rollers 9Y, 9M, 9C, and 9K. The toner images of respective colors on the photosensitive drums 1Y, 1M, 1C, and 1K are primary-transferred onto the intermediate transfer belt 8 in a
30 superimposed manner.

Thereafter, the intermediate transfer belt 8 onto which the toner images of respective colors are transferred in a superimposed manner reaches the position facing a

secondary transfer roller 19. At this position, the secondary transfer bias roller 12 sandwiches the intermediate transfer belt 8 together with the secondary transfer roller 19 to form a secondary transfer nip. The toner images of four colors formed on the intermediate transfer belt 8 are transferred onto a recording medium P such as a transfer sheet conveyed to the position of the secondary transfer nip. At this time, the non-transfer toner that has not been transferred onto the recording medium P remains on the intermediate transfer belt 8.

Thereafter, the intermediate transfer belt 8 reaches the position of the intermediate transfer cleaning unit (not shown). At this position, the non-transfer toner on the intermediate transfer belt 8 is collected.

As a result, a series of transfer processes performed on the intermediate transfer belt 8 are finished.

The recording medium P conveyed to the position of the secondary transfer nip is conveyed through a paper feeding roller 27, a pair of resist rollers 28, and the like from a paper feeding unit 26 disposed below the apparatus body 100.

Specifically, a plurality of recording media P such as transfer sheets are stored in a superimposed manner in the paper feeding unit 26. If the paper feeding roller 27 is rotationally driven counterclockwise in Fig. 1, the top recording medium P is fed toward between the rollers of the pair of resist rollers 28.

The recording medium P fed to the pair of resist rollers 28 stops at the position of a roller nip of the pair of resist rollers 28 that has stopped rotational driving. In synchronization with timing of the color image on the intermediate transfer belt 8, the pair of resist rollers 28 is rotationally driven, and the recording medium P is conveyed toward the secondary transfer nip. Thus, a

desired color image is transferred onto the recording medium P.

Thereafter, the recording medium P onto which the color image has been transferred at the position of the secondary transfer nip is conveyed to the position of a fixing device 20. At this position, the color image transferred onto the surface is fixed to the recording medium P by heat and pressure by a fixing belt and a pressing roller.

Thereafter, the recording medium P passes through between rollers of a pair of ejecting rollers 29 and then is ejected to the outside of the apparatus. A recording medium P ejected to the outside of the apparatus by the pair of ejecting rollers 29 is sequentially stacked on a stack unit 30 as an output image.

Thus, in the image forming apparatus, a series of image forming processes are finished.

Next, a configuration and operation of the developing device in the image forming unit will be described in further detail with reference to Fig. 2.

The developing device 5Y includes a developing roller 51Y facing the photosensitive drum 1Y, a doctor blade 52Y facing the developing roller 51Y, two conveying screws disposed in developer storage units 53Y and 54Y, a density detecting sensor 56Y for detecting the density of the toner contained in the developer, and the like. The developing roller 51Y is configured with a magnet fixedly disposed to the inside thereof, a sleeve rotating around the magnet, and the like. A two-component developer G composed of a carrier and a toner is stored in the developer storage units 53Y and 54Y. The developer storage unit 54Y is communicated with a toner falling conveying path 64Y through an opening formed thereabove.

The developing device 5Y having the above described configuration operates as follows.

The sleeve of the developing roller 51Y rotates in a direction of an arrow in Fig. 2. The developer G supported
5 on the developing roller 51Y by a magnetic field formed by the magnet moves on the developing roller 51Y as the sleeve rotates.

The developer G inside the developing device 5Y is adjusted so that a ratio of toner (toner density) contained
10 in the developer can be within a predetermined range. Specifically, as the toner inside the developing device 5Y is consumed, the toner stored in the toner container 32Y is fed to the inside of the developer storage unit 54Y through the toner feeding device 60Y (for example, see Fig. 3). A
15 configuration and operation of the toner feeding device will be described later in detail.

Thereafter, the toner fed to the inside of the developer storage unit 54Y circulates through the two
20 developer storage units 53Y and 54Y while being mixed and agitated together with the developer G by the two conveying screws 55Y (movement in a direction vertical to a paper plane of Fig. 2). The toner in the developer G is absorbed into the carrier by frictional electrification with the carrier and supported on the developing roller 51Y together
25 with the carrier by magnetic force formed on the developing roller 51Y.

The developer G supported on the developing roller 51Y is conveyed in a direction of an arrow in Fig. 2 and then reaches the position of the doctor blade 52Y. The
30 developer G on the developing roller 51Y is adjusted to an appropriate developer amount at this position and then conveyed up to the position (a developing area) facing the photosensitive drum 1Y. The toner is absorbed into a

latent image formed on the photosensitive drum 1Y by a magnetic field formed on the developing area. Thereafter, as the sleeve rotates, the developer G remaining on the developing roller 51Y reaches above the developer storage unit 53Y and leaves the developing roller 51Y at this position.

Next, the toner feeding devices 60Y, 60M, 60C, and 60K will be described in detail with reference to Figs. 3 to 5.

Referring to Fig. 3, the toners inside the toner containers 32Y, 32M, 32C, and 32K installed in the toner container storage unit 70 of the apparatus body 100 are appropriately fed to the inside of the developing devices by the toner feeding devices 60Y, 60M, 60C, and 60K respectively installed for toner colors as the toners inside the developing devices of respective colors are consumed.

The four toner feeding devices 60Y, 60M, 60C, and 60K and the toner containers 32Y, 32M, 32C, and 32K (the developer containers) have almost the same configuration except that the toner colors used in the image forming process are different. Thus, a description will be made focusing on the toner feeding devices 60Y and the toner container 32Y corresponding to yellow, and a description of the toner feeding devices 60M, 60C, and 60K and the toner containers 32M, 32C, and 32K corresponding to the remaining three colors will be appropriately omitted.

Referring to Fig. 1, if a body cover (not shown) installed on the front side of the apparatus body 100 (the front side in a direction vertical to the paper plane in Fig. 1) is opened, the toner container storage unit 70 (an insertion opening 71) is exposed. In the state in which a longitudinal direction of the toner containers 32Y, 32M, 32C, and 32K (the developer containers) is a horizontal

direction, performed is an attaching/detaching operation of the toner containers 32Y, 32M, 32C, and 32K to/from the front side of the apparatus body 100 (an attaching/detaching operation in which the longitudinal
5 direction of the toner container is an attaching/detaching direction).

As illustrated in Fig. 4, when the toner containers 32Y, 32M, 32C, and 32K are mounted on the toner container storage unit 70 of the apparatus body 100 (movement in a
10 direction of an arrow Q), in conjunction with the mounting operation, a shutter member 34d of the toner containers 32Y, 32M, 32C, and 32K moves, and so a toner discharge opening W (a discharging opening) is opened, so that toner feeding
openings 73w (for example, see Fig. 3) of the toner feeding
15 devices 60Y, 60M, 60C, and 60K are communicated with the toner discharge opening W. The toner stored in the toner containers 32Y, 32M, 32C, and 32K is discharged from the toner discharge opening W and stored in a toner tank unit
61Y through the toner feeding opening 73w of the toner
20 feeding devices 60Y, 60M, 60C, and 60K.

Referring to the schematic view of Fig. 3, the toner container 32Y includes a cap section 34Y that is a nearly cylindrical-shaped toner bottle and is usually non-rotatably held on the toner container storage unit 70 and a
25 container body 33Y (a bottle body) in which a gear 33c is integrally formed. The container body 33Y is relatively rotatably held on the cap section 34Y and is rotationally driven in a direction of an arrow in Fig. 3 by a driving unit 91 (including a driving motor, a driving gear 81, and
30 the like). As the container body 33Y rotates, the toner stored inside the toner container 32Y (the container body 33Y) is conveyed in a longitudinal direction (conveyance from the left to the right in Fig. 3) by a protrusion 33b

formed on an inner peripheral surface of the container body 33Y in a helical form, and the toner is discharged from the toner discharge opening W of the cap section 34Y. That is, as the container body 33Y of the toner container 32Y is
5 appropriately rotationally driven by the driving unit 91, the toner is appropriately supplied to the toner tank unit 61Y. Further, when each of the toner containers 32Y, 32M, 32C, and 32K reaches the end of its life (when the stored toner is almost consumed and becomes empty), it is replaced
10 with a new one.

Referring to Fig. 3, the toner feeding devices 60Y, 60M, 60C, and 60K include the toner container storage unit 70, the toner tank unit 61Y, a toner conveying screw 62Y, an agitating member 65Y, a toner end sensor 66Y, the
15 driving unit 91, and the like.

The toner tank unit 61Y is disposed below the toner discharge opening W of the toner container 32Y and stores the toner discharged from the toner discharge opening W of the toner container 32Y. The bottom of the toner tank unit
20 61Y is connected with an upstream section of the toner conveying screw 62Y.

The toner end sensor 66Y that detects that the toner stored in the toner tank unit 61Y has become smaller than a predetermined amount is installed on the wall surface of
25 the toner tank unit 61Y (at the position of a predetermined height from the bottom). A piezoelectric sensor or the like may be used as the toner end sensor 66Y. When the control unit 90 detects that the toner stored in the toner tank unit 61Y has become smaller than a predetermined
30 amount (toner end detection) through the toner end sensor 66Y, the driving unit 91 rotationally drives the container body 33Y the toner container 32Y during a predetermined time under control of the control unit 90, so that the

toner is fed to the toner tank unit 61Y. Further, when toner end detection by the toner end sensor 66Y is not released even if such control is repeated, it is recognized that there is no toner in the toner container 32Y, and a
5 message for encouraging the replacement of the toner container 32Y is displayed on a display unit (not shown) of the apparatus body 100.

Further, the agitating member 65Y that prevents the toner stored in the toner tank unit 61Y from being
10 agglomerated is installed on the central section of the toner tank unit 61Y (near the toner end sensor 66Y). The agitating member 65Y has a flexible member installed on a shaft section and rotates clockwise in Fig. 3 to agitate the toner inside the toner tank unit 61Y. Further, the
15 leading end of the flexible member of the agitating member 65Y comes in sliding contact with the detection surface of the toner end sensor 66Y at a rotation period, thereby preventing a problem in that the toner is fixed to the detection surface of the toner end sensor 66Y and so a
20 degree of detection accuracy decreases.

Even though not shown, the toner conveying screw 62Y conveys the toner stored in the toner tank unit 61Y obliquely upward. Specifically, the toner conveying screw 62Y linearly conveys the toner from the bottom of the toner
25 tank unit 61Y (the lowest point) toward the top of the developing device 5Y. The toner conveyed by the toner conveying screw 62Y falls through the toner falling conveying path 64Y (for example, see Fig. 2) by its own weight and is fed to the inside of the developing device 5Y
30 (the developer storage unit 54Y).

Referring to Fig. 4, the toner container storage unit 70 mainly includes a cap receiving section 73 for holding the cap section 34Y of the toner container 32Y, a bottle

receiving section 72 (a container body bearing) for holding the container body 33Y of the toner container 32Y, and an insertion opening 71 that functions as an insertion opening at the time of the mounting operation of the toner container 32Y.

Next, the toner container storage unit 70 (the bottle receiving section 72 and the cap receiving section 73) will be described in detail with reference to Figs. 6 to 17.

First, as described above with reference to Figs. 4 and 5, the bottle receiving section 72, the cap receiving section 73, and the insertion opening 71 (that is not shown in Fig. 5) are formed in the toner container storage unit 70. The toner container 32Y is mounted on the toner container storage unit 70 through the insertion opening 71 by a user gripping a gripping section 33d in a state in which the longitudinal direction is the horizontal direction and the longitudinal direction is the mounting direction in which the cap section 34Y is the head of the container body 33Y. The toner container 32Y inserted through the insertion opening 71 is pushed toward the cap receiving section 73 by the user while sliding on a bottle receiving surface 72a of the bottle receiving section 72 (for example, see Figs. 5, 6, and 9). Referring to Fig. 6, in the bottle receiving section 72, the bottle receiving surface 72a is formed for each color, and the toner containers 32Y, 32M, 32C, and 32K corresponding to respective colors are inserted (inserted in a direction of a white arrow). Further, referring to Fig. 8, even in the cap receiving section 73, bottle receiving sections 73Y, 73M, 73C, and 73K are formed for respective colors, and the toner containers 32Y, 32M, 32C, and 32K corresponding to respective colors are inserted (inserted in a direction of a white arrow). At this position, the cap receiving section

is non-rotatably held.

Referring to Figs. 5 and 24(A), the bottle receiving surface 72a, a stopper release urging section 72b, and the like are formed in the bottle receiving section 72 of the toner container storage unit 70.

The bottle receiving surface 72a functions as a sliding surface of the toner container 32Y at the time of the attaching/detaching operation of the toner container 32Y and functions as a holding unit of the rotationally driven container body 33Y after the toner container 32Y has been completely set.

Referring to Fig. 5, the stopper release urging section 72b is a trapezoidal rib formed above the bottle receiving surface 72a (at the downstream side of the toner container 32Y in the mounting direction). Referring to Fig. 24, the stopper release urging section 72b pushes a stopper release section 34d21 of the shutter member 34d up and releases a contact state between a stopper section 34d22 and a contact section 34n5 in conjunction with the mounting operation of the toner container 32Y (allows an opening operation of the shutter member 34d).

Referring to Figs. 14A, 14B, and 15, in the cap receiving section 73 of the toner container storage unit 70, a main reference pin 73a, a sub reference pin 73b, a contacted groove 73m, a lateral groove 73h, a wall section 73g, a through hole 73f, and the like are disposed.

The main reference pin 73a and the sub reference pin 73b as positioning pins are fitted into a first positioning hole 34a and a second positioning hole 34b of the cap section 34Y of the toner container 32Y illustrated in Figs. 20 and 21, respectively. Positioning of the cap section 34Y is performed in the cap receiving section 73.

Referring to Fig. 7, the main reference pin 73a is

formed to be longer than the sub reference pin 73b in the longitudinal direction (the position of the reference surface that is the base section is formed on the same plane surface). Further, the main reference pin 73a has a tapered leading end portion. Thus, in the attaching operation of the toner container 32Y to the cap receiving section 73 in the longitudinal direction, the toner container 32Y can be smoothly mounted on the cap receiving section 73.

Further, referring to Figs. 14A, 14B, and 15, the contacted groove 73m is the inner wall of the cap receiving section 73 and is also a concave section that is formed, above the main reference pin 73a, in a groove shape at an upstream side in the mounting direction further than the leading end section of the main reference pin 73a. A guide rail section 34e that is formed to extend in the longitudinal direction in an upper outer circumference of the cap section 34Y of the toner container 32Y which will be described later is fitted into the contacted groove 73m before the main reference pin 73a is inserted into the positioning hole 34a.

Referring to Figs. 12 and 15, the lateral groove 73h that is formed to extend in the longitudinal direction and is penetrated toward the outer circumferential side of the cap receiving section 73 is formed on each of both sides of the inner wall of the cap receiving section 73 in a left-right symmetrical relation. Further, referring to Figs. 12 and 13, cap section sandwiching members 73r that have a nearly pentagonal shape when viewed from the top and a groove section 73r1 (that is formed to be connected with a lateral groove 73h) when viewed in the longitudinal direction are disposed on an outer circumferential side of the cap receiving section 73 in a left-right symmetrical

relation.

The cap section sandwiching member 73r is formed of a member different from the cap receiving section 73, fitted into a dent formed on the outer circumferential surface of the cap receiving section 73, urged by a torsion coil spring 93 disposed thereabove centering on a cylindrical axis, and thus pressed against the side of the lateral groove 73h. As a result, the lateral groove 73h is connected with the groove section 73r1 of the cap section sandwiching member 73r, and a pair of deeper left and right groove sections is apparently formed.

In the case of attaching or detaching the toner container 32Y, the lateral protrusion 34c formed in the cap section 34Y pushes and passes through the cap section sandwiching member 73r urged by the torsion coil spring 93 inside the above described deeper groove section (one in which the groove section 73r1 is formed integrally with the lateral groove 73h). Thus, the user who performs the attaching/detaching operation of the toner container 32Y to/from the image forming apparatus body 100 (the cap receiving section 73) can feel a click feeling synchronized with the attaching/detaching operation and perform the attaching/detaching operation of the toner container 32Y at an optimum speed (acceleration) other than a half-hearted speed.

Referring to Figs. 14A and 15, on the inner side wall surface of the cap receiving section 73 (the wall surface rising in a vertical direction at an apparatus direction inner side), the through hole 73f having a shape obtained by connecting and overlapping edge lines of an elliptical hole and a quadrate hole extending in the vertical direction is formed. A connector 73e (for example, see Fig. 16) which will be described later is installed to be

exposed in the inner wall side of the cap receiving section 73 through the through hole 73f (for example, see Fig. 17). When the toner container 32Y is mounted on the cap receiving section 73 (the apparatus body 100), the connector 73e comes in face contact with an ID chip 35 disposed at the leading end of the cap section 34Y, and so information communication can be performed between the ID chip 35 and the apparatus body 100 (the control unit 90).

An installation form of the connector 73e on the cap receiving section 73 of the toner container storage unit 70 will be described below.

The four connectors 73e are disposed in the cap receiving sections 73, corresponding to the toner containers 32Y, 32M, 32C, and 32K of respective colors of yellow, magenta, cyan, and black. Referring to Fig. 8, the four connectors 73e are disposed in line on a single rectangular common electronic substrate 95. Specifically, by fitting a snap fit 73e4 formed on the bottom of the connector 73e into a hole (not shown) formed in the common electronic substrate 95, the connector 73e is fixed onto the common electronic substrate 95.

Further, referring to Figs. 8 and 17, the common electronic substrate 95 to which the four connectors 73e are fixed are installed and fixed along the arrangement direction of the four cap receiving sections 73K, 73C, 73M, and 73Y in the state in which the four connectors 73e are inserted into the inside of the cap receiving section 73 through the through holes 73f, respectively. Specifically, four screws 99 are screwed into female screw sections 73x formed below the outer wall sections of the four cap receiving sections 73K, 73C, 73M, and 73Y through holes formed in the common electronic substrate 95, and the common electronic substrate 95 is screw-coupled with the

cap receiving section 73 from the outside.

A configuration and operation of the connector 73e will be described below.

Referring to Fig. 16, the connector 73e includes a
5 connector body 73e1, four body side terminals 73e2, two
positioning pins 73e3 (positioning protruding sections),
and the like. The four body side terminals 73e2 of the
connector 73e are flat (or linear) metallic members,
respectively, have one terminal side as a fixed terminal
10 and the other terminal side as a free end, and are fixed to
the connector body 73e1. The four body side terminals 73e2
have curved sections (sections that become contact points
with a metallic pad 35a as a metallic plate) that curve
toward the side of the ID chip 35 at the other end side
15 thereof. By the mounting operation of the cap section 34Y
to the cap receiving section 73, the curved section of the
body side terminal 73e2 is displaced in a - X direction of
Fig. 16 and slides toward the left in Fig. 29 (near a first
virtual line S1) from a longitudinal direction central
20 section while gradually increasing contact pressure on the
metallic pad 35a (the metallic plate) of the ID chip 35
disposed in the cap section 34Y.

As illustrated in Fig. 16, the leading end section of
the positioning pin 73e3 has a tapered shape so that
25 engagement with a notch 35b1 of the ID chip 35 can be
smoothly performed.

Referring to Figs. 14A, 14B, 15, and 17, a wall
section 73g is installed to surround the lower section and
the side section of the through hole 73f in which the
30 connector 73e is installed. By forming the wall section
73g, even if the toner is scattered from the vicinity of
the toner discharge opening W of the toner container 32Y to
the outside, since the scattered toner is blocked by the

wall section 73g, the scattered toner is difficult to stick directly to the connector 73e and the ID chip 35. Thus, a contact failure (a communication failure) between the connector 73e (the body side terminal 73e2) and the ID chip 35 (the metallic pad 35a) caused by the scattered toner can be suppressed.

Necessary information is exchanged between the ID chip 35 (the information storage device) of the toner containers 32Y, 32M, 32C, and 32K and the connector 73e of the apparatus body 100. Information communicated between both sides includes information such as a manufacturing number, a manufacturing date, and the number of recycling times of the toner container or the ID chip, information such as capacity, a lot number, and color of a toner, and information such as a use history of the image forming apparatus body 100. In the ID chip 35 (the information storage device), the electronic information is stored in advance before it is installed in the image forming apparatus body 100 (or information received from the apparatus body 100 after it is installed is stored). The ID chip 35 (the information storage device) will be described later in further detail.

Next, the toner containers 32Y, 32M, 32C, and 32K will be described in detail with reference to Figs. 18 to 30.

Referring to Figs. 18 to 20, the toner container 32Y mainly includes the container body 33Y (a bottle body) and the cap section 34Y (a bottle cap) disposed at the head thereof. Further, the ID chip 35 as the information storage device or the like is detachably installed in the cap section 34Y of the toner container 32Y.

On the head of the container body 33Y, the gear 33c that integrally rotates together with the container body 33Y and an opening A are disposed on one end side in the

longitudinal direction (the left-right direction in Fig. 30) (for example, see Figs. 19 and 30). The opening A is disposed on the head of the container body 33Y (the position that becomes the front side in the mounting operation) and discharges the toner stored in the container body 33Y toward the space inside the cap section 34Y (a hollow space, for example, see Fig. 30).

Further, as the toner is consumed at the image forming apparatus body side, toner conveyance from the inside of the container body 33Y to the hollow space inside the cap section 34Y (rotational driving of the container body 33Y) is appropriately performed.

The gear 33c meshes with a driving gear 81 disposed in the toner container storage unit 70 of the apparatus body 100 and rotationally drives the container body 33Y centering on a rotational shaft. Specifically, the gear 33c is exposed through a notch hole 34x (for example, see Fig. 18) formed on the outer circumferential surface of the cap section 34Y which will be described later and meshes with the driving gear 81 of the apparatus body 100 at the obliquely downward meshing position in Fig. 21. Further, driving force is transferred from the driving gear 81 to the gear 33c, and the container body 33Y rotates clockwise in Fig. 21. In the present first embodiment, the driving gear 81 and the gear 33c are spur gears.

Referring to Fig. 18, on the other end side of the container body 33Y in the longitudinal direction (the rear end section in the mounting direction), the gripping section 33d gripped by the user when performing the attaching/detaching work of the toner container 32Y is disposed. The user mounts the toner container 32Y to the image forming apparatus body 100 while gripping the gripping section 33d (movement of the toner container 32Y

in a direction of an arrow in Fig. 18).

Further, on the outer circumferential surface of the container body 33Y, the helical protrusion 33b (a helical groove when viewed from the outer circumference surface side) is disposed. The helical protrusion 33b rotationally drives the container body 33Y in a predetermined direction and discharges the toner through the opening A. The container body 33Y having the above described configuration may be fabricated by blow molding together with the gear 33c disposed on the circumferential surface thereof and the gripping section 33d.

Referring to Fig. 30, in the toner container 32Y according to the present first embodiment, an agitating member 33f that rotates together with the container body 33Y is fitted into a bottle mouth section 33a (the opening A) illustrated in Fig. 19. The agitating member 33f is a rod-like member that extends from the hollow space inside the cap section 34Y to the inside of the container body 33Y. Since the agitating member 33f rotates together with the opening A of the container body 33Y, discharging efficiency of the toner from the opening A is improved.

Referring to Figs. 19 and 30, an engaged section 33j (a flange section), which is engaged with a claw section 34j (for example, see Fig. 21) of the cap section 34Y to connect both members 33Y and 34Y with each other, is formed around the opening A of the container body 33Y to make one round around the outer circumference. As described above, the container body 33Y is rotatably fitted into the cap section 34Y.

Further, referring to Figs. 19 and 30, a head section 33Yc of the container body 33Y (near the position at which the gear 33c is formed) is formed to have the inner diameter smaller than the inner diameter of a storage

33

section 33Ya storing the toner (the position at which the helical protrusion 33b is formed). In the container body 33Y, a pumping section 33Yb (a section encircled by an alternate long and short dash line in Fig. 20) formed to protrude from the inner circumferential surface thereof toward the inside is disposed between the head section 33Yc and the storage section 33Ya. As the container body 33Y rotates, the toner conveyed toward the opening A by the helical protrusion 33b is pumped to the small diameter section of the head section 33Yc by the pumping section 33Yb. Thereafter, the toner pumped to the small diameter of the head section 33Yc is discharged toward the hollow space of the cap section 34Y from the opening A while being agitated by the agitating member 33f.

Referring to Figs. 20 to 23, the ID chip 35 (the information storage device), the shutter member 34d, a shutter seal 36, and the like are installed in the cap section 34Y of the toner container 32Y.

Referring to Fig. 22, the cap section 34Y has a structure in which roughly a cylindrical section (a larger diameter cylindrical section 34Y1, a medium diameter cylindrical section 34Y2, and a small diameter cylindrical section 34Y3) in which the outer diameter and the inner diameter decreases from the container body 33Y side toward the shutter member 34d side in three stages is combined with a box section (a wide width box section 34Y11 and a narrow width box section 34Y12), disposed at the bottom, in which the width in the horizontal direction decreases in two stages are combined.

An insertion section 34z (for example, see Fig. 30) including the larger diameter cylindrical section 34Y1, the medium diameter cylindrical section 34Y2, the wide width box section 34Y11, and part of the narrow width box section

34Y12 is formed in the cap section 34Y. The head section 33Yc of the container body 33Y and part of the pumping section 33Yb are inserted into the insertion section 34z. Referring to Fig. 30, in the insertion section 34z, the
5 medium diameter cylindrical section 34Y2 is formed to have the inner diameter D smaller than the tip diameter of the gear 33c and larger than the outer diameter of the opening A of the container body 33Y. Further, the small diameter cylindrical section 34Y3 is formed to have the inner
10 diameter B smaller than the inner diameter D of the medium diameter cylindrical section 34Y2 and smaller than the outer diameter of the opening A.

An annular cap seal 37 (an elastic seal) in which the opening diameter becomes nearly the same as the inner
15 diameter B is attached to an annular vertical wall surface (the surface facing the circumference of the opening A of the container body 33Y), which connects the medium diameter cylindrical section 34Y2 with the small diameter cylindrical section 34Y3, by a double-sided tape. The head
20 section 33Yc and part of the pumping section 33Yb are inserted into the insertion section 34z such that an edge of the opening A of the head section 33Yc of the container body 33Y comes in contact with and bites into the cap seal 37. By the above described configuration, a functional
25 section such as part of the gear 33c (a section excluding a section exposed from the notch hole 34x) and a connection section between the cap section 34Y and the container body 33Y are covered with the larger diameter cylindrical section 34Y1. For this reason, even when the toner
30 container 32 is solely held by the user, the user can be prevented from touching the functional portion, and even if unexpected external force (for example, careless hitting) is applied to the toner container 32Y, toner leak from the

connection section or damage of the tooth surface of the gear 33c can be alleviated. Further, since the annular cap seal 37 is excellent in sliding property and elasticity of the surface, even if the container body 33Y rotates while
5 biting into the annular cap seal 37, there does not occur toner leak caused by a gap generated between the container body 33Y and the cap section 34Y. As a material of the cap seal 37, a high-density microcell urethane sheet having a structure that is high in density, fine, and uniform unlike
10 general soft polyurethane foam (PUR) is used. As a result, compared to the case of using the general PUR, settling of the cap seal 37 is small, and the sealing property between the container body 33Y and the cap section 34Y can be maintained for a long time.

15 Referring to Figs. 22 and 30, inside the narrow width box section 34Y12 positioned below the small diameter cylindrical section 34Y3 of the cap section 34Y, disposed is a toner falling path C having a hole of a hexagonal cylindrical shape for discharging the toner discharged from
20 the opening A of the container body 33Y to the container outside downward in the vertical direction (falling by its own weight). The toner falling path C has a predetermined flow passage area of a hexagonal cross section and communicates the lower side circumferential surface inside
25 the small diameter cylindrical section 34Y3 with the toner discharge opening W (discharge opening). The toner discharged to the inside of the small diameter cylindrical section 34Y3 of the cap section 34Y from the opening area A of the container body 33Y falls through the toner falling
30 path C of the hexagonal cylindrical shape by its own weight and then is smoothly discharged from the toner discharge opening W to the container outside (the toner tank section 61Y).

On the bottom of the narrow width box section 34Y12, part of the shutter member 34d (a main shutter section 34d1) for performing opening/closing of the toner discharge opening W in conjunction with the attaching/detaching operation of the toner container 32Y to/from the toner container storage unit 70 is held to be slidably movable.

Figs. 22 and 23 illustrate an operation in which the shutter member 34d starts opening of the toner discharge opening W and then completes opening. Figs. 24(A) to 24(C) are schematic views illustrating the opening operation of the shutter member 34d (a shutter deforming section 34d2) at that time. Further, Figs. 25 and 26 are perspective views illustrating the shutter member 34d. In Figs. 24(B) and 24(C), the cap section 34Y, the cap receiving section 73, and the bottle receiving section 72 which are illustrated in Fig. 24(A) are partially omitted.

Referring to Figs. 22 to 26, the shutter member 34d is formed of a resin material such as polystyrene and mainly includes a plate-like main shutter section 34d1 and a shutter deforming section 34d2 that protrudes the main shutter section 34d1, is thinner in thickness than the main shutter section 34d1, and has elasticity.

Referring to Figs. 25 and 26, in the main shutter section 34d1 of the shutter member 34d, vertical wall 34d13 standing at both side end sections (vertical walls extending in parallel to the mounting direction of the toner container 32Y) and a shutter slider 34d12 having a plurality of protruding objects protruding from the vertical walls 34d13 are formed on both side end sections, respectively. The shutter slider 34d12 includes a slide protruding section 34d12a protruding from the inner side surface of the vertical wall 34d13, an L-shaped engaged protruding section 34d12b protruding from the outer side

37

surface of the vertical wall 34d13, and a pair of prismatic sections 34d12c that is disposed to protrude from the same outer side surface as the engaged protruding section 34d12b and extends from the body of the main shutter section 34d1 to the wide width box section 34Y11. Meanwhile, in the narrow width box section 34Y12 of the cap section 34Y, a pair of slide grooves 34t (for example, see Fig. 23) extending in both side walls in the longitudinal direction is formed by a rib. The slide protruding section 34d12a is fitted into the slide groove 34t, and thus the main shutter section 34d1 of the shutter member 34d is slide-movably supported on the cap section 34Y.

Further, a shutter seal 36 adheres to the upper surface of the main shutter section 34d1 (the surface facing the toner discharge opening W) as a seal member. The shutter seal 36 is a thin rectangular parallelepiped-like elastic seal, and similarly to the cap seal 37, a high density microcell urethane sheet is used as a material in view of sliding property and elasticity of the surface. For this reason, even if the opening/closing operation of the shutter member 34d is repeated, a sealing characteristic in the toner discharge opening W can be maintained in the state in which the shutter member 34d closes the toner discharge opening W.

The slide protruding section 34d12a of the shutter slider 34d12 is fitted into the slide groove 34t of the narrow width box section 34Y12 (the cap section 34Y). Further, in this state, the shutter seal 36 is sandwiched between a protrusion 34r (for example, see Fig. 23) of a hexagonal ring shape protruding downward along an edge of the hexagonal toner discharge opening W of the narrow width box section 34Y12 and a main shutter section 34d1, and the shutter seal 36 becomes a slightly compressed state. In

this state, the shutter member 34d moves along the slide groove 34t, and thus the main shutter section 34d1 opens or closes the toner discharge opening W while suppressing toner leak. Further, in the state in which the main shutter section 34d1 (the shutter member 34d) has closed the toner discharge opening W, the toner leak from between the main shutter section 34d1 and the toner discharge opening W is prevented.

Specifically, the shutter member 34d relatively moves in the longitudinal direction from the cap section 34Y side to the container body 33Y side (moves to the left in Fig. 30) to open the toner discharge opening W and relatively moves in the longitudinal direction from the container body 33Y side to the cap section 34Y side (moves to the right in Fig. 30) to close the toner discharge opening W. The opening/closing operation of the shutter member 34d (the opening/closing operation of the toner discharge opening W) is performed in conjunction with the attaching/detaching operation of the toner container 32Y to/from the toner container storage unit 70 (the apparatus body 100) in the longitudinal direction.

Referring to Figs. 25 and 26, the shutter deforming section 34d2 of the shutter member 34d is formed integrally with the main shutter section 34d1 and formed at the board thickness thinner than the board thickness of the main shutter section 34d1 as described above. The shutter deforming section 34d2 mainly includes two spindly flat plate sections 34d23 extending from the end surface of the main shutter section 34d1 at the container body 33Y and a plate-like member 34d24 extending in a direction orthogonal to the longitudinal direction to connect the two flat plate sections 34d23 with each other near the leading end sections (the free ends). The shutter deforming section

34d2 is formed to be elastically deformed in the vertical direction from a fixed end (a connection portion) with the main shutter section 34d1 as a reference point. On the leading end sections (the free ends) of the two flat plate sections 34d23, formed are stopper sections 34d22 for fixing the shutter member 34d so as to prevent careless opening of the toner discharge opening W as will be described later. On the bottom side of the plate-like member 34d24, formed is the stopper release section 34d21 that is an inclined protrusion (having a triangular cross section) protruding, in a mountain shape, downward in the vertical direction and that releases fixing of the shutter member 34d in cooperation with the stopper release urging section 72b of the cap receiving section 73 as will be described later.

Referring to Figs. 22 and 23, in the wide width box section 34Y11 positioned below the larger diameter cylindrical section 34Y1 of the cap section 34Y, formed is a shutter storage section 34n that stores the shutter deforming section 34d2 therein at the time of shutter opening. Among the four side surfaces of the wide width box section 34Y11, the two side surfaces facing in the longitudinal direction (a direction of an arrow in Fig. 22) are opened. Particularly, in the side surface formed at the toner discharge opening W side, part of the wall surface is formed at both side ends of the bottom side, but most of it functions as an opening 34n1 extending in the horizontal direction. The opening 34n1 is formed such that two surfaces including the side surface and the bottom surface that are at the toner discharge opening W side of the wide width box section 34Y11 are cut out. Among edge sections of the opening 34n1, an edge section formed to stand from the bottom surface of the wide width box section

34Y11 in the vertical direction becomes the contact section 34n5.

The stopper section 34d22 of the shutter deforming section 34d2 is a wall section formed at a farthest end section of the shutter deforming section 34d2 (the leading
5 end of the shutter deforming section 34d2 away from the main shutter section 34d1) in the opening direction (the left direction in Fig. 24). The stopper section 34d22 of the shutter deforming section 34d2 comes in contact with
10 the contact section 34n5 and thus restricts the shutter member 34d from moving in the direction of opening the toner discharge opening W from the state in which the toner discharge opening W is closed. That is, when the toner container 32Y is in a separated state (the state in which
15 it is not set to the apparatus body 100 yet), since the stopper section 34d22 of the shutter member 34d comes in contact with the contact section 34n5, a phenomenon that the shutter member 34d moves in the opening direction on its own and so opens the toner discharge opening W does not
20 happen.

Meanwhile, the stopper release section 34d21 comes in contact with the stopper release urging section 72b (for example, see Figs. 5 and 24) formed in the bottle receiving section 72 in conjunction with the mounting operation of
25 the toner container 32Y to the toner container storage unit 70 and is pushed upward by the stopper release urging section 72b (as external force is applied upward). Then, the shutter deforming section 34d2 is elastically deformed upward, and the stopper section 34d22 is also displaced
30 upward. As a result, the contact state between the stopper section 34d22 and the contact section 34n5 is released, so that the shutter member 34d can move in the opening direction.

An operation of the shutter member 34d in conjunction with the mounting operation of the toner container 32Y to the toner container storage unit 70 will be described below in detail with reference to Figs. 24(A) to 24(C). The
5 position of the shutter member 34d in Figs. 24(A) and 24(C) corresponds to the position of the shutter member 34d in Figs. 22 and 23, respectively.

As illustrated in Fig. 24, the mounting operation of the toner container 32Y to the toner container storage unit
10 70 (movement in the left direction in Fig. 24) starts, and when the stopper release section 34d21 of the shutter member 34d does not reach the position of the stopper release urging section 72b (for example, also see Fig. 5) formed in the bottle receiving section 72, the stopper
15 section 34d22 of the shutter member 34d comes in contact with the contact section 34n5, and thus movement of the shutter member 34d in the opening direction is restricted. Further, on the upper surface of the bottle receiving section 72 at the cap receiving section 73 side near the
20 stopper release urging section 72b, a bristle brush 72f is disposed to rub the bottom surface of the shutter member 34d and clean contamination. Particularly, the bristle brush 72f is effective in cleaning flying toner sticking to the bottom surface of the shutter member 34d during an
25 operation of attaching/detaching the toner container 32Y.

Thereafter, when the mounting operation of the toner container 32Y proceeds, as illustrated in Fig. 24(B), the stopper release section 34d21 is pushed up by the stopper release urging section 72b, and so the shutter deforming
30 section 34d2 is elastically deformed from the connection position (a section encircled by an alternate long and short dash line) as the reference point. As a result, the contact state between the stopper section 34d22 and the

contact section 34n5 is released, and so the shutter member 34d can relatively move in the opening direction.

Thereafter, the shutter member 34d comes in contact with the wall section (a section indicated as "contact position" in the drawings) formed around the toner feeding opening 73w of the cap receiving section 73, and so movement in the toner container storage unit 70 (the cap receiving section 73) is restricted (the shutter member 34d does not absolutely move in the longitudinal direction). However, since movement in the mounting direction of the toner container 32Y is performed, the shutter member 34d moves relative to the toner discharge opening W in the opening direction. That is, as illustrated in Fig. 24(C), the shutter member 34d relatively moves to the container body 33Y side, and so the shutter deforming section 34d2 is stored in the shutter storage section 34n. As a result, opening of the toner discharge opening W is completely finished by movement of the shutter member 34d in the opening direction. Further, the toner discharge opening W matches with the toner feeding opening 73w of the cap receiving section 73 in a superimposed manner, and an integrated toner feeding passage leading from the toner container 32Y to the toner feeding device is formed. At this time, the stopper release section 34d21 of the shutter member 34d is stored in a notch 34n6 (for example, see Figs. 22 and 23) that is an extension section of the opening 34n1 of the cap storage section 34n. Thus, it is possible to prevent a problem in that the shutter deforming section 34d2 stored in the shutter storage section 34n is held in a greatly elastically deformed state by contact between the stopper release section 34d21 and the shutter storage section 34n.

As described above, in the toner container 32Y

according to the present first embodiment, the shutter deforming section 34d2 that is elastically deformed from the connection position with the main shutter section 34d1 as the reference point is disposed in the shutter member 34d, and the stopper section 34d22 that restricts movement of the shutter member 34d in the opening direction and the stopper release section 34d21 that releases the stopper section 34d22 are disposed in the shutter deforming section 34d2. Thus, the shutter member 34d does not open the toner discharge opening W as it pleases in the state in which the toner container 32Y is removed, and only when the toner container 32Y is set to the image forming apparatus body 100, the shutter member 34d opens the toner discharge opening W in conjunction with the mounting operation thereof.

An operation of the L-shaped engaged protruding section 34d12b related to the shutter opening/closing operation will be described below.

As illustrated in Fig. 25, the L-shaped engaged protruding sections 34d12b are formed on both side end sections of the main shutter section 34d1, respectively. Meanwhile, even though not shown because it is illustrated in the drawings of Japanese Patent Application No. 2011-9782, on the bottom surface inside the cap receiving section 73, a pair of urging members is installed to face a pair of engaged protruding sections 34d12b. The pair of urging members is an L-shaped lever (a spindle that becomes a rotation center is formed near an L-shaped curved portion) that forms a shape symmetrical to each other, and an arm section at one side thereof is urged by a torsion coil spring. If the toner container 32Y (the cap section 34Y) is mounted on the cap receiving section 73, an arm section of the other end side of the urging member is

engaged with the engaged protruding section 34d12b and applies urging force in a direction resisting the direction in which the shutter member 34d is opened. The user pushes the toner container 32Y by force overcoming urging force by the above described urging member, and opening of the shutter member 34d is rapidly performed. As a result, a state in which the toner discharge opening W does not match with the toner feeding opening 73w of the cap receiving section 73 occurs only instantaneously, and toner leak from between the toner discharge opening W and the toner feeding opening 73w can be suppressed.

On the other hand, when the toner container 32Y (the cap section 34Y) is removed from the cap receiving section 73, the arm section of the urging member becomes a state urged to push the engaged protruding section 34d12b in the mounting direction. The user attempts to pull out the toner container 32Y by force overcoming urging force by the urging member, and so closing of the shutter member 34d is rapidly performed. As a result, similarly to the time of the opening operation, toner leak from between the toner discharge opening W and the toner feeding opening 73w can be suppressed.

Referring to Figs. 20, 21, and 30, in the upper section (the ceiling portion) of the cap section 34Y, the first positioning hole 34a extending in the longitudinal direction from the end surface of the cap section 34Y orthogonal to the longitudinal direction is formed. The first positioning hole 34a becomes a main positioning reference of the cap section 34Y in the image forming apparatus body 100. Specifically, the main reference pin 73a (for example, see Figs. 14A, 14B and 17) as the positioning pin of the cap receiving section 73 is fitted into the first positioning hole 34a of the cap section 34Y

in conjunction with the mounting operation of the toner container 32Y to the toner container storage unit 70 in the longitudinal direction.

In the lower section (the bottom portion) of the cap section 34Y, the second positioning hole 34b extending in the longitudinal direction from the end surface of the cap section 34Y orthogonal to the longitudinal direction is formed not to reach the position of the toner discharge opening W. The second positioning hole 34b becomes a sub positioning reference of the cap section 34Y in the image forming apparatus body 100. Specifically, the sub reference pin 73b (for example, see Figs. 14A, 14B and 17) as the positioning pin of the cap receiving section 73 is fitted into the second positioning hole 34b of the cap section 34Y in conjunction with the mounting operation of the toner container 32Y to the toner container storage unit 70 in the longitudinal direction. Further, the second positioning hole 34b as illustrated in Fig. 21 is a oblong hole in which a vertical direction is a longitudinal direction (this "longitudinal direction" has a different meaning from the "longitudinal direction" of the toner container 32Y described in the other sections).

Positioning of the cap section 34Y in the toner container storage unit 70 is performed by the two positioning holes 34a and 34b having the above described configuration.

Referring to Fig. 30, the hole depth of the first positioning hole 34a is set to be larger than the hole depth of the second positioning hole 34b. The length of the main reference pin 73a in the longitudinal direction is set to be larger than the length of the sub reference pin 73b in the longitudinal direction. In the mounting operation of the toner container 32Y to the toner container

storage unit 70 (the cap receiving section 73) in the longitudinal direction, the main reference pin 73a starts to be fitted into the first positioning hole 34a that is the main positioning reference, and then the sub reference
5 pin 73b starts to be fitted into the second positioning hole 34b that is the sub positioning reference, so that the toner container 32Y can be smoothly mounted on the toner container storage unit 70 (the cap receiving section 73). Further, since the first positioning hole 34a that is long
10 in the longitudinal direction is disposed in the ceiling section of the cap section 34Y (a section that is not buried in the toner), there is no influence on a conveying property (a flow property) of the toner inside the cap section 34Y. The second positioning hole 34b that is short
15 in the longitudinal direction is formed on the bottom of the cap section 34Y but sufficiently performs a function as the sub positioning reference since it can be disposed using a small space from the end surface of the cap section 34Y to the position of the toner discharge opening W.

20 Referring to Fig. 20, on the outer circumferential surface of the cap section 34Y above the first positioning hole 34a of the cap section 34Y, a guide rail section 34e extending in an axial direction of the first positioning hole 34a is formed. The guide rail section 34e protrudes
25 upward in the vertical direction from the outer circumferential surface of the cap section 34Y to be line-symmetrical to a virtual vertical line passing through the hole center of the first positioning hole 34a when viewed in a cross section orthogonal to the longitudinal direction
30 (a cross section parallel to a front view of Fig. 21) and extends in the longitudinal direction (a direction vertical to a paper plane of Fig. 21). Before the main reference pin 73a is inserted into the positioning hole 34a, the

guide rail section 34e is fitted into the contacted groove 73m (a concave section), which is formed in a groove shape in the inner wall of the cap receiving section 73 above the main reference pin 73a, from the upstream side in the mounting direction further than the leading end section of the main reference pin 73a and restricts a posture of the cap section 34Y in the horizontal direction orthogonal to the longitudinal direction at the time of mounting movement to the image forming apparatus body 100 (the cap receiving section 73). Further, in the leading end of the guide rail section 34e, a protruding section 34e1 slightly protruding in the longitudinal direction from the end surface of the first positioning hole 34a is formed. The protruding section 34e1 is formed in a tapered shape as illustrated in Fig. 20. The guide rail section 34e enters the contacted grooves 73m formed on the cap receiving section 73, and so the cap section 34Y is guided to the inside of the cap receiving section 73. Thus, when the cap section 34Y is mounted on the cap receiving section 73, in the first positioning hole 34a, the tapered protruding section 34e1 is fitted into the contacted groove 73m before the first positioning hole 34a is fitted into the main reference pin 73a, and thus the cap section 34Y is smoothly mounted on the cap receiving section 73.

Referring to Figs. 20 and 21, lateral protrusions 34c for restricting a posture of the cap section 34Y in the rotation direction in the image forming apparatus body 100 (the cap receiving section 73) are formed on both side sections of the cap section 34Y, respectively. The lateral protrusion 34c protrudes to both sides in the horizontal direction from the outer circumferential surface of the cap section 34Y to be disposed on a virtual horizontal line passing through the center of a virtual line segment

connecting the hole center of the first positioning hole 34a with the hole center of the second positioning hole 34b when viewed in a cross section orthogonal to the longitudinal direction and extends in the longitudinal direction (a direction vertical to a paper plane of Fig. 21). The two lateral protrusions 34c are engaged with the lateral groove 73h and the groove section 73rl, for example, illustrated in Fig. 12 while being pressed to be pushed back in a direction opposite to pushing by the cap section sandwiching member 73r (for example, see Fig. 12) in the cap receiving section 73. Thus, the cap section 34Y is attached to or detached from the cap receiving section 73 while the posture of the cap section 34Y in the rotation direction is being restricted, and the posture of the cap section 34Y in the rotation direction is restricted in the state in which the cap section 34Y is mounted on the cap receiving section 73.

In further detail, in the lateral protrusion 34c, the leading end in the longitudinal direction (the mounting direction) is formed in a tapered shape as illustrated in Fig. 20. Here, when the cap section 34Y is mounted on the cap receiving section 73, the guide rail section 34e is first fitted into the contacted groove 73m, and then the two lateral protrusions 34c having the tapered leading end are fitted into the lateral grooves 73h and the groove sections 73rl. Thus, the cap section 34Y is smoothly mounted on the cap receiving section 73 in the state in which the posture of the cap section 34Y is restricted with a high degree of certainty.

Referring to Figs. 20 and 21, on both ends of the bottom of the cap section 34Y, disposed are convex sections 34g and 34h for securing incompatibility of the toner container 32Y (the developer container). In detail, on the

upper surface side of a flat plate-like blade member extending laterally from the bottom of the cap section 34Y, the convex sections 34g and 34h are disposed to protrude upward. The convex sections 34g and 34h are configured to
5 be fitted into a fitting section 72m (that is formed in the bottle receiving section 72 of the toner container storage unit 70) illustrated in Fig. 9 when the mounting operation of the toner container 32Y to the toner container storage unit 70 is correct (when the toner container 32Y is mounted
10 to the true position of the toner container storage unit 70).

Specifically, even though not shown, the convex sections 34g and 34h are disposed at the different positions depending on color of the toner stored in the
15 toner container (the container body). In detail, if it is assumed that the leading end in the mounting direction when the toner container 32Y is mounted on the image forming apparatus body 100 is the front, the convex sections 34g and 34h are disposed so that the protruding positions are
20 not superimposed when viewed from the front and are disposed at the different positions depending on the color. The convex sections 34g and 34h of the toner container corresponding to cyan are formed at the position to be fitted only into the cyan fitting section 72m of the toner
25 container storage unit 70, the convex sections 34g and 34h of the toner container corresponding to magenta are formed at the position to be fitted only into the magenta fitting section 72m of the toner container storage unit 70, the convex sections 34g and 34h of the toner container
30 corresponding to yellow are formed at the position to be fitted only into the yellow fitting section 72m of the toner container storage unit 70, and the convex sections 34g and 34h of the toner container corresponding to black

are formed at the position to be fitted only into the black fitting section 72m of the toner container storage unit 70.

The above described configuration prevents a problem in that the toner container of a different color (for example, the toner container of yellow) is set to the toner container storage unit of a predetermined color (for example, the toner container storage unit of cyan) and thus a predetermined color image cannot be formed. That is, the toner container is prevented from being erroneously set to the toner container storage unit.

Fig. 10 illustrates the state when the mounting operation of the toner container 32Y to the toner container storage unit 70 is correct. The convex sections 34g and 34h of the cap section 34Y do not interfere with the fitting section 72m of the bottle receiving section 72. On the other hand, Fig. 11 illustrates the state when the mounting operation of the toner container 32Y to the toner container storage unit 70 is not correct. The convex sections 34g and 34h of the cap section 34Y interfere with the fitting section 72m of the bottle receiving section 72.

The ID chip 35 (the information storage device) that is characteristic in the toner container 32Y (the removable device) according to the present first embodiment will be described below in detail.

Referring to Fig. 20, on the end surface of the cap section 34Y, the ID chip 35 as the information storage device in which various electronic information is stored is installed at the position of a holding member 34k installed between the first positioning hole 34a and the second positioning hole 34b. The ID chip 35 is configured to be connected to the connector 73e of the cap receiving section 73 in the state in which the cap section 34Y is mounted to the toner container storage unit 70 (the cap receiving

section 73) (for example, see Figs. 3 and 17).

Specifically, in the state in which the cap section 34Y is mounted on the toner container storage unit 70 (the cap receiving section 73), a plurality of metallic pads 35a (metallic plates) of the ID chip 35 come in contact with a plurality of body side terminals 73e2 of the connector 73e. The ID chip 35 performs communication (wire line communication) with the control unit 90 through the connector 73e as illustrated in Fig. 3 in the state in which the cap section 34Y is held on the cap receiving section 73.

Referring to Figs. 27 to 29, in the present first embodiment, a holding mechanism installed in the toner container 32Y (the removable device) removably installed to the image forming apparatus body 100 includes the ID chip 35 as the information storage device, the holding member 34k as the holding section, and the like. The ID chip 35 as the information storage device held on the holding mechanism includes a substrate 35b, an information storage unit 35c, metallic pads 35a as a plurality of terminals (metallic plates), and the like.

Referring to Fig. 29, the information storage unit 35c is an electronic circuit in which various information exchanged between the control unit 90 of the image forming apparatus body 100 and the toner container 32Y is stored. In Fig. 29, the information storage unit 35c is illustrated as a box-like one by hatched lines for simplicity but corresponds to an assembly of a memory IC, a condenser for noise reduction, a resistor, and the like. The information storage unit 35c is disposed on the back surface side of the substrate 35b (the side facing the end surface of the cap section 34Y) and electrically connected to all or some of the metallic pads 35a as a plurality of metallic plates.

The metallic pads 35a as the plurality of terminals come in contact with the plurality of body side terminals 73e2 of the connector 73e installed in the cap receiving section 73 (the apparatus body 100), respectively, and
5 exchange an electrical signal related to information with the image forming apparatus body 100 (the control unit 90). The plurality of metallic pads 35a are disposed at the front surface side of the substrate 35b (the side facing the cap receiving section 73). Further, the plurality of
10 metallic pads 35a are formed in a nearly rectangular shape and arrayed in a transverse direction thereof with a clearance therebetween (a Z direction (vertical direction) in Fig. 29(A)).

On the substrate 35b on which the information storage
15 unit 35c and the metallic pads 35a are disposed, positioning notches 35b1 (that has a shape of a half when an elliptical circumference is divided into two by a straight line) are formed on both ends in the vertical direction, respectively. The positioning notch 35b1 is
20 fitted into the positioning pin 73e3 (for example, see Figs. 16 and 17) as a cylindrical positioning protruding section installed in the connector 73e (the image forming apparatus body 100) and is used for positioning the plurality of
metallic pads 35a on the plurality of body side terminals
25 73e2.

The ID chip 35 (the information storage device) having the above described configuration is held on the holding member 34k (the holding section) that is configured removably from the cap section 34Y.

30 The holding member 34k (the holding section) holds the contact type ID chip 35 (the information storage device) to be able to move on a virtual plane (a virtual plane substantially orthogonal to) intersecting with the movement

direction (a direction of an arrow in Fig. 17) in which the metallic pads 35a (terminals) approach and come in contact with the body side terminals 73e2.

Specifically, in the present first embodiment, the holding member 34k holds the ID chip 35 (the substrate 35b) to be able to move on a virtual plane (an XZ plane in Fig. 20) orthogonal to the attaching/detaching direction of the toner container 32Y to/from the image forming apparatus body 100. That is, the ID chip 35 (the substrate 35b) is configured to be able to move (about 1 mm) on the XZ plane in Fig. 20 freely to some extent in a state held by the holding member 34k (the cap section 34Y) as illustrated in Fig. 20. Specifically, the ID chip 35 (the substrate 35b) is held loosely to some extent inside the box-like holding member 34k (the holding mechanism). That is, the ID chip 35 is held with a predetermined gap between the ID chip 35 and the side wall inside the holding member 34k. Referring to Figs. 28 and 29, the ID chip 35 is held such that a small clearance Δt (for example, " $\Delta t + t$ " is about 0.85 to 1.05 mm) is formed in a $\pm Y$ direction on the thickness t (about 0.8 mm) of the substrate 35b) inside the holding member 34k. For this reason, it is possible to make the substrate 35b stand to orthogonally cross in the insertion direction of the positioning pin 73e3 to some extent. Thus, prevented is a problem in that the substrate 35b is excessively laid down in the insertion direction of the positioning pin 73e3, the positioning pin 73e3 is seized by the notch 35b1, and thus the positioning pin 73e3 fails to be fitted into the notch 35b1.

Through the above described configuration, even when the size of the image forming apparatus body 100 or the toner container 32Y decreases and so the plurality of metallic pads 35a (terminals) on the substrate 35b are

densely arranged so as to reduce the size of the ID chip 35 installed thereon, a contact failure that is caused by a positioning failure between the plurality of metallic pads 35a and the body side terminal 73e2 of the connector 73e is difficult to occur regardless of whether or not a degree of dimension accuracy or a degree of assembly accuracy of an associated component is high or low.

Specifically, referring to Fig. 17, if the mounting operation of the cap section 34Y of the toner container 32Y on the cap receiving section 73 proceeds, the positioning pins 73a and 73b are inserted into the positioning holes 34a and 34b, and so the cap section 34Y is positioned in the cap receiving section 73. If the mounting operation of the cap section 34Y further proceeds, the positioning pin 73e3 of the connector 73e (for example, see Figs. 16 and 17) is inserted into the notch 35b1 of the substrate 35b of the ID chip 35, and the substrate 35b (the plurality of metallic pads 35a) is positioned with respect to the connector 73e (the plurality of body side terminal 73e2).

In further detail, the positioning pin 73e3 comes in contact with the edge section (or the inner surface) of the notch 35b1, and so movement of the substrate 35b is restricted. At this time, since the ID chip 35 (the substrate 35b) having the notch 35b1 formed therein is configured to be movable on the XZ plane in the holding member 34k, an allowable tolerance of a degree of dimension accuracy or a degree of assembly accuracy of an associated component according to mass production has to be large.

Thus, when positioning between the toner container 32Y and the image forming apparatus body 100 is performed, even if the position of the notch 35b1 is misaligned with the positioning pin 73e3 from the beginning, the ID chip 35 (the substrate 35b) is restricted by the tapered leading

end of the positioning pin 73e3 and moves on the XZ plane, and thus the cylindrical section of the positioning pin 73e3 can be fitted into the notch 35b1. That is, independently of positioning between the toner container 5 32Y and the image forming apparatus body 100, the cylindrical section of the positioning pin 73e3 can be fitted into the notch 35b1. Thus, the contact failure that is caused by the positioning failure between the plurality of metallic pads 35a and the body side terminals 73e2 of 10 the connector 73e is difficult to occur.

Referring to Fig. 27, the holding member 34k as the holding section is removably configured on the cap section 34Y and is a box-like member having an insertion opening 34k1, formed in the upper side thereof, through which the 15 ID chip 35 is inserted or separated.

In detail, when assembling the holding mechanism to the cap section 34Y, the ID chip 35 (the information storage device) is first inserted into the holding member 34k through the insertion opening 34k1 (movement in a 20 direction of an arrow in Fig. 27). Thereafter, the holding member 34k (the holding section) having the ID chip 35 mounted thereon moves in the arrow direction in Fig. 27 and is press-fitted into the convex section of the cap section 34Y. At this time, the holding member 34k is fixed and 25 held at the position contacting a pedestal section 34q (disposed at the position not contacting the substrate 35b) disposed in the convex section of the cap section 34Y. Further, when ejecting the ID chip 35 from the cap section 34Y, an operation is performed in a procedure reverse to 30 the above described procedure. The pedestal section 34q is a rib standing in the mounting direction of the toner container 32Y (or toward the holding member 34k) inside the concave section of the cap section 34Y and disposed at the

position other than a place into which the positioning pin 73e3 of the connector 73e is to be inserted.

In the present first embodiment, the holding member 34k is press-fitted into and fixed to the concave section of the cap section 34Y, but the holding member 34k may be mounted on and screw-fixed to the concave section of the cap section 34Y. Specifically, a flaky rib having a hole in the side wall of the holding member 34k protrudes to form a female screw section in the end surface of the cap section 34Y. The holding member 34k is mounted on the concave section of the cap section 34Y, and in the state in which the flaky rib of the holding member 34k comes in contact with the end surface of the cap section 34Y, a screw is screwed into the female screw section of the cap section 34Y through the hole of the rib related to the holding member 34k. Even in this configuration, the holding member 34k can be comparatively easily attached to or detached from the cap section 34Y.

As described above, since the ID chip 35 (the substrate 35b) is configured to be attached to or detached from the cap section 34Y, efficiency of assembling the ID chip 35 (the substrate 35b) to the toner container 32Y as the removable device increases, and at the same time, efficiency of a disassembly operation of the ID chip 35 (the substrate 35b) when recycling the toner container 32Y increases. Particularly, in the present first embodiment, the substrate 35b of the ID chip 35 is a small substrate having the size of about 12 mm × 8 mm to 15 mm × 10 mm. If data input/output (data input/output when a probe terminal comes in contact with the metallic pad 35a) is about to be performed in the state in which the substrate 35b is mounted on the cap section 34Y in the manufacturing process, it may be difficult to do a work on the cap section 34Y of

a complicated shape, and a process time may increase. Thus, in the present first embodiment, the ID chip 35 (the substrate 35b) is removably configured, and thus there is a great effect since a data input/output operation can be performed on the ID chip 35 alone (or for each holding member 34k) if necessary.

Referring to Figs. 17 and 27, in the cap section 34Y, formed is a standing member 34f that blocks the insertion opening 34k1 in the state in which the holding member 34k is mounted on the concave section.

Thus, prevented is a problem in that the ID chip 35 falls off from the insertion opening 34k1 of the holding member 34k after the ID chip 35 (the holding member 34k) is mounted on the cap section 34Y.

Referring to Fig. 28, inside the holding member 34k (the box-like member), formed are a first facing section 34k4 and a second facing section 34k5. The first facing section 34k4 faces a first plane of the substrate 35b (referring to Fig. 29, a surface where the plurality of metallic pads 35a are disposed) and is formed to come in contact only with and slide on an outer peripheral area of the first plane where the metallic pads 35a are not disposed so as not to interfere with the plurality of metallic pads 35a. The second facing section 34k5 faces a second plane of the substrate 35b (referring to Fig. 29, a surface where the information storage unit 35c is disposed) and is formed to slide on part of the second plane so as not to interfere with the information storage unit 35c. Thus, inside the holding member 34k, the ID chip 35 can freely move on the XZ plane (can move to slide on the facing sections 34k4 and 34k5) without falling off from the holding member 34k, and without the metallic pads 35a or the information storage unit 35c getting damaged.

Further, openings 34k2 and 34k3 are formed in the front and back surfaces of the holding member 34k, respectively. The first opening 34k2 is formed to allow the plurality of metallic pads 35a and the positioning notch 35b1 to be exposed at the side facing the connector 73e even when the substrate 35b moves in the XZ plane to some extent. Thus, in accompany with movement of the substrate 35b in the XZ plane, the positioning pin 73e3 and the notch 35b1 can be engaged with each other, and the metallic pads 35a and the body side terminals 73e2 can be connected with (come in contact with) each other. Further, the second opening 34k3 to allow the information storage unit 35c to be exposed at the side facing the concave section of the cap section 34Y even when the substrate 35b moves on the XZ plane to some extent.

Referring to Fig. 28, the opening 34k2 formed in the front surface of the holding member 34k is formed such that the left side has a convex shape and the right side has a concave shape. Thus, an area encircled by a dotted line in Fig. 28 functions as a hook (a stopper) for preventing the ID chip 35 from falling off from the opening 34k2.

Fig. 29 is a three-plane view illustrating the ID chip 35.

As illustrated in Fig. 29, in the ID chip 35, the metallic pads 35a as four metallic plates are disposed in line in the Z direction on the first plane of the substrate 35b. The metallic pad 35a has a multi-layer structure having three layers of a copper layer, a nickel layer, and a metallic layer which are disposed in order from the substrate 35b side, and the metallic layer as the surface layer is comparatively expensive but disposed to prevent oxidization. The metallic pad 35a is formed by electric field evaporation on the substrate 35b that is masked in

advance.

The positioning notches 35b1 are formed on both end sections of the four metallic pads 35a in the arrangement direction (the Z direction) to sandwich the four metallic pads 35a. In the present first embodiment, a first virtual straight line S1 that passes through the centers of the notches 35b1 and is parallel to the arrangement direction of the plurality of metallic pads 35a is configured to be positioned not to overlap a second virtual straight line S2 that connects the centers of the plurality of metallic pads 35a in the longitudinal direction. Specifically, the first virtual straight line S1 that connects the two positioning notches 35b1 (a virtual line that connects the centers of original oblong holes in the notches 35b1 each of which has a shape of a half when the oblong hole is divided into two in the longitudinal direction) is configured to be positioned not to overlap the second virtual straight line S2 that connects the centers of the plurality of metallic pads 35a in the longitudinal direction. That is, in the notches 35b1, the virtual straight line S1 that connects sections that are most bitten toward the inside of the substrate 35b is positioned not to overlap the virtual straight line S2. Further, the virtual straight line S1 is configured to be nearly parallel to the virtual straight line S2.

In the present first embodiment, dimensions a to f in Fig. 29 have been set to 6.2 mm, 5.2 mm, 1.5 mm, 2 mm, 6 mm, and 11.7 mm, respectively. The substrate 35b having the small area size is small in deflection amount even if external force is applied and comparatively large in resistance characteristic (stiffness) against shearing force. In the present first embodiment, the ID chip 35 is held to be movable inside the holding member 34k, and

employed is a positioning method in which the positioning pin 73e3 is inserted into the notch 35b1 and is likely to be "seized" (a state in which the positioning pin 73e3 enters the notch 35b1 obliquely rather than vertically, a sliding load between the notch 35b1 and the positioning pin 73e3 increases, and so the substrate 35b is deflected and does not move) in the case of the ID chip 35 having the large area size. However, since the substrate 35b has the small area size, stiffness increases, and so the positioning method that is difficult to cause deflection that causes "seizure" is implemented. Further, an interval between the metallic pads 35a in the substrate 35b is narrow, but the contact failure between the metallic pads 35a and the body side terminals 73e2 can be prevented by high accuracy positioning in accompany with movement of the substrate 35b in the XZ plane, and thus the area size of the expensive metallic pads 35a having the metal layer can be suppressed to a minimal area size.

Fig. 16 is a schematic perspective view illustrating the connector 73e at the apparatus body 100 side.

Referring to Fig. 16, the four body side terminals 73e2 in the connector 73e are plat-like (linear) metallic members, have one end as the fixed end and the other end as the free end, and are fixed to and supported on the connector body 73e1. On the other end sides of the four body side terminals 73e2, formed are curved sections that curve toward the ID chip 35 (toner container 32Y) side. That is, the body side terminals 73e2 curve toward the ID chip 35 like a knee (or a boomerang). The curved sections of the body side terminals 73e2 are sections that functions as contact points with the metallic pads 35a.

In accompany with the mounting operation of the cap section 34Y (the toner container 32Y) on the cap receiving

61

section 73, the curved section of the body side terminal 73e2 comes in contact with nearly the central section of the metallic pad 35a in the longitudinal direction. Then, when the mounting operation of the cap section 34Y further proceeds, the ID chip 35 (the substrate 35b) approaches to the connector 73e side, the body side terminal 73e2 is deformed so that the curved section of the body side terminal 73e2 get close to the first virtual straight line S1 while being pressed by the metallic pad 35a and elastically deformed (a state in which a curved knee stretches). That is, in accompany with the mounting operation of the cap section 34Y, the curved section of the body side terminal 73e2 slides toward the left in Fig. 29 from the central section in the longitudinal direction (approaches the first virtual straight line S1) while gradually increasing contact pressure on the metallic pad 35a.

Through the above described configuration, even if the position of the cap section 34Y (the metallic pad 35a) in the longitudinal direction (the Y direction) is misaligned with the cap receiving section 73 (the body side terminal 73e2) depending on whether or not a degree of dimensions accuracy or a degree of assembly accuracy of an associated component is high or low (a dimension variation), the contact failure between the body side terminal 73e2 and the metallic pad 35a can be prevented with a high degree. Finally, since the body side terminal 73e2 and the metallic pad 35a come in contact with each other near the position where the positioning pin 73e3 is engaged with the notch 35b1 (near the first virtual straight line S1), the distance between the positioning section and the connect section can be reduced. As a result, a degree of accuracy of the contact position between the body side terminal 73e2

and the metallic pad 35a increases.

Further, in the present first embodiment, the plurality of metallic pads 35a are disposed in line in the arrangement direction that is the vertical direction.

5 As a result, the positioning direction of the cap section 34Y in the cap receiving section 73 (the arrangement direction of the positioning pins 73a and 73b and the positioning holes 34a and 34b) is the same as the positioning direction of the connector 73e and the
10 substrate 35b (the arrangement direction of the positioning pin 73e3 and the notch 35b1), and thus the contact failure between the body side terminal 73e2 and the metallic pad 35a is difficult to occur.

Referring to Fig. 21, the positioning holes 34a and
15 34b of the cap section 34Y are formed at positions apart from each other in the vertical direction to sandwich the ID chip 35 (the information storage device). A third virtual straight line S3 that connects the centers of the two positioning holes 34a and 34b is configured to be
20 parallel to the first virtual straight line S1 that connects the two positioning notches 35b1.

As described above, since the ID chip 35 is disposed
be fixed between the first positioning hole 34a (the main reference) and the second positioning hole 34b (the sub
25 reference), the position of the ID chip 35 with respect to the connector 73e of the cap receiving section 73 is decided with a high degree of accuracy. Thus, the communication failure caused by position misalignment between the connector 73e and the ID chip 35 can be
30 suppressed. Particularly, since the positioning direction of the cap section 34Y in the cap receiving section 73 (the arrangement direction of the positioning pins 73a and 73b and the positioning holes 34a and 34b) is the same as the

positioning direction of the connector 73e and the substrate 35b (the arrangement direction of the positioning pin 73e3 and the notch 35b1), the positioning operation of the toner container 32Y on the image forming apparatus body 100 contributes to making it easier to position of the substrate 35b on the connector 73e. As a result, there is an effect in that the contact failure between the body side terminal 73e2 and the metallic pad 35a is difficult to occur.

10 Further, a procedure in which components of the bottle receiving section 72 and the cap receiving section 73 are concerned with the cap section 34Y when the mounting operation of the toner container 32Y on the toner container storage unit 70 proceeds is as follows.

15 First, the cap section 34Y slides on the bottle receiving surface 72a, and thereafter, the guide rail section 34e of the cap section 34Y is fitted into the engaged groove 73m of the cap receiving section 73, the lateral protrusion 34c of the cap section 34Y is fitted
20 into the lateral groove 73h and the groove section 73rl of the cap receiving section 73, and the posture of the cap section 73Y in the cap receiving section 73 in the vertical and horizontal directions is restricted. At this time, shaking of the cap section 34Y before being inserted into
25 the cap receiving section 73 is prevented by the cap section sandwiching member 73r. The first positioning hole 34a of the cap section 34Y is fitted into the main reference pin 73a of the cap receiving section 73, and so positioning of the main reference is performed. Thereafter,
30 the second positioning hole 34b of the cap section 34Y is fitted into the sub reference pin 73b of the cap receiving section 73, and so main and sub positioning is completed. Further, while the positioning is being completed, the

contact state between the stopper section 34d22 of the shutter member 34d of the cap section 34Y and the contact section 34n5 is released by the stopper release urging section 72b, and the postures of the shutter member 34d and the cap section 34Y in the cap receiving section 73 are decided by a body side shutter closing mechanism (not shown). In this state, the opening operation of the shutter member 34d is performed. The toner discharge opening W opened in the cap section 34Y is communicated with the toner feeding opening 73w of the cap receiving section 73. The notch 35b1 of the ID chip 35 of the cap section 34Y is engaged with the positioning pin 73e3 of the connector 73e of the apparatus body 100, the position of the ID chip 35 in the cap section 34Y is decided, and the plurality of metallic pads 35a of the ID chip 35 come in contact with the plurality of body side terminals 73e2 of the connector 73e, respectively, with a high degree of certainty. Thus, setting of the cap section 34Y (the toner container 32Y) in the cap receiving section 73 (the toner container storage unit 70) is completed. At this time, the gear 33c of the container body 33Y meshes with the driving gear 81 of the apparatus body 100.

Meanwhile, when extracting (removing) the toner container 32Y from the toner container storage unit 70 (the cap receiving section 73), the procedure reverse to the procedure at the time of mounting is performed.

As described above, in the image forming apparatus according to the present first embodiment, as the user performs one action of moving the toner container 32Y in the longitudinal direction while gripping the gripping section 33d (excluding the opening/closing operation of the body cover), the opening/closing operation of the toner discharge opening W by the shutter member 34d is also

performed in conjunction with the operation, and the mounting operation and the removing operation of the toner container 32Y is completed.

Further, in the toner container 32Y according to the present first embodiment, the toner discharge opening W having the comparatively large opening area size is disposed downward in the vertical direction, and so the toner can be discharged such that it falls directly from the toner discharge opening W by its own weight.

Further, since the toner container 32Y is not placed from above the toner container storage unit 70 (the apparatus body 100) but attached to or detached from the front surface of the toner container storage unit 70 (the apparatus body 100), a degree of freedom of the layout above the toner container storage unit 70 increases. For example, even when a scanner (a document reading section) is disposed directly above the toner feeding device, operability or workability at the time of attachment/detachment of the toner container 32Y does not deteriorate.

Further, since the toner container 32Y is disposed in the apparatus body 100 such that the longitudinal direction is the horizontal direction, it does not have any influence on the overall layout of the image forming apparatus body 100 in the height direction. The toner capacity of the toner container 32Y increases, and so the replacement frequency can be reduced.

As described above, in the present first embodiment, the contact-type ID chip 35 (the information storage device) is held on the holding member 34k (the holding section) to be movable on the virtual plane that is substantially orthogonal to the movement direction in which the metallic pads 35a (terminals) approach and come in

contact with the body side terminals 73e2. Thus, even when the contact-type ID chip 35 (the information storage device) is installed in the toner container 32Y (the removable device) installed removably on the image forming apparatus body 100, the contact failure caused by the positioning failure with the body side terminals 73e2 of the connector 73e of the image forming apparatus body 100 is difficult to occur.

10 Second Embodiment

A second embodiment of the present invention will be described in detail with reference to Figs. 31 to 33.

Fig. 31 is a schematic cross sectional view illustrating a toner container 232Y according to the present second embodiment. Fig. 32 is a back view illustrating a cap section 234Y of a toner container 232Y. Fig. 33 is a perspective view illustrating a holding cover 234k8 that is fitted into a holding member 234k.

The toner container 232Y according to the present second embodiment is different from the first embodiment in configuration of the holding member 234k in a holding mechanism for holding the information storage device.

Similarly to the first embodiment, the toner container 232Y according to the present second embodiment includes the container body 33Y and a cap section 234Y. The ID chip 35 as the information storage device is removably installed in the cap section 234Y.

In the cap section 234Y according to the present second embodiment, the holding member 234k in which the opening 34k2 exposing part of the ID chip 35 (the metallic pads 35a and the notch 35b1) is formed is integrally formed.

The ID chip 35 is inserted into from the inner side of the cap section 234Y in a direction of an arrow in Fig. 31

and set at the position of the holding member 234k. In the state in which the ID chip 35 is set at the position of the holding member 234k, the holding cover 234k8 is inserted into from the inner side of the cap section 234Y in the direction of the arrow in Fig. 31 and fitted into the holding member 234k (the state of Fig. 32).

In the holding cover 234k8, a pedestal section 234q that is fitted into the holding member 134k is disposed so as not to come in contact with the substrate 35b.

Further, the holding cover 234k8 is tightly installed without a clearance with the inner wall of the cap section 234Y so as to prevent the toner leaking from the toner container 232Y from sticking to the ID chip 35.

Even in the present second embodiment, the ID chip 35 (the substrate 35b) is held in the holding member 234k (and the holding cover 234k8) to be movable on the XZ plane.

As described above, similarly to the first embodiment, even in the present second embodiment, the contact-type ID chip 35 (the information storage device) is held on the holding member 234k (the holding section) to be movable on the virtual plane that is substantially orthogonal to the movement direction in which the metallic pads 35a (terminals) approach and come in contact with body side terminals 73e2. Thus, even when the contact-type ID chip 35 (the information storage device) is installed in the toner container 232Y (the removable device) installed removably on the image forming apparatus body 100, the contact failure caused by the positioning failure with the body side terminals 73e2 of the connector 73e of the image forming apparatus body 100 is difficult to occur.

Third Embodiment

A third embodiment of the present invention will be

described in detail with reference to Fig. 34.

Fig. 34 is a schematic view illustrating a state in which the information storage device 35 of a toner container 332Y according to the present third embodiment is set to the connector 73e of the cap receiving section 73. Fig. 34 is a view corresponding to Fig. 27 in the first embodiment.

The present third embodiment is different from the first embodiment in that a cushion material 334k10 is installed inside the holding member 34k and a configuration of a wall section 373g of a cap receiving section 373 is different.

Similarly to the above embodiments, a toner container 332Y according to the present third embodiment includes a container body 33Y and the cap section 34Y. The ID chip 35 as the information storage device is removably installed in the cap section 34Y. Further, the ID chip 35 is held in the holding member 34k to be movable in the XZ plane.

In the present third embodiment, the cushion material 334k10 is disposed between the inner wall (the second facing section 34k5) of the holding member 34k and the substrate 35b. The cushion material 334k10 is made of an elastic material such as foamed polyurethane, and a low frictional material adheres to a section facing the substrate 35b. Thus, it is possible to alleviate damage occurring in the substrate 35b when the positioning pin 73e3 is engaged with the notch 35b1 without hindering movement of the ID chip (the substrate 35b) in the XZ plane.

In the present third embodiment, the wall section 373g of the cap receiving section 373 is installed to surround four sides of the connector 73e. In order to cope with it, the concave section for avoiding interference with the wall section 373g is formed in the cap section 34Y. By

disposing the wall section 373g as described above, even if the toner is scattered from the vicinity of the toner discharge opening W of the toner container 332Y to the outside, the scattered toner is difficult to stick directly to the connector 73e or the ID chip 35. Thus, the contact failure (the communication failure) between the connector 73e (the body side terminal 73e2) and the ID chip 35 (the metallic pad 35a) caused by the scattered toner can be prevented.

As described above, similarly to the above embodiments, even in the present third embodiment, the contact-type ID chip 35 (the information storage device) is held on the holding member 34k (the holding section) to be movable on the virtual plane that is substantially orthogonal to the movement direction in which the metallic pads 35a (terminals) approach and come in contact with body side terminals 73e2. Thus, even when the contact-type ID chip 35 (the information storage device) is installed in the toner container 332Y (the removable device) installed removably on the image forming apparatus body 100, the contact failure caused by the positioning failure with the body side terminals 73e2 of the connector 73e of the image forming apparatus body 100 is difficult to occur.

Fourth Embodiment

A fourth embodiment of the present invention will be described in detail with reference to Fig. 35.

Fig. 35 is a three-plane view illustrating a substrate 435b of an information storage device 435 according to the present fourth embodiment. Fig. 35 is a view corresponding to Figs. 14A and 14B in the first embodiment.

Similarly to the above embodiments, a toner container (432Y) according to the present fourth embodiment also

includes the container body 33Y and the cap section 34Y. The ID chip 435 as an information storage device is removably installed in the cap section 34Y. Further, the ID chip 435 is held in the holding member 34k to be movable
5 in the XZ plane.

In a substrate 435b of the ID chip 435 according to the present third embodiment, instead of the positioning notch 35b1 in the above embodiments, positioning holes 435b11 and 435b12 are disposed. In accompany with the
10 mounting operation of the toner container (432Y), the substrate 435b freely moves in the XZ plane, and the positioning holes 435b11 and 435b12 are engaged with the positioning pins 73e3 of the connector 73e. Specifically, edges (or inner surfaces) of the holes 435b11 and 435b12
15 come in contact with the positioning pins 73e3, and movement of the substrate 435b is restricted. Thus, the contact failure caused by the positioning failure between the plurality of metallic pads 35a and the body side terminals 73e2 of the connector 73e is difficult to occur.

20 In the present fourth embodiment, in view of the fact that the substrate 435b is positioned at the lower side of the holding member 34k due to the weight of the substrate 435b directly before the positioning holes 435b11 and 435b12 are engaged with the positioning pins 73e3, the
25 circular hole 435b11 is formed in the lower section of the substrate 435b, and the elliptical hole 435b12 is formed in the upper section of the substrate 435b. The hole 435b11 in the lower section is picked up by the positioning pin 73e3, and so the substrate 435b is raised, and the
30 positioning pin 73e3 is smoothly inserted into the other elliptical hole (the hole 435b12). If the hole in the lower section is the elliptical hole and the hole in the upper section is the circular hole, the substrate 435b may

not be raised by the positioning pin 73e3, and the positioning pin 73e3 may not be difficult to be inserted into the circular hole in the upper portion.

In the present fourth embodiment, the two positioning
5 holes 435b11 and 435b12 are formed in the substrate 35b of the ID chip 35. On the other hand, in the substrate 435b of the ID chip 435, one may be formed of the positioning holes 435b11 (or 435b12), and the other may be formed of the positioning notch 35b1 (that has been used in the above
10 embodiments). Even in this case, the same effect as in the present fourth embodiment can be obtained.

As described above, similarly to the above embodiments, even in the present fourth embodiment, the contact-type ID chip 435 (the information storage device) is held on the
15 holding member 34k (the holding section) to be movable on the virtual plane that is substantially orthogonal to the movement direction in which the metallic pads 35a (terminals) approach and come in contact with body side terminals 73e2. Thus, even when the contact-type ID chip
20 435 (the information storage device) is installed in the toner container (the removable device) installed removably on the image forming apparatus body 100, the contact failure caused by the positioning failure with the body side terminals 73e2 of the connector 73e of the image
25 forming apparatus body 100 is difficult to occur.

Fifth Embodiment

A fifth embodiment of the present invention will be described in detail with reference to Figs. 36 to 41.

30 Fig. 36 is a three-plane view illustrating a substrate of an information storage device 535 according to the present fifth embodiment and is a view corresponding to Fig. 29 in the first embodiment. Fig. 37 is a perspective view

illustrating the information storage device 535, a holding member 534k (534k25), and a connector 573e and is a perspective view illustrating a relative positional relation of the three members 534k (534k25), 535, and 573e.

- 5 Fig. 38 is a perspective view illustrating a condition in which the information storage device 535 is engaged with the connector 573e. Figs. 39A and 39B are circuit diagrams illustrating an electric circuit of the information storage device 535 and an electric circuit of the connector 573e.
- 10 Fig. 40A is a front view illustrating a condition in which the information storage device 535 is held on the connector 573e, and Fig. 40B is a front view illustrating a condition in which the information storage device 535 is rotating on a positioning hole 535b21. Fig. 41 is a view illustrating
- 15 the information storage device 535 that comes in contact with a probe 400 in an inspection process when manufactured in a factory.

The present fifth embodiment is different from the first to fourth embodiments in that only one positioning

20 hole 535b21 is formed in the substrate 535b of the information storage device 535, and the positioning hole 535b21 is disposed between a plurality of rectangular metallic pads 35a1, 35a2, and 35a3 (metallic pads).

Referring to Fig. 36, the ID chip 535 as the

25 information storage device according to the present fifth embodiment has the positioning hole 535b21 that is formed at the upper position in the vertical direction further than the gravity center of the substrate 535b. An earth metallic terminal 535d is disposed on an inner surface of

30 the hole 535b21 and around the hole 535b21. In the present fifth embodiment, the metallic terminal 535d formed on the surface of the substrate 535b includes two protruding sections 535d1 that are formed to extend from a rink-like

section in the horizontal direction.

Further, the rectangular metallic pad 35a1 is installed above the positioning hole 535b21 in the vertical direction, and the two rectangular metallic pads 35a2 and
5 35a3 are installed below the positioning hole 535b21 in the vertical direction.

Further, on the back side of the substrate 535b (the side facing the cap section 34Y), a protection member 535e that is made of a resin material having a substantially
10 hemispherical shape or a shape of an inverted pan such as epoxy and covers the information storage unit is disposed. In the present fifth embodiment, although it depends on the shape of the substrate 535b or the configuration/arrangement of the back surface such as the
15 protection member 535e, by disposing the hole 535b21 above the protection member 535e that may include the information storage unit such as an integrated circuit (IC) thereinside and is a heaviest component, a positional relation in which the hole 535b21 is installed vertically above the gravity
20 center of the ID chip 535 is implemented. Specifically, referring to Fig. 40A, the ID chip 535 (the information storage device) according to the present fifth embodiment is formed so that the center position of the positioning hole 535b21 is at the distance Z_a above the gravity center
25 of the ID chip 535.

Referring to Fig. 37, the connector 573e includes a connector body 573e21 that is made of resin and is a hollow box, and a positioning pin 573e23 (a positioning protruding section) that is a hollow cylinder and having a tapered tip
30 is disposed on the connector body 573e21 to stand in the horizontal direction. A body side earth terminal 573e25 (an earth terminal) is installed in the positioning pin 573e23. The body side earth terminal 573e25 is a plat-like

(or linear) metallic member, partially stored in the hollow section of the positioning pin 573e23 formed integrally with a connector 573e21, and has a curved section that is exposed from a slit-like opening formed in part of the circumferential surface of the hollow cylinder and protrudes from the cylindrical outer circumferential surface. Further, one body side terminal 573e2 is installed vertically above the positioning pin 573e23 (the body side earth terminal 573e25), and two body side terminals 573e2 are installed vertically below the positioning pin 573e23 (the body side earth terminal 573e25). The body side terminals 573e2 are plat-like (or linear) metallic members and are formed almost in the same manner as in the above embodiments except that the installation position is different.

Further, swing preventing members 573e24 as a pair of guiding members protrude from the right and left sides of the positioning pin 573e23. The guiding members include a pair of plates whose tips have inner tapered surfaces facing each other and the guide the both sides of the ID chip 535 to be upright.

Similarly to the above embodiments, the holding member 534k (the holding section) is fixed to a toner container (532Y) and positioned between the connector 573e and the ID chip 535. The holding member 534k has almost the same function (a function for movably holding the ID chip 35) as in the above embodiments. Referring to Fig. 37, the holding member 534k according to the present fifth embodiment has a first facing section 534k24 that is configured to be linearly symmetrical on a center axis in the vertical direction and is formed to cover an area from two upper corners of the ID chip 535 to both sides of the hole 535b21. The holding member 534k is formed to cover

the lower section of the substrate 535b further than the lowest metallic pad 35a3, and through the above described configuration, the ID chip 535 is prevented from falling from the holding member 534k.

5 Further, in the holding member 534k, the first facing section 534k24 including an area facing the four body side terminals 573e2 and 573e25 of the connector 573e is formed of an opening. Particularly, in the holding member 534k, formed is an opening 534k22 that is opened up to a section
10 corresponding to a pair of swing preventing members 573e24. At the time of mounting of the toner container 532Y, the positioning pin 573e23 is inserted into the opening 534k22, and thereafter the pair of swing preventing members 573e24 (the pair of guiding members) is also inserted into the
15 holding member 534k through the opening 534k22.

A second facing section 534k25 of a flat plate form facing the back surface of the ID chip 535 (the side of the holding member 535e) is fixed to the holding member 534k by adhesion or a snap fit (not shown). The second facing
20 section 534k25 includes a opening 534k26 similarly to the opening 534k22 and so can avoid interference with the holding member 535e or the inserted swing preventing member 573e24. Meanwhile, when the positioning pin 573e23 is inserted into the hole 535b21 of the ID chip 535, the ID
25 chip 535 is pushed, but since the second facing section 534k25 supports the substrate 535b from the rear side, the contact condition between the terminals can be maintained.

Fig. 38 is a schematic perspective view illustrating the condition in which positioning of the connector 573e
30 and the ID chip 535 at the apparatus body 100 side is completed. The condition is that the toner container 532Y according to the fifth embodiment is mounted on the apparatus body 100, and the body side terminals 573e2 and

573e25 are connected with the abovementioned metallic pads 35a1 to 35a3 and the earth terminal 535d. In Fig. 38, for the sake of easy understanding, the holding member 534k (534k25) between the connector 573e and the ID chip 535 and the metallic pads 35a1 to 35a3 are omitted.

When mounting the toner container 532Y on the image forming apparatus body, the main and subordinate positioning holes 34a and 34b of the cap section 534Y are fitted into the main and subordinate positioning pins 73a and 73b of the cap receiving section 73, and positioning of the cap section 534Y is performed. This mounting operation is the same as the mounting operation of the first embodiment. After the position of the cap section 534Y is decided, the hole 535b21 of the ID chip 535 is fitted into the positioning pin 573e23 to be picked up by the tapered tip of the positioning pin 573e23 of the connector 573e. As a result, the position of the ID chip 535 in the horizontal direction and the vertical direction is decided at the same time. Further, as illustrated in Fig. 40A, the swing preventing member 573e24 (the pair of guiding members) of the connector 573e that includes the pair of plates are inserted into the lower edge portions that are at both right and left sides of the substrate 535b and at the lower area further than the center of the hole 535b21. At this time, it is a possible case that the posture of the ID chip is misaligned as illustrated in Fig. 40B. Even in this case, if the inner tapered surfaces of the plates comes in contact with the lower edge portions, it causes the substrate 535b to rotate in a direction for having the posture to be vertical by the action of the gravity center, and the misalignment of the posture in the rotation direction (rotation in a direction of an arrow illustrated in Fig. 40B) is corrected (it becomes a condition of Fig.

40A). Thus, positioning of the ID chip 535 is completed. At this time, part of the earth terminal 535d of the ID chip 535 (a section corresponding to the inner surface of the hole 535b21) comes in contact with the body side earth terminal 573e25 of the positioning pin 573e23 illustrated in Fig. 38, and the ID chip 535 is earthed (conduction). Further, after the earth is connected the three metallic pads 35a (35a1, 35a2, and 35a3) of the ID chip 535 also come in contact with the three body side terminals 573e2 of the connector 573e, respectively, and so information can be transmitted between the ID chip 535 and the body side connector 573e (the apparatus body 100).

As described above, in the present fifth embodiment, a high-accuracy positioning mechanism is implemented by an inexpensive configuration by adding various ideas such as the following ideas (1) to (5).

(1) It is only one positioning hole 535b21 for ID chip 535 to need to be positioned. Thus, the drill processing time of the substrate 535b in the manufacturing become shorter than two positioning holes type's ID chip, and the manufacturing cost can be reduced.

(2) The body side earth terminal 573e25 is integrally installed on the side circumferential surface of the positioning pin 573e23. Thus, the distance between the positioning pin 573e23 and the body side earth terminal 573e25 can become real zero (0), and a degree of position accuracy of the earth terminal 535d with respect to the body side terminal 573e25 can increase.

(3) In the mounting completion condition of Fig. 38, the positional relation between the positioning hole 535b21 and the curved sections of the body side terminals 573e2 is adjusted so as to match the hole center of the hole 535b21 with the line that connects the curved sections (connection

sections) of the three body side terminals 573e2 at the connector 573e side. Thus, the distance in the horizontal direction from the hole 535b21 as the positioning section to the contact sections can be reduced to nearly 0 mm. As
5 a result, when the three metallic pads 35a1, 35a2, and 35a3 come in contact with the body side terminals 573e2, a degree of position accuracy is improved.

(4) A plurality of metallic pads 35a1, 35a2, and 35a3 are lined, and the positioning hole 535b21 is arranged at
10 either of two spaces formed between two of the three lined pads. Thus, compared to another arrangement type's ID chip in which the hole is disposed at the lower side or the upper side outside a row of the plurality of metallic pads 35a1, 35a2, and 35a3, the distance (that corresponds to the
15 arm length of the pendulum) from the center of the positioning hole 535b21 to the farthest metallic pad 35a can be reduced. Specifically, on the another type, the arm length becomes the distance corresponding to the three metallic pads from the hole center. However, in the
20 present fifth embodiment, the arm length can be the distance corresponding to the two metallic pads. Since the arm length of the pendulum is short, even if the parallelism of the farthest metallic pad 35a on the body side terminal 73e2 is misaligned due to, for example,
25 variability in the mass production, the misalignment can be suppressed to a minimum.

(5) When a user stores the toner container in some space out of the image forming apparatus, an alien substance may enter the holding member 534k and so the
30 nipping position between the ID chip 535 and the facing sections 534k24 and 534k25 may remain misaligned. On this problem, in the present fifth embodiment, the positional relation between the hole 535b21 and the gravity center of

the ID chip 535 is improved. The hole 535b21 is arranged vertically above the gravity center of the ID chip 535. Thus, when the pair of the swing preventing members 573e24 is inserted below the hole 535b21 that is the rotation
5 center, the substrate 535b contacts with the tapered tips of the swing preventing member 573e24. Then, the posture of the ID chip 535 is urged to rotate in the vertical direction by the force of gravity and is corrected to be upright. As a result, even if there is one positioning
10 hole 535b21, a degree of position accuracy of the plurality of metallic pads 35a1, 35a2, and 35a3 on the plurality of body side terminals 573e2 can be increased at the same time.

Depending on a number of produced planned to be made, there is a possibility that it is determined that the
15 conduction inspection device has a margin in durability. In this case, inspection can be conducted using a inspection device having a configuration similar to the connector of the image forming apparatus body 100, i.e. by inserting a conduction probe into the hole in which the
20 earth terminal 535d is formed. In this case, as in a modification of the ID chip illustrated in Fig. 87, a circular earth terminal that does not include the protruding sections 535d1 may be employed. The same also applies to a case in which a manufacturing method in which
25 the conduction inspection is omitted based on improvement in production process is employed. With this modification, the area of the metallic members can be reduced and the manufacturing cost can be reduced. In fig. 87, the ID chip is illustrated assumed as being of a type in which no
30 protection member is provided on the IC circuit on the back surface and, therefore, the IC circuit is exposed. If the manufacturing environment, etc. allows absence of the protection member, such an ID chip is useful for cost

reduction. Although any layout is available so long as the IC circuit keeps out from both the right-and-left areas for smooth sliding, it is preferable to arrange a relatively large IC in a lower section so that the center of gravity is located at a lower position.

Moreover, if the earth conduction probe is of one pin, it is allowable to provide, as illustrated in Fig. 88A, one protruding section with which the earth probe 401 comes in contact. For easy earth inspection, the modification illustrated in Fig. 88B that has a size-increased probe contacting section may be employed. This is useful in particular in a case of manual inspection. The modification illustrated in Fig. 88C that has not a circular frame but a square frame may also be employed. Any of the modifications of Figs. 88A, 88B, and 88C are designed freely so long as the outer circumferential area of the terminal formed in the hole keeps out from both the right-and-left sliding areas. The back surfaces of the ID chips of Figs. 88A, 88B, and 88C can be either covered by the protection member or uncovered.

As described in the above described ideas (1) to (5), each of the five ideas can provide each function effect, and even if an inexpensive configuration in which the area size of the metallic pad 35a becomes minimal is employed, it is possible to highly increase a degree of positioning accuracy between the plurality of terminals 35a1, 35a2, and 35a3 and 535d including the earth terminal at the ID chip 535 and the plurality of body side terminals 573e2 and 573e25.

Further, in the present fifth embodiment, the ideas and function effects different from ones described above will be described.

Firstly, each of the metallic pads 35a1, 35a2, and

35a3 are described. The metallic pad 35a1, which is at the highest level, receives a clock signal for communication control. While a serial communication method that is low-speed but low-cost because of sequential data transfer is employed and an I2C (Inter-Integrated Circuit) is employed as a serial bus, The metallic pad 35a1 forms a signal line to which a serial clock (SCL) is input when the signal line is connected to the body side connector. The metallic pad 35a1 corresponds to a terminal to which a clock-signal is input. Because a clock signal flows in one way, it is expected that the possibility that the ID chip 535 breaks down if to a short circuit occurs between the metallic pad 35a1 and a later-described Vcc (the power supply or the metallic pad 35a3) than between the other terminals and the Vcc. Therefore, to prevent break down of the ID chip 535, the metallic pad 35a1 is arranged more distant from the Vcc. This is because the possibility of bread down is lower if a short circuit occurs between the metallic pad 35a1 and the GND (the earth terminal 535d).

The metallic pad 35a2 also employs a serial communication method, employing an I2C as a serial bus, and forms a signal line to which serial data (SDA) is input/output when the signal line is connected to the body side connector. Because this pad has a bidirectional input/output mechanism, the possibility that the ID chip 535 breaks down due to a short circuit is lower than the possibility due to the one-way input metallic pad 35a1.

The metallic pad 35a3 forms a power input portion (Vcc) to which a 5V voltage or a 3.3V voltage is input when it is connected to the body side connector. To decrease the risk of break down of the entire device due to a short circuit between the power supply and the GND, the serial-data input terminal (the metallic pad 35a2) is arranged

between the GND (the earth terminal 535d) and the serial-clock input terminal (the metallic pad 35a1). As illustrated in Fig. 36, the Vcc or the metallic pad 35a3 overlaps with the protection member 535e that is on the back side of the ID chip in such a manner that the substrate 535b is between them; therefore, the metallic pad 35a3 is close to an IC driving circuit included in the protection member 535e. With this arrangement, a short and thick line can be used as a power-supply line, which enables stable power-supply operations (=suppression of malfunction due to noises).

Secondly, ideas for earth are described. In the mounting operation of the toner container 532Y, the earth terminal 535d of the ID chip 535 comes in contact with the body side earth terminal 573e25 of the positioning pin 573e23 (the connector 573e), and then the three metallic pads 35a1, 35a2, and 35a3 of the ID chip 535 start to come in contact with the three body side terminals 573e2 of the connector 573e. That is, in the detaching operation of the toner container 532Y, contact between the three metallic pads 35a1, 35a2, and 35a3 of the ID chip 535 and the three body side terminals 573e2 of the connector 73e is released, and then the earth terminal 535d of the ID chip 535 is released from the contact condition with (separated from) the body side earth terminal 573e25 of the positioning pin 573e23 (the connector 573e). Specifically, referring to Fig. 39A, the body side earth terminal 573e25 in the connector 573e has the contact start position closer to the ID chip 535 side than the three body side terminals 573e2.

Through the above described configuration, in the mounting operation of the toner container 532Y, the metallic pads 35a1, 35a2, and 35a3 always start to be connected with the body side terminals 573e2 in the

condition in which the ID chip 535 is earthed, and in the detaching operation of the toner container 532Y, the metallic pads 35a1, 35a2, and 35a3 always start to be separated from (released from the contact condition with) the body side terminals 573e2 in the condition in which the ID chip 535 is earthed. Thus, an electric circuit at the ID chip 535 is prevented from being not earthed and so becoming an electrically floating condition, and so the ID chip 535 is difficult to be electrically damaged.

In detail, when the electric circuit at the ID chip 535 is not earthed and becomes an electrically floating condition, the electrical circuit becomes a condition that is earthed with very large impedance. If static electricity, which is generated when the metallic pads 535a come in contact with or are separated from the body side terminals 573e2, slightly flows to the electric circuit, a high voltage that is the same as impedance is applied to the current is generated. The high voltage causes insulation breakdown inside the IC in the ID chip 535, and thus the IC is broken. This problem easily occurs when the contact start positions of the three body side terminals 573e2 and the body side earth terminal 573e25 on the ID chip 535 are formed at the same position, with respect to the connector 573e, as illustrated in Fig. 39B.

On the other hand, in the present fifth embodiment, the curved section of the body side earth terminal 573e25 exposed from the slit-like opening of the positioning pin 573e23 is disposed to be closer to the ID chip 535 than the curved section of the body side terminal 73e2 that most protrudes to the ID chip 535 side. Thus, since the earth is first connected, and at the time of separation and the earth is lastly disconnected at the time of contact, the impedance is always theoretically zero, and even if static

electricity flows to the inside of the electric circuit, insulation breakdown inside the IC is prevented.

Further, in the ID chip 535 (the information storage device) according to the present fifth embodiment, the two
5 protruding sections 535d1 are disposed on part of the outer circumference of the earth terminal 535d as described above with reference to Fig. 36.

Since the protruding sections 535d1 are disposed on the front surface of the substrate 535b of the ID chip 535
10 as described above, in the inspection process (a process of inspecting whether or not the ID chip 535 is defective) at the time of manufacturing in a factory, an operation of contacting a conduction inspection probe can be easily performed. In detail, as illustrated in Fig. 41, leading
15 ends of a plurality of probes 401 of a conduction inspection device 400 are pressed downward against the metallic pads 35a and the earth terminal 535d of the ID chip 535 placed on an inspection table. At this time, since the protruding section 535d1 of the earth terminal
20 535d has an area that can sufficiently come in contact with the leading ends of the probes 401, a conduction inspection failure caused by a contact failure of the probes 401 can be prevented. Further, since conduction inspection is performed by pressing the leading end sections of the
25 probes 401 downward against the earth terminal 535d (the protruding section 535d1), compared to when conduction inspection is performed by inserting the probes 401 into the hole 535b21, a resistance characteristic of the probes 401 that are repetitively used for inspection can be
30 improved, and a problem in that the hole 535b21 of the ID chip 535 wears by conduction inspection can be prevented.

In a surplus space broadening in a wedge form between the annular earth terminal 535d and the rectangular

metallic pad 35a1, 35a2, the protruding section 535d1 has a horizontal direction boundary (boundary line) that comes in contact with the annular outer circumference and is disposed to be parallel to the metallic pads 35a1, 35a2, and 35a3. Thus, the protruding section 535d1 does not protrude in the vertical direction, the protruding section 535d1 can be prevented from protruding to the left and sliding areas of the substrate 535b that slides against the first facing section 534k24 (protruding in the horizontal direction). As a result, the size of the substrate 535b does not increase, and at the time of manufacturing, it is possible to obtain as many substrates 535b having the standard size as possible from a substrate material. Further, the cost of the ID chip 535 can be suppressed from increasing.

As described above, similarly to the above embodiments, even in the present fifth embodiment, the contact-type ID chip 535 (the information storage device) is held on the holding member 534k (the holding section) to be movable on the virtual plane that is substantially orthogonal to the movement direction in which the metallic pads 35a1, 35a2, and 35a3 (terminals) approach and come in contact with body side terminals 573e2. Thus, even when the contact-type ID chip 535 (the information storage device) is installed in the toner container 532Y (the removable device) installed removably on the image forming apparatus body 100, the contact failure caused by the positioning failure with the body side terminals 573e2 of the connector 573e is difficult to occur.

Further, in the present fifth embodiment, even when the contact-type ID chip 535 (the information storage device) is installed in the toner container 532Y (the removable device) installed removably on the image forming

apparatus body 100, since the earth terminal 535d that is engaged with the body side earth terminal 573e25 formed in the positioning pin 573e23 (the protruding section) of the connector 573e (the image forming apparatus body 100) is
5 formed in one hole 535b21 formed in the substrate 535b of the ID chip 535, the ID chip 535 is difficult to be electrically damaged.

Sixth Embodiment

10 A sixth embodiment of the present invention will be described in detail with reference to Figs. 42A to 47C.

Figs. 42A and 42B are perspective views illustrating a toner container 632Y according to a sixth embodiment. Particularly, Fig. 42A is an exploded view illustrating a
15 state in which the ID chip 535 described in the fifth embodiment is not mounted, and Fig. 42B is a view illustrating a state in which the ID chip 535 is mounted. Fig. 43 is a front view illustrating the toner container 632Y in which a face plate 634p is not
20 installed and is a view corresponding to Fig. 21 in the first embodiment. Fig. 44 is a cross-sectional view illustrating a main part of the toner container 632Y in which the ID chip 535 and the face plate 634p are installed. Fig. 45 is a view illustrating a state in which the ID chip
25 535 is inserted into the connector 573e.

In the present sixth embodiment, the ID chip 535 as the information storage device is the same as in the fifth embodiment. The present sixth embodiment is different from the fifth embodiment in that the ID chip 535 is loosely
30 held in a concave section disposed in a cap section 634Y and movably covered by the face plate 634p, and the remaining configuration is the same as in the fifth embodiment.

Similarly to the above embodiments, the toner container 632Y according to the present sixth embodiment also includes the container body 33Y and the cap section 634Y. The ID chip 535 as the information storage device is
5 removably installed in the cap section 634Y.

Referring to Figs. 42A and 42B, in the present sixth embodiment, the ID chip 535 is not installed in the cap section 534Y in a state in which it is loosely inserted into the holding member 534k, and the falling prevention
10 face plate 634p is screw-coupled to the cap section 634Y in a state in which the ID chip 535 is loosely held in the concave section (in which a pedestal section 634q is formed) formed in the cap section 634Y.

In detail, referring to Fig. 42A and Fig. 43, the
15 concave section for holding the ID chip 535 to be movable in the XZ plane is formed on the end surface of the cap section 634Y. In the concave section, formed is the pedestal section 634q that comes in surface contact with part of the ID chip 535. In the state in which the ID chip
20 535 is loosely held in the concave section of the cap section 634Y, the face plate 634p for preventing the ID chip 535 from falling from the concave section is attached. Referring to Fig. 42B, Fig. 43, and Fig. 44, the face plate 634p is screw-coupled to come in contact with part of the
25 substrate 35b of the ID chip 35 in the state in which the metallic pads 35a1, 35a2, and 35a3, the positioning hole 535b21 (the earth terminal 535d), and the like of the ID chip 535 formed similarly to the fifth embodiment are exposed.

30 In further detail, in the cap section 634Y, a positioning pin 634s1 for positioning the face plate 634p is formed on the right side of the concave section, and a screw hole 634s11 for screw-fixing the face plate 634p is

formed on the left of the concave section with the concave section interposed therebetween. Meanwhile, in the face plate 634p, a positioning hole 634p1 is formed at the position corresponding to the positioning pin 634s1, and a hole 634p2 through which a screw 680 passes is formed at the position corresponding to the screw hole 634s11. In the lower section of the face plate 634p, a contact section 634p3 that comes in contact with the outer circumferential edge of the second positioning hole 34b and functions as a rotation stopper is formed. The position of the face plate 634p with respect to the cap section 634Y is decided by the positioning hole 634p1 and the contact section 634p3 for rotation stopping. The screw 680 is screwed into the screw hole 634s11 formed in the cap section 634Y through the hole 634p2 formed in the face plate 634p, and so the face plate 634p is fixed to the cap section 634Y. Thus, the ID chip 535 does not fall from the cap section 634Y and is held on the cap section 634Y to be movable in the XZ plane.

Referring to Fig. 45, similarly to the fifth embodiment, in accompany with the mounting operation of the toner container 632Y, the positioning hole 535b21 (the earth terminal 535d) of the ID chip 535 is engaged with the positioning pin 573e23 (the body side earth terminal 573e25) of the connector 573e of the apparatus body 100, thereafter the body side terminal 573e2 of the connector 573e comes in contact with the metallic pads 35a1, 35a2, and 35a3 of the ID chip 535, and so electrical contact between the connector 573e and the ID chip 535 is completed. In this case, since the ID chip 535 in the cap section 634Y of the toner container 632Y is held to be movable in the XZ plane, similarly to the above embodiments, the contact failure caused by the positioning failure with the body side terminals 73e2 and 573e25 of the connector 573e of the

apparatus body 100 is difficult to occur. In the normal state, the ID chip 535 remains down to the lower side of the concave section of the cap section 534Y due to gravity, and the center position of the hole 535b21 of the ID chip 535 is misaligned downward on the axial center position of the positioning pin 573e23 like the most left one among the three ID chips 535 illustrated in Fig. 45.

Then, when the mounting operation of the toner container 632Y starts and the ID chip 535 comes in contact with the positioning pin 573e23, the ID chip 535 moves upward (in the Z direction) (is scooped up) such that the hole 535b21 follows the tapered leading end section of the positioning pin 573e23, the hole 535b21 is fitted into the positioning pin 573e23, and finally the body side terminals 573e2 comes in contact with the metallic pads 35a1, 35a2, and 35a3.

In the present sixth embodiment, the face plate 634p has been fixed (screw-coupled) to the cap section 34Y by the screw 680.

On the other hand, as illustrated in Figs. 46A and 46B, a face plate 734p may be fixed to a cap section 734Y by snap fit fixing. In detail, as illustrated in Fig. 46A, a plurality of snap fit fixing engaging section 734p2 are formed on the outer circumferential section of the face plate 734p, and snap fit fixing engaged sections 734s2 are formed at the positions of the cap section 734Y corresponding thereto. As illustrated in Fig. 46B, in the state in which the ID chip 535 is loosely inserted into the concave section of the cap section 734Y, the face plate 734p is snap fit-fixed to the cap section 734Y. In further detail, while aligning a hole 734p3 formed in the face plate 734p with a positioning boss section 734s3 formed in the cap section 734Y, the engaging section 734p2 of the

face plate 734p is engaged with the engaged section 734s2 of the cap section 734Y, and the face plate 734p is positioned and fixed to the cap section 734Y. Even in the case of this configuration, the same effect as in the sixth
5 embodiment can be obtained.

Further, in the present sixth embodiment, since replacement can be made again even after the face plate 634p (or the face plate 734p illustrated in Figs. 46A and 46B) is assembled, the toner container can be manufactured
10 by a procedure in which the toner container and the face plate manufactured by a foreign partner company are first imported, and then, within the country, after or before a process of filling the toner container with the toner, the ID chip 535 purchased from another company is assembled,
15 and toner information is input to the ID chip 535. Thus, the manufacturing process of the toner container can be effectively performed.

Further, a recycling process of collecting the used toner container from the market and filling the toner again
20 after cleaning it may be performed by a procedure of replacing the ID chip 535 or removing the ID chip 535 from the toner container, rewriting information, and mounting the ID chip 535 on the cap section again. Thus, the reusing process of the toner container can be effectively
25 performed.

However, referring to Fig. 47C (that is a cross-sectional view illustrating a cap section 834Y on which the ID chip 535 is mounted), when it is desired to increase an assembly strength between a face plate 834p and a cap
30 section 834Y without needing to remove the ID chip 535, only the positioning boss 734s3 (for example, see Figs. 46A and 46B) may be disposed in the cap section without disposing the shape for screw coupling or the shape for

5 snap fitting. Then, after the ID chip 535 and the face plate 834p are assembled in the cap section 834Y, the leading end of the positioning boss 734s3 may be thermally molten to fix the face plate 834p to the cap section 834Y, or an adhesive may be coated between the face plate 834p and the cap section 834Y to fix the face plate 834p to the cap section 834Y.

As described above, in the present sixth embodiment, the contact-type ID chip 535 (the information storage
10 device) is held on the cap section 634Y, 734Y, or 834Y to be movable on the virtual plane that is substantially orthogonal to the movement direction in which the metallic pads 35a1, 35a2, and 35a3 (terminals) approach and come in contact with body side terminals 573e2. Thus, even when
15 the contact-type ID chip 535 (the information storage device) is installed in the toner container 632Y, 732Y, or 832Y (the removable device) installed removably on the image forming apparatus body 100, the contact failure caused by the positioning failure with the body side
20 terminals 573e2 of the connector 573e of the image forming apparatus body 100 is difficult to occur.

Further, even in the present sixth embodiment, similarly to the fifth embodiment, even when the contact-type ID chip 535 (the information storage device) is
25 installed in the toner container 632Y (the removable device) installed removably on the image forming apparatus body 100, since the earth terminal 535d engaged with the body side earth terminal 573e25 formed in the positioning pin 573e23 (the protruding section) of the connector 573e
30 (the image forming apparatus body 100) is formed in one hole 535b21 formed in the substrate 535b of the ID chip 535, the ID chip 535 is difficult to be electrically damaged.

Figs. 47A and 47B are views illustrating a toner

container 932Y of another embodiment. Particularly, Fig. 47A is a front view illustrating a cap section 934Y on which the ID chip 535 is mounted, and Fig. 47B is a front view illustrating the cap section 934Y and the ID chip 535 before the ID chip 535 is mounted. In the toner container 932Y illustrated in Figs. 47A and 47B, unlike the above embodiments, the ID chip 535 (the information storage device) is fixed to and held on the cap section 934Y (held to be movable in the XZ direction). Specifically, a concave section of the cap section 934Y (a section encircled by a dotted line in Fig. 47B) is formed in a shape according to an outer circumferential shape of the ID chip 535 so that the ID chip 535 can be fitted thereinto (fitted thereinto within a dimension variation range by a fitting tolerance of about 0.3 mm at maximum even if shaken). In this case, unlike the above embodiments, the ID chip 535 cannot move in the XZ plane, but the function effects of the ideas (1) to (4) among the five ideas (1) to (5) described in the fifth embodiment can be obtained. That is, since one positioning hole 535b21 in which the earth terminal 535d is formed is installed in the ID chip 535, the effects described in the fifth embodiment can be obtained.

Seventh Embodiment

A seventh embodiment of the present invention will be described in detail with reference to Figs. 48 and 49. Fig. 48 is an exploded perspective view illustrating a toner container 1032Y according to the seventh embodiment. Fig. 49 is a cross-sectional view illustrating the toner container 1032Y.

The toner container according to the present seventh embodiment is different from the above embodiments in which

the container body 33Y is rotatably held on the toner container storage unit 70 in that a container body 1033Y is combined with any one of the cap sections 634Y, 734Y, 834Y, and 934Y illustrated in the sixth embodiment and non-rotatably held on the toner container storage unit 70 together with the cap section.

Referring to Figs. 48 and 49, similarly to the above embodiments, the toner container 1032Y according to the present seventh embodiment mainly includes the container body 1033Y (the bottle body) and the cap section 634Y installed on the head section thereof (or the cap section 734Y, 834Y, or 934Y of another form). Hereinafter, the cap section according to the present seventh embodiment will be described using the cap section 634Y described with reference to Figs. 42A and 42B in the sixth embodiment.

Unlike the above embodiments, in the toner container 1032Y according to the present seventh embodiment, the container body 1033Y (the bottle body) is fixed to the cap section 634Y by a fixing method, for example, it adheres to (fuses with) or is engaged with the cap section 634Y (the bottle cap). That is, the container body 1033Y is non-rotatably fixed to the cap section 634Y.

Unlike the above embodiments, in the container body 1033Y according to the present seventh embodiment, a helical protrusion is not formed on the circumferential surface thereof. Further, the gear 33c in the above embodiments is not integrally formed with the container body 1033Y, and a gear member 1042Y is installed rotatably on the container body 1033Y and the cap section 634Y together with the agitating member 33f. Inside the container body 1033Y, unlike the above embodiments, a conveying member 1041Y for conveying the toner stored in the container body 1033Y toward the opening A is formed

such that one end thereof is fixed to the gear 1042Y, and the other end thereof is rotatably supported on a bearing 1033d1 of the container body 1033Y which will be described later.

5 The cap section 634Y has almost the same configuration as in the fifth embodiment except that it non-rotatably adheres to or is fixed to the container body 1033Y.

 The agitating member 33f has almost the same configuration, form, and function as in the above
10 embodiments except that it is not fixed to the container body 1033Y but held only on the gear 1042Y.

 A further detailed description will be made with reference to Figs. 48 and 49.

 Referring to Fig. 48, even in the seventh embodiment,
15 on the other end side of the container body 1033Y in the longitudinal direction (the side opposite to one end side, at which the cap section 634Y is installed, in the longitudinal direction and an end section at the rear side in the mounting direction on the apparatus body 100),
20 disposed is a gripping section 1033d gripped by the user when the attaching/detaching operation of the toner container 1032Y is performed. In the gripping section 1033d, a through hole communicating with the inside and outside of the container body 1033Y is formed, and a cover
25 member 1049Y that is formed of deformable flexible resin such as polypropylene or polyethylene is removably installed in the through hole. The cover member 1049Y is used when filling the inside of the toner container 1032Y (the container body 1033Y) with the toner (or cleaning),
30 for example, at the time of manufacturing or recycling. The cover member 1049Y is removed from the container body 1033Y when filling the toner (cleaning) and mounted to the container body 1033Y after filling of the toner is

completed.

Referring to Fig. 49, the conveying member 1041Y installed inside the container body 1033Y is formed such that a thin flexible agitating member 1041Yb formed of a material such as mylar (a trade name: a polyester film) adheres to a shaft section 1041Ya, and an agitator member 1041Yc is formed at the opposite side. In the shaft section 1041Ya of the conveying member 1041Y, an end section at one end side in the longitudinal direction is engaged with and fixed to a connection section 1033f20 installed at the position of the rotation center of the agitating member 33f. An end section at the other side in the longitudinal direction is rotatably supported on the bearing section 1033d1 (which is a base section of the gripping section 1033d and formed in a section stuck into the container body 1033Y). In the state in which the container body 1033Y and the cap section 634Y are non-rotatably held on the toner container storage unit 70, the agitating member 33f receives driving force from the driving unit 91 and rotates together with the gear member 1042Y, and so the conveying member 1041Y connected with the agitating member 33f at the position of the connection section 1033f20 also rotates. Thus, the toner stored in a container body 1044Y is agitated by agitating force of the agitator member 1041Yc installed in the conveying member 1041Y, and the toner stored in the container body 1033Y is conveyed toward the cap section 1034Y by conveying force of the flexible agitating member 1041Yb installed in the conveying member 1041Y in the shaft direction.

The flexible agitating member 1041Yb of the conveying member 1041Y includes cutouts 1041Yb1 formed at a plurality of positions (in the present seventh embodiment, six positions) in the longitudinal direction. Thus, in

accompany with rotation of the conveying member 1041Y, the leading end of the flexible agitating member 1041Yb (the free end side that is not supported on the shaft section 1041Ya) comes in sliding contact with the inner
5 circumferential surface of the container body 1033Y, and the flexible agitating member 1041Yb rotates in the appropriately twisted and bent state, so that the toner stored in the container body 1033Y is agitated and conveyed toward the right side in Fig. 49 in the shaft direction.

10 As described above, even in the toner container 1032Y according to the present seventh embodiment, similarly to the above embodiments, the toner is discharged from the toner discharge opening W of the cap section 1034Y.

Here, the gear member 1042Y is rotatably attached to
15 the container body 1033Y.

In detail, a gear engaging section (a claw section snap fitted into) (not shown) formed in the gear member 1042Y is caught in a flange section (in which a protrusion 1033e which will be described later is formed) formed to
20 make one round around the outer circumferential surface of a bottle mouth section 1033a of the container body 1033Y, and so the gear member 1042Y is rotatably held on the container body 1033Y. Further, a gear section (a spur gear) is formed on the outer circumferential surface of the
25 gear member 1042Y, and when the toner container 1032Y is set to the apparatus body 100, the gear section meshes with the driving gear 81 of the apparatus body 100.

A seal material is disposed between the gear member 1042Y and the end surface of the bottle mouth section 1033a
30 so as to prevent the toner from leaking to the outside of the toner container 1032Y. The seal material is made of a foamed elastic material such as foamed polyurethane, formed in an annular shape to be bitten into the end surface of

the bottle mouth section 1033a, and adheres to the gear member 1042Y. When the gear member 1042Y is set to the container body 1033Y, the seal material is pressed against the opening end surface of the bottle mouth section 1033a, and so a sealing characteristic between both members 1033Y and 1042Y is secured.

The gear member 1042Y is not fixed to the cap section 1034Y but rotatably held on the claw section 34j of the cap section 634Y. A method of holding the gear member 1042Y on the cap section 634Y is similar to the method of holding the cap section 34Y on the bottle mouth section 33a of the container body 33Y described in the above embodiments. That is, the claw section 34j of the cap section 634Y is engaged with a flange-like engaged protruding section 1033j disposed to make one round around the outer circumference of the gear member 1042Y, and the gear member 1042Y is rotatably supported on the cap section 1034Y. Through the above described configuration, the container body 1033Y is connected with the cap section 634Y via the gear 1042Y. Further, in order to prevent the container body 1033Y from rotating on the cap section 634Y, the protrusion 1033e formed near the opening 1033e of the container body 1033Y is fitted into a notch groove 1034t formed on the side surface of the cap section 634Y to play a role of a rotation stopper.

Further, in the cap section 634Y, a cap seal made of a foamed elastic material adheres to a section where the end surface of the gear member 1042Y (the end surface at the side opposite to the container body 1033Y side) is pressed. Thus, the toner leak from between the gear member 1042Y and the cap section 634Y can be prevented.

The agitating member 33f is attached to the inner surface of the gear member 1042Y. Further, the shaft

section 1041Ya (the end section at one end side) of the conveying member 1041Y is connected to the connection section 1033f20 of the agitating member 33f as described above.

5 As described above, even in the present seventh embodiment, similarly to the above embodiments, the contact-type ID chip 535 (the information storage device) is held on the cap section 634Y to be movable on the virtual plane that is substantially orthogonal to the
10 movement direction in which the metallic pads 35a1, 35a2, and 35a3 (terminals) approach and come in contact with body side terminals 573e2. Thus, even when the contact-type ID chip 535 (the information storage device) is installed in the toner container 1032Y (the removable device) installed
15 removably on the image forming apparatus body 100, the contact failure caused by the positioning failure with the body side terminals 573e2 of the connector 573e of the image forming apparatus body 100 is difficult to occur.

 Further, in the present seventh embodiment, the cap
20 section 634Y described, for example, with reference to Figs. 42A and 42B in the sixth embodiment has been used as the cap section of the toner container, but as the cap section of the toner container in the present seventh embodiment, the cap section 734Y described with reference to Figs. 46A
25 and 46B in the sixth embodiment may be used, the cap section 834Y described with reference to Fig. 47C in the sixth embodiment may be used, or the cap section 934Y described with reference to Figs. 47A and 47B in the sixth embodiment may be used.

30 Further, even in the present seventh embodiment, similarly to the fifth and sixth embodiments, even when the contact-type ID chip 535 (the information storage device) is installed in the toner container (the removable device)

installed removably on the image forming apparatus body 100, since the earth terminal 535d engaged with the body side earth terminal 573e25 formed in the positioning pin 573e23 (the protruding section) of the connector 573e (the image forming apparatus body 100) is formed in one hole 535b21 formed in the substrate 535b of the ID chip 535, the ID chip 535 is difficult to be electrically damaged.

Eighth Embodiment

10 An eighth embodiment of the present invention will be described in detail with reference to Figs. 50 to 51B.

Fig. 50 is an exploded perspective view illustrating an image forming apparatus 1100 according to the eighth embodiment. Fig. 51A is a cross-sectional view illustrating part of a toner cartridge 1106Y installed in the image forming apparatus, and Fig. 51B is a bottom view illustrating part of the toner cartridge 1106Y. In Figs. 50 to 51B, a toner discharge mechanism and a positioning mechanism for having the toner cartridge to operate are omitted.

The image forming apparatus 1100 according to the present eighth embodiment is different from those according to the above embodiments in which the toner container 532Y, 632Y, 732Y, 832Y, 932Y, or 1032Y in which the ID chip 535 is installed is mounted on the apparatus body 100 in the horizontal direction, where the longitudinal direction is the mounting direction in that the toner cartridge 1106Y in which the ID chip 535 is mounted on the apparatus body 1100 from above.

30 Referring to Fig. 50, the image forming apparatus 1100 according to the present eighth embodiment is configured so that toner cartridges 1106Y, 1106M, 1106C, and 1106K as four removable devices are attached or detached from above.

100

Fig. 50 illustrates the state in which the three toner cartridges 1106M, 1106C, and 1106K except the yellow toner cartridge 1106Y have been mounted on the apparatus body 1100.

5 The toner cartridges 1106Y, 1106M, 1106C, and 1106K are attached to or detached from an installation section of the apparatus body 1100 in the state in which a body cover 1110 (a body door) is opened as illustrated in Fig. 50.

 Meanwhile, the toner cartridges 1106Y, 1106M, 1106C,
10 and 1106K include an opening with a shutter that is disposed at the position of the lower side facing the developing device and store toner of corresponding color (one-component developer) thereinside. Referring to Figs. 51A and 51B, on the lower surfaces of the end sections of
15 the toner cartridges 1106Y, 1106M, 1106C, and 1106K in the longitudinal direction, the ID chip 535 (the information storage device) is movably held by a holding member 1134k in the horizontal plane direction (the paper surface direction of Fig. 51B).

20 The holding member 1134k is screw-coupled to the toner cartridge 1106Y to come in contact with part of the substrate 535b of the ID chip 535 in the state in which the metallic pads 35a1, 35a2, and 35a3, the positioning hole 535b21 (the earth terminal 535d), and the like of the ID
25 chip 535 that is the same as that in the fifth embodiment are exposed. In detail, the hole of the holding member 1134k is combined with a boss section 1181 formed in the end section of the toner cartridge 1106Y, a screw 1180 is screwed into a screw hole formed at the opposite side with
30 the ID chip 535 interposed between the boss section 1181 of the toner cartridge 1106Y and the hole formed in the holding member 1134k, and the holding member 1134k is fixed to the toner cartridge 1106Y. Thus, the ID chip 535 does

101

not fall from the toner cartridge 1106Y and is held to be movable in the horizontal plane. Referring to Fig. 50, in accompany with the mounting operation of the toner cartridge 1106Y from above on the apparatus body 1100, the positioning pin 573e23 (the body side earth terminal 573e25) of the connector 573e installed in the installation section of the apparatus body 1100 is fitted into the positioning hole 535b21 (the earth terminal 535d) of the ID chip 535. Thereafter, the body side terminal 73e2 of the connector 573e comes in contact with the metallic pads 35a1, 35a2, and 35a3 of the ID chip 535, and electrical contact between the connector 573e and the ID chip 535 is completed. In this case, since the ID chip 535 in the toner cartridge 1106Y is held to be movable in the horizontal plane, similarly to the above embodiments, the contact failure caused by the positioning failure with the body side terminals 73e2 and 573e25 of the connector 573e of the apparatus body 1100 is difficult to occur.

As described above, in the present eighth embodiment, the contact-type ID chip 535 (the information storage device) is held on the toner cartridge 1106Y to be movable on the virtual plane that is substantially orthogonal to the movement direction in which the metallic pads 35a1, 35a2, and 35a3 (terminals) approach and come in contact with body side terminals 573e2. Thus, even when the contact-type ID chip 535 (the information storage device) is installed in the toner cartridge 1106Y (the removable device) installed removably on the image forming apparatus body 1100, the contact failure caused by the positioning failure with the body side terminals 73e2 of the connector 573e of the image forming apparatus body 1100 is difficult to occur.

Further, even in the present eighth embodiment,

similarly to the fifth to seventh embodiments, even when the contact-type ID chip 535 (the information storage device) is installed in the toner cartridge 1106Y (the removable device) installed removably on the image forming apparatus body 1100, since the earth terminal 535d engaged with the body side earth terminal 573e25 formed in the positioning pin 573e23 (the protruding section) of the connector 573e (the image forming apparatus body 1100) is formed in one hole 535b21 formed in the substrate 535b of the ID chip 535, the ID chip 535 is difficult to be electrically damaged.

Ninth Embodiment

A ninth embodiment of the present invention will be described in detail with reference to Figs. 52 and 53.

Fig. 52 is a perspective view illustrating an image forming apparatus according to the ninth embodiment and is a view corresponding to Fig. 50 in the eighth embodiment. Fig. 53 is a schematic view illustrating a state in which the connector 573e is connected to the ID chip 535 in accompany with a closing operation of a body cover 1210 of an apparatus body 1200.

The image forming apparatus 1200 according to the present ninth embodiment is different from those according to the eighth embodiment in that the ID chip 535 is installed on an upper surface of a process cartridge 1206Y rather than the toner cartridge, and the connector 573e is installed in a body cover 1210 of the apparatus body 1200.

Referring to Fig. 52, the image forming apparatus 1200 according to the present ninth embodiment is configured so that process cartridges 1206Y, 1206M, 1206C, and 1206K as four removable devices are attached or detached from above. Fig. 52 illustrates the state in which the three process

cartridges 1206M, 1206C, and 1206K except the yellow process cartridge 1206Y have been mounted on the apparatus body 1200.

The process cartridges 1206Y, 1206M, 1206C, and 1206K
5 are attached to or detached from an installation section of the apparatus body 1200 in the state in which the body cover 1210 (the body door) is opened as illustrated in Fig. 52. Here, in the present ninth embodiment, in the body cover 1210, LED units 1207Y, 1207M, 1207C, and 1207K for
10 performing an exposure process are installed at the positions corresponding to the four process cartridges 1206Y, 1206M, 1206C, and 1206K, respectively (in Fig. 52, the two LED units 1207Y and 1207M are omitted). Referring to Fig. 53, when the body cover 1210 is closed, the LED
15 unit 1207Y moves to face the positioning of the photosensitive drum 1201Y for an electrostatic latent image in the process cartridge 1206Y.

Meanwhile, in each of the process cartridges 1206Y, 1206M, 1206C, and 1206K, the photosensitive drum, the
20 charging unit, the developing unit, and the cleaning unit are integrally formed, and toner of corresponding color (one component developer) is stored inside the developing unit. Referring to Fig. 52, on the upper surfaces of the end sections of the process cartridges 1206Y, 1206M, 1206C,
25 and 1206K in the longitudinal direction, the ID chip 535 (the information storage device) is held by the holding member (not shown) (or the face plate) to be movable in the horizontal plane direction (the vertical direction and the left-right direction in the paper plane of Fig. 53).

30 The holding member is screw-coupled to an outer cover of the process cartridge 1206Y to come in contact with part of the substrate 535b of the ID chip 535 in the state in which the metallic pads 35a1, 35a2, and 35a3, the

positioning hole 535b21 (the earth terminal 535d), and the like of the ID chip 535 that is formed similarly to that in the fifth embodiment are exposed. Thus, the ID chip 535 does not fall from the process cartridge 1206Y and is held to be movable in the horizontal plane. Referring to Fig. 52, in accompany with the mounting operation of the process cartridge 1206Y from above on the apparatus body 1200 (the mounting operation in accompany with the closing operation of the body cover 1210), the positioning pin 573e23 (the body side earth terminal 573e25) of the connector 573e installed in the body cover 1210 is fitted into the positioning hole 535b21 (the earth terminal 535d) of the ID chip 535. Thereafter, the body side terminal 73e2 of the connector 573e comes in contact with the metallic pads 35a1, 35a2, and 35a3 of the ID chip 535, and electrical contact between the connector 573e and the ID chip 535 is completed. In this case, since the ID chip 535 in the process cartridge 1206Y is held to be movable in the horizontal plane, similarly to the above embodiments, the contact failure caused by the positioning failure with the body side terminals 573e2 and 573e25 of the connector 573e of the apparatus body 1200 is difficult to occur.

Further, in the present ninth embodiment, referring to Fig. 53, the LED unit 1207Y (having an end section in which the connector 573e is installed) is installed to be rotatable (swingable) on the body cover 1210 clockwise or counterclockwise in Fig. 53 via a support arm 1211. The LED unit 1207Y is urged by a compression spring 1212 installed inside the support arm 1211. When the body cover 1210 is closed to mount the four LED units on the process cartridges by the swing function and the urging force against the process cartridge side, as illustrated in Fig. 53, the LED unit 1207Y shakes the neck along the wall

105

surface of the process cartridge 1206Y and is guided to a predetermined position. At the same time, the connector 573e also moves to approach the ID chip 535 and is positioned similarly to the fifth to eighth embodiments.

5 Thus, due to the urging force of the compression spring 1212, the connector 573e comes in contact with the ID chip 535 of the process cartridge 1206Y mounted on the installation section of the apparatus body 1200 with appropriate force.

10 As described above, in the present ninth embodiment, the contact-type ID chip 535 (the information storage device) is held on the process cartridge 1206Y to be movable on the virtual plane that is substantially orthogonal to the movement direction in which the metallic
15 pads 35a1, 35a2, and 35a3 (terminals) approach and come in contact with body side terminals 573e2. Thus, even when the contact-type ID chip 535 (the information storage device) is installed in the process cartridge 1206Y (the removable device) installed removably on the image forming
20 apparatus body 1200, the contact failure caused by the positioning failure with the body side terminals 573e2 of the connector 573e of the image forming apparatus body 1200 is difficult to occur.

Further, in the present ninth embodiment, even when
25 the contact-type ID chip 535 (the information storage device) is installed in the process cartridge 1206Y (the removable device) installed removably on the image forming apparatus body 1200, since the earth terminal 535d engaged with the body side earth terminal 573e25 formed in the
30 positioning pin 573e23 (the protruding section) of the connector 573e (the image forming apparatus body 1200) is formed in one hole 535b21 formed in the substrate 535b of the ID chip 535, the ID chip 535 is difficult to be

electrically damaged.

Tenth Embodiment

A tenth embodiment of the present invention will be
5 described in detail with reference to Figs. 54 and 55.

Fig. 54 is a perspective view illustrating an ink
cartridge 1306Y (a developer container) according to the
tenth embodiment. Fig. 55 is a front view illustrating an
inkjet printer 1300 as an image forming apparatus in which
10 ink cartridges 1306Y, 1306M, 1306C, and 1306K are installed.

The image forming apparatus 1300 according to the
present tenth embodiment is different from those according
to the above embodiments in that the ink cartridge 1306Y
having the side surface on which the ID chip 535 is
15 installed is mounted on the apparatus body 1300 from the
side.

Referring to Fig. 55, the image forming apparatus 1300
(the inkjet printer) according to the present tenth
embodiment includes a carriage 1301 that includes recording
20 heads 1301a and 1301b and moves in a direction of an
double-headed arrow, a guide lock 1302, a supply tube 1303
that supplies ink from the ink cartridges 1306Y, 1306M,
1306C, and 1306K of respective colors to a sub tank of the
carriage 1301, a conveying belt 1304 for conveying a
25 recording medium P in a direction of an arrow, and the like.
The ink cartridges 1306Y, 1306M, 1306C, and 1306K of
respective colors (the removable devices) are removably
installed on an installation section disposed in the end
section of the apparatus body 1300 (installation having the
30 vertical direction in Fig. 55 as the attaching/detaching
direction).

Further, a main configuration of an image forming
apparatus 300 is the same as stated in, for example,

Japanese Patent Application Laid-open No. 2010-234801 and has been well known, and thus a detailed description thereof will not be repeated.

Referring to Fig. 54, in the ink cartridge 1306Y (an ink bag 1307 is stored thereinside) as the removable device, the ID chip 535 (the information storage device) held on a holding member 1334k to be movable in the XZ direction is installed on a concave section 1308 formed on the side surface thereof.

10 The holding member 1334k and the ID chip 535 have the same configuration as those in the fifth embodiment. That is, the holding member 1334k is fitted into the concave section 1308 of the ink cartridge 1306Y in the state in which the metallic pads 35a1, 35a2, and 35a3, the
15 positioning holes 535b21 (the earth terminal 535d), and the like of the ID chip 535 are exposed. Thus, the ID chip 535 does not fall from the ink cartridge 1306Y and is held on the holding member 1334k to be movable in the XZ plane. Referring to Fig. 54, in accompany with the mounting
20 operation on the apparatus body 1300, the positioning pin 573e23 (the body side earth terminal 573e25) of the connector 573e installed in the apparatus body 1300 is fitted into the positioning hole 535b21 (the earth terminal 535d) of the ID chip 535. Thereafter, the body side
25 terminal 73e2 of the connector 573e comes in contact with the metallic pads 35a1, 35a2, and 35a3 of the ID chip 535, and electrical contact between the connector 573e and the ID chip 535 is completed. In this case, since the ID chip 535 in the ink cartridge 1306Y is held to be movable in the
30 XZ plane, similarly to the above embodiments, the contact failure caused by the positioning failure with the body side terminals 573e2 and 573e25 of the connector 573e of the apparatus body 1300 is difficult to occur.

As described above, in the present tenth embodiment, the contact-type ID chip 535 (the information storage device) is held on the ink cartridge 1306Y through the holding member 1334k to be movable on the virtual plane that is substantially orthogonal to the movement direction in which the metallic pads 35a1, 35a2, and 35a3 (terminals) approach and come in contact with body side terminals 573e2. Thus, even when the contact-type ID chip 535 (the information storage device) is installed in the ink cartridge 1306Y (the removable device) installed removably on the image forming apparatus body 1300, the contact failure caused by the positioning failure with the body side terminals 573e2 of the connector 573e of the image forming apparatus body 1300 is difficult to occur.

Further, even in the present tenth embodiment, even when the contact-type ID chip 535 (the information storage device) is installed in the ink cartridge 1306Y (the removable device) installed removably on the image forming apparatus body 1300, since the earth terminal 535d engaged with the body side earth terminal 573e25 formed in the positioning pin 573e23 (the protruding section) of the connector 573e (the image forming apparatus body 1300) is formed in one hole 535b21 formed in the substrate 535b of the ID chip 535, the ID chip 535 is difficult to be electrically damaged.

Eleventh Embodiment

An eleventh embodiment of the present invention will be described in detail with reference to Figs. 56 to 58.

Fig. 56 is a perspective view illustrating a connector 1473e of an image forming apparatus according to the tenth embodiment and is a view corresponding to Fig. 16 according to the first embodiment. Fig. 57 is a three-plane view

illustrating an ID chip 1435 as an information storage device that comes in contact with the connector 1473e of Fig. 56 and is a view corresponding to Fig. 29 according to the first embodiment. Fig. 58 is a three-plane view
5 illustrating an ID chip 1535 as an information storage device of another form and is a view corresponding to Fig. 35 according to the fourth embodiment.

The eleventh embodiment is different from the first and fourth embodiments in that a body side earth terminal
10 1473e5 is installed in a positioning pin 1473e3 of the connector 1473e, and a metallic earth terminal 1435d or 1535d (an earth terminal) that comes in contact with the body side earth terminal 1473e5 is installed in the ID chip 1435 or 1535.

15 Referring to Fig. 56, in the image forming apparatus according to the present eleventh embodiment, similarly to the first embodiment, installed is the connector 1473e that includes a connector body 1473e1, four body side terminals 1473e2, two positioning pins 1473e3 (positioning protruding
20 sections), a snap fit 1473e4, and the like.

In the connector 1473e according to the present eleventh embodiment, the body side terminal 1473e5 (the earth terminal) is installed inside the positioning pin 1473e3 (a section that comes in contact with a notch 1435b1
25 of the ID chip 1435 or a hole 1535b11).

Meanwhile, referring to Fig. 57, in the ID chip 1435 (the substrate 1435b) according to the present eleventh embodiment, the metallic earth terminal 1435d (the earth terminal) is installed on the inner surface of the two
30 notches 1435b1 and around the two notches 1435b1.

Through the above described configuration, in the mounting operation of the toner container, the earth terminal 1435d of the ID chip 1435 comes in contact with

110

the body side earth terminal 1473e5 (for example, see Fig. 56) of the positioning pin 1473e3 (the connector 1473e), and then the fourth metallic pads 35a of the ID chip 1435 start to come in contact with the four body side terminals 1473e2 of the connector 1473e. That is, in the detaching operation of the toner container, contact between the four metallic pads 35a of the ID chip 1435 and the four body side terminals 1473e2 of the connector 1473e is released, and then the earth terminal 1435d of the ID chip 1435 is released from the contact state with (separated from) the body side earth terminal 1473e5 of the positioning pin 1473e3 (the connector 1473e). Specifically, the body side earth terminal 1473e5 in the connector 1473e has the contact start position closer to the ID chip 1435 side than the four body side terminals 1473e2.

Through the above described configuration, in the mounting operation of the toner container, the metallic pads 35a always start to be connected with the body side terminals 1473e2 in the state in which the ID chip 1435 is earthed, and in the detaching operation of the toner container, the metallic pads 35a always start to be separated from (released from the contact state with) the body side terminals 1473e2 in the state in which the ID chip 1435 is earthed. Thus, an electric circuit at the ID chip 1435 is prevented from being not earthed and so becoming an electrically floating state, and so the ID chip 1435 is difficult to be electrically damaged.

Further, similarly to a relation between the ID chip according to the first embodiment and the ID chip according to the fourth embodiment, the ID chip 1435 illustrated in Fig. 57 may be replaced with the ID chip 1535 illustrated in Fig. 58.

In detail, referring to Fig. 58, in the ID chip 1535,

111

a metallic earth terminal 1535d (an earth terminal) is installed on the inner surface of one positioning hole 1535b11 and around the positioning hole 1535b11.

Through the above described configuration, in the mounting operation of the toner container, the earth terminal 1535d of the ID chip 1535 comes in contact with the body side earth terminal 1473e5 (for example, see Fig. 56) of the positioning pin 1473e3 (the connector 1473e), and then the four metallic pads 35a of the ID chip 1535 start to come in contact with the four body side terminals 1473e2 of the connector 1473e. That is, in the detaching operation of the toner container, contact between the four metallic pads 35a of the ID chip 1535 and the four body side terminals 1473e2 of the connector 1473e is released, and then the earth terminal 1535d of the ID chip 1535 is released from the contact state with (separated from) the body side earth terminal 1473e5 of the positioning pin 1473e3 (the connector 1473e). Specifically, the body side earth terminal 1473e5 in the connector 1473e has the contact start position closer to the ID chip 1535 side than the four body side terminals 1473e2.

Through the above described configuration, in the mounting operation of the toner container, the metallic pads 35a always start to be connected with the body side terminals 1473e2 in the state in which the ID chip 1535 is earthed, and in the detaching operation of the toner container, the metallic pads 35a always start to be separated from (released from the contact state with) the body side terminals 1473e2 in the state in which the ID chip 1535 is earthed. Thus, an electric circuit at the ID chip 1535 is prevented from being not earthed and so becoming an electrically floating state, and so the ID chip 1535 is difficult to be electrically damaged.

As described above, even in the present eleventh embodiment, the contact-type ID chip 1435 or 1535 (the information storage device) is held on the holding member 34k (the holding section) to be movable on the virtual
5 plane that is substantially orthogonal to the movement direction in which the metallic pads 35a (terminals) approach and come in contact with the body side terminals 1473e2.

Thus, even when the contact-type ID chip 1435 or 1535
10 (the information storage device) is installed in the toner container (the removable device) installed removably on the image forming apparatus body, the contact failure caused by the positioning failure with the body side terminals 1473e2 of the connector 1473e of the image forming apparatus body
15 is difficult to occur.

As described above, in the present eleventh embodiment, even when the contact-type ID chip 1435 or 1535 (the information storage device) is installed in the toner container (the removable device) installed removably on the
20 image forming apparatus body 100, since the earth terminal 1435d or 1535d engaged with the body side earth terminal 1473e5 formed in the positioning pin 1473e3 (the protruding section) of the connector 1473e (the image forming apparatus body 100) is formed in the notch 1435b1 or the
25 hole 1535b11 formed in the substrate 1435b or 1535b of the ID chip 1435 or 1535, the ID chip 1435 or 1535 is difficult to be electrically damaged.

Twelfth Embodiment

30 A twelfth embodiment of the present invention will be described in detail with reference to Figs. 59 to 62.

Fig. 59 is a perspective view illustrating a toner container 1632Y as a removable device according to the

twelfth embodiment. The toner container 1632Y includes a container body 1633Y having the same configuration as the container body 33Y, a cap section 1634Y that covers a toner discharge opening (not shown) formed in the container body 1633Y from the outer side, an ID chip as an information storage device attached to the leading end of the cap section 1634Y, and a holding mechanism 1635 that holds the ID chip. For example, the ID chip 535 described in the fifth embodiment may be used as the ID chip.

10 The toner container 1632Y relates to a toner container attachable to and detachable from a toner feeding device of a toner suction conveying type disclosed in Japanese Patent No. 4396946 or U.S. patent No. 7,835,675. That is, except for the ID chip, the holding mechanism, and a communication method of the ID chip, the toner container and the toner feeding device disclosed in the relevant patent are employed. The relevant patent is referred to in connection with a positioning configuration, which allows attachment and detachment, disposed in both the toner container and 20 the feeding device, a configuration for driving the container body, and the like. The difference between the toner container of the present embodiment and the toner container of Japanese Patent No. 4396946 or U.S. patent No. 7,835,675 will be described later. The toner feeding device of the present embodiment is different from the toner feeding device of Japanese Patent No. 4396946 or U.S. patent No. 7,835,675 in that the former employs a contact type communication method, whereas the latter employs a non-contact type communication method (a so-called RFID 25 method). Thus, as the body side connector of the former, the connector 573e of Figs. 37, 38, and 45 described with reference to the fifth embodiment is disposed at a position facing the toner container cap end surface of the toner 30

feeding device of Japanese Patent No. 4396946 or U.S. patent No. 7,835,675.

As illustrated in Fig. 60, the positioning hole 535b21 described above is formed in the ID chip 535, and, for
5 example, the positioning pin 573e23 of the connector installed in the apparatus body described above is inserted into the positioning hole 535b21.

The holding mechanism 1635 includes a holding section 1635A that holds the ID chip 535 in a movable manner in the
10 XZ direction and a holding cover 1635B as a cover member that is removably fitted into the holding section 1635A.

As illustrated in Fig. 61, the holding section 1635A includes a concave section 1635Aa formed on an ID chip mounting surface 1634Ya that is vertically flat and formed
15 at the leading end of the cap section 1634Y, a pedestal section 1635q, formed in the concave section 1635Aa, in which the ID chip 535 is installed, and an ID chip installation wall section 1635Ab of a substantially frame shape formed to surround the concave section 1635Aa and the
20 pedestal section 1635q from the outer side. The ID chip installation wall section 1635Ab is formed to protrude outward from the ID chip mounting surface 1634Ya further than the pedestal section 1635q. The ID chip installation wall section 1635Ab has a size capable of storing the ID
25 chip 535 having an outward rectangular form and holds the ID chip 535 in a movable manner in the XZ direction when the ID chip 535 is placed. That is, the ID chip 535 is installed in the pedestal section 1635q but not fixed to the cap section 1634Y. When installed in the pedestal
30 section 1635q, the ID chip 535 is installed with a clearance with the ID chip installation wall section 1635Ab that is formed to surround the ID chip 535 from the outer side.

On the ID chip mounting surfaces 1634Ya, positioning bosses 1615a and 1615b for mounting the holding cover 1635B are formed to protrude from the ID chip mounting surface 1634Ya. The positioning bosses 1615a and 1615b are
5 integrally formed with the cap section 1634Y by resin.

The holding cover 1635B is mounted on and fixed to the holding section 1635A by a melt-fixing method (for example, heat calking) described below, with the ID chip being disposed in the holding section 1635A. A central section
10 of the holding cover 1635B is provided with an opening 1635Bc that allows a contact point (not shown) and the positioning hole 535b21 of the ID chip 535 to be exposed to the outside and allows the connector terminal (not shown) of the connector and the positioning pin 573e23 to be
15 inserted therethrough. The holding cover 1635B is configured to sandwich the IC chip 535 set inside the ID chip installation wall section 1635Ab together with the ID chip installation wall section 1635Ab so that the ID chip 535 does not separate. Above and below the opening 1635Bc
20 of the holding cover 1635B, mounting holes 1635Ba and 1635Bb are formed at positions corresponding to the positioning bosses 1615a and 1615b.

In this configuration, when mounting the ID chip 535 on the cap section 1634Y, the back surface of the ID chip
25 535 comes in contact with the pedestal section 1635q so that its position in a depth direction is determined. Along this, up, down, left and right positioning is done by the surrounding thanks to the ID chip installation wall section 1635Ab. The holding cover 1635B is superimposed on
30 the ID chip installation wall section 1635Ab in a direction facing the ID chip installation wall section 1635Ab, and the positioning bosses 1615a and 1615b are inserted into the mounting holes 1635Ba and 1635Bb. Thus, the ID chip

535 is positioned in a state covered by the holding cover 1635B, and mounted and held on the cap section 1634Y. In this state, the ID chip 535 is installed on the ID chip mounting surface 1634Ya of the cap section 1634Y but is not
5 fixed directly to the cap section 1634Y. That is, the ID chip 535 is mounted to the cap section 1634Y through the ID chip installation wall section 1635Ab formed on the ID chip mounting surface 1634Ya.

The present embodiment features a fixing method
10 between the holding cover 1635B and the cap section 1634Y. In the present embodiment, a melt-fixing method is employed as a fixing method of the holding cover 1635B and the cap section 1634Y.

Since the holding cover 1635B is held such that the
15 positioning bosses 1615a and 1615b formed at the cap section 1634Y side are inserted into the mounting holes 1635Ba and 1635Bb as described above, in the present embodiment, as illustrated in Fig. 62, the holding cover 1635B is fixed to the cap section 1634Y by heat calking.
20 In Fig. 62, a reference numeral 1640 represents a calking section (a fixing section). For example, the positioning bosses 1615a and 1615b illustrated in Fig. 61 have the size protruding from the mounting holes 1635Ba and 1635Bb. The positioning bosses 1615a and 1615b are heated by a heating
25 member such as a heatable iron, and the calking section 1640 is formed by crushing and thermally deforming the bosses while melting them by heat. Accordingly, the holding cover 1635B can be fastened to and fixed to the cap section 1634Y.

30 In the present embodiment, as the fixing method between the holding cover 1635B and the cap section 1634Y, fixing by heat calking has been described, but as the fixing method between the holding cover 1635B and the cap

section 1634Y, another melt-fixing method such as ultrasonic welding may be used, and a resin melting method not limited to the present embodiment.

5 Thirteenth Embodiment

A thirteenth embodiment will be described in detail with reference to Figs. 63 and 64.

In the present embodiment, the holding cover 1635B is not fixed by a process such as heat calking but fixed by a fastening method using a fastening member. The remaining sections of the toner container and the form of the toner feeding device are the same as in the twelfth embodiment. In present embodiment, the holding cover 1635B is fixed to the cap section 1634Y such that fastening members 1650a and 1650b are inserted into the mounting holes 1635Ba and 1635Bb formed in the holding cover 1635B that allows the positioning bosses 1615a and 1615b to be inserted into and screwed into the ID chip mounting surface 1634Ya. For example, when the screw fixing is performed using a self-tap screw that creates a screw groove in an opposing hole at the same time when it is screwed into the opposing hole as the fastening members 1650a and 1650b, all you have to do is to form a tubular pilot hole (corresponding to 1651a and 1651b of Fig. 64) in the ID chip mounting surface 1634Ya.

As another embodiment, for example, there is a case in which the holding cover 1635B is fixed to the cap 1634Y without the ID chip being held therein and then the resultant product is shipped from a toner container manufacturing factory, and then in another factory, the holding cover 1635B is removed, the ID chip is set inside, and the holding cover 1635B is fixed again to the cap 1634Y, or there is a case of recycling the used toner container.

In this case, if attachment/detachment of the holding cover 1635B is repeated within a certain range, the above described tubular pilot hole is preferable. However, if five or six times, or more times of attachments/detachments are expected and the stability of fastening force on each occasion should be considered, it is preferable that screw holes 1651a and 1651b are formed in advance in the ID chip mounting surface 1634Ya, and fixing is performed by screwing screws into the screw holes 1651a and 1651b through the mounting holes 1635Ba and 1635Bb so as to correspond to the pitch of the screw holes 1651a and 1651b as fastening members 1650Ba and 1650Bb, as illustrated in Fig. 64. In the present embodiment, the fastening members 1650a and 1650b are fixed at two positions below and above the holding cover 1635B but may be fixed at one position, or more positions than the above. Further, the fastening members 1650a and 1650b may be mounted at the left and right sides rather than the upper and lower sides of the holding cover 1635B, and are not limited in terms of number and position to the present embodiment.

Fourteenth Embodiment

A fourteenth embodiment of the present invention will be described in detail with reference to Figs. 65 and 66.

In the present embodiment, the holding cover is characterized in that it is not fastened to and fixed to the cap section 1634Y by the process such as heat calking or the fastening member but fixed by a fitting method using a claw member. The remaining sections of the toner container and the form of the toner feeding device are the same as those in the twelfth embodiment.

A holding cover 1635C according to the present embodiment basically has the same function as the holding

cover 1635B. Specifically, the mounting holes 1635Ba and 1635Bb are eliminated from the holding cover 1635B, and instead hook sections 1636a and 1636b that pass through up to an opening 1635Cc formed at a central section are formed in an upper section 1635Ca and a lower section 1635Cb. Like the opening 1635Bc, the opening 1635Cc allows the contact point (not shown) and the positioning hole 535b21 of the ID chip 535 to be exposed to the outside and allows the connector terminal (not shown) of the connector and the positioning pin 573e23 to be pass therethrough.

In the present embodiment, the cap section 1634Y, as illustrated in Fig. 66, is provided with claw sections 1637a and 1637b as engaging sections that enter the inside of the hook sections 1636a and 1636b and engage with the hook sections 1636a and 1636b. In the present embodiment, the claw sections 1637a and 1637b are formed to be disposed respectively on the upper section and the lower section of the ID chip installation wall section 1635Ab covered with the holding cover 1635C. The claw sections 1637a and 1637b have inclined surfaces 1637a1 and 1637b1 formed at the insertion side and are configured so as to guide the holding cover 1635C to the tops of the claw sections 1637a when the holding cover 1635C is aligned and mounted.

With this configuration, when the ID chip 535 is set in the ID chip installation wall section 1635Ab and the holding cover 1635C is moved toward the ID chip installation wall section 1635Ab so as to be superimposed on the ID chip installation wall section 1635Ab, the claw section 1637a formed in the ID chip installation wall section 1635Ab that becomes the cap section 1634Y side enters the inside of the hook sections 1636a and 1636b formed in the holding cover 1635C, and the holding cover 1635C can be fixed to the cap section 1634Y by fitting

between both sides.

In the present embodiment, the hook sections 1636a and 1636b are fitted into the claw sections 1637a and 1637b at the two positions of the upper and lower sections of the holding cover 1635C, but they may be fitted at the left and right sections or at the upper, lower, left, and right sections of the holding cover 1635C instead of the upper and lower sections. The fitting position and number are not limited to the present embodiment.

In the thirteenth and fourteenth embodiments, the method of fastening or fitting the holding cover 1635C to be attached to or detached from the cap section 1634Y has been described. However, as another fixing method, for example, the cover member may be fixed to the ID chip installation wall section 1635Ab by an adhesive. In this case, the cover member preferably has adhesive force sufficient not to fall off at the time of detachment of the toner container 1632Y from the apparatus body, and a kind of an adhesive and an adhesion area are not particularly limited.

In the twelfth to fourteenth embodiments, even in any embodiment, even when the ID chip 535 that is the contact-type information storage device is installed in the toner container 1632Y, the contact failure caused by the unsatisfactory positioning relative the terminal of the connector of the apparatus body is difficult to occur.

Fifteenth Embodiment

In the toner container according to any one of the first to seventh embodiments, part of the inventive (the shutter mechanism) for solving the above described third problem will be described in detail once again as a fifteenth embodiment.

The stopper release urging section 72b in Fig. 5 will be described with reference to Fig. 18 and the subsequent figures. The stopper release urging section 72b is a section used to open the toner discharge opening W by
5 displacing the shutter 34d disposed in the cap section 34Y from the closed state to the open state in conjunction with the insertion (mounting) operation of the developer storage containers 32Y, 32M, 32C, and 32K. The stopper release urging section 72b is configured with a trapezoidal rib
10 that protrudes upward from the upper surface of the bottle receiving surface 72a toward the shutter.

Meanwhile, Figs. 18 and 20 illustrate the entire configuration of the developer storage containers 32Y, 32M, 32C, and 32K (see Fig. 18) and the details of the cap
15 section 34Y disposed in the container (see Fig. 20).

In Fig. 18, the developer storage container 32Y mainly includes the container body 33Y (the bottle body) and the cap section 34Y (the bottle cap) disposed at the head thereof. Further, the ID chip 35 as the information
20 storage device or the like is detachably installed in the cap section 34Y of the developer storage container 32Y.

Among the sections described above, the configuration illustrated in Fig. 20 is used at the position where the ID chip 35 is installed so that the ID chip 35 can be mounted.

25 On the leading end surface of the cap section 34Y, as illustrated in Fig. 20, the first and second positioning holes 34a and 34b that can be engaged with the first and second positioning pins (not shown) disposed in the cap receiving section 73 are disposed at the two positions in
30 the longitudinal direction (the vertical direction).

Between the first and second positioning holes 34a and 34b, formed is a rectangular concave section 35a that has a shape connectable with the connector disposed at the

developer storage container storage unit 70 (see Fig. 5) and extends in the vertical direction as illustrated in Figs. 67 and 68. Inside the concave section, as illustrated in Fig. 67, the holding member 34k to which the ID chip is attachable is mounted. A reference numeral 33f illustrated in Fig. 67 represents the agitating member having an agitating section positioned inside the cap, and the agitating member rotates in conjunction with the gear 33c which will be described later.

10 The mounting position of the holding member 34k is vertically higher than the position of the toner discharge opening W that is opened or closed by the shutter 34d which will be described later with reference to Figs. 70A to 70C (in Fig. 67, for convenience, the position having the height H between a bottom section 35a1 of the concave section 35a and the toner discharge opening W), and thus the holding member 34k is separated from the toner discharge opening W. Further, a convex wall is disposed at a circumferential edge of the rectangular concave section.

20 Thus, obtained is the state in which part of the concave section 35a is difficult to be superimposed on part of the toner discharge opening W in the transverse direction. That is, the bottom section 35a1 of the concave section 35a does not get close to the toner discharge opening W. Thus, part of the toner discharge opening W is prevented from being filled with the bottom section 35a1, and discharging of the toner is not inhibited. Further, even when the toner leaks and is scattered from the toner discharge opening W of the developer storage container 32Y to the outside, the scattered toner does not reach the connector against its own weight, and the scattered toner is blocked by the convex wall. Thus, the contact failure caused when the toner sticks to the connector can be prevented, and the

30

occurrence of the communication failure can be prevented. The concave section 35a is disposed at the first positioning hole 34a side.

Meanwhile, in the head section of the container body 33Y illustrated in Fig. 20, as illustrated in Fig. 67, the gear 33c integrally rotating together with the container body 33Y and the opening A are disposed at one end side in the longitudinal direction (the left-right direction in Fig. 67).

The opening A is disposed on the head section positioned at the front side when the container body 33Y is mounted and allows the toner stored in the container body 33Y to be discharged toward a hollow space section B inside the cap section 34Y.

Further, as the toner is consumed at the image forming apparatus body side, toner conveyance (rotation driving of the container body 33Y) from the inside of the container body 33Y to the hollow space B inside the cap section 34Y is appropriately performed.

Next, the configuration of the cap section 34Y of the developer storage container 32Y will be described below with reference to Figs. 20, 67, and 68.

In the cap section 34Y of the developer storage container 32Y, installed are the ID chip 35 (the information storage device), the shutter member 34d, and the shutter seal 36.

As illustrated in Fig. 68, the cap section 34Y has a structure in which roughly a cylindrical body in which the outer diameter and the inner diameter decreases from the container body 33Y side toward the shutter member 34d side in three stages (large, medium, and small) is combined with a box section, disposed at the bottom, in which the width in the horizontal direction decreases in two stages (wide

width and narrow width). The cap section 34Y includes an insertion section including the large diameter section and the medium diameter section of the cylindrical section and the wide width box section 34n.

5 In the large diameter section of the cap section 34Y, a cut-out hole 34P0 formed such that part of the outer circumference is removed is disposed, and as illustrated in Fig. 68, part of the teeth of the gear 33c is exposed to the outside.

10 In the insertion section, in Fig. 68, the cut-out hole 34P0 and a circumferential section 34P1 adjacent thereto in the shaft direction have the outer diameter smaller than a circumferential section 34P2 that is not adjacent to the cut-out hole 34P0 in the circumferential direction. In Fig.
15 68, for convenience, D1 and D2 representing the outer diameters are attached to the reference numerals of the circumferential sections 34P1 and 34P2, and the relation between the outer diameters is $D1 < D2$.

As described above, the circumferential section
20 adjacent to the cut-out hole 34P0 of the insertion section in the shaft direction has the outer diameter smaller than other sections, and thus the teeth surface of the gear engaged with the gear 33c, which is exposed to the outside through the cut-out hole 34P0, in the shaft direction
25 becomes difficult to interfere with the insertion section outer circumference. As a result, the engagement operation of the gear 33c with the gear moving in the shaft direction can be smoothly performed without being disturbed by part of the insertion section.

30 Further, in Fig. 68 and Fig. 81 illustrating a seventeenth embodiment, which will be described later, that is a modification in which a main part is shared with the configuration illustrated in Fig. 68, a reference numeral

34YG0 represents a retaining section configured by a step section at the leading end side of a guide rail 34YG. The retaining section 34YG0 is a section that is hit by a slide protruding section 34dlc (see Figs. 70A to 70C) disposed at the shutter 34d side so that the shutter 34d cannot move forward further, thereby retaining the shutter 34d as will be described later.

As illustrated in detail in Fig. 81, an upper rail rib 34SG that is at a predetermined distance from the guide rail 34YG and parallel to the guide rail 34YG is disposed above the guide rail 34YG. The upper rail rib 34SG prevents a sandwiching section of a body side shutter closing mechanism 73d (see Fig. 72) illustrated in Fig. 72 and drawings subsequent thereto from entering between the cylindrical circumferential surface of the cap 34Y and the guide rail 34YG.

On the upper surface of the guide rail 34YG, a shutter protruding section 34YG2 including a protruding section is disposed at the position that the shutter 34d reaches before hitting the retaining section 34YG0 (see Fig. 81). The shutter protruding section 34YG2 is used as a section for restricting movement of the shutter 34d when the shutter 34d is in the closed state.

An insertion/removal (attachment/detachment) operation of the developer storage container 33Y can be performed by the user gripping the gripping section disposed on the rear side end section of the container body 33Y in the insertion (mounting) direction as indicated by a reference numeral 33d in Fig. 18.

A narrow width box section 34Y1 is formed in the small diameter cylindrical section of the cap section 34Y, and inside the box section 34Y1, as illustrated in Fig. 69B, the toner discharge opening W for discharging (falling by

its own weight) the toner, discharged from the opening A of the container body 33Y, to the lower side in vertical direction, that is, the container outside is disposed to communicate with the hollow space section B illustrated in
5 Fig. 67.

As illustrated in Fig. 69B, the toner discharge opening W is formed in a hexagonal shape that is one of polygonal shapes and has a predetermined flow passage area and communicates the lower side circumferential surface of
10 the space B inside the small diameter cylindrical section with the toner discharge opening W (discharge opening). Thus, the toner discharged to the space B inside the small diameter cylindrical section of the cap section 34Y from the opening A of the container body 33Y falls from the
15 toner discharge opening W of the hexagonal cylindrical shape by its own weight and then is smoothly discharged to the container outside (the toner tank section 61Y).

In the toner discharge opening W, as illustrated in Fig. 67 and 69B, a rib W1 protruding toward a seal material
20 36 of the shutter 34d which will be described later is formed along the opening circumferential edge. The rib W1 has a function of folding and riding up the end section of the seal material 36 which will be described later, a function of improving adhesion of the seal material 36 by
25 coming in press contact with a section other than the end section, and a function of damming the toner that is about to leak from the toner discharge opening W.

In Figs. 69A and 69B, in the bottom section of the narrow width box section 34Y1 disposed in the lower section
30 of the cap section 34Y, the shutter 34d for performing opening and closing of the toner discharge opening W in conjunction with the attaching/detaching operation of the developer storage container 32Y on the developer storage

container storage unit 70 is held to be slidably movable.

The shutter 34d is a feature section of the present invention and has the following configuration which will be described with reference to Figs. 70A and 70B. In addition,
5 Fig. 70A is a perspective view in which the shutter 34d is viewed from the bottom surface side, and Fig. 70B is a perspective view in which the shutter 34d is viewed from the top surface.

The shutter 34d is made of a resin material such as
10 polystyrene and mainly includes a plate-like main shutter section 34d1 and a shutter deforming section 34d2 that protrudes the main shutter section 34d1, is thinner in thickness than the main shutter section 34d1, and has elasticity.

15 In the main shutter section 34d1, vertical wall 34d1a standing at both side end sections of a plate section and a pair of shutter sliders 34d12 having a protruding objects protruding from the vertical walls are disposed.

The vertical walls 34d1a includes a pair of slide
20 protruding sections 34d1c that are disposed at the inner side surfaces of the vertical walls to protrude facing each other and L-shaped engaged protruding sections 34d1b that are disposed on the outer side surfaces at the side opposite to the slide protruding sections 34d1c.

25 The engaged protruding section 34d1b is shaped such that a plate section extending in the shutter moving direction is present on the upper surface, and a protrusion 34d1b1 engaged with a sandwiching section which will be described later extends downward from a section positioned
30 in the front side of the plate section in an insertion direction of the developer storage container.

The shutter slider 34d12 includes a pair of prismatic sections that is disposed to protrude from the surface of

the same side as the engaged protruding section 34dlb of the vertical wall 34dla and extends toward the rear side in the direction of closing the toner discharge opening W of the shutter 34d indicated by an arrow.

5 In the present embodiment, as illustrated in Fig. 70B, the protrusion 34dlb1 disposed in the engaged protruding section 34dlb is disposed at the position offset from the front end surface of the main shutter section 34d1 (the position where a section corresponding to a distance
10 indicated by a symbol S1 in Fig. 70B is removed). As will be described in Fig. 72 and drawings subsequent thereto, the protrusion 34dlb1 is used as a section for preventing interference when one of sandwiching sections 73d2 (see Fig. 72) disposed in a body side shutter closing mechanism 73d
15 starts to turn.

 In the shutter 34d, the shutter deforming section 34d2 is configured in a cantilever shape, and an inner side angular section of a base station connected to the main shutter section 34d1 is formed of an arc-like curvature-
20 shaped section (a shape indicated by symbol R in Figs. 70A and 70B) and functions to avoid stress concentration when deflectively deformed.

 Further, the shutter deforming section 34d2 is formed such that part of the base end positioned at the main
25 shutter section 34d1 side becomes a horizontal surface (a section indicated by symbol S2 in Fig. 70C), and the remaining section is inclined from the leading end of the horizontal surface as illustrated in Fig. 70C in which the engaged protruding section 34dlb is omitted. In this
30 configuration, unlike when the inclined base end of the shutter deforming section 34d2 is directly connected with the main shutter section 34d1, it is possible to avoid stress from being concentrated at the connection position

between the inclined base end of the shutter deforming section 34d2 and the main shutter section 34d1 when the base end side of the shutter deforming section 34d2 oscillates.

5 The shutter deforming section 34d2 is configured with a cantilever shaped piece section (a section having the length indicated by symbol L in Fig. 70A) extending to the rear side in the insertion direction of the developer storage container as the base end of the main shutter
10 section 34d1. The shutter deforming section 34d2 is inclined such that it goes downward from the base end side to the rear side in the insertion direction.

 The free ends of the shutter deforming section 34d2 are integrated by a connecting plate section 34d2a that
15 bridges them laterally. In the central section of the connecting plate section 34d2a in the bridging direction, a stopper release section 34d21 is disposed to face the stopper release urging section 72b (see Fig. 5) that is configured with a trapezoidal rib disposed at the cap
20 receiving section 73 side. On both sides in the bridging direction, as will be described later, disposed are stopper sections 34d22 for fixing the shutter 34d so as to prevent careless opening of the toner discharge opening W.

 The stopper release section 34d21 is formed to have a
25 triangular cross section. By running on the stopper release urging section 72b (see Fig. 5) disposed at the cap receiving section 73 side, the stopper release section 34d21 changes the shutter deforming section 34d2 from an inclined state to a horizontal state, so that engagement
30 between the stopper section 34d22 and an engaging end surface 34n1 (see Figs. 69A and 69B) positioned in the wide width box section 34n that is present on the bottom of the cap section 34Y can be released. Thus, the shutter 34d can

move in the direction of opening or closing the toner discharge opening W.

The engaging end surface 34n1 positioned in the wide width box section 34n is disposed as a section for
5 restricting movement of the shutter 34d in the direction of opening the toner discharge opening W in the state in which the toner discharge opening W is closed.

Figs. 71B and 71C are views for explaining the relation between the engaging end surface 34n1 and the
10 stopper section 34d22 at the shutter deforming section 34d2 side. At the time of closing of the toner discharge opening W illustrated in Fig. 71C, since the shutter deforming section 34d2 at the shutter 34d side in the inclined state as the initial state, the stopper section
15 34d22 positioned at the inclined free end faces the engaging end surface 34n1, and the shutter 34d cannot move independently. Thus, the state in which the toner discharge opening W is not carelessly opened is maintained.

Further, as illustrated in Figs. 69B and 71B, when the
20 shutter 34d has moved in the direction of opening the toner discharge opening W, the front end 34d1d of the main shutter section 34d1 in the moving direction comes in contact with the engaging end surface 34n1, and thus the moving position of the main shutter section 34d1 can be
25 specified. Fig. 71C illustrates the case in which the shutter 34d has moved in the direction of closing the toner discharge opening W. In this case, the free end section of the shutter deforming section 34d2 becomes inclined, and so the stopper section 34d22 positioned at the free end
30 section comes in face contact with the engaging end surface 34n1. Thus, movement of the shutter 34d is stopped unless the stopper release section 34d21 is pushed up.

The seal material 36 is composed of a rectangular

parallelepiped body attached to the main shutter section 34d1. As the seal material 36 hits against the rib W1 illustrated in Fig. 67, the end section is folded and rides up, and a section other than the end section comes into
5 press contact with the rib W1 and thus is deflectively deformed toward the toner discharge opening W in the fractional contact state. The seal material 36 is an elastic seal made of a flexible material. As the material, a high-density microcell urethane sheet is employed in view
10 of sliding property and elasticity of the surface.

The seal material 36 has the length (the length indicated by symbol L1 in Fig. 70A) at which the leading end in the direction of closing the toner discharge opening W by the shutter 34d protrudes to the outer side further
15 than the leading end of the main shutter section 34d1. The protruding leading end section is a section that easily rides up when hitting against the rib W1 disposed at the circumferential edge of the toner discharge opening W.

The shutter 34d is stored inside the wide width box
20 section 34n positioned in the lower portion of the large diameter cylindrical section of the cap section 34Y and slidably moves.

In the wide width box section 34n, among four wall surfaces disposed at the side surface, two wall surfaces
25 facing in the longitudinal direction (the shaft direction of the cap section cylinder) are opened. Particularly, since the wall surface is partially left on the corner at the bottom side, an opening extending in the horizontal direction is formed on most of the wall surface at the
30 toner discharge opening W side. The opening is formed such that two surfaces of the side surface and the bottom surface at the toner discharge opening W side in the longitudinal direction of the wide width box section 34n

are cut out.

Meanwhile, in Figs. 20, 68, 69A, 69B, and 71A to 71C, lateral protrusions 34c for restricting the posture of the cap section 34Y in the rotation direction in the image forming apparatus body 100 (the cap receiving section 73) are formed on both side sections of the cap section 34Y, respectively.

The lateral protrusions 34c are positioned on both sides in a right angle direction in the same plane as a column direction of the positioning holes 34a and 34b in the circumferential surface of the medium diameter cylindrical section, has a triangular shape in a planar view, and has the top section at the position away from the circumferential surface of the medium diameter cylindrical section from the head section of the cap section 34Y to the rear side.

In the inclined surface of the lateral protrusion 34c, a rising edge angle of an inclined piece positioned behind the top section is larger than a rising edge angle of an inclined piece positioned at the head section side of the cap section 34Y ahead of the top section.

The inclined piece at the head section is disposed at the cap receiving section 73 side and can move while contacting the lateral protrusions 34c with a thrusting member (not shown) that is subject to tucking behavior by urging of elastic force. That is, if a section having a small inclined angle, so-called inclined plane, faces the thrusting member when thrusting toward the thrusting member, the inclined plane can enter with respect to the thrusting member without any resistance. If the top section of the inclined plane goes beyond the thrusting member, the inclined surface at the rear side is engaged with the thrusting member, movement resistance from the thrusting

member abruptly decreases directly after going beyond the thrusting member, and a feeling of resistance when fitted into the thrusting member, so-called click feeling, is caused.

5 In the present embodiment, of the inclined pieces of the later protrusion, the angle of the inclined piece at the head section side is set to 30°, and the angle of the inclined piece at the rear side is set to 45°.

10 In Figs. 20, 68, 69A, 69B, and 71A to 71C, reference numerals 34g and 34h are convex sections that are disposed on both ends of the bottom section of the cap section 34Y and are for securing incompatibility of the developer storage container 32Y (the developer storage container).

15 The convex sections 34g and 34h are sections for judging whether or not the mounting operation of the developer storage container 32Y on the developer storage container storage unit 70 is correct. If a fitting state on a fitting section (not shown) disposed at the developer storage container storage unit 70 side is normal, the
20 developer storage container, in which toner of predetermined color is stored, specified at a predetermined position is mounted at that position, and it is judged that it has been correctly mounted. Thus, it is possible to prevent an erroneous operation, so-called erroneous setting,
25 in which color of toner stored in the developer storage container is not mounted in a predetermined mounting section.

30 Meanwhile, the shutter 34d can be maintained in the state in which the toner discharge opening W is closed by the body side shutter closing mechanism 73d illustrated in Figs. 72 to 75D. The body side shutter closing mechanism 73d is disposed to solve a problem in that the toner container 32Y is extracted from the apparatus body 100

while the toner discharge opening W is not completely closed, for example, at the time of replacement of the developer storage container.

In Fig. 72, the body side shutter closing mechanism
5 73d (a shutter sandwiching mechanism) is disposed at the bottom section inside the cap receiving section 73 and at the upstream side of the toner discharge opening W in the mounting direction of the developer storage container 32Y.

In Fig. 72, the body side shutter closing mechanism
10 73d is a pair of horseshoe shaped members disposed to face each other in the left-right direction of Fig. 72 and is configured to be rotatable on a support shaft 73d3 in which a torsion coil spring is installed.

The body side shutter closing mechanism 73d (the
15 shutter sandwiching mechanism) includes a first sandwiching section 73d1 formed on one end side and a second sandwiching section 73d2 formed on the other end side.

In the sandwiching sections, at the time of the opening/closing operation of the shutter 34d in the
20 developer storage container 32Y, the engaged protruding section 34dlb of the shutter 34d is sandwiched by the second sandwiching members 73d2, and a vertical surface (the surface where an outgoing line leading end section of symbol 34YG in Fig. 73 is positioned) of the guide rail
25 34YG (see Figs. 68, 69A, 69B, and 71A to 71C) of the cap section 34Y is sandwiched by the first sandwiching members 73d1 (the state illustrated in Fig. 73). At the time of the opening/closing operation of the shutter 34d, the postures of the shutter 34d of the cap receiving section 73
30 and the cap section 34Y are decided, and thus the opening/closing operation can be smoothly performed.

Figs. 72 to 74 are views illustrating an operation of the body side shutter closing mechanism 73d (the shutter

sandwiching mechanism) when opening or closing the shutter 34d.

At the time of the opening operation of the shutter 34d, as illustrated in Fig. 72, in accompany with the mounting operation of the developer storage container 32Y in a white arrow direction, the first sandwiching members 73d1 first come in contact with a leading end 34YG1 (see Figs. 68, 69A, 69B, and 71A to 71C) of the guide rail 34YG of the shutter 34d, and then, as will be described later, the second sandwiching members 73d2 come in contact with the protrusions 34dlb1 positioned in the engaged protruding sections 34dlb of the shutter 34d.

As illustrated in Fig. 73, when the mounting operation of the developer storage container 32Y proceeds in the white arrow direction, the body side shutter closing mechanism 73d (the shutter sandwiching mechanism) rotates on a support shaft section 73d3.

When the body side shutter closing mechanism 73d rotates, the first sandwiching members 73d1 sandwich the vertical surfaces (the surfaces where an outgoing line leading end section of symbol 34YG in Fig. 73 is positioned) of the guide rails 34YG of the cap section 34Y, and the second sandwiching members 73d2 sandwich the side wall surfaces by coming in face contact with the side wall surfaces of the main shutter section 34d1 where the base ends of the engaged protrusion 34dlb are positioned while being engaged with the protrusions 34dlb1 positioned in the engaged protruding section 34dlb of the shutter 34d.

Thereafter, even though not shown, the shutter 34d comes in contact with the wall section formed around the toner feeding opening at the cap receiving section 73 side and so stops movement in the mounting direction. Then, the vertical surface of the guide rail 34YG is sandwiched by

the first sandwiching sections 73d1, and movement of the shutter 34d in the cap receiving section 73 is restricted (the shutter 34d does not absolutely move in the longitudinal direction).

5 In the state in which movement of the shutter 34d is restricted, when the developer storage container 32Y moves in the mounting direction, the shutter 34d whose movement in the mounting direction is stopped moves in a direction relative to movement of the cap section 34Y in the mounting
10 direction. Further, when the cap section 34Y moves to the front side in the mounting direction further than the shutter 34d whose movement is stopped, the toner discharge opening W is opened as illustrated in Fig. 74.

 At this time, as illustrated in Fig. 74, the vertical
15 surfaces of the cap section 34Y are sandwiched by first sandwiching members 73d1, and the protrusions 34dlb1 positioned in the engaged protruding section 34dlb of the shutter 34d are engaged by second sandwiching members 73d2. Since the opening operation of the shutter 34d is performed
20 in the state in which the shutter 34d is sandwiched, the postures of the shutter 34d and the cap section 34Y in the cap receiving section 73 are decided, and thus the opening/closing operation can be smoothly performed.

 Meanwhile, when extracting (separating) the developer
25 storage container 32Y from the developer storage container storage unit 70 (the cap receiving section 73), the operation is performed in a procedure reverse to the mounting procedure. That is, the operation of the body side shutter closing mechanism 73d (the shutter sandwiching
30 mechanism) accompanying with the closing operation of the shutter 34d is performed in order of Figs. 74, 73, and 72.

 The seal state of the seal member 36 on the toner discharge opening W at the time of the opening/closing

operation of the shutter will be described in connection with the movement position of the shutter 34d with reference to Figs. 75A to 75D.

Fig. 75A illustrates the state in which the toner discharge opening W of the cap 34 is closed by the shutter 34d. In this state, since the developer storage container is not loaded on the cap receiving section 73, the shutter 34d closes the toner discharge opening W. Since the seal material 36 is in press contact with the rib W1 positioned at the circumferential edge of the toner discharge opening W, the state in which the shutter 34d is in close contact with the toner discharge opening W is maintained. A dotted line in Fig. 75A represents the state in which the stopper release section 34d21 of the shutter 34d is pushed up by the stopper release urging section 72b at the cap receiving section 73 side. The shutter deforming section 34d2 is deflectively deformed from the inclined state to the horizontal state. The stopper section 34d22 positioned at the free end of the shutter deforming section 34d2 is released from engagement with the engaging end surface 34n1 positioned in the wide width box section 34n that is at the bottom side of the cap section 34Y as illustrated in Figs. 69A and 69B.

Thus, as described in Figs. 72 to 74, it can move up to the position where the engaged protruding section 34dlb at the shutter 34d side is sandwiched by the second sandwiching members 73d2 of the body side shutter closing mechanism 73d. As described in Fig. 72, movement of the shutter 34d in the mounting direction is restricted, whereas the cap section 34Y can move in the mounting direction, so that the toner discharge opening W is opened, and the state of Fig. 75B is obtained. Fig. 75B illustrates the state in which the developer storage

container is inserted toward the cap receiving section 73.

Fig. 75C illustrates a state of a section indicated by symbol C in Fig. 75B, that is, a state directly before the toner container starts an removing operation from the main body, and the shutter 34d starts to close the toner discharge opening W during the operation. In Fig. 75C, when the shutter 34d further moves in the direction of closing the toner discharge opening W, the corner (a ridgeline section) of the seal material 36 at the leading end side hits against the rib W1 positioned at the circumferential edge of the toner discharge opening W and so gets caught (ride up) between the rib W1 and the upper seal surface.

Fig. 75D illustrates the state in which the toner discharge opening is completely closed by the shutter 34d. At the time of closing completion, the corner of the seal material 36 at the leading end side gets caught in and comes in close contact with the rib W1 side. The leading end surface of the seal material 36 is pulled by the caught ridgeline section and deformed, and rides up to cover the contact section between the rib W1 and the seal material 36 when the cap section 34Y is viewed from the front.

As a result, since the toner discharge opening W is sealed by the seal material 36 until the developer storage container is completely mounted, the toner can be prevented from carelessly leaking from the toner discharge opening W.

The shutter mechanism according to the present fifteenth embodiment is the invention for solving the above mentioned third problem. In the present embodiment, by the configuration in which the rib W1 is disposed on the circumferential edge for the toner discharge opening W used as the existing component and the configuration of the seal material 36 having a section that gets caught by hitting

against the rib W1 for the seal material used as the existing component, adhesion on the toner discharge opening increases without adding any other component, and so leak of the toner can be prevented with a high degree of
5 certainty.

Particularly, since the toner discharge opening W has the hexagonal shape, the leading end of the seal material 36 concentratedly receives a load causing turning-up and is easily turned up, and turning-up can be caused while
10 alleviating sliding resistance in the entire end section in continuity with the top section of the hexagon on which the load is concentrated. Thus, adhesion on the entire circumferential edge of the toner discharge opening W can be secured.

15

Sixteenth Embodiment

Next, an embodiment in which an ID chip as another invention is mounted in the developer storage container according to the fifteenth embodiment will be described.

20 In the present embodiment, a connector, at the cap receiving side, to which an electrical connection relation with an ID chip 2035 illustrated in Figs. 76A and 76B is set increases matching of the connection position, and the contact failure by the toner at the connection position is
25 prevented. A description will be made in connection with this configuration.

Figs. 76A and 76B are front views illustrating a configuration of the ID chip 2035 and a toner container 2032Y in which the ID chip 2035 is mounted. In the same
30 figure, the ID chip 2035 is configured such that, with respect to on a central section of a rectangular terminal plate body, a terminal 2035a is provided at the right, and a non-contact type communication area (an antenna section)

2035b such as a wireless type is provided at the left (see Fig. 76A). Since both the contact-type and the non-contact type are provided, there are the following merits. For writing on the ID chip in an assembly or toner filling process in a toner container factory, toner information or the like is written in the ID chip by non-contact communication during an assembly line operation. Thus, the manufacturing speed can be remarkably improved, and thus an inexpensive toner container having a low manufacturing cost can be produced. Meanwhile, inside the image forming apparatus, an inexpensive non-contact type electronic substrate can be employed in a body side communication device, thereby contributing to the cost reduction of the image forming apparatus.

Next, a mounting configuration of the ID chip on the toner container according to the sixteenth embodiment will be described. The ID chip 2035 has semicircular notches 2035d on a central section. As illustrated in Fig. 76B, the ID chip 2035 is held on the leading end surface of a cap section 2034Y of the toner container 2032Y to be slightly movable in the horizontal direction that is the longitudinal direction. As the holding method, the ID chip 2035 is sandwiched and held between two flange pins 2034f, which are disposed at nearly the center of the relevant leading end surface, at the positions of the notches 2035d. A gap between the two flange pins 2034f is larger than the shortest width between the two notches 2035d, and so the ID chip 2035 is held on the cap section 2034Y with a backlash.

Meanwhile, in a cap receiving section 2073 of the developer storage container storage unit 70, as will be described later, a through hole 2073f that exposes a connector 2073e (that is not shown in Fig. 77 for convenience) used as an electrical connection section on

the ID chip 2035 and a wall section 2073g are disposed as illustrated in Fig. 77.

The wall section 2073g is a section for shielding a surrounding area of the connector 2073e which will be
5 described later, and when the connector 2073e which will be described later is exposed through the through hole 2073f, the wall section 2073g blocks the toner from entering the connector 2073e.

The through hole 2073f is a place that allows the
10 connector 2073e disposed in a common electric substrate which will be described in Fig. 78 to be exposed and face the ID chip 2035.

Fig. 78 is a view illustrating a configuration of the connector 2073e disposed in the common electric substrate.
15 In the same figure, the connector 2073e includes a plurality of terminal plates 2073e1 disposed in a connector body 2073e0. As the terminal plate 2073e1, used is a bent flexible metallic plate having excellent conductivity.

In the connector 2073e, disposed is a configuration
20 for performing positioning at the time of contact with the ID chip 2035, which will be described below.

In Fig. 78, on a surrounding area of the terminal plate 2073e1 disposed in the connector 2073e or part thereof, the wall section 2073g illustrated in Fig. 77 is
25 disposed, and on part of the wall section 2073g, formed are positioning pins 2073e3 that are fittable into positioning holes 2035b and 2035c (see Fig. 76A and 76B) disposed at the ID chip 2035 side.

The positioning holes 2035b and 2035c are for contact-
30 positioning with the terminal plates 2073e1 at the connector 2073e on the terminal 2035a at the ID chip 2035 side. In order to make it easier to fit the positioning pin 2073e3 into, one is formed of a round hole, and the

other is formed of an elongate hole. In Fig. 79 which will be described later, the flange pin 2034f is fixed to a concave section 2035a and protrudes from a holding member 2034k. A reference numeral 34q represents a pedestal of the holding member 2034k.

The connector 2073e at the common electric substrate side is connected with the ID chip 2035 in a state illustrated in Fig. 79. In Fig. 79, when the cap section 2034Y of the developer storage container is inserted into a cap receiving section 2073, the positioning pins 73a and 73b at the cap receiving section 2073 side are inserted into the positioning holes 34a and 34b at the cap section 2034Y, and so the cap section 2034Y is positioned in the cap receiving section 2073.

When the cap section 2034Y is further inserted, the positioning pins 2073e3 of the connector 2073e moves inside the positioning holes 2035b and 2035c at the ID chip 2035 side, and so the position of terminals 2035a1 at the ID chip 2035 side matches with the position of the terminal plates 2073e1 at the connector 2073e, thereby preventing the contact failure caused by position mismatching.

As the cap section 2034Y is inserted, the wall section 2073g positioned around the connector 2073e covers not only a surrounding area of the connector but also a surrounding area of the ID chip 2035 as indicated by an alternate long and two short dashes line in Fig. 79. Further, the ID chip 2035 is installed at the upper position away from the toner discharge opening W. Thus, it is possible to prevent the toner scattered from the toner discharge opening W from sticking to the contact position between the terminals.

Seventeenth Embodiment

Next, a toner container in which both techniques of

the shutter configuration mentioned in the toner container according to the fifteenth embodiment and the ID chip 535 according to the fifth embodiment are mounted will be described as a seventeenth embodiment.

5 A target configuration is a configuration related to the body side shutter closing mechanism 73d that has been described in Figs. 73 to 75D.

Fig. 80 is a perspective view viewed from the front right side in an insertion direction of a cap 2134Y in the state in which the shutter 34d is closed, and Fig. 81 is a perspective view viewed from the front left side in the insertion direction of the cap 2134Y in the state in which the shutter 34d is opened. These figures are different from the previous drawings in the following points.

15 In Fig. 80, unlike the configuration illustrated in Fig. 67, a front cover 2134P for preventing falling of the ID chip 535 loaded into the concave section 35a is disposed on the front surface of the cap 2134Y.

A configuration for mounting the front cover 2134P includes a heat calking pin 2134P10 disposed, on the front surface of the cap 2134Y, below the front surface center and a pair of main and sub reference pins 734S3 that are disposed at the positions different from the heat calking pin 2134P10 while sandwiching the concave section 35a as illustrated in Fig. 81. After the front surface cover 2134P is fixed, the heat calking pin 2134P10 becomes a state in which the leading end is crushed by a jig while being heated, but a non-crushed state is illustrated in Figs. 82 to 86.

30 In the front surface cover 2134P, holes into which the pins 2134P10 and 734S3 are inserted and an opening that exposes part of the ID chip 535 to the outside are formed, respectively.

By fitting the main reference pin 734S3 and the sub reference pin 734S3 into and inserting the heat calking pin 2134P10 into, the front surface cover 2134P is positioned in the state in which the ID chip 535 is exposed to the outside. The heat calking pin 2134P10 is heated and compressed, so that the front surface cover 2134P is fixed to the front surface of the cap 2134Y.

In the holes, at the front surface cover 2134P side, into which the pins are fitted, one of the reference pins is a round hole, and the other is an elongate hole, a longitudinal direction of which is horizontal. Further, the insertion hole of the heat calking pin 2134P10 has the diameter slightly larger than the heat calking pin 2134P10.

By the fixing state, even if the toner container 2132Y is inserted into or separated from the toner container storage unit, the ID chip 535 does not fall off, and communication or electrical connection of the ID chip exposed to the outside through the opening can be performed.

Meanwhile, a structure related to the body side shutter closing mechanism 73d includes a guide rail 2134YG disposed at the side surface of the narrow width box 34Y1 of the cap 2134Y.

The guide rail 2134YG has a configuration different from the guide rail 34YG illustrated, for example, in Fig. 68. As illustrated in Figs. 80 and 81, the guide rail 2134YG includes a protruding section 2134YG3 that is configured to protrude to the front side further than the leading end surface of the narrow width box section 34Y1 and have a protruding portion rounding toward the central side. The protruding sections 2134YG3 are symmetrically disposed on both sides of the narrow width box 34Y1.

Further, as a configuration different from the configurations of the above embodiments, as illustrated in

Fig. 83, at the position (the position indicated by a reference numeral 2134P3) facing the engaged protruding section 34d12b of the shutter 34d in the circumferential surface of the medium diameter cylindrical section 34Y2, formed is a concave section that has the outer diameter smaller than the outer diameter of the medium diameter cylindrical section 34Y2. The circumferential surface 2134P3 that forms the concave section is configured not to interfere with turning of a sandwiching member 73d2 disposed in the body side shutter closing mechanism 73d illustrated in Fig. 72.

In this configuration, when the cap 2134Y is loaded on the cap receiving section 73 of the apparatus body in the same procedure as illustrated in Figs. 72 to 74, the cap 2134Y is sandwiched by the body side shutter closing mechanism 73d. Figs. 84 to 86 are views corresponding to Figs. 72 to 74 illustrating the loading state of the cap section 34Y used in the above configuration.

At the time of the opening operation of the shutter 34d, first, as illustrated in Fig. 84, in accompany with the mounting operation of the developer storage container 32Y in the white arrow direction, the first sandwiching members 73d1 come in contact with the protruding sections 2134YG3.

Thereafter, as illustrated in Fig. 85, when the mounting operation of the developer storage container 32Y proceeds in the white arrow direction, the body side shutter closing mechanism 73d (the shutter sandwiching mechanism) is pushed by the protruding sections 2134YG3 and so rotates on the support shaft section 73d3.

When the body side shutter closing mechanism 73d rotates, the first sandwiching members 73d1 sandwich the vertical surfaces of the guide rails 2134YG continuing from

146

the protruding section 2134YG3, and the second sandwiching members 73d2 sandwich the side wall surfaces of the main shutter section 34d1 while being engaged with the protrusions 34dlb1 positioned in the engaged protruding
5 section 34dlb of the shutter 34d.

Thereafter, the shutter 34d comes in contact with the wall section (not shown) formed around the toner feeding opening at the cap receiving section 73 side and so stops movement in the mounting direction. At this time, the
10 vertical surfaces of the guide rails 2134YG are sandwiched by the first sandwiching sections 73d1.

In the state in which movement of the shutter 34d is stopped, when the toner container 2132Y moves in the mounting direction, the shutter 34d whose movement in the mounting direction is stopped relatively moves when viewed
15 from the cap section 2134Y, and the narrow width box section 34Y12 of the cap section 2134Y moves to the front side in the mounting direction further than the shutter member 34d. By the relative movement, as illustrated in
20 Fig. 86, the toner discharge opening W is opened.

At this time, as illustrated in Fig. 74, the vertical surfaces of the cap section 2134Y are sandwiched by the first sandwiching members 73d1, and the protrusions 34dlb1 positioned in the engaged protruding section 34dlb of the
25 shutter 34d are engaged by the second sandwiching members 73d2. Since the opening operation of the shutter 34d is performed in the state in which the shutter 34d is sandwiched, the postures of the shutter 34d and the cap section 2134Y in the cap receiving section 73 are decided,
30 and thus the opening/closing operation of the shutter 34d can be smoothly performed.

Meanwhile, when extracting (separating) the developer storage container 2132Y from the developer storage

container storage unit 70 (the cap receiving section 73), the operation is performed in a procedure reverse to the mounting procedure. That is, the operation of the body side shutter closing mechanism 73d (the shutter sandwiching mechanism) accompanying with the closing operation of the shutter 34d is performed in order of Figs. 86, 85, and 84.

In the configuration illustrated in Fig. 81, since the protruding section 2134YG3 that is present at the front end of the guide rail 2134YG protrudes to the front side further the front surface of the narrow width box section 34Y12, turning start timing of the body side shutter closing mechanism 73d is delayed. That is, since the protruding section 2134YG3 protrudes from the front surface of the narrow width box section 34Y12 to the outside, when the cap section 2134Y is extracted, a time period when turning of the first sandwiching section 73d1 is stopped by the protruding section 2134YG3 is lengthier, and the shutter 34d remains sandwiched for a longer time compared to when the protruding section 2134YG3 is not disposed.

When the cap section 2134Y moves in the extracting direction, since the first sandwiching section 73d1 faces the engaged protruding section 34d1 of the shutter 34d, the non-turnable state is maintained. For this reason, a protrusion amount of the protruding section 2134YG3 is set so that the body side shutter closing mechanism 73d can be maintained in the non-turnable state until the shutter 34d is completely closed, and sandwiching of the guide rail 2134YG by the first sandwiching section 73d1 can be released when the shutter 34d completely closes the toner discharge opening W.

Since the engaged protruding sections 34d1b at the shutter 34d side are sandwiched by the second sandwiching sections 73d2 until the toner discharge opening W is

completely closed by the shutter 34d, when the cap 34Y moves in the extracting direction, the shutter 34d traverses the toner discharge opening W in the sandwiched state and so closes the toner discharge opening W.

5 Next, a description will be made in connection with features of the toner used in the developer feeding device as follows.

As the toner contained in the toner containers 32Y, 32M, 32C, and 32K, toner formed so that the following
10 relations hold true:

$$3 \leq D_v \leq 8 \quad (1)$$

$$1.00 \leq D_v / D_n \leq 1.40 \quad (2),$$

where D_v (μm) represents a volume-average particle diameter, and D_n (μm) represents a number-average particle
15 diameter. A toner particle is selected according to an image pattern in the developing process and excellent image quality is maintained, and satisfactory developing capability is maintained even if the toner is agitated for a long time in the developing device. Moreover, the toner
20 can be efficiently and reliably conveyed without blocking the toner supply path.

The volume average particle diameter and the number average particle diameter of toner can be measured by using a typical device such as a Coulter Counter type particle
25 diameter distribution measuring device: Coulter Counter-TA-II (manufactured by Coulter Electronics Limited); or Coulter Multisizer II (manufactured by Coulter Electronics Limited).

Furthermore, in the present embodiment, as toner
30 contained in the developer storage containers 32Y, 32M, 32C, and 32K, used is substantially spherical toner that is formed so that a shape factor SF-1 is in a range of 100 to 180 and a shape factor SF-2 is in a range of 100 to 180.

As a result, high transfer efficiency is maintained, and reduction in cleaning performance is suppressed. Moreover, the toner can be efficiently and reliably conveyed without blocking the toner supply path such as the tube 71.

5 Here, the shape factor SF-1 represents the sphericity of the toner particle and obtained by the following equation.

$$SF-1 = (M^2/S) \times (100\pi/4)$$

10 In the above equation, M is the maximum particle diameter (the largest particle diameter in uneven particle diameters) in a project plane of the toner particle, and S is a project area of the toner particle. Therefore, the toner particle whose shape factor SF-1 is 100 is perfectly spherical, and the degree of sphericity lowers as it
15 becomes greater than 100.

The shape factor SF-2 represents irregularity of the toner particle and obtained by the following equation.

$$SF-2 = (N^2/S) \times (100/4\pi)$$

20 In the above equation, N is the circumferential length in the project plane of the toner particle, and S is the project area of the toner particle. Therefore, the toner particle whose shape factor SF-2 is 100 has no irregularity and the irregularity becomes larger as it becomes greater than 100.

25 The shape factor SF-1 and the shape factor SF-2 are obtained by photographing the toner particle by a scanning electron microscope "S-800" (manufactured by Hitachi, Ltd.) and analyzing the photograph of the toner particle by an image analyzer "LUSEX3" (manufactured by Nireco Corp.).

30 In the first to eight embodiments and the eleventh to seventeenth embodiments, only toner (one component developer) is contained in the toner container (designated as 32Y, 32M, 32C, and 32K) as the developer container.

However, as for an image forming apparatus that appropriately supplies the developing device with a two component developer composed of toner and a carrier, the two component developer can be contained in the toner container (the developer container). Even in these cases, the same effects as in the above embodiments can be obtained.

In the first to eight embodiments and the eleventh to seventeenth embodiments, some or all of image forming units 6Y, 6M, 6C, and 6K can be replaced with process cartridges. Even in this case, the same effects as in the above embodiments can be obtained.

Further, in the first to sixth embodiments and the eleventh to seventeenth embodiments, by rotatably configuring the container body 33Y, a configuration has been made to convey the toner contained in the container body 33Y toward the opening A. On the other hand, as in the seventh embodiment described with reference to Figs. 48 and 49, the toner contained in the container body 1033Y may be conveyed toward the opening A such that the container body 1033Y is configured to be non-rotatably held on the toner container storage unit 70 together with the cap section 1034Y, and a conveying member (for example, a conveying member that includes a plurality of conveying blade members installed on a shape section and rotates in a predetermined direction) that conveys the toner toward the opening A inside the container body 1033Y is installed. Even in this case, the same effects as in the above embodiments can be obtained.

Further, in the above embodiments, in the substrate (designated as 35b or 535b) of the ID chip (designated as 35 or 535), a plurality of metallic pads 35a have been arranged in line in the vertical direction so that the

position in the longitudinal direction is not misaligned. On the other hand, in the substrate of the ID chip, a plurality of metallic pads 35a may be arranged in the vertical direction so that the position in the longitudinal direction is alternately misaligned in a zigzag form. In this case, in order to conform to the metallic pads 35a arranged in the zigzag form, a plurality of body side terminals (designated as 73e2 or 573e2) in the connector (designated as 73e or 573e) are also arranged in the zigzag form. Even in this case, the same effects as in the above embodiments can be obtained.

Furthermore, in the above embodiments, the present invention has been applied to the ID chip (the information storage device) disposed in the toner container 32Y (the developer container) or the like as the removable device removably installed on the image forming apparatus body 100 or the like. However, the application of the present invention is not limited thereto, and the present invention can be applied even to any other removable device removably installed on the image forming apparatus body 100 or the like as long as the information storage device is installed in the removable device similarly to the above embodiments. For example, in the image forming apparatus 100 illustrated in Fig. 1, even when the information storage device is installed in the process cartridges 6Y, 6M, 6C, and 6K as the removable device, the fixing device 20 (the fixing unit) as the removable device, the intermediate transfer unit 15 as the removable device, or the like, the present invention can be applied to each of them similarly to the above embodiments. Even in this case, the same effects as in the above embodiments can be obtained.

The present invention is not limited to the above embodiments, and it is obvious that the above embodiment

can be appropriately changed in addition to what have been suggested in the above embodiments. Further, the number, the position, the shape, and the like of component members are not limited to the above embodiments and may be changed
5 to the number, the position, the shape, and the like suitable for implementing the present invention.

In the present disclosure, there is another invention corresponding to the fifteenth to seventeenth embodiments for solving the third problem. This can be summarized in
10 the form of claims as follows.

1. A developer storage container removably installed in an image forming apparatus body, comprising:

a cap section provided with a toner discharge opening configured to discharge toner in a vertical direction,
15 outside the developer storage container; and

a shutter that is held on the cap section and is configured move along an outer surface of the cap section to open and close the toner discharge opening

wherein, a seal material that is deformable and made
20 of a flexible material is disposed on a surface of the shutter, the surface facing the toner discharge opening, and

wherein when the shutter moves in a direction in which the shutter moves to close the toner discharge opening, a
25 leading end of the seal material in the direction is rolled up toward the toner discharge opening so that the leading end comes into close contact with a circumferential edge of the toner discharge opening.

2. The developer storage container according to claim
30 1, wherein a rib that protrudes toward the seal material is disposed at the circumferential edge of the toner discharge opening and bumps against the seal material to cause the seal material to be rolled up when the shutter moves in the

direction in which the shutter moves to close the toner discharge opening so that the leading end comes into close contact with the circumferential edge of the toner discharge opening.

5 3. The developer storage container according to claim 1 or 2, wherein a leading end of the seal material in the direction in which the shutter moves to close the toner discharge opening protrudes from an end of the shutter toward the direction, and the leading end is used as a
10 portion that is deformed and rolled up.

 4. The developer storage container according to claim 1, 2, or 3, wherein the toner discharge opening is a polygonal-shaped opening .

 5. The developer storage container according to claim
15 4, wherein the toner discharge opening has a hexagonal shape in a planar view that has a vertex pointing towards the leading end side of the seal material.

 6. The developer storage container according to claim 1 or 2, wherein the shutter is provided with a shutter
20 deforming section of a cantilever shape which has a base end at a surface on which the seal material is disposed, extends to a rear side in the direction in which the shutter moves to close the toner discharge opening, and has a free end that is inclined downward in a vertical
25 direction, and

 wherein the free end of the shutter deforming section is provided with an engagement releasing section and a stopper section, the engagement releasing section being capable of running on an engagement release urging section
30 having a convex rib disposed in a cap receiving section of a developer storage container storage unit provided in the image forming apparatus on which the cap section is mounted, the stopper section being engagable with an engagement end

surface formed at a bottom of the cap section at a position of holding the cap section, and wherein the engagement release section runs on the convex rib in a process in which the cap section moves in a direction of opening the toner discharge opening so that the shutter deforming section is deformed from a state in which the shutter deforming section extends in a inclined direction to a state in which the shutter deforming section horizontally extends, engagement of the stopper section is released from the engagement end surface, and movement of the shutter to a position where the shutter opens the toner discharge opening is allowed.

7. The developer storage container according to claim 1 or 2, wherein the cap portion is provided with an information storage device at a position distanced from the toner discharge opening in a vertical direction, the information storage device being configured to be mounted in a rectangular concave section formed between a pair of positioning sections arranged in a vertical direction of on an end surface of the cap section, the concave section being disposed in the end surface of the cap section at an upper position distanced from the toner discharge opening in the vertical direction.

8. An image forming apparatus, comprising:
the developer storage container according to any one of claims 1 to 7.

Although the invention has been described with respect to specific embodiments for a complete and clear disclosure, the appended claims are not to be thus limited but are to be construed as embodying all modifications and alternative constructions that may occur to one skilled in the art that fairly fall within the basic teaching herein set forth.

CLAIMS

1. An information storage device installed in a removable device configured to be removably installed in an image forming apparatus body, comprising:

5 an information storage unit that stores information communicated between the image forming apparatus body and the removable device;

a terminal that comes in contact with a body side terminal installed in the image forming apparatus body and
10 communicates the information with the image forming apparatus body; and

a substrate that holds the information storage unit and the terminal and includes at least one of a hole and a notch configured to be engaged with a protruding section
15 installed in the image forming apparatus body,

wherein an earth terminal, which comes in contact with a body side earth terminal formed in the protruding section of the image forming apparatus body, is formed in the hole or the notch formed in the substrate.

20

2. The information storage device according to claim 1, wherein the earth terminal is formed at least on an inner surface of the hole or the notch.

25 3. The information storage device according to claim 1, wherein the substrate includes one hole as the hole in which the earth terminal is formed is one.

4. The information storage device according to claim 3,
30 wherein the terminal includes a plurality of terminals each including one of a plurality of metallic plates arranged in a transverse direction thereof with a clearance therebetween, and

the hole is disposed at a position sandwiched between two metallic plates among the plurality of metallic plates.

5. The information storage device according to claim 3,
5 wherein the hole is formed at a position above a gravity center of the substrate.

6. The information storage device according to claim 1,
wherein the earth terminal includes a protruding
10 section formed to extend in a predetermined direction on a front surface of the substrate on which the terminal is formed.

7. A removable device that is installed removably in an
15 image forming apparatus body and is any one of a toner cartridge inside which toner is contained, a process cartridge, and an ink cartridge inside which ink is contained, comprising:

the information storage device according to claim 1.
20

8. The removable device according to claim 7,
further comprising a holding section that holds the information storage device such that the information storage device is movable on a virtual plane that
25 intersects with a moving direction in which the earth terminal approaches and comes in contact with the body side earth terminal.

9. An image forming apparatus, comprising:
30 the removable device according to claim 7 that is mounted in the image forming apparatus body,
wherein the body side terminal includes a plurality of body side terminals each including one of a plurality of

plate-like or linear metallic members each of which is fixed to and supported on the image forming apparatus body to have one end formed as a fixed end and the other end formed as a free end and has a curved section that curves
5 toward the removable device on a side of the other end,

the protruding section is a positioning pin that has a leading end formed in a tapered shape and is engaged with the hole,

the body side earth terminal includes a plate-like or
10 linear metallic member in which a part thereof is contained inside the positioning pin, and a section thereof to be in contact with the earth terminal is exposed outside the positioning pin, and

a section of the body side earth terminal to be in
15 contact with the earth terminal is arranged closer to the facing information storage device than the curved section of the body side terminal.

10. An image forming apparatus, comprising:

20 a removable device that includes the information storage device according to claim 5 mounted therein and is mounted in the image forming apparatus body,

wherein the body side terminal includes a plurality of terminals each including one of a plurality of plate-like
25 or linear metallic members each of which is fixed to and supported on the image forming apparatus body to have one end formed as a fixed end and the other end formed as a free end and has a curved section that curves toward the removable device on a side of the other end,

30 the protruding section is a positioning pin that has a leading end formed in a tapered shape and is engaged with the hole,

the body side earth terminal includes a plate-like or

linear metallic member in which a part thereof is contained inside the positioning pin, and a section thereof to be in contact with the earth terminal is exposed outside the positioning pin,

5 a section of the body side earth terminal to be in contact with the earth terminal is arranged closer to the facing information storage device than the curved section of the body side terminal, and

10 a pair of restricting members each of which is arranged to face one of both side end surfaces of the substrate at a position below the center of the hole.

11. A developer container that is installed removably in an image forming apparatus body in a state in which a
15 longitudinal direction the developer container is horizontal, and that stores a developer thereinside, comprising:

 a pipe-shaped container body that includes an opening formed at one end in the longitudinal direction and is
20 configured such that the developer stored thereinside is conveyed toward the opening;

 a cap section in which the opening of the container body is inserted and that includes a discharge opening used to discharge the developer, which has been discharged from
25 the opening of the container body, outside the developer container; and

 a shutter member that is held in the cap section and moves to open/close the toner discharge opening in conjunction movement of the developer container when the
30 developer container is attached to/detached from the image forming apparatus body,

 wherein the cap section includes an information storage device installed in an end section in the

longitudinal direction and a positioning hole engaged with a positioning pin installed in the image forming apparatus body, and

the information storage device is the information
5 storage device according to claim 1.

12. The developer container according to claim 11,
further comprising a holding section that holds the
information storage device such that the information
10 storage device is movable on a virtual plane that
intersects with a moving direction in which the earth
terminal approaches and comes in contact with the body side
earth terminal.

15 13. An image forming apparatus, comprising:

the developer container according to claim 11 that is
mounted in the image forming apparatus body,

wherein the body side terminal includes a plurality of
body side terminals each including one of a plurality of
20 plate-like or linear metallic members each of which is
fixed to and supported on the image forming apparatus body
to have one end formed as a fixed end and the other end
formed as a free end and has a curved section that curves
toward the developer container side on a side of the other
25 end,

the protruding section is a positioning pin that has a
leading end formed in a tapered shape and is engaged with
the hole,

the body side earth terminal includes a plate-like or
30 linear metallic member in which a part thereof is contained
inside the positioning pin, and a section thereof to be in
contact with the earth terminal is exposed outside the
positioning pin, and

a section of the body side earth terminal to be in contact with the earth terminal is arranged closer to the facing information storage device than the curved section of the body side terminal.

5

14. An image forming apparatus, comprising:

a developer container that includes the information storage device according to claim 5 mounted therein and is mounted in the image forming apparatus body,

10

wherein the body side terminal includes a plurality of body side terminals each including one of a plurality of plate-like or linear metallic members each of which is fixed to and supported on the image forming apparatus body to have one end formed as a fixed end and the other end formed as a free end and has a curved section that curves toward the removable device side on a side of the other end,

15

the protruding section is a positioning pin that has a leading end formed in a tapered shape and is engaged with the hole,

20

the body side earth terminal includes a plate-like or linear metallic member in which a part thereof is contained inside the positioning pin, and a section thereof to be in contact with the earth terminal is exposed outside the positioning pin,

25

a section of the body side earth terminal to be in contact with the earth terminal is arranged closer to the facing information storage device than the curved section of the body side terminal, and

30

a pair of restricting members each of which is arranged to face one of both side end surfaces of the substrate at a position below the center of the hole.

15. A removable device that is configured to be removably

161

installed in an image forming apparatus body and holds an information storage device, comprising:

the information storage device including

an information storage unit that stores information
5 communicated between the image forming apparatus body and the removable device,

a terminal that comes in contact with a body side terminal installed in the image forming apparatus body and communicates the information with the image forming
10 apparatus body,

a substrate that holds the information storage unit and the terminal and includes at least one of a hole and a notch that allows a protruding section installed in the image forming apparatus body to be inserted into, and

15 a holding section that holds the information storage device such that the information storage device is movable on a virtual plane that intersects with a moving direction in which the terminal approaches and comes in contact with the body side terminal.

20

16. The removable device according to claim 15,
wherein the holding section includes:

a first facing section that faces a first plane of the substrate on which the terminal is installed and is formed
25 such that a part of the first plane is slidable on the first facing section;

a second facing section that faces a second plane of the substrate that is opposite to the first plane and on which the information storage unit is installed, the second
30 facing section being formed such that a part of the second plane is slidable on the second facing section; and

an opening formed to expose the terminal and the hole or the notch at a side facing the body side terminal.

17. The removable device according to claim 15,

wherein the terminal includes a plurality of terminals each including one of a plurality of metallic plates that are arranged in a transverse direction thereof with a clearance therebetween,

the body side terminal includes a plurality of body side terminals each including one of a plurality of plate-like or linear metallic members each of which is fixed to and supported on the image forming apparatus body to have one end formed as a fixed end and the other end formed as a free end and has a curved section that curves toward the removable device side on a side of the other end,

a first virtual straight line that passes through the center of the hole or the notch and is parallel to a direction in which the plurality of metallic plates are arranged is configured to be positioned not to overlap a second virtual straight line that connects the centers of the plurality of metallic plates in a longitudinal direction thereof, and

when the plurality of metallic plates approach and come in contact with the plurality of body side terminals, the plurality of body side terminals are deformed so that the curved section that becomes a contact point between the plurality of body side terminals and the plurality of metallic plates get close to the first virtual straight line while being pressed by the plurality of metallic plates and elastically deformed.

18. The removable device according to claim 17,

wherein the plurality of metallic plates are arranged so that the direction in which the plurality of metallic plates are arranged is vertical in a state in which the

removable device is mounted on the image forming apparatus body.

19. The removable device according to claim 17,

5 wherein the hole or the notch includes two holes or notches that are formed on both ends in the direction in which the plurality of metallic plates are arranged so that the plurality of metallic plates are sandwiched between the two holes or notches.

10

20. The removable device according to claim 17,

 further comprising positioning holes that are engaged with positioning pins installed in the image forming apparatus body and are formed at positions away from each
15 other in a vertical direction so that the information storage device is sandwiched between the positioning holes in a state in which the removable device is mounted on the image forming apparatus body,

 wherein a third virtual straight line that connects
20 the centers of the two positioning holes is configured to be parallel to the first virtual straight line.

21. The removable device according to claim 15,

 wherein the holding section is configured to be
25 removably installed in the removable device and includes an insertion opening through which the information storage device is inserted.

22. The removable device according to claim 15,

30 wherein the removable device is any one of a developer container inside which a developer is contained, a process cartridge, and an ink cartridge inside which ink is contained.

23. A developer container that is installed removably on an image forming apparatus body in a state in which a longitudinal direction of the developer container is horizontal, comprising:

a pipe-shaped container body that includes an opening formed at an end in the longitudinal direction and is configured such that a developer stored therein is conveyed toward the opening;

a cap section in which the opening of the container body is inserted and that includes a discharge opening, which is disposed at a bottom section, used to discharge the developer, which has been discharged from the opening of the container body, outside the developer container; and

a shutter member that is held in the bottom section of the cap section and moves along an outer surface of the cap section to open/close the toner discharge opening,

wherein the cap section includes: a holding section that is installed at an end in the longitudinal direction and holds an information storage device; and a positioning hole engaged with a positioning pin installed in the image forming apparatus body,

the information storage device includes:

an information storage unit that stores information communicated between the image forming apparatus body and the removable device;

a terminal that comes in contact with a body side terminal installed in the image forming apparatus body and communicates the information with the image forming apparatus body; and

a substrate that holds the information storage unit and the terminal and includes at least one of a hole and a notch that allows a protruding section installed in the

165

image forming apparatus body to be inserted into, and

the holding section that holds the information storage device such that the information storage device is movable on a virtual plane that intersects with a moving direction in which the terminal approaches and comes in contact with the body side terminal.

24. The developer container according to claim 23, wherein the holding member includes:

10 a first facing section that faces a first plane of the substrate on which the terminal is installed and is formed such that a part of the first plane is slidable on the first facing section;

15 a second facing section that faces a second plane of the substrate that is opposite to the first plane and on which the information storage unit is installed, the second facing section being formed such that a part of the second plane is slidable on the second facing section; and

20 an opening formed to expose the terminal and the hole or the notch at a side facing the body side terminal.

25. The developer container according to claim 23,

wherein the terminal includes a plurality of terminals each including one of a plurality of metallic plates that are arranged in a transverse direction thereof with a clearance therebetween,

the body side terminal includes a plurality of body side terminals each including one of a plurality of plate-like or linear metallic members each of which is fixed to and supported on the image forming apparatus body and has a curved section that curves toward the removable device side on a side of the other end,

the hole or the notch consist of two holes or two

notches each of which is formed on one of both ends in a direction in which the plurality of metallic plates are arranged such that the plurality of metallic plates are sandwiched between the two holes or the two notches,

5 a first virtual straight line that connects the two holes or the two notches is configured to be positioned not to overlap a second virtual straight line that connects the centers of the plurality of metallic plates in a longitudinal direction thereof, and

10 when the plurality of metallic plates approach and come in contact with the plurality of body side terminals, the plurality of body side terminals are deformed so that the curved section that becomes a contact point between the plurality of body side terminals and the plurality of
15 metallic plates get close to the first virtual straight line while being pressed by the plurality of metallic plates and elastically deformed.

26. The developer container according to claim 25,
20 wherein the plurality of metallic plates are arranged so that a direction in which the plurality of metallic plates are arranged is vertical in a state in which the developer container is mounted on the image forming apparatus body.

25
27. The developer container according to claim 25,
 wherein the first virtual straight line is configured to be parallel to the second virtual straight line.

30 28. The developer container according to claim 25,
 wherein the positioning hole of the cap section consist of two positioning holes each of which is formed on one of both ends in a vertical direction so that the

167

information storage device is sandwiched between the two positioning holes in a state in which the developer container is mounted on the image forming apparatus body, and

5 a third virtual straight line that connects the centers of the two positioning holes is configured to be parallel to the first virtual straight line.

29. The developer container according to claim 23,
10 wherein the holding section is configured to be removably installed in the cap section and includes an insertion opening through which the information storage device is inserted, and
 the cap section includes a standing member that blocks
15 the insertion opening in a state in which the holding member is installed in the cap section.

30. The developer container according to claim 23,
 wherein the developer is toner.

20

31. The developer container according to claim 23,
 wherein the developer is a two component developer in which toner and a carrier are mixed.

25 32. An image forming apparatus, comprising:
 the removable device according to claim 15 that is installed in the image forming apparatus body.

33. An image forming apparatus, comprising:
30 the developer container according to claim 23 that is installed in the image forming apparatus body.