

MACHINE LEARNING SYSTEM AND DATA FUSION FOR OPTIMIZATION OF DEPLOYMENT CONDITIONS FOR DETECTION OF CORROSION UNDER INSULATION

5

FIELD OF THE INVENTION

[001] The present invention relates to inspection technologies, and, more particularly, relates to a hardware and software-based system for the prediction and detection of corrosion under
10 insulation (CUI).

BACKGROUND OF THE INVENTION

[002] Corrosion under insulation (CUI) is a condition in which an insulated structure such as a metal pipe suffers corrosion on the metal surface beneath the insulation. As the corrosion
15 cannot be easily observed due to the insulation covering, which typically surrounds the entire structure, CUI is challenging to detect. The typical causes of CUI are moisture buildup that infiltrates into the insulation material. Water can accumulate in the annular space between the insulation and the metal surface, causing surface corrosion. Sources of water that can induce corrosion include rain, water leaks, and condensation, cooling water tower drift, deluge systems
20 and steam tracing leaks. While corrosion usually begins locally, it can progress at high rates especially if there are repetitive thermal heating and/or cooling cycles or contaminants in the water medium or surrounding air such as chloride or acid.

[003] When CUI is undetected, the results of can lead to the shutdown of a process unit or an entire facility and can lead to catastrophic incidents. Since it is a hidden corrosion mechanism,
25 the damage remains unnoticed until insulation is removed or advanced NDT (non-destructive testing) techniques, such as infrared thermography, are used to ascertain the metal condition beneath the insulation. Removal of insulation can be a time-consuming and costly process, while the accuracy of NDT techniques can be insufficient due to the large number of variables (e.g., geometrical, environmental, material-related), that cause false positives (incorrect
30 detection of corrosion) and false negatives (incorrect non-detection of corrosion) in the detection process. Additionally, many facilities have elevated networks of pipes that are difficult to access, requiring scaffolding for visual inspection.

[004] Due to these challenges, it has been found that localized visual inspections of assets are not reliably effective at detecting CUI, and they do not reflect conditions of the assets. There is a related technical gap in predictive risk assessment of CUI. Accordingly, there is a pressing need for improved detection and risk assessment tools to determine levels of CUI damage, institute proper maintenance scheduling, and reduce the burdensome costs imposed by this problem.

[005] It is with respect to these and other considerations that the disclosure made herein is presented.

SUMMARY OF THE INVENTION

[006] Embodiments of the present invention provide a system for predicting and detecting of corrosion under insulation (CUI) in an infrastructure asset using machine learning and data fusion. The system comprises at least one infrared camera positioned to capture thermal images of the asset, and at least one smart mount mechanically supporting and electrically coupled to the at least one infrared camera and having a position that is adjustable with respect to the asset. The at least one smart mount includes a communication module, memory storage adapted to store thermal image data received from the at least one camera, a battery module operative to recharge the at least one infrared camera, an ambient sensor module adapted to obtain ambient condition data, and at least one additional sensor adapted to obtain CUI-related data from the asset. The system further includes at least one computing device having a processor configured with instructions for executing a machine learning algorithm taking as inputs from either the communication module or memory storage of the at least one smart mount a) thermal images of the asset, b) the ambient condition data, c) CUI-related data from the probe sensor providing data fusion and d) result data obtained from conventional CUI tests, and adapted to output a CUI prediction regarding the asset. A machine-learning platform is adapted to train the machine learning algorithm based on accumulated input data received from the at least one computing device over time.

[007] The at least one computing device is adapted to test current deployment conditions of the at least one infrared camera and at least one smart mount by executing the machine learning algorithm using current infrared images, ambient sensor data and CUI-related data by determining whether performance of the machine learning algorithm under current deployment conditions meets a threshold level.

[008] In some embodiments, the performance of the machine learning algorithm conditions is measured by corrosion prediction accuracy. In other embodiments, the performance of the current deployment conditions is measured by a cost of deployment and testing. In still further embodiments, the performance of the current deployment conditions is measured by a speed of deployment and testing.

[009] The deployment conditions tested by the at least one computing device can include a time of year in which the at least one infrared camera and at least one smart mount are deployed, a time of day in which the at least one infrared camera and at least one smart mount are deployed, a position, orientation and image capture duration of the at least one camera, and a position, type and number of images captured per time period of the at least one camera.

[0010] Embodiments of the present invention provide a system for predicting and detecting of corrosion under insulation (CUI) in an infrastructure asset. The system includes at least one infrared camera positioned to capture thermal images of the asset, at least one smart mount mechanically supporting and electrically coupled to the at least one infrared camera, the at least one smart mount including a wireless communication module, memory storage adapted to store thermal image data received from the at least one camera, a battery module operative to recharge the at least one infrared camera, an ambient sensor module adapted to obtain ambient condition data; and a structural probe sensor adapted to obtain CUI-related data from the asset. The system further includes at least one computing device having a wireless communication module that is communicatively coupled to the at least one smart mount, the computing device configured with instructions for executing a machine learning algorithm taking as inputs thermal image data, ambient condition data and CUI-related data from the probe sensor, and outputting a CUI prediction regarding the asset, and a cloud computing platform adapted to receive and store the thermal image data, ambient condition data and CUI-related data from the probe sensor, and the prediction output by the computing device, the cloud computing platform adapted to receive verification data for updating the machine learning algorithm stored on the computing device.

[0011] In certain embodiments, the at least one smart mount includes a fixture for supporting the infrared camera, the mount being rotatable and extendable to enable the infrared camera to be translated and tilted.

[0012] In certain implementations, asset includes identification tags and at least one smart mount further includes a standard camera operative to scan the identification tags on the asset.

5 **[0013]** In certain implementations, the ambient sensor module is operative to detect temperature, humidity and air pressure. The structural probe sensor can include a magnetometry sensor.

[0014] In certain embodiment, the system further comprises a control station communicatively coupled to the at least one smart mount and adapted to transmit configuration and control commands to the at least one smart mount.

10 **[0015]** The machine learning algorithm employed by the at least one computing device can include a deep recurrent neural network, and in some implementations, the deep recurrent neural network is a long short-term memory (LSTM) network. The machine learning algorithm employed by the at least one computing device can further include a convolutional neural network.

15 **[0016]** In some implementations, the at least one computing device is configured to perform noise reduction on the data received from the at least one smart mount. The system can have multi-node capability in which each of the at least one mounts can communicate with each other via their respective communication modules.

[0017] Embodiments of the present invention also provide a method of obtaining data from an
20 infrastructure asset for enabling prediction and detection of corrosion-under-insulation (CUI). The method comprises capturing thermal image data of the asset over time, probing the asset using an additional sensing mode to obtain additional probe over time, measuring ambient conditions to obtain ambient condition data over time, combining the thermal image, additional probe and ambient condition data into a computer readable file, and transmitting the file to a
25 computing device that uses an algorithm that uses the thermal image, additional probe and ambient condition data to predict whether the asset contains CUL

[0018] Certain embodiments of the method further comprise scanning the asset for identification tags to obtain tag photo data and including the tag photo data in the computer readable file. The additional sensing mode can include, for example, a magnetometry sensor.
30 The ambient condition data can include temperature, humidity and air pressure measurements.

[0019] Embodiments of the present invention also provide a method of predicting corrosion-under-insulation (CUI) in an infrastructure asset using a cloud computing platform. The

method comprises receiving a stream of data including thermal images of the asset, additional sensor probe data of the asset, and ambient conditions at the asset, executing, in real time, one or more machine learning algorithms using the received stream of data and weights received as updated from the cloud computing platform to generate a prediction as to whether the asset contains CUI, and transmitting the received stream of data and prediction to the cloud computing platform.

[0020] Some embodiments of the method further comprise filtering the received data for noise.

[0021] The method can also include generating synthetic thermal image data based on ambient conditions and parameters of the asset using a thermal dynamic model. At the cloud computing platform, the synthetic thermal image data can be combined with the stream of including thermal images of the asset, additional sensor probe data of the asset, and ambient conditions at the asset to create a data training set for training a machine learning model. In some embodiments, the machine learning model including a deep recurrent neural network. Implementations of the method can include a long short memory network (LSTM). The machine learning model can further include a convolutional neural network.

[0022] Embodiments of the present invention also provide a method of optimizing deployment conditions of at least one investigative kit for obtaining data from an infrastructure asset to enable prediction and detection of corrosion-under-insulation (CUI). The method comprises receiving thermal images, sensor data acquired from asset over time acquired by the at least one investigative kit and deployment condition information regarding the at least one investigative kit, obtaining result data of conventional CUI detection methods corresponding of the asset over time, training a machine learning algorithm using the captured thermal images and other sensor data and the result data acquired from the asset, and testing the deployment conditions of the at least one investigative kit. The testing of deployment conditions includes receiving current test conditions including ambient condition data and current deployment conditions at the at least one investigative kit to obtain ambient condition data over time, executing the machine learning algorithm using the ambient conditions data and current deployment conditions of the at least one investigative kit, and determining whether a performance of the machine learning algorithm based on the test conditions exceeds a preset performance threshold. If performance of the machine learning algorithm exceeds the threshold, the deployment conditions are optimized using the test conditions. In contrast, if performance of the machine learning algorithm does not exceed the threshold, the deployment conditions of the at least one investigative kit are changed, and the machine learning algorithm

is repeated iteratively until performance exceeds the threshold or a set number of repetitions have been conducted.

5 [0023] In some embodiments, the method further comprises measuring the performance of the machine learning algorithm based on corrosion prediction accuracy using current test conditions. In other embodiments, the method further comprises measuring the performance of the machine learning algorithm based on a cost of deployment and testing. In still further embodiments, the method comprises measuring the performance of the machine learning algorithm based on a speed of deployment and testing.

10 [0024] The current deployment conditions can include a time of year at which the at least one investigative kit is deployed, a time of day at which the at least one investigative kit is deployed, a position, orientation and image capture duration of the at least one investigative kit, and a position, type and number of images capture per time period of the at least one investigative kit.

15 [0025] These and other aspects, features, and advantages can be appreciated from the following description of certain embodiments of the invention and the accompanying drawing figures and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

20 [0026] FIG. 1 is a schematic illustration of a cloud-based learning system for predicting and detecting CUI according to an embodiment of the present invention.

[0027] FIG. 2 is a schematic illustration of an embodiment of the cloud-based system in which four infrared cameras and corresponding smart mounts and computing devices are deployed to monitor a structure for CUL

25 [0028] FIG. 3 is a block diagram showing functional elements of a smart mount according to an exemplary embodiment of the present invention.

[0029] FIG. 4 is a block flow diagram illustrating a method for generating synthetic thermal image data structures according to an exemplary embodiment of the present invention.

[0030] FIG. 5A is a flow chart of a method for acquiring data for CUI predication performed using an investigative kit according to an embodiment of the present invention.

[0031] FIG. 5B is a flow chart of a method of real time CUI prediction according to an embodiment of the present invention.

[0032] FIG. 6 is a flow chart of a method of using a machine learning system to optimize deployment conditions for deploying investigative kit for CUI detection according to an embodiment of the present invention.

[0033] FIG. 7A is a flow chart for optimizing a time of year for corrosion detection according to an embodiment of the present invention.

[0034] FIG. 7B is a flow chart for optimizing a time of day for corrosion detection according to an embodiment of the present invention.

[0035] FIG. 7C is a flow chart for optimizing investigative kit position, orientation and image capture duration for corrosion detection according to an embodiment of the present invention.

[0036] FIG. 7D is a flow chart for optimizing investigative kit position, camera type and number of images captured for corrosion detection according to an embodiment of the present invention.

[0037] FIG. 8A is an exemplary graph of predictive accuracy of corrosion versus time of year.

[0038] FIG. 8B is an exemplary graph of predictive accuracy of corrosion versus time of day.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS OF THE INVENTION

[0039] Embodiments of the present invention provide a predictive approach for detecting corrosion under insulation (CUI) taking into account dependent and independent surrounding variables. Thermal images of investigated assets are captured over time.

[0040] As a series of thermal images of the same or overlapping area(s) are captured over time, changes in phenomena can be readily observed, including the impact of temporary issues such as wind. The thermal images can provide several types, or orders, of temperature information that can be indicative of locations vulnerable to CUI. The first order of temperature information is regular temperature (T) data revealed by the color shown in the thermal images. The second order of temperature information is changes in temperature (δT), such as the contrasts shown between different regions, and a third order of information is rate of change in temperature analytics ($df(T)/dt$) as determined by analysis of a series of images over time. Additional evaluations are performed with an independent non-destructive testing (NDT) technique, such as, for example, electromagnetic detection at other portions of the EM spectrum, or

magnetometry, to determine correlative relationships. This "sensor fusion" increases the accuracy of CUI detection, shadow detection, or abnormal process activities, the effects of which can be minimized. Ambient condition data such as the time of day, weather, process conditions, etc. can be included as parameter inputs to machine learning algorithms that are used to generate conclusions from the multiple sources of input. Additionally, in some embodiments, to reduce the effects of "noise" in the thermal images caused by shadows, reflections or other artifacts, a noise filter can be employed as a preprocessing step.

[0041] Through the combination of sensor fusion and time-based analysis non-determinative or confounding variables can be excluded, allowing the learning algorithms to zero-in on anomalies that are contrary to ambient conditions, and thus are more likely indicative of CUL. Such anomalies are recorded; afterwards field engineers can perform a verification inspection upon the locations where such anomalies occur. The results of the field inspection (i.e., a "CUI verified" or "CUI not verified") can be stored locally or on cloud-based platforms and used to train supervised machine learning systems, enabling the systems to become more 'intelligent' over time as parameters (weights, factors) are refined over time by a continually more encompassing data set.

[0042] FIG. 1 is a schematic illustration of a machine learning system 100 for prediction and detection of CUI according an embodiment of the present invention. FIG. 1 shows an exemplary structure 105 to be tested, in this case a set of insulated pipes. The insulated pipes of this example can comprise a metallic pipe conduit surrounded by one or more layers of insulation. Corrosion, when it occurs, tends form in the annular region between the insulation and the metallic pipe where moisture can become trapped and accumulate. In FIG. 1, one or more infrared cameras 110 (only one camera is shown in the figure) are situated proximally to the structure 105 to capture infrared radiation and record thermal images emitted from the structure. One example of a suitable infrared camera for CUI detection is the C3 Wi-Fi enabled thermal camera supplied by FLIR Systems, Inc. of Wilsonville, Oregon, although other devices can also be used. The thermal images captured from the structure 105 can reveal internal thermal contrasts within the structure that are undetectable in the visible spectrum radiation and can be indicative of moisture accumulation and/or corrosion. The infrared camera 110 preferably captures thermal images received from regions of the structure continuously over a selected duration, and/or intermittently at different times or dates. Infrared camera 110 is adapted to convert the thermal images into a standardized computer-readable file format (i.e., thermograph files, jpgs).

[0043] The infrared camera 110 is positioned on a mount 112, which as described in greater detail below, can be "smart" and have a variety of components and functions. In some embodiments, the mount can be implemented as a tripod. The mount 112 can be extendable to reach high elevations on the structure (e.g., by telescoping) and can include a mechanical head
5 fixture coupling to the camera that has several degrees of freedom to pan and tilt at various angles with respect to a fixed plane. Field technical personal can set the extension and orientation of the mount head to capture thermal images from different areas of the structure, as required.

[0044] In some facilities, identification tags can be posted on assets, or portions thereof. The
10 precise geographical location of each tag can be determined using GPS. The identification tags can be implemented using image-based tags such as QR codes that are readable from a distance. To take advantage of the tagging feature, in some embodiments, a standard camera can be included along with the infrared camera on the mount to scan tags on the assets. Depending on the size of tags (of known size) in the image, distances from the camera to the tags can be
15 determined. Tagging enables simultaneous scanning and localization of the facility assets without the need to create complex three-dimensional CAD models of the facility.

[0045] The infrared camera 110 can be physically and communicatively coupled to the mount 112 (e.g., wirelessly by Bluetooth or Wi-Fi communication). The mount 112 also includes or is coupled to one or more additional detectors, such as a visible light sensor (regular camera),
20 or an electromagnetic sensor (not shown in FIG. 1), which can be used to probe the structure and obtain supplemental readings to complement the data obtained by thermal imaging. In this manner, data from two or more distinct and independent sensing modes can be combined, referred to as "sensor fusion", that can make downstream prediction and detection much more robust by reduction of false positive classifications. The mount 112 also includes sensors for
25 detecting ambient conditions including temperature, humidity, and air pressure. Received thermal images can be associated with the ambient conditions and the current time at which the ambient conditions are recorded. This data comprises parameters used by the machine learning algorithms that contribute to the interpretation and classification of the thermal images captured from the structure.

[0046] In some embodiments, the mount 112 can be communicatively coupled to a computing
30 device 115, which can be a tablet, laptop or any other suitable computing device with sufficient processing and memory capability that can be conveniently taken onsite in the field for use by field technical professionals. In such embodiments, the mount 112 is operative to transmit

thermographic files received from the camera 110 to the computing device 115. In other embodiments, data stored by the infrared camera 110 and other sensors of mount 112 can be stored locally, for example in a memory card, and then transferred to computing device 115. The computing device 115 preferably stores executable applications for predictive analysis.

5 Prior to predictive analysis, the thermal images can be preprocessed by the infrared camera 110 and/or the computing device 115. Preprocessing can include image filtering steps for reducing noise in the images that can arise from many causes. The computer device also executes one or more machine learning algorithms that take the received thermograph files (thermal images) as inputs and output a prediction as to the probability that the thermal images contain anomalies
10 of interest in real time. As discussed in related commonly-owned application, U.S. Patent Application Serial No. 15/712,490, entitled "Thermography Image Processing with Neural Networks to Identify Corrosion Under Insulation (CUI)", a plurality of machine learning algorithms, including deep learning algorithms can be used for CUI detection. In some implementations, convolutional networks, which are useful for classifying images in detail, are
15 used in a first stage, and recurrent neural networks, which are useful for tracking changes over time, are used in an additional stage. The computing device 115 provides the output of the machine learning algorithms in an application user interface that can be conveniently consulted by field technical personnel. Real time predicative analysis in the field allows field technical personal to support observations and focus rapidly on high-risk areas of the structure that are
20 more likely subject to corrosion damage.

[0047] In the depicted embodiment, the computing device 115 communicates wirelessly via a network switch 120 (via wireless communication network 122) with a cloud computing platform 125. Alternatively, the computing device can be coupled via a wired connection to a computer network and to cloud computing platform 125. Wireless network 122 can be a
25 wireless local area network (WLAN), wireless wide area networks (WWAN), cellular networks or a combination of such networks. The cloud computing platform 125 comprises computing resources, typically dynamically allocated, including one or more processors (e.g., one or more servers or server clusters), that can operate independently or collaboratively in a distributed computing configuration. The cloud computing platform 125 includes database storage
30 capacity for storing computer-executable instructions for hosting applications and for archiving received data for long term storage. For example, computing device 115 in the field can upload all thermal image and other data received to the cloud computing platform 125 for secure storage and for further processing and analysis. More specifically, the computing device 115

can format and send data records in, for example, MySQL or another database format. An example database record can include, among other fields, a tagged asset location, a series of thermal images taken over time at a particular asset location (or a link thereto), the data value for the camera's ID (cameraID) of the camera that captured the thermal images, the time/date at which each image was captured, ambient conditions at the time/date (e.g., temperature), sensor fusion data (e.g., visible light, electromagnetic data). The cloud database can store include a detailed geographical mapping of the location and layout of the infrastructure assets (e.g., from LiDAR data) and applications executed on the cloud platform can perform detailed analyses that combine the sensor data and predictive analyses with the detailed mapping of the assets to make risk assessments covering entire structures or groups of structures. Reports of such assessments and results of other processing performed at the cloud computing platform are accessible to a control station communicatively coupled to the cloud computing platform. In alternative embodiments, it is possible for the smart mount 112 to format and transmit the received data to the cloud computing platform directly before analysis of the data is performed on site.

[0048] FIG. 2 depicts an exemplary implementation of a cloud-based learning system for CUI prediction and detection more generally shown in FIG. 1. In FIG. 2, this system 150 includes four sets of cameras, mounts and computing devices ("investigative kits") positioned at various positions in proximity to structure 105 for capturing thermal image and other data. Although four investigative kits are used in this embodiment, it is again noted that fewer or a greater number of kits can be employed depending, for example, on the size of the structure or installation investigated. More specifically, the system 150 is configured using a first infrared camera 152 associated with a first mount 154 and first computing device 156 positioned at a first location; a second infrared camera 162 associated with a second mount 164 and second computing device 166 positioned at a second location; a third infrared camera 172 associated with a third mount 174 and third computing device 176 positioned at a third location; and a fourth infrared camera 182 associated with a fourth mount 184 and fourth computing device 186 positioned at a fourth location proximal to the asset 105. Two-way wireless communications can be supported by all the mounts and computing devices of the system, each of which can thus communicate with each other. For example, thermal image data received by the computing devices 156, 166, 176, 186, can be transmitted to the cloud computing platform 125 via network switch 120, and to control station 130. Alternatively, the smart mounts 154, 164, 174, 184 can communicate directly with the control station when wireless connectivity is

available. By providing redundant connectivity, each smart mount or computing device in the system can act as a communication node in a multi-node system, so that if one or more of the mounts or computing devices loses connectivity with the control station, data can be forwarded to other nodes that maintain connectivity. The control station 130 is configured to provide configuration and control commands to the smart mounts 154, 164, 174, 184 or computing devices 156, 166, 176, 186.

[0049] To take readings from numerous structures and locations in a facility, the investigative kits can be moved manually or automatically. As the kits are moved to different positions, infrared images and other sensor readings are obtained over a range of points in a given space (i.e., a Cartesian space, x , y and z) and are provided to the computing device for processing as described herein. For example, the sensor data can initially produces sets of vector data $(x_1, y_1, z_1, i(\text{sensor})_1) \dots (x_n, Y_n, Z_n, i(\text{sensor})_n)$ for the sensor data and $(x_1, y_1, z_1, i(\text{inf})_1) \dots (X_n, Y_n, Z_n, i(\text{inf})_n)$ for the infrared image data. The two sets of data can be combined in a single vector, i.e., $(x_n, Y_n, Z_n, i(\text{sensor})_n, i(\text{inf})_n)$, when the data is captured from substantially the same location (i.e., there is no offset, or there is a finite offset, between the areas sensed by the non-infrared and infrared sensors, respectively). As described further below, for each pair of sensing modes (or more than two modes) for a given location, the computing system makes a prediction as to whether the asset location has been subject to corrosion. The data mappings are thereby supplemented with a prediction obtained by feeding a prediction engine with a model such as, for example, $(x_n, Y_n, Z_n, i(\text{THZ})_n, i(\text{inf})_n, \text{Prediction}_n)$. As predictions are determined over a large three-dimensional space at a facility, in some instances "hot" areas in which several data points in the same vicinity are associated with a positive prediction of corrosion can be identified. Likewise, contiguous areas in which comparatively less or no corrosion has been predicted can also be identified. Remedial measures can then be applied to such hot areas and not to the other areas in which comparatively less corrosion has been determined. In this manner, insulation removal and other remedial measures can be performed on specific sections in which there is a high probability of corrosion damage, eliminating the need to remove sections of insulation randomly or according to a statistical pattern to determine the presence of corrosion.

[0050] FIG. 3 is a block diagram showing functional elements of a smart mount according to an exemplary embodiment of the present invention. The smart mount 112 includes a camera coupling or mount 202 by means of which the infrared camera 110 can be securely mechanical affixed and electrically connected to the mount 112. As noted above, the camera coupling 202

can include expandable and rotatable elements, such as telescoping shafts, and various joints with degrees of freedom for enabling the camera to be translated and tilted to a desired position and orientation. In some implementations, the smart mount can be supported on a counterweighted movable to provide a steering sub-system on the ground.

5 **[0051]** To enable inter-communication with other elements of the system, the smart mount 112 can include a communication module 204 which can include an antenna, a transceiver, and electronic components configured to support two-way wireless communication with other smart mounts, computing devices, and the control station 130. The smart mount 112 also includes a memory module 206 which can be implemented using SSD card memory. If the
10 infrared cameras are mounted in locations where signal obstructions result in suboptimal data rates that are inferior to the actual thermal image streaming rate, the onboard memory module can be used to store the thermal image stream to provide latency while the wireless attempts to support the data download.

[0052] The smart mount 112 further includes an ambient sensor module 210 that can include
15 temperature, humidity and pressure sensors. An additional structural probe sensor module 212 includes detectors that can be used to probe the structure for CUI using modes distinct from thermal imaging, including, without limitation, visible photography, magnetic (magnetometry) and ultrasonic detectors. Together with the thermal images from the infrared camera, the structural probe sensor module provides the sensor fusion that enhances CUI prediction and
20 risk assessment. An electrical power module 220 includes a battery module 222 of sufficient size to provide electrical power for the smart mount components and to charge the infrared camera battery via a power supply circuit 224 for a suitable data gathering period before requiring recharging. A suitable duration for data gathering can be for example, about 45 minutes to about 90 minutes. Larger or smaller batteries can be employed for longer or shorter
25 data gathering periods.

[0053] In operation, the field computing devices receive (ingest) thermal image, probe sensor and ambient condition data from the infrared cameras and smart mounts. The initial data ingest can be affected by conditions at the site, including, shadows, reflections and spurious signals. As noted above, before executing machine learning algorithms, it can be useful to filter
30 incoming data for noise using noise filtering mechanism integrated within software (or firmware or hardware if the filtering mechanism is implemented in the infrared camera) as a preprocessing step to filter out noise and amplify the signal-to-noise ratio. In some embodiments, ingested data can be filtered by dimensionality reduction and autoencoding

techniques. In other embodiments, linear or non-linear smoothing filters can be applied instead of or in addition to dimensionality reduction techniques. The noise filtering step helps discriminate CUI signals from shadows, reflections as well as normal near infrared thermal signals. While such noise and other artifacts in the data can be eventually recognized and compensated for in the machine learning process using multi-context embedding in the neural network stage, it can be more time and resource efficient to preprocess the data by filtering in this manner.

[0054] Another refinement which can be used to enhance robustness to noise, is the introduction of synthetic training data to supplement data taken from the field. Mathematical models including finite element analyses are based on the thermal dynamics of insulated metal structures and on thermal images taken in the field as a basis for calibration and comparison. The synthetic data can be to simulate and augment the thermal image training dataset. The synthetic data can also make the learning system more robust to different environmental conditions such as weather conditions, temperature, exposure to sun light, and material temperature behind the insulation, for example. The synthetic data can be generated locally by the computing devices or the cloud computing platform. In either case the synthetic data can be incorporated in the training and application database at the cloud computing platform.

[0055] FIG. 4 is a block flow diagram illustrating a method for generating synthetic thermal image data structures according to the present invention for supplementing a training set for a predictive machine learning model. The inputs for generating synthetic thermal images include environmental variables 302 (e.g., temperature, humidity, air pressure, time of day), asset parameters 304 (e.g., dimensions, position, material, insulation), and a set of thermal images 306 of various assets captured in the field ("field thermographs"). The environmental variables 302 and asset parameters 304 are input to a thermal dynamics model 310 that uses known thermodynamic properties of materials based on environmental conditions to generate a synthetic temperature map 315 of insulated assets over time, based on a random probability distribution of temperature and humidity conditions. The synthetic temperature map 315 and the field thermographs are inputs to an imaging model 320. While images can be created from the temperature map alone, the field thermographs can be used as a basis of calibration and comparison. As an example, if a temperature maps of assets exhibits a tendency toward greater temperature contrasts than shown in field thermographs of similar asset under similar conditions, the imaging model can make weighting adjustments to bring the temperature map closer to the field thermographs. After such adjustments are made, the imaging model

generates a set of synthetic thermal images 325 that can be used to supplement the field thermographs during training.

[0056] FIG. *SA* is a flow chart of a method for acquiring data for CUI predication performed using an investigative kit according to an embodiment of the present invention. The method
 5 begins in step 400. In step 402, smart mounts and cameras (infrared, standard) are installed at suitable locations to monitor assets at a facility. In step 404, any tags posted on the assets are scanned. In step 406, thermal image, sensor fusion, and ambient condition data are captured and stored in memory. In step 408, this information is transmitted to a local computing device for real time analysis. The method ends in step 410.

10 [0057] FIG. *SB* is a flow chart of a method of real time CUI prediction according to an embodiment of the present invention. In step 500 the method begins. In step 502, the computing device receives the captured data from the smart mounts. In step 504, the received data is filtered for noise. In step 506, CUI prediction and detection is conducted using machine learning algorithms based on the filtered data and parameter weights from prior training. The
 15 machine learning algorithms can include deep learning techniques such as convolutional and recurrent neural networks. In an optional step 508, synthetic data is generated to supplement the data received from the smart mounts. In step 510, prediction output is generated on a graphical user interface to be viewed by field technical personnel. In a following step 512, the received data and the prediction output is transmitted to the cloud computing platform. In step
 20 514, the method ends.

[0058] FIG. 6 is a flow chart of a method of using a machine learning system to optimize deployment conditions for deploying investigative kit for CUI detection according to an embodiment of the present invention. The method starts in step 600. In step 602 infrared images and other sensor fusion data are input to the system. In step 604, result data (images)
 25 of conventional invasive corrosion testing is input to the system. The results data is used to correlate the infrared and other data with actual results in the field in order to train the system to correlate certain observed conditions with the presence or absence of corrosion.

[0059] At step 606, the machine learning system receives the input data and determines whether to apply the data for training versus testing. In training, the machine learning system
 30 applies the data to optimize parameters for correlating the image and sensor data with the results data. In other words, training attempts to match the results (presence or absence of corrosion) with certain types of infrared image data and other sensor data received over time.

The optimized parameters can be coefficients that are applied to the different orders of temperature data, such as one or all of temperature (T), static or dynamic temperature contrasts (T), or rates of change in temperature analytics ($df(T)/dt$). Additionally, the parameters can include deployment characteristics of the of the investigative kit, as will be described further below. In contrast, during testing, the machine learning system uses current data or different data from the data that was used for training, to determine whether the trained system is robust and is applicable to a wide variety conditions. If it is determined by the processor executing instructions configured to implement this algorithm, in step 606, that the data is to be used for training, the data is used, in step 608, in a machine learning algorithm. In step 610, the machine learning algorithm generates a trained neural network with parameters optimized based on the input data. If it is determined by the processor executing instructions, in step 606, that the data is to be used for testing, in step 612 the data is applied to test the robustness of the optimized parameters generated in step 608. In order to test the data in step 612, in step 614 temporal condition data (i.e., time., date, temperature($t_1, t_2, \dots t_n$), humidity($t_1, t_2, \dots t_n$), wind speed($t_1, t_2, \dots t_n$)) obtained as a time series over a period by the investigative kit in the field is also used as an input during testing along with new IR image and result data.

[0060] In step 616 it is determined by the processor executing instructions whether the performance of the machine learning algorithm, using the temporal ambient condition data 614 and current IR images 602 and results data 604, exceeds a preset threshold. The preset threshold for determining efficacy of the test performance can be a set percentage of accurate predictions of the machine algorithm based on the test data (e.g., 90%) that match result data. If the threshold is reached, it is determined in step 618 that the parameters, such as deployment conditions, have been optimized. The method then ends in step 620. If the test does not meet the threshold, the method reverts back to steps 602, 604 and 614, in which data is obtained for another iteration of training and testing.

[0061] FIGS. 7A, 7B, 7C, and 7D are flow charts, based on the flow chart of FIG. 6, for optimizing particular deployment conditions for determining corrosion at a facility site. The flow chart of FIG. 7A is identical to the flow chart of FIG. 6 except that in step 708, which is analogous to step 608 in FIG. 6, the machine algorithm optimizes performance using the time of year of testing as a deployment condition variable. The time of year during which a test is performed determines, at least in part, the angle of incident sunlight upon the investigated structures, and also partially determines the rate at which the structures heat up or cool down due to the intensity of incident sunlight. Additionally, the time of year can determine the level

of humidity (for example, humidity can vary in a seasonal manner). Due to the relationship between time of year and ambient temperature and humidity conditions, the time of year of deployment of the investigative kits can affect the accuracy of corrosion detection. It would therefore be useful for engineers to know what times of year that are optimal for corrosion testing. This can be determined through the machine learning algorithms using programming in the processor to implement, for instance, recurrent neural networks. In step 718, after it is determined by the processor executing instructions whether the test data has exceeded the threshold for performance, the optimal times of year can be determined and reported as an output of the machine learning and testing process. FIG. 8A is an exemplary graph of performance versus time of year and shows that over a portion of the year 802 (covering a part of summer and most of autumn) in which the performance is above a preset accuracy threshold (e.g., 85%). The graph of FIG. 8A indicates that late summer and autumn are, in general, the best times for performing corrosion testing of structures in the field. It is noted that the example graph shown in FIG. 8A is merely illustrative of the principles of the present invention and is not meant to represent that these times of the year are actually optimal in this regard.

[0062] FIG. 7B is similarly identical to the flow chart of FIG. 6 except that in step 728, which is analogous to step 608 in FIG. 6, which is analogous to step 608 in FIG. 6, the machine algorithm executes code which optimizes performance using the time of day of testing as a deployment condition variable. Like the time of year, the time of day partially determines the intensity of sunlight and level of humidity. For the similar reasons as for time of year, it would therefore be useful for engineers to know what times of day are optimal for corrosion testing. In step 738, after it is determined by code executing in the processor whether the test data has exceeded the threshold for performance, the optimal times of day for can be determined and reported as an output of the machine learning and testing process. FIG. 8B is an exemplary graph of performance versus time of year and shows that over a portion of the day 804 (covering the middle of the day) the performance is above a preset accuracy threshold (e.g., 85%). The graph of FIG. 8B indicating that the middle of the day in a range from a few hours before to a few hours after noon is, in general, the best time for performing corrosion testing of structures in the field. It is noted that the example graph shown in FIG. 8B is also merely illustrative of the principles of the present invention and is not meant to represent that these times of the day are necessarily optimal in this regard.

[0063] FIG. 7C is a flow chart of a method for optimizing investigative coverage of an area by optimizing the position of the cameras of the investigative kits, and/or the duration of camera

utilization. In the field the infrared cameras and other devices can be arranged at various distances and angles with respect to the structure(s) of interest. Moreover, the amount of time that the infrared camera or other sensors acquire data from a particular section can vary based on user settings. Some arrangements can be more conducive to obtaining high-quality thermal images than others. In some implementations, there can be a minimum period required for exposure under which the infrared images obtained are of lower quality. On the other hand, overly long camera exposure times can increase the overall duration and cost of the investigation. In the flow chart of FIG. 7C, for the purpose of training, the infrared data input in step 742 includes metadata in addition to image data. The metadata can include the positions of each infrared camera in the investigative kits at different times, the angular position (orientation) of each camera at such times measured against reference axes, as well as the image capture duration. This metadata can be associated with the captured thermal images taken at each time increment. In step 748, a machine algorithm is executed using the input training data. In some embodiments, the machine learning algorithm is configured by code executing in the processor to optimize the parameters based on predictive accuracy (i.e., the ability to detect corrosion correctly based on the input data and result data). If in step 756, it is determined during testing of the trained algorithm using temporal testing data that performance is below a threshold, commands can be given in step 758 to automatically move the position and angle of one or more of the cameras incrementally into a new position so as to adjust the coverage of the structure by the cameras. In step 760, new infrared image data is acquired. Additionally, the image capture duration can be incremented. The deployment conditions can be incremented in series (one at a time) to better distinguish their effects. In some implementations, the cameras can be moved manually by field technical personnel. The incrementing of the deployment conditions can be done iteratively in a loop until the performance exceeds a threshold in step 756.

[0064] Once the performance exceeds the threshold, in step 762 the position, angle and exposure time variables can be considered optimized for prediction of corrosion at the preset accuracy threshold. This does not necessarily mean that the arrangement determined in step 762 is the absolute optimal arrangement for acquiring structural data. To determine the absolute optimal arrangement a series of tests can be performed, and the results compared.

[0065] FIG. 7D is a flow chart of a method for optimizing the number of infrared images acquired based on camera type, location and climate conditions. During investigation, different types of infrared cameras (e.g., cameras with aperture sizes and resolutions) can be used in the

investigative kits and the positions of the cameras can be varied in different arrangements. Furthermore, depending on the investigative kit arrangements and ambient conditions, the number of images required to obtain sufficient coverage and/or clarity can change. In the flow chart of FIG. 7D, for the purpose of training, the infrared data input in step 772 includes

5 metadata in addition to image data. The metadata can include the positions of each infrared camera in the investigative kit at different times, the type of each camera deployed, and the number of images captured by the cameras at each position. The metadata can be associated with the thermal images. In step 778, a machine algorithm is executed using the input training data. The machine algorithm optimizes performance using the infrared image metadata (i.e.,

10 position of camera n (x_n, Y_n, Z_n) at times $t_1, t_2, b \dots$, the type of camera n Typ_n and the number of images acquired by each camera n at times t_1, t_2, b . If in step 786, it is determined during testing of the trained algorithm that performance is below a threshold, commands can be given in step 788 to automatically modify the position of one ore more of the cameras and/or repeat data acquisition by one or more of the cameras of a different number of images. In step 790,

15 new infrared image data is acquired using the incremented position and/or number of captured images. Alternatively, the cameras can be moved manually by field technical personnel. This can be done iteratively in a loop until the performance exceeds a threshold in step 776.

[0066] Once the performance exceeds the threshold, in step 792 the position, camera type and number of capture images variables can be considered optimized sufficiently for prediction of

20 corrosion at the preset accuracy threshold. This does not necessarily mean that the arrangement determined in step 792 is the optimal arrangement for acquiring structural data. To determine the optimal arrangement a series of tests can be performed, and the results compared.

[0067] In the embodiments described above with respect to FIGS. 7A, 7B, 7C and 7D, the machine learning algorithm is design to optimize corrosion detection accuracy (i.e., the cost

25 function of the algorithm is the discrepancy between predicted results and actual results). In other embodiments or implementations, other parameters such as the speed of the test, and the cost of the test in monetary terms can be the optimized variable so that machine learning training and tests can be performed to determine faster and/or less expensive ways of arranging or using the investigative kits of the corrosion detection system.

30 **[0068]** It is to be understood that any structural and functional details disclosed herein are not to be interpreted as limiting the systems and methods, but rather are provided as a representative embodiment and/or arrangement for teaching one skilled in the art one or more ways to implement the methods.

[0069] It is to be further understood that like numerals in the drawings represent like elements through the several figures, and that not all components and/or steps described and illustrated with reference to the figures are required for all embodiments or arrangements

[0070] The terminology used herein is for describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising", when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0071] Terms of orientation are used herein merely for purposes of convention and referencing and are not to be construed as limiting. However, it is recognized these terms could be used with reference to a viewer. Accordingly, no limitations are implied or to be inferred.

[0072] Also, the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of "including," "comprising," or "having," "containing," "involving," and variations thereof herein, is meant to encompass the items listed thereafter and equivalents thereof as well as additional items.

[0073] While the invention has been described with reference to exemplary embodiments, it will be understood by those skilled in the art that various changes can be made and equivalents can be substituted for elements thereof without departing from the scope of the invention. In addition, many modifications will be appreciated by those skilled in the art to adapt a particular instrument, situation or material to the teachings of the invention without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiment disclosed as the best mode contemplated for carrying out this invention, but that the invention will include all embodiments falling within the scope of the appended claims.

CLAIMS

1. A system for predicting and detecting of corrosion under insulation (CUI) in an infrastructure asset using machine learning and data fusion comprising:

at least one infrared camera positioned to capture thermal images of the asset;

5 at least one smart mount mechanically supporting and electrically coupled to the at least one infrared camera and having a position that is adjustable with respect to the asset, the at least one smart mount including:

a communication module;

10 memory storage adapted to store thermal image data received from the at least one camera;

a battery module operative to recharge the at least one infrared camera;

an ambient sensor module adapted to obtain ambient condition data; and

at least one additional sensor adapted to obtain CUI-related data from the asset;

15 at least one computing device having a processor, the computing device being configured with instructions for executing a machine learning algorithm in the processor which receives input from either the communication module or memory storage of the at least one smart mount comprising: (a) thermal images of the asset; (b) the ambient condition data; (c) CUI-related data from the at least one additional sensor; and (d) results of prior CUI tests, and which outputs a CUI prediction regarding the asset; and

20 a machine-learning platform adapted to train the machine learning algorithm based on accumulated input data received from the at least one computing device over time,

in which the inputs to the machine learning-platform comprise sensor data from at least two sources that detect CUI-related data including the at least one infrared camera and the at least one additional sensor, which combination of data from the at least two
25 sources of sensor data provides data fusion.

2. A system according to Claim 1, in which the at least one computing device is adapted to test current deployment conditions of the at least one infrared camera and at least one smart mount by executing the machine learning algorithm using current infrared images, ambient

sensor data and CUI-related data by determining whether performance of the machine learning algorithm under current deployment conditions meets a threshold level.

3. A system according to Claim 2, in which the performance of the machine learning algorithm conditions is measured by at least one of:

- 5 corrosion prediction accuracy;
- a cost of deployment and testing; and
- a speed of deployment and testing.

4. A system according to Claim 2, in which the current deployment conditions tested by the at least one computing device include a time of year in which the at least one infrared
10 camera and at least one smart mount are deployed or a time of day in which the at least one infrared camera and at least one smart mount are deployed.

5 A system according to Claim 2, in which the current deployment conditions tested by the at least one computing device include a position, orientation and image capture duration of the at least one camera.

15 6. A system according to Claim 2, in which the current deployment conditions tested by the at least one computing device include a position, type and number of images captured per time period of the at least one camera.

7 A system according to Claim 1, in which the at least one smart mount includes a fixture for supporting the infrared camera, the fixture being rotatable and extendable to enable the
20 infrared camera to be translated and tilted.

8. A system according to Claim 1, in which the at least one smart mount further includes a standard camera operative to scan the identification tags that appear on the asset.

9. A system according to Claim 1, in which the at least one additional sensor comprises a magnetic sensor.

25 10. A system according to Claim 1, further comprising a control station communicatively coupled to the at least one smart mount and adapted to transmit configuration and control commands to the at least one smart mount.

11. A system according to Claim 1, in which the deep recurrent neural network is a long short term memory (LSTM) network.

12. A system according to Claim 1, in which the at least one computing device is configured to perform noise reduction on the data received from the at least one smart mount.

5 13. A system according to Claim 1, in which each of the at least one smart mounts can communicate with each other via their respective communication modules.

14. A method of predicting corrosion-under-insulation (CUI) in an infrastructure asset using data fusion, comprising:

10 receiving a stream of data including thermal images of the asset, additional sensor probe data of the asset, and ambient conditions at the asset;

executing, in real time, one or more machine learning algorithms using the received stream of data and weights received a database to generate a prediction as to whether the asset contains CUI; and

transmitting the received stream of data and prediction to the database,

15 in which the one or more machine learning algorithms include a supervised machine learning algorithm obtained by training at least one of a convolution neural network and a deep recurrent neural network using a training data set comprising, for a plurality of assets, (i) thermal images of each asset, (ii) additional sensor probe data of each asset, (iii) ambient conditions at each asset, and (iv) known CUI results data.

20 15. A method according to Claim 14, further comprising filtering the received data for noise.

16. A method according to Claim 14, further comprising generating synthetic thermal image data based on ambient conditions and parameters of the asset using a thermal dynamic model.

25 17. A method according to Claim 16, in which, at the database, the synthetic thermal image data is combined with the stream of data including thermal images of the asset, additional sensor probe data of the asset, and ambient conditions at the asset to create the training data set.

18. A method according to Claim 14, in which the deep recurrent neural network includes a long short memory network (LSTM).