

IN THE UNITED STATES RECEIVING OFFICE
INTERNATIONAL PATENT (PCT) APPLICATION

5 Title: **FLOATING BIOREACTOR SYSTEM**

Applicant(s): **EROS G. KAW**

10 Inventor(s): **EROS G. KAW**

Filed by:

15 SHAHANI, Ray K., Esq.
RAY K. SHAHANI ATTORNEY AT LAW
Twin Oaks Office Plaza
477 Ninth Avenue, Suite 112
San Mateo, California 94402-1854
U.S.A.
20 Registration No.: 37,554
Customer No.: 46770

Tel: (650) 348-1444
Fax: (650) 348-8655
25 E-mail: rks@attycubed.com

RELATED APPLICATION(S)

This PCT Application claims all benefits applicable under 35 U.S.C. § 119(e) related to U.S. Non-provisional Patent Application Serial No. 12/982,669 filed on December 30, 2010 entitled “FLOATING BIOREACTOR SYSTEM”, which is a U.S. Non-provisional Patent Application related
5 to U.S. Provisional Patent Application Serial No. 61/317,715 filed March 26, 2010 entitled “FLOATING BIOREACTOR SYSTEM”, and incorporates both U.S. Provisional Patent Application Serial No. 61/317,715 and U.S. Non-provisional Patent Application Serial No. 12/982,669 in each of its entirety herein by reference.

10 ///

FIELD OF THE INVENTION

The present invention pertains to an aeration device and microbial bioreactor system for use in a liquid medium. More specifically, the invention relates to floating bioreactor systems that can be adapted to applications for treatment of water, leachate and industrial waste in rivers, streams and
5 creeks, as well as water in aquariums and domestic septic systems.

///

BACKGROUND OF THE INVENTION

Subsurface aeration seeks to release bubbles at the bottom of the pond and allow them to rise by the force of gravity. Diffused aeration systems utilize bubbles to aerate as well as mix the pond. Water displacement from the expulsion of bubbles can cause a mixing action to occur, and the contact between the water and the bubble will result in an oxygen transfer.

Bioreactors are also designed to treat sewage and wastewater. In the most efficient of these systems there is a supply of free-flowing, chemically inert media that acts as a receptacle for the bacteria that breaks down the raw sewage. Aerators supply oxygen to the sewage and media further accelerating breakdown. In the process, the liquids Biochemical Oxygen Demand BOD is reduced sufficiently to render the contaminated water fit for reuse. The biosolids are collected for further processing or dried and used as fertilizer, agricultural feed, etc.

Subsurface aeration, bioreactors and most likely a combination of both are commonly employed to treat sewage water, recycle wastewater and other water treatment applications both industrially or domestically.

///

ADVANTAGES AND SUMMARY OF THE INVENTION

The present invention relates to a system that consists of an apparatus for aerating and circulating a liquid medium and at the same time an apparatus for the continuous microbial bio-remediation of organic waste in rivers, sewers and other waste laden environments utilizing in-situ microbial seeding.

The present invention is a microbe bio-reactor designed to work in open water such as lakes and ponds and in lagoons and tanks to clean up water biologically. It can clean tip water in a short amount of time and will be energy efficient. It works by having imbedded microbes in, and these are stores in its main reactor chamber that is a slotted pipes.

The core of its main reactor chamber is a perforated hose. Air is pumped into the perforated hose and is released all along the pipe. The air is diffused in the water surrounding this and this causes the water to rise and it circulate the microbe with the dirty water. This feeds the microbes imbedded in the media and this causes the microbes to replicate and thus releasing billions of microbes every second. As the microbes are release upward it is oxygenated greatly by the main hose diffusers and this causes the microbes to multiply even much more.

At the top of the water, the water is pushed out and is mixed causing even more microbial growth. At the surface of the water, it again is exposed to the atmosphere and is not only evenly spread out, it is again oxygenated and thus multiplying organisms even more.

The microbes create an even larger zone of air and/or oxygen transfer to the water, thus facilitating even more microbial growth. Thus, all along the water flow cycle, the present invention generates even more microbes in the expense of minimum electricity usage of the approximate range of 2HP.

As the water is pulled down under the tank or water body, it pulls down not only microbes but increases dissolved oxygen such that microbial growth at the bottom of the tank or water body is greatly enhanced. Thus, water is cleaned and revived. In addition, the process removes hydrogen sulfide present in the contaminated water or other liquid medium. The process also reduces methane, a green house gas, formation to help preserve the environment.

An advantage of the present invention is that biosolids and/or sludge handling is eliminated. The biosolids are eaten up and consumed by the microbes, thus eliminating the need for sludge and biosolids handling equipment, disposal, etc. In addition, having the microbes on the surface of the water increases the efficiency of oxygen transfer in the bioreactor.

Another object of the present invention is the very small amounts of electricity consumed due to high efficiency which helps to reduce energy consumption.

Another object of the present invention is that the biosafety level one microbes can inhabit the micropores in the rocks and river beds of the streams and keep on improving even after the bioreactor is disengaged although the effect is much better to leave it in place.

Another object of the present invention is that even without expensive membrane filters, the bioreactor can be applied to sewage with results that clean waste water to bod less than 5 or less than 1 and then it is percolated and the treated waste water can recharge ground water.

///

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a representative upper front perspective view of floating bioreactor system **100** of the present invention.

5 FIG. 1B is a representative graph showing the relationship between Standard Oxygen Transfer Rate [SOTR] and various Total Dissolved Solids [TDS] values of the liquid medium.

FIG. 1C is a representative graph showing the relationship between Standard Aeration Efficiency [SAE] and various Total Dissolved Solids [TDS] values of the liquid medium.

10 FIG. 1D is a representative graph showing the relationship between Standard Aeration Efficiency [SAE] and various Salt Concentration [TDS] values of the liquid medium.

FIG. 1E is a representative graph showing the relationship between Standard Aeration Efficiency [SAE] and various Salt Concentration [TDS] values of the liquid medium.

15 FIG. 2 is a representative upper front perspective view of an in situ bioreactor container **200** of floating bioreactor system **100** of the present invention.

20 FIG. 3 is a representative view showing the method of application of the floating bioreactor system **100** of the present invention.

FIG. 4A is a representative view showing one method of adaption of an alternative embodiment, viz. aquarium bioreactor and aerator system **400**.

25 FIG. 4B is a representative side view of bioreactor and aerator combo **401** of aquarium bioreactor and aerator system **400**.

FIG. 4C is a representative side partially exposed view of bioreactor and aerator combo **401** of aquarium bioreactor and aerator system **400**.

FIG. 5A is a representative view showing one method of adaption of an alternative embodiment, viz. home septic bioreactor and aerator system **500**.

FIG. 5B is a representative side view of home septic unit **501** of home septic bioreactor and aerator system **500**.

FIG. 5C is a representative side partially exposed view of home septic unit **501** of home septic bioreactor and aerator system **500**.

FIG. 6A is a representative view showing one method of adaption of an alternative embodiment, viz. aero dynamic mixer bioreactor and aerator system **600**.

FIG. 6B is a representative side view of aero dynamic mixer **601** of aero dynamic mixer bioreactor and aerator system **600**.

///

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The description that follows is presented to enable one skilled in the art to make and use the present invention, and is provided in the context of a particular application and its requirements. Various
5 modifications to the disclosed embodiments will be apparent to those skilled in the art, and the general principals discussed below may be applied to other embodiments and applications without departing from the scope and spirit of the invention. Therefore, the invention is not intended to be limited to the embodiments disclosed, but the invention is to be given the largest possible scope which is consistent with the principals and features described herein.

DEFINITION OF TERMS:

Standard Oxygen Transfer Rate [SOTR] – Pounds of oxygen transferred to water per hour
[lbs O₂ /hour]. SOTR is measured in clean water when the dissolved oxygen [DO] concentration is
zero at all points in the water volume, the water temperature is 20°C, at a barometric pressure of 1.00
15 atm [101kPa].

Standard Aeration Efficiency [SAE] – Standard Oxygen Transfer Rate per unit total power
input. SAE is typically expressed as the pounds of oxygen transferred to the water per hour per HP
[lbs O₂ /hour/HPwire], and is sometimes referred to as SAE Wire. SAE is used as a measure of how
20 efficiently an aerator is transferring oxygen.

FIG. 1A is a representative upper front perspective view of floating bioreactor system **100** of
the present invention. Floating bioreactor system **100** of the present invention has a housing **102**. In
one embodiment, housing **102** is made of fiberglass that is strong enough to support the weight of the
25 entire floating bioreactor system **100** without the assistance of buoyance and is not prone to
corrosion, degradation in the presence of water and/or other liquid medium, including salt water or
waste water with other chemicals. Housing **102** of floating bioreactor system **100** can be assembled

by nuts and bolts or other optimal mechanical fastening means. As shown in FIG. 1A, a plurality of floats **120** are attached to housing **102** on both sides. The main function of floats **120** is to lend buoyance to the entire floating bioreactor system **100** such that the present invention is able to float and maintain an appropriate buoyance level within the liquid medium. Optionally, floats **120** are inflatable or otherwise adjustable so buoyancy and waterline of the overall housing **102** can be adjusted.

As shown in FIG. 1A, blower **104** is placed on top of housing **102**. In one embodiment, blower **104** is a 1.75kW regenerative blower which is an ideal solution for moving large volume of air at lower pressures or near vacuum. The main function of blower **104** is to be an air source for the aeration process of the present invention **100**. Using blower **104** can be one of the most cost effective methods for producing pressure or vacuum. Filter **106** cleans particulate from the air that goes in and through blower **104** to avoid dust or oil in contact with diffuser grids **130**.

As best shown in FIG. 1A, blower **104** is connected to diffuser grids **130** via diverter **150** and subsequently hoses **152**. Hoses **152** are attached to diverter **150** to receive the necessary air for diffuser grids **130**. In one embodiment, diverter **150** spreads the air generated from blower **104** evenly to diffuser grids **130** via a plurality of hoses **152**. The main function of diffuser grids **130** is to create aeration within the liquid medium that the present invention **100** is trying to clean. In alternative embodiments, multiple diffuser grids **130** can be installed and connected to blower **104** to increase overall effectiveness and scale of cleaning power of floating bioreactor system **100** of the present invention.

For efficient aeration system, whether it is an aeration system or device splashes, sprays, or diffuses air, an important factor is how much surface area it creates. The surface area is where water/liquid medium contacts air and where oxygen transfer takes place. Smaller bubble size results in more surface area, which is why fine bubble aeration devices are superior in oxygen transfer than

coarse bubble aerators. To maximize aeration efficiency in a system, an aerator must create fine bubbles while expending a minimum amount of energy. The main purpose is to have a high SOTR and SAE for the aeration system.

5 In one embodiment, there are a number of commercially available diffuser grids **130** that can be incorporated in the floating bioreactor system **100** of the present invention. Most of these models resemble what has been disclosed in US Patent No. 5,811,164, issued September 22, 1998 to Mitchell entitled "AERATION PIPE AND METHOD OF MAKING SAME", which is incorporated herein by reference in its entirety. One of the commercial models is Aero-Tube™ diffuser grids. One of the
10 most important structure for the extremely high performance and efficiency of diffuser grids **130** is the adaptation of hose segments **132** which, through a unique combination of technique and raw material, creates numerous micro-pores **134** throughout the length of hose segments **132**. These micro-pores **134** create tiny air bubbles and hence high surface area, which allows the efficient transfer of air into the water. In one embodiment, diffuser grids **130** are made up of hose segments
15 **132**. Preferably, hose segments **132** are made from thermoset polymer particles in a matrix of thermoplastic binder material, which may be made according to a method described in the '164 patent.

In one embodiment, the specifications of hose segments **132** are in the approximate range as
20 follows: Outside Diameter, 1.00 inch (2.54 cm); Inside Diameter, 0.500 inch (1.27 cm); Wall Thickness, 0.250 inch (0.635 cm); Weight, 0.220 lbs per foot (0.327 kg per meter); Roll Length, 200 ft. (60.98 meters); Roll Weight, 44 lbs. (19.9 kg); Burst Pressure, 80 PSI (5.5 bar).

Due to the number of pores created during the manufacturing process, there is little resistance
25 created when pushing air through hose segments **132**. Resistance equals energy demand hence diffuser grids **130** uses significantly less horsepower when compared with traditional methods of aeration such as bubblers, paddlewheels, aspirators, less efficient tubing, etc. Moreover, diffuser

grids **130** bare tiny pore size which creates bubbles with extremely small diameters. The smaller the gas bubbles, the more efficiently they transfer oxygen into water. Small bubbles also take longer to rise once they are introduced into water. Slower rising, small-diameter bubbles mean more contact with the water and a much higher rate of oxygen transfer. By creating significantly smaller bubbles, more efficiently, diffuser grids **130** are able to deliver high rates of oxygen transfer [SOTR] and energy efficiency [SAE].

As shown in FIG. 1A, bioreactor pump **108** is also mounted on housing **102**. In one embodiment, bioreactor pump **108** is a relatively less powerful pump in the range of about 60W that supplies air to the in situ bioreactor container **200**. Bioreactor hose **140** that connects bioreactor **200** also transfers air from bioreactor pump **108** to the bioreactor **200** for the biocarrier media therein. Air and nutrients are supplied to the microbial population which are located within the biocarrier media. In one embodiment, bioreactor **200** is secured at the bottom of housing **102** and underneath diffuser grids **130** to provide continuous in-situ addition of beneficial microbes directly within an environment to be treated thereby permitting optimized mineralization of waste being treated as well as acclimation of the microbes to such waste.

FIG. 1B is a representative graph showing the relationship between Standard Oxygen Transfer Rate [SOTR] and various Total Dissolved Solids [TDS] values of the liquid medium of both commercial diffuser grids **130** and traditional aeration device like paddle wheel. As best shown in FIG. 1B, diffuser grids **130** performs better than paddle wheel throughout the range of TDS from 0 to approximately 35,0000 mg/L. This demonstrates that using diffuser grids **130** is an effective, improved method for aeration [higher SOTR].

FIG. 1C is a representative graph showing the relationship between Standard Aeration Efficiency [SAE] and various Total Dissolved Solids [TDS] values of the liquid medium of both commercial diffuser grids **130** and traditional aeration device like paddle wheel. As best shown in

FIG. 1C, diffuser grids **130** performs better than paddle wheel throughout the range of TDS from 0 to approximately 35,000 mg/L. Proving that using diffuser grids **130** is a much more cost efficient method for aeration [higher SAE].

5 FIG. 1D is a representative graph showing the relationship between Standard Aeration Efficiency [SAE] and various Salt Concentration [TDS] values of the liquid medium for most common aeration methods including Aero-Tube™. FIG. 1E is a representative graph showing the relationship between Standard Aeration Efficiency [SAE] and various Salt Concentration [TDS] values of the liquid medium for most common aeration methods including Aero-Tube™. An
10 internationally recognized engineering firm conducted performance tests on the aeration tube in both fresh and salt water environments. In a controlled study, they compared an airlift aerator utilizing Aero-Tube™ technology with an equal horsepower paddle wheel and brush paddle wheel aerator, two of the most popular aeration technologies on the market today.

15 Aero-Tube™ performed extremely well in all areas, including its ability to transfer oxygen to water, expressed in terms of a standard oxygen rate [SOTR], and its efficiency in terms of pounds of oxygen per kilowatt-hour [the standard aerator efficiency or SAE Wire, rate].

 In the fresh water testing, the Aero-Tube™ aerator exceeded the paddle wheel's energy
20 efficiency [SAE Wire] by up to 2.6 times.

 Aero-Tube™ aeration tubing performed even better in the salt water test. As the density of the water's salt content increased [from 5,000mg to 35,000 mg], the oxygen advantage of the Aero-Tube™ system steadily rose. At 35,000 mg/L NaCl, the energy efficiency of Aero-Tube™
25 aerator was as much as 4.2 times the efficiency of the paddle wheel.

 While performance of diffuser grids **130** may vary among different brands and models, in

general diffuser grids **130** are considered one of the most effective and cost efficient aeration devices because nearly all of the energy used to deliver the air that goes through hoses **140** and hose segments **132** goes directly into the water/liquid medium. A paddle wheel, wastes energy by throwing water/liquid medium into the air to pick up oxygen.

5

FIG. 2 is a representative upper front perspective view of an in situ bioreactor tube or container **200** of floating bioreactor system **100** of the present invention. In summary, in situ bioreactor is a bio reactor paired with an aeration device such as a microbubble generator. The purpose of the microbubble generator is to generate highly oxygenated water which infuses microbes with the nutrients required to achieve very high levels of process and treatment effectiveness and efficiency. The accelerated regeneration of microbes accelerates the natural mineralization process, reducing treatment cycle times and virtually eliminating organic contaminant levels.

10

As best shown in FIG. 2, in one embodiment, in situ bioreactor tube container **200** has an external slotted pipe structure **220** which has lots of inner bores **220**. Within each inner bore **220**, enough microbial media **210** should be loaded. In one embodiment, there is aeration tubing **230** embedded within the slotted pipe structure **220**. One end of aeration tubing **230** is connected to bioreactor hose **140** and subsequently to bioreactor pump **108**. When the bioreactor pump **108** is on, it supplies air through aeration tubing **230** which tiny air bubbles are created. Air bubbles diffuse from the internal to the external surfaces of bioreactor **200** and ultimately disperse to the surrounding water/liquid medium via numerous inner bores **220** where microbial media **210** are contained. The air bubbles supply both oxygen and nutrients to microbial media **210** and eventually disperse them into the surrounding water/liquid medium.

15

20

25

FIG. 3 is a representative view showing the method of application of the floating bioreactor system **100** of the present invention. As shown in FIG. 3, floating bioreactor system **100** of the present invention is installed and immersed in the treated liquid medium **310**. The waste **320** is

received via inlet pipe **312** and is discharged out through the outlet **314** after treatment. In one embodiment, housing **102** is suspended and floating with the assistance of floats **120** on both side. As best shown in FIG. 3, when the floating bioreactor system **100** is turned on, bioreactor **200** disperses microbes **360** which are originally contained in its inner bores **220**. The tiny air bubbles **350** generated from aeration tubing **230** will further disperse microbes **360** out of the system while continuously supplying oxygen and nutrients to the microbes **360**. Eventually, the microbes **360** dispersed from bioreactor **200** will establish themselves as the dominant species within the liquid medium **310** being treated.

While at the same time, tiny air bubbles **350** are generated continuously from diffuser grids **130**. The fine air bubbles **350** are more readily absorbed into water per volume of air compared to coarse air bubbles. Consequently, oxygen content is much increased in the treated liquid medium **310**. Moreover, the low head-loss of diffuser grids **130** combined with bioreactor **200** leads to a high efficacy for the microbial population to the liquid medium being treated.

As shown in FIG. 3, microbial population **360** is dispersed from bioreactor **200** and move vertically away from the bioreactor **200** towards diffuser grids **130**. Air bubbles **350** released not only support the life of the microbes **360** but also help evenly dispense microbes **360** out to the liquid medium for treatment **310**. As best shown in FIG. 3, the combination of diffuser grids **130** and bioreactor **200** and more importantly their relative orientation in floating bioreactor system **100** of the present invention greatly enhances the efficiency and effectiveness in treating liquid medium **310**.

It will be understood that biosolids and/or sludge handling requirements are eliminated in the present invention. The biosolids are eaten up and consumed by the microbes, thus eliminating the need for sludge and biosolids handling equipment, disposal, etc. In addition, having the microbes on the surface of the water increases the efficiency of oxygen transfer in the floating bioreactor system **100**.

TEST RESULTS:

Test Laboratory: Robinsons Land Corporation; Analysis No.: WA-10-217

Model: BioCleaner™ 1200 m3 system [16 HP]

Test Date: Sample - October 18, 2010; Analysis - October 18-23, 2010

5 Sample Source: STP-Main Mall

Quantitative Water Analysis

<u>Sample Identification</u> (Lab. Sample Nos.)	<u>Influent</u> (S10-WA-506)	<u>Effluent</u> (S10-WA-506)	<u>DENR Effluent</u> <u>Standard for</u> <u>Inland Water</u> Class C - "NPI"	<u>Method of</u> <u>Analysis</u>
pH, as received	6.41	7.26	6.5-9.0	Glass Electrode Method
10 Temperature, °C	27.6	28.3		Mercury-Filled Thermometer
Chemical Oxygen Demand (COD), mg/L	780.49	25.68	100 maximum	Dichromate Reflux Method
15 Biochemical Oxygen Demand (5-days BOD), mg/L	721.26	<1	50 maximum	Azide Modification (Dilution Technique)
Settleable Solids, ml/L	n/a	0.1	0.5 maximum	Volumetric (Imhoff Cone) Method
20 Dissolved Oxygen, mg/L	n/a	6.58		Azide Modification (Winkler Method)

Total Coliform, MPN/100ml	n/a	<2	≤ 10,000 maximum	Multiple Tube Fermentation Technique
------------------------------	-----	----	---------------------	--

As shown in the above Test Result, which the experiment and analysis was carried out by an independent laboratory, after treatment by one of the models of floating bioreactor system **100** of the present invention, the overall quality of waste water improved significantly. Most notable results included the BOD reduction from over 700mg/L in the influent sample to a mere <1 mg/L in the effluent sample. The value of Total Coliform [E. coli] was also reduced to <2 MPN/100ml. Both values are way lower than the DENR Effluent Standard for Inland Water Class C - "NPI, making the effluent sample Class AA water, better or equivalent to drinking water quality in those respects. The waste water was treated only by floating bioreactor system **100** of the present invention with no chlorination, no filters, no sludge handling and no chemicals, pre or post treatment.

FIG. 4A is a representative view showing one method of adaption of an alternative embodiment, viz. aquarium bioreactor and aerator system **400**. As shown in FIG. 4A, floating bioreactor system **100** of the present invention can be adapted to be used in an aquarium. In one embodiment, aquarium bioreactor and aerator system **400** consists of air pump **414**, air hose **413** and bioreactor and aerator combo **401**. In one embodiment, air pump is a low wattage pump, approximately 2-3 watts, supplying air to in situ bioreactor and aerator combo **401** via air hose **413**. In one embodiment, bioreactor and aerator combo **401** is completely submerged in the water **412**. Preferably, approximately 150 grams by weight of bioreactor and aerator combo **401** should be used for an aquarium of 81 to 160 liters by volume. For smaller tanks with volume below 80 liters, 100grams by weight of bioreactor and aerator combo **401** should be used.

To sufficiently aerate a 100 gallon tank, air pump **414** should be around 5 watts of power or approximately 0.07 watts of power per gallon of water. In one embodiment, regularly clean filter and

the inner wall of the tank to prevent forming of biofilms. The system **400** works best in conjunction with a carbon filter **409**.

The advantages of using aquarium bioreactor and aerator system **400** include no odor, no sedimentation, controlled water pH value, various set microbes for controlling nitrogen cycle, water and energy conservation, fishes that are more resistant to diseases, no need for mechanical filter and no chemicals needed.

FIG. 4B is a representative side view of bioreactor and aerator combo **401** of aquarium bioreactor and aerator system **400**. FIG. 4C is a representative side partially exposed view of bioreactor and aerator combo **401** of aquarium bioreactor and aerator system **400**. The main purpose of bioreactor and aerator combo **401** is to both generate tiny air bubbles for aeration and disperse microbes to clean up waste in aquariums. As shown in FIG. 4B, the exterior of bioreactor and aerator combo **401** is made of perforated stainless steel plate wherein numerous holes **420** are present. In one embodiment, bioreactor and aerator combo **401** is cylindrical in shape with approximate dimensions in the range of four inches by two and a half inches in diameter. As best shown in FIG. 4C, air generated from air pump **414** enters bioreactor and aerator combo **401** via hose **413** subsequently rubber hose **408** inside bioreactor and aerator combo **401**. Air will then reach air diffuser **407** and tiny air bubbles **415** are generated. Air bubbles **415** will then reach surrounding microbial media **406** where appropriate types and amount of microbial is contained. Air bubbles **415** will provide oxygen and nutrients for the microbial population to thrive and also disperse them out of bioreactor and aerator combo **401** via holes **420**. The microbes produced by bioreactor and aerator combo **401** will feed on the fish waste and other contaminant in the aquarium making the water **412** clearer and odorless.

FIG. 5A is a representative view showing one method of adaption of an alternative embodiment, viz. home septic bioreactor and aerator system **500**. Home septic bioreactor and aerator

system **500** provides a method and apparatus for continuous, in-situ microbial seeding at the septic tank **512**. As shown in FIG. 5A, home septic bioreactor and aerator system **500** consists essentially of home septic unit **501**, air pump and air hoses **511**. In one embodiment, home septic unit **501** is an immersible container which also serves as a bio-reactor. Home septic unit **501** is immersed in the waste water **530** completely and is secured at the bottom of septic tank **512** at footing **503** by mechanical means. In one embodiment, home septic unit **501** is also attached to cables **510** for support at handle brackets **504** and has an air pump located above the septic tank **512**.

FIG. 5B is a representative side view of home septic unit **501** of home septic bioreactor and aerator system **500**. FIG. 5C is a representative side partially exposed view of home septic unit **501** of home septic bioreactor and aerator system **500**. Although home septic unit **501** can be in any number of different configurations, in one embodiment, home septic unit **501** is a roughly cylindrical hollow container having a footing **503**. As shown in FIG. 5B, home septic unit **501** has a cap **505** on top, numerous inlet holes **502** at the bottom and outlet opening **520** near the top half of the structure. In one embodiment, air enters home septic unit **501** via air hose **506** and diffuser hose **509**. As shown in FIG. 5C, home septic unit **501** microbial media **507** in its core that store and produce the microbes. In one embodiment, a diffuser unit **508** is placed at the bottom of home septic unit **501**, which is powered by air pump. Diffuser unit **508** generates tiny air bubbles that provide oxygen and nutrients to microbial that is contained in microbial media **507** and simultaneously creates vacuum that sucks in waste water **530** from inlet holes **503** at the bottom. Waste water **530** travels upward inside home septic unit **501** and is then released at the top via outlet opening **520**. During the journey upward, waste water makes contact with the microbial media **507** in the process and carries with it microbial when it is released back to open water.

By continuous adding a desired microbial population directly into waste water **530** to be treated, the present invention **500** allows for demand growth and microbial acclimation based on the waste content within the said environment. The microbial agents generated by the present invention

500 are provided with a continuous supply of oxygen and/or nutrients by diffuser unit **508**, such microbial agents can more effectively mineralize waste within an environment **530** being treated. The present invention **500** can specifically makes the septic tank **512** of houses into a small sewage treatment plant. Over time, the in-situ microbial addition provided by home septic bioreactor and aerator system **500** of the present invention shall make waste water **530** to acceptable discharge level.

FIG. 6A is a representative view showing one method of adaption of an alternative embodiment, viz. aero dynamic mixer bioreactor and aerator system **600**. FIG. 6B is a representative side view of aero dynamic mixer of aero dynamic mixer bioreactor and aerator system **600**. In one embodiment, aero dynamic mixer bioreactor and aerator system **600** is an aeration device adapted to be used in outdoor environment such as lakes and ponds. As shown in FIG. 6A, aero dynamic mixer is basically a housing adapted to float within the liquid medium **609** such that the top portion remains above surface of the water/liquid medium **609**. The airlift device has been known for many years and essentially operates by supplying air bubbles into the water at a predetermined depth below the surface. Some of this air is absorbed into the water, which causes the water to become less dense and rise towards the surface. The rising of the water causes circulation **608**, which distributes the aerated water and brings additional water toward the device for aeration.

Water **609** is aerated in an airlift device by use of a diffuser. When the diffuser is submerged in water **609**, the movement of gas through the device causes bubbles to emerge from the pores and into the water **609**. In one embodiment, the aero dynamic mixer bioreactor and aerator system **600** uses a patented porous rubber houses as a diffuser.

The present invention **600** is comprised of a series of porous diffusers called Aerogrids™ arranged in a way that they are in a straight line. These aeration diffusers are positioned in fiberglass frames that are supported by floaters **603**.

As best shown in FIG. 6B, above the surface are blowers **650** situated to give air to the diffusers. A skirt **606** varying in dimensions, depending on the depth of the medium, wraps around the device **600** in such a way it has openings **607** only at the top and bottom. A small opening **660** is also noticed on one side of the device **600** just below the surface. This will serve as a mouth to water
5 **609** coming out created by the vacuum when the said present invention **600** is turned on. The present invention **600** is capable of drawing water **609** and recirculating it in a very potent manner. Also it is a mobile device that can easily hoist to a boat and move from one location to another.

Although the inventions herein is to be understood that these are merely illustrative of the
10 principles and applications of the present inventions. Therefore, it is understood that numerous modifications may be made to the illustrative embodiments and that other modifications may be devised without departing from the scope and functions of the inventions as defined by the claims to be followed.

Unless defined otherwise, all technical and scientific terms used herein have the same
15 meaning as commonly understood by one of ordinary skill in the art to which the present invention belongs. Although any methods and materials similar or equivalent to those described can be used in the practice or testing of the present invention, the preferred methods and materials are now described. All publications and patent documents referenced in the present invention are incorporated
20 herein by reference.

While the principles of the invention have been made clear in illustrative embodiments, there will be immediately obvious to those skilled in the art many modifications of structure, arrangement, proportions, the elements, materials, and components used in the practice of the invention, and
25 otherwise, which are particularly adapted to specific environments and operative requirements without departing from those principles. The appended claims are intended to cover and embrace any and all such modifications, with the limits only of the true purview, spirit and scope of the invention.

I claim:

1. A portable, floating aeration and microbial reactor system for cleaning sewage water, the aeration and microbial reactor system comprising:

a rigid, semi-open and stable housing frame having two side walls and a back wall to half of its height, the housing frame further having a plurality of buoyant members attached on its sides such that the top portion of the housing frame remains afloat when it is submerged in sewage water of various density;

an aeration sub-system further having a blower attached mechanically and sitting on top of the housing frame, a flat aeration grid device extending horizontally across the entire width and attached in the bottom half of said housing frame, the aeration grid device further comprises a plurality of porous plastic pipes having a gas permeable wall of thermoset polymer particles and thermoplastic binder in a minor amount thereby bonding said polymer particles and creating a substantially uniform porosity through the pipe wall along the length of the pipe, said porosity provided by a plurality of micropores having an average diameter of about 0.001 inch to about 0.004 inch along the length of said pipe for diffusion of gas therethrough and transfer to a medium, said thermoset polymer particles having a mesh size of about 60 to about 140 mesh, a plurality of air hoses connecting said blower to said aeration grid device;

a microbial reactor sub-system further having an air pump attached mechanically and sitting on top of the housing frame, an elongated, tubular and externally perforated microbial reactor portion extending essentially horizontally across the entire width of said housing frame and underneath said aeration grid device, the microbial reactor portion further comprises an inner aeration tube powered by said air pump, an perforated outside tube further having a plurality of slots, microbial media containing live bacteria imbedded within said slots, an air hose connecting said air pump to said microbial reactor portion.

2. A portable, floating aeration and microbial reactor system for cleaning sewage water, the aeration and microbial reactor system comprising:

a rigid, semi-open and stable housing frame having two side walls and a back wall to half of its height, the housing frame further having a plurality of buoyant members attached on its sides such that the housing frame remains afloat when it is submerged in sewage water of various density;

an aeration sub-system further having a blower attached mechanically and sitting on top of the housing frame, a flat aeration grid device extending horizontally across the entire width and attached in the bottom half of said housing frame, the aeration grid device further comprises a plurality of porous plastic, said porosity provided by a plurality of micropores having an average diameter of about 0.001 inch to about 0.004 inch along the length of said pipe for diffusion of gas therethrough and transfer to a medium, a plurality of air hoses connecting said blower to said aeration grid device;

a microbial reactor sub-system further having an air pump attached mechanically and sitting on top of the housing frame, an elongated, tubular and externally perforated microbial reactor portion extending essentially horizontally across the entire width of said housing frame and underneath said aeration grid device, the microbial reactor portion further comprising an inner aeration tube powered by said air pump, an perforated outside tube further having a plurality of slots, microbial media containing live bacteria imbedded within said slots, an air hose connecting said air pump to said microbial reactor portion.

3. A portable, floating aeration and microbial reactor system for decontaminating water, the aeration and microbial reactor system comprising:

a rigid frame having an upper portion and a lower portion;

a plurality of buoyant members attached to the upper portion of the rigid frame such that the reactor system remains afloat when submerged in contaminated water;

an aeration sub-system coupled to the rigid frame, the aeration system comprising a blower attached mechanically to and sitting on the upper portion of the rigid frame, a flat horizontally-oriented aeration grid coupled to the rigid frame intermediate the upper portion and the lower portion thereof, the aeration grid further comprising microporous tubing having a plurality of micropores

with an average diameter between about 0.001 inch and about 0.004 inch along the length of said microporous tubing for diffusion of gas therethrough and transfer to a medium, the aeration sub-system further comprising a plurality of air hoses connecting the blower to the aeration grid; and

a microbial reactor sub-system having an air pump mechanically coupled to the upper portion of the rigid frame, the microbial reactor sub-system further comprising an elongated, tubular and externally perforated microbial reactor portion coupled to the lower portion of the rigid frame and extending essentially horizontally and underneath the aeration grid, the microbial reactor portion comprising an inner aeration tube powered by the air pump, a perforated outside tube having a plurality of slots extending therethrough, the microbial reactor portion further comprising microbial media containing live bacteria imbedded within said slots, the microbial reactor sub-system further having air hose connecting the air pump to the microbial reactor portion.

4. The portable, floating aeration and microbial reactor system of claim 3 installed in an outdoor stream.

5. The portable, floating aeration and microbial reactor system of claim 3 installed in an outdoor pond.

6. The portable, floating aeration and microbial reactor system of claim 3 installed in a settling pond.

7. The portable, floating aeration and microbial reactor system of claim 3 installed in a fish aquarium.

8. The portable, floating aeration and microbial reactor system of claim 3 installed from a residential septic system.

9. The portable, floating aeration and microbial reactor system of claim 3 in conjunction with an aerodynamic mixing system for decontaminating waste water.

///