

# **DEVICE NETWORKING ACTIVATION METHOD, APPARATUS AND CLOUD NETWORK DEVICE**

This application claims priority to Chinese Patent Application No. 201810085739.5, filed on January 29, 2018 and entitled “Device Networking Activation Method, Apparatus, and Cloud Network Device,” which is incorporated herein by reference in its entirety.

## **TECHNICAL FIELD**

The present invention relates to the field of the Internet of Things, and, more particularly, to a device networking activation method, an apparatus, and a cloud network device.

## **BACKGROUND**

With the rapid development of Internet technology, the Internet of Things technology has become widely used in people’s work and daily life. For example, people now use a mobile phone to remotely operate a rice cooker to complete the cooking process of food. In order for a user terminal to operate a device of the Internet of Things remotely, the device of the Internet of Things needs to be networked and activated to determine the legitimacy of the user terminal and the access right of the user terminal.

In the existing technology, the networking process and activation process of the device to be networked (that is, the aforementioned device of the Internet of Things) are not decoupled. That is, the networking process and the activation process are integrated, and the security and convenience of the activation process are not improved accordingly. Most of the works are for the purpose of personalized improvement and certain adjustments of the networking process. In addition, a user needs to trigger the networking instruction of the device to be networked through the user terminal to enable the device to be networked enter the networking process, and then determine the association relationship between the device to be networked and the user terminal.

The solution in which the above networking process and activation process are integrated has the following problems:

(1) The same networking instructions are used for different devices to be networked, and thus the security of the devices to be networked is low.

(2) Since the activation process is performed first and then the networking process is performed, the complexity of the networking process is increased, and the success rate of networking of devices to be networked is reduced.

(3) There is no time window for networking instructions, which may reduce the networking security of the devices to be networked.

In view of the above problem that the safety and reliability of the activation of the device to be networked is low due to the fact that the networking and activation of the device to be networked in the existing technology are not decoupled, no effective solution has been proposed yet.

## **SUMMARY**

Example embodiments of the present invention provide a device networking activation method, an apparatus, and a cloud network device to at least solve the technical problem of low safety and reliability of the activation of a device to be networked due to the fact that the networking and activation of the device to be networked are not decoupled in the existing technology.

According to an aspect of the example embodiments of the present invention, a device networking activation method is provided, which comprises: networking a device to be networked; in the case where the device to be networked is successfully networked, pushing an activation strategy for activating the device to be networked to the device to be networked that has been successfully networked; and according to the activation strategy pushed, activating the device to be networked that has been successfully networked.

According to another aspect of the example embodiments of the present invention, a device networking activation method is provided, which comprises: networking a device to be networked; in the case where the device to be networked is successfully networked, receiving an activation strategy for activating the device to be networked; and according to the received activation strategy, activating the device to be networked.

According to another aspect of the example embodiments of the present invention, an apparatus for device networking activation is provided, and the apparatus comprises: a first networking module, which is used for networking a device to be networked; a pushing module, which is used for, in the case where the device to be networked is successfully networked, pushing an activation strategy for activating the device to be networked to the device to be networked that has been successfully networked; a first activating module, which

is used for, according to the activation strategy pushed, activating the device to be networked that has been successfully networked.

According to another aspect of the example embodiments of the present invention, a cloud network device is provided, and the cloud network device comprises the apparatus for device networking activation as mentioned above.

According to another aspect of the example embodiments of the present invention, an apparatus for device networking activation is provided, and the apparatus comprises: a second networking module, which is used for networking a device to be networked; a receiving module, which is used for, in the case where the device to be networked is successfully networked, receiving an activation strategy for activating the device to be networked; and a second activating module, which is used for, according to the received activation strategy, activating the device to be networked.

According to another aspect of the example embodiments of the present invention, a cloud network device is provided, and the cloud network device comprises the apparatus for device networking activation as mentioned above.

According to another aspect of the example embodiments of the present invention, a storage medium is provided, and the storage medium comprises a stored program, wherein, when the program is running, a device where the storage medium is located is controlled to execute the device networking activation method.

According to another aspect of the example embodiments of the present invention, a processor is provided, and the processor is used to run a program, when the program is running, the device networking activation method is executed.

In the example embodiments of the present invention, the decoupling of the networking process and the activation process is adopted, by connecting the device to be networked to a network, and then in the case where the device to be networked is successfully networked, the device to be networked that has been successfully networked is pushed with the activation strategy for activating the device to be networked that has been successful networked. According to the pushed activation strategy, the device to be networked that has been successful networked is activated, so as to achieve the purpose of completely decoupling the networking process and activation process of the device to be networked, thereby achieving the technical effect of improving the security of the activation process. Furthermore, the technical problem of low safety and reliability of the activation of a device to be networked caused by not decoupling the networking and activation of the device to be networked in the existing technology is solved.

## **BRIEF DESCRIPTION OF DRAWINGS**

The drawings described herein are meant to enable a further understanding of the present disclosure and form a part of the present application. The schematic example embodiments of the present disclosure and their descriptions are used to explain the present disclosure and do not constitute an undue limitation on the present disclosure. In the drawings:

FIG. 1 is a flowchart of a device networking activation method according to an example embodiment of the present invention.

FIG. 2 is a schematic structural diagram of an optional system based on a device networking activation method according to an example embodiment of the present invention.

FIG. 3 is a schematic diagram of an optional interaction based on a device networking activation method according to an example embodiment of the present invention.

FIG. 4 is a flowchart of a device networking activation method according to an example embodiment of the present invention.

FIG. 5 is a schematic structural diagram of an apparatus for device networking activation according to an example embodiment of the present invention.

FIG. 6 is a schematic structural diagram of an apparatus for device networking activation according to an example embodiment of the present invention.

FIG. 7 is a block diagram of a hardware structure of a computer terminal according to an example embodiment of the present invention.

## **DETAILED DESCRIPTION**

In order to enable a person skilled in the art to better understand the solutions of the present invention, the technical solutions in the example embodiments of the present invention will be described clearly and completely in conjunction with the drawings of the example embodiments of the present invention. Obviously, the described example embodiments are only a part of the example embodiments, but not all the example embodiments of the present invention. Based on the example embodiments of the present invention described herein, all other example embodiments obtained by a person of ordinary skill in the art without inventive efforts shall fall within the scope of protection of the present invention.

It should be noted that the terms “first” and “second” in the description and claims of the present invention and the above drawings are used to distinguish similar objects, and are not used to describe a specific order or sequence. It should be understood that the data so used can be interchanged under appropriate circumstances so that the example embodiments

of the present invention described herein can be implemented in an order other than those illustrated or described herein. In addition, the terms “comprising,” “including” and any variations thereof are intended to cover non-exclusive inclusions, for example, processes, methods, systems, products or devices that contain a series of steps or units need not be limited to those clearly listed steps or units, but may further include other steps or units not explicitly listed or inherent to these processes, methods, products or devices.

First, some of the nouns or terms that appear in the process of describing the example embodiments of the present application are suitable for the following explanation:

(1) Decoupling, refers to the use of a method to remove the association relationship between two or more systems.

(2) Time window, refers to a period of time during which an event or thing can be processed or reacted.

(3) Device activation, refers to the process of performing authorization binding between a user terminal and a device after the device completes networking, so that the user terminal can control the device.

#### Example 1

According to the example embodiments of the present invention, an example embodiment of a device networking activation method is provided. It should be noted that the device networking activation method provided in the present application can completely decouple the networking process from the activation process so as to improve the success rate of the networking process, and at the same time enhance the security of the activation process. In addition, the activation rules in the activation process can be flexibly configured by the manufacturers, by means of comprehensively considering the characteristics of different devices to be networked, so that the convenience and security of the activation operation of the device to be networked can be improved. Finally, the activation process in the device networking activation method provided in the present application can be visualized, and the number of retries and the activation window of the activation process can be dynamically configured, thereby greatly improving the user's activation experience.

In addition, it should be noted that the device networking activation method provided in the present application can be widely used in the field of the Internet of Things. With the rapid development of science and technology, the Internet of Things technology has been widely used in people's work and daily life. For example, people can start air conditioning remotely through their mobile phones from their workplace before going back home, so that users can enjoy a comfortable environment at the moment when arriving at home. Before a

user can control the air conditioner through a mobile phone, the air conditioner (that is, a device to be networked) needs to be networked and activated. According to the device networking activation method provided in the present application, the networking process and activation process of the air conditioner will be decoupled; the user can remotely control the air conditioner via the mobile phone.

In the above application scenario, as an optional example embodiment, FIG. 1 shows a flowchart of a device networking activation method according to an example embodiment of the present application. As shown in FIG. 1, the method specifically includes the following steps:

Step S102 includes networking a device to be networked.

It should be noted that the above device to be networked may be, but is not limited to, a smart home device, a smart logistic device, a smart transportation device, a smart grid device, etc. that can perform the Internet of Things. In addition, the device on the cloud can decouple the networking process and activation process of the device to be networked, and execute the networking process and activation process after the decoupling process. The device located on the cloud may be, but is not limited to, a cloud server.

In addition, it should be noted that the above networking process is a process of connecting the device to be networked to a cloud server, and the above activation process is a process of activating the device to be networked. Due to the decoupling process for the networking process and activation process of the device to be networked, the networking process and activation process become independent from each other, thereby reducing the complexity of the networking process, improving the success rate of networking, and further enhancing the security of the activation process.

In an optional example embodiment, the device to be networked is connected through a networked device, where the networked device can be any device that has been connected to the Internet, for example, a mobile phone. In addition, the device to be networked can also be networked through an application or program installed on a networked device. Specifically, the networked device starts a monitoring mode to detect whether a broadcast message sent by a device to be networked is received. After the networked device receives the broadcast message sent by the device to be networked, the networked device sends the networked information to the device to be networked, and the device to be networked sends the networked information to the cloud server. After receiving the networking information, the cloud server completes the networking between the cloud server and the device to be networked.

It should be noted that in the networking process, there is no need to consider the association between the networked device and the device to be networked, as long as the networked device can obtain the broadcast message sent by the device to be networked, that is, only the networking capability of the device to be networked needs to be considered, thereby reducing the complexity of the networking process of the device to be networked and increasing the success rate of networking.

Step S104 includes, in the case where the device to be networked is successfully networked, pushing an activation strategy for activating the device to be networked to the device to be networked that has been successfully networked.

It should be noted that the manufacturer platform that provides the activation strategy of the activation process can provide the activation strategy set to the cloud server, wherein the activation strategy set includes a plurality of activation strategies, among them, each activation strategy has different configuration parameters, and the configuration parameters can be, but are not limited to, activation instructions, expiration time parameters, and other parameters. For example, the activation instructions in each activation strategy can be different.

In an optional example embodiment, when the device to be networked is successfully connected to the network, the cloud server pushes the activation strategy to the device to be networked according to the activation strategy set provided by the manufacturer's platform. After confirming the activation strategy, according to the activation process, the cloud server activates the device to be networked based on the activation strategy.

Step S106 includes, according to the activation strategy pushed, activating the device to be networked that has been successfully networked.

It should be noted that the activation process of the device to be networked is performed only after the device is successfully networked. This can effectively reduce the complexity of the networking process. In addition, different activation strategies correspond to different activation instructions, thereby solving the problem of reduced safety of activation of the device to be networked caused by the use of the same activation instruction for different activation strategies in the existing technology. In this way, the safety of the activation of the device to be networked is improved.

Based on the method defined in the above steps S102 to S106, it can be known that by connecting the device to be networked to the network, and then in the case where the device to be networked is successfully networked, the device to be networked is pushed with the activation strategy to activate the device to be networked, and then the device to be

networked that has been successful networked can be activated according to the pushed activation strategy.

It is easy to notice that because the networking process is separated from the activation process, the networking process is executed first, and the activation process is executed only when the networking process is successful, and that this can effectively improve the networking success rate of the device to be networked, and thus improve the activation security of the device to be networked. In addition, since different activation strategies correspond to different activation instructions, the present application effectively improves the security of the activation of the device to be networked.

In addition, the example embodiments mentioned above can also achieve the purpose of completely decoupling the networking process and the activation process of the device to be networked, thereby achieving the technical effect of improving the security of the activation process, and thus solving the problem of a device to be networked in the existing technology, because the networking process and activation process of a device to be networked are not decoupled in the existing technology, so the safety and reliability of the device to be networked activation are low.

In an alternative example embodiment, FIG. 2 shows a schematic diagram of a system structure based on the device networking activation method. It can be seen from FIG. 2 that the system includes a networked device 10, a cloud server 20, a device to be networked 30, and a vendor platform 40 (not shown in FIG. 2). The networked device 10 is used to complete the networking process of the device to be networked 30. The networked device 10 may be, but is not limited to, a smart phone, a tablet, a computer, a wearable device, such as a smart bracelet, a smart watch, and the like. The cloud server 20 may send an activation strategy to the device to be networked 30. After the user confirms the activation strategy through the device to be networked 30, the cloud server 20 then activates the device to be networked 30 based on the activation strategy. In addition, the vendor platform 40 can push the activation strategy to the cloud server.

In a preferred example embodiment, FIG. 3 shows a schematic diagram of the system interaction based on the system structure shown in FIG. 2. As can be seen from FIG. 3, the specific interaction process is as follows:

Step S301 includes a vendor platform pushing an activation strategy set to a cloud server.

Step S302 includes a networked device starting to monitor whether a device to be networked sends a broadcast message, wherein the networked device is a device connected to a network.

Step S303 includes the device to be networked sending a broadcast message to the networked device.

Step S304 includes the networked device sending networking information to the device to be networked.

Step S305 includes the device to be networked sending the networking information to the cloud server to establish a connection between the device to be networked and the cloud server.

Step S306 includes, after the device to be networked is successfully connected to the cloud server, the cloud server selecting an activation strategy from the activation strategy set and pushing it to the device to be networked.

Step S307 includes, after receiving the activation strategy pushed by the cloud server, the device to be networked displaying it on a display interface thereof or sending prompt information to a user in the form of a voice to prompt the user to perform an activation operation.

Step S308 includes, after viewing the prompt information through the device to be networked, the user sending activation information to the cloud server by operating with a display screen or a button of the device to be networked.

Step S309 includes, after receiving the activation information, the cloud server starting an activation time window.

Step S310 includes, the user operating the device to be networked within the activation time window to activate the device to be networked, and after the device to be networked is activated, the device to be networked sending an activation confirmation message to the cloud server to confirm that the device to be networked has been activated.

Step S311 includes, after receiving the activation confirmation message, the cloud server determining that the device to be networked is activated.

Step S312 includes, after determining that the device to be networked has been activated, the cloud server sending confirmation activation information to the device to be networked.

Step S313 includes, after receiving the confirmation activation information, the user checking the running state of the device to be networked through the display screen or the

button of the device to be networked, or controlling the device to be networked to complete a corresponding action or execute a corresponding control instruction.

According to the interactive schematic diagram shown in FIG. 3, the step of pushing the activation strategy for activating the device to be networked to the device to be networked that has been successful networked includes:

Step S2020 includes determining at least one activation strategy to be pushed to the device to be networked.

Step S2022 includes selecting an activation strategy from the at least one activation strategy, and pushing the selected activation strategy to the device to be networked that has been successfully networked, and wherein when the device to be networked that has been successfully networked needs to be pushed with a respective activation strategy multiple times, the activation strategy selected each time is different.

It should be noted that after the device to be networked is connected to the cloud server, the cloud server can obtain the device information of the device to be networked, and according to the device information of the device to be networked, it can select an activation strategy that matches the device information of the device to be networked from an activation strategy collection containing at least a set of activation strategies, and then push the selected activation strategy to the device to be networked. In this case, the activation strategies of different devices to be networked may be different. In addition, the device information of the device to be networked may be, but is not limited to, the name, model, and identification information of the device to be networked.

In addition, it should be noted that each time the activation strategy pushed to the device to be networked is different, the activation instruction of the device to be networked is also different, and thus, the security and reliability of the activation of the device to be networked can be improved.

In addition, it should also be noted that after obtaining the activation strategy collection pushed by the vendor platform, the cloud server needs to select at least one activation strategy that can be pushed to the device to be networked from the activation strategy collection, and the specific method is as follows:

Step S2020a includes obtaining at least one activation strategy for activating the device to be networked generated according to a product characteristic of the device to be networked.

Step S2020b includes determining the obtained at least one activation strategy as the at least one activation strategy to be pushed to the device to be networked.

It should be noted that the product characteristic of the device to be networked includes, but is not limited to, the device information and functional information of the device to be networked, for example, heating, dehumidification, and cooling.

Specifically, after establishing a connection with the device to be networked, the cloud server obtains the product characteristic of the device to be networked, and then traverses the activation strategy collection pushed by the vendor platform based on the product characteristic to obtain all activation strategies that match the product of the device to be networked. In addition, the cloud server can traverse each characteristic among the product characteristics of the device to be networked to obtain all of the activation strategies corresponding to the product characteristic of the device to be networked, and remove any repeated activation strategy, so as to obtain at least one activation strategy consistent with the product characteristic of the device to be networked.

In an alternative example embodiment, step S106, according to the activation strategy pushed, activating the device to be networked that has been successfully networked, may specifically include the following steps:

Step S2040 includes determining an activation time window for limiting the time to activate the device to be networked.

Step S2042 includes, within the determined activation time window, the device to be networked that has been successfully networked is activated according to the pushed activation strategy.

Specifically, after the cloud server pushes the activation strategy, the user performs activation confirmation by operating the device to be networked; the device to be networked generates activation information, and then sends the activation information to the cloud server. After receiving the activation information, the cloud server starts an activation time window to execute the activation process within the activation time window to activate the device to be networked that has been successful networked. In addition, the user can generate the activation information by operating a function key of the device to be networked. For example, by operating the “keep warm” button on a rice cooker three times in a row, or in the case where there is an activation button on the device to be networked, the user can generate the activation information by operating the activation button on the device to be networked.

It should be noted that the activation process for the device to be networked needs to be completed within a specified activation time window that has a specified period of time. If the activation process cannot be completed within the activation time window, the device to be networked activation fails to activate this time. In such a case, the user may perform

multiple activation processes with the device to be networked. The specific method includes the following steps:

Step S2042a includes obtaining a number of times for supporting activation retries.

Step S2042b includes, within the obtained number of times, activating the device to be networked that has been successfully networked according to the pushed activation strategy.

It should be noted that the number of activation retries can be set by the user.

Specifically, if the activation process is not completed within the activation time window, the cloud server continues to determine whether the number of failed activation processes is greater than the present number of activation retries. If the number of failed activation processes is not greater than the preset number of activation retries, the device to be networked continues the activation process. If the number of failed activation processes is greater than the preset number of activation retries, it is determined that the activation of the device to be networked has failed.

In addition, it should also be noted that, according to the pushed activation strategy, after the activation of the device to be networked that has been successful networked, in the case where the activation of the device to be networked that has been successful networked is successful, the device to be networked is pushed with the device information of the device to be networked and the control authority of a user to control the device to be networked to the device to be networked.

Specifically, after the activation process is performed, the cloud server pushes the device information of the device to be networked and control authority of a user to control the device to be networked to the device to be networked. The user can view the device information of the device to be networked and the control authority of the user through the display screen of the device to be networked or a user terminal associated with the device to be networked.

It should be noted that, for the foregoing method example embodiments, for the sake of simple description, they are all expressed as a series of action combinations. However, a person skilled in the art should know that the present invention is not limited by the described sequence of actions. According to the present invention, certain steps can be performed in other orders or simultaneously. In addition, a person skilled in the art should also know that the example embodiments described in the specification are all preferred example embodiments, and the involved actions and modules are not necessarily required by the present invention.

Through the description of the above example embodiments, a person skilled in the art can clearly understand that the device networking activation method according to the above example embodiments can be implemented by means of software plus a necessary general hardware platform. Certainly, it may be performed through hardware. But in many cases, the former would be a better form of implementation. Based on this understanding, the technical solutions of the present invention, in essence, or the part thereof that contributes to the existing technology, can be embodied in the form of software products. The software products may be stored in a storage medium (such as ROM/RAM, a magnetic disk, an optical disk), and includes several instructions to enable a terminal device (which may be a mobile phone, a computer, a server, a network device, or the like) to execute the methods as described in the examples of the present invention.

#### Example 2

According to the example embodiments of the present invention, an example embodiment of a device networking activation method is further provided. As shown in the flowchart of the device networking activation method provided in FIG. 4, the method specifically includes the following steps:

Step S402 includes networking a device to be networked.

It should be noted that the device to be networked can complete the networking process through a networked device. For example, the networking process can be completed through an application or program installed on a networked device. Specifically, the networked device starts a monitoring mode to detect whether a broadcast message sent by the device to be networked is received. After the networked device receives the broadcast message sent by the device to be networked, the networked device sends the networking information to the device to be networked, and the device to be networked then sends the networking information to the cloud server, so as to complete the networking between the cloud server and the device to be networked.

It should be noted that in the networking process, there is no need to consider the association between the networked device and the device to be networked, as long as the networked device can obtain the broadcast message sent by the device to be networked, that is, only the networking capability of the device to be networked needs to be considered, thereby reducing the complexity of the networking process of the device to be networked and increasing the success rate of networking.

Step S404 includes in the case where the device to be networked is successfully networked, receiving an activation strategy for activating the device to be networked.

It should be noted that the above prompt information may be displayed on the display screen of the device to be networked in the form of text or characters, or may be presented to the user in the form of a voice.

In addition, it should be noted that after the user obtains the activation prompt information through the device to be networked, the user may operate a touch control display of the device to be networked or a button of the device to be networked to send the activation information to the cloud server, and after receiving the activation information, the cloud server confirms the activation of the device to be networked and then sends an activation strategy to the device to be networked.

Step S406 includes, according to the received activation strategy, activating the device to be networked.

It should be noted that, after receiving the activation strategy, the device to be networked executes the activation process so as to activate the device to be networked.

Based on the method defined in the above steps S402 to S406, it can be known that by networking the device to be networked, in the case where the device to be networked is successfully networked, an activation strategy for activating the device to be networked can be received, and according to the received activation strategy, the device to be networked is then activated.

It is easy to notice that because the networking process is separated from the activation process, the networking process is executed first, and the activation process is executed only when the networking process is successful, and that this can effectively improve the networking success rate of the device to be networked, and thus improve the activation security of the device to be networked. In addition, since different activation strategies correspond to different activation instructions, the present application effectively improves the security of the activation of the device to be networked.

In addition, the example embodiments mentioned above can also achieve the purpose of completely decoupling the networking process and the activation process of the device to be networked, thereby achieving the technical effect of improving the security of the activation process, and thus solving the problem of a device to be networked in the existing technology, because the networking process and activation process of a device to be networked are not decoupled in the existing technology, so the safety and reliability of the device to be networked activation are low.

In an alternative example embodiment, Step S406, according to the received activation strategy, activating the device to be networked, includes the following specific steps:

Step S4080 includes, according to the received activation strategy, starting an activation time window for limiting the time to activate the device to be networked.

Step S4082 includes, within the activation time window, activating the device to be networked.

In addition, the step of, within the activation time window, activating the device to be networked, includes the following specific steps:

Step S4082a includes displaying operation prompt information for prompting to perform an activation authentication operation.

Step S4082b includes determining whether operation confirmation information for performing the activation authentication operation on the device to be networked is received in the activation time window.

Step S4082c includes, in the case where the determining result is yes, activating the device to be networked.

Specifically, on the display screen of the device to be networked, the user is prompted to perform an activation authentication operation on the device to be networked, such that the user completes the activation authentication operation according to operation prompt information. For example, the activation authentication operation can be completed by operating the “keep warm” button on a rice cooker three times in a row, or operating an activation button of the device to be networked. After the activation authentication operation is completed, the device to be networked sends activation authentication operation information to the cloud server, and the cloud server then starts an activation time window. After the activation time window is started, if the device to be networked receives operation confirmation information within the activation time window, the activation process is performed to complete the activation of the device to be networked.

It should be noted that the activation process for the device to be networked needs to be completed within a specified activation time window that has a specified period of time. If the activation process cannot be completed within the activation time window, the device to be networked activation fails to activate this time. In such a case, the user may perform multiple activation processes with the device to be networked. The specific method includes the following steps:

Step S4084 includes according to the received activation strategy, obtaining a number of times for supporting activation retries.

Step S4086 includes displaying the obtained number of times for supporting activation retries.

Step S4088 includes, within the displayed number of times, activating the device to be networked.

Specifically, if the activation process is not completed within the activation time window, the cloud server continues to determine whether the number of failed activation processes is greater than the present number of activation retries. If the number of failed activation processes is not greater than the preset number of activation retries, the device to be networked continues the activation process. If the number of failed activation processes is greater than the preset number of activation retries, it is determined that the activation of the device to be networked has failed.

In addition, it should also be noted that after activating the device to be networked according to a separate activation process, if the device to be networked is activated successfully according to the separate activation process, the device to be networked is further pushed with the device information of the device to be networked and the control authority of a user to control the device to be networked to the device to be networked.

Specifically, after activating the device to be networked according to the received activation strategy, the method further includes the following steps:

Step S410 includes, in the case where the device to be networked is successfully activated according to the received activation strategy, receiving the pushed device information of the device to be networked and control authority of a user to control the device to be networked.

Step S412 includes displaying the device information and the control authority received.

Specifically, after the activation process is performed, the cloud server pushes the device information of the device to be networked and control authority of a user to control the device to be networked to the device to be networked. The user can view the device information of the device to be networked and the control authority of the user through the display screen of the device to be networked or a user terminal associated with the device to be networked.

### Example 3

According to the example embodiments of the present invention, an apparatus for device networking activation for implementing the device networking activation method of the above example embodiment 1 is further provided. As shown in FIG. 5, the apparatus 20 includes a first networking module 501, a pushing module 503, and a first activating module 505.

The first networking module 501 is used for networking a device to be networked. The pushing module 503 is used for, in the case where the device to be networked is successfully networked, pushing an activation strategy for activating the device to be networked to the device to be networked that has been successfully networked. The first activating module 505 is used for, according to the activation strategy pushed, activating the device to be networked that has been successfully networked.

It should be noted herein that the above-mentioned first networking module 501, pushing module 503, and first activating module 505 correspond to steps S102 to S106 in example 1. In addition, the three modules have the same examples and application scenarios as the corresponding steps, but are not limited to the contents disclosed in example 1.

In an optional example embodiment, the pushing module includes: a first determining module and a first pushing module. Among them, the first determining module is used for determining at least a set of activation strategies to be pushed to the device to be networked; and the first pushing module is used for selecting an activation strategy from the at least a set of activation strategies, and pushing the selected activation strategy to the device to be networked that has been successfully networked, wherein when the device to be networked that has been successfully networked needs to be pushed with a respective activation strategy multiple times, the activation strategy selected each time is different.

It should be noted herein that the first determining module and the first pushing module correspond to steps S2020 to S2022 in example 1. In addition, the two modules have the same examples and application scenarios as the corresponding steps, but are not limited to the contents disclosed in example 1.

In an optional example embodiment, the first determining module includes: a first obtaining module and a second pushing module. Among them, the first obtaining module is used for obtaining at least one activation strategy for activating the device to be networked generated according to a product characteristic of the device to be networked; and the second pushing module is used for determining the obtained at least one activation strategy as the at least one activation strategy to be pushed to the device to be networked.

It should be noted herein that the first determining module and the second pushing module correspond to steps S2020a to S2022b in example 1. In addition, the two modules have the same examples and application scenarios as the corresponding steps, but are not limited to the contents disclosed in example 1.

In an optional example embodiment, the first activating module includes a second determining module and a second activating module. Among them, the first activating module is used for determining an activation time window for limiting the time to activate the device to be networked; and the second activating module is used for, within the determined activation time window, activating the device to be networked that has been successfully networked according to the pushed activation strategy.

It should be noted herein that the second determining module and the second activating module correspond to steps S2040 to S2042 in example 1. In addition, the two modules have the same examples and application scenarios as the corresponding steps, but are not limited to the contents disclosed in example 1.

In an optional example embodiment, the first activating module includes a second obtaining module and a third activating module. Among them, the second obtaining module is used for obtaining a number of times for supporting activation retries; and the third activating module is used for, within the obtained number of times, activating the device to be networked that has been successfully networked according to the pushed activation strategy.

It should be noted herein that the second obtaining module and the third activating module correspond to steps S2042a to S2042b in example 1. In addition, the two modules have the same examples and application scenarios as the corresponding steps, but are not limited to the contents disclosed in example 1.

In an optional example embodiment, the apparatus for device networking activation further includes: a third pushing module, wherein the third pushing module is used for, in the case where the device to be networked that has been successfully networked is activated successfully, pushing device information of the device to be networked and control authority of a user to control the device to be networked to the device to be networked.

#### Example 4

According to the example embodiments of the present invention, a cloud network device is further provided, which includes the apparatus for device networking activation as described in the foregoing example 3.

### Example 5

According to the example embodiments of the present invention, the present invention further provides an apparatus for device networking activation for implementing the device networking activation method of the above example 2. As shown in FIG. 6, the apparatus for device networking activation includes: a second networking module 601, a receiving module 603, and a second activating module 605.

The second networking module 601 is used for networking a device to be networked; the receiving module 603 is used for, in the case where the device to be networked is successfully networked, receiving an activation strategy for activating the device to be networked; and the second activating module 605 is used for, according to the received activation strategy, activating the device to be networked.

It should be noted herein that the above-mentioned second networking module 601, receiving module 603, and second activating module 605 correspond to steps S402 to S406 in example 2. In addition, the three modules have the same examples and application scenarios as the corresponding steps, but are not limited to the contents disclosed in example 2.

In an optional example embodiment, the second networking module includes: a starting unit and a second activating unit, wherein the starting unit is used for, according to the received activation strategy, starting an activation time window for limiting the time to activate the device to be networked; and the second activating unit is used for, within the activation time window, activating the device to be networked.

It should be noted herein that the starting unit and the second activating unit correspond to steps S4080 to S4082 in example 2. In addition, the two modules have the same examples and application scenarios as the corresponding steps, but are not limited to the contents disclosed in example 2.

In an optional example embodiment, the second activating unit includes a first displaying subunit, a determining subunit, and a third activating subunit. Among them, the first displaying subunit is used for displaying operation prompt information for prompting to perform an activation authentication operation; the determining subunit is used for determining whether operation confirmation information for performing the activation authentication operation on the device to be networked is received in the activation time window; and the third activating subunit is used for, in the case where the determining result is yes, activating the device to be networked.

It should be noted herein that the first displaying subunit, the determining subunit, and the third activating subunit correspond to steps S4082a to S4082c in example 2. In addition,

the two modules have the same examples and application scenarios as the corresponding steps, but are not limited to the contents disclosed in example 2.

In an optional example embodiment, the second activating module includes: an obtaining unit, a displaying unit, and a third activating unit. Among them, the obtaining unit is used for obtaining a number of times for supporting activation retries; the displaying unit is used for displaying the obtained number of times for supporting activation retries, and the third activating unit is used for, within the obtained number of times, activating the device to be networked that has been successfully networked according to the pushed activation strategy.

It should be noted herein that the obtaining unit, the displaying unit, and the third activating unit correspond to steps S4084 to S4088 in example 2. In addition, the three modules have the same examples and application scenarios as the corresponding steps, but are not limited to the contents disclosed in example 2.

In an optional example embodiment, the apparatus for device networking activation also includes: a second receiving module and a second displaying module. Among them, the second receiving module is used for, in the case where the device to be networked is successfully activated according to the received activation strategy, receiving the pushed device information of the device to be networked and control authority of a user to control the device to be networked; and the second displaying module is used for displaying the device information and the control authority received.

It should be noted herein that the second receiving module and the second displaying module correspond to steps S410 to S412 in example 2. In addition, the two modules have the same examples and application scenarios as the corresponding steps, but are not limited to the contents disclosed in example 2.

#### Example 6

According to the example embodiments of the present invention, the present invention further provides a cloud network device, including the apparatus for device networking activation in the foregoing example 5.

#### Example 7

An example embodiment of the present invention may provide a computer terminal, and the computer terminal may be any computer terminal device in a computer terminal group. Optionally, in this example embodiment, the above computer terminal may also be replaced with a terminal device such as a mobile terminal.

Optionally, in this example embodiment, the foregoing computer terminal may be located in at least one network device among a plurality of network devices in a computer network.

In this example embodiment, the above computer terminal can execute the program code of the following steps in the device networking activation method of the application program: networking a device to be networked; in the case where the device to be networked is successfully networked, pushing an activation strategy for activating the device to be networked to the device to be networked that has been successfully networked; and according to the activation strategy pushed, activating the device to be networked that has been successfully networked.

FIG. 7 shows a hardware block diagram of a computer terminal. As shown in FIG. 7, the computer terminal A may include one or more processors 702 (shown as 702a, 702b, ..., 702n in the figure) (the processor 702 may include, but is not limited to, a microprocessor MCU or a processing device such as a programmable logic device FPGA), a memory 704 for storing data, and a transmission device 706 for a communication function. In addition, it may also include: a display, an input/output interface (I/O interface), a universal serial bus (USB) port (which can be included as one of the ports of the I/O interface), a network interface, a power supply and/or a camera. A person of ordinary skill in the art would understand that the structure shown in FIG. 7 is merely an illustration, which does not limit the structure of the above electronic device. For example, the computer terminal A may also include more or fewer components than those shown in FIG. 7 or have a configuration different from that shown in FIG. 7.

It should be noted that the aforementioned one or more processors 702 and/or other data processing circuits may generally be referred to herein as “data processing circuits.” A data processing circuit may be fully or partially embodied as software, hardware, firmware, or any other combination thereof. In addition, the data processing circuit may be a single independent processing module, or may be wholly or partially integrated into any one of other elements in the computer terminal A. As mentioned in the example embodiments of the present application, the data processing circuit serves as a kind of processor control (for example, the selection of a variable resistance terminal path connected to an interface).

The processor 702 can call the information and application programs stored in the memory through the transmission device to perform the following steps: networking a device to be networked; in the case where the device to be networked is successfully networked, pushing an activation strategy for activating the device to be networked to the device to be

networked that has been successfully networked; and according to the activation strategy pushed, activating the device to be networked that has been successfully networked.

The memory 704 may be used to store software programs and modules of application software, such as program instructions/data storage devices corresponding to the device networking activation method in the example embodiments of the present application, and the processor 702 runs the software programs and modules stored in the memory 704, thereby performing various functional applications and data processing, that is, implementing the above-mentioned device networking activation method. The memory 704 may include a high-speed random access memory, and may also include a nonvolatile memory, such as one or more magnetic storage devices, flash memory, or other nonvolatile solid-state memory. In some examples, the memory 704 may further include memories remotely provided with respect to the processor 702, and these remote memories may be connected to the computer terminal A through a network. Examples of the above network include but are not limited to the Internet, an intranet, a local area network, a mobile communication network, and combinations thereof.

The transmission device 706 is used to receive or send data via a network. The above specific example of the network may include a wireless network provided by the communication provider of the computer terminal A. In one example, the transmission device 706 includes a network adapter (Network Interface Controller, NIC), which can be connected to other network devices through a base station to communicate with the Internet. In one example, the transmission device 706 may be a radio frequency (Radio Frequency, RF) module, which is used to communicate with the Internet in a wireless manner.

The display may be, for example, a touch screen type liquid crystal display (LCD), which may enable a user to interact with the user interface of the computer terminal A.

It should be noted herein that, in some optional example embodiments, the computer terminal A shown in FIG. 7 may include hardware elements (including circuits), software elements (including computer code stored on a computer-readable medium), or a combination of hardware and software components. It should be noted that FIG. 7 is only an example, and is intended to show the types of components that can be present in the computer terminal A as described above.

In this example embodiment, the computer terminal A can execute the program code of the following steps in the device networking activation method of the application program: networking a device to be networked; in the case where the device to be networked is successfully networked, pushing an activation strategy for activating the device to be

networked to the device to be networked that has been successfully networked; and according to the activation strategy pushed, activating the device to be networked that has been successfully networked.

The processor can call the information and application stored in the memory through the transmission device to perform the following steps: determining at least one activation strategy to be pushed to the device to be networked; and selecting an activation strategy from the at least one activation strategy, and pushing the selected activation strategy to the device to be networked that has been successfully networked, wherein when the device to be networked that has been successfully networked needs to be pushed with a respective activation strategy multiple times, the activation strategy selected each time is different.

Optionally, the above processor may also execute the program code of the following steps: obtaining at least one activation strategy for activating the device to be networked generated according to a product characteristic of the device to be networked; and determining the obtained at least one activation strategy as the at least one activation strategy to be pushed to the device to be networked.

Optionally, the above processor may also execute the program code of the following steps: determining an activation time window for limiting the time to activate the device to be networked; and within the determined activation time window, activating the device to be networked that has been successfully networked according to the pushed activation strategy.

Optionally, the above processor may also execute the program code of the following steps: obtaining a number of times for supporting activation retries; and within the obtained number of times, activating the device to be networked that has been successfully networked according to the pushed activation strategy.

Optionally, the above processor may also execute the program code of the following steps: in the case where the device to be networked that has been successfully networked is activated successfully, pushing device information of the device to be networked and control authority of a user to control the device to be networked to the device to be networked.

A person of ordinary skill in the art would understand that the structure shown in FIG. 7 is merely an illustration, and the computer terminal may also be a smartphone (such as an Android phone, an iOS phone, and the like), a tablet computer, a palm computer, a mobile Internet device (MID), a PAD or another terminal device. FIG. 7 does not limit the structure of the above electronic device. For example, the computer terminal A may also include more or fewer components than those shown in FIG. 7 (such as a network interface, a display device, and the like), or have a configuration different from that shown in FIG. 7.

A person of ordinary skill in the art would understand that all or part of the steps in the various methods of the above example embodiments may be completed by instructing hardware related to the terminal device through a program. The program may be stored in a computer-readable storage medium, which may include: a flash disk, a Read-Only Memory (ROM), a Random Access Memory (RAM), a magnetic disk, an optical disk, or the like.

#### Example 8

The example embodiments of the present invention also provide a storage medium. Optionally, in this example embodiment, the storage medium may be used to store the program code executed by the device networking activation method provided in the above example 1.

Optionally, in this example embodiment, the above storage medium may be located in any computer terminal in the computer terminal group in a computer network, or in any mobile terminal in a mobile terminal group.

Optionally, in this example embodiment, the storage medium is set to store program code for performing the following steps: networking a device to be networked; in the case where the device to be networked is successfully networked, pushing an activation strategy for activating the device to be networked to the device to be networked that has been successfully networked; and according to the activation strategy pushed, activating the device to be networked that has been successfully networked.

Optionally, in this example embodiment, the storage medium is set to store the program code for performing the following steps: determining at least one activation strategy to be pushed to the device to be networked; and selecting an activation strategy from the at least one activation strategy, and pushing the selected activation strategy to the device to be networked that has been successfully networked, wherein when the device to be networked that has been successfully networked needs to be pushed with a respective activation strategy multiple times, the activation strategy selected each time is different.

Optionally, in this example embodiment, the storage medium is set to store the program code for performing the following steps: obtaining at least one activation strategy for activating the device to be networked generated according to a product characteristic of the device to be networked; and determining the obtained at least one activation strategy as the at least one activation strategy to be pushed to the device to be networked.

Optionally, in this example embodiment, the storage medium is set to store the program code for performing the following steps: determining an activation time window for limiting the time to activate the device to be networked; and within the determined activation

time window, activating the device to be networked that has been successfully networked according to the pushed activation strategy.

Optionally, in this example embodiment, the storage medium is set to store the program code for performing the following steps: obtaining a number of times for supporting activation retries; and within the obtained number of times, activating the device to be networked that has been successfully networked according to the pushed activation strategy.

Optionally, in this example embodiment, the storage medium is set to store the program code for performing the following steps: in the case where the device to be networked that has been successfully networked is activated successfully, pushing device information of the device to be networked and control authority of a user to control the device to be networked to the device to be networked.

The sequence numbers of the above example embodiments of the present invention are for description only, and do not represent the advantages and disadvantages of the example embodiments.

In the above example embodiments of the present invention, the description of each example embodiment has its own emphasis. For a part that is not detailed in an example embodiment, it can be referred to the related descriptions in other example embodiments.

In the several example embodiments provided in the present application, it should be understood that the disclosed technical contents may be implemented in other ways. The device example embodiments described above are only schematic. For example, the division of the unit is only a logical function division. In actual implementation, there may be another division manner, for example, multiple units or components may be combined or integrated into another system, or some features can be ignored, or not implemented. In addition, the displayed or discussed coupling or direct coupling or communication connection may be indirect coupling or communication connection through some interfaces, units or modules, and may be in electrical or other forms.

The units described as separate components may or may not be physically separated, and the components displayed as units may or may not be physical units, that is, they can be located in one place, or can be distributed on multiple network elements. Some or all of the units may be selected according to actual needs to achieve the purpose of the solution of the example embodiment.

In addition, each functional unit in each example embodiment of the present invention may be integrated into one processing unit, or each unit may exist alone physically, or two or

more units may be integrated into one unit. The integrated unit can be implemented in the form of hardware or software function units.

If the integrated unit is implemented in the form of a software functional unit and sold or used as an independent product, it may be stored in a computer-readable storage medium. Based on this understanding, the technical solution of the present invention essentially, or as a part thereof that makes contribution to the existing technology, or all or part of the technical solution can be embodied in the form of a software product, and such a software product is stored in a storage medium, which includes several instructions to enable a computer device (which may be a personal computer, a server, a network device, etc.) to perform all or part of the steps of the methods described in various example embodiments of the present invention. The foregoing storage media include: a USB disk, a read-only memory (ROM), a random access memory (RAM), a mobile hard disk, a magnetic disk, an optical disk and other media that can store program codes.

The above are only some preferred example embodiments of the present invention. It should be noted that for a person of ordinary skill in the art, without departing from the principles of the present invention, several improvements or modifications can be made, and these improvements and modifications should also be regarded as within the scope of protection of the present invention.

## CLAIMS

1. A device networking activation method comprising:  
connecting a device to be connected to a network;  
in response to determining that the device to be networked is successfully networked,  
pushing an activation strategy for activating the device to be networked to the device to be networked that has been successfully networked; and  
activating the device to be networked that has been successfully networked according to the pushed activation strategy.
2. The method according to claim 1, wherein the pushing the activation strategy for activating the device to be networked to the device to be networked that has been successfully networked comprises:  
determining at least one activation strategy to be pushed to the device to be networked;  
and  
selecting the activation strategy from the at least one activation strategy, and pushing the selected activation strategy to the device to be networked that has been successfully networked, wherein when the device to be networked that has been successfully networked needs to be pushed with a respective activation strategy multiple times, the respective activation strategy selected each time is different.
3. The method according to claim 2, wherein the determining at least one activation strategy to be pushed to the device to be networked comprises:  
obtaining at least one activation strategy for activating the device to be networked generated according to a product characteristic of the device to be networked; and  
determining the obtained at least one activation strategy as the at least one activation strategy to be pushed to the device to be networked.
4. The method according to claim 1, wherein the activating the device to be networked that has been successfully networked according to the pushed activation strategy comprises:  
determining an activation time window for limiting a time to activate the device to be networked; and

activating the device to be networked that has been successfully networked within the determined activation time window according to the pushed activation strategy.

5. The method according to claim 1, wherein the activating the device to be networked that has been successfully networked according to the pushed activation strategy comprises:

obtaining a number of times for supporting activation retries; and

activating the device to be networked that has been successfully networked within the obtained number of times according to the pushed activation strategy.

6. The method according to any one of claims 1 to 5, wherein after the activating the device to be networked that has been successfully networked according to the pushed activation strategy, the method further comprises:

in response to determining that the device to be networked that has been successfully networked is activated successfully, pushing device information of the device to be networked and control authority of a user to control the device to be networked to the device to be networked.

7. A device networking activation method comprising:

networking a device to be networked;

in response to determining that the device to be networked is successfully networked, receiving an activation strategy for activating the device to be networked; and

activating the device to be networked according to the received activation strategy.

8. The method according to claim 7, wherein the activating the device to be networked according to the received activation strategy comprises:

starting an activation time window for limiting the time to activate the device to be networked according to the received activation strategy; and

activating the device to be networked within the activation time window.

9. The method according to claim 8, wherein the activating the device to be networked within the activation time window comprises:

displaying operation prompt information for prompting to perform an activation authentication operation;

determining whether operation confirmation information for performing the activation authentication operation on the device to be networked is received in the activation time window; and

in response to determining that the operation confirmation information for performing the activation authentication operation on the device to be networked is received in the activation time window, activating the device to be networked.

10. The method according to claim 7, wherein the activating the device to be networked according to the received activation strategy comprises:

obtaining a number of times for supporting activation retries according to the received activation strategy;

displaying the obtained number of times for supporting activation retries; and

activating the device to be networked within the displayed number of times.

11. The method according to any one of claims 7 to 10, wherein after the activating the device to be networked according to the received activation strategy, the method further comprises:

in response to determining that the device to be networked is successfully activated according to the received activation strategy, receiving pushed device information of the device to be networked and control authority of a user to control the device to be networked; and

displaying the device information and the control authority.

12. An apparatus for device networking activation, the apparatus comprising:

a first networking module that networks a device to be networked;

a pushing module that, in the case where the device to be networked is successfully networked, pushes an activation strategy for activating the device to be networked to the device to be networked that has been successfully networked; and

a first activating module that activates the device to be networked that has been successfully networked according to the activation strategy pushed.

13. A cloud network device comprising the apparatus for device networking activation according to claim 12.

14. An apparatus for device networking activation comprising:  
a second networking module that networks a device to be networked;  
a receiving module that, in the case where the device to be networked is successfully networked, receives an activation strategy for activating the device to be networked; and  
a second activating module that activating the device to be networked according to the received activation strategy.

15. A device to be networked comprising the apparatus for device networking activation according to claim 14.

16. A storage medium comprising a stored program, wherein, when the program is running, a device where the storage medium is located is controlled to execute the device networking activation method according to any one of claims 1 to 11.

17. A processor comprising: when the processor runs a program, the processor executes the device networking activation method according to any one of claims 1 to 11.