

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
16 May 2002 (16.05.2002)

PCT

(10) International Publication Number
WO 02/39474 A1

(51) International Patent Classification⁷: H01H 71/74

(21) International Application Number: PCT/IB01/02091

(22) International Filing Date:
7 November 2001 (07 11 2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/710,244 10 November 2000 (10 11.2000) US

(71) Applicant: EATON CORPORATION [US/US], Eaton Center, 111 Superior Avenue, Cleveland, OH 44114 (US)

(72) Inventors: MALINGOWSKI, Richard, P., 6413 Union Avenue, Finleyville, PA 15332 (US) GULA, Lance, 147 Saratoga Drive, Clinton, PA 15026 (US) RODGERS, Craig, A., 127 Rimp Road, Butler, PA 15002-9252 (US)

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette

(54) Title: CIRCUIT INTERRUPTER WITH THERMAL TRIP ADJUSTABILITY



(57) Abstract: A circuit interrupter including a housing, separable main contacts within the housing, and an operating mechanism within the housing and interconnected with the separable main contacts. A trip mechanism is disposed within the housing that includes a trip bar assembly rotatable about an axis and that, when rotated, generates a tripping operation causing the operating mechanism to pen the contacts. The trip bar assembly includes a trip member translatable along the axis. The trip mechanism includes a tripping actuator movable along a predetermined path of travel as a function of electrical current. The tripping actuator contacts a contact area of the trip member at a predetermined location along the predetermined path of travel of the tripping actuator and causes the trip bar assembly to rotate and generate the tripping operation upon a predetermined current threshold. When the trip member is translated along the axis, the contact area is contacted by the tripping actuator at a different location along the predetermined path of the tripping actuator whereby the predetermined current threshold is changed

WO 02/39474 A1

162162