

DESCRIPTION

MOBILE COMMUNICATION METHOD, MOBILE STATION, AND RADIO BASE
STATION

5 TECHNICAL FIELD

[0001]

The present invention relates to a mobile communication method in which a mobile station starts a reception of downlink data, transmitted from a radio base station, by using a downlink
10 radio resource persistently allocated in first cycles, at a first allocation starting time, and transmits acknowledgement information for the downlink data by using a persistently allocated uplink radio resource, and relates to the mobile station and the radio base station.

15

BACKGROUND ART

[0002]

A communication method as a successor of the W-CDMA scheme and the HSDPA scheme, namely, the LTE (Long Term
20 Evolution) scheme has been considered by the W-CDMA standardization organization 3GPP, and the specification setting work is underway.

[0003]

As a radio access scheme of the LTE scheme, use of the
25 OFDMA in the downlink and the SC-FDMA (Single-Carrier Frequency Division Multiple Access) in the uplink is under consideration.

[0004]

The OFDMA is a scheme for dividing a frequency band into plural narrow frequency bands (sub-carriers) and transmitting

data loaded on the respective divided frequency bands. In this scheme, high-speed transmission is achieved and frequency utilization efficiency is improved by arranging sub-carriers densely on the frequency bands in such a manner that the sub-carriers partially overlap but do not interfere with each other.

[0005]

The SC-FDMA is a transmission scheme which reduces interference between terminals by dividing a frequency band and transmitting data by using frequency bands different among plural terminals. The SC-FDMA has a feature of less fluctuation in the transmission power, which achieves low power consumption and wide coverage of terminals.

[0006]

The LTE scheme is a system in which plural mobile stations perform communication by sharing one or more physical channels in both uplink and downlink.

[0007]

A channel shared by plural mobile stations is generally called a shared channel, which is, in the LTE scheme, a "Physical Uplink Shared Channel (PUSCH)" in the uplink and a "Physical Downlink Shared Channel (PDSCH)" in the downlink.

[0008]

Also, such a shared channel is, as a transport channel, an "Uplink Shared Channel (UL-SCH)" in the uplink and a "Downlink Shared Channel (DL-SCH)" in the downlink.

[0009]

In such a communication system using shared channels as described above, it is necessary to select mobile station

UE to which the shared channel is to be allocated, and to transmit, to the selected mobile station UE, a signal indicating the allocation of the shared channel, for each sub-frame (1ms, in the LTE scheme).

5 [0010]

In the LTE scheme, a control channel used for the signaling is called the "Physical Downlink Control Channel (PDCCH)" or "Downlink L1/L2 Control Channel (DL L1/L2 Control Channel)".

10 [0011]

Meanwhile, the processing for each sub-frame of selecting mobile station UE to which the shared channel is to be allocated is generally called the "scheduling". In this case, the processing may also be called the "dynamic scheduling", because the mobile station UE to which the shared channel is allocated is dynamically selected for each sub-frame. Furthermore, "allocating the shared channel" described above may be alternatively expressed as "allocating a radio resource for the shared channel".

20 [0012]

Information of the physical downlink control channel includes, for example, the "downlink scheduling information", "the uplink scheduling grant", and the like.

[0013]

25 The downlink scheduling information includes, for example, downlink resource block allocation information, ID of UE, the number of streams, information on the precoding vector, data size, modulation scheme, information on the HARQ (hybrid automatic repeat request), and the like, on the downlink shared

channel.

[0014]

Meanwhile, the "uplink scheduling grant" includes, for example, uplink resource block allocation information, ID of UE, data size, modulation scheme, uplink transmission power information, information on demodulation reference signal in the uplink MIMO, and the like, on the uplink shared channel.

[0015]

Note that, the "downlink scheduling information" and the "uplink scheduling grant" described above may be collectively referred to as "downlink control information (DCI)".

[0016]

In the LTE scheme, the HARQ is applied to a communication using the shared channel described above. For example, on the downlink, the mobile station UE decodes the downlink shared channel, and transmits, to the radio base station eNB, acknowledgement information (ACK/NACK) based on the decoding result (CRC check result) by using the physical uplink control channel (PUCCH).

[0017]

Then, the radio base station eNB performs retransmission control according to a content of the acknowledgement information, which is expressed either with a positive response (ACK) indicating that the transmitted signal is received properly or a negative response (NACK) indicating that the transmitted signal is not received properly.

[0018]

FIG. 8 shows the downlink dynamic scheduling and the

HARQ processing in a mobile communication system of the LTE scheme described above.

[0019]

In the sub-frame #3, the radio base station eNB transmits,
5 to the mobile station UE, downlink scheduling information via a PDCCH and downlink data via a PDSCH.

[0020]

Then, the mobile station UE receives downlink data via the PDSCH, on the basis of the downlink scheduling information
10 received via the PDCCH.

[0021]

In the sub-frame #7, the mobile station UE transmits the acknowledgement information for the downlink data using a PUCCH, and the radio base station eNB receives the
15 acknowledgement information (ACK/NACK) mapped to the PUCCH.

[0022]

The radio resource of the PDSCH described above is dynamically allocated as being notified by the PDCCH. Also, the radio resource of the PUCCH described above is associated
20 with the radio resource number of the PDCCH described above. Dynamic allocation of such radio resource of the PDCCH also results in dynamic allocation of such radio resource of the PUCCH.

[0023]

25 That is, in the normal downlink scheduling (dynamic scheduling) of a mobile communication system of the LTE scheme, the radio base station eNB is configured to dynamically allocate a downlink radio resource and an uplink radio resource to the mobile station UE through the PDCCH, the downlink radio resource

being for transmitting downlink data to the mobile station UE, the uplink radio resource being for transmitting acknowledgement information for the downlink data.

[0024]

5 Furthermore, in the dynamic scheduling described above, a time difference between a sub-frame from which a PUCCH signal is transmitted and a sub-frame from which a PDCCH signal and a PDSCH signal are transmitted is fixed.

[0025]

10 On the other hand, in the "persistent scheduling" that is under consideration to achieve the VoIP and the like, the radio base station eNB is configured to start a persistent allocation of the downlink radio resource (PDSCH) to a mobile station in the first cycles, at a sub-frame (first allocation
15 starting time) in which the downlink scheduling information is transmitted to the mobile station UE through the PDCCH, and to persistently allocate the uplink radio resource (PUCCH) to the mobile station UE through the upper layer (Radio Resource Control: RRC) signaling.

20 [0026]

 In the "persistent scheduling", the downlink scheduling information is transmitted via the PDCCH in a first transmission only, and the downlink scheduling information is not transmitted via the PDCCH in the subsequent transmissions. For
25 this reason, the method for associating a radio resource of the PUCCH with a radio resource number of the PDCCH cannot be applied unlike the "dynamic scheduling" described above.

[0027]

 Accordingly, the uplink radio resource (PUCCH) in the

“persistent scheduling” is persistently allocated to the mobile station UE by using the upper layer (RRC) signaling.

[0028]

Here, the uplink radio resource represents, for example,
5 a code resource in the code multiplexing or a frequency resource in the frequency multiplexing.

[0029]

The frequency resource may be designated by a resource block number of a resource block (set of sub-carriers) from
10 which the PUCCH is transmitted.

[0030]

Furthermore, when a plurality of acknowledgement information are multiplexed within one resource block, the uplink radio resource may be designated by a predetermined
15 identification number. For example, an identification number may be used to designate an amount of cyclic shift in the multiplexing of CAZAC sequence cyclic shift or an orthogonal cover code in the block spreading.

[0031]

20 Furthermore, generally in the HARQ, a time difference between a time point where the above-described downlink radio resource (PDSCH) is allocated and a time point where the above-described uplink radio resource (PUCCH) is allocated is fixed. Accordingly, a transmission timing of the PUCCH is
25 uniquely determined by designating a first allocation starting time through the PDCCH.

[0032]

In the example shown in FIG. 9, the downlink radio resource (PDSCH) described above are persistently allocated in

cycles of 20 ms, and the uplink radio resource (PUCCH) described above is persistently allocated for each downlink radio resource (PDSCH).

[0033]

5 Specifically, the downlink radio resource (PDSCH) is persistently allocated in the sub-frames #3, #23, ..., while the acknowledgement information is transmitted in the sub-frames #7, #27, ...

[0034]

10 Note that, in the sub-frame #3 of the example shown in FIG. 9, a first allocation starting time is designated by the PDCCH.

SUMMARY OF THE INVENTION

15 PROBLEMS TO BE SOLVED BY THE INVENTION

[0035]

 Here, in the prior art, a time difference between a time point where the downlink radio resource (PDSCH) described above is allocated and a time point where the uplink radio resource
20 (PUCCH) described above is allocated, is specified as a predetermined period of time (for example, four sub-frames).

[0036]

 Accordingly, when a timing of the downlink radio resource (PDSCH) allocated in the "persistent scheduling" is
25 changed, a timing at which the uplink radio resource (PUCCH) is allocated is also changed similarly.

[0037]

 Note that, in the persistent scheduling, the uplink radio resource (PUCCH) such as a code resource in the code

multiplexing and a frequency resource in the frequency multiplexing is persistently allocated to the mobile station UE by using the upper layer signaling as described above. For this reason, even in the case where a timing at which the uplink radio resource (PUCCH) is allocated is changed, the uplink radio resource (PUCCH) such as the code resource and the frequency resource is not changed.

[0038]

At this time, if the uplink radio resource (PUCCH) allocated at a changed timing is already used by another mobile station UE, the uplink radio resource (PUCCH) after the change contends with the uplink radio resource (PUCCH) of the another mobile station UE. Thus, there has been a problem that the process of changing the timing of the downlink radio resource (PDSCH) allocated in the "persistent scheduling" described above cannot be performed.

[0039]

In other words, there has been a problem that a timing of the downlink radio resource (PDSCH) allocated in the "persistent scheduling" cannot be changed freely, since a time difference between a time point where the above-described downlink radio resource (PDSCH) is allocated and a time point where the above-described uplink radio resource (PUCCH) is allocated is fixed, and the uplink radio resource (PUCCH) is set in advance.

[0040]

Accordingly, the present invention has been made to solve the above problems. An object of the present invention is to provide a mobile communication method, a mobile station

and a radio base station which are capable of flexibly setting a timing of a downlink radio resource (PDSCH) allocated in "persistent scheduling".

5 DISCLOSURE OF THE INVENTION

[0041]

A first aspect of the present invention is summarized as a mobile communication method in which a mobile station starts a reception of downlink data, transmitted from a radio base station, by using a downlink radio resource persistently allocated in first cycles, at a first allocation starting time, and transmits acknowledgement information for the downlink data by using a persistently allocated uplink radio resource, the mobile communication method including the steps of: (A) notifying, from the radio base station to the mobile station, the first cycle and first information on the uplink radio resource; and (B) determining, at the mobile station, the first allocation starting time, starting a reception of the downlink data via the downlink radio resource at the first allocation starting time, and transmitting the acknowledgement information via the uplink radio resource, when receiving a persistent allocation signal from the radio base station; wherein, in the step (B), the uplink radio resource is determined based on the first information on the uplink radio resource and second information on the uplink radio resource included in the persistent allocation signal; and the acknowledgement information is transmitted via the determined uplink radio resource.

[0042]

In the first aspect, in the step (A), the first information on the uplink radio resource can be an identification number of a resource block, an orthogonal cover sequence number in a block spreading, or an identification
5 number designating an amount of cyclic shift in a CAZAC sequence.

[0043]

In the first aspect, a part of information on the uplink radio resource can be notified by the first information on the
10 uplink radio resource; and a rest of information on the uplink radio resource is notified by the second information on the uplink radio resource.

[0044]

In the first aspect, the first information on the uplink
15 radio resource can be an identification number of a resource block; and the second information on the uplink radio resource can be an orthogonal cover sequence number in a block spreading and an amount of cyclic shift in a CAZAC sequence.

[0045]

20 In the first aspect, in the step (B), the second information on the uplink radio resource can be notified by a power control command in a dynamic allocation signal to be used in a scheduling in which a downlink radio resource is dynamically allocated or a bit designating a redundancy version
25 of HARQ, when a signal format of the persistent allocation signal is the same as a signal format of the dynamic allocation signal.

[0046]

A second aspect of the present invention is summarized

as a mobile station configured to start a reception of downlink data, transmitted from a radio base station, by using a downlink radio resource persistently allocated in first cycles, at a first allocation starting time, and to transmit acknowledgement
5 information for the downlink data by using a persistently allocated uplink radio resource, the mobile station including:
a persistent communication information receiving unit configured to receive the first cycle and first information on the uplink radio resource from the radio base station; and a
10 communication unit configured to determine the first allocation starting time, to start a reception of the downlink data via the downlink radio resource at the first allocation starting time, and to transmit the acknowledgement information via the
uplink radio resource, when receiving a persistent allocation
15 signal from the radio base station; wherein the communication unit is configured to determine the uplink radio resource based on the first information on the uplink radio resource and second information on the uplink radio resource included in the
persistent allocation signal, and to transmit the
20 acknowledgement information via the determined uplink radio resource.

[0047]

In the second aspect, the first information on the uplink radio resource can be an identification number of a resource
25 block, an orthogonal cover sequence number in a block spreading, or an identification number designating an amount of cyclic shift in a CAZAC sequence.

[0048]

In the second aspect, a part of information on the uplink

radio resource can be notified by the first information on the uplink radio resource; and a rest of information on the uplink radio resource is notified by the second information on the uplink radio resource.

5 [0049]

In the second aspect, the first information on the uplink radio resource can be an identification number of a resource block; and the second information on the uplink radio resource can be an orthogonal cover sequence number in a block spreading and an amount of cyclic shift in a CAZAC sequence.

[0050]

In the second aspect, the communication unit can be configured to acquire the second information on the uplink radio resource based on a power control command in a dynamic allocation signal to be used in a scheduling in which a downlink radio resource is dynamically allocated or a bit designating a redundancy version of HARQ, when a signal format of the persistent allocation signal is the same as a signal format of the dynamic allocation signal.

20 [0051]

A third aspect of the present invention is summarized as a radio base station used in a mobile communication system in which a mobile station starts a reception of downlink data, transmitted from the radio base station, by using a downlink radio resource persistently allocated in first cycles, at a first allocation starting time, and transmits acknowledgement information for the downlink data by using a persistently allocated uplink radio resource, the radio base station including: a persistent communication information

transmitting unit configured to notify, to the mobile station, the first cycle and first information on the uplink radio resource; a persistent allocation signal transmitting unit configured to transmit a persistent allocation signal to the mobile station; and a communication unit configured to start a transmission of the downlink data via the downlink radio resource at the first allocation starting time to be determined by the persistent allocation signal, and to receive the acknowledgement information via the uplink radio resource; wherein the communication unit is configured to determine the uplink radio resource based on the first information on the uplink radio resource and second information on the uplink radio resource included in the persistent allocation signal and to receive the acknowledgement information via the determined uplink radio resource.

[0052]

In the third aspect, in the step (A), the first information on the uplink radio resource can be an identification number of a resource block, an orthogonal cover sequence number in a block spreading, or an identification number designating an amount of cyclic shift in a CAZAC sequence.

[0053]

In the third aspect, a part of information on the uplink radio resource can be notified by the first information on the uplink radio resource; and a rest of information on the uplink radio resource is notified by the second information on the uplink radio resource.

[0054]

In the third aspect, the first information on the uplink radio resource can be an identification number of a resource block; and the second information on the uplink radio resource can be an orthogonal cover sequence number in a block spreading and an amount of cyclic shift in a CAZAC sequence.

[0055]

In the third aspect, the communication unit can be configured to notify the second information on the uplink radio resource by a power control command in a dynamic allocation signal to be used in a scheduling in which a downlink radio resource is dynamically allocated or a bit designating a redundancy version of HARQ, when a signal format of the persistent allocation signal is the same as a signal format of the dynamic allocation signal.

[0056]

In the third aspect, the persistent allocation signal transmitting unit is configured to set the second information on the uplink radio resource in such a manner that the uplink radio resource does not contend with a uplink radio resource allocated to another mobile station.

[0057]

A fourth aspect of the present invention is summarized as a radio resource selecting method of semi-persistently selecting a radio resource to be allocated to an uplink acknowledgement signal indicating a reception state of a persistently allocated downlink signal from a plurality of radio resources defined by frequencies and codes, the radio resource selecting method including the steps of: (A) selecting candidates for an allocation radio resource to be allocated to

the uplink acknowledgement signal from the plurality of radio resources; (B) notifying candidate information on the selected candidates for the allocation radio resource; and (C) selecting a single allocation radio resource from the plurality of candidates for the allocation radio resource indicated in the candidate information notified in the step (B).

[0058]

In the fourth aspect, in the step (C), an unused allocation radio resource can be selected from the plurality of candidates for the allocation radio resource.

[0059]

In the fourth aspect, the radio resource selecting method according can further include the step of: (D) notifying designation information on a single allocation radio resource among the plurality of candidates for the allocation radio resource, and, in the step (C), the single allocation radio resource related to the designation information notified in the step (D) can be selected from the plurality of candidates for the allocation radio resource indicated in the candidate information notified in the step (B).

[0060]

A fifth aspect of the present invention is summarized as a radio base station configured to semi-persistently select a radio resource to be allocated to an uplink acknowledgement signal indicating a reception state of a persistently allocated downlink signal from a plurality of radio resources defined by frequencies and codes, the radio base station including: a candidate selector unit configured to select candidates for an allocation radio resource to be allocated to the uplink

acknowledgement signal from the plurality of radio resources;
and a candidate notification unit configured to notify
candidate information on the selected candidates for the
allocation radio resource.

5 [0061]

In the fifth aspect, the radio base station can further
include: a selector unit configured to select a single
allocation radio resource from the plurality of candidates for
the allocation radio resource; and a designation information
10 notification unit configured to notify designation information
on the selected single allocation radio resource.

[0062]

A sixth aspect of the present invention is summarized
as a mobile station used in a mobile communication system in
15 which a radio base station semi-persistently selects a radio
resource to be allocated to an uplink acknowledgement signal
indicating a reception state of a persistently allocated
downlink signal from a plurality of radio resources defined by
frequencies and codes, the mobile station including: a
20 candidate information receiver unit configured to receive
candidate information on candidates for allocation radio
resource from the radio base station; and a radio resource
selector unit configured to select a single allocation radio
resource from the plurality of candidates for the allocation
25 radio resource indicated in the received candidate information.

[0063]

In the sixth aspect, the radio resource selector unit
can be configured to select an unused allocation radio resource
from the plurality of candidates for the allocation radio

resource.

[0064]

In the sixth aspect, the mobile station can further include a designation information receiver unit configured to receive designation information on the single allocation radio resource among the plurality of candidates for the allocation radio resource, and the radio resource selector unit can be configured to select the single allocation radio resource notified in the designation information from the plurality of candidates for the allocation radio resource.

EFFECT OF THE INVENTION

[0065]

As described above, according to the present invention, it is possible to provide a mobile communication method, a mobile station and a radio base station which are capable of flexibly setting a timing of a downlink radio resource (PDSCH) allocated in "persistent scheduling".

BRIEF DESCRIPTION OF THE DRAWINGS

[0066]

[FIG. 1] FIG. 1 is a functional block diagram of a mobile station according to a first embodiment of the present invention.

[FIG. 2] FIG. 2 is a diagram for explaining a scheduling performed in a mobile communication system according to the first embodiment of the present invention.

[FIG. 3] FIG. 3 is a diagram for explaining a method of determining an uplink radio resource (PUCCH) performed in a

mobile communication system according to the first embodiment of the present invention.

[FIG. 4] FIG. 4 is a functional block diagram of a radio base station according to the first embodiment of the present invention.

[FIG. 5] FIG. 5 is a diagram for explaining a method of determining contents of second information on the uplink radio resource (PUCCH) performed in the mobile communication system according to the first embodiment of the present invention.

[FIG. 6] FIG. 6 is a flowchart showing operations of a mobile station according to the first embodiment of the present invention.

[FIG. 7] FIG. 7 is a flowchart showing operations of a radio base station according to the first embodiment of the present invention.

[FIG. 8] FIG. 8 is a diagram for setting up a scheduling in a general LTE mobile communication system.

[FIG. 9] FIG. 9 is a diagram for setting up a scheduling in a general mobile communication system of the LTE scheme.

MODES FOR CARRYING OUT THE INVENTION

[0067]

(Configuration of Mobile Communication System according to First Embodiment of Present Invention)

Referring to FIG. 1 and FIG. 2, a configuration of a mobile communication system according to a first embodiment of the present invention is described. This embodiment is described by citing a mobile communication system of the LTE scheme, but the present invention can also be applied to mobile

communication systems to which any other scheme is applied.
[0068]

In a mobile communication system according to this embodiment, the mobile station UE is configured to start a
5 reception of the downlink data, transmitted from the radio base station eNB, by using a PDSCH (downlink radio resource) persistently allocated in first cycles, at a first allocation starting time, and to transmit acknowledgement information (ACK/NACK) for the downlink data by using an PUCCH (uplink radio
10 resource).

[0069]

Here, a time difference between a reception timing of the downlink data and a transmission timing of the acknowledgement information is fixed.

15 [0070]

As shown in FIG. 1, the mobile station UE includes a persistent information receiver unit 11, a persistent allocation signal receiver unit 12, a downlink data receiver unit 13 and an ACK/NACK transmitter unit 14.

20 [0071]

The persistent information receiver unit 11 is configured to receive, from the radio base station eNB, persistent information (persistent communication information) containing the above-described first cycle and first
25 information on the uplink radio resource (PUCCH).

[0072]

Specifically, the persistent information receiver unit 11 is configured to acquire the above-described persistent information on the basis of an RRC message transmitted by the

radio base station eNB.

[0073]

As will be described later, in the mobile communication system according to the first embodiment of the present invention, the information on the uplink radio resource (PUCCH) includes first information on the uplink radio resource (PUCCH) and second information on the uplink radio resource (PUCCH), and is notified from the radio base station eNB to the mobile station UE.

10 [0074]

As will be described later, the second information on the uplink radio resource (PUCCH) is notified by a persistent allocation signal, i.e., a PDCCH which instructs a persistent allocation of the PDSCH (downlink radio resource) for the “persistent scheduling”.

15 [0075]

Here, the information on the uplink radio resource (PUCCH) represents, for example, a resource block number of a resource block (set of sub-carriers) to which the PUCCH is transmitted, or an identification number used when a plurality of acknowledgement information are multiplexed within one resource block.

[0076]

For example, an amount of cyclic shift in the multiplexing of the CAZAC sequence cyclic shift or an orthogonal cover number in the block spreading may be designated by such identification number.

25 [0077]

Moreover, a part of information out of the information

on the uplink radio resource (PUCCH) is notified by the persistent information (persistent communication information), while the rest of the information is notified by the persistent allocation signal as will be described later.

5 [0078]

Here, for example, the persistent information is a RRC message and the persistent allocation signal is the PDCCH which instructs a persistent allocation of the PDSCH (downlink radio resource) for the "persistent scheduling".

10 [0079]

To be more precise, for example, out of the information on the uplink radio resource (PUCCH), a resource block number of a resource block (set of subcarriers) from which the PUCCH is transmitted may be notified by the persistent information (persistent communication information), while the rest of the information, namely, an identification number used when a plurality of acknowledgment information within one resource block are multiplexed is notified by the persistent allocation signal as will be described later.

20 [0080]

Here, for example, the identification number is an amount of cyclic shift in the multiplex of the CAZAC sequence cyclic shift or an orthogonal cover number in the block spreading.

25 [0081]

Note that the above-described example is merely an example. The identification number used when a plurality of acknowledgment information within one resource block are multiplexed may be notified by the persistent information

(persistent communication information), while the rest of the information, namely, the resource block number of the resource block (set of subcarriers) from which the PUCCH is transmitted may be notified by the persistent allocation signal.

5 [0082]

Alternatively, a part of the information on the uplink radio resource (PUCCH) divided by any other methods may be notified by the persistent information (persistent communication information), while the rest of the information
10 may be notified by the persistent allocation signal.

[0083]

Meanwhile, the information on the uplink radio resource (PUCCH) described above may be in any form as long as the radio resource can be identified.

15 [0084]

For example, the information on the uplink radio resource (PUCCH) may be an identification number of a code resource in the code multiplexing described above, an identification number of a frequency resource in the frequency
20 multiplexing, an identification number of a time resource in the time multiplexing, or an identification number of a resource in a hybrid multiplexing of the code multiplexing, the frequency multiplexing and the time multiplexing described above.

[0085]

25 In this case as well, a part of the information on the uplink radio resource (PUCCH) is notified by the persistent information (persistent communication information), while the rest of the information is notified by the persistent allocation signal.

[0086]

To be more precise, for example, when multiplexing is performed in accordance with a hybrid multiplexing of the time multiplexing and the frequency multiplexing, an identification
5 number of a resource in the time multiplexing may be notified by the persistent information (persistent communication information), while an identification number of a resource in the frequency multiplexing may be notified by the persistent allocation signal, and vice versa.

10 [0087]

Meanwhile, for example, when multiplexing is performed in accordance with a hybrid multiplexing of the time multiplexing and the code multiplexing, an identification
15 number of a resource in the time multiplexing may be notified by the persistent information (persistent communication information), while an identification number of a resource in the code multiplexing may be notified by the persistent allocation signal, and vice versa.

[0088]

20 Meanwhile, for example, when multiplexing is performed in accordance with a hybrid multiplexing of the frequency multiplexing and the code multiplexing, an identification number of a resource in the frequency multiplexing may be notified by the persistent information (persistent
25 communication information), while an identification number of a resource in the code multiplexing may be notified by the persistent allocation signal, and vice versa.

[0089]

The above-described example shows a case where a part

of the information out of the information on the uplink radio resource (PUCCH) is notified by the persistent information (persistent communication information), while the rest of the information is notified by the persistent allocation signal.

5 However, it is not always necessary to define the information to be notified by the persistent information (persistent communication information) and the information to be notified by the persistent allocation signal to be exclusive of each other. These information may partially or entirely overlap
10 each other.

[0090]

Meanwhile, the above-described information on the uplink radio resource (PUCCH) is supplied to the ACK/NACK transmitter unit 14.

15 [0091]

Furthermore, in a mobile communication system of the LTE scheme, information on the first allocation starting time described above is not included in such persistent information.

[0092]

20 This is intended to make the radio base station eNB flexibly determine a time resource to allocate the PDSCH (downlink radio resource) described above, whereby utilization efficiency of the radio resource is improved when the "persistent scheduling" is applied.

25 [0093]

Meanwhile, it is not necessary that the transmission timing of the uplink radio resource (PUCCH) is contained as the persistent information, since this information is uniquely determined based on the reception timing of the downlink radio

resource (PDSCH) described above and a fixedly defined time offset.

[0094]

For example, transmission timing of the uplink radio
5 resource (PUCCH) may be defined as follows:

(Transmission timing of uplink radio resource (PUCCH))
= (reception timing of downlink radio resource PDSCH)) + 4 ms
[0095]

Meanwhile, the above value of 4 ms is just an example
10 and therefore may be other than 4 ms. Alternatively, 4 ms may
be expressed as four sub-frames.

[0096]

The persistent allocation signal receiver unit 12 is
configured to receive the persistent allocation signal from the
15 radio base station eNB.

[0097]

Specifically, the persistent allocation signal
receiver unit 12 is configured to receive, from the radio base
station eNB, a PDCCH instructing a persistent allocation of the
20 PDSCH (downlink radio resource) for the "persistent scheduling",
as the persistent allocation signal.

[0098]

For example, the persistent allocation signal receiver
unit 12 may be configured to determine, on the basis of RNTI
25 or the like set to PDCCH, whether the PDCCH is a PDCCH to instruct
a persistent allocation of the PDSCH (downlink radio resource)
for the "persistent scheduling" or a PDCCH to dynamically
allocate the PDSCH (downlink radio resource) for normal
downlink scheduling.

[0099]

Meanwhile, the persistent allocation signal receiver unit 12 may be configured to determine, on the basis of one specific bit in the PDCCH, whether the PDCCH is a PDCCH to instruct a persistent allocation of the PDSCH (downlink radio resource) for the "persistent scheduling" or a PDCCH to dynamically allocate the PDSCH (downlink radio resource) for normal downlink scheduling.

[0100]

Alternatively, when a part of information elements in the PDCCH is configured to indicate whether the PDCCH is a PDCCH to instruct a persistent allocation of the PDSCH (downlink radio resource) for the "persistent scheduling", or a PDCCH to dynamically allocate the PDSCH (downlink radio resource) for normal downlink scheduling, the persistent allocation signal receiver unit 12 may be configured to determine, on the basis of the part of information elements in the above PDCCH, whether the PDCCH is a PDCCH to instruct a persistent allocation of the PDSCH (downlink radio resource) for the "persistent scheduling", or a PDCCH to dynamically allocate the PDSCH (downlink radio resource) for normal downlink scheduling.

[0101]

Furthermore, the persistent allocation signal contains the second information on the uplink radio resource (PUCCH), in addition to the information to instruct a persistent allocation of the PDSCH (downlink radio resource) for the "persistent scheduling".

[0102]

Here, the second information on the uplink radio

resource (PUCCH) is, for example, a resource block number of the PUCCH (uplink radio resource), or information indicating an identification number used when a plurality of acknowledgment information are multiplexed within one resource
5 block.

[0103]

To be more precise, as described previously, the second information on the uplink radio resource (PUCCH) is the information other than the information notified by the
10 persistent information (persistent communication information) (first information on uplink radio resource (PUCCH)) out of the information on the uplink radio resource (PUCCH).

[0104]

In other words, a part of the information out of the
15 information on the uplink radio resource (PUCCH) is notified by the persistent information (persistent communication information), while the rest of the information is notified by the persistent allocation signal.

[0105]

20 Here, for example, the persistent information is the RRC message, and the persistent allocation signal is the PDCCH which instructs a persistent allocation of the PDSCH (downlink radio resource) for the "persistent scheduling".

[0106]

25 To be more precise, for example, out of the information on the uplink radio resource (PUCCH), the resource block number of the resource block (set of subcarriers) from which the PUCCH is transmitted may be notified by the persistent information (persistent communication information), while the rest of the

information, namely, the identification number used when a plurality of acknowledgment information are multiplexed within one resource block may be notified by the persistent allocation signal.

5 [0107]

Here, the identification number is, for example, the amount of cyclic shift in the multiplex of CAZAC sequence cyclic shift or the orthogonal cover number in the block spreading.
[0108]

10 Note that the above-described example is merely an example. Out of the information on the uplink radio resource (PUCCH), the identification number used when a plurality of acknowledgment information are multiplexed within one resource block may be notified by the persistent information (persistent
15 communication information), while the rest of the information, namely, the resource block number of the resource block (set of subcarriers) from which the PUCCH is transmitted may be notified by the persistent allocation signal.

[0109]

20 Alternatively, a part of the information on the uplink radio resource (PUCCH) divided by any other methods may be notified by the persistent information (persistent communication information), while the rest of the information may be notified by the persistent allocation signal.

25 [0110]

Details of the second information on the uplink radio resource (PUCCH) will be described later.

[0111]

Such second information on the uplink radio resource

(PUCCH) is given to the ACK/NACK transmitter unit 14.

[0112]

The downlink data receiver unit 13 is configured to receive the downlink data transmitted via the PDSCH (downlink
5 radio resource) allocated by the PDCCH.

[0113]

Specifically, the downlink data receiver unit 13 is configured to, when the above-described persistent allocation signal (persistent allocation signal) is received by the
10 persistent allocation signal receiver unit 12, determine a sub-frame which has received such PDCCH as a first allocation starting time described above, and start a persistent reception of the downlink data via the PDSCH (downlink radio resource) for the "persistent scheduling" in the above-described first
15 cycle, at the first allocation starting time.

[0114]

In the example shown in FIG. 2, since the persistent allocation signal receiver unit 12 has received the above-described persistent allocation signal in the sub-frame
20 #3 via the PDCCH, the downlink data receiver unit 13 is configured to receive the downlink data via the PDSCH (downlink radio resource) mapped to resource blocks (resource block: set of sub-carriers) within the sub-frame #3 designated by the PDCCH.

25 [0115]

Furthermore, the downlink data receiver unit 13 is configured to start a reception of the downlink data via a PDSCH (downlink radio resource) mapped to the resource blocks (resource block: set of sub-carriers) designated by the PDCCH

in the cycle of 20 ms, at the sub-frame #3.

[0116]

That is, the downlink data receiver unit 13 is configured to receive the downlink data via the PDSCH (downlink radio resource) mapped to resource blocks (resource block: set of sub-carriers) designated by the PDCCH in the sub-frames #3, #23, #43, ...

[0117]

The ACK/NACK transmitter unit 14 is configured to receive, from the persistent information receiver unit 11, the first information on the uplink radio resource (PUCCH) notified by the persistent information.

[0118]

In addition, the ACK/NACK transmitter unit 14 is configured to receive, from the persistent information receiver unit 12, the second information on the uplink radio resource (PUCCH) notified by the persistent allocation signal.

[0119]

The ACK/NACK transmitter unit 14 is configured to determine the uplink radio resource (PUCCH) on the basis of the first information on the uplink radio resource (PUCCH) notified by the persistent information and the second information on the uplink radio resource (PUCCH) notified by the persistent allocation signal, and to transmit acknowledgment information (ACK/NACK) corresponding to the received downlink data via the uplink radio resource (PUCCH). The acknowledgment information (ACK/NACK) is determined based on a decoding result of the downlink data by the downlink data receiver unit 13.

[0120]

By using FIG. 3, an example is shown of a method of determining the uplink radio resource (PUCCH) on the basis of the above-described first information on the uplink radio resource (PUCCH) notified by the persistent information and the
5 second information on the uplink radio resource (PUCCH) notified by the persistent allocation signal.

[0121]

In FIG. 3, two resource blocks are defined as the uplink radio resource (PUCCH), and #0 and #1 are defined as resource
10 block numbers thereof.

[0122]

Meanwhile, eight radio resources are defined in each resource block, and #0, #1, #2, ..., #7 are defined as identification numbers thereof. For example, these
15 identification numbers may be the above-described identification numbers when a plurality of the acknowledgment information are multiplexed within one resource block.

[0123]

Here, consideration is made of a case where the resource
20 block number #1 is designated by the first information on the uplink radio resource (PUCCH) notified by the persistent information and the identification number #5 is designated by the second information on the uplink radio resource (PUCCH) notified by the persistent allocation signal.

25 [0124]

In this case, the ACK/NACK transmitter unit 14 determines the radio resource defined by the resource block number #1 and the identification number #5 inside that resource block as the radio resource for transmitting the acknowledgment

information (ACK/NACK) corresponding to the received downlink data, i.e., the uplink radio resource (PUCCH).

[0125]

Specifically, the radio resource for transmitting the
5 acknowledgment information (ACK/NACK) corresponding to the received downlink data, i.e., the uplink radio resource (PUCCH) is determined based on the first information on the uplink radio resource (PUCCH) notified by the persistent information and the second information on the uplink radio resource (PUCCH)
10 notified by the persistent allocation signal.

[0126]

In other words, a part of the information on the uplink radio resource (PUCCH) is notified by the persistent information, while the rest of the information is notified by
15 the persistent allocation signal, and the uplink radio resource (PUCCH) is determined based on both of the information.

[0127]

In the above-described example, the resource block number is notified by the above-described first information on
20 the uplink radio resource (PUCCH), while the identification information in one resource block is notified by the above-described second information on the uplink radio resource (PUCCH). Instead, the identification information in one resource block may be notified by the above-described first
25 information on the uplink radio resource (PUCCH), while the resource block number may be notified by the above-described second information on the uplink radio resource (PUCCH).

[0128]

Alternatively, a part of the information on the uplink

radio resource (PUCCH) divided by any other methods may be notified as the first information on the uplink radio resource (PUCCH), while the rest of the information may be notified as the second information on the uplink radio resource (PUCCH).

5 [0129]

Here, the identification information in one resource block is, for example, the amount of cyclic shift in the multiplexing of CAZAC sequence cyclic shift or the orthogonal cover number in the block spreading.

10 [0130]

Meanwhile, a plurality of identification numbers for identifying resources other than those described above may be defined, and a part of the plurality of identification numbers may be notified by the above-described first information on the uplink radio resource (PUCCH), while the rest of the plurality of identification numbers may be notified by the above-described first second information on the uplink radio resource (PUCCH).

[0131]

20 Although eight radio resources are defined in each resource block in the above-described example, a similar method of determining the uplink radio resource (PUCCH) is applicable when more or less than eight radio resources are defined.

[0132]

25 Meanwhile, although two resource blocks are defined in the above-described example, it is also possible to define a single resource block or three or more resource blocks.

[0133]

Meanwhile, in the above-described example, the uplink

radio resource (PUCCH) is determined based on the first information on the uplink radio resource (PUCCH) notified by the persistent information and the second information on the uplink radio resource (PUCCH) notified by the persistent allocation signal. Instead, it is possible to apply a configuration in which the first information on the uplink radio resource (PUCCH) is not notified by the persistent information and the second information on the uplink radio resource (PUCCH) is notified by the PDCCH. In this configuration, the uplink radio resource (PUCCH) may be determined only by the second information on the uplink radio resource (PUCCH).

[0134]

In this case, there is a disadvantage that the number of bits for the information on the uplink radio resource (PUCCH) is increased, while there is an advantage that the uplink radio resource (PUCCH) can be set up more flexibly.

[0135]

In the above-described example, for example, the second information may be at least one of information such as a resource block number #1 and information such as an identification number #5.

[0136]

Specifically, the identification number used when the plurality of acknowledgment information are multiplexed within one resource block or the resource block number of the PUCCH may be notified by the PDCCH.

[0137]

Incidentally, the second information on the uplink radio resource (PUCCH) is defined as a part of information

elements to be notified by a persistent allocation signal (persistent allocation signal).

[0138]

Here, for example, when a signal format of the persistent allocation signal is the same as a signal format of the dynamic allocation signal in the dynamic scheduling, bits of the power control command used for transmission power control in the dynamic allocation signal may be used as the second information on the uplink radio resource (PUCCH).

10 [0139]

In the persistent scheduling, there is only a little significance to notify the power control command used for transmission power control. Accordingly, the bits of the command used for the transmission power control can be used as the second information on the uplink radio resource (PUCCH).

15 [0140]

Alternatively, when the signal format of the persistent allocation signal is the same as the signal format of the dynamic allocation signal in the dynamic scheduling, bits designating the "redundancy version" in the dynamic allocation signal may be used as the second information on the uplink radio resource (PUCCH).

20 [0141]

In the persistent scheduling, there is only a little significance to notify the bits for designating the redundancy version. Accordingly, the bits for designating the redundancy version of the transmission power control command used for the transmission power control can be used as the second information on the uplink radio resource (PUCCH).

25

[0142]

In this case, the redundancy version is set to a predetermined redundancy version.

[0143]

5 Alternatively, when the signal format of the persistent allocation signal is the same as the signal format of the dynamic allocation signal in the dynamic scheduling, bits designating the "MCS (Modulation and Coding Scheme)" in the dynamic allocation signal may be used as the second information on the
10 uplink radio resource (PUCCH).

[0144]

 Since the number of bits for designating such MCS in the persistent scheduling is smaller compared with the dynamic scheduling, a part or all of such bits for designating the MCS
15 may be used as the second information on the uplink radio resource (PUCCH).

[0145]

 Alternatively, when the signal format of the persistent allocation signal is the same as the signal format of the dynamic
20 allocation signal in the dynamic scheduling, a bit of a "new data indicator" in the dynamic allocation signal may be used as the second information on the uplink radio resource (PUCCH).

[0146]

 Alternatively, when the signal format of the persistent
25 allocation signal is the same as the signal format of the dynamic allocation signal in the dynamic scheduling, a part or all of bits for designating the "RB assignment" in the dynamic allocation signal may be used as the second information on the uplink radio resource (PUCCH).

[0147]

Since the number of bits for designating such RB assignment in the persistent scheduling is smaller compared with the dynamic scheduling, a part or all of such bits for designating the RB assignment may be used as the second information on the uplink radio resource (PUCCH).

[0148]

Instead, when the signal format of the persistent allocation signal is to the same as the signal format of the dynamic allocation signal in the dynamic scheduling, at least any one of the bit of the power control command, the bit for designating the "redundancy version", the bits for designating the "MCS", the bits of the "new data indicator", and the bits for designating the "RB assignment" can be used as the second information on the uplink radio resource (PUCCH).

[0149]

In this case, since the resource can be designated based on a plurality of information elements in the PDCCH, it is possible to perform a resource allocation of the PUCCH (uplink radio resource) more flexibly.

[0150]

If the first information on the uplink radio resource (PUCCH) is not notified by the persistent information and only the second information on the uplink radio resource (PUCCH) is notified by the PDCCH, the bits of the power control command, the bits for designating the "redundancy version", the bits for designating the "MCS", the bits of the "new data indicator", and the bits for designating the "RB assignment" may be used as the signal for notifying the information on the uplink radio

resource (PUCCH).

[0151]

Here, the information on the uplink radio resource (PUCCH) is the identification number used when the plurality of acknowledgment information are multiplexed within one resource block or the resource block number of the PUCCH, for example.

[0152]

As described previously, identification as to whether the received PDCCH is the persistent allocation signal (persistent allocation signal) or the dynamic allocation signal is performed based on RNTI or the like which is set in the PDCCH.

[0153]

In other words, the mobile station UE regards the PDCCH as the dynamic allocation signal when the CRC on the RNTI of the dynamic scheduling is "OK", and regards the PDCCH as the persistent allocation signal (persistent allocation signal) when the CRC on the RNTI of the persistent scheduling is "OK".

[0154]

Then, when regarding the PDCCH as the persistent allocation signal (persistent allocation signal), the mobile station UE performs a reception of the signal while regarding that any of the bits of the power control command, the bits for designating the "redundancy version", the bits for designating the "MCS", the bits of the "new data indicator", and the bits for designating the "RB assignment" is used as the second information on the uplink radio resource (PUCCH).

[0155]

Note that, a timing when the acknowledgement

information (ACK/NACK) for the downlink data received is transmitted via the uplink radio resource (PUCCH) is a timing uniquely determined based on the reception timing of the downlink radio resource (PDSCH) and the fixedly defined time offset, as described above.

[0156]

Furthermore, in the example described above, although the acknowledgement information (ACK/NACK) for the PDSCH (downlink data) is transmitted by the PUCCH, the acknowledgement information for the downlink data may be transmitted by being multiplexed with PUSCH when a physical uplink shared channel for transmitting uplink data is transmitted in a sub-frame in which the acknowledgment information (ACK/NACK) is transmitted.

[0157]

Alternatively, when the physical uplink shared channel for transmitting uplink data is allocated in the sub-frame in which the acknowledgement information (ACK/NACK) is transmitted, the acknowledgement information for such downlink data may be transmitted as partial information within the PUSCH.

[0158]

On the other hand, the radio base station eNB according to the present invention is configured to notify, to the mobile station UE, the first cycle and the information on the uplink radio resource (PUCCH).

[0159]

Description of such information on the uplink radio resource (PUCCH) is omitted, as it is the same as the description given for the mobile station UE.

[0160]

As shown in FIG. 4, the radio base station eNB includes a persistent information transmitter unit 21, a persistent allocation signal transmitter unit 22, a downlink data transmitter unit 23 and an ACK/NACK transmitter receiver unit 24.

[0161]

The persistent information transmitter unit 21 is configured to transmit, to the mobile station UE, the persistent information (persistent communication information) containing the first cycle and the first information on the uplink radio resource (PUCCH).

[0162]

Specifically, the persistent information transmitter unit 21 is configured to notify, to the mobile station UE, the above-described persistent information by using an RRC message.

[0163]

Description of the first information on the uplink radio resource (PUCCH) is omitted, as it is the same as the description given for the mobile station UE. Meanwhile, such first information on the uplink radio resource (PUCCH) is given to the ACK/NACK receiver unit 24.

[0164]

The persistent allocation signal transmitter unit 22 is configured to transmit, to the mobile station UE, a persistent allocation signal.

[0165]

Specifically, the persistent allocation signal transmitter unit 22 is configured to transmit, to the mobile

station UE, the PDCCH instructing a persistent allocation of the PDSCH (downlink radio resource) for the "persistent scheduling", as a persistent allocation signal.

[0166]

5 Note that, such a persistent allocation signal contains the information to instruct a persistent allocation of the PDSCH (downlink radio resource) for the "persistent scheduling", and additionally contains second information on the uplink radio resource (PUCCH) to make notification of the resource block
10 number of the PUCCH (uplink radio resource) and the identification number used when a plurality of acknowledgement information are multiplexed within one resource block.

[0167]

 Here, as described previously, it is also possible to
15 execute processing in which the information on the uplink radio resource (PUCCH) is not notified by the persistent information and the second information on the uplink radio resource (PUCCH) is notified by the PDCCH.

[0168]

20 The second information on the uplink radio resource (PUCCH) is supplied to the ACK/NACK receiver unit 24.

[0169]

 Note that, the persistent allocation signal transmitter
unit 22 may be configured to determine contents of the
25 above-described second information on the uplink radio resource (PUCCH) in such a manner that the radio resource of the acknowledgement information for the downlink data does not contend with radio resources of the acknowledgement information transmitted from other mobile stations.

[0170]

By using FIG. 5, one example of a method for determining the contents of the second information on the uplink radio resource (PUCCH) in such a manner that the radio resource of the acknowledgement information for the downlink data does not contend with the radio resources of the acknowledgement information transmitted from the other mobile stations.

[0171]

In FIG. 5, two resource blocks are defined as the uplink radio resource (PUCCH), and #0 and #1 are defined as resource block numbers thereof. Meanwhile, eight radio resources are defined in each resource block, and #0, #1, #2, ..., #7 are defined as identification numbers thereof.

[0172]

Here, an assumption is made that the resource block number #1 is notified by the persistent information as the first information on the uplink radio resource (PUCCH).

[0173]

Meanwhile, at a transmission timing of this acknowledgment information, the radio resources corresponding to the identification numbers #2, #3, and #4 in the resource block number #1 have already been used by a mobile station UE#A, a mobile station UE#B, and a mobile station UE#C, respectively.

[0174]

In this case, when the uplink radio resource (PUCCH) to be transmitted from the mobile station UE by using the second information on the uplink radio resource (PUCCH) contend with the uplink radio resources (PUCCH) to be transmitted from the mobile stations UE#A, UE#B, and UE#C, transmission

characteristics of the uplink radio resources (PUCCH) of the contending mobile stations UE and the mobile station UE will be significantly deteriorated.

[0175]

5 Accordingly, in order to avoid the above-described contention, the persistent allocation signal transmitter unit 22 determines, for example, to set the identification number of the uplink radio resource (PUCCH) of the mobile station UE to #5 by use of the second information on the uplink radio
10 resource (PUCCH). Here, the determination to set the identification number to #5 is merely an example and it is also possible to set the identification number to #6 or #1 as long as no contention occurs.

[0176]

15 Alternatively, when the processing in which “the first information on the uplink radio resource (PUCCH) is not notified by the persistent information and only the second information on the uplink radio resource (PUCCH) is notified by the PDCCH”
is performed as described above, the persistent allocation
20 signal transmitter unit 22 may determine to notify the “resource block number #1” and the “identification number #5” as the information on the uplink radio resource in order to avoid the above-mentioned contention.

[0177]

25 Here, it is also possible to notify, for example, the identification number #0 or #1 or the resource block #0 instead of the “identification #5” as long as no contention occurs.

[0178]

The downlink data transmitter unit 23 is configured to

transmit downlink data transmitted via the PDSCH (downlink radio resource) allocated by the PDCCH.

[0179]

Specifically, the downlink data transmitter unit 23 is
5 configured to, when the above-described persistent allocation signal (persistent allocation signal) is transmitted by the persistent allocation signal transmitter unit 22, determine a sub-frame in which such PDCCH has been transmitted as the above-described first allocation starting time, and to start
10 a transmission of the downlink data via the PDSCH (downlink radio resource) for the "persistent scheduling" persistently in the above-described first cycle, at the first allocation starting time.

[0180]

15 The ACK/NACK receiver unit 24 is configured to receive, from the persistent information transmitter unit 21, the first information on the uplink radio resource (PUCCH) notified by the persistent information.

[0181]

20 Moreover, the ACK/NACK receiver unit 24 receives, from the persistent allocation signal transmitter unit 22, the second information on the uplink radio resource (PUCCH) notified by the persistent allocation signal.

[0182]

25 The ACK/NACK receiver unit 24 is configured to determine the uplink radio resource (PUCCH) on the basis of the first information on the uplink radio resource (PUCCH) notified by the persistent information and the second information on the uplink radio resource (PUCCH) notified by the persistent

allocation signal, and to receive the acknowledgment information (ACK/NACK) for the transmitted downlink data via the uplink radio resource (PUCCH).

[0183]

5 Here, a method of determining the uplink radio resource (PUCCH) on the basis of the first information on the uplink radio resource (PUCCH) notified by the persistent information and the second information on the uplink radio resource (PUCCH) notified by the persistent allocation signal is the same as the
10 description in the mobile station UE and will therefore be omitted.

[0184]

(Operations of Mobile Communication System according to First Embodiment of Present Invention)

15 Operations of the mobile communication system according to the first embodiment of the present invention will be described with reference to FIG. 6.

[0185]

As shown in FIG. 6, in step S101, the mobile station
20 UE receives, from the radio base station eNB, the persistent information including the above-described first cycle and the first information on the uplink radio resource (PUCCH) through an RRC message or the like. Then, the mobile station UE acquires the first information on the uplink radio resource (PUCCH).

25 [0186]

In step S102, the mobile station UE receives the persistent allocation signal (persistent allocation signal) transmitted from the radio base station eNB via the PDCCH. Then, the mobile station UE acquires the second information on the

uplink radio resource (PUCCH) included in the persistent allocation signal.

[0187]

In step S102, the mobile station UE determines a
5 reception timing of the persistent allocation signal as the first allocation starting time.

[0188]

In step S103, the mobile station UE determines the uplink radio resource (PUCCH) on the basis of the first information
10 on the uplink radio resource (PUCCH) and the second information on the uplink radio resource (PUCCH).

[0189]

Here, for example, the first information on the uplink radio resource (PUCCH) may be the resource block number of the
15 PUCCH, while the second information on the uplink radio resource (PUCCH) may be the orthogonal cover sequence number in the block spreading or the identification number designating the amount of cyclic shift in the CAZAC sequence.

[0190]

20 A method of determining the uplink radio resource (PUCCH) on the basis of the first information on the uplink radio resource (PUCCH) and the second information on the uplink radio resource (PUCCH) is similar to the above-described method of determining the uplink radio resource (PUCCH) which has already
25 been described in conjunction with the above-described ACK/NACK transmitter unit 14 of the mobile station UE.

[0191]

Here, when the processing in which "the first information on the uplink radio resource (PUCCH) is not notified

by the persistent information and only the second information on the uplink radio resource (PUCCH) is notified by the PDCCH" is performed as described above, the uplink radio resource (PUCCH) is determined in step S103 on the basis of the second
5 information on the uplink radio resource (PUCCH) mapped in the PDCCH.

[0192]

In step S104, the mobile station UE receives the downlink data via the PDSCH (downlink radio resource) for the "persistent
10 scheduling" designated by the persistent allocation signal at a reception timing of the "persistent scheduling" calculated from the first allocation starting time and the first cycle.

[0193]

In step S105, the mobile station UE transmits the
15 acknowledgement information (ACK/NACK) for the downlink data received in step S104 via the uplink radio resource (PUCCH) determined in step S103.

[0194]

Then, the mobile station UE receives downlink data via
20 the PDSCH (downlink radio resource) persistently allocated in the first cycle (step S104), and transmits the acknowledgement information (ACK/NACK) for the downlink data via the PUCCH (uplink radio resource) (step S105).

[0195]

Referring to FIG. 7, operations of the radio base station
25 according to the first embodiment of the present invention is described.

[0196]

As shown in FIG. 7, in step S201, the radio base station

eNB transmits, to the mobile station UE, the persistent information including the above described first cycle and the first information on the uplink radio resource (PUCCH) through an RRC message or the like.

5 [0197]

In step S202, the radio base station eNB determines to transmit, to the mobile station UE, the persistent allocation signal (persistent allocation signal) to be transmitted via the PDCCH.

10 [0198]

In step S203, the radio base station eNB determines the second information on the uplink radio resource (PUCCH) to be included in the persistent allocation signal (persistent allocation signal) so as to avoid contention with the uplink radio resources (PUCCH) of other mobile stations UE.

15 [0199]

Here, for example, the first information on the uplink radio resource (PUCCH) may be the resource block number of the PUCCH, while the second information on the uplink radio resource (PUCCH) may be the orthogonal cover sequence number in the block spreading or the identification number designating the amount of cyclic shift in the CAZAC sequence.

20 [0200]

(Operation and Effect of Mobile Communication System according to First Embodiment of Present invention)

25 According to the mobile communication system of the first embodiment of the present invention, when the timing to allocate the downlink radio resource (PDSCH) is changed, it is possible to allocate the uplink radio resource (PUCCH) in a way

that the uplink radio resource (PUCCH) does not contend with the uplink radio resources (PUCCH) of other mobile stations UE. Therefore, it is possible to flexibly set up a time point to allocate the downlink radio resource (PDSCH) in the “persistent
5 scheduling” and thereby to improve radio utilization efficiency.

[0201]

(Modification)

Note that operation of the above described mobile
10 station UE and the radio base station eNB may be implemented by means of hardware, a software module executed by a processor, or a combination of both.

[0202]

The software module may be provided in any type of
15 storage medium such as an RAM (Random Access Memory), a flash memory, a ROM (Read Only Memory), an EPROM (Erasable Programmable ROM), an EEPROM (Electrically Erasable and Programmable ROM), a register, a hard disk, a removable disk, or a CD-ROM.

20 [0203]

The storage medium is connected to the processor so that the processor can read and write information from and to the storage medium. Also, the storage medium may be integrated into the processor. Also, the storage medium and the processor may
25 be provided in an ASIC. The ASIC may be provided in the mobile station UE and the radio base station eNB. Also, the storage medium and the processor may be provided in the mobile station UE and the radio base station eNB as a discrete component.

[0204]

Hereinabove, the present invention has been described in detail using the above embodiment; however, it is apparent to those skilled in the art that the present invention is not limited to the embodiment described herein. Modifications and
5 variations of the present invention can be made without departing from the spirit and scope of the present invention defined by the description of the scope of claims. Thus, what is described herein is for illustrative purpose, and has no intention whatsoever to limit the present invention.

CLAIMS

[1] A radio resource selecting method of semi-persistently selecting a radio resource to be allocated to an uplink acknowledgement signal indicating a reception state of a persistently allocated downlink signal from a plurality of radio resources defined by frequencies and codes, the radio resource selecting method comprising the steps of:

(A) selecting candidates for an allocation radio resource to be allocated to the uplink acknowledgement signal from the plurality of radio resources;

(B) notifying candidate information on the selected candidates for the allocation radio resource; and

(C) selecting a single allocation radio resource from the plurality of candidates for the allocation radio resource indicated in the candidate information notified in the step (B).

[2] The radio resource selecting method according to claim 1, wherein

in the step (C), an unused allocation radio resource is selected from the plurality of candidates for the allocation radio resource.

[3] The radio resource selecting method according to claim 1, further comprising the step of:

(D) notifying designation information on a single allocation radio resource among the plurality of candidates for the allocation radio resource, wherein

in the step (C), the single allocation radio resource

related to the designation information notified in the step (D) is selected from the plurality of candidates for the allocation radio resource indicated in the candidate information notified in the step (B).

5

[4] A radio base station configured to semi-persistently select a radio resource to be allocated to an uplink acknowledgement signal indicating a reception state of a persistently allocated downlink signal from a plurality of radio resources defined by frequencies and codes, the radio base station comprising:

a candidate selector unit configured to select candidates for an allocation radio resource to be allocated to the uplink acknowledgement signal from the plurality of radio resources; and

a candidate notification unit configured to notify candidate information on the selected candidates for the allocation radio resource.

[5] The radio base station according to claim 4, further comprising:

a selector unit configured to select a single allocation radio resource from the plurality of candidates for the allocation radio resource; and

a designation information notification unit configured to notify designation information on the selected single allocation radio resource.

[6] A mobile station used in a mobile communication system

in which a radio base station semi-persistently selects a radio resource to be allocated to an uplink acknowledgement signal indicating a reception state of a persistently allocated downlink signal from a plurality of radio resources defined by
5 frequencies and codes, the mobile station comprising:

a candidate information receiver unit configured to receive candidate information on candidates for allocation radio resource from the radio base station; and

a radio resource selector unit configured to select a
10 single allocation radio resource from the plurality of candidates for the allocation radio resource indicated in the received candidate information.

[7] The mobile station according to claim 6, wherein
15 the radio resource selector unit is configured to select an unused allocation radio resource from the plurality of candidates for the allocation radio resource.

[8] The mobile station according to claim 6, further
20 comprising:

a designation information receiver unit configured to receive designation information on the single allocation radio resource among the plurality of candidates for the allocation radio resource, wherein

25 the radio resource selector unit is configured to select the single allocation radio resource notified in the designation information from the plurality of candidates for the allocation radio resource.