



(43) International Publication Date
17 November 2005 (17.11.2005)


PCT

(10) International Publication Number
WO 2005/108273 A2

- | | |
|--|--|
| <p>(51) International Patent Classification⁷: B66B 7/04, 7/02</p> <p>(21) International Application Number:
PCT/JP2005/008845</p> <p>(22) International Filing Date: 10 May 2005 (10.05.2005)</p> <p>(25) Filing Language: English</p> <p>(26) Publication Language: English</p> <p>(30) Priority Data:
2004-140763 11 May 2004 (11.05.2004) JP</p> <p>(71) Applicant (for all designated States except US):
TOSHIBA ELEVATOR KABUSHIKI KAISHA
[JP/JP]; 5-27, Kitashinagawa 6-chome, Shinagawa-ku,
Tokyo, 1410001 (JP).</p> <p>(72) Inventors; and</p> <p>(75) Inventors/Applicants (for US only): ITO, Hiroaki.
MORISHITA, Mimpei. TONAMI, Yosuke.</p> | <p>(74) Agents: MIYOSHI, Hidekazu et al.; Toranomon Kotohira Tower, 2-8, Toranomon 1-chome, Minato-ku, Tokyo, 1050001 (JP).</p> <p>(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.</p> <p>(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,</p> |
|--|--|

[Continued on next page]

- (54) Title:** MAGNET UNIT, ELEVATOR GUIDING APPARATUS AND WEIGHING APPARATUS



(57) Abstract: A magnet unit includes a first magnetic pole (7a), a second magnetic pole (7b) and a third magnetic pole (7c) at a center between the first magnetic pole (7a) and the second magnetic pole (7b), providing an E-shaped configuration. In the magnet unit, a first magnet is defined between the first magnetic pole (7a) and the third magnetic pole (7c) by connecting two electromagnets (71aa, 73aa) with each other through a permanent magnet (72a), while a second magnet is defined between the second magnetic pole (7b) and the third magnetic pole (7c) by connecting two electromagnets (71ba, 73ba) with each other through a permanent magnet (72b). With this configuration, it is possible to reduce a deviation in the length of respective magnetic paths from the permanent magnets (72a, 72b) up to their respective magnetic poles. By controlling exciting currents to the respective magnetic poles. By controlling exciting currents to the respective electromagnets (71aa, 73aa, 71ba, 73ba), it is also possible to adjust fluxes (or flux density) in respective directions x, y individually.



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*