WHAT IS CLAIMED IS:

1. A laser-based multi-axis machine tool for processing a workpiece, comprising:

a laser source configured to generate laser light;

a support frame;

a scan head;

a first actuator coupled between the support frame and the scan head, wherein the first actuator is arranged and configured to translate the scan head along a first direction relative to the support frame;

a second actuator coupled between the first actuator and the support frame, wherein the second actuator is arranged and configured to translate the scan head and the first actuator along a second direction relative to the support frame;

a plurality of optical components arranged and configured to guide the laser light from the laser source to the scan head along a propagation path, wherein the plurality of optical components includes:

a first mirror coupled to the support frame; and

a second mirror coupled to the second actuator such that the second mirror is movable relative to the first mirror along the second direction and such that the scan head is moveable relative to the second mirror along the first direction; and

a first shroud enclosing a first space occupied by the laser source and a first group of the plurality of optical components;

a second shroud enclosing a second space occupied by the scan head and a second group of the plurality of optical components; and

a thermal management system operative to compensate for heat generated within the first space,

wherein the thermal management system includes a duct system operative to transfer heated air within the first space into the second space.

2. The laser-based multi-axis machine tool of claim 1, further comprising a workpiece positioning assembly arranged beneath the support frame, wherein the workpiece positioning assembly is operative to move the workpiece relative to the support frame.

3. The laser-based machine tool of claim 1, wherein the thermal management system includes a heating unit operative to heat the second space.

4. The laser-based machine tool of claim 1, wherein the thermal management system includes a cooling unit operative to cool the first space.

5. The laser-based machine tool of claim 1, further comprising a chiller arranged within the first space and operative to prevent the laser source from overheating, wherein the chiller generates heat during operation.

6. The laser-based machine tool of claim 1, further comprising a pump arranged within the first space and operative to positively pressurize the first space relative to the second space, wherein the pump generates heat during operation.