

DESCRIPTION

HEATING COOKER

5 Technical Field

[0001] The present invention relates to a heating cooker that supplies steam when cooking, with heat, an object to be cooked, such as bread.

Background Art

10 [0002] Known heating cookers include those using only a heater, and those using a steam generator (such as a boiler) in addition to a heater (see Patent Documents 1 to 3). Cooking methods in which steam is added during heating depending on the object to be cooked are also known.

15 Citation List

Patent Document

[0003] Patent Document 1: JP H07-055155A

Patent Document 2: JP H08-128653A

Patent Document 3: JP 2014-023801A

20

Summary of Invention

Technical Problem

[0004] The aforementioned heating cookers have the following problems. That is to say, when cooking toast, which is main usage of those heating
25 cookers, moisture that is originally contained in bread, such as a slice of square bread, evaporates during cooking, and the texture and taste thereof is lost. Also, as in the case where a savory smell comes from the toaster during cooking, the smell of butter contained in the bread also escapes to the air with the evaporation of the moisture, and the flavor is significantly lost.

30 [0005] Furthermore, dressed bread, croissants, and the like are burnt on their

surface before being heated to the inside, and there has been no method for optimally heating these kinds of bread.

[0006] Also, a water tank is necessary to supply water to a boiler. If the water in the tank is not used up, or the water remains in the boiler, the tank
5 needs to be cleaned or the water needs to be drained for hygiene, which takes time and effort.

[0007] The present invention aims to provide a heating cooker that is capable of perform cooking to serve tasty food by appropriately managing moisture of an object to be cooked without burning the surface thereof.

10 [0008] The present invention also aims to provide a heating cooker that has a steam function and is capable of performing cooking while appropriately maintaining a hygienic state of an object to be cooked by using up all water.

Solution to Problem

15 [0009] To solve the foregoing problems and achieve the above-stated objects, a heating cooker according to the present invention is configured as follows.

[0010] A box-shaped housing; a cooking cavity for accommodating an object to be cooked, the cooking cavity being arranged within the housing; an upper heater and a lower heater for heating the object to be cooked, the upper heater
20 and the lower heater being arranged within the cooking cavity; a steam generator for feeding steam into the cooking cavity; and a control unit for controlling the upper heater, the lower heater, and the steam generator, are provided, wherein the control unit alternately operates the upper heater and the lower heater to heat the object to be cooked while operating the steam
25 generator to generate steam, thereafter stops the steam generator, and operates at least one of the upper heater and the lower heater to heat the object to be cooked.

Advantageous Effects of Invention

30 [0011] According to the present invention, cooking can be performed to serve tasty food by appropriately managing moisture of an object to be cooked without burning the surface thereof. Also, the steam function is provided but

no water tank is necessary, and cooking can be performed while appropriately maintaining a hygienic state of an object to be cooked by using up the water.

Brief Description of Drawings

- 5 [0012] FIG. 1 is a perspective view showing a heating cooker according to a first embodiment of the present invention.
- FIG. 2 is an illustrative diagram showing an internal structure of the heating cooker.
- FIG. 3 is an illustrative diagram showing a control device in the heating cooker.
- 10 FIG. 4 is an illustrative diagram showing a heating cooking flow of the heating cooker.
- FIG. 5 is an illustrative diagram showing exemplary control in a cooking mode in the heating cooking flow.
- FIG. 6 is an illustrative diagram showing another example of a cooking mode
- 15 in the heating cooking flow.
- FIG. 7 is a perspective view showing main part of a heating cooker according to a second embodiment of the present invention.
- FIG. 8 is an illustrative diagram showing a heating cooking flow of the heating cooker according to the second embodiment of the present invention.
- 20 FIG. 9 is a perspective view showing main part of a heating cooker according to a third embodiment of the present invention.

Description of Embodiments

- [0013] FIG. 1 is a perspective view showing a heating cooker 10 according to
- 25 the first embodiment of the present invention. FIG. 2 is an illustrative diagram showing an internal structure of the heating cooker 10. FIG. 3 is an illustrative diagram showing a control unit 100 in the heating cooker 10. FIG. 4 is an illustrative diagram showing a heating cooking flow of the heating cooker 10. FIG. 5 is an illustrative diagram showing an example of a cooking
- 30 mode in the heating cooking flow. FIG. 6 is an illustrative diagram showing

another example of a cooking mode in the heating cooking flow.

[0014] The heating cooker 10 includes a rectangular parallelepiped, box-shaped housing 11, a rectangular parallelepiped cooking cavity 20 that is arranged within the housing 11 and accommodates an object to be cooked, a
 5 heater unit 30 arranged within the cooking cavity 20, a boiler (steam generator) 40 arranged within the cooking cavity 20, and a control unit 100 for controlling operations of the heater unit 30 and the boiler 40.

[0015] A door 12 is provided in a front face of the housing 11, and an operation unit 13 is provided in a front face of this door 12. The operation unit 13 is
 10 provided with an input portion 14 for setting a heating time and switching a cooking mode, and a notifying portion 15, such as an LED or a buzzer.

[0016] A water tray 21 is provided in an upper portion of the cooking cavity 20. A water guide passage 50 for guiding water W from the water tray 21 to a later-described boiler container 41 is provided in the housing 11. The water
 15 guide passage 50 includes a first guide portion 51 that guides the water W in an obliquely downward direction from the bottom of the water tray 21 toward an upper portion of an outer face of the cooking cavity 20, and a second guide portion 52 that guides the water W from the upper portion towards the lower portion of the outer face of the cooking cavity 20 in a vertical direction to the
 20 boiler container 41.

[0017] The water tray 21 can accommodate a given amount (e.g. 10 cc) of water W, and is formed to be capable of receiving the given amount of water W contained in a measuring cup M without being flooded, and causing the water W to flow into the water guide passage 50. The given amount is determined
 25 to be an amount that can be entirely evaporated in a given steaming time (e.g. 1 minute) when a later-described boiler heater 42 is energized.

[0018] A metal grill grid 22, on which an object to be cooked is placed, is provided substantially horizontally at the middle of the cooking cavity 20. Furthermore, an in-cavity thermistor (temperature sensor) 24 is provided
 30 within the cooking cavity 20.

[0019] The heater unit 30 includes an upper-face heater 31 arranged in an upper portion of the cooking cavity 20, and a lower-face heater 32 arranged in a lower portion.

[0020] The boiler 40 includes the boiler container 41 formed in a plate shape and located below the grill grid 22, the boiler heater 42 for heating the boiler container 41, and a boiler thermistor (temperature sensor) 43 attached to the boiler container 41. The capacity of the boiler container 41 is greater than or equal to a given amount (e.g. 10 cc).

[0021] The control unit 100 includes a control device 110 for giving operation instructions, and performing calculation and detection according to programs for executing a heating cooking flow shown in FIG. 4, for example, and a power supply device 120 for independently energizing the upper-face heater 31, the lower-face heater 32, and the boiler heater 42.

[0022] The control device 110 receives input from the in-cavity thermistor 24 and the boiler thermistor 43 and input from the input portion 14, and makes output to the notifying portion 15 and output to the power supply device 120. The control device 110 also causes an operation to generate steam from the boiler container 41 to be performed for at least a given steaming time (e.g. 1 minute) from when cooking starts.

[0023] The power supply device 120 is provided with a first relay 121, a second relay 122, and a third relay 123 that are connected to the upper-face heater 31, the lower-face heater 32, and the boiler heater 42, respectively.

[0024] The thus-configured heating cooker 10 performs heating cooking as follows. Initially, the door 12 is opened, and a given amount (10 cc) of water W is poured into the water tray 21. The given amount can easily be poured by pouring water using a measuring cup with a predetermined capacity (10 cc). The water W poured in the water tray 21 is guided to the boiler container 41 through the water guide passage 50. Next, an object to be cooked, such as a slice of square bread, is placed on the grill grid 22, and the door 12 is closed.

[0025] For cooking settings, a cooking mode is selected (ST10), and a timer is

set (ST 11). When setting the timer, any time from 1 minute at shortest up to 15 minutes at longest can be set to adjust the degree of browning the object to be cooked. Thus, heating cooking starts (ST12), and boiler control and heating control are performed.

5 [0026] In boiler control, the third relay 123 operates first, and the boiler heater 42 is energized (ST20). As a result, the water W in the boiler container 41 is heated and evaporated, and the steam fills the cooking cavity 20. The steam enfolds the object to be cooked, making it difficult for the moisture in the object to be cooked to evaporate. Note that the temperature at the boiler
10 thermistor 43 does not exceed 100°C in a state where the water W remains. After the water W has entirely evaporated and run out, the temperature in the boiler container 41 rapidly increases. When the temperature at the boiler thermistor 43 reaches or exceeds 120°C (ST21), it is determined that the water W has run out. The control device 110 opens the third relay 123 in the power
15 supply device 120 to stop energizing the boiler heater 42 (ST23).

[0027] If the temperature at the boiler thermistor 43 does not exceed 120°C, it is measured whether or not 1 minute has passed (ST22). The flow proceeds to ST23 if 1 minute has passed, and returns to ST21 if not.

[0028] In heating control, the first relay 121 and the second relay 122 are
20 operated in a heating pattern corresponding to a selected cooking mode to energize the upper-face heater 31 and the lower-face heater 32, and heating cooking starts (ST30). FIGS. 5 and 6 show exemplary heating patterns.

[0029] After the elapsed time from when heating started has reached the time set to the timer (e.g. 10 minutes) (ST31), energization of the upper-face heater
25 31 and the lower-face heater 32 is stopped (ST32), and heating cooking ends.

[0030] As described above, with the heating cooker 10 according to this embodiment, a predetermined given amount of water W can be entirely evaporated within a given time from when cooking starts. Accordingly, no water W remains after the heating cooking. Also, since a small amount of
30 water W is required for heating cooking, water need only be supplied every

time cooking is performed, and no water tank is necessary. Accordingly, water W is always new and hygienic.

[0031] Regarding the object to be cooked, it is possible to prevent moisture from escaping from the object to be cooked and suppress oxidation of the object to be cooked to make the texture of the surface thereof crispy and make the object to be cooked tasty through cooking, by supplying steam in first 1 minute or so and thereafter heating the object to be cooked, rather than continuously supplying steam during cooking or supplying steam at the last stage of cooking. For this reason, this heating cooker is suitable for objects to be cooked such as croissants.

[0032] Furthermore, in the case of an object to be cooked such as toast, moisture that is originally contained in the bread is not evaporated during cooking, and the texture and taste thereof are not lost. The smell of butter contained in the bread is not lost with the evaporation of the moisture either, and the flavor can be maintained. In addition, there has been no method to optimally heat dressed bread, croissants, and the like since the surface thereof is burnt before being heated to the inside. However, the heating cooker 10 can heat the bread to the inside without burning the surface thereof.

[0033] FIG. 7 is a perspective view showing a heating cooker 10A according to the second embodiment of the present invention with a door 12 removed. FIG. 8 is an illustrative diagram showing a heating cooking flow of the heating cooker 10A. Note that, in FIG. 7, the same functional portions as those in FIGS. 1 and 2 are assigned the same signs, and detailed descriptions thereof will be omitted.

[0034] The heating cooker 10A includes a rectangular parallelepiped, box-shaped housing 11, a rectangular parallelepiped cooking cavity 20A that is arranged within the housing 11 and accommodates an object to be cooked, a heater unit 30 arranged within the cooking cavity 20A, a boiler (steam generator) 40A arranged next to the cooking cavity 20, and a control unit 100A for controlling operations of the heater unit 30 and the boiler 40A.

[0035] The cooking cavity 20A is provided with a water tank 200 with a capacity of 1000 cc, for example, and a water supply valve 210 provided below the water tank 200, in place of the water tray 21 and the water guide passage 50.

5 [0036] The water supply valve 210 is configured to be able to measure a given amount (e.g. 10 cc) of water W and supply the water W to a boiler container 41. The given amount is determined to be an amount that can be entirely evaporated in a given steaming time (e.g. 1 minute) when a later-described boiler heater 42 is energized.

10 [0037] The boiler 40 is provided below the water tank 200, and includes the boiler container 41, the boiler heater 42 for heating the boiler container 41, and a boiler thermistor (temperature sensor) 43 attached to the boiler container 41. The capacity of the boiler container 41 is greater than or equal to a given amount (e.g. 10 cc).

15 [0038] A control unit 100A has a function of giving operation instructions, and performing calculation and detection according to programs for executing a heating cooking flow shown in FIG. 8, for example.

[0039] The thus-configured heating cooker 10A performs heating cooking as follows. Initially, the door 12 is opened, and water W of an amount (e.g. 800
20 cc) that is close to the upper limit of the capacity of the water tank 200 is poured into the water tank 200. Next, an object to be cooked, such as toast, is placed on the grill grid 22, and the door 12 is closed.

[0040] For cooking settings, a cooking mode is selected (ST40), and a timer is set (ST41). When setting the timer, any time from 1 minute at shortest up to
25 15 minutes at longest can be set to adjust the degree of browning the object to be cooked. Thus, heating cooking starts (ST42), and boiler control and heating control are performed.

[0041] In boiler control, the water supply valve 210 is opened (ST50), a given amount (e.g. 10 cc) of water W corresponding to a cooking mode is supplied
30 from the water tank 200 to the boiler container 41 (ST51), and the water supply

valve 210 is closed (ST52). The boiler heater 42 is then energized (ST53), and thus the water W in the boiler container 41 is heated to become steam, and blows into the cooking cavity 20A. The steam enfolds the object to be cooked, making it difficult for the moisture in the object to be cooked to evaporate.

5 Note that the temperature at the boiler thermistor 43 does not exceed 100°C in a state where the water W remains. After the water W has entirely evaporated and run out, the temperature in the boiler container 41 rapidly increases. When the temperature at the boiler thermistor 43 reaches or exceeds 120 °C, it is determined that the water W has run out (ST54), and
10 energization of the boiler heater 42 is stopped (ST56).

[0042] If the temperature at the boiler thermistor 43 does not exceed 120°C, it is measured whether or not the time set in the cooking mode has passed (ST55). If the time set in the cooking mode has passed, the flow proceeds to ST56.

15 [0043] Heating control is the same as that in the above-described heating cooker 10, and a description thereof will be omitted.

[0044] As described above, with the heating cooker 10A according to this embodiment, a predetermined given amount of water W can be entirely evaporated in a given time, and accordingly, no water W remains after the
20 heating cooking. Also, since water W required for heating cooking is supplied using the water supply valve 210 in accordance with the cooking mode, it is not necessary to supply water every time cooking is performed. Furthermore, the necessary amount of water W can be adjusted in accordance with the cooking mode, and a change in the size or type of an object to be cooked can be dealt
25 with.

[0045] Regarding the object to be cooked, it is possible to prevent moisture from escaping from the object to be cooked and suppress oxidation of the object to be cooked to make the texture of the surface thereof crispy and make the object to be cooked tasty through cooking, by supplying steam in first 1 minute
30 or so and thereafter heating the object to be cooked, rather than continuously

supplying steam during cooking or supplying steam at the last stage of cooking. For this reason, this heating cooker is suitable for objects to be cooked such as croissants.

[0046] In addition, the same effects as those of the heating cooker 10 can be achieved.

[0047] FIG. 9 is a perspective view showing a heating cooker 10B according to the third embodiment of the present invention with a door 12 removed. In FIG. 9, the same functional portions as those in FIG. 7 are assigned the same signs, and detailed descriptions thereof will be omitted.

[0048] The heating cooker 10B is provided with a boiler 40 above a water tank 200. The heating cooker 10B can also perform heating cooking similar to the heating cooker 10A, and can achieve the same effects as those of the heating cooker 10A.

[0049] Note that the present invention is not limited to the above-described embodiments. For example, although the above example uses the boiler 40 as a steam generator, steam may be generated using an ultrasonic generation device. The configuration or the like of the heater unit 30 may be changed as appropriate in accordance with the size and shape of the cooking cavity 20, the type of an object to be cooked, or the like. Furthermore, although the given steaming time is set to 1 minute, it is not limited to this time, and may be changed as appropriate in accordance with the size of the cooking cavity 20, the type of an object to be cooked, or the like. Of course, the present invention may be modified and implemented in various manners without departing from the gist of the invention.

List of Reference Numerals

[0050] 10, 10A, 10B Heating cooker

11. Housing

12 Door

13 Operation unit

	14	Input portion
	15	Notifying portion
	20, 20A	Cooking cavity
	21	Water tray
5	22	Grill grid
	24	In-cavity thermistor (temperature sensor)
	30	Heater unit
	31	Upper-face heater
	32	Lower-face heater
10	40	Boiler (steam generator)
	41	Boiler container
	42	Boiler heater
	43	Boiler thermistor (temperature sensor)
	50	Water guide passage
15	100	Control unit
	110	Control device
	120	Power supply device
	200	Water tank
	210	Water supply valve
20	W	Water

CLAIMS

1. A heating cooker comprising:
 - a box-shaped housing;
 - a cooking cavity for accommodating an object to be cooked, the cooking cavity being arranged within the housing;
 - an upper heater and a lower heater for heating the object to be cooked, the upper heater and the lower heater being arranged within the cooking cavity;
 - a steam generator for feeding steam into the cooking cavity; and
 - a control unit for controlling the upper heater, the lower heater, and the steam generator,wherein the control unit is configured to operate the steam generator to generate steam, and while operating the steam generator to generate the steam, the control unit is configured to alternately operate the upper heater and the lower heater to heat the object to be cooked, and wherein the control unit is further configured to thereafter stop the steam generator, and to operate at least one of the upper heater and the lower heater to heat the object to be cooked.
2. The heating cooker according to claim 1,
 - wherein a grill grid on which the object to be cooked is to be placed is provided within the cooking cavity.
3. The heating cooker according to claim 1 or 2,
 - wherein the steam generator includes a boiler container for accommodating water and a boiler heater for heating the boiler container,
 - wherein the control unit is configured to control energization of the upper heater, the lower heater, and the boiler heater.
4. The heating cooker according to claim 3, further comprising:
 - an operation unit for setting a timer to a heating time for the object to be cooked,
 - wherein if the timer is set, the control unit is configured to start to energize the boiler heater.
5. The heating cooker according to claim 3, further comprising:

an operation unit for setting a timer to a heating time for the object to be cooked,

wherein if the timer is set and water is supplied to the boiler container, the control unit is configured to start to energize the boiler heater.

6. The heating cooker according to any one of claims 3 to 5, further comprising:

a water tray into which a given amount of water is to be poured, the heating cooker being configured such that the given amount of water is entirely evaporated within a given steaming time; and

a water guide passage for guiding the water from the water tray to the boiler container,

wherein the control unit is configured to energize the boiler heater for at least the steaming time.

7. The heating cooker according to any one of claims 3 to 5, further comprising:

a water tank for accommodating water; and

a water supply valve for supplying a given amount of water from the water tank to the boiler container, the heating cooker being configured such that the given amount of water is entirely evaporated within a given steaming time,

wherein the control unit is configured to energize the boiler heater for at least the steaming time.

8. The heating cooker according to any one of claims 3 to 7,


wherein the boiler container is provided with a temperature sensor, and

the control unit is configured to control turning ON and OFF of energization of the boiler heater based on output of the temperature sensor.


9. The heating cooker according to claim 8,

wherein the control unit is configured to stop energizing the boiler heater at a time point when a temperature detected by the temperature sensor reaches a given temperature that is higher than or equal to a boiling point of water.


[FIG.2]




[FIG.3]




[FIG.4]




[FIG.5]



[FIG.6]



[FIG.7]



[FIG.8]

