

Description

This invention relates to the mounting between tilt levers and a lift arm of a linkage arrangement of a loader-type vehicle, such as an earthmoving vehicle.

In a construction vehicle, such as a wheel or a track-type loader for example, a loader linkage is provided that typically consists of a pair of lift arms that extend from the front end of the vehicle and mount a work implement, such as a bucket. The vehicle usually loads the bucket with material such as dirt and then dumps the material into a truck for removal from the work site. In order to empty the material from the bucket into the truck, a tilting apparatus is incorporated into the loader linkage. The tilting apparatus consists of at least one lever that extends upwardly from each lift arm. The upper portion of each lever is in turn connected to the upper portion of the bucket by a tilt link. A hydraulic cylinder is provided that has one end connected to the tilt lever and its other end connected to the vehicle frame. The cylinder may be directly connected to the tilt lever or it may be connected through another tilt lever and link arrangement. When actuated, the hydraulic cylinder rotates the levers forward until a portion of the levers come into contact with a stop member that is located on each side of the respective lift arms. When the tilt levers are moved to this position, the bucket, through its connection with the levers, is rotated about its connection to the lift arms and the material held within the bucket is dumped out.

While a linkage apparatus of this type has proven to be extremely reliable over the years, improvements in the componentry are always desirable. One such area that has been improved upon is the structure of the tilt levers and their mounting to the lift arms. Due to the large capacity of the buckets utilized by loaders, the weight of the material and the force from the tilt cylinder apply a very substantial force to the tilt apparatus and particularly to the tilt lever when they are brought into contact with the dump stops on the lift arm. Because of this it has been common practice to form the tilt levers from a casting or fabrication that is large enough to accept the loading. The tilt levers typically have a one-piece body that has two bifurcated projections that straddle the lift arm. A pin that is secured to one of the projections extends through the lift arm and both of the projections of each tilt lever to rotatably connect the two members together. A flat surface must be provided at a forward portion of the tilt levers that will engage the dump stops on the lift arms to limit the travel of the tilt levers. To properly transfer the loads through the tilt levers, it is important that the surface of each tilt lever engage the dump stop on both sides of the lift arm. However, during fabrication, machining or assembly of the components, a stack-up of tolerances may occur and create a situation wherein only one side of a tilt lever engages a dump stop. Since the lever is a

one-piece casting or fabrication, just one side of the lever will be caused to carry the majority of the load, thus imparting a twist in the tilt lever during normal operation. This may result in premature failure of the linkage.

US-A-4431364 discloses a linkage arrangement comprising an elongate support arm having at least one bearing bore defined therethrough along an axis; a pair of first and second elongate, laterally spaced tilt levers disposed in embracing relation to the support arm and having bores therethrough aligned with the bearing bore in the support arm; means for mounting the tilt levers to the support arm for pivoting relative thereto about the axis; and means for limiting axial movement of the tilt levers along the axis while permitting limited pivoting between the levers. Such an arrangement is hereinafter referred to as of the kind described. The mounting and axial movement limiting means comprise a pin that has a retainer associated with each of the tilt levers. The pin is not connected to either of the tilt levers but is free to rotate within the bores in the tilt levers and support arm. An arrangement of this configuration, however, requires the provision of two retainers, hardened bearing surfaces in all of the components and the required provisions for lubrication of all the bearing surfaces. This greatly increases the cost of the linkage as well as the time required to maintain it.

According to the present invention, a linkage arrangement of the kind described is characterized in that the mounting means is snugly journaled in the bearing bore, more loosely extends through the bores in the tilt levers and is coupled to one of the tilt levers for pivoting therewith; and in that the limiting means is coupled to the other of the levers for pivoting therewith.

The present invention provides a simple and economical way of mounting the components for relative rotation with respect to each other while also providing a limiting means for axial movement between the components. This allows the tilt levers to rotate relatively to each other about their mounting with the lift arm. In doing so, each tilt lever will fully engage the dump stops on the lift arm to insure proper loading of the tilt levers.

In the drawings:—

Figure 1 is a fragmentary side view of a front end loader having a linkage arrangement in accordance with the present invention;

Figure 2 is a fragmentary sectional view taken along lines II—II of Figure 1; and,

Figure 3 is a fragmentary sectional view taken along lines III—III of Figure 2.

Referring to the drawings, Figure 1 discloses a linkage arrangement 10 for a loader-type vehicle 12. The linkage arrangement includes a pair of elongate lift arms 14 (one shown) that have a first end portion 16 rotatably connected to a frame 18 of the vehicle 12 by a pin arrangement 20. A second end portion 22 of the lift arms 14 support a work implement such as a bucket 24, also by a pin arrangement 26 or other suitable mounting

means that allows the bucket to rotate with respect to the lift arms 14. The lift arms 14 and bucket 24 are vertically movable with respect to the vehicle in response to the actuation of a hydraulic lift cylinder 28 that is connected at one end 30 to the vehicle frame 18 and at its other end 32 to the lift arms 14.

A tilting apparatus shown generally at 34 is also included in the loader linkage arrangement 10. The tilting apparatus 34 includes a pair of power levers 36 (one shown) and a pair of tilt lever assemblies 38 (one shown) that are pivotally mounted to each of the lift arms 14. The power levers 36 are rotatably mounted to the lift arms 14 at a location 40 intermediate its end portions. A first end portion 42 of the power lever 36 is connected to a rod end 44 of a hydraulic tilt cylinder 46. The head end 48 of the cylinder 46 is connected to the vehicle frame 18 at a location shown generally at 49. A second end 50 of the power lever 36 is interconnected with the tilt lever assemblies 38 by a pair of power links 52 (one shown) at an intermediate portion 54 of the tilt lever assemblies 38. Each tilt lever assembly includes first and second elongated lever members 56 and 58. As best shown in Figure 2, each lever 56 and 58 has a first end portion 60 and 61, respectively, that is rotatably mounted to the lift arms 14 by a common mounting device shown generally at 62 that will be described in greater detail hereinafter. The first tilt lever 56 is positioned on a first side 64 of the lift arm 14 while the second tilt lever 58 is positioned on a second, or opposite side 66 of the lift arm. A second end portion 68 and 69 of the respective tilt levers 56 and 58 is connected to an upper portion 70 of the bucket 24 by a pair of tilt links 72 (one shown). A flat portion 74 is machined or otherwise accurately located on a forward edge 76 of the tilt levers 56 and 58. The flat portion 74 is positioned to engage a surface 78 of a mechanical stop member 80 that forms a portion of lift arm 14. While this particular tilting apparatus 34 includes a pair of power levers 36 and power links 52, it may be desirable to eliminate these components and connect the tilt cylinder 46 directly between the tilt lever assemblies 38 and the lift arms 14.

The mounting apparatus 62, shown best in Figures 2 and 3, consists of a rotational securing means 82 and an axial movement limitation portion 84. The rotational securing means 82 consists of a pin member 86 that extends through a pair of bores 88 and 89 defined in the respective first end portions 60 and 61 of each of the tilt levers 56 and 58 and a bearing bore 92 defined in the lift arm 14. All of the bores are positioned along a common axis X that is transverse to the lift arm 14. A flange member 94 has a first end portion 95 fixedly attached, as by welding, to a first end portion 96 of the pin 86. The flange member 94 extends upwardly from the pin 86 in a direction normal to axis X, to a position adjacent the first tilt lever 56. A threaded fastening member 98, such as a bolt, extends through a second end portion 99 of the flange member 94

and is received in threaded aperture 100 provided in the first tilt lever 56. A bearing member 102 is positioned between the pin 86 and the bore 92 of the lift arm 14 to allow relative rotation therebetween.

Axial movement of the pin 86 and thus the axial movement between the first and second tilt levers 56 and 58 and the lift arm 14 is controlled by a plate member 104. As best shown in Figure 3, the plate member 104 extends in a direction normal to axis X to a location adjacent the second tilt lever 58. The plate member 104 has a first end portion 106 that defines a concave or semicircular indentation 108. The first end portion 106 is sufficiently configured to engage a groove 110 that is defined in a second end portion 112 of the pin 86. The indentation 108 is positioned about the pin in close proximity to the base of the groove 110 which has a reduced diameter. The outside diameter of the pin is large enough to contact the plate member 104 with either of two shoulders 114, 116 that are positioned on opposite sides of the plate member 104. A second end portion 118 of the plate member 104 is secured to the second tilt lever 58 by a threaded fastening member 120, such as a bolt, that extends through the plate member and is received in a threaded aperture 122 in the second tilt lever 58.

In operation of the loader linkage 10 of the vehicle 12, the bucket 24, in the position shown in Figure 1, is moved by the vehicle 12 into a pile of material (not shown) to fill the bucket. The vehicle is then manoeuvred along side the bed of a truck or hopper, to dump the contents of the bucket 24. The lift arms 14 are then vertically raised to position the bucket above the side of the truck by actuation of the hydraulic lift cylinder 28. With the bucket positioned over the bed of the truck, the hydraulic tilt cylinder 46 is retracted to initiate the dumping process. With the retraction of the cylinder 46, the power levers 36 are rotated with respect to the lift arms 14 in a clockwise or forward direction as viewed in Figure 1. With the rotation of the power levers, the tilt lever assemblies 38 are also rotated in a clockwise direction since they are connected to the power levers 36 by power links 52. As the first and second tilt levers 56 and 58 of the tilt lever assemblies rotate, the bearing 102 accommodates the relative movement between the pin 86 and the bore 92 in the lift arm 14. However, since the pin 86 is attached to first tilt lever 56 and rotates with the tilt lever assembly, a relatively large clearance is permitted and therefore no bearing is needed between the pin 86 and the bore 88 in the first tilt lever 56. Similarly, since the first tilt lever 56 moves very little with respect to the second tilt lever 58, a relatively large clearance also exists between the pin 86 and the bore 89, which also requires no bearing.

During the normal rotation of the tilt lever assemblies 38 with respect to the lift arms 14, the axial positioning of the first and second tilt levers 56 and 58 with respect to the lift arms 14 is maintained by plate member 104. Since the first

end portion 106 of the plate member 104 is positioned within the groove 110, between the shoulders 114 and 116 of the pin 86, axial movement of the tilt levers with respect to the lift arm is limited in both directions.

The tilt lever assemblies 38 will continue to rotate until the flat position 74 of the first and second tilt levers 56 and 58 engage the corresponding stop members 80 positioned on the respective first and second sides 64 and 66 of the lift arm 14. Since the first and second tilt levers 56 and 58 are not connected to each other by means other than the mounting apparatus 62 on the first and second end portions 60, 61 and 68, 69 respectively, they are allowed limited relative rotation with respect to each other. If by some reason, during manufacturing or assembly, the dump stop members 80 are not precisely positioned, the first and second tilt levers 56 and 58 will still properly rest upon the respective stop member to accept a full share of the loading.

Thus it can be seen from the foregoing description that the arrangement between the lift arms 14 and the tilt lever assemblies 38 utilizes a mounting apparatus 62 that mounts the components of the linkage together for relative rotation therebetween. And, since the mounting apparatus 62 has the means 82 thereof secured to and rotating with one of the first and second tilt levers 56 and 58, no bearing or lubrication means is required between the first and second tilt levers and the mounting member such as pin 86. Likewise, the axial movement between the first and second tilt levers 56 and 58 and the lift arm 14 is controlled by a single member 86 that is mounted to the other of the first and second tilt levers also requiring no bearing or lubrication. With such an apparatus, the linkage arrangement 10 consists of an extremely simple and economical arrangement that is very easily maintained. Also, the linkage arrangement 10 assures that loads applied thereto will be evenly distributed to provide extended life of the associated components.

Claims

1. A linkage arrangement (10) comprising:
an elongate support arm (14) having at least one bearing bore (92) defined therethrough along an axis (X);

a pair of first and second elongate, laterally spaced tilt levers (56, 58) disposed in embracing relation to the support arm (14) and having bores (88, 89) therethrough aligned with the bearing bore (92) in the support arm (14);

means (82) for mounting the tilt levers (56, 58) to the support arm (14) for pivoting relative thereto about the axis (X); and

means (84) for limiting axial movement of the tilt levers (56, 58) along the axis (X) while permitting limited pivoting between the levers (56, 58); characterised in that the mounting means (82) is snugly journaled in the bearing bore (92), more loosely extends through the bores (88, 89)

in the tilt levers (56, 58) and is coupled to one of the tilt levers (56, 58) for pivoting therewith;

and in that the limiting means (84) is coupled to the other of the levers (56, 58) for pivoting therewith.

2. A linkage arrangement (10) according to claim 1, wherein the mounting means (82) includes:

a pin (86) having a first (96) and a second (112) end portion, the second end portion (112) having an annular groove (110) defined therearound;

a flange member (94) having a first end portion (95) secured to the first end portion (96) of the pin (86) and a second end portion (99) extending laterally from the pin (86) in a direction normal to the axis (X); and

means (98) for fastening the flange member (94) to the first lever (56) and thereby securing the pin (86) to the first lever (56) for pivoting therewith.

3. A linkage arrangement (10) according to claim 2, wherein the limiting means (84) includes:

a plate member (104) having a first (106) and a second (118) end portion, the first end portion (106) engaging the groove (110) formed in the pin (86); and

means (120) for fastening the plate member (104) to the second lever (58) in a manner to permit pivoting between the second lever (58) and the pin (86).

4. A linkage arrangement (10) according to any of the preceding claims, wherein the support arm (14) is a lift arm (14) of a construction vehicle (12), and the linkage arrangement further comprises a work implement (24) pivotally mounted on one end of the lift arm (14).

5. A linkage arrangement (10) according to claim 4, wherein the first (56) and second (58) levers comprise a tilt lever assembly (38) that is connected to the lift arm (14) to form a portion of a tilting apparatus (34) that is associated with the work implement (24).

6. A linkage arrangement (10) according to claim 5, wherein the tilting apparatus (34) also includes a tilt link (72) that extends between the tilt lever assembly (38) and the work implement (24) to cause the rotation of the work implement (24) with respect to the lift arm (14) upon movement of the tilt lever assemblies (38).

7. A linkage arrangement (10) according to claim 6, further comprising an actuator (46) connected to the tilt levers (56, 58) to cause rotation thereof with respect to the lift arm (14) and thus the rotation of the work implement (24) with respect to the lift arm (14).

8. A linkage arrangement (10) according to any of the preceding claims, wherein a bearing member (102) is positioned within the bearing bore (92) of the support arm (14) to accommodate pivoting of the pin (86) relative to the support arm (14).

end portion 106 of the plate member 104 is positioned within the groove 110, between the shoulders 114 and 116 of the pin 86, axial movement of the tilt levers with respect to the lift arm is limited in both directions.

The tilt lever assemblies 38 will continue to rotate until the flat position 74 of the first and second tilt levers 56 and 58 engage the corresponding stop members 80 positioned on the respective first and second sides 64 and 66 of the lift arm 14. Since the first and second tilt levers 56 and 58 are not connected to each other by means other than the mounting apparatus 62 on the first and second end portions 60, 61 and 68, 69 respectively, they are allowed limited relative rotation with respect to each other. If by some reason, during manufacturing or assembly, the dump stop members 80 are not precisely positioned, the first and second tilt levers 56 and 58 will still properly rest upon the respective stop member to accept a full share of the loading.

Thus it can be seen from the foregoing description that the arrangement between the lift arms 14 and the tilt lever assemblies 38 utilizes a mounting apparatus 62 that mounts the components of the linkage together for relative rotation therebetween. And, since the mounting apparatus 62 has the means 82 thereof secured to and rotating with one of the first and second tilt levers 56 and 58, no bearing or lubrication means is required between the first and second tilt levers and the mounting member such as pin 86. Likewise, the axial movement between the first and second tilt levers 56 and 58 and the lift arm 14 is controlled by a single member 86 that is mounted to the other of the first and second tilt levers also requiring no bearing or lubrication. With such an apparatus, the linkage arrangement 10 consists of an extremely simple and economical arrangement that is very easily maintained. Also, the linkage arrangement 10 assures that loads applied thereto will be evenly distributed to provide extended life of the associated components.

Claims

1. A linkage arrangement (10) comprising:
 - an elongate support arm (14) having at least one bearing bore (92) defined therethrough along an axis (X);
 - a pair of first and second elongate, laterally spaced tilt levers (56, 58) disposed in embracing relation to the support arm (14) and having bores (88, 89) therethrough aligned with the bearing bore (92) in the support arm (14);
 - means (82) for mounting the tilt levers (56, 58) to the support arm (14) for pivoting relative thereto about the axis (X); and
 - means (84) for limiting axial movement of the tilt levers (56, 58) along the axis (X) while permitting limited pivoting between the levers (56, 58);
 - characterised in that the mounting means (82) is snugly journaled in the bearing bore (92), more loosely extends through the bores (88, 89)

in the tilt levers (56, 58) and is coupled to one of the tilt levers (56, 58) for pivoting therewith;

and in that the limiting means (84) is coupled to the other of the levers (56, 58) for pivoting therewith.

2. A linkage arrangement (10) according to claim 1, wherein the mounting means (82) includes:

a pin (86) having a first (96) and a second (112) end portion, the second end portion (112) having an annular groove (110) defined therearound;

a flange member (94) having a first end portion (95) secured to the first end portion (96) of the pin (86) and a second end portion (99) extending laterally from the pin (86) in a direction normal to the axis (X); and

means (98) for fastening the flange member (94) to the first lever (56) and thereby securing the pin (86) to the first lever (56) for pivoting therewith.

3. A linkage arrangement (10) according to claim 2, wherein the limiting means (84) includes:

a plate member (104) having a first (106) and a second (118) end portion, the first end portion (106) engaging the groove (110) formed in the pin (86); and

means (120) for fastening the plate member (104) to the second lever (58) in a manner to permit pivoting between the second lever (58) and the pin (86).

4. A linkage arrangement (10) according to any of the preceding claims, wherein the support arm (14) is a lift arm (14) of a construction vehicle (12), and the linkage arrangement further comprises a work implement (24) pivotally mounted on one end of the lift arm (14).

5. A linkage arrangement (10) according to claim 4, wherein the first (56) and second (58) levers comprise a tilt lever assembly (38) that is connected to the lift arm (14) to form a portion of a tilting apparatus (34) that is associated with the work implement (24).

6. A linkage arrangement (10) according to claim 5, wherein the tilting apparatus (34) also includes a tilt link (72) that extends between the tilt lever assembly (38) and the work implement (24) to cause the rotation of the work implement (24) with respect to the lift arm (14) upon movement of the tilt lever assemblies (38).

7. A linkage arrangement (10) according to claim 6, further comprising an actuator (46) connected to the tilt levers (56, 58) to cause rotation thereof with respect to the lift arm (14) and thus the rotation of the work implement (24) with respect to the lift arm (14).

8. A linkage arrangement (10) according to any of the preceding claims, wherein a bearing member (102) is positioned within the bearing bore (92) of the support arm (14) to accommodate pivoting of the pin (86) relative to the support arm (14).



Patentansprüche

1. Gelenkanordnung (10), die folgendes aufweist:

einen langgestreckten Tragarm (14) mit mindestens einer längs einer Achse (X) hindurch verlaufenden definierten Bohrung (92);

ein Paar von ersten und zweiten langgestreckten, seitlich mit Abstand angeordneten Kipphebeln (56, 58), angeordnet in Umfassungsbeziehung bezüglich des Tragarms (14) und mit hindurchgehenden Bohrungen (88, 89) ausgerichtet mit der Lagerbohrung (92) im Tragarm (14);

Mittel (82) zur Anordnung der Kipphebel (56, 58) am Tragarm (14), um relativ demgegenüber um die Achsen (X) zu verschwenken; und

Mittel (84) zur Begrenzung der Axialbewegung der Kipphebel (56, 58) längs der Achse (X), während eine begrenzte Schwenkbewegung zwischen den Hebeln (56, 58) gestattet ist;

dadurch gekennzeichnet, daß die Befestigungsmittel (82) eng passend in der Lagerbohrung (92) gelagert sind, sich lockerer durch die Bohrungen (88, 89) in den Kipphebeln (56, 58) erstrecken und mit einem der Kipphebel (56, 58) zur Verschwenkung damit gekuppelt sind; und

daß die Begrenzungsmittel (84) mit dem anderen der Hebel (56, 58) zum Verschwenken damit gekuppelt sind.

2. Gelenkanordnung (10 nach Anspruch 1, wobei die Befestigungsmittel (82) folgendes aufweisen:

einen Stift (86) mit einem ersten (96) und einem zweiten (112) Endteil, wobei der zweite Endteil (112) eine Ringnut (110) darum herum definiert aufweist;

ein Flanschglied (94) mit einem ersten Endteil (95) befestigt am ersten Endteil (96) des Stifts (86) und mit einem zweiten Endteil (99), der sich seitlich vom Stift (86) in einer Richtung senkrecht zur Achse (X) erstreckt; und

Mittel (98) zur Befestigung des Flanschglieds (94) am ersten Hebel (56) und dadurch Befestigung des Stifts (86) am ersten Hebel (56) zur Verschwenkung damit.

3. Gelenkanordnung (10) nach Anspruch 2, wobei die Begrenzungsmittel (84) folgendes aufweisen:

ein Plattenglied (104) mit einem ersten (106) und einem zweiten (118) Endteil, wobei das erste Endteil (106) mit der im Stift (86) gebildeten Nut (110) in Eingriff steht; und

Mittel (120) zur Befestigung des Plattenglieds (104) am zweiten Hebel (58) in einer Art und Weise, daß das Verschwenken zwischen dem zweiten Hebel (58) und dem Stift (86) gestattet ist.

4. Gelenkanordnung (10) nach einem der vorhergehenden Ansprüche, wobei der Tragarm (14) ein Hubarm (14) eines Baufahrzeugs (12) ist, und die Gelenkanordnung ferner ein Werkzeug (24) aufweist, welches schwenkbar an einem Ende des Hubarms (14) angeordnet ist.

5. Gelenkanordnung (10 nach Anspruch 4, wobei die ersten (56) und zweiten (58) Hebel eine Kipphebelanordnung (38) aufweisen, die mit dem

Hubarm (14) verbunden ist, um einen Teil einer Kippvorrichtung (34) zu bilden, die mit dem Werkzeug (24) verbunden ist.

6. Gelenkanordnung (10) nach Anspruch 5, wobei die Kippvorrichtung (34) ebenfalls ein Kippgelenk (72) aufweist, welches sich zwischen den Kipphebelanordnung (38) und dem Werkzeug (24) erstreckt, um die Drehung des Werkzeugs (24) bezüglich des Hubarms (14) bei Bewegung der Kipphebelanordnungen (38) zu bewirken.

7. Gelenkanordnung (10) nach Anspruch 6, wobei ferner eine Betätigungsvorrichtung (46) vorgesehen ist, die mit den Kipphebeln (56, 58) verbunden ist, um die Drehung desselben bezüglich des Hubarms (14) zu bewirken, und somit die Drehung des Werkzeugs (24) bezüglich des Hubarms (14).

8. Gelenkanordnung (10) nach einem der vorhergehenden Ansprüche, wobei die Lagerglied (102) innerhalb der Lagerbohrung (92) des Tragarms (14) positioniert ist, um das Schwenken des Stifts (86) bezüglich des Tragarms (14) zu ermöglichen.

Revendications

1. Mécanisme de liaison (10) comportant:

un bras support (14) de forme allongée, présentant au moins un alésage formant portée (92) défini à travers le bras le long d'un axe (X);

une paire d'un premier et d'un second leviers de basculement (56, 58) de forme allongée, espacés latéralement l'un de l'autre et disposés de façon à enserrer le bras support (14) et à avoir les alésages (88, 89) qui les traversent alignés avec l'alésage formant portée (92) prévu dans le bras support (14);

un moyen (82) pour monter les leviers de basculement (56, 58) sur le bras support (14) en vue d'un pivotement relatif par rapport à lui autour de l'axe (X); et

un moyen (84) pour limiter le mouvement axial des leviers de basculement (56, 58) le long de l'axe (X) tout en autorisant un pivotement limité entre les leviers (56, 58);

caractérisé en ce que le moyen de montage (82) tourillonne en douceur dans l'alésage formant portée (92), s'étend plus librement dans les alésages (88, 89) prévus dans les leviers de basculement (56, 58), et est couplé à l'un des leviers de basculement (56, 58) pour pivoter avec lui;

et en ce que le moyen de limitation (84) est couplé à l'autre des leviers (56, 58) pour pivoter avec lui.

2. Mécanisme de liaison (10) selon la revendication 1, dans lequel le moyen de montage (82) comporte:

une broche (86) comprenant une première (96) et une seconde (112) portions d'extrémité, la seconde portion d'extrémité (112) présentant une rainure annulaire (110) qui est définie tout autour d'elle;

une bride (94) comprenant une première portion d'extrémité (95) fixée à la première portion d'extrémité (96) de la broche (86) et une seconde



portion d'extrémité (99) qui s'étend latéralement à partir de la broche (86) dans une direction normale à l'axe (X); et

un moyen (98) pour fixer la bride (94) au premier levier (56) et fixer de ce fait la broche (86) au premier levier (56) pour pivoter avec lui.

3. Mécanisme de liaison (10) selon la revendication 2, dans lequel le moyen de limitation (84) comporte:

une plaquette (104) comprenant une première (106) et une seconde (118) portions d'extrémité, la première portion d'extrémité (106) venant s'ajuster dans la rainure (110) formée dans la broche (86); et

un moyen (120) pour fixer la plaquette (104) au second levier (58) de façon à permettre un pivotement entre le second levier (58) et la broche (86).

4. Mécanisme de liaison (10) selon l'une quelconque des revendications précédentes, dans lequel le bras support (14) est un bras élévateur (14) d'un engin de travaux publics (12); et le mécanisme de liaison comporte en outre un outil de travail (24) monté, avec possibilité de pivotement, sur l'une des extrémités du bras élévateur (14).

5. Mécanisme de liaison (10) selon la revendication 4, dans lequel le premier (56) et le second (58)

leviers comportent un ensemble formant levier de basculement (38) qui est relié au bras élévateur (14) pour former une portion d'un dispositif de basculement (34) qui est associé à l'outil de travail (24).

6. Mécanisme de liaison (10) selon la revendication 5, dans lequel le dispositif de basculement (34) comporte également une pièce de liaison de basculement (72) qui s'étend entre l'ensemble formant levier de basculement (38) et l'outil de travail (24) pour provoquer la rotation de l'outil de travail (24) par rapport au bras élévateur (14) lors d'un mouvement des ensembles formant leviers de basculement (38).

7. Mécanisme de liaison (10) selon la revendication 6, comportant en outre un actionneur (46) relié aux leviers de basculement (56, 58) pour provoquer leur rotation par rapport au bras élévateur (14) et donc la rotation de l'outil de travail (24) par rapport au bras élévateur (14).

8. Mécanisme de liaison (10) selon l'une quelconque des revendications précédentes, dans lequel un coussinet (102) est placé à l'intérieur de l'alésage formant portée (92) du bras support (14) pour autoriser le pivotement de la broche (86) par rapport au bras support (14).

30

35

40

45

50

55

60

65

6

