

1 A MONOLITHIC INKJET PRINthead AND INK COMPOSITIONS

2

3 Field of the invention

4

5 The present invention relates to a monolithic inkjet printhead, a set of different ink
6 compositions suitable for use in said printhead, a printing apparatus comprising said
7 printhead, and methods thereof.

8

9 Background to the invention

10

11 Piezoelectric inkjet (PIJ) printheads are still a field of active research and development.
12 To date, most PIJ printheads incorporate a piezoelectric actuator in a wall of an ink
13 chamber. Deformation of a piezoelectric element causes deflection of the piezoelectric
14 actuator, inducing a pressure change in the ink stored within the chamber and thereby
15 causing ink droplet ejection through a nozzle. To achieve the required print resolution,
16 commercial PIJ printheads usually employ many parallel electrical connections to
17 external actuator drivers to drive individual piezoelectric actuators within the printhead.
18 Large numbers of wires not only increase complexity of the manufacture, but also
19 reduce reliability of the printing itself. Further, multi-colour printing may require different
20 operational inputs (e.g. different actuation waveforms) and/or different nozzles to eject
21 different inks, both adding complication to the printhead with respect to its operation
22 and configuration.

23

24 The known art in this field suffers from one or more problems as described above.

1

2 US 2011/0134175A1 describes a method of adjusting ink ejection characteristics of an
3 inkjet printing apparatus which include adjusting at least one of a voltage and an
4 application duration of a driving signal applied to a plurality of piezoelectric actuators
5 that provide ejection pressures to a plurality of nozzles so that volumes of a plurality of
6 ink droplets ejected from the plurality of nozzles are uniform, and displacing an
7 application starting time of the driving signal applied to the plurality of piezoelectric
8 actuators so that the plurality of ink droplets ejected from the plurality of nozzles reach
9 a printing medium at a same time.

10

11 US 6328395B1 describes a drive signal generating means that generates a drive signal
12 including a plural number of drive pulses during one period. Print data generating
13 means generates print data to input one or a plural number of the drive pulses to each
14 pressure generating element during one print period. The pressure generating means
15 expands and contracts in accordance with the drive pulses input thereto, to thereby
16 cause the ejection of an ink droplet or droplets.

17

18 US 6364444B1 describes an apparatus for driving an inkjet recording head which
19 includes a piezoelectric device, a drive waveform generation circuit and a waveform
20 extraction circuit. The drive waveform generation circuit generates a drive waveform in
21 which n basic waveforms are connected in series, each of the n basic waveforms
22 having a single period. The waveform extraction circuit which extracts m of the n basic
23 waveforms as a print drive waveform based on externally supplied print data and
24 applies the print drive waveform to the piezoelectric device. Thereby, an ink is
25 discharged from a nozzle based on a distortion of the piezoelectric device.

26

27 In view of the deficiencies of the prior art, the present invention aims to provide an
28 improved inkjet printhead and printing apparatus that can reliably deliver fine and
29 accurate printing. Embodiments of the invention seek to provide an inkjet printhead
30 with simple manufacture, simple operation, and compact configuration. The printhead
31 according to the present invention is for ejecting a set of different ink compositions, for
32 example a set of ink compositions of different colours.

33

34 The present invention also aims to provide a set of different ink compositions with
35 performance characteristics for high-quality printing. The ink compositions are
36 preferably a set of ink compositions of different colours. The set may be used with an
37 improved inkjet printhead with simple design and simple operation. The deposited ink

1 droplets on a printing medium may give corresponding size and shape so as to achieve
2 quality printing. It is noted that this does not exclude the use of the ink compositions
3 with printheads of complicated designs and/or operations (to achieve quality printing).

4
5 According to the present invention, a set of different ink compositions are employed
6 which, although different, have properties which are controlled such that they can be
7 ejected by corresponding droplet ejectors. Desirably, during use, the ink compositions
8 are ejected by substantially the same actuation waveform, and the resultant droplets
9 on a printing medium (e.g. a piece of paper) may have the same size and shape so as
10 to provide high quality printing, while minimising wiring complexity.

11
12 The present invention further aims to provide a printing apparatus that include said
13 inkjet printhead and preferably said ink compositions. In this way, the apparatus may
14 provide all the advantages of the printhead and the ink compositions.

15
16 WO 2021/229040A1 describes a droplet ejector assembly for a printhead comprises a
17 substrate, the substrate comprising a CMOS control circuit, a plurality of layers on the
18 first surface of the substrate, a fluid chamber having a droplet ejection outlet, and a
19 piezoelectric actuator element formed by one or more said layers and comprising first
20 and second electrodes in contact with a piezoelectric body.

21
22 US 2019/0283424A1 describes a droplet ejector for a printhead, the droplet ejector
23 comprising a substrate having a mounting surface and an opposite nozzle surface; at
24 least one electronic component integrated with the substrate; a nozzle-forming layer
25 formed on at least a portion of the nozzle surface; a fluid chamber defined at least in
26 part by the substrate and at least in part by the nozzle-forming layer; and a piezoelectric
27 actuator formed on at least a portion of the nozzle portion.

28 29 Summary of the invention

30
31 In a first aspect of the invention, there is provided a monolithic inkjet printhead for
32 ejecting a set of different ink compositions, wherein the printhead comprises a
33 substrate, the substrate comprising a plurality of ejectors each comprising: (i) a nozzle,
34 (ii) a chamber for receiving an ink composition of the set and each said chamber in fluid
35 communication with said nozzle, and (iii) a piezoelectric actuator coupled to said nozzle
36 for selectively ejecting said ink composition therefrom.

37

1 Typically, each ejector is configured to eject ink droplets of the different ink
2 compositions with corresponding volume and velocity.

3

4 Typically, each ejector is configured to eject ink compositions which meet a plurality of
5 physical property criteria with corresponding volume and velocity, the physical property
6 criteria including at least corresponding density and viscosity. The physical property
7 criteria typically also include corresponding surface tension. Typically, corresponding
8 compressibility is not required.

9

10 By corresponding viscosity, we refer to the viscosity of the ink compositions of the
11 composition being the same or similar (e.g. at 25°C and 1 atmosphere pressure). For
12 example, the viscosity values of said compositions may be such that the difference
13 between any two compositions is not more than 20% of the largest viscosity value of
14 the set, preferably not more than 10%, more preferably not more than 5%, and most
15 preferably not more than 1%.

16

17 By corresponding density, we refer to the densities of the ink compositions being the
18 same or similar (e.g. at 25°C and 1 atmosphere pressure). For example, it may be that
19 the difference in the density between any two compositions is not more than 20% of
20 the largest density value of the set, preferably not more than 10%, more preferably not
21 more than 5% and most preferably not more than 1%.

22

23 By corresponding surface tension, we refer to the surface tension of the ink
24 compositions being the same or similar (e.g. at 25°C and 1 atmosphere pressure). For
25 example, it may be that the surface tension values of said compositions are such that
26 the difference between any two compositions is not more than 20% of the largest
27 surface tension value of the set, preferably not more than 10%, more preferably not
28 more than 5%, and most preferably not more than 1%.

29

30 It will be understood that all possible combinations of the ranges of the viscosity,
31 density, surface tension and the preferred ranges of the viscosity, density, surface
32 tension are also contemplated. For instance, it may be that the differences in viscosity,
33 density and optionally surface tension between any two compositions are not more
34 than 10% of the largest corresponding value of the set, or the differences in viscosity,
35 density and optionally surface tension between any two compositions are not more
36 than 5% of the largest corresponding value of the set. It is also possible that the
37 difference in viscosity between any two compositions is not more than 20% of the

1 largest viscosity of the set, the difference in density between any two compositions is
2 not more than 10% of the largest density of the set, and, optionally, the difference in
3 surface tension between any two compositions is not more than 10% or 5% of the
4 largest surface tension of the set. It may also be that the difference in viscosity between
5 any two compositions is not more than 10% of the largest viscosity of the set, the
6 difference in density between any two compositions is not more than 5% or 1% of the
7 largest density of the set, and optionally the difference in surface tension between any
8 two compositions is not more than 5% of the largest surface tension of the set. It may
9 also be that the difference in viscosity between any two compositions is not more than
10 1% of the largest viscosity of the set, the difference in density between any two
11 compositions is not more than 1% of the largest density of the set, and optionally the
12 difference in surface tension between any two compositions is not more than 1% of the
13 largest surface tension of the set.

14

15 Typically, the configuration of the ejector comprises the dimensions of the nozzle and
16 the chamber of the ejector.

17

18 Typically, the configuration of the ejector comprises the actuation waveform of the
19 actuator in use. The actuation waveform typically comprises the time-varying
20 displacement of and the force applied to ink composition in the chamber during
21 actuation.

22

23 Typically, all the nozzles and actuators have corresponding dimensions and materials
24 such that the ejected ink droplets of the ink compositions have corresponding volume
25 and velocity.

26 Typically, the substrate has a first surface and an opposite second surface, the
27 substrate comprises a CMOS control circuit, a plurality of layers on the first surface of
28 the substrate, the piezoelectric actuator being formed by one or more said layers and
29 the nozzle comprising a hole through the one or more said layers, such that the
30 piezoelectric actuator displaces the one or more said layers and the nozzle in use to
31 thereby eject ink composition. Thus, the ejectors are typically configured to eject ink
32 composition in an inertial mode. It may be that the hole extends through the
33 piezoelectric actuator.

34

35 In the context of the present invention, it is typical that the ejected ink droplets of the
36 different compositions have corresponding volume and velocity. Said volume and
37 velocity can be evaluated by known and effective methods, such as a printed test

1 pattern. Various 'printed test pattern' methods have been described by prior art, for
2 example, US 2011/227988A1, US 8322814B2, US 10589519B2 and US 7855037B2,
3 incorporated herein by reference. The printed test pattern can be in the form of a
4 printer's testing page (e.g. a coloured printer testing page), or any suitable form
5 configured to permit evaluation of correspondence. The method can be optionally
6 repeated once or multiple times (e.g. when adjustments are needed and the
7 correspondence of volume and velocity should be evaluated again). In other words, the
8 printed test pattern can be produced multiple times. The printed test pattern may
9 comprise features such as one or more symbols (e.g. squares, dots, diamonds),
10 numbers, letters, fiducials, cross hairs, lines, grids, and mixtures thereof. The
11 positioning(s) of those features can be evaluated (e.g. by users or machines or
12 software or other suitable technologies) to determine the satisfaction of
13 correspondence, since positioning is a function of droplet volume and velocity.

14

15 By corresponding volume, we refer to having the same or similar volume (e.g. at 25°C
16 and 1 atmosphere pressure). Suitably, the ejected ink droplets have corresponding
17 volume such that the difference of volume of any two droplets from different ink
18 compositions is not more than 1 picoliters, or not more than 0.5 picoliters, or not more
19 than 0.2 picoliters, or not more than 0.1 picoliters, or not more than 0.05 picoliters, or
20 not more than 0.01 picoliters, or zero. Additionally or alternatively, the difference of
21 volume of any two droplets from different ink compositions is not more than 20% with
22 respect to the larger volume of the two droplets, or not more than 10%, or not more
23 than 5%, or not more than 1%, or zero.

24

25 By corresponding velocity, we refer to having the same or similar velocity (e.g. at 25°C
26 and 1 atmosphere pressure). Suitably, the ejected ink droplets have corresponding
27 velocity such that the difference of velocity of any two droplets from different ink
28 compositions is not more than 2m/s, or not more than 1m/s, or not more than 0.2m/s,
29 or not more than 0.1m/s, or not more than 0.05m/s, or zero. Additionally or
30 alternatively, the difference of velocity of any two droplets from different ink
31 compositions is not more than 20% with respect to the larger velocity of the two
32 droplets, or not more than 10%, or not more than 10%, or not more than 5%, or not
33 more than 1%, or zero. Herein, it will be understood that all possible combinations of
34 the sub-ranges of the volume and velocity are also contemplated. For instance, the
35 difference of volume may not be more than 10% and the difference of velocity may not
36 be more than 10% or 5%, as described above. For instance, the difference of volume
37 may not be more than 5% and the difference of velocity may not be more than 5% or

1 1%, as described above. For instance, the difference of volume may not be more than
2 0.5 picoliters, and the difference of velocity may not be more than 1m/s or 0.2m/s, as
3 described above. For instance, the difference of volume may not be more than 0.2
4 picoliters, and the difference of velocity may not be more than 0.2m/s or 0.1m/s, as
5 described above.

6
7 In the context of the present invention, a printhead is a component for use in a printing
8 apparatus. In the present invention, monolithic means all the component parts of the
9 printhead are integrated to form a single unit. This can be achieved by large-scale
10 manufacturing of multiple ejectors on a single substrate (e.g. from a single substrate
11 wafer) or by manufacturing multiple ejectors on each of a plurality of substrates and
12 joining these together.

13
14 It may be that the printhead comprises at least 100 ejectors, preferably at least 1000
15 ejectors. It may be that the printhead is for ejecting a single ink composition from the
16 plurality of nozzles.

17
18 Typically, the printhead comprises a plurality of groups (typically at least four groups)
19 of ejectors, each group of ejectors for ejecting an ink composition, at least two (and
20 typically at least four) of the ink compositions being different from each other. In this
21 way, the exemplar printhead can be used to eject a plurality (typically at least four)
22 different ink compositions. The groups are typically known in the art as channels.
23 Typically, the printhead comprises a separate manifold for each group of ejectors, to
24 supply an ink composition from a respective ink store to each ejector of the respective
25 group of ejectors.

26
27 It will be understood that each ink chamber is in fluid communication with a supply of
28 the respective ink composition to the respective nozzle. Thus, the chamber not only
29 receives and stores the ink composition but is in fluid communication with the nozzle
30 for the composition to be ejected therefrom.

31
32 It will be understood that the nozzle comprises an opening through which the ink
33 composition can be controllably ejected by operation of a piezoelectric actuator.
34 Typically, the nozzle has a cross-sectional area of less than 3 mm², for example less
35 than 0.3mm². The piezoelectric actuator typically operates to cause displacement of a
36 resiliently deformable membrane defining at least a portion of the nozzle in such a way

1 as to cause ejection of the ink composition from said nozzle on operation of said
2 actuator.

3
4 According to the present invention, the piezoelectric actuator is coupled to the
5 respective nozzle. Thus, deformation of the piezoelectric actuator during use leads to
6 movement of the nozzle. Typically, the droplet ejector comprises a resiliently
7 deformable membrane that comprises the piezoelectric actuator and defines at least a
8 portion of the nozzle (or defining the nozzle). Thus, the resilient deformable membrane
9 defines at least part (e.g. a wall of) the chamber. Typically, the actuator is disposed
10 adjacent to, for example around, the nozzle. Typically, actuation of the piezoelectric
11 actuator deflects the resiliently deformable membrane, which defines the nozzle. Thus,
12 the resiliently deformable membrane and nozzle move in use to eject ink composition
13 from within the chamber out through the nozzle. Typically, the printhead comprises a
14 nozzle-defining layer formed on the substrate, the nozzle-defining layer comprising the
15 piezoelectric actuator and defining the nozzle. The nozzle-defining layer typically
16 comprises at least one piezoelectric layer and one or more electrodes in electrical
17 contact with the at least one piezoelectric layer.

18
19 This contrasts with arrangements where the actuator is in distal association with the
20 nozzle, and/or where the nozzle and actuator are on different walls of the chamber (e.g.
21 the nozzle is on one wall of the fluid chamber, and the actuator is on the opposing wall
22 of the same chamber such that the actuator is far away from the nozzle). Existing PIJ
23 technologies where the actuator is not coupled to the nozzle/is away from the nozzle
24 require a large actuation force to compress almost the entire ink composition stored in
25 the chamber in order to eject said ink composition. This operation thus depends upon
26 compressibility mode. In these arrangements, the compressibility of the ink
27 compositions directly affects the printing process. For instance, the compressibility of
28 the ink compositions may influence the ejection procedure (e.g., by influencing the
29 stiffness of the ejectors). In this way, the compressibility of the ink is also relevant to
30 printing quality. In addition, the mass of the droplets may be influenced by the entire
31 ink in the nozzle as well as the ink in the chamber, and in some configurations, even
32 be influenced by the ink sitting very remotely from the chamber. The complication with
33 compressibility mode is that the remote ink may be relevant to damping of the ejection
34 procedure. As such, the damping is moderate, and the ejection procedure may be
35 susceptible to cross talk problem as explained below. By contrast, the present
36 arrangement avoids disturbing the majority of the ink in the chamber, and only requires
37 a small actuation force to displace the ink in the nozzle. The ink is then ejected mainly

1 by inertial force (i.e. inertial ejection) from the nozzle. Herein, ejection by inertial force
2 can also be referred to as inertial ejection or ejection by inertial mode. In the context of
3 the present invention, since the actuator is coupled to the respective nozzle, the
4 invention permits ejection of the ink (from the respective nozzle) by inertial mode other
5 than by compressibility mode. Thus, the ink compressibility is secondary to the ejection
6 procedure. The actuator of the present invention is suitably configured to eject ink
7 composition (from the respective nozzle) by inertial mode (i.e. inertial ejection).

8
9 Ejection by inertial mode (i.e. inertial ejection) has a number of closely associated
10 benefits. It permits the use of low-temperature processable piezoelectric materials
11 having lower piezoelectric constants (i.e. piezoelectric materials which are processable
12 below 450 degC or below 300 degC) since only a small actuation force is initially
13 required. The small force exerted by a piezoelectric actuator comprising low-
14 temperature processable piezoelectric materials gives relatively low fluid pressure
15 such that an acoustic cross talk problem (i.e. neighbouring actuators and fluid
16 chambers interact with one another through pressure waves in the fluid.) is mitigated.
17 Lower levels of acoustic cross talk in turn permit close integration of neighbouring
18 ejectors for a compact configuration of the printhead. Further, the mass of the droplet
19 may be influenced by the ink in the nozzle (e.g. the ink in the nozzle head) rather than
20 the entire volume of ink in the chambers. As such, damping is light, and cross talk is
21 mitigated as explained above.

22
23 To obtain a high-quality printing, the ejected ink droplets need to have corresponding
24 volume and velocity. In this way, the deposited droplets on a printing medium (e.g. a
25 paper) may give corresponding shape and volume. For inertial ejection, it is found that
26 satisfactory correspondence may be achieved by matching the frequency of an
27 actuation waveform sent to an actuator to the resonant frequency (e.g. the in-use
28 resonant frequency) of the respective nozzle. Thus, the complexity of inertial ejection
29 can be directly related to the number of separate waveforms required to drive the
30 nozzles, especially nozzles ejecting different ink compositions. For simplicity, it is
31 typical if all the nozzles require the same or similar waveforms during actuation(i.e.
32 waveforms with the same or similar frequency, typically with the same frequency). This
33 can be achieved if all nozzles have the same or similar resonant frequency (e.g. same
34 or similar resonant frequency during use). The difference of (e.g., in-use) resonant
35 frequency of any two nozzles may be not more than 10 kHz, or not more than 1 kHz,
36 or not more than 100Hz, or not more than 10 Hz, or not more than 1 Hz, or zero Hz.
37 The difference of (e.g. in-use) resonant frequency of any two nozzles may be not more

1 than 10% with respect to the larger resonant frequency of the two nozzles, or not more
2 than 5%, or not more than 1%, or not more than 0.1%, or not more than 0.01%, or zero.
3 It may be that the waveform frequency is matched to the (e.g., in-use) resonant
4 frequency of the respective nozzle in a way that the difference is not more than 10 kHz,
5 or not more than 1 kHz, or not more than 100Hz, or not more than 10 Hz, or not more
6 than 1 Hz, or zero Hz. The difference may be not more than 10% with respect to the
7 (e.g. in- use) resonant frequency of the respective nozzle, or not more than 5%, or not
8 more than 1%, or not more than 0.1%, or not more than 0.01%, or zero. The (e.g.in-
9 use) resonant frequency of the nozzle is typically from 100000 kHz to 10 kHz, more
10 typically from 10000 kHz to 20 kHz, still more typically from 5000 kHz to 50 kHz, and
11 most typically from 2000 kHz to 100 kHz. The (e.g., in-use) resonant period of the
12 nozzle is typically from 0.01 μ s (microsecond) to 100 μ s (microsecond), more typically
13 from 0.1 μ s to 50 μ s, still more typically from 0.2 μ s to 20 μ s, and most typically from
14 0.5 μ s to 10 μ s.

15

16 It will be understood that the resonant frequency of a nozzle may be influenced by the
17 dimensions and materials of the nozzle as well as those of the respective actuator. To
18 align the resonant frequency as described in the previous paragraph, it is desirable that
19 all the nozzles in the printhead have corresponding materials and dimensions, and all
20 the actuators in the printhead have corresponding materials and dimensions. It may be
21 that said nozzles have the same dimensions and materials. It may be that said
22 actuators have the same dimensions and materials. Herein, dimensions include
23 geometries, sizes and/or configurations of the nozzle and the actuator. Materials refers
24 to the articles (e.g. substances, mixtures) used to build the nozzle and the actuator.

25

26 It will be further understood that the resonant frequency may also be influenced by
27 viscosity and density (and also surface tension) of the ink composition in the nozzle.
28 Thus, there is a need to align those parameters of different ink compositions so that
29 the resultant resonant frequency of the nozzles is the same or similar (as described
30 above). Accordingly, a simple actuation force (i.e the same or similar actuation
31 waveforms) can be used to eject ink droplets from the nozzles with corresponding
32 volume and velocity, which leads to high quality printing. In other words, it would be
33 beneficial to align the identified ink parameters (i.e. viscosity, density, and surface
34 tension) in order to achieve quality printing (via a simple operation). This is especially
35 the case for inertial ejection.

36

1 It will be further understood that since the present invention (using inertial ejection) is
2 different from the existing technologies which depend on either compressibility mode
3 or thermo-ejection mode (e.g. a thermal inkjet printhead), the alignments of ink
4 properties such as compressibility (e.g. acoustic compressibility), and/or volatility,
5 and/or heat capacity (Cp), and/or thermal conductivity are usually not required. In other
6 words, there is usually no need to match (e.g. no need to match in a way as described
7 in a second aspect of the invention hereinafter) one or more said properties between
8 different ink compositions of the set.

9 In a second aspect of the invention, there is provided a set of different ink compositions
10 for use in a monolithic inkjet printhead according to the first aspect of the invention,
11 wherein: (i) the viscosity values of said compositions are matched in a way that the
12 difference between any two compositions is not more than 20% of the largest viscosity
13 value of the set, preferably not more than 10%, more preferably not more than 5%, and
14 most preferably not more than 1%; (ii) the density values of said compositions are
15 matched in a way that the difference between any two compositions is not more than
16 20% of the largest density value of the set, preferably not more than 10%, more
17 preferably not more than 5% and most preferably not more than 1%; and (iii) the
18 surface tension values of said compositions are matched in a way that the difference
19 between any two compositions is not more than 20% of the largest surface tension
20 value of the set, preferably not more than 10%, more preferably not more than 5%, and
21 most preferably not more than 1%. It is also possible that there is no difference between
22 any two compositions of the set with respect to viscosity value, and/or surface tension
23 value, and/or density value. Herein, it will be understood that all possible combinations
24 of the ranges of the viscosity, density, surface tension and the preferred ranges of the
25 viscosity, density, surface tension are also contemplated. For instance, the differences
26 in viscosity, density and optionally surface tension between any two compositions may
27 not be more than 10% of the largest corresponding value of the set, or the differences
28 in viscosity, density and optionally surface tension between any two compositions may
29 not be more than 5% of the largest corresponding value of the set. It is also possible
30 that the difference in viscosity between any two compositions is not more than 20% of
31 the largest viscosity of the set, the difference in density between any two compositions
32 is not more than 10% of the largest density of the set, and difference in surface tension
33 between any two compositions is not more than 10% or 5% of the largest surface
34 tension of the set. It may also be that the difference in viscosity between any two
35 compositions is not more than 10% of the largest viscosity of the set, the difference in
36 density between any two compositions is not more than 5% of the largest density of

1 the set, and, optionally, the difference in surface tension between any two compositions
2 is not more than 5% or 1% of the largest surface tension of the set.

3
4 As stated above, the set of ink compositions are formulated such that selected
5 properties (viscosity, density, and surface tension) of the compositions are specially
6 matched. In this way, the set can provide high-quality printing (via a simple operation).
7 Especially in inertial ejection, the same or similar actuation waveforms can be used to
8 eject these matched inks to give corresponding volume and velocity, which results in
9 corresponding shape and volume of the ink droplets deposited on a printing medium.

10
11 As stated above, there is generally no need to match compressibility of the ink
12 compositions. Herein, compressibility (k) refers to the fractional change in volume per
13 unit increase in pressure, typically measured at 20°C (and 1 atmosphere pressure).
14 The compressibility (k) is also known as the reciprocal of the Bulk modulus (B). For
15 example, for each atmosphere increase in pressure, the volume of water would
16 decrease 46.4 parts per million (i.e., $k=46.4$).

17
18 In the context of the present invention, it may be that the difference of compressibility
19 (k) of two ink compositions of the set, or of any two ink compositions in the set, is at
20 least 1% or at least 5% of the largest compressibility value of the set, or at least 10%,
21 or at least 20%, or at least 30%, or at least 40% or at least 50% of the largest
22 compressibility value of the set.

23
24 In some embodiments, the difference in viscosity between any two compositions is not
25 more than 1% of the largest viscosity of the set, the difference in density between any
26 two compositions is not more than 1% of the largest density of the set, and optionally
27 the difference in surface tension between any two compositions is not more than 1%
28 of the largest surface tension of the set, whereas the difference in compressibility (k)
29 of two ink compositions of the set, or of any two ink compositions in the set, is at least
30 1%.

31
32 In the context of the present invention, it may be that the viscosity values, the density
33 values, and the surface tension values of the set of different ink compositions are
34 matched in a way that the ejected ink droplets from the monolithic inkjet printhead have
35 corresponding volume and velocity. A 'printed test pattern' method as described herein
36 can be used to evaluate whether the droplets correspond.

1 It may be that the viscosity, density and surface tension of the set are matched
2 according to the combination of the above two paragraphs. Herein, 'different ink
3 compositions' refer to ink compositions that comprise one or more components that
4 are different from each other, and/or have one or more weight percentages that are
5 different from each other. The weight percentages can be for the same or different
6 components comprised in the compositions, and all weight percentages referred to are
7 based on the total weight of the respective ink composition. For instance, the set may
8 comprise a first composition comprising 80% aqueous carrier, and a second
9 composition comprising 80% organic carrier; or the composition may comprise a first
10 composition comprising 80% aqueous carrier, and the second composition comprising
11 85% aqueous carrier. At least two compositions of the set are different from each other,
12 and it may be that any two compositions of the set are different from each other.

13

14 In the context of the present invention, it may be that the viscosity values of the
15 compositions are matched in a way that the difference between any two compositions
16 is not more than 4 mPa·s, or not more than 2 mPa·s, or not more than 1 mPa·s, or not
17 more than 0.2 mPa·s, or zero. It may be that the density values of the compositions are
18 matched in a way that the difference between any two compositions is not more than
19 200 kg/m³, or not more than 100 kg/m³, or not more than 50 kg/m³, or not more than 10
20 kg/m³, or not more than 1 kg/m³, or zero. It may be that the surface tension values of
21 the compositions are matched in a way that the difference between any two
22 compositions is not more than 7 mN/m, or not more than 5 mN/m, or not more than 2
23 mN/m, or not more than 1 mN/m or zero.

24

25 It may be that the viscosity values of the compositions are from 1.5 mPa·s to 20 mPa·s,
26 or from 5 mPa·s to 15 mPa·s, or from 7.5 mPa·s to 12.5 mPa·s. The density values of
27 the compositions may be from 650 kg/m³ to 1750 kg/m³, or from 800 kg/m³ to 1500
28 kg/m³, or from 1000 kg/m³ to 1250 kg/m³. The surface tension values of the
29 compositions may be from 20 mN/m to 75 mN/m, or from 25 mN/m to 70 mN/m, or from
30 30 N/m to 65 N/m, or from 35 mN/m to 60 mN/m, or from 40 mN/m to 55 mN/m. It will
31 be understood that the viscosity, density and surface tension values of the different ink
32 compositions are suitably matched as described herein (i.e., any possible
33 combinations are also contemplated), and optionally those values may also be in the
34 numerical ranges as described herein (i.e., any possible combinations are also
35 contemplated). For instance, it may be that the difference in viscosity is not more than
36 4 mPa·s, the difference in density is not more than 50 kg/m³, the difference in surface
37 tension is not more than 5 mN/m, and optionally the viscosity values are from 5 mPa·s

1 to 15 mPa·s, the density values are from 800 kg/m³ to 1500 kg/m³ and the surface
2 tension values are from 30 N/m to 65 N/m (e.g. from 35 mN/m to 60 mN/m, or from 40
3 mN/m to 55 mN/m).

4
5 A suitable test method for viscosity may be based on or derived from ASTM D 4040-
6 99. Suitably, the viscosities mentioned in the present invention are measured at 25 °C/1
7 atmosphere pressure by using a rotatory viscometer (RE-80L, manufactured by TOKI
8 SANGYO CO., LTD.). A standard cone rotor (1°34' x R24) geometry can be used and
9 the ink sample size is about 1.2 mL. The speed of rotations of the geometry is 50
10 rotations per minute (rpm). The measurement lasts three minutes. A viscosity value is
11 recorded at the end of the three-minute measurement. Typically, three repeats are
12 needed for one ink sample, and the reported viscosity value is the average of these
13 three measurements.

14
15 A suitable test method for density may be based on or derived from ASTM D1475-
16 98. Suitably, the densities mentioned in the present invention are measured at 25 °C/1
17 atmosphere pressure by using a clean and dry measuring cylinder (e.g. 100 mL or
18 250mL). A balance is used to measure the mass (M) of the cylinder (e.g. typically in
19 grams). The cylinder is then taken off the balance and filled with an ink sample. The
20 volume (V) of the ink sample is recorded. The filled cylinder is put back on the balance
21 and a new mass is recorded. The density of the ink sample is determined by the
22 following equation:

$$D_{\text{density}} = (M_{\text{cylinder+ink}} - M_{\text{cylinder}}) / V_{\text{ink}}$$

23
24
25 Typically, three repeats are needed for one ink sample, and the reported density value
26 is the average of these three measurements.

27
28 A suitable test method for surface tension may be based on or derived from ASTM
29 D1331-20. Suitably, the surface tensions mentioned in the present invention are
30 measured at 25 °C/1 atmosphere pressure by using a Kruss tensiometer (e.g. Kruss
31 K11, K100). A ring method (i.e. the probe is a ring) can be used. Typically, the
32 tensiometer is calibrated by water (e.g. surface tension = 72 mN/m) prior to each ink
33 measurement. A suitable amount of ink sample (e.g. 2mL- 5mL) is put into a sample
34 container which equilibrates at 25°C. The experimental procedure of obtaining a
35 surface tension value typically follows the steps described in the supplier's manual.
36 These steps typically include lowering the ring to make contact with the ink surface,
37 waiting for equilibrium, lifting the ring up from the ink surface, and recording the surface

1 tension value measured during the lifting process. Typically, three repeats are needed
2 for one ink sample, and the reported surface tension value is the average of these three
3 measurements.

4
5 In the context of the present invention, the set of different ink compositions may have
6 the following chemical characteristics.

7
8 Colourants

9 It may be that the set of different ink compositions comprises a plurality of ink
10 compositions, each comprising a different colourant (i.e., any two compositions of the
11 set comprising colourants that are different from each other). Typically, the colourant
12 is selected from cyan (C), yellow (Y), magenta (M), key (K), red (R), green (G), blue
13 (B), orange, violet, gold, silver, white, and mixtures thereof, more typically selected
14 from CYMK and mixtures thereof, or selected from RGBK and mixtures thereof. It may
15 be that the set of different ink compositions comprise a first composition comprising a
16 cyan (C) or red (R) colourant, a second composition comprising a yellow (Y) or green
17 (G) colourant, a third composition comprising a magenta (M) or blue (B) colourant and
18 a fourth composition comprising a key (K) colourant. Preferably, the first composition
19 comprises a cyan(C) colourant, the second composition comprises a yellow (Y)
20 colourant, the third composition comprises a magenta (M) colourant, and the fourth
21 composition comprises a key (K) colourant.

22
23 In a suitable example, the printhead comprises four groups of ejectors (channels),
24 wherein each of the four groups of ejectors comprises a plurality of nozzles (e.g. 100
25 or 1000) and each group is operatively coupled to or coupled to a coloured ink
26 composition as described above, to allow ejection of the composition from the plurality
27 of the nozzles. In the same example, it may be that each of the four ink compositions
28 comprises a different colourant. Preferably the four ink compositions are with CMYK or
29 RGBK colourants, more preferably CMYK colourants.

30
31 The colourants can be pigments, dyes, or lakes (i.e., dyes precipitated from solvent to
32 a solid form), typically pigments or dyes. The pigments may be inorganic pigments,
33 organic pigments, pearl pigments, metal pigments, or mixtures thereof. Inorganic
34 pigments can be selected from titanium oxide, zinc oxide, zinc sulphate, iron oxide,
35 calcium oxide, antimony oxide, magnesium oxide, zirconium oxide, CI. Pigment Whites
36 6, 18, and 21, barium sulphate, aluminium hydroxide, barium yellow, cadmium red,
37 chrome yellow, carbon black (e.g. acetylene black, channel black, furnace black, lamp

1 black, thermal black), and mixtures thereof. Those pigments can be produced by
2 known and effective methods such as the contact method, the furnace method, and
3 the thermal method. Organic pigments can be selected from azo pigments (e.g.,
4 insoluble azo pigments, condensed azo pigments, chelate azo pigments), polycyclic
5 pigments (e.g. phthalocyanine pigments, diarylide pigments, xanthene pigments,
6 perylene pigments, perinone pigments, anthraquinone pigments, anthrapyridone
7 pigments, quinacridone pigments, dioxazine pigments, indigo pigments, thioindigo
8 pigments, isoindolinone pigments, and quinophthalone pigments), dye chelates, nitro
9 pigments, nitroso pigments, aniline black, white hollow resins, and mixtures thereof.
10 Pearl pigments can be selected from titanium dioxide-coated mica, fish scale foil,
11 bismuth trichloride, and mixtures thereof. Metal pigments are usually elemental or
12 mixed metals, selected from aluminium, silver, gold, platinum, nickel, chromium, tin,
13 zinc, indium, titanium, copper, and alloys thereof. Dyes can be selected from acid
14 dyes, direct dyes, reactive dyes, basic dyes, food dyes, and mixtures thereof.
15 Examples of the dyes include C.I. Acid Yellow 17, 23, 42, 44, 79, and 142, C.I. Acid
16 Red 52, 80, 82, 249, 254, and 289, Disperse Red 60, C.I. Acid Blue 9, 45, and 249, C.I.
17 Acid Black 1, 2, 24, and 94, C. I. Food Black 1 and 2, C.I. Direct Yellow 1, 12, 24, 33,
18 50, 55, 58, 86, 132, 142, 144, and 173, C.I. Direct Red 1, 4, 9, 80, 81, 225, and 227,
19 C.I. Direct Blue 1, 2, 15, 71, 86, 87, 98, 165, 199, and 202, C.I. Direct Black 19, 38, 51,
20 71, 154, 168, 171, and 195, C.I. Reactive Red 14, 32, 55, 79, and 249, and C.I.
21 Reactive Black 3, 4, and 35. The total level of colourant is suitably from 0.01% to 10%
22 by weight of a total ink composition, or from 0.1 to 8 wt%, or from 0.5 to 5 wt%, or from
23 1 to 3wt%. Typically, the difference of weight percentages of the total colourants
24 comprised in at least two compositions of the set or any two compositions of the set is
25 not more than 5, or not more than 2, or not more than 1, or not more than 0.1, or zero.
26 Herein, it is also possible that the difference of weight percentages of the total
27 colourants comprised in at least two compositions of the set or any two compositions
28 of the set is at least 0.01, or at least 0.1, or at least 1, or at least 2, or at least 5.

29

30 Typically, the set of different ink compositions comprises a first composition comprising
31 a cyan(C) or red (R) colourant, a second composition comprising a yellow (Y) or green
32 (G) colourant, a third composition comprising a magenta (M) or blue (B) colourant and
33 a fourth composition comprising a key (K) colourant, wherein each said colourant is
34 present from 1 to 10% (e.g. from 1% to 5%, or from 1% to 3%) by weight of the
35 respective composition. Optionally, the difference of weight percentages of these
36 colourants comprised in at least two compositions, or any two compositions is not more
37 than 2, or not more than 1, or not more than 0.1, or zero. For instance, the first

1 composition may comprise 2wt% cyan colourant, the second composition may
2 comprise 2.5 wt% yellow colourant, the third composition may comprise 3 wt%
3 magenta colourant and the fourth composition may comprise 4 wt% key colourant.
4 Optionally, the difference of weight percentages of the colourants comprised in at least
5 two compositions of the set, or any two compositions of the set, is at least 0.01, or at
6 least 0.1, or at least 0.5, or at least 1, or at least 2. For instance, the first composition
7 may comprise 1 wt% cyan colourant, the second composition may comprise 3 wt%
8 yellow colourant, the third composition may comprise 5wt% magenta colourant and the
9 fourth composition may comprise 7wt% key colourant.

10
11 In the context of the present invention, it may be that one or more components
12 (excluding the colourants that are present) of at least two coloured ink compositions or
13 any two coloured ink compositions are different. Additionally or alternatively, it may
14 also be that the weight percentages of one or more components (excluding the
15 colourants that are present) of at least two coloured ink compositions or any two
16 coloured ink compositions are different.

17
18 It may be that at least one ink composition of the set or each ink composition of the set
19 further comprises one or more components selected from carriers, rheological
20 modifiers, surfactants, dispersants, defoaming agents, corrosion inhibitors, UV-curable
21 resins, preservatives, and humectants, or selected from carriers, rheological modifiers,
22 surfactants, and humectants, or selected from carriers, rheological modifiers, and
23 surfactants, or selected from rheological modifiers. It may be that at least one ink
24 composition of the set or each ink composition of the set comprises a carrier, and/or a
25 rheological modifier, and/or a surfactant. It may be that at least one ink composition or
26 each ink composition comprises a carrier, a rheological modifier, and a surfactant.

27 28 Rheological modifier

29
30 It may be that at least one ink composition of the set or each ink composition of the set
31 comprises a rheological modifier. The modifier helps to modify (e.g. adjust) the
32 rheological behaviour (e.g. viscosity) of the ink composition. In this way, if the viscosity
33 values do not match within the set, the rheological modifier can increase or decrease
34 viscosity (where appropriate) in order to aid the matching. Although not necessary, it is
35 desirable for at least two compositions of the set or all the compositions to have the
36 same rheological modifier. It is also possible that at least two compositions of the set
37 or any two compositions of the set have rheological modifiers that are different from

1 each other. Those skilled in the art can effectively adjust the types and/or levels of the
2 modifiers comprised in the compositions. Typically, the total level of the rheological
3 modifiers by weight of a total ink composition is from 0.1 to 25%, or from 1 to 20wt%,
4 or from 2 to 15wt%, or from 5 to 10wt%. Typically, the difference of weight percentages
5 of the total rheological modifiers comprised in at least two compositions of the set or
6 any two compositions of the set is not more than 10, or not more than 5, or not more
7 than 1, or not more than 0.1. For instance, the first composition may comprise 20 wt%
8 modifier(s), the second composition may comprise 10 wt% modifier(s) and the third
9 composition may comprise 15 wt% modifier(s). It may also be that at least two
10 compositions of the set (e.g. all compositions of the set) comprise the same level of
11 rheological modifiers. It is also possible that the difference of weight percentages of
12 the total rheological modifiers comprised in at least two compositions of the set (e.g.
13 any two compositions of the set) is at least 0.01, or at least 0.1, or at least 1, or at least
14 2, or at least 5, or at least 10. For instance, the first composition may comprise 20 wt%
15 modifier(s), the second composition may comprise 25 wt% modifier(s), and the third
16 composition may comprise 15wt% modifier(s).

17

18 A suitable example of a rheological modifier is a polymer. The polymer can be natural
19 or synthetic. Additionally and optionally, it can be selected from anionic polymers, non-
20 ionic polymers, or amphoteric polymers. Typically, the polymer is a polyurethane,
21 polyacrylic or polyacrylate, polysaccharide (e.g. cellulose, mannose, fructose,
22 galactose, glucose, mannose, ribose, xylose, arabinose, gum, guar, pectin, starch),
23 polyvinyl alcohol, or an ethoxylated polymer. A preferred choice is a polyacrylic or
24 polyacrylate homopolymer or copolymer. Such a polymer can be prepared by addition
25 polymerization of a mixture of ethylenically unsaturated monomers. The polyacrylic or
26 polyacrylate can also be a linear or crosslinked copolymer and such a copolymer can
27 be optionally hydrophobically modified. Typically, the ink composition (e.g. at least one
28 ink composition of the set or all ink compositions of the set) comprises a rheological
29 modifier which is a polymer (e.g. polyacrylic or polyacrylate as described herein), at a
30 level of from 0.1 to 5 by weight of the total composition, or from 0.2 to 2wt%, or from
31 0.5 to 1wt%.

32

33 Commercial examples of polymer rheology modifiers include, but are not limited to,
34 ACRY SOL® RM-5000 and ACRY SOL® RM-825 (Rohm & Haas, a wholly owned
35 subsidiary of Dow Chemical Company); BORCHIGEL® L75N, BORCHIGEL® L0625,
36 and BORCHIGEL® L W44 (all available from OMG Borchers GmbH, Langenfeld,
37 Germany) BYK® 428 and BYK® 429 (both available from BYK Chemie GmbH); and

1 DSX® R2000 E, DSX® R3000 E, and DSX® R3075 E (all available from Cognis
2 GmbH, Monheim am Rhein, Germany).

3
4 Another suitable example of a rheological modifier is glycerol. Other polyols may also
5 be used. It is found that glycerol may effectively increase the viscosity of the ink
6 composition, aiding the matching of viscosity values. Typically, the ink composition
7 (e.g. at least one ink composition of the set or all ink compositions of the set) comprises
8 from 5 to 25% glycerol by weight of the total composition, or from 7 to 20 wt%, or from
9 10 to 15 wt%. It may be that one or more compositions of the set (e.g. all compositions
10 of the set) comprise a glycerol, or comprise both glycerol and polymer rheology
11 modifier(s), optionally the ratio of glycerol/polymer being from 100/1 to 1/1, or from 50/1
12 to 2/1, or from 20/1 to 5/1, or from 15/1 to 10/1. It may also be that one or more
13 compositions of the set comprise a glycerol and one or more compositions comprise a
14 polymer rheological modifier.

15
16 The carrier

17
18 It may be that one or more ink compositions (e.g. all ink compositions) of the set
19 comprise a carrier. The carrier is typically a liquid at 20°C at atmospheric pressure.
20 Herein, carrier refers to a liquid in which other components of the ink composition can
21 be dispersed or dissolved to form said composition.

22
23 An ink composition can suitably comprise one or more carriers. The ink composition
24 can be water based or oil based. Thus, the carriers can be aqueous carriers, organic
25 carriers or mixtures thereof. It is advantageous that at least two compositions of the set
26 or all the compositions of the set comprise the same carrier, or comprise at least the
27 same type of carriers (e.g. all the compositions comprise an aqueous carrier, or
28 comprise an organic carrier, or comprise a mixture of aqueous and organic carriers).
29 In this way, the densities of the set may be matched with ease. It is also possible for at
30 least two compositions of the set or any two compositions of the set to comprise
31 different carriers, or to comprise different types of carriers (e.g. one of the at least two
32 ink compositions comprises an aqueous carrier and the other of the at least two ink
33 compositions comprises an organic carrier).

34
35 Herein, an aqueous carrier typically refers to a carrier containing water, typically at
36 least 50% water by weight of the total aqueous carrier, or at least 70 wt%, or at least
37 80 wt%, or at least 90wt%, or at least 95wt%, or 100 wt%. The aqueous carrier can be

1 water. Typically, the water is purified water. Examples of purified water include but are
2 not limited to deionized water (D.I., water), ultra-filtrated water, distilled water, and ion
3 exchanged water. The use of such water can prevent microorganism (e.g. fungi, mould)
4 growth during ink storage, hence promoting ink hygiene.

5
6 The carrier can be an oil. Herein, the term 'oil' signifies a water-insoluble organic
7 material that is liquid at 20°C. Any material having a solubility of less than 0.1g/100ml
8 at 20°C is considered to be insoluble. Oils can be selected from hydrocarbons (e.g.
9 aliphatic hydrocarbons, isomerized aliphatic hydrocarbons, branched or linear chain
10 aliphatic hydrocarbons, aromatic hydrocarbons), silicone oils, vegetable oils, and
11 mixtures thereof. Oil carriers are organic carriers.

12
13 The carrier can also be a water-soluble or water miscible organic carrier. Suitable
14 examples include but are not limited to ethanol, isopropyl alcohol, acetone, diacetone
15 alcohol, polyols (e.g. ethylene glycol, diethylene glycol, triethylene glycol, polyethylene
16 glycol, propylene glycol, dipropylene glycol, tripropylene glycol, polypropylene glycol,
17 propanediol, butanediol), glycol ethers (e.g., ethylene glycol monomethyl ether,
18 diethylene glycol monomethyl ether, diethylene glycol monoethyl ether, diethylene
19 glycol monobutyl ether), amines having a hydroxyl group and mixtures thereof.

20
21 Other suitable examples of the carriers include but are not limited to triethylene glycol
22 monobutyl ether, 2-[2-(2-butoxyethoxy)ethoxy]ethanol, 3-Methyl-1,5-pentanediol,
23 Poly(oxy-1,2-ethanediyl), α,α' -[1,4-dimethyl-1,4-bis(2-methylpropyl)-2-butyne 1,4-
24 diyl]bis[omega.-hydroxy], Bis(2-ethoxyethyl) ether and 1-ethoxy-2-(2-methoxy
25 ethoxy)ethane.

26
27 The total level of carriers in an ink composition is typically from 10 to 85 %, or from 15
28 to 80 %, or from 20 to 75%, or from 50 to 70% by weight of the total composition. If the
29 carrier is an aqueous carrier (e.g. water), the total level in an ink composition is typically
30 from 50 to 85 wt%, or from 55 to 80wt%, or from 60 to 70wt%. If the carrier is an organic
31 carrier (e.g. an oil, a water-soluble organic carrier) or a mixture of organic carriers, the
32 total level is typically from 10 to 60 wt%, or from 20 to 50 wt%, or from 30 to 40 wt%. If
33 the carrier is a mixture of aqueous and organic carriers, the weight ratio of the aqueous
34 to the organic carriers may be at least 1/1, or greater than 1/1. Typically, the difference
35 of weight percentages of the carriers comprised in any two compositions of the set or
36 at least two compositions of the set is not more than 10, or not more than 5, or not more
37 than 1, or not more than 0.1. It is also possible for all the compositions of the set to

1 comprise the same level of carriers. For instance, the set may comprise five different
2 ink compositions and each ink composition comprises 80 wt% carrier(s) in total. It is
3 also possible that the difference of weight percentages of the carriers comprised in at
4 least two compositions of the set (e.g. any two compositions of the set) is at least 0.01,
5 or at least 0.1, or at least 1, or at least 5, or at least 10.

6 7 The surfactant

8
9 It may be that at least one ink composition or each ink composition of the set comprises
10 a surfactant. The surfactant is typically used to lower the surface tension of the ink
11 composition. In this way, the surfactant helps to adjust (if needed) the surface tension
12 of the ink composition. The surfactant may be selected from anionic surfactants, non-
13 ionic surfactants, cationic surfactants, amphoteric surfactants, and mixtures thereof. It
14 is desirable for any least two compositions of the set or any two compositions of the
15 set to comprise the same surfactant, or to comprise at least the same type of
16 surfactants (i.e. all the compositions comprise an anionic surfactant, or comprise a
17 cationic surfactant, or comprise a non-ionic surfactant, or comprise an amphoteric
18 surfactant). It is also possible for at least two compositions of the set or any two
19 compositions of the set to comprise surfactants different from each other, or to
20 comprise different types of surfactants (e.g. one of the at least two ink compositions
21 comprises an anionic surfactant and the other of the at least two ink compositions
22 comprises an non-ionic surfactant).

23
24 Typically examples of the surfactants include but are not limited to acetylenic
25 surfactants, phosphate surfactants (e.g. phosphate esters of fatty alcohols or fatty
26 alcohol alkoxylates), acetylene glycol-based surfactants, silicone-based surfactants
27 (e.g. polysiloxanes), polyethylene glycol (PEG)-based surfactants (e.g. PEG 8000,
28 Polysorbate 80, Pluronic F-68, PEG-fatty acids), fluorine-based surfactants (e.g.
29 fluorine-modified polymers), and mixtures thereof.

30
31 The total level of the surfactants is typically from 0.01% to 10% by weight of an ink
32 composition, or from 0.02 to 2.5 wt%, or from 0.05 to 2 wt%, or from 0.1 to 1 wt%.
33 Typically, the difference of weight percentages of the surfactants comprised in at least
34 two compositions of the set or any two compositions of the set is not more than 5, or
35 not more than 2, or not more than 1, or not more than 0.1. It is also possible for all the
36 compositions of the set to comprise the same level of surfactants. For instance, it is
37 possible for a set to comprise five different ink compositions and each composition

comprises the same level of surfactants in total. It is also possible that the difference of weight percentages of the surfactants comprised in at least two compositions (e.g. any two compositions of the set) is at least 0.01, or at least 0.1, or at least 1, or at least 2, or at least 5.

The humectant

It may be that at least one ink composition or each ink composition of the set comprises a humectant. The humectant is typically a water-soluble or water-miscible organic compound. Inclusion of such a compound may improve the moisturization of the ink composition so that the nozzle is less likely to be clogged even if unattended for a long time.

Typically, the humectant comprises a hydrophilic group. A humectant can be selected from alkyl polyols (e.g. ethylene glycol, propylene glycol, glycerol), nitrogen-containing cyclic compounds (e.g. 2-pyrrolidone, N-methyl-2-pyrrolidone), lactones (e.g., γ -butyrolactone), betaines, glycol ethers (e.g., diethylene glycol mono-butyl ether, propylene glycol monoethylether), ureas (e.g. ethyl urea, tetramethyl urea, thiourea, 1,3-dimethyl-2-imidazolidinone), amides (e.g. N-methylformamide), amines (e.g. monoethanolamine, triethylamine), and mixtures thereof.

The total level of humectants is typically from 0.1% to 30% by weight of a total ink composition, or from 0.2 wt% to 20 wt%, or from 0.5 to 15wt%, or from 1 to 10 wt%, or from 2 to 5wt%. The amount included is effective against clogging as well as possible for a skilled worker to match the values of the viscosity, density and surface tension of the set.

Other optional components

Further, at least one ink composition of the set or each ink composition of the set may comprise a preservative. Examples may include sodium benzoate, sodium pentachlorophenol, phenoxyethanol, 2-pyridinethiol-1-oxide sodium, sodium sorbate, sodium dehydroacetate, 1,2-benzisothiazolin-3-one, and 4-Chloro-3-methylphenol. The ink composition may comprise a UV-curable resins (e.g. acrylated epoxies, acrylated polyesters, acrylated urethanes, acrylated silicones). The ink composition may comprise a dispersant. Examples of dispersants may include anionic dispersants (e.g. naphthalene sodium sulfonate), non-ionic dispersants, polymer dispersants (e.g.

1 acrylic resins, styrene resins, urethane resins). The composition may comprise a
2 defoaming agent such as silicone-based defoaming agent, polyether-based defoaming
3 agent, aliphatic acid ester-based defoaming agent. The composition may comprise a
4 corrosion inhibitor such as acid sulphite, and sodium thiosulfate. Each of the above
5 optional components may be present in an amount effective to accomplish its purpose
6 in the ink composition. Generally, these optional components are included individually
7 at an amount of up to 5%, by weight of a total ink composition. At least one ink
8 composition of the set or each composition of the set may comprise one or more
9 optional components as described herein.

10
11 In preferred embodiments, at least one composition of the set or each composition of
12 the set comprises a colourant (e.g. 0.01-10 wt%), a carrier (e.g. 10-85 wt%), a
13 surfactant (e.g. 0.01-5 wt%) and a rheological modifier (e.g. 0.1-25 wt%). Said
14 composition may also comprise one or more other ingredients as described herein (e.g.
15 a humectant optionally from 0.1 to 10 wt%). In still preferred embodiments, a set of
16 different ink compositions comprises a first composition comprising a cyan (C) or red
17 (R) colourant, a second composition comprising a yellow (Y) or green (G) colourant, a
18 third composition comprising a magenta (M) or blue (B) colourant and a fourth
19 composition comprising a key (K) colourant (e.g. black colourant), wherein each said
20 colourant is present from 1 to 10% by weight of the respective composition. In the same
21 or other embodiments, it may be that at least one composition of the set or each
22 composition of the set further comprises a carrier (e.g. 10-85 wt% or 50-80 wt%), a
23 surfactant (e.g. 0.01-5 wt% or 0.1-2 wt%, and a rheological modifier (e.g. 0.1-25 wt%,
24 or 0.5- 20 wt%).

25
26 In the above-mentioned preferred embodiments and other embodiments, the
27 difference of weight percentages of the colourants comprised in at least two
28 compositions, or any two compositions of the set may be not more than 5, or not more
29 than 2, or not more than 1, or not more than 0.1 and any weight percentage is based
30 on the total weight of a respective ink composition. It is also possible that the difference
31 of weight percentages of the total colourants comprised in at least two compositions of
32 the set (e.g. any two compositions of the set) is at least 0.01, or at least 0.1, or at least
33 1, or at least 2, or at least 5. Alternatively or additionally, it may be that the difference
34 of weight percentages of the rheological modifiers, and/or the surfactants, and/or the
35 carriers comprised in at least two compositions or any two compositions is not more
36 than 20, or not more than 10, or not more than 5, or not more than 1, or not more than
37 0.1. Alternatively or additionally, at least two compositions of the set or any two

1 compositions of the set may comprise rheological modifiers different from each other,
2 and/or surfactants different from each other, and/or carriers different from each other,
3 and optionally wherein the difference of weight percentages of the rheological
4 modifiers, and/or the surfactants, and/or the carriers comprised in at least two
5 compositions of the set (e.g. any two compositions of the set) is at least 0.1, or at least
6 1, or at least 5, or at least 10.

7
8 Manufacturing method of the ink compositions

9
10 In a further aspect of the invention, there is provided a method of making the set of
11 different ink compositions as described herein. The method comprises the steps of: (i)
12 making at least two ink compositions; (ii) determining whether the viscosity, density
13 and surface tension values of the at least two ink compositions are matched in a way
14 as described herein (i.e. the set is a set of different ink compositions according to the
15 present invention); and (iii) if this is not the case, modifying at least one of the at least
16 two ink compositions one or more times until the set of the compositions is a set
17 according to the present invention. The set of different ink compositions is for use in a
18 printing apparatus as described hereinafter.

19
20 The method may further comprise the steps of: (a) mixing the carrier, the colourant, the
21 rheological modifier, the surfactant, and optionally other components (e.g. other
22 components as described herein), and optionally (b) filtering to remove impurity or
23 impurities from the mixture.

24
25 Steps (a) and/or (b) may be optionally repeated.

26
27 In step (a), the mixing can be in any appropriate order. It is typically performed by
28 adding the required components into a container equipped with a stirrer (e.g. a
29 magnetic stirrer, a sand mill, a homogenizer, a ball mill), and mixing therein until
30 homogeneity. The mixing can also be done by using a paint shaker, or an ultrasonic
31 dispersing device, or any suitable high-speed dispersing device.

32
33 The viscosity, density and surface tension values of an ink composition can be
34 determined by any suitable methods, for example, by the ASTM methods or suitable
35 methods described herein. Virtual simulation (e.g. computer calculation to predict
36 those values of the ink) is not excluded. If the values are matched as described herein

1 (i.e. the set of ink compositions is a set of different ink compositions As according to
2 the present invention), further modification(s) of the ink may not be necessary.

3
4 If the values are not matched as described herein, the viscosity, density and surface
5 tension can suitably be modified (e.g. adjusted), for example, by adjusting the types
6 and/or levels of the rheological modifiers, the carriers, and the surfactants respectively.
7 The modified (e.g. adjusted) ink composition(s) may be determined for its viscosity,
8 density and surface tension. If needed, further modification (e.g. adjustment) may be
9 performed to achieve the matching as described herein. In other words, steps (ii) and
10 (iii) of the method may be optionally repeated until the matching is achieved (i.e. until
11 the set of the compositions is a set according to the present invention).

12
13 The resulting set of different ink compositions may be used in printing. The resulting
14 set of different ink compositions may be used as the specification for inks to be
15 manufactured. Corresponding inks may then be manufactured.

16 17 Selecting a set of ink compositions

18
19 In still a further aspect of the invention, there is provided a method of selecting a set of
20 different ink compositions, comprising the steps of: (i) defining at least one
21 characteristic of an ejected ink droplet; (ii) using the at least one defined characteristic
22 to determine target values of viscosity, density and surface tension of an ink
23 composition; and (iii) selecting at least two ink compositions with reference to the target
24 values as described in steps (ii), wherein the values of the at least two ink compositions
25 are also matched in a way as described herein (i.e. the set of the ink compositions is a
26 set of different ink compositions according to the present invention). The set of different
27 ink compositions is for use in a printing apparatus as described hereinafter.

28
29 The at least one defined characteristic may be used to determine target values of
30 viscosity, density and surface tension of an ink composition in combination with a
31 printhead according to the invention, or a simulation thereof.

32
33 The at least one defined characteristic of the ejected ink droplet may comprise the size
34 of said droplet. Additionally and optionally in step (i), a value of dots per inch (DPI) may
35 also be defined. The DPI may be from 100 to 2000 dpi, or from 300 to 1800 dpi, or from
36 600 to 1600 dpi. The defined characteristic of the ink droplet (optionally with the defined
37 DPI) helps to determine target physical properties of the ink (i.e. viscosity, density and

1 surface tension). It will be further understood that the characteristic of the ejected
2 droplet and/or the DPI may be defined virtually (e.g. by using a computer-implemented
3 method). The ink compositions are selected with reference to those target physical
4 properties. Herein, 'with reference to' means the physical properties of the selected
5 inks are matched with the target physical properties. Typically, the difference of
6 viscosity is not more than 10 % with respect to the target viscosity, or not more than
7 5%, or not more than 1%. Typically, the difference of density is not more than 20% with
8 respect to the target density, or not more than 10%, or not more than 5%, or not more
9 than 1%. Typically, the difference of surface tension is not more than 10% with respect
10 to the target surface tension, or not more than 5%, or not more than 1%. Any possible
11 combinations of the sub-ranges are also contemplated. The selected inks also have
12 the physical properties matched with each other, as described herein (i.e. the selected
13 set of ink compositions is a set of different ink compositions according to the present
14 invention).

15

16 After target physical properties are determined (i.e. after step (ii)), it may be that a set
17 of candidate ink compositions is first determined. Typically, the candidate ink
18 compositions are already different to each other (due to differences in colour or
19 chemical composition or reactivity). The viscosity, surface tension, and density of the
20 candidates can be determined (e.g. according to the methods as described herein). If
21 the values match with each other (as described herein) and with the target physical
22 properties, the candidate set can be selected (e.g. in accordance with step (iii)).
23 Otherwise, at least one composition of the set can be modified (e.g. one or more times,
24 optionally as by the methods described herein), and the physical properties of the
25 modified set can be determined again. Said modification and determination can be
26 optionally repeated until the required matching is achieved. Then the modified set of
27 different inks can be selected for subsequent manufacture and/or use (e.g. in
28 accordance with step (iii)).

29

30 The printer

31

32 In still a further aspect of the invention, there is provided a printing apparatus
33 comprising a monolithic printhead according to the first aspect of the invention. The
34 printing apparatus further comprises a signal generator configured to generate a
35 driving signal having a repeating waveform, and a control circuitry configured to relay
36 the driving signal to the actuators through switches and to control the switches to
37 selectively apply the driving signal to individual actuators to thereby eject ink droplets

1 of the different ink compositions with corresponding volume and velocity. Preferably,
2 the printing apparatus is a printer. Preferably, the printing apparatus comprises the set
3 of different ink compositions of the invention, and the ink compositions are received or
4 receivable in the chambers of the printhead. Preferably, the viscosity, the density and
5 the surface tension of the set of different ink compositions are matched in a way that
6 the difference between any two compositions is not more than 5% (or not more than
7 1%) of the largest corresponding value of the set. Optionally and additionally, the
8 difference of compressibility of two ink compositions or of any two ink compositions is
9 at least 5% (or at least 10%) of the largest compressibility value of the set.

10
11 It may be that the printhead and the set of different ink compositions are comprised in
12 an ink cartridge, wherein the compositions are received in the chambers of the
13 printhead. The ink cartridge can be a component part of the printing apparatus.

14
15 Suitably, the control circuitry configured to relay the driving signal is comprised in the
16 monolithic inkjet printhead. In other words, the control circuitry can be part of the
17 printhead. Furthermore, the complexity of wiring connections in the printhead can be
18 reduced, because separate control wiring to each actuator need only be provided from
19 the control circuitry on each printhead; the control instructions for any actuators on a
20 printhead can be provided onto the printhead via a single wiring connection to the
21 control circuitry on the printhead.

22
23 The control circuitry may comprise a CMOS circuit (i.e. a complementary metal oxide
24 semiconductor) and a plurality of circuit elements each associated with a printhead
25 ejector.

26
27 The control circuitry may be integrally formed with the printhead nozzles. In other
28 words, formation of the control circuitry, the printhead nozzles and (optionally) the
29 piezoelectric actuators can be provided at the same time, without requiring assembly
30 of multiple component parts assembled separately. By providing the control circuitry
31 using an integrated circuit, the control circuitry can be provided adjacent the printhead
32 nozzles, thereby ensuring the printhead is compact.

33
34 It may be that the control circuitry comprises (a) a digital register. It may be that the
35 control circuitry comprises (b) a nozzle trimming calculation circuit and/or register. It
36 may be that the control circuitry comprises (c) a temperature measurement circuit. It
37 may be that the control circuitry comprises (d) a fluid chamber fill detection circuit.

1

2 The digital register may be a shift register, or a latch register, for example. In operation,
3 it may be that data is stored in or read from a register within the control circuitry. In
4 operation, it may be that temperature is measured using a temperature sensitive
5 component of the temperature measurement circuit. In operation, it may be that the fill
6 level of a fluid chamber is measured.

7

8 It may be that the control circuitry is configured to modify the voltage pulses applied to
9 one or more electrodes of one or more piezoelectric actuators responsive to data
10 stored by the control circuitry or measurements from one or more sensors, which are
11 typically within the printhead. In operation, it may be that the control circuitry measures
12 the voltage pulses applied to one or more electrodes of one or more piezoelectric
13 actuators responsive to data stored by the control circuitry or measurements from one
14 or more sensors, which are typically within the printhead.

15

16 Modifying the voltage pulses may comprise shifting them in time. Modifying the voltage
17 pulses may comprise compressing or expanding them. Modifying the voltage pulses
18 may comprise modifying their magnitude. Modifying the voltage pulses may comprise
19 swapping between a plurality of (typically repeating) sequences of received actuator
20 drive pulses with different profiles. The control circuitry is typically configured to modify
21 the voltage pulses applied to one or more electrodes of one or more individual
22 piezoelectric actuators responsive to data relating to that individual piezoelectric
23 actuator stored by the control circuitry or measurements from one or more sensors.

24

25 The control circuitry comprises a plurality of circuit elements each associated with a
26 printhead ejector. The circuit element can be an ejection transistor. The ejection
27 transistor is typically in direct electrical communication (without intervening switched
28 semiconductor junction) with an electrode of the piezoelectric actuator. In operation, it
29 may be that the ejection transistor is controlled to cause a potential output from the
30 ejection transistor to be applied directly to an electrode of the piezoelectric actuator.

31

32 The control circuitry may be configured to receive input control signals from outside the
33 printhead and to output actuator control signals to each of the plurality of actuators to
34 control ejection of the inks from the plurality of printhead nozzles.

35

36 It may be that the printhead further comprises an electrical input for receiving actuator
37 drive pulses. In operation, the printhead may receive actuator drive pulses.

1

2 The printhead may comprise a controller for controlling the printhead. The controller
3 may comprise one or more microcontrollers or microprocessors, which may be
4 integrated or distributed, in communication with or comprising a memory storing
5 program code.

6

7 It may be that the controller comprises a signal generator configured to generate
8 (typically a sequence of) actuator drive pulses. Each printhead typically comprises an
9 electrical input connected to the controller through which the actuator drive pulses are
10 received. In operation, the printhead assembly may generate actuator drive pulses
11 (e.g. in a controller) and conduct them to the printhead through an electrical connection.

12

13 The actuator drive pulses are typically analogue signals. The actuator drive pulses
14 typically comprise periodic repeating voltage waveforms.

15

16 It may be that the control circuitry is configured to switchedly connect or disconnect at
17 least one electrode of the or each of a plurality of piezoelectric actuators to the received
18 actuator drive pulses to thereby selectively actuate the piezoelectric actuators. In
19 operation, it may be that the printhead switchedly connects or disconnects at least one
20 electrode of the or each of a plurality of piezoelectric actuators to the received actuator
21 drive pulses to thereby selectively actuate the piezoelectric actuators.

22

23 It may be that the controller comprises one or more pulse generators which generate
24 a plurality of sequences of actuator drive pulses, and electrical inputs of the printhead
25 receive the plurality of sequences of actuator drive pulses (generated by the one or
26 more pulse generators) through a plurality of electrical connections to the controller,
27 and the control circuitry is configured to switchedly connect or disconnect at least one
28 electrode of the or each of a plurality of piezoelectric actuators to received actuator
29 drive pulses selected from a plurality of different received sequences of actuator
30 pulses. In operation, it may be that the printhead generates a plurality of different
31 sequences of actuator drive pulses (e.g. in a controller) and conducts them to the
32 printhead through separate electrical connections, and switchedly connects or
33 disconnects at least one electrode of the or each of a plurality of piezoelectric actuators
34 to one or more received actuator drive pulses received from a variable (and selectable)
35 one of the plurality of different sequences of actuator drive pulses.

36

1 The selection as to which received sequence of actuator pulses at least one electrode
2 of piezoelectric actuator is connected to may be responsive to stored data specific to
3 the respective piezoelectric actuator and/or responsive to measurements of operation
4 of the respective piezoelectric actuator. Accordingly, the control circuitry can typically
5 select whether or not each piezoelectric actuator ejects a droplet at each of a sequence
6 of periodic droplet ejection decision points. By a decision point we refer to a time prior
7 to the start of an actuator drive pulses where it is determined whether or not to
8 communicate that actuator drive pulse to at least one electrode of a specific
9 piezoelectric actuator.

10
11 Typically, the actuator drive pulses repeat periodically. It may be that the actuator drive
12 pulses are amplified by the controller. It may be that the actuator drive pulses are not
13 amplified by the printhead. It may be that the printhead does not generate actuator
14 drive pulses.

15
16 Typically pulses from the pulse generator are conducted to a plurality of control circuits,
17 which may be part of a plurality of printheads. Thus a single pulse generator circuit
18 may drive multiple piezoelectric transducers on the same substrate and/or multiple
19 printheads having separate substrates, each having multiple piezoelectric transducers.

20
21 The digital actuation control signals are typically received from a controller. The digital
22 actuation control signals are typically received through a flexible connector. The digital
23 actuation control signals may be received in serial form and converted to parallel
24 control signals using a shift register within the control circuitry.

25
26 It may be that the controller comprises a pulse generator configured to generate
27 actuator drive pulses which are conducted to the printhead and digital control signals
28 which are conducted to the printhead and the digital control signals are processed in
29 the control circuitry of the printhead to determine which actuator drive pulses are
30 conducted to at least one electrode of the piezoelectric actuator or piezoelectric
31 actuators of the one or more printhead modules to cause droplet ejection.

32
33 In operation, it may be that the printhead assembly generates actuator drive pulses
34 (e.g. at a controller) and digital control signals, and conducts both the actuator drive
35 pulses and the digital control signals to the control circuitry of the printhead and the
36 control circuitry processes the digital control signals and, responsive thereto, conducts

1 selected actuator drive pulses to at least one electrode of the piezoelectric actuator or
2 piezoelectric actuator of the one or more printheads to cause droplet ejection.

3
4 Thus, typically analogue actuator drive pulse and digital control signals are input by the
5 control circuitry (and typically by the printhead modules). Typically the digital control
6 signals are used to selectively switch the analogue actuator drive pulses to thereby
7 selectively transmit them to the piezoelectric actuators.

8
9 In some embodiments, the control circuitry is configured to switchedly connect one or
10 more of ground and a single fixed non-zero voltage line, or multiple fixed voltage lines
11 of different voltages (one or more of which may be ground) to one or both electrodes
12 of a piezoelectric actuator to cause droplet ejection of print agent. For example, the
13 control circuitry may switch an electrode between a connection to ground and a
14 connection to a fixed voltage or multiple fixed voltage lines of different voltages and
15 back to ground again in order to cause a droplet ejection. Typically, the second
16 printhead module is configured to conduct a said ground and/or a said single fixed non-
17 zero voltage from the first printhead module to the third printhead module.

18
19 Switching an electrode between a connection to ground and a connection to a fixed
20 voltage or between fixed voltage lines may comprise operating a latch.

21
22 It may be that the control circuitry is configured to individually and selectively actuate
23 at least three (or at least four) said piezoelectric actuator elements formed by one or
24 more said layers on the same substrate and defining part of different respective fluid
25 chambers (with different respective droplet ejection outlets, sometimes referred to as
26 printhead nozzles), optionally wherein the said at least three (or at least four) actuator
27 elements are configured for ejecting different coloured ink compositions or as
28 redundant droplet ejection outlets.

29
30 It may be that the said at least three (or at least four) piezoelectric actuator elements
31 are located on the substrate (optionally adjacent each other, optionally in a row) and
32 the control circuitry is connected to a flexible printhead cable having one or more
33 electrical signal conductors, wherein the control circuitry is configured to individually
34 and selectively actuate the actuator elements of the at least three (or at least four)
35 piezoelectric actuator elements responsive to actuation commands received through
36 the same signal conductor.

37

1 Thus, due to the integration of the control circuitry which is configured to drive at least
2 three (or at least four) actuator elements, an individual signal conductor may transmit
3 a control signal leading to the actuation of individual actuator elements of the at least
4 three (or at least four) piezoelectric actuator elements. Typically the control signals are
5 digital control signals.

6
7 The at least three (or at least four) piezoelectric actuator elements may comprise or
8 are a group of piezoelectric actuator elements, for example a group of piezoelectric
9 actuator elements which are configured to eject the same ink composition (for example
10 have chambers in fluid communication with the same ink supply), or ink compositions
11 of different colours (for example have chambers in fluid communication with separate
12 ink supplies), or a group of piezoelectric actuator elements which are divided into a
13 plurality of (typically at least three or at least four) sub-groups, wherein the piezoelectric
14 actuator elements in each sub-group are configured to eject the same ink composition
15 (for example have fluid chambers in fluid communication with the same fluid supply)
16 and the piezoelectric actuator elements of some or all of the sub-groups are configured
17 to eject ink compositions of different colours (for example are in fluid communication
18 with separate ink supplies). Piezoelectric actuator elements in the same sub-group
19 may be arranged in an array and there may be a plurality of arrays for respective sub-
20 groups.

21
22 It may be that the control circuitry is configured to individually and selectively actuate
23 at least double the number of piezoelectric actuator elements than signal conductors
24 through which the control circuitry receives actuation control signals.

25
26 It may be that the said control circuitry is configured to individually and selectively
27 actuate at least 128 (or at least 256) piezoelectric actuator elements and the control
28 circuitry receives actuation control signals through at most 32 (or at most 16) signal
29 conductors.

30
31 The control circuitry may comprise a serial to parallel conversion circuit configured to
32 convert a digital signal received in serial form through one or more signal conductors
33 into a selection of piezoelectric actuators to be actuated to carry out a droplet ejection
34 simultaneously (i.e. in parallel). The serial to parallel conversion circuit typically
35 comprises one or more shift registers.

36
37 Manufacturing of the printing apparatus and the printing method

1
2 In still a further aspect of the invention, there is provided a method of manufacturing a
3 printing apparatus, comprising the steps of: (i) forming control circuitry in a substrate;
4 (ii) forming a plurality of piezoelectric actuators each in electrical communication with
5 the control circuitry; (iii) forming a plurality of nozzles, each coupled to a respective one
6 of the plurality of piezoelectric actuators; and (iv) forming a plurality of chambers each
7 in fluid communication with a respective one of the plurality of nozzles. The set of
8 different ink compositions may be received or receivable in the plurality of chambers.
9 The method may also comprise making the set of different ink compositions for use in
10 said printing apparatus. The ink compositions may be made as described herein. The
11 method may comprise receiving the set of different ink compositions each in a
12 respective one of the plurality of the chambers.

13
14 In still a further aspect of the invention, there is provided a method of printing
15 comprising the steps of: (i) providing a printing apparatus as described in the previous
16 aspect; and (ii) operating the control circuitry to eject at least one, and typically at least
17 two, ink composition(s) of the set according to the second aspect from at least one,
18 and typically at least two, of the plurality of the nozzles of the plurality of the printhead
19 ejectors. Typically, the ink droplets of at least two ink compositions from the at least
20 two of the plurality of nozzles are ejected with corresponding volume and velocity. The
21 printing apparatus may be as described herein. The ink compositions may be as
22 described herein.

23
24 Any feature of one aspect of the present invention may be utilised in any other aspect
25 of the invention where appropriate. Any feature of a particular embodiment may be
26 utilized in any other embodiment of the invention where appropriate. Any optional
27 feature (e.g. features described as 'preferred' or 'typical') should be understood to be
28 particularly preferred in combination with a further optional feature or features. Unless
29 otherwise stated, no features described should be considered incompatible with any
30 other features, unless such a combination is clearly and inherently incompatible. It
31 should be generally envisaged that each and every separate feature disclosed in the
32 present invention is combinable in any appropriate way with any other feature, unless
33 explicitly or clearly incompatible. The word 'comprising' is intended to mean 'including'
34 but not necessarily 'consisting of' or 'composed of'. In other words, the listed steps or
35 options need not be exhaustive. Throughout the description and claims of this
36 specification, the singular encompasses the plural unless the context otherwise
37 requires or indicates, and vice versa. In particular, where the indefinite article is used,

1 the specification is to be understood as contemplating plurality as well as singularity,
2 unless the context requires or indicates otherwise. The examples and embodiments
3 given in the description above are intended to clarify the invention but not to limit the
4 invention. All percentages are weight percentages based upon the total weight of
5 relevant materials unless otherwise indicated. Except in the operating and comparative
6 examples, or where otherwise explicitly indicated, all numbers in this description
7 indicating amounts of material or conditions of reaction, physical properties or materials
8 and/or use are to be understood as modified by the word 'about'. Numerical ranges
9 expressed in the format 'from x to y' are understood to include x and y, unless specified
10 otherwise. When for a specific feature multiple optional ranges are described in the
11 format 'from x to y', it is understood that all ranges combining the different endpoints
12 are also contemplated. It will be understood that all possible combinations of the
13 ranges and sub-ranges described herein are also contemplated. For instance, the
14 range of viscosity of not more than 20% of the largest viscosity value of the set is
15 understood to be particularly preferred to be combined with any one of the preferred
16 ranges of density, and further with any one of the preferred ranges of surface tension.
17 For instance, any one of the preferred ranges of viscosity is understood to be
18 particularly preferred to be combined with any one of the preferred ranges of density,
19 and further with any one of the preferred ranges of surface tension. For instance, any
20 one of the optional ranges of the volume is understood to be particularly preferred to
21 be combined with any one of the optional ranges of the velocity.

22

23 Description of the Figures

24

25 An example embodiment of the present invention will now be illustrated with reference
26 to the following Figures in which:

27

28 Figure 1 is a schematic diagram showing an arrangement of an actuator, printhead
29 nozzle and control circuitry as disclosed herein;

30

31 Figure 2 is an illustration of the arrangement shown in Figure 1, including a plurality of
32 printhead nozzles;

33

34 Figure 3 is a block diagrams of control circuitry for a printhead as disclosed herein;

35

36 Figures 4a, 4b and 4c are graphical representations of actuator control signals for the
37 circuitry described herein;

Figure 5 is a flowchart for a procedure for matching a set of inks.

A monolithic inkjet printhead with which the invention is useful, and its operation, is now described with reference to Figures 1 to 4. Figure 1 is a schematic diagram showing an arrangement of an actuator, printhead nozzle and control circuitry. A droplet ejector assembly 100 comprises a silicon substrate 102 comprising control circuitry 104 on the first surface 106 of the silicon substrate 102. The control circuitry 104 is typically an integrated circuit 104 in the form of a CMOS circuit 104. The person skilled in the art will appreciate that a CMOS circuit comprises both doped regions of the substrate and metallisation layers and interconnections formed on the first surface of the substrate. A plurality of layers shown generally as 112 are formed on the first surface 106 of the silicon substrate 102. Layer 112 is the CMOS metallization layer and comprises metal conductive traces and a passivation insulator such as SiO₂, SiN, SiON. The droplet ejector assembly 100 further comprises a piezoelectric actuator 118 comprising a piezoelectric body 120 which in this example is formed of AlN or ScAlN but may be formed of another suitable piezoelectric material which is processable at a temperature of below 450°C. The piezoelectric actuator 118 forms a diaphragm with layers of materials such as silicon, silicon oxide, silicon nitride or derivatives thereof and has a passivation layer 160 (sometimes referred to as a nozzle defining layer 160) which prevents applied electrical potentials from contacting fluid.

At least one metallisation layer 112 includes interconnects, conducting signals from an external controller via a bond pad 180 to a first portion 105a of the control circuitry 104 and from second and third portions 105b, 150c of the control circuitry 104 to the piezoelectric actuator via electrical interconnects 108, in particular to first electrodes 140 and second electrodes 142 arranged to apply an electrical potential difference across and thereby actuate the piezoelectric body 120. An opening 120a is defined in the piezoelectric body 120 for passage of the electrical interconnect 108 between the second portion 105b of the control circuitry 104 and the second electrode 142.

The piezoelectric actuator 118 and accompanying passivation layer 160 defines a wall of a fluid chamber 122 which receives print agent, such as ink (in the case of an inkjet printer) or another printable fluid (for example in the case of an additive manufacturing printer) through a conduit 124 and which is in communication with a printhead nozzle 126 for ejecting liquid. The piezoelectric actuator 118 and the nozzle defining layer 160 further define a wall of the printhead nozzle 126. The conduit 124 forms at least

1 part of a print agent manifold providing a fluid communication pathway between a print
2 agent inlet (not shown in Figure 1) and the printhead nozzle 126 (as well as further
3 printhead nozzles, not shown in Figure 1), via the chamber 122. The conduit 124 is
4 defined by the silicon substrate 102, the metallisation layer 112 and the nozzle defining
5 layer 160. A protective front surface 170 provides the external surface of the droplet
6 ejector assembly 100, provided to cover and protect the piezoelectric actuator 118, and
7 abutting against a surface 162 of the nozzle defining layer 160. The protective front
8 surface 170 has apertures which define the nozzles 126. The piezoelectric actuator
9 118, chamber 122 and nozzle 126 together form a droplet ejector shown generally as
10 101.

11

12 Typically, the CMOS control circuit comprises patterned regions of doped silicon and
13 metallisation layers. The number of metallisation layers depends on the complexity of
14 the CMOS control circuit but three layers should suffice for many applications.

15

16 Although only one printhead nozzle 126 and piezoelectric actuator 118 is shown in
17 Figure 1 for clarity, it will be understood that a plurality of printhead nozzles 126 and
18 corresponding piezoelectric actuators 118 are provided, including actuators which
19 dispense a plurality of different inks. Each piezoelectric actuator 118 is configured to
20 control ejection of print agent from the respective printhead nozzle 126.

21

22 The droplet ejector of Figure 1 ejects ink compositions through the nozzle. The
23 piezoelectric transducer is in the nozzle defining layer which moves with the nozzle.
24 Thus the surface of the chamber 122 which includes the nozzle moves during
25 actuation. This contrasts with devices in which the surface which includes the nozzle
26 does not move and another surface, e.g. the opposite surface, is actuated. As a result,
27 only a small actuation force is required to displace the ink in the nozzle. The ink is then
28 ejected mainly by inertial force (i.e. inertial ejection) from the nozzle. Herein, ejection
29 by inertial force can also be referred to as inertial ejection or ejection by inertial mode.
30 The ejection of the ink is dictated predominantly by the density and viscosity of the ink
31 - not by compressibility as would be the case if another surface was actuated and the
32 ink in the chamber was displaced as a whole.

33

34 Figure 2 shows an illustration of the arrangement shown in Figure 1, including a
35 plurality of printhead nozzles. With reference to Figure 2 specifically, which shows a
36 printhead 100a having multiple droplet ejectors 101 (individual piezoelectric actuators,
37 fluid chambers and droplet ejection outlets), flexible cable interconnect 138 with a

1 limited number of signal conductors connects an external controller through wires to
2 the printhead 100a that comprises multiple droplet ejectors shown as 101, for ejecting
3 different print agents, for example ink of different colours. The chambers (122a, b, c
4 and d) may comprise ink of different colours. The piezoelectric actuators 118, the
5 control circuitry 104 and the printhead nozzles 126, forming multiple droplet ejectors
6 101, are typically formed from a single CMOS/actuator substrate, though the print
7 agent manifold of each printhead 100a may be at least partly defined by at least one
8 further component provided in fluid communication with the printhead nozzles 126. In
9 these examples, as well as the main portion of CMOS control circuit 104, the CMOS
10 control circuit includes separate circuit elements 104' associated with each droplet
11 ejector, which may for example comprise a latch and an ejector transistor for each
12 piezoelectric actuator.

13
14 Figure 3 is a block diagram of the control circuitry for a printhead assembly. In this
15 example, actuator control is distributed between a machine controller 220 and the
16 control circuitry (e.g., CMOS circuit) 104 within the printhead 100a. They are connected
17 in part by conductors extending through a single or multiple flexible cable interconnects
18 138. Multiple actuators 120 are controlled by the application of potentials to their
19 electrodes 140, 142. The machine controller comprises at least a processor 200, such
20 as a microprocessor or microcontroller which has memory 202 storing relevant data
21 and program code. A wired or wireless electronic interface 204 receives input data
22 from an external device driver. One skilled in the art will appreciate that the machine
23 controller may be distributed between a number of separate components or functional
24 modules, such as one component which converts an image into a pixelated pattern for
25 printing using a dither matrix, for example, and a separate component which converts
26 the pixelated pattern into a print pattern for the different nozzles.

27
28 The machine controller comprises a waveform generator and a voltage amplifier 208
29 which provides a continuous pattern of actuator control pulses (shown in Figure 4) to
30 the printhead through one or more drive signal conductors 210. Although the machine
31 controller is capable of generating a plurality of different waveforms, in the context of
32 the present invention, it is advantageous to generate and use a single waveform for
33 ejecting each type of ink, as this reduces wiring and provides other benefits as
34 described hereinbefore.

35
36 A ground conductor 212 also extends from the machine controller to the droplet ejector
37 assembly 100. (Ground connections within printhead not shown for clarity). The

1 processor 200 generates digital control signals 214 typically as a serial bus, and also
2 transmits clock signals 216 to the printhead which serve to synchronise printing with
3 movements of the printhead. The connector also provides voltage levels associated
4 with the operational voltage of CMOS control electronics.

5
6 Within the printhead 100a, contact pads 136 are connected to the conductors of the
7 flexible connector and signals are routed through patterned metallised layer 112 to the
8 CMOS control circuit 104 and from the CMOS control circuit to the electrodes 140, 142
9 which actuate individual piezoelectric bodies 120 within respective piezoelectric
10 actuators. The control circuit 104 on substrate 102 comprises ejection switch circuit
11 220, including ejection transistors having outputs which are in direct electrical
12 connection with the electrodes 140, 142 (i.e. without a further intervening switching
13 semiconductor junction). The ejection switch circuit switches the actuator control pulse
14 signals and if one of the electrodes remains connected to ground, the ejection switch
15 circuit may be as simple as single transistor per actuator, or a single transistor per
16 electrode to switch the signal applied to that electrode. The ejection switch circuit may
17 be distributed around the substrate with a portion (e.g. a transistor or transistor and
18 latch) proximate each droplet ejector.

19
20 The ejection switch circuit does not carry out power amplification. Instead it switches
21 the actuator control pulses, determining whether each pulse is relayed to the respective
22 actuator or not, for each pulse. Voltage amplification is carried out in the machine
23 controller by amplifier 208.

24
25 The ejection switch circuit is controlled by latch and shift transistors 222, which receive
26 and store digital data from a control circuit 224 which processes received data, for
27 example converting received serial data, storing these in registers 226 and using the
28 received data to determine which actuators are to actuate during each successive
29 actuator firing events. The control circuit 228 also stores trim data used to customise
30 the precise timing of voltage switching for each actuator, which is typically determined
31 during a calibration step on set-up, and may store configuration data 230 which
32 indicates the physical layout of nozzles, security information and or nozzle actuation
33 count history information. The control circuit 224 also receives data from sensors 232,
34 234, 236, some of which are associated with individual actuators, for example nozzle
35 fill levels sensors, and some of which sense parameters relevant to the function of the
36 printhead as a whole, for example temperature sensors.

37

1 Figures 4(a), 4(b) and 4(c) show three possible drive waveforms generated by
2 waveform generator or voltage amplification 206 in alternative embodiments. The x
3 axis is time (in milliseconds) and the y axis is potential per μm thickness of actuator.
4 As the piezoelectric bodies are made of a non-ferro electric material in this example
5 the pulses may be applied in either direction. In Figure 4(a) the signals have a default
6 voltage of 0 and in each pulse are switch to a positive potential and back to zero after
7 a predetermined period of time. In Figure 4(b) the signals have a default voltage of 0
8 and are switched first to a positive potential (to cause the piezoelectric actuator to
9 deform in one direction) and then to a negative potential (to cause the piezoelectric
10 actuator to deform in the opposite direction) before returning to zero. In Figure 4(c) the
11 signals have a default voltage of 200V and are switched to a voltage of -200V (causing
12 the electric fields in the piezoelectric body to reverse in direction) before returning to
13 200V.

14

15 During operation, the processor 200 receives printing data, such as bitmaps, in digital
16 form through interface 204 and processes this data by known means to send a
17 sequence of printing instructions through serial connection 216 to each printhead.
18 These printing instructions may be as detailed as instructions for each printhead as to
19 whether and when to eject a droplet during printing cycles. In one embodiment, the
20 waveform generator generates repeating voltage pulses suitable for application to the
21 electrodes of individual piezoelectric actuators. These are periodic with a time spacing
22 which determines the time between droplet ejection events on the printhead.
23 Alternatively, the voltage amplification, 208, may provide and maintain a single voltage
24 level of multiple voltage levels to the printhead assembly. The ejection transistors
25 within the printhead will switch these voltages according to the CMOS control circuit.

26

27 As the waveform generator or generators are not located on the printhead and is used
28 to drive numerous piezoelectric actuators, it or they can generate a significant amount
29 of heat without causing problems. There are not substantial substrate space limitations
30 so it or they may be relatively complex circuits adapted to carefully control the shape
31 of the waveform, with selected, and optionally variable, slew rates, and the power
32 amplifier may be selected to produce the desired voltage up to the maximum possible
33 current requirement in the event that all actuators which may be actuated
34 simultaneously be actuated together.

35

36 The control circuit 224 on an individual printhead substrate receives the printing
37 instructions through serial connection 216 and processes these (for example

1 converting from serial to parallel instructions). With reference to the clock signals 214,
2 it is determined whether each individual piezoelectric actuator should be actuated to
3 eject a droplet during each printing cycle and this data is loaded into latches 222. At
4 an appropriate time during each printing cycle, the latched data is passed to the
5 ejection switch circuit which thereby either switch the received printing waveform to the
6 electrodes of the respective actuator element, causing it to carry out a droplet ejection
7 cycle, or to not do so in which case both electrodes of the respective actuator element
8 remain connected to ground and the droplet ejector does not carry out a droplet
9 ejection cycle.

10
11 Sensors 232, 234, 236 are monitored during printing. The precise timing of switching
12 the received printing waveform to the electrodes of the respective actuator element can
13 be varied responsive to a measure of temperature using a temperature sensitive
14 CMOS element.

15
16 The shift registers move the droplet fire pattern information through to the latch
17 registers. Thus, the shift registers interface with the serial connection, and move all
18 print data to the latch registers in a given print cycle. The latch registers interface with
19 the ejection registers to initiate a print command.

20
21 In some embodiments, instead of the machine controller including a waveform
22 generator and the waveform being conducted to the printhead and the CMOS control
23 circuit thereon, the CMOS control circuit actuates the piezoelectric actuators, causing
24 droplet ejection, by switching the voltage applied to one or more of the electrodes of
25 each piezoelectric actuator, for example between ground and a fixed voltage, or
26 between multiple fixed voltage levels, one or more of which may be ground. In this
27 case, the flexible connector 138 contains one or more electrical conductors carrying a
28 fixed voltage from the machine controller to the printhead.

29
30 Figure 5 shows a flowchart 500 illustrating a method of matching a plurality of inks for
31 use in the apparatus of Figures 1 through 4. First, the characteristics of the ink droplet
32 (e.g. the size of the ink droplet) are defined 510. The defined characteristics coupled
33 with droplet ejection waveform 510' are used to determine a set of target physical
34 properties of the ink (i.e. viscosity, density and surface tension) 520 (functioning as the
35 physical property criteria). Next, a candidate set of ink compositions (e.g. a candidate
36 set of different ink compositions) can be determined 530. The candidate set can be, for
37 example, a set of inks manufactured with appropriate ingredients at relevant levels,

1 already aiming to achieve the target physical properties. Alternatively, the candidate
2 set can be a random set of inks. After 530, the physical properties (i.e. viscosity, density
3 and surface tension) of the candidate set are determined 540. Typically, those
4 properties can be determined by using the methods described herein, or any suitable
5 and effective methods known to a skilled person. If the properties of the candidate ink
6 set match with each other and match with the target physical properties 550, the
7 candidate set is selected 570. Otherwise, one or more inks (e.g. all the inks) of the
8 candidate set are modified 560 and their physical properties are determined 540 again.
9 The modification can suitably be carried out by adjusting type(s) and/or level(s) of the
10 appropriate ingredients (e.g. surfactants, carriers and rheological modifiers). If after
11 modification, the candidate set still does not meet the matching requirement 550, the
12 set may be modified again 560. In this way, steps 540, 550 and 560 may be suitably
13 repeated one or more times until a set of ink is selected 570. The selected set can be
14 put in use (e.g. be placed in the chambers of the printhead as described herein) and
15 the specification of the set of inks can be used to manufacture corresponding sets of
16 inks which can, where appropriate, be packaged into cartridges. A cartridge may
17 comprise each of the inks in the set.

18

19 Detailed Description of an ink set

20

21 The present invention will be illustrated by the following non-limiting examples.

22 The ingredients in Table 1 may be used in the ink compositions.

23

24 Table 1: Ingredients

Ingredient Name	Function
D.I. water	Carrier
glycerol	Rheological modifier/carrier
Carbon black, copper phthalocyanine (CuPc), diarylide yellows (C.I. Pigment Yellow 13), Quinacridone Magenta	Colourant
Polyacrylic/Polyacrylate homo/co-polymer (e.g. ACRY SOL® RM-5000 and ACRY SOL® RM-825)	Rheological modifier
PEG-based surfactant	Surfactant
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3- one	preservative

1

2 An exemplar set of ink compositions is shown in Table 2.

3

4 Table 2: A set of Ink compositions

Ingredients	C1 (wt%)	C2 (wt%)	C3 (wt%)	C4 (wt%)
D.I. water	To 100%	To 100%	To 100%	To 100%
glycerol	5-20%	5-20%	5-20%	5-20%
Carbon black	1-3%			
CuPc		1-3%		
diarylide yellow			1-3%	
Quinacridone Magenta				1-3%
PEG-based surfactant	0.1-5%	0.1-5%	0.1-5%	0.1-5%
Polyacrylic/Polyacrylate homo/co-polymer	0.1-5%	0.1-5%	0.1-5%	0.1-5%
1,2-benzisothiazol- 3(2H)-one; 1,2-benzisothiazolin-3- one	0.001- 0.05%	0.001- 0.05%	0.001- 0.05%	0.001- 0.05%

5

6 The weight percentages shown above are based on the total weight of an ink
7 composition. Target viscosity, density and surface tension of each ink composition are
8 determined experimentally or theoretically for a target dpi (e.g. 1200). Narrow ranges
9 (e.g. 1% variation) in viscosity, density and surface tension are determined. These
10 ranges depend very much on the implementation and may be anywhere within a
11 viscosity range of 1.5 mPa·s - 20 mPa·s, a density range of 650 kg/m³-1750 kg/m³, and
12 surface tension range of 20 mN/m - 75 mN/m.

13

14 The amount of each ingredient is adjusted in a way that all compositions C1-C4 have
15 a viscosity, density and surface tension within the narrow target ranges. Those values
16 are measured according to the methods described herein. Thus, the values of viscosity,
17 density and surface tension of the compositions C1-C4 are matched in a way that the
18 difference between any two compositions was not more than 1% of the largest
19 corresponding value of the set (i.e. the values were matched in accordance with the
20 present invention). However, because compressibility is not critical, the variation in
21 compressibility between different compositions C1-C4 in the set is allowed to vary and
22 may be greater than 1% or more. The lack of a requirement for close tolerance in

- 1 compressibility facilitates optimisation of the more important viscosity, density and
- 2 surface tension parameters.
- 3

1 Claims

- 2
- 3 1. A monolithic inkjet printhead for ejecting a set of different ink compositions,
4 wherein the printhead comprises at least one substrate and the substrate
5 comprises a plurality of ejectors each comprising: (i) a nozzle, (ii) a chamber
6 for receiving an ink composition of the set, wherein said chamber is in fluid
7 communication with said nozzle, and (iii) a piezoelectric actuator coupled to
8 said nozzle for selectively ejecting said ink composition therefrom, wherein
9 each ejector is configured to eject ink droplets of the different ink compositions
10 with corresponding volume and velocity.
- 11
- 12 2. A monolithic inkjet printhead according to claim 1, wherein each ejector is
13 configured to eject ink compositions which meet a plurality of physical property
14 criteria with corresponding volume and velocity, the physical property criteria
15 including at least corresponding density and viscosity.
- 16
- 17 3. A monolithic inkjet printhead according to claim 1 or claim 2 wherein the
18 configuration of the ejector comprises the actuation waveform of the actuator in
19 use, and the actuation waveform typically comprises the time-varying
20 displacement of and the force applied to ink composition in the chamber during
21 actuation.
- 22
- 23 4. A monolithic inkjet printhead according to any one preceding claim, wherein the
24 substrate comprises a CMOS control circuit, a plurality of layers on the first
25 surface of the substrate, the piezoelectric actuator being formed by one or more
26 said layers and the nozzle comprising a hole through the one or more said
27 layers, such that the piezoelectric actuator displaces the one or more said
28 layers and the nozzle in use to thereby eject ink composition in an inertial mode.
- 29
- 30 5. A monolithic printhead according to any one preceding claim, comprising at
31 least 100 ejectors, preferably at least 1000 ejectors.
- 32
- 33 6. A set of different ink compositions for use in a monolithic inkjet printhead
34 according to any one preceding claim, wherein: (i) the viscosity values of said
35 compositions are matched in a way that the difference between any two
36 compositions is not more than 20% of the largest viscosity value of the set,
37 preferably not more than 10%, more preferably not more than 5%, and most

- 1 preferably not more than 1%; (ii) the density values of said compositions are
2 matched in a way that the difference between any two compositions is not more
3 than 20% of the largest density value of the set, preferably not more than 10%,
4 more preferably not more than 5% and most preferably not more than 1%; and
5 (iii) the surface tension values of said compositions are matched in a way that
6 the difference between any two compositions is not more than 20% of the
7 largest surface tension value of the set, preferably not more than 10%, more
8 preferably not more than 5% and most preferably not more than 1%.
- 9
10
11 7. A set of different ink compositions according to claim 6, wherein the set
12 comprises a plurality of compositions each comprising a different colourant,
13 selected from cyan (C), yellow (Y), magenta (M), key (K), red (R), green (G),
14 blue (B), violet, orange, gold, silver, white and mixtures thereof, preferably
15 selected from CYMK and mixtures thereof, or selected from RGBK and
16 mixtures thereof, and optionally wherein the difference of weight percentages
17 of the colourants comprised in at least two compositions of the set or any two
18 compositions of the set is not more than 5, or not more than 2, or not more than
19 1, or not more than 0.1 and any weight percentage is based on the total weight
20 of a respective ink composition.
- 21
22 8. A set of different ink compositions according to claim 7, wherein the set
23 comprises a first composition comprising a cyan (C) or red (R) colourant, a
24 second composition comprising a yellow (Y) or green (G) colourant, a third
25 composition comprising a magenta (M) or blue (B) colourant and a fourth
26 composition comprising a key (K) colourant.
- 27
28 9. A set of different ink compositions according to any one of claims 6 to 8, wherein
29 at least one composition of the set or each composition of the set comprises a
30 rheological modifier, and/or a surfactant, and/or a carrier, and optionally
31 wherein the difference of weight percentages of the rheological modifiers,
32 and/or the surfactants, and/or the carriers comprised in at least two
33 compositions of the set or any two compositions of the set is not more than 20,
34 or not more than 10, or not more than 5, or not more than 1, and any weight
35 percentage is based on the total weight of a respective ink composition.
- 36
37 10. A set of different ink compositions according to claim 9, wherein at least two
38 compositions of the set or any two compositions of the set comprise rheological

- 1 modifiers different from each other, and/or surfactants different from each other,
2 and/or carriers different from each other, and optionally wherein the difference
3 of weight percentages of the rheological modifiers, and/or the surfactants,
4 and/or the carriers comprised in at least two compositions or any two
5 compositions of the set is at least 0.1, or at least 1, or at least 5, or at least 10,
6 and any weight percentage is based on the total weight of a respective ink
7 composition.
8
- 9 11. A printing apparatus comprising a monolithic printhead according to any one of
10 claims 1 to 5, a signal generator configured to generate a driving signal having
11 a repeating waveform, and a control circuitry configured to relay the driving
12 signal to the actuators through switches and to control the switches to
13 selectively apply the driving signal to individual actuators to thereby eject ink
14 droplets of the different ink compositions with corresponding volume and
15 velocity.
16
- 17 12. A printing apparatus according to claim 11, further comprising a set of ink
18 compositions according to any one of claims 6 to 10, wherein the compositions
19 are received or receivable in the chambers.
20
- 21 13. A method of printing comprising the steps of: (i) providing a printing apparatus
22 according to claim 11 or claim 12; and (ii) operating the control circuitry to eject
23 at least two ink compositions of the set according to any one of claims 6 to 10
24 from at least two of the plurality of nozzles of the plurality of the printhead
25 ejectors, whereby ink droplets of the at least two different ink compositions are
26 ejected from the at least two of the plurality of nozzles with corresponding
27 volume and velocity.
28
- 29 14. A method of making a set of different ink compositions according to any one of
30 claims 6 to 10, comprising the steps of: (i) making at least two ink compositions;
31 (ii) determining whether the viscosity, density and surface tension values of the
32 at least two ink compositions are such that the set of the at least two ink
33 compositions is a set of different ink compositions according to any one of
34 claims 6 to 10; and (iii) if this is not the case, modifying at least one of the at
35 least two ink compositions one or more times until the set is a set of different
36 ink compositions according to any one of claims 6 to 10.
37

- 1 15. A method of selecting a set of different ink compositions according to any one
2 of claims 6 to 10, comprising the steps of: (i) defining at least one characteristic
3 of an ejected ink droplet; (ii) using the at least one defined characteristic to
4 determine target values of viscosity, density and surface tension of an ink
5 composition; and (iii) selecting at least two ink compositions with reference to
6 the target values as described in steps (ii), wherein the values of the at least
7 two ink compositions are such that the set of the at least two ink compositions
8 is a set of different ink compositions according to any one of claims 6 to 10.
9
- 10 16. A set of different ink compositions according to any one of claims 6 to 10,
11 wherein: (i) the viscosity values of said compositions are matched in a way that
12 the difference between any two compositions is not more than 10% of the
13 largest viscosity value of the set, preferably not more than 5%, and more
14 preferably not more than 1%; (ii) the density values of said compositions are
15 matched in a way that the difference between any two compositions is not more
16 than 10% of the largest density value of the set, preferably not more than 5%
17 and more preferably not more than 1%; and (iii) the surface tension values of
18 said compositions are matched in a way that the difference between any two
19 compositions is not more than 10% of the largest surface tension value of the
20 set, preferably not more than 5% and more preferably not more than 1%.
21
- 22 17. A set of different ink compositions according to claim 16, wherein: (i) the
23 viscosity values of said compositions are matched in a way that the difference
24 between any two compositions is not more than 5% of the largest viscosity
25 value of the set, preferably not more than 1%; (ii) the density values of said
26 compositions are matched in a way that the difference between any two
27 compositions is not more than 5% of the largest density value of the set,
28 preferably not more than 1%; and (iii) the surface tension values of said
29 compositions are matched in a way that the difference between any two
30 compositions is not more than 5% of the largest surface tension value of the
31 set, preferably not more than 1%.
32
- 33 18. A set of different ink compositions according to any one of claims 6 to 10, 16
34 and 17, wherein the difference of compressibility (k) of two ink compositions of
35 the set, or of any two ink compositions of the set, is at least 1% of the largest
36 compressibility value of the set, or at least 5%, or at least 10%, or at least 20%,
37 or at least 30%, or at least 40% or at least 50%.

- 1 19. A set of different ink compositions according to claim 18, wherein the difference
2 of compressibility (k) of the two ink compositions of the set, or of any two ink
3 compositions of the set, is at least 5% or 10% of the largest compressibility
4 value of the set.
5
- 6 20. A printing apparatus comprising a monolithic printhead according to any one of
7 claims 1 to 5, and a set of different ink compositions according to any one of
8 claims 6 to 10 and 16 to 19, wherein the compositions are received or
9 receivable in the chambers.
10
- 11 21. A printing apparatus according to claim 20, wherein the set of different ink
12 compositions is according to any one of claims 17 to 19.
13
- 14 22. A printing apparatus according to claim 20 or claim 21, further comprising a
15 signal generator configured to generate a driving signal having a repeating
16 waveform, and a control circuitry configured to relay the driving signal to the
17 actuators through switches and to control the switches to selectively apply the
18 driving signal to individual actuators to thereby eject ink droplets of the different
19 ink compositions with corresponding volume and velocity.
20
- 21 23. A printing apparatus according to claim 22, wherein the set of different ink
22 compositions is according to any one of claims 17 to 19.
23
- 24 24. A method of printing, comprising: providing a printing apparatus according to
25 claim 22 or claim 23, and operating the control circuitry to eject at least two ink
26 compositions of the set of different ink compositions from at least two of the
27 plurality of nozzles of the plurality of the printhead ejectors, whereby ink
28 droplets of the at least two different ink compositions are ejected from the at
29 least two of the plurality of nozzles with corresponding volume and velocity.
30
- 31 25. A method of making a set of different ink compositions for use in a printing
32 apparatus according to any one of claims 20 to 23, comprising: making at least
33 two ink compositions; determining whether the viscosity, density and surface
34 tension values of the at least two ink compositions are such that the at least two
35 ink compositions are the set of different ink compositions; and (iii) if this is not
36 the case, modifying at least one of the at least two ink compositions one or more

- 1 times until the at least two ink compositions are the set of different ink
2 compositions.
3
- 4 26. A method of selecting a set of different ink compositions for use in a printing
5 apparatus according to any one of claims 20 to 23, comprising: defining at least
6 one characteristic of an ejected ink droplet; using the at least one defined
7 characteristic to determine target values of viscosity, density and surface
8 tension of an ink composition; and selecting at least two ink compositions with
9 reference to the target values, wherein the values of the at least two ink
10 compositions are such that the at least two ink compositions are the set of
11 different ink compositions.
12
- 13 27. A method of manufacturing a printing apparatus according to any one of claims
14 11, 12 and 20 to 23, comprising: forming control circuitry in a substrate; forming
15 a plurality of piezoelectric actuators each in electrical communication with the
16 control circuitry; forming a plurality of nozzles, each coupled to a respective one
17 of the plurality of piezoelectric actuators; and forming a plurality of chambers
18 each in fluid communication with a respective one of the plurality of nozzles.
19
- 20 28. A method of manufacturing a printing apparatus according to claim 27, further
21 comprising the method of making a set of different ink compositions according
22 to claim 14 or claim 25.
23
- 24 29. A method according to claim 28, further comprising receiving the set of different
25 ink compositions each in a respective one of the plurality of the chambers.
26
27
28
29
30