

CLAIMS

1. A substrate transport apparatus comprising:
a frame;
a drive section connected to the frame; and
an articulated arm having at least one articulated arm link operably connected to the drive section so that the articulated arm rotates, about a pivot axis, relative to the frame and extends and retracts relative to the pivot axis;
wherein the articulated arm has an end effector pivotally mounted to the at least one articulated arm link forming a joint between the end effector and the at least one articulated arm link with an arm joint pivot axis disposed so that the end effector rotates relative to the at least one articulated arm link about the arm joint pivot axis, and wherein the articulated arm has a drive band transmission with drive and driven pulleys where the driven pulley is connected to the articulated wrist, wherein the at least one band is wrapped around at least one of the connected pulleys so the at least one band is overwrapped relative to itself so the transmission is capable of generating rotation of the end effector well in excess of 180 Deg in either direction.
2. The substrate transport apparatus of claim 1, wherein the rotation of the end effector between a maximum extension stroke and a maximum retraction stroke is at least about 300°.

3. The substrate transport apparatus of claim 1, wherein the at least one band is overwrapped relative to itself.

4. The substrate processing apparatus of claim 3, wherein the at least one band is overwrapped so that the band wrap spirals over itself on the pulley.

5. The substrate processing apparatus of claim 3, wherein the at least one band is overwrapped so that the band wrap laps over itself.

6. The substrate processing apparatus of claim 3, wherein the at least one band is overwrapped so that the band wrap spirals alongside itself with the band being wrapped having coil edges juxtaposed along a pulley axis.

7. The substrate transport apparatus of claim 1, wherein at least one pulley of the connected pulleys is an idler pulley coupled to the end effector so that idler pulley rotation rotates the end effector about the joint pivot axis.

8. The substrate transport apparatus of claim 7, wherein the at least one band is overwrapped relative to itself around the idler pulley.

9. The substrate transport apparatus of claim 7, wherein the idler pulley is non-circular pulley.

10. The substrate transport apparatus of claim 7, wherein the idler pulley has a band seating surface with a non-circular radial periphery on which the at least one band seats as the band is wound and dispensed from the idler pulley.

11. The substrate transport apparatus of claim 7, wherein another of the at least one pulley of the connected pulleys is a drive pulley, where the drive pulley is a non-circular pulley.

12. The substrate transport apparatus of claim 11, wherein the idler pulley and the drive pulley have pulley profiles that engage respective opposing bands winding and unwinding so as to maintain a substantially constant reduction ratio between the idler pulley and the drive pulley in each rotation direction throughout the end effector extension and retraction strokes.

13. The substrate transport apparatus of claim 1, wherein the end effector has a substrate holding station thereon.

14. The substrate transport apparatus of claim 1, wherein the end effector has more than one substrate holding stations, at least two of the more than one substrate holding stations being on opposite ends of the end effector.

15. The substrate transport apparatus of claim 1, wherein the end effector has more than one end effectors, each separately connected to a respective idler pulley for independent rotation about the joint pivot axis with respect to each other.

16. A substrate transport apparatus comprising:
a frame;
a drive section connected to the frame; and
an articulated arm having at least one articulated arm link operably connected to the drive section so that the articulated arm rotates, about a pivot axis, relative to the frame and extends and retracts relative to the pivot axis;
wherein the articulated arm has an end effector pivotally mounted to the at least one articulated arm link forming a joint between the end effector and the at least one articulated arm link with an arm joint pivot axis disposed so that the end effector rotates relative to the at least one articulated arm link about the arm joint pivot axis, and wherein the articulated arm has a drive band transmission, with pulleys and dual opposing bands connecting the pulleys, that extends and retracts the articulated arm through an arm motion stroke extending or retracting the articulated arm and moving the end effector through a corresponding end effector stroke; and
wherein the dual opposing bands have a winding geometry on at least one of the pulleys that determines rotation of the end effector about the joint pivot axis that provides at least substantially 300° end effector rotation from end to end of the end effector stroke.
17. The substrate transport apparatus of claim 16 wherein the winding geometry provides at least substantially 145° end

effector rotation from midstroke to either end of the end effector stroke.

18. The substrate transport apparatus of claim 16, wherein the winding geometry effects asymmetric winding and unwinding rates of respective opposing bands for common rotation of the at least one of the pulleys.

19. The substrate transport apparatus of claim 18, wherein another pulley of the at least one of the pulleys connected to each other by the opposing bands is configured with a compensator arranged to compensate for the asymmetric winding and unwinding of the respective opposing bands so as to maintain substantially constant tension on each band of the opposing bands throughout the end effector stroke.

20. The substrate transport apparatus of claim 19, wherein the compensator has a geometry that generates, for a common rotation of the another pulley, asymmetric unwinding rates and winding rates of the respective opposing bands on the another pulley commensurate with asymmetric winding rates and unwinding rates of the respective opposing bands on the at least one of the pulleys.

21. The substrate transport apparatus of claim 19, wherein the another pulley has respective non-circular pulley profile with a cam lobe for each of the respective opposing bands, the

respective cam lobes of the respective non-circular profiles form the compensator.

22. The substrate transport apparatus of claim 21, wherein the respective cam lobes of the respective non-circular pulley profiles are disposed on the pulley periphery out of phase by a degree that defines the compensator geometry.

23. The substrate transport apparatus of claim 19, wherein the at least one of the pulleys is an idler pulley, and the another pulley is a drive pulley.

24. The substrate transport apparatus of claim 23, wherein the idler pulley and the drive pulley have pulley profiles that engage the respective opposing bands winding and unwinding so as to maintain a substantially constant reduction ratio between the idler pulley and the drive pulley in each rotation direction throughout the end effector stroke.

25. The substrate transport apparatus of claim 23, wherein the idler pulley has a band seating surface with a non-circular radial periphery on which the at least one band seats as the band is wound and dispensed from the idler pulley.

26. The substrate transport apparatus of claim 25, wherein another of the at least one pulley of the connected pulleys is a drive pulley, where the drive pulley is a non-circular pulley.

27. The substrate transport apparatus of claim 16, wherein each of the opposing bands is overwrapped relative to itself.

28. The substrate processing apparatus of claim 27, wherein each of the opposing bands is overwrapped so that the band wrap spirals over itself on the pulley.

29. The substrate processing apparatus of claim 27, wherein each of the opposing bands is overwrapped so that the band wrap laps over itself.

30. The substrate processing apparatus of claim 27, wherein each of the opposing bands is overwrapped so that the band wrap spirals alongside itself with the band being wrapped having coil edges juxtaposed along a pulley axis.

31. The substrate transport apparatus of claim 16, wherein the at least one of the pulleys is an idler pulley coupled to the end effector so that idler pulley rotation rotates the end effector about the joint pivot axis.

32. The substrate transport apparatus of claim 31, wherein each of the opposing bands is overwrapped relative to itself around the idler pulley.

33. A method comprising:
providing a substrate transport apparatus, where the substrate transport apparatus includes

a frame;

a drive section connected to the frame;

an articulated arm having at least one articulated arm link operably connected to the drive section so that the articulated arm rotates, about a pivot axis, relative to the frame and extends and retracts relative to the pivot axis; and

an end effector pivotally mounted to the at least one articulated arm link forming a joint between the end effector and the at least one articulated arm link with an arm joint pivot axis disposed so that the end effector rotates relative to the at least one articulated arm link about the arm joint pivot axis;

moving the end effector respectively through an extension stroke and a retraction stroke with a drive band transmission with pulleys and at least one band connecting the pulleys that extends and retracts the articulated arm; and

wherein the at least one band is wrapped around at least one of the connected pulleys so the at least one band is overwrapped relative to itself so the transmission generates rotation of the end effector, relative to the at least one articulated arm link, about the joint pivot axis that is at least about 145° from an end effector midstroke rotation position of the end effector to a maximum stroke rotation position of the end effector.

34. The method of claim 33, wherein the rotation of the end effector between a maximum extension stroke and a maximum retraction stroke is at least about 300°.

35. The method of claim 33, wherein the at least one band is overwrapped relative to itself.

36. The method of claim 35, wherein the at least one band is overwrapped so that the band wrap spirals over itself on the pulley.

37. The method of claim 35, wherein the at least one band is overwrapped so that the band wrap laps over itself.

38. The method of claim 35, wherein the at least one band is overwrapped so that the band wrap spirals alongside itself with the band being wrapped having coil edges juxtaposed along a pulley axis.

39. The method of claim 33, wherein at least one pulley of the connected pulleys is an idler pulley coupled to the end effector so that idler pulley rotation rotates the end effector about the joint pivot axis.

40. The method of claim 39, wherein the at least one band is overwrapped relative to itself around the idler pulley.

41. The method of claim 39, wherein the idler pulley is non-circular pulley.

42. The method of claim 39, wherein the idler pulley has a band seating surface with a non-circular radial periphery on which

the at least one band seats as the band is wound and dispensed from the idler pulley.

43. The method of claim 39, wherein another of the at least one pulley of the connected pulleys is a drive pulley, where the drive pulley is a non-circular pulley.

44. The method of claim 43, wherein the idler pulley and the drive pulley have pulley profiles that engage respective opposing bands winding and unwinding so as to maintain a substantially constant reduction ratio between the idler pulley and the drive pulley in each rotation direction throughout the end effector extension and retraction strokes.

45. The method of claim 33, wherein the end effector has a substrate holding station thereon.

46. The method of claim 33, wherein the end effector has more than one substrate holding stations, at least two of the more than one substrate holding stations being on opposite ends of the end effector.

47. The method of claim 33, wherein the end effector has more than one end effectors, each separately connected to a respective idler pulley for independent rotation about the joint pivot axis with respect to each other.

48. A method comprising:

providing a substrate transport apparatus, where the substrate transport apparatus includes

- a frame;

- a drive section connected to the frame;

- an articulated arm having at least one articulated arm link operably connected to the drive section so that the articulated arm rotates, about a pivot axis, relative to the frame and extends and retracts relative to the pivot axis; and

- an end effector pivotally mounted to the at least one articulated arm link forming a joint between the end effector and the at least one articulated arm link with an arm joint pivot axis disposed so that the end effector rotates relative to the at least one articulated arm link about the arm joint pivot axis; and

moving the end effector through a corresponding end effector stroke, where the articulated arm has a drive band transmission, with pulleys and dual opposing bands connecting the pulleys, that extends and retracts the articulated arm through an arm motion stroke extending or retracting the articulated arm;

wherein the dual opposing bands have a winding geometry on at least one of the pulleys that determines rotation of the end effector about the joint pivot axis that provides at least substantially 300° end effector rotation from end to end of the end effector stroke.

49. The method of claim 48, wherein the winding geometry provides at least substantially 145° end effector rotation from midstroke to either end of the end effector stroke.

50. The method of claim 48, wherein the winding geometry effects asymmetric winding and unwinding rates of respective opposing bands for common rotation of the at least one of the pulleys.

51. The method of claim 50, further comprising compensating for, with a compensator or another pulley, the asymmetric winding and unwinding of the respective opposing bands so as to maintain substantially constant tension on each band of the opposing bands throughout the end effector stroke.

52. The method of claim 51, further comprising generating, with a geometry of the compensator, for a common rotation of the another pulley, asymmetric unwinding rates and winding rates of the respective opposing bands on the another pulley commensurate with asymmetric winding rates and unwinding rates of the respective opposing bands on the at least one of the pulleys.

53. The method of claim 51, wherein the another pulley has respective non-circular pulley profile with a cam lobe for each of the respective opposing bands, the respective cam lobes of the respective non-circular profiles form the compensator.

54. The method of claim 53, wherein the respective cam lobes of the respective non-circular pulley profiles are disposed on the pulley periphery out of phase by a degree that defines the compensator geometry.

55. The method of claim 51, wherein the at least one of the pulleys is an idler pulley, and the another pulley is a drive pulley.

56. The method of claim 55, wherein the idler pulley and the drive pulley have pulley profiles that engage the respective opposing bands winding and unwinding so as to maintain a substantially constant reduction ratio between the idler pulley and the drive pulley in each rotation direction throughout the end effector stroke.

57. The method of claim 55, wherein the idler pulley has a band seating surface with a non-circular radial periphery on which the at least one band seats as the band is wound and dispensed from the idler pulley.

58. The method of claim 57, wherein another of the at least one pulley of the connected pulleys is a drive pulley, where the drive pulley is a non-circular pulley.

59. The method of claim 48, wherein each of the opposing bands is overwrapped relative to itself.

60. The method of claim 59, wherein each of the opposing bands is overwrapped so that the band wrap spirals over itself on the pulley.

61. The method of claim 59, wherein each of the opposing bands is overwrapped so that the band wrap laps over itself.

62. The method of claim 59, wherein each of the opposing bands is overwrapped so that the band wrap spirals alongside itself with the band being wrapped having coil edges juxtaposed along a pulley axis.

63. The method of claim 48, wherein the at least one of the pulleys is an idler pulley coupled to the end effector so that idler pulley rotation rotates the end effector about the joint pivot axis.

64. The method of claim 63, wherein each of the opposing bands is overwrapped relative to itself around the idler pulley.