

- 1 -

5

**WELL SCREEN INFLOW CONTROL DEVICE WITH CHECK VALVE
FLOW CONTROLS**

TECHNICAL FIELD

10 The present invention relates generally to equipment
utilized and operations performed in conjunction with a
subterranean well and, in an embodiment described herein,
more particularly provides a well screen inflow control
device with check valve flow controls.

15

BACKGROUND

It is desirable to exclude, or at least substantially
reduce, the production of water from a well intended for
hydrocarbon production. For example, it is very desirable
for the fluid which is produced from the well to have a
20 relatively high proportion of hydrocarbons, and a relatively
low proportion of water. In some cases, it is also
desirable to restrict the production of hydrocarbon gas from
a well.

In addition, where fluid is produced from a long
25 interval of a formation penetrated by a wellbore, it is
known that balancing the production of fluid along the
interval can lead to reduced water and gas coning, and more
controlled conformance, thereby increasing the proportion
and overall quantity of oil produced from the interval.
30 Inflow control devices (ICD's) have been used in conjunction

- 2 -

with well screens in the past to restrict flow of produced fluid through the screens for this purpose of balancing production along an interval. For example, in a long horizontal wellbore, fluid flow near a heel of the wellbore
5 may be more restricted as compared to fluid flow near a toe of the wellbore, to thereby balance production along the wellbore.

However, further advancements are needed in the art of reducing production of undesired fluids from hydrocarbon
10 wells, in part due to the difficulties and costs associated with separating the undesired fluids from the desired fluids at the surface and then disposing of the undesired fluids.

SUMMARY

In the present specification, well screen inflow
15 control devices are provided which solve at least one problem in the art. One example is described below in which a velocity check valve is used to reduce production of water. Another example is described below in which fluid loss is prevented. Yet another example is described in
20 which restriction to flow through a well screen assembly can be substantially decreased, if desired.

In one aspect, a well screen assembly is provided which includes a filter portion for filtering fluid and a flow control device which varies a resistance to flow of the
25 fluid in response to a change in velocity of the fluid. The flow control device may increase the resistance to flow as a density of the fluid increases. The flow control device may decrease a flow area in response to an increase in the velocity of the fluid. The flow control device may increase
30 the resistance to flow as the velocity of the fluid increases.

- 3 -

In another aspect, a well screen assembly is provided which includes a filter portion for filtering fluid and a flow resistance device which decreases a resistance to flow of the fluid in response to a predetermined stimulus applied from a remote location. The stimulus may be a pressure variation. The stimulus may be an increase in a pressure differential from an interior to an exterior of the screen assembly.

In yet another aspect, a well screen assembly is provided which includes a filter portion for filtering fluid and a valve including an actuator having a piston which displaces in response to a pressure differential to thereby selectively permit and prevent flow of the fluid through the valve. The well screen assembly may also include a flow restrictor and/or an excluder device which increasingly blocks flow of an undesired portion (such as gas and/or water) of the fluid as the undesired portion increases.

These and other features, advantages, benefits and objects will become apparent to one of ordinary skill in the art upon careful consideration of the detailed description of representative embodiments of the invention hereinbelow and the accompanying drawings, in which similar elements are indicated in the various figures using the same reference numbers.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic partially cross-sectional view of a well system embodying principles of the present invention;

FIG. 2 is an enlarged scale schematic cross-sectional view through a screen assembly in the well system of FIG. 1, the screen assembly embodying principles of the invention; and

- 4 -

FIGS. 3-16 are schematic cross-sectional views of alternate constructions of the screen assembly embodying principles of the invention.

DETAILED DESCRIPTION

5 It is to be understood that the various embodiments of the present invention described herein may be utilized in various orientations, such as inclined, inverted, horizontal, vertical, etc., and in various configurations, without departing from the principles of the present
10 invention. The embodiments are described merely as examples of useful applications of the principles of the invention, which is not limited to any specific details of these embodiments.

 In the following description of the representative
15 embodiments of the invention, directional terms, such as "above", "below", "upper", "lower", etc., are used for convenience in referring to the accompanying drawings.

 Representatively illustrated in FIG. 1 is a well system
10 which embodies principles of the present invention. A tubular string 12, such as a production tubing string, is
20 installed in a wellbore 14 having a substantially horizontal section. Multiple well screen assemblies 16 are interconnected in the tubular string 12 and positioned in the horizontal section of the wellbore 14.

25 The wellbore 14 is depicted in FIG. 1 as being uncased or open hole in the horizontal section. Packers 18 may be used between various ones of the screen assemblies 16 if desired, for example, to isolate different zones or intervals along the wellbore 14 from each other.

30 Note that it is not necessary in keeping with the principles of the invention for screen assemblies to be

- 5 -

positioned in a horizontal wellbore portion, for the wellbore to be uncased, for packers to be used between screen assemblies, or for any of the other details of the well system 10 to exist. The well system 10 is just one
5 example of many different uses for the inventive concepts described herein.

Referring additionally now to FIG. 2, a schematic partially cross-sectional view of one of the well screen assemblies 16 is representatively illustrated at an enlarged
10 scale. This screen assembly 16 is one of several different examples of screen assemblies described below in alternate configurations.

In this example, the screen assembly 16 includes a filter portion 20 and a flow control portion 22. The filter
15 portion 20 is used to filter sand and/or other debris from fluid 24 which flows generally from an exterior to an interior of the screen assembly 16.

During production operations, the fluid 24 would typically flow from the wellbore 14 external to the screen
20 assembly 16, through the filter portion 20 and flow control portion 22, and then into an internal flow passage 26 which extends longitudinally through the screen assembly as part of the tubular string 12. The fluid 24 can then be produced through the tubular string 12 to the surface.

25 However, it is not necessary for the fluid 24 to always flow inwardly through the filter portion 20 and/or the flow control portion 22. For example, at times during completion operations the fluid 24 may flow in the opposite direction. Some examples of screen assemblies which operate to prevent
30 such reverse direction flow of the fluid 24, in order to prevent loss of the fluid into, or damage to, a formation surrounding the wellbore, are described below.

- 6 -

It is also not necessary for the fluid 24 to flow first through the filter portion 20 and then through the flow control portion 22. For example, the flow control portion 22 could be upstream of the filter portion 20, if desired.

5 The filter portion 20 is depicted in FIG. 2 as being of the type known as "wire-wrapped," since it is made up of a wire closely wrapped helically about a base pipe 28, with a spacing between the wire wraps being chosen to keep sand, etc. from passing between the wire wraps. Other types of
10 filter portions (such as sintered, mesh, pre-packed, expandable, slotted, perforated, etc.) may be used, if desired.

The flow control portion 22 performs several functions. The flow control portion 22 is an ICD which functions to
15 restrict flow therethrough, for example, to balance production of fluid along an interval. Furthermore, the flow control portion 22 functions to prevent fluid loss due to reverse flow of the fluid 24 from the passage 26 to the wellbore 14.

20 Several different constructions of the flow control device 30 are described below in various different configurations of the screen assembly 16. It should be understood that any of the flow control devices 30 described herein may be used in any of the screen assemblies described
25 herein, without departing from the principles of the invention.

A flow restrictor 40 is connected upstream of the flow control device 30, so that the fluid 24 flows through the flow restrictor before flowing through the device and into
30 the flow passage 26. Different arrangements of these elements may be used, if desired. For example, the flow

- 7 -

restrictor 40 could be connected downstream of the flow control device 30.

In the example of FIG. 2, the flow restrictor 40 is an orifice or nozzle, but other types of flow restrictors may be used, if desired. For example, an annular passage, a helical tube or other type of flow restrictor could be used. The flow restrictor 40 could be in different positions, for example, an opening 42 in the base pipe 28 for admitting the fluid 24 into the passage 26 could be a flow restricting orifice.

The flow restrictor 40 is preferably used to balance production along an interval as discussed above. The resistance to flow through the flow restrictor 40 may be different for each of the screen assemblies 16 along an interval.

Although only one set of the flow control device 30 and flow restrictor 40 are depicted in FIG. 2 as part of the flow control portion 22, it should be understood that the flow control portion could include any number of flow control devices and any number of flow restrictors in keeping with the principles of the invention.

In this construction, the flow control device 30 includes a check valve in the form of a rod 50 reciprocally received within a generally tubular housing 52, and a seat 54 formed in a bulkhead 56 through which the fluid 24 flows during production operations.

The flow control device 30 in this configuration of the screen assembly 16 prevents loss of fluid into the formation surrounding the wellbore 14. As depicted in FIG. 2, the fluid 24 is flowing into the filter portion 20, and then through the flow control portion 22 into the flow passage 26 for production to the surface.

- 8 -

However, if the direction of flow should reverse (such as during completion operations, etc.), the drag on the rod 50 due to the fluid flowing through a small annulus 58 between the rod and the housing 52 will cause the rod to
5 displace into engagement with the seat 54, thereby preventing this reverse flow of fluid from the flow passage 26 to the exterior of the screen assembly 16.

Due to sealing engagement between the rod 50 and the seat 54, as long as pressure in the flow passage 26 exceeds
10 pressure external to the screen assembly 16, the flow control device 30 will remain closed. To commence production, pressure in the flow passage 26 can be reduced relative to pressure external to the screen assembly 16 (for example, by circulating lighter weight fluid into the
15 tubular string 12, operating a pump, etc.) to thereby open the flow control device 30 by displacing the rod 50 away from the seat 54.

The rod 50 and housing 52 also function as a flow restrictor, in that a pressure drop will be generated as the
20 fluid 24 flows through the annulus 58 between the rod and housing. This pressure drop is a function of the flow rate, annular area, density and viscosity of the fluid 24. Similarly, fluid loss from the tubular string 12 to the reservoir will produce a pressure drop through the annulus
25 58, thereby displacing the rod 50 into engagement with the seat 54. Thus, the pressure drop through the annulus 58 will hold the rod 50 away from the seat 54 and function as an ICD during production flow, and the pressure drop will cause the rod to engage the seat and prevent fluid loss in
30 the event of reverse flow.

Referring additionally now to FIG. 3, another alternate construction of the screen assembly 16 is representatively

- 9 -

illustrated. The screen assembly 16 includes the flow control portion 22 which functions as an ICD and also prevents fluid loss due to reverse flow of the fluid 24. The ICD has two flow restricting devices -- the flow
5 restrictor 40 and the annulus 58 between the rod 50 and the housing 52.

The screen assembly 16 of FIG. 3 is similar in many respects to the screen assembly of FIG. 2, in that the flow control device 30 includes the rod 50, housing 52 and seat
10 54 for preventing reverse flow and loss of fluid to the formation surrounding the wellbore 14. However, the screen assembly 16 of FIG. 3 also includes an alternate bypass flowpath 60 which can be opened if desired to bypass the flow control portion 22, or at least provide a decreased
15 resistance to flow between the filter portion 20 and the flow passage 26.

If it is desired to open the bypass flowpath 60, pressure in the flow passage 26 may be increased relative to pressure external to the screen assembly 16 (for example, by
20 applying increased pressure to the interior of the tubular string 12 from a remote location, etc.), in order to displace the rod 50 into engagement with the seat 54 (due to the pressure drop through the annulus 58) and burst a rupture disk 62. The flowpath 60 and rupture disk 62 thus
25 comprise a flow resistance device 59 for decreasing a resistance to flow of the fluid 24 in response to a predetermined stimulus applied from a remote location.

It will be appreciated that, after the rupture disk 62 has been ruptured to open the flowpath 60, the resistance to
30 flow between the filter portion 20 and the flow passage 26 will be substantially decreased as compared to the resistance to flow through the flow restrictor 40 and the

- 10 -

annulus 58 between the rod 50 and the housing 52. Thus, the screen assembly 16 of FIG. 3 provides fluid loss prevention (for example, during completion operations, etc.), but also enables increased flow through the filter portion 20 when
5 desired.

Referring additionally now to FIG. 4, another alternate construction of the screen assembly 16 is representatively illustrated. The screen assembly 16 includes the flow control portion 22 which functions as an ICD and also
10 prevents reverse flow of the fluid 24. The ICD has two flow restricting devices -- the flow restrictor 40 and the annulus 58 between the rod 50 and the housing 52.

In this embodiment of the screen assembly 16, the flow control device 30 is used in addition to at least one other
15 flow restrictor 40 (not visible in FIG. 4) which provides for fluid communication between the filter portion 20 and the flow passage 26. For example, there could be one or more flow restrictors 40 provided in the bulkhead 56 as depicted in FIG. 3.

20 The flow control device 30 depicted in FIG. 4 permits a restriction to the flow of the fluid 24 to be decreased when desired, by opening one or more bypass flowpaths 64 which are initially blocked by respective one or more plugs 66. This result is accomplished by increasing pressure in the
25 flow passage 26 relative to pressure on the exterior of the screen assembly 16, to thereby cause the rod 50 to displace toward the seat 54 adjacent the flow restrictor 40 (see FIG. 3).

Once the rod 50 has engaged the seat 54 adjacent the
30 flow restrictor 40, a pressure differential across the plug 66 will cause the plug to dislodge from the flowpath 64. A sealing surface 70 on the rod 50 will then engage the seat

- 11 -

54 to close off the bypass flowpath 64, so that any other flow control devices 30 included in the flow control portion 22 can be similarly operated to open additional bypass flowpaths. The flowpath 64 and plug 66 comprise a flow resistance device 63 for decreasing a resistance to flow of the fluid 24 in response to a predetermined stimulus applied from a remote location.

Thus, when pressure in the flow passage 26 is increased, those rods 50 which are associated with flow restrictors 40 will displace into engagement with the seats 54 adjacent the flow restrictors 40, thereby enabling a pressure differential to be applied across the plugs 66. As each plug 66 is dislodged from its respective flowpath 64, the associated rod 50 will displace into engagement with its seat to close off the flowpath. This process will occur in each screen assembly 16 along the tubular string 12.

Production can be resumed by reducing the pressure in the flow passage 26 relative to pressure external to the screen assembly 16 to thereby displace the rods 50 away from the seats 54 and allow flow of the fluid 24 through the bypass flowpaths 64. It will be appreciated that, by opening one or more of the bypass flowpaths 64 in the flow control portion 22, restriction to flow of the fluid 24 through the flow control portion 22 can be substantially decreased.

If further reduction in the restriction to flow of the fluid 24 is desired, the bypass flowpath 60 and rupture disk 62 can be provided, as in the embodiment of FIG. 3.

Referring additionally now to FIG. 5, another alternate construction of the screen assembly 16 is representatively illustrated. The screen assembly 16 includes the flow control portion 22 which functions as an ICD and also

- 12 -

prevents reverse flow of the fluid 24. The ICD has two flow restricting devices -- the flow restrictor 40 and the annulus 58 between the rod 50 and the housing 52.

This example functions almost the same way as the embodiment of FIG. 4, except that instead of the plug 66, a rupture disk 72 initially blocks flow of the fluid 24 through the bypass flowpath 64. The rupture disk 72 may be ruptured due to an increase in pressure differential from the flow passage 26 to the exterior of the screen assembly 16.

The flow control device 30 is used in addition to at least one other flow restrictor 40 (not visible in FIG. 5) which provides for fluid communication between the filter portion 20 and the flow passage 26. For example, there could be one or more flow restrictors 40 provided in the bulkhead 56 as depicted in FIG. 3.

The flow control device 30 depicted in FIG. 5 permits a restriction to the flow of the fluid 24 to be decreased when desired, by opening one or more bypass flowpaths 64 which are initially blocked by respective one or more rupture disks 72. This result is accomplished by increasing pressure in the flow passage 26 relative to pressure on the exterior of the screen assembly 16, to thereby cause the rod 50 to displace toward the seat 54 adjacent the flow restrictor 40 (see FIG. 3).

Once the rod 50 has engaged the seat 54 adjacent the flow restrictor 40, a pressure differential across the rupture disk 72 will cause the disk to rupture and open the flowpath 64. A sealing surface 70 on the rod 50 will also eventually engage the seat 54 to close off the bypass flowpath 64, so that any other flow control devices 30

- 13 -

included in the flow control portion 22 can be similarly operated to open additional bypass flowpaths.

Thus, when pressure in the flow passage 26 is increased, those rods 50 which are associated with flow
5 restrictors 40 will displace into engagement with the seats 54 adjacent the flow restrictors 40, thereby enabling a pressure differential to be applied across the rupture disks 72. As each disk 66 is ruptured, the associated rod 50 will displace into engagement with its seat to close off the
10 flowpath. This process will occur in each screen assembly 16 along the tubular string 12.

After the disks 72 are ruptured or otherwise opened, the sealing surface 70 will engage the seat 54, and the remainder of the operation of the screen assembly is the
15 same as described above for the FIG. 3 embodiment. The flowpath 64 and rupture disk 72 thus comprise a flow resistance device 71 for decreasing a resistance to flow of the fluid 24 in response to a predetermined stimulus applied from a remote location.

20 Referring additionally now to FIG. 6, an alternate construction of the screen assembly 16 is representatively illustrated. The screen assembly 16 of FIG. 6 includes the flow control portion 22 which functions as an ICD and also reduces production of undesired fluids. The ICD includes
25 the flow restrictor 40.

The flow restrictor 40 as depicted in FIG. 6 is a bent tubular structure which forces the fluid 24 to change direction as it enters and flows through the flow
30 restrictor. This repeated change in momentum of the fluid 24 increases the resistance to flow through the flow restrictor 40 without requiring use of narrow flow passages which would more easily become clogged.

- 14 -

A pressure drop through the flow restrictor 40 will increase as the length of the tube increases, and as the number of bends in the tube increases. A viscous fluid such as oil will flow much slower through the tube as compared to
5 water.

The flow control device 30 depicted in FIG. 6 is of the type known to those skilled in the art as a velocity check valve. It includes a poppet 44, a biasing device 46 and a seat 48. The biasing device 46 applies a force to the
10 poppet 44 in a direction away from the seat 48.

The flow control device 30 of FIG. 6 is responsive to a flow rate and velocity of the fluid 24, and since the velocity of the fluid is related to its density, the flow control device is also responsive to the density of the
15 fluid.

As the velocity of the fluid 24 increases, the drag force on the poppet 44 gradually overcomes the biasing force exerted by the biasing device 46, and the poppet displaces more toward the seat 48, thereby reducing the flow area
20 through the flow control device 30. When the velocity of the fluid 24 is great enough, the poppet 44 will engage the seat 48, thereby closing the flow control device 30 and preventing flow of the fluid 24 through the flow control device.

25 As long as pressure external to the screen assembly 16 exerted via the filter portion 20 is sufficiently greater than pressure in the interior flow passage 26 (as would be the case in typical production operations), the flow control device 30 will remain closed. This will exclude higher
30 density fluid (such as water) from being produced through the screen assembly 16.

- 15 -

If it is later desired to restart production through the screen assembly 16, then pressure in the interior flow passage 26 may be increased relative to pressure external to the screen assembly (for example, by shutting in the tubular string 12 downstream of the screen assembly to equalize the pressures, or by applying increased pressure to the flow passage 26, etc.). In this manner, the poppet 44 can be displaced away from the seat 48, and the flow control device 30 will again be open for permitting flow of the fluid 24.

It is a particular advantage of this configuration of the screen assembly 16 that it can be "reset" in this manner when desired.

Referring additionally now to FIGS. 7 & 8, another alternate construction of the screen assembly 16 is representatively illustrated. The screen assembly 16 of FIGS. 7 & 8 includes the flow control portion 22 which functions as an ICD and also reduces production of undesired fluids.

This example is similar in many respects to the embodiment of FIG. 6, except that the FIGS. 7 & 8 embodiment includes an inhibitor device 74 which progressively varies a response of multiple flow control devices 30 as more of the flow control devices respond to the change in velocity of the fluid 24.

The flow control devices 30 include the poppet 44, biasing device 46 and seat 48 of the FIG. 6 embodiment, so that the flow control devices function as velocity check valves to close off flow of the fluid 24 when the flow rate or velocity of the fluid increases. The inhibitor device 74 progressively inhibits the flow control devices 30 from closing as an increasing number of the flow control devices close.

- 16 -

The inhibitor device 74 includes a flexible cable 76 which passes through extensions 78 of the poppets 44. In FIG. 8 it may be seen that the cable 76 extends around to each of the extensions 78, and also passes through rigid posts 80 positioned between the flow control devices 30.

When the velocity of the fluid 24 flowing through one of the flow control devices 30 increases sufficiently, the flow control device will close (i.e., the poppet 44 will engage the seat 48). As a result, the corresponding extension 78 will displace with the poppet 44, thereby applying an increased tensile force to the cable 76.

This increased force transmitted to the cable 76 will inhibit the next flow control device 30 from closing. However, when the velocity of the fluid 24 flowing through this next flow control device 30 does increase sufficiently to overcome the increased force in the cable 76, it too will close and thereby apply a further increased tensile force to the cable 76.

Thus, it will be appreciated that, as each flow control device 30 closes, the inhibitor device 74 increasingly inhibits the next flow control device from closing. A biasing device 82, such as a spring, may be interconnected in the cable 76 to supply an initial force in the cable 76, and to provide resilience. The biasing device 82 may be conveniently designed to regulate the amount by which each successive flow control device 30 is progressively inhibited from closing.

It is contemplated that, if the fluid 24 is stratified into layers of oil and water in the flow control portion 22, the flow control device 30 having the greatest proportion of water flowing through it will close first (due to the reduced viscosity of the water resulting in an increased

- 17 -

velocity of flow of the water through that flow control device). This will reduce the production of water through the screen assembly 16, while still allowing production of oil through the screen assembly.

5 Subsequent flow control devices 30 will close when further increased velocities of flow of the fluid 24 through the flow control devices are experienced. This helps to keep one or more of the flow control devices 30 open until the fluid 24 includes a substantial proportion of water,
10 while still allowing the first few flow control devices to close when the fluid includes only a small proportion of water.

 One beneficial feature of this embodiment is that the inhibitor device 74 works in this manner to exclude
15 production of the higher density, lower viscosity proportion of the fluid 24 without regard to a certain azimuthal orientation of the flow control portion 22. Thus, the screen assembly 16 does not have to be installed in any particular orientation to achieve the benefits described
20 above.

 Referring additionally now to FIG. 9, another alternate construction of the screen assembly 16 is representatively illustrated. The screen assembly 16 of FIG. 9 includes the flow control portion 22 which functions as an ICD and also
25 reduces production of undesired fluids. The ICD includes the flow restrictor 40.

 This example is very similar to the embodiments of FIGS. 7 & 8, except that the inhibitor device 74 is positioned on an opposite side of the flow control device
30 30. Thus, the poppet 44 in the embodiment of FIG. 9 "pushes" on the cable 76 via the extension 78, instead of "pulling" on the cable as in the embodiment of FIGS. 7 & 8.

- 18 -

Referring additionally now to FIGS. 10 & 11, another alternate construction of the screen assembly 16 is representatively illustrated. The screen assembly 16 of FIGS. 10 & 11 includes the flow control portion 22 which functions as an ICD and also reduces production of undesired fluids. The ICD includes the flow restrictor 40.

This example of the screen assembly 16 is similar in many respects to the embodiment of FIGS. 7 & 8, except that instead of the cable 76, the embodiment of FIGS. 10 & 11 includes a relatively stiff wire 82. The wire 82 extends through each extension 78 of the flow control devices 30, but no posts 80 are used. Instead, the wire 82 has ears 84 formed thereon which engage an inclined surface 86 formed on the bulkhead 56.

This engagement between the ears 84 of the wire 82 and the inclined surface 86 resists displacement of the poppets 44 toward their respective seats 48. Eight flow control devices 30, with an ear 84 positioned between each adjacent pair of flow control devices, are depicted in FIG. 11, but it should be understood that any number of these elements may be used in keeping with the principles of the invention.

Referring additionally now to FIG. 12, another alternate construction of the screen assembly 16 is representatively illustrated. The screen assembly 16 of FIG. 12 includes the flow control portion 22 which functions as an ICD and also reduces production of undesired fluids. The ICD includes flow restrictors 40 and an annular flowpath 36 between a rod 32 and housing 34.

This example of the screen assembly 16 functions somewhat the same as the FIG. 6 embodiment, but demonstrates that similar functionality can be achieved by different

- 19 -

configurations in keeping with the principles of the invention.

The FIG. 12 embodiment includes the rod 32, housing 34 and biasing device 38, but in this embodiment the rod is
5 rigidly attached to the bulkhead 56 and the housing is reciprocally disposed on the rod. As the flow rate or velocity of the fluid 24 increases (e.g., due to decreased viscosity of the fluid) a drag force produced as the fluid flows through the annular flowpath 36 increases as displaces
10 the housing 34 toward the seat 48, against the biasing force exerted by the biasing device 38.

Eventually, the housing 34 engages the seat 48 and shuts off flow of the fluid 24 into the flow passage 26. In this manner, the flow control device 30 operates as a
15 velocity check valve to eventually reduce the flow area through the flow control device to zero as the velocity of the fluid 24 increases.

Referring additionally now to FIG. 13, another alternate construction of the screen assembly 16 is
20 representatively illustrated. The screen assembly 16 of FIG. 13 includes the flow control portion 22 which functions as an ICD, prevents fluid loss from the tubular string 12 and also reduces production of undesired fluids. The ICD includes the flow restrictor 40, which could be a tube,
25 orifice, nozzle or coiled tube. The openings 42 could also serve as flow restrictors if so designed.

This example of the screen assembly 16 is similar in some respects to those embodiments described above (e.g., the embodiments of FIGS. 2 & 3) which prevent reverse flow
30 of fluid through the screen assembly. However, the flow control device 30 of the FIG. 13 embodiment includes a hydraulic actuator 88 for selectively opening and closing a

- 20 -

valve 92 to thereby control flow of fluid and prevent loss of fluid. The actuator 88 includes a piston 90 which displaces in response to a pressure differential between internal chambers 94, 96. The valve 92 includes a closure
5 98 with sealing surfaces 100 for sealingly engaging seats 102.

When pressure in the chamber 94 sufficiently exceeds pressure in the chamber 96 (due to a pressure drop through the flow restrictor 40), the piston 90 will displace in a
10 direction pulling the closure 98 and sealing surfaces 100 away from the seats 102, thereby permitting flow of the fluid 24 through the flow control portion 22. However, if pressure in the chamber 96 sufficiently exceeds pressure in the chamber 94 (as would be the case typically in a reverse
15 flow condition), the piston 90 will exert a biasing force to displace the closure 98 and sealing surfaces 100 into engagement with the seats 102 to thereby shut off the flow.

The flow control device 30 may be "reset" to again permit flow by reducing pressure in the flow passage 26
20 relative to pressure on the exterior of the screen assembly 16, thereby increasing the pressure differential from the chamber 94 to the chamber 96. This will cause the piston 90 to exert a biasing force on the closure 98 and displace the closure away from the seats 102, thereby opening the flow
25 control portion 22 to flow of the fluid 24.

The flow control portion 22 of the FIG. 13 embodiment also includes a water excluder device 104 and a gas excluder device 106. The water excluder device 104 preferably includes multiple spherical bodies 108 which are neutrally
30 buoyant in water, so that when water is produced through the flow control portion 22, the bodies float in the water and engage the openings 42 to close off the openings and thereby

- 21 -

exclude production of the water. As the fluid 24 includes a greater proportion of water, progressively more of the openings 42 are closed off.

The gas excluder device 106 preferably includes
5 multiple spherical bodies 110 which are less dense than oil, so that when gas is produced through the filter portion 22, the bodies float on top of the oil and engage the openings 42 to close off the openings and thereby exclude production of the gas. As the fluid 24 contains a greater proportion
10 of gas, progressively more of the openings 42 are closed off.

The water and gas excluder devices 104, 106 may be similar to any of those described in U.S. patent no. 7,185,706 and application serial nos. 11/671319 filed
15 February 5, 2007 and 11/466022 filed August 21, 2006. The entire disclosures of this patent and these applications are incorporated herein by this reference. Of course, other types of water and/or gas excluder devices may be used in keeping with the principles of the invention.

20 Referring additionally now to FIG. 14, another alternate construction of the screen assembly 16 is representatively illustrated. The screen assembly 16 includes the flow control portion 22 which functions as an ICD, prevents fluid loss from the tubular string 12 and also
25 reduces production of undesired fluids. The ICD has two flow restrictors 40.

This example of the screen assembly 16 is similar in many respects to the embodiment of FIG. 13, except that the actuator 88 and valve 92 are somewhat differently
30 configured. In the embodiment of FIG. 14, a much larger flow area through the valve 92 is provided, and the piston 90 of the actuator 88 has a larger differential piston area.

- 22 -

In addition, only one each of the sealing surface 100 and seat 102 are used in the valve 92.

Referring additionally now to FIG. 15, another alternate construction of the screen assembly 16 is representatively illustrated. This example of the screen assembly 16 is similar in many respects to the embodiment of FIG. 14, except that the actuator chamber 96 is directly exposed to pressure in the interior flow passage 26 via an opening 112.

10 The chamber 96 is formed between two bulkheads 114, 116, with the opening 112 providing direct communication between the chamber and the flow passage 26. Thus, the actuator 88 is more directly responsive to the pressure differential between the flow passage 26 and the exterior of the screen assembly 16 as compared to the embodiments of FIGS. 13 & 14.

Referring additionally now to FIG. 16, other alternate construction of the screen assembly 16 is representatively illustrated. This example of the screen assembly 16 is similar in many respects to the embodiment of FIG. 15, except that the actuator chamber 96 is not exposed to pressure in the interior flow passage 26, but is instead exposed to pressure in a line 118 extending to a remote location.

25 Thus, pressure delivered via the line 118 may be used to regulate the operation of the valve 92 by varying the pressure differential between the chambers 94, 96. Specifically, the valve 92 may be closed by applying increased pressure to the line 118, thereby causing the actuator 88 to displace the piston 98 and close the valve 92. Reduced pressure may be applied via the line 118 to open the valve 92.

- 23 -

The line 118 may be of the type known to those skilled in the art as a control line, and the line may be positioned internal, external or within a sidewall of the tubular string 12. The line 118 may extend to the surface, or to
5 another remote location in the well, such as to a pump or control module. In this manner, the flow control device 30 may be operated remotely to control flow of the fluid 24 through the screen assembly 16.

It may now be fully appreciated that the foregoing
10 detailed description provides many advancements in the art. For example, the present specification provides a well screen assembly 16 which includes a filter portion 20 for filtering fluid 24, and a flow control device 30 which varies a resistance to flow of the fluid 24 in response to a
15 change in velocity of the fluid.

The flow control device 30 may include a velocity check valve (such as in the embodiments of FIGS. 6 & 12). The flow control device 30 may decrease a flow area in response to an increase in the velocity of the fluid 24.

20 The flow control device 30 may increase the resistance to flow in response to an increase in density of the fluid 24 (such as in the embodiments of FIGS. 7-11). The flow control device 30 may increase the resistance to flow in response to an increase in velocity of the fluid 24.

25 The well screen assembly 16 may include one or more flow restrictors 40 interconnected upstream and/or downstream of the flow control device 30.

The well screen assembly 16 may include multiple flow control devices 30, and an inhibitor device 74 which
30 progressively varies a response of the flow control devices as more of the flow control devices respond to the change in velocity of the fluid 24. The inhibitor device 74 may

- 24 -

progressively inhibit the flow control devices 30 from closing as an increasing number of the flow control devices close.

Also provided are the well screen assembly 16
5 embodiments which include a flow resistance device 59, 63 and/or 71 which decreases a resistance to flow of the fluid 24 in response to a predetermined stimulus applied from a remote location. The stimulus may comprise a pressure variation. The pressure variation may comprise an increase
10 in a pressure differential from an interior to an exterior of the well screen assembly 16.

The flow resistance device 59, 63, 71 may comprise a flowpath 60, 64 which opens in response to the stimulus. The flowpath 60, 64 may bypass a flow restrictor 40 which
15 restricts flow of the fluid 24. The flow resistance device 63 may include a plug 66 which displaces to unblock the flowpath 64 in response to the stimulus. The flow resistance device 63, 71 may include a check valve which closes the flowpath 64 in response to the stimulus, and
20 which opens the flowpath in response to release of the stimulus.

Also provided are the well screen assembly 16
embodiments which comprise a valve 92 including an actuator 88 having a piston 90 which displaces in response to a
25 pressure differential to thereby selectively permit and prevent flow of the fluid 24 through the valve 92. The well screen assembly 16 may also include a flow restrictor 40 which restricts flow of the fluid 24.

The pressure differential may be between chambers 94,
30 96 on respective upstream and downstream sides of the flow restrictor 40. The pressure differential may be between an inner flow passage 26 extending longitudinally through the

- 25 -

well screen assembly 16 and an internal chamber 94 of the well screen assembly 16 in selective fluid communication with the filter portion 20. The internal chamber 94 may be upstream of a flow restrictor 40 which restricts flow of the fluid 24. The pressure differential may be between a line 118 extending to a remote location and an internal chamber 94 of the well screen assembly 16 in selective fluid communication with the filter portion 20.

The well screen assembly 16 may include a water excluder device 104 which increasingly restricts flow of the fluid 24 as a proportion of water in the fluid increases. The well screen assembly 16 may include a gas excluder device 106 which increasingly restricts flow of the fluid 24 as a proportion of gas in the fluid increases. The well screen assembly 16 may include any excluder device 104, 106 which increasingly blocks flow of an undesired portion of the fluid 24 as the undesired portion increases, and a flow restrictor 40 which restricts flow of the fluid 24.

Of course, a person skilled in the art would, upon a careful consideration of the above description of representative embodiments of the invention, readily appreciate that many modifications, additions, substitutions, deletions, and other changes may be made to these specific embodiments, and such changes are within the scope of the principles of the present invention. Accordingly, the foregoing detailed description is to be clearly understood as being given by way of illustration and example only, the spirit and scope of the present invention being limited solely by the appended claims and their equivalents.

- 26 -

WHAT IS CLAIMED IS:

1. A well screen assembly, comprising:

a filter portion for filtering fluid; and

5 a flow control device which varies a resistance to flow of the fluid in response to a change in velocity of the fluid.

2. The well screen assembly of claim 1, wherein the flow control device comprises a velocity check valve.

10 3. The well screen assembly of claim 1, wherein the flow control device decreases a flow area in response to an increase in the velocity of the fluid.

4. The well screen assembly of claim 1, wherein the flow control device increases the resistance to flow in
15 response to an increase in density of the fluid.

5. The well screen assembly of claim 1, wherein the flow control device increases the resistance to flow in response to an increase in velocity of the fluid.

6. The well screen assembly of claim 1, further
20 comprising at least one flow restrictor interconnected at least one of upstream and downstream of the flow control device.

7. The well screen assembly of claim 1, further comprising multiple ones of the flow control device, and an
25 inhibitor device which progressively varies a response of the flow control devices as more of the flow control devices respond to the change in velocity of the fluid.

8. The well screen assembly of claim 1, further comprising multiple ones of the flow control device, and an
30 inhibitor device which progressively inhibits the flow

- 27 -

control devices from closing as an increasing number of the flow control devices close.

9. A well screen assembly, comprising:

a filter portion for filtering fluid; and

5 a flow resistance device which decreases a resistance to flow of the fluid in response to a predetermined stimulus applied from a remote location.

10. The well screen assembly of claim 9, wherein the stimulus comprises a pressure variation.

10 11. The well screen assembly of claim 10, wherein the pressure variation comprises an increase in a pressure differential from an interior to an exterior of the well screen assembly.

12. The well screen assembly of claim 9, wherein the
15 flow resistance device comprises a flowpath which opens in response to the stimulus.

13. The well screen assembly of claim 12, wherein flowpath bypasses a flow restrictor which restricts flow of the fluid.

20 14. The well screen assembly of claim 12, wherein the flow resistance device further comprises a plug which displaces to unblock the flowpath in response to the stimulus.

15. The well screen assembly of claim 12, wherein the
25 flow resistance device further comprises a check valve which closes the flowpath in response to the stimulus, and which opens the flowpath in response to release of the stimulus.

16. A well screen assembly, comprising:

a filter portion for filtering fluid; and

- 28 -

a valve including an actuator having a piston which displaces in response to a pressure differential to thereby selectively permit and prevent flow of the fluid through the valve.

5 17. The well screen assembly of claim 16, further comprising a flow restrictor which restricts flow of the fluid.

10 18. The well screen assembly of claim 17, wherein the pressure differential is between chambers on respective upstream and downstream sides of the flow restrictor.

15 19. The well screen assembly of claim 16, wherein the pressure differential is between an inner flow passage extending longitudinally through the well screen assembly and an internal chamber of the well screen assembly in selective fluid communication with the filter portion.

20 20. The well screen assembly of claim 19, wherein the internal chamber is upstream of a flow restrictor which restricts flow of the fluid.

25 21. The well screen assembly of claim 16, wherein the pressure differential is between a line extending to a remote location and an internal chamber of the well screen assembly in selective fluid communication with the filter portion.

30 22. The well screen assembly of claim 16, further comprising a water excluder device which increasingly restricts flow of the fluid as a proportion of water in the fluid increases.

35 23. The well screen assembly of claim 16, further comprising a gas excluder device which increasingly restricts flow of the fluid as a proportion of gas in the fluid increases.

- 29 -

24. The well screen assembly of claim 16, further comprising an excluder device which increasingly blocks flow of an undesired portion of the fluid as the undesired portion increases, and a flow restrictor which restricts
5 flow of the fluid.