

A PUSH-BUTTON ELECTRICAL SWITCH ARRANGEMENT

10

This invention relates to the construction of electrical push-button operated switches, especially but not exclusively for use in telephone instruments.

A recent development in the field of such manually-
15 operable switching is the use of a so-called rubber (or rubber-like material) dimple pad, which is a sheet of the rubber (or rubber-like material) with a dimple per push-button position. Each such dimple is a dome on the sheet surface which has on its concave surface a region of conductive material, e.g. metal or conductive plastics. The
20 dimple pad is located over a sheet of an electrically insulating material having electrically conductive regions on it. When a push-button is depressed, its dimple's dome is collapsed so that its conductive region contacts the conductive region on the lower sheet to complete one or more
25 connections. On release of the push-button it restores to rest, assisted by the resilience of the dimple. In the case of a telephone keypad we use a 4 x 3 dimple pad, with a corresponding matrix of conductive tracks on the lower sheet.

30 An object of the invention is to produce a simple and inexpensive push-button switch using such dimple switches, and to produce a keypad using such push-buttons.

According to the invention there is provided a push-button switch arrangement, which includes a frame-like
35 structure of an electrically-insulating plastics material having a cut-out portion within which the push-button is located, the push-button being of generally rectangular

shape and having an upstanding portion which is depressible by a user to operate the switch arrangement, two supporting arms each of which extends from a respective one of a pair of generally parallel sides of the push-button to the frame-like structure, and contact means located below the push-button so as to be controllable thereby, in which the two arms each extend away from the push-button generally in the same direction from the push-button, said arms diverging mutually from the push-button, in which each said arm is longer than the major dimension of the push-button, and in which each said arm is integral with the push-button and with the frame-like structure and is resilient so that resetting of a depressed push-button when the latter is released is aided by the resilience of the arms.

Embodiments of the invention will now be described with reference to the accompanying drawings, in which

Fig. 1 is a view from the top of one corner of a one-piece frame which incorporates a number of push-button switches embodying the invention;

Fig. 2 is a view similar to Fig. 1 of another corner of the frame;

Fig. 3 is a cross-section of a push-button such as that in the corner shown in Fig. 1;

Fig. 4 is a cross-section along the line III-III of Fig. 3;

Fig. 5 is a perspective view of a further embodiment of the invention.

The arrangement shown in Figs. 1 and 2 is a frame which carries twelve push-buttons arranged in a 4 x 3 co-ordinate matrix. Such arrays are much used as keypads for telephone instruments. The frame has sides 1, 2, interconnected by two more sides only one of which, 3, is shown. In addition lengthwise intermediate strips such as 4 extend between the sides 1, 2.

Each push-button such as 5 has two upstanding ribs 6 and a depending circular portion 7 which fits

snugly into a circular portion, indicated at 8, on a push-button support. Integral with this support for a push-button there are arms 9, 10, formed integral with the portion such as 8, and extending to and
5 integral with respective ones of the edges 3 and strips 4. Each pair of arms defines a V with the push-button at the apex.

When a push-button is depressed, it thus pivots about the point at which its arms 9, 10, are formed
10 integral with the edges on strips 3, 4. Due to the resilience of the material, there is some assistance with resetting when the user removes his finger from a depressed button.

We now refer to Fig. 5, in which the rubber
15 dimple pad referred to above is shown at 15, this having twelve dimples such as the one indicated at 16. Above the dimple pad we have a one-piece structure 17, which carries the twelve push-buttons such as 18, each coupled to the structure of a pair of arms such
20 as 19. In this case the push-buttons are each integral with the pair of arms, and, unlike the push-buttons of Figs. 1 to 4, each button is "sausage-shaped" in plan. The buttons each extend through a correspondingly-shaped hole in a cover plate 20.

25 In the arrangement shown in Figs. 1 to 4, the ribs 6, see especially Fig. 3, may be omitted if so desired. Further, although the dimple pad has been referred to as having a disc of metal or conductive plastics, this disc could be of a conductive rubber-
30 like material. Further, since only one push-button is operated at once, the sheet and dimples could all be electrically conductive.

An important advantage of the 'A' frame construction described herein is that it enables the use
35 of long support arms which overlap the positions of adjacent buttons. This allows the button to travel

through a large radius, producing an action closer to the parallel action at present typical in keypads.

CLAIMS :

1. A push-button switch arrangement, which includes a frame-like structure of an electrically-insulating plastics material having a cut-out portion within which the push-button is located, the push-button being of generally rectangular shape and having an upstanding portion which is depressible by a user to operate the switch arrangement, two supporting arms each of which extends from a respective one of a pair of generally parallel sides of the push-button to the frame-like structure, and contact means located below the push-button so as to be controllable thereby, in which the two arms each extend away from the push-button generally in the same direction from the push-button, said arms diverging mutually from the push-button, in which each said arm is longer than the major dimension of the push-button, and in which each said arm is integral with the push-button and with the frame-like structure and is resilient so that resetting of a depressed push-button when the latter is released is aided by the resilience of the arms.
2. A switch arrangement as claimed in claim 1, and in which the push-button co-operates with a collapsible dimple which carries part of said contact means.
3. A push-button switch matrix which includes a co-ordinate array of switch arrangements each as claimed in claim 1, the push-buttons and the arms of all of the buttons and a single said frame-like structure being formed as a single integral unit.
4. A matrix as claimed in claim 3, and in which the contact means of the switch arrangements are provided by a single layer of insulating material formed with a collapsible dimple per push-button, each said dimple carrying a contact which is brought into engagement with stationary contact means when its buttons is depressed.
5. A push-button switch arrangement, substantially as described with reference to Figs. 1 to 4, or Fig. 5 of the accompanying drawings.