



(51) International Patent Classification:
E06C 7/44 (2006.01) *F16B 2/24* (2006.01)

(21) International Application Number:
PCT/NL2010/050064

(22) International Filing Date:
11 February 2010 (11.02.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09152567.5 11 February 2009 (11.02.2009) EP
61/176,262 7 May 2009 (07.05.2009) US

(71) Applicant (for all designated States except US): **SMART LEVEL COMPANY B.V.** [NL/NL]; De Hulst 13, NL-5807 EW Oostrum (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BUS, Karolus, Theodorus, Wilhelmina, Maria** [NL/NL]; Spoorstraat 40 a, NL-5821 BD Vierlingsbeek (NL).

(74) Agent: **VAN WESTENBRUGGE, Andre**; J.W. Friso-laan 13, NL-2517 JS The Hague (NL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: SUPPORTING ELEMENT FOR AN OBJECT AND APPARATUS COMPRISING A SUPPORTING ELEMENT

Fig 3a



(57) Abstract: The invention relates to a supporting element (2) for an object. The supporting element comprises a first leg member (22) and a second leg member (20). The first leg member is axially movable relative to the second leg member for axially extending the support member. The first leg member comprises a house (32) that is arranged for slidably receiving the second leg member. The house comprises a locking element (30) having a locking position for locking the relative axial movement of the first leg member with respect to the second leg member, and having an open position for enabling relative axial movement of the two members. A catch (34) may be provided in the locking element. The catch may be tiltably movable within the house for alternately acquiring the locking position and the open position of the locking element. The catch may comprise a cavity (40) receiving the second leg, wherein the cavity has a stopping surface (47) engaging at least opposed perimeter parts of the second leg member in a locking position of the locking element.