

TRAIN CREW SUPPORT DEVICE

DESCRIPTION

5 TECHNICAL FIELD

[0001] The present invention relates to a train crew support device for supporting train crew in performing a door opening-closing operation.

10 BACKGROUND ART

[0002] Conventionally, a train crew support device disclosed in, for example, Patent Literature 1 mentioned below is configured in such a way that, upon arrival of a train at a station platform, information regarding the door
15 opening side transmitted from a ground device installed at the platform or the like is received for identifying the door opening side. Herein, for example, consider a case when disruption occurs to train services while trains are moving and train traffic rescheduling is performed so that
20 a train is forced to make a temporary stop at a station not being a scheduled stop. In such a case, even if a crew member performs incorrect manipulation of a door opening switch provided on a cab, the configuration is such that the doors do not open unless the information regarding the
25 door opening side is consistent with the manipulation.

[0003] Patent Literature 1: Japanese Patent Application Laid-open No. 2002-205640

DISCLOSURE OF INVENTION

30 PROBLEM TO BE SOLVED BY THE INVENTION

[0004] However, since the ground device is highly expensive, the installment thereof gets confined only to interlocking stations. That makes it difficult to support

the train crew in performing the door opening-closing operation at all stations.

[0005] Moreover, even in the case of installing the ground devices at interlocking stations, if train traffic
5 rescheduling is performed just before a train makes a stop; then the information regarding the door opening side might be received after the train has stopped at a station. That makes it difficult for the crew members to swiftly direct the passengers.

10 [0006] The present invention has been made in view of the above and it is an object of the present invention to provide a train crew support device that enables obtaining information regarding the door opening side in a prompt manner without having to install ground devices.

15

MEANS FOR SOLVING PROBLEM

[0007] To solve the problem above and achieve the object, a train crew support device according to the present invention is equipped with a door opening-closing signal
20 output unit for controlling a door opening-closing device of a train in response to a door opening-closing operation performed by a crew member, the train crew support device includes: a train classification information interface that imports, from a train number setting device, train number
25 classification information that includes a line code indicating a travelling line of a train, a station code indicating a stop, a track code indicating a train track, platform information indicating a platform direction, a door opening-closing side, and a platform train-car
30 capacity; an ATS interface that imports, from an ATS system, ATS control information that includes the line code, the station code, and the track code; a memory unit that stores the train number classification information; and an

operation determining unit that checks the line code, the station code, and the track code included in the ATS control information against the train number classification information, identifies a door opening side of
5 corresponding train, and outputs a door opening-closing signal to the door opening-closing signal output unit.

EFFECT OF THE INVENTION

[0008] According to an aspect of the present invention,
10 since ATS control information transmitted from an existing ATS system includes line codes, station codes and track codes; information regarding the door opening side can be obtained in a prompt manner without having to install
ground devices.

15

BRIEF DESCRIPTION OF DRAWINGS

[0009] Fig. 1 is a diagram of an exemplary configuration of a train crew support device according to a first embodiment and exemplary configurations of devices
20 connected to the train crew support device.

Fig. 2 is a diagram illustrating contents of a door opening information table.

FIG. 3 is a diagram illustrating an example of contents of ATS control information.

25 Fig. 4 is a schematic diagram of station yard wiring and a velocity check pattern P1 in an interlocking station.

Fig. 5 is an exemplary flowchart explaining a flow for the case when the train crew support device decides on the door opening side.

30 FIG. 6 is a diagram illustrating an example of contents of the ATS control information for the case of a stop aspect.

Fig. 7 is a diagram of an exemplary configuration of

the train crew support device according to a third embodiment and exemplary configurations of devices connected to the train crew support device.

Fig. 8 is an exemplary flowchart explaining a flow for the case when the train crew support device and a train crew support device decide on the door opening side.

Fig. 9 is a diagram of an exemplary configuration of the train crew support device according to a fourth embodiment and exemplary configurations of devices connected to the train crew support device.

EXPLANATIONS OF LETTERS OR NUMERALS

	[0010]	10	ATS system
	11	ATS ground device	
15	12, S1, S2, S3, S4, S5, S6	Transponder	
	13	ATS on-train device	
	20, 20a	Train crew support device	
	21	ATS interface	
	22	Train classification information interface	
20	23, 23a	Operation determining unit	
	24, 24a	Memory unit	
	25, 25a	Left-door opening-closing-signal output unit	
	26, 26a	Right-door opening-closing-signal output unit	
	27, 27a	Transmitting unit	
25	28, 28a	Train information providing device interface	
	30	Train number setting device	
	40	Left door opening switch	
	41	Right door opening switch	
	50, 50a	Left door opening-closing device	
30	51, 51a	Right door opening-closing device	
	70, 70a	Train information providing device	
	71, 71a	Passenger compartment indicator	
	100	Transmission path	

- 200 Door opening information table
- 201, 313, 618 Station code
- 202, 314, 617 Track code
- 203 Platform information
- 5 204 Door opening side
- 205 Platform train-car capacity
- 300a, 600a ATS control information contents
- 300b Individual information regarding divergence velocity limitation
- 10 300c Post-revision individual information regarding divergence velocity limitation
- 301, 601 Synchronization flag
- 302, 602 Information type
- 303, 603 Driving direction
- 15 304, 604 Track antenna number
- 305, 605 Individual information
- 306, 606 CRC
- 307, 607 Termination flag
- 308, 608, 611, 616 Free space
- 20 309 Limiting velocity
- 310 Limiting zone length
- 311 Distance to turnout
- 312, 619 Line code
- 401 Home signal
- 25 600b Individual information regarding stop aspect
- 600c Post-revision individual information regarding stop aspect
- 609 Divergence pattern continuance
- 610 Aspect code
- 30 612 Signal pattern correction
- 613 Maintenance information
- 614 Distance to home signal
- 615 Distance to subsequent turnout

1D Train classification information
 2D ATS control information
 3D Door opening-closing signal
 1L Normal track
 5 2L Reverse track
 1R Normal track
 2R Reverse track
 A Train
 H1, H2, H3, H4 Platform

10

BEST MODE(S) FOR CARRYING OUT THE INVENTION

[0011] Exemplary embodiments of a train crew support device according to the present invention are described in detail below with reference to the accompanying drawings.

15 The present invention is not limited to these exemplary embodiments.

[0012] First embodiment

Fig. 1 is a diagram of an exemplary configuration of a train crew support device 20 according to a first
 20 embodiment and exemplary configurations of devices connected to the train crew support device 20. To the train crew support device (hereinafter, simply referred to as "support device") 20, it is possible to connect an ATS system 10, a train number setting device (hereinafter,
 25 simply referred to as "trn-num setting device") 30, a left door opening switch 40 (hereinafter, simply referred to as "switch 40"), a right door opening switch 41 (hereinafter, simply referred to as "switch 41"), a left door opening-closing device 50, and a right door opening-closing device
 30 51.

[0013] Fig. 2 is a diagram illustrating contents of a door opening information table. A door opening information table (hereinafter, simply referred to as "table") 200

includes items such as station code 201, track code 202, platform information 203, door opening side 204, and platform train-car capacity 205.

[0014] The station code 201 indicates the stops. The
 5 track code 202 indicates the travelling directions of trains. For example, besides indicating the tracks along the up line and the down line, the track code 202 can also indicate the tracks diverging at shunts (points). The platform information 203 indicates platform numbers in a
 10 corresponding manner to the track code 202. The door opening side 204 indicates the sides of open doors in a corresponding manner to the track code 202 and the platform information 203. The platform train-car capacity 205 indicates the number of train cars that can stop along each
 15 platform. Although codes such as "1L" are specified in the right column of the track code 202 in FIG. 2, binary codes are registered in the actual table 200, as illustrated in the left column of each code.

[0015] With reference to Fig. 1, the support device 20
 20 includes an ATS interface 21, a memory unit 24, a left-door opening-closing-signal output unit 25 (hereinafter, simply referred to as "left door opening-closing unit), a right-door opening-closing-signal output unit 26 (hereinafter, simply referred to as "right door opening-closing unit),
 25 and an operation determining unit 23.

[0016] The trn-num setting device 30 is a device for setting train classification information. For example, train classification information 1D includes the station code 201, the track code 202, the platform information 203,
 30 the door opening side 204, the platform train-car capacity 205, number of train cars, train numbers, train types, starting stations, destinations, stops, and arrival time and departure time at those stops. Although the

installation location of the trn-num setting device 30 differs for each railway company, it is common practice to install it in a crew member monitoring device on the cab. At the beginning of working, the train classification information 1D is stored in a recording medium such as an IC card and is retrieved for use with a reading device disposed in a train.

[0017] An ATS on-train device 13 can receive, from a transponder 12 installed on the line, information (hereinafter, referred to as "control information") 2D regarding stop signals, velocity limitation locations, distances, and the like. The transponder 12 is controlled by an ATS ground device (hereinafter, simply referred to as "ground device") 11 and is configured to wirelessly transmit information to the trains passing thereabove. Meanwhile, the ground device 11, the transponder 12, and the ATS on-train device 13 are hereinafter collectively referred to as the ATS system 10. As the ATS system 10, a pattern generating ATS system 10 is used that performs velocity control by generating a velocity check pattern (a curved line representing velocity variation from the start of braking to attainment of a halting state).

[0018] The switch 40 and the switch 41 are installed in a crew member operation panel and are used by a crew member to open the doors on the left side or on the right side when the train makes a stop at a platform.

[0019] The left door opening-closing device 50 and the right door opening-closing device 51 are devices that perform opening-closing control of the doors in each train car in accordance with a manipulation of the switch 40 and the switch 41, respectively.

[0020] An information interface 22 is able to import the train classification information 1D that has been

transmitted by the trn-num setting device 30. Besides, for example, the information interface 22 includes a connection port for LAN or RS422. The transmission control procedure is desirable to make use of TCP/IP for LAN; and it is
 5 desirable to make use of HDLC for RS422, for example.

However, the configuration is not limited to those cases.

[0021] The memory unit 24 can store therein the train classification information 1D that has been transmitted by the information interface 22. Besides, the memory unit can
 10 also store therein, based on the train classification information 1D, the table 200 that includes the station code 201, the track code 202, the platform information 203, the door opening side 204, the platform train-car capacity 205 in a corresponding manner.

15 [0022] The ATS interface 21 can import the control information 2D that has been detected by the ATS on-train device 13.

[0023] The operation determining unit 23 receives the control information 2D from the ATS interface 21, checks
 20 the control information 2D against the table 200 stored in the memory unit 24, and outputs a signal for driving the left door opening-closing unit 25 or the right door opening-closing unit 26.

[0024] The left door opening-closing unit 25 or the
 25 right door opening-closing unit 26 is configured to output a door opening-closing signal 3D to the left door opening-closing device 50 or the right door opening-closing device 51, in the case when a crew member manipulates the switch 40 or the switch 41, and when conjunction is established
 30 between the signal transmitted by the switch 40 or the switch 41 and the signal transmitted by the operation determining unit 23. Therefore, when a crew member correctly performs the door opening-closing operation, the

left door opening-closing unit 25 or the right door opening-closing unit 26 outputs the door opening-closing signal 3D, which corresponds to the switch 40 or the switch 41, to the left door opening-closing device 50 or the right door opening-closing device 51, respectively. However, if a crew member makes an error in performing the door opening-closing operation, then the door opening-closing signal 3D is not output and the left door opening-closing device 50 or the right door opening-closing device 51 do not perform opening-closing control. A coil-type relay circuit is used in the left door opening-closing unit 25 and the right door opening-closing unit 26 illustrated in FIG. 1; however, the configuration is not limited to that case.

[0025] With the abovementioned configuration, upon receiving information transmitted by the ATS system 10, the support device 20 according to the first embodiment is able to identify the door opening side 204 using the station code 201 stored in the table 200 as the key code.

[0026] FIG. 3 is a diagram illustrating an example of contents of the ATS control information 2D. In the upper part in Fig. 3, contents 300a of the control information 2D include a synchronization flag 301 (8 bits), an information type 302 (6 bits), a driving direction 303 (2 bits), a track antenna number 304 (34 bits), individual information 305 (36 bits), a CRC 306 (16 bits), and a termination flag 307 (8 bits) in that order from the left side.

[0027] The information type 302 indicates the types of information handled by the transponder 12. For example, a stop aspect or a warning aspect is assigned to the information type 302. Besides, as the velocity limitations assigned are a divergence velocity limitation, a curvilinear velocity limitation, a gradient velocity

limitation, and a provisional velocity limitation are assigned. The CRC 306 (Cyclic Redundancy Check) is a code for detecting an error in data.

[0028] In the middle part in Fig. 3, the contents of individual information 300b are given for the case of divergence velocity limitation. The individual information 300b regarding the divergence velocity limitation includes free space 308 (3 bits), a limiting velocity 309 (5 bits), a limiting zone length 310 (8 bits), a distance to turnout 311 (10 bits), a line code 312 (4 bits), and a station code 313 (6 bits) in that order from the left side.

[0029] Herein, although the individual information 300b regarding the divergence velocity limitation includes the line code 312 and the station code 313, the support device 20 according to the first embodiment requires codes equivalent to the track code 202 in the table 200.

[0030] The free space 308 of 3 bits is available in the individual information 300b regarding the divergence velocity limitation. In the case of allocating that free space to the track code; it is necessary to secure 5 bits by taking into consideration, for example, large stations having many tracks.

[0031] 10 bits are allotted to the distance to turnout 311. If the calculation is done with the minimum resolution of 4 mm intervals, it is possible to obtain up to the total distance of 4092 m (4×1023 patterns).

Assuming that the actual velocity of a train is 130 km/h, it takes a distance of about 670 m to make a stop from that velocity upon application of the emergency brakes (in the case of usual deceleration of about 3.5 km/hr/sec). If the size of the distance to turnout 311 is changed to 8 bits; with the minimum resolution of 4 m, it is possible to obtain up to the travel distance of 1024 m (4×256 patterns)

at the time of applying the emergency brakes. That is, in the ground device 11, by changing the size of the distance to turnout 311 to 8 bits and by allotting the remaining 2 bits to the free space 308, it becomes possible to allocate that free space to the track code. As a result, as illustrated in the lower part in Fig. 3, in post-revision individual information 300c regarding the divergence velocity limitation, it is possible to include the line code 312 and the station code 313 as well as a track code 314.

[0032] Given below is the detailed description of operations performed by the support device 20 disposed at an interlocking station (i.e., at a station installed with a shunt). Fig. 4 is a schematic diagram of station yard wiring and a velocity check pattern P1 in an interlocking station. In Fig. 4, the passengers in a train A get off at a platform H1, a platform H2, or a platform H3. For example, if a train enters the station from the right side, the track thereof is a normal track 1L or a reverse track 2L; and if a train enters the station from the left side, the track thereof is a normal track 1R or a reverse track 2R.

[0033] The train A entering from the normal track 1L can make a stop at the platform H1. Moreover, the train A entering from the reverse track 2L or from the reverse track 2R can make a stop at the platform H2. Furthermore, the train A entering from the normal track 1R can make a stop at the platform H3. Meanwhile, the departure tracks from each platform for the train A are assumed to be a reverse track 3L, a normal track 4L, a normal track 3R, and a reverse track 4R.

[0034] In Fig. 4, the transponder 12 illustrated in Fig. 1 is disposed in plurality on each train line. Herein,

transponders S1 and S4 are disposed as protection against advancing blindly against a home signal 401 and as protection against excessive velocity at the divergence crossing; while transponders S2, S3, S5, and S6 are
5 disposed for performing platform halt control.

[0035] Assume that the train A moving in from the right side has the original travelling direction toward the platform H1, that is, on the normal track 1L, but train traffic rescheduling, which is performed while the train A
10 is moving, has forced a change from the normal track 1L to the reverse track 2L. In that case, the home signal 401 that is installed in the vicinity of the shunt for the normal track 1L and the reverse track 2L indicates a stop aspect for the normal track 1L and a warning aspect for the
15 reverse track 2L. Under that condition, when the train A passes over the transponder S1; the support device 20 receives the control information 2D containing the individual information 300c (warning aspect) via the ATS on-train device 13.

20 [0036] Upon receiving the control information 2D, the train A performs velocity control by creating the velocity check pattern P1 as illustrated in Fig. 4. Meanwhile, the operation determining unit 23 checks the control information 2D against the table 200 stored in the memory
25 unit 24, and determines the station code 201, the track code 202, the platform information 203, the door opening side 204, and the platform train-car capacity 205. Thus, the door opening side 204 can be identified before arriving at the platform H2.

30 [0037] Herein, since the doors on the right side with respect to the travelling direction of the train A are to be opened, the operation determining unit 23 outputs a signal for driving the right door opening-closing unit 26.

After the train A makes a stop and when the crew member presses the switch 41, conjunction is established thereby making it possible to output the door opening-closing signal 3D to the right door opening-closing device 51.

- 5 Herein, even if the crew member mistakenly presses the switch 40, no conjunction is established and thus the left door opening-closing device 50 does not operate.

[0038] Fig. 5 is an exemplary flowchart explaining a flow for the case when the train crew support device 20 decides on the door opening side. The support device 20 reads the control information 2D at a constant interval (Step S101). The operation determining unit 23 determines whether the line code 312, the station code 313, and the track code 314 are recorded in the control information 2D.

10 If that information is recorded (Yes at Step S102), then the operation determining unit 23 calls the table 200 stored in the memory unit 24 and identifies the platform information 203 and the door opening side 204, which correspond to the station code 201 and the track code 202 in the table 200 (Step S103). When the identified door opening side 204 is the left side (Left at Step S104) and when the crew member has pressed the switch 40 (Yes at Step S105), the operation determining unit 23 outputs the door opening-closing signal 3D to the left door opening-closing device 50 (Step S106). On the other hand, when the identified door opening side 204 is the right side (Right at Step S104) and when the crew member has pressed the switch 41 (Yes at Step S107), the operation determining unit 23 outputs the door opening-closing signal 3D to the right door opening-closing device 51 (Step S108).

20 25 30

[0039] Meanwhile, if the line code 312, the station code 313, and the track code 314 are not recorded in the control information 2D (No at Step S102), then the operation

determining unit 23 terminates the processing.

[0040] Moreover, when the identified door opening side 204 is the left side (Left at Step S104) but when the crew member has not pressed the switch 40 (No at Step S105),
5 then the operation determining unit 23 terminates the processing without outputting the door opening-closing signal 3D. Similarly, when the identified door opening side 204 is the right side (Right at Step S104) but when the crew member has not pressed the switch 41 (No at Step
10 S107), then the operation determining unit 23 terminates the processing without outputting the door opening-closing signal 3D.

[0041] As described above, the support device 20 according to the first embodiment receives the control
15 information 2D, which includes the individual information 300c having the codes revised by the reliable and existing ground device 11, and checks the individual information 300c against the table 200. Hence, information regarding the door opening side can be received without having to
20 install other ground devices. Moreover, even if train traffic rescheduling is performed just before a train makes a stop, the crew member can direct the passengers in a swift manner. Furthermore, it used to be the case that the train classification information set in a train at the
25 beginning gets overwritten by the use of a ground device thereby making software processing a complex task. However, herein, such processing can also be eliminated.

[0042] Second embodiment

In the support device 20 according to a second
30 embodiment, a station code and a track code are assigned to the individual information for the case of a stop aspect.

[0043] FIG. 6 is a diagram illustrating an example of contents of the control information 2D for the case of a

stop aspect. In the upper part in Fig. 6, contents 600a of the control information 2D are identical to the contents 300a of the control information 2D illustrated in FIG. 3.

[0044] In the middle part in Fig. 3 are given the
5 contents of individual information 600b regarding a stop aspect. The individual information 600b regarding a stop aspect includes free space 608 (2 bits), divergence pattern continuance 609 (1 bit), aspect code 610 (3 bits), free space 611 (2 bits), signal pattern correction 612 (3 bits),
10 maintenance information 613 (5 bits), distance to home signal 614 (10 bits), distance to subsequent turnout 615 (5 bits), and free space 616 (5 bits) in that order from the left side. Herein, the divergence pattern continuance 609 is information indicating that, if divergence velocity
15 limitation control is already underway, then it is to be continued.

[0045] Meanwhile, in the individual information 300b regarding the divergence velocity limitation, the free space 308 of 3 bits is available. In the case of
20 allocating that free space to the track code, it is necessary to secure 5 bits by taking into consideration, for example, large stations having many tracks.

[0046] Herein, the support device 20 according to the second embodiment requires codes equivalent to the station
25 code 201 and the track code 202 in the table 200 as well as requires a line code. Regarding the track code 202, the maintenance information 613 specified in the individual information 600b regarding a stop aspect corresponds to the track code 202. On the contrary, regarding a line code and
30 a station code, it is necessary to add codes using the free space 608, the free space 611, and the free space 616.

[0047] The station code and the line code require 6 bits and 4 bits, respectively. Since the free space 608, the

free space 611, and the free space 616 have a total of 9 bits; there is a shortage of 1 bit. In the individual information 600b regarding a stop aspect, 10 bits are allotted to the distance to home signal 614. Instead, 5 similar to the abovementioned description, if 8 bits are allotted to the distance to home signal 614; then it becomes possible to secure 2 bits. By allotting those 2 bits among the free space 608, the free space 611, and the free space 616; it becomes possible to allocate that free 10 space to the line code and the station code. Meanwhile, as described above, revision of the number of bits can be performed in the ground device 11. As a result, as illustrated in the lower part in Fig. 6, in post-revision individual information 600c regarding a stop aspect, it is 15 possible to include line code 619, station code 618, and track code 617.

[0048] Given below with reference to Fig. 4 is the detailed description of operations performed by the support device 20. Herein, assume that the train A moving in from 20 the right side has the original travelling direction toward the platform H1, that is, on the normal track 1L without being subjected to train traffic rescheduling while moving. In that case, the home signal 401 indicates a stop aspect for the normal track 1L. Under that condition, when the 25 train A passes over the transponder S1; the support device 20 installed in the train A receives the control information 2D including the individual information 600c (stop aspect) via the ATS on-train device 13.

[0049] The operation determining unit 23 checks the 30 control information 2D against the table 200 stored in the memory unit 24, and determines the station code 201, the track code 202, the platform information 203, the door opening side 204, and the platform train-car capacity 205.

[0050] Herein, since the doors on the left side with respect to the travelling direction of the train A are to be opened, the operation determining unit 23 outputs a signal for driving the left door opening-closing unit 25.

5 After the train A makes a stop and when the crew member presses the switch 40, conjunction is established thereby making it possible to output the door opening-closing signal 3D to the left door opening-closing device 50. Herein, even if the crew member mistakenly presses the
10 switch 41, no conjunction is established and thus the right door opening-closing device 51 does not operate. Meanwhile, since the sequence of operations performed by the support device 20 is identical to the flowchart illustrated in Fig. 5, the explanation thereof is not repeated.

15 [0051] As described above, the support device 20 according to the second embodiment receives the control information 2D, which includes the individual information 600c having the codes revised by the reliable and existing ground device 11, and checks the individual information
20 600c against the table 200. Hence, even in the case of making a stop at a non-interlocking station or at a stop having no diversions; it becomes possible to obtain exit information, to direct the passengers in a swift manner, and to eliminate software processing without having to
25 install ground devices.

[0052] Third embodiment

 The support device 20 according to a third embodiment is configured to transmit the train classification information 1D and the control information 2D received by
30 it to a support device 20a installed in each train car.

[0053] Fig. 7 is a diagram of an exemplary configuration of the train crew support device 20 according to the third embodiment and exemplary configurations of devices

connected to the train crew support device 20. For example, the support device 20 is installed in the first train car and the support device 20a is installed in every other train car other than the first train car.

5 [0054] The support device 20 is configured by additionally disposing a transmitting unit 27 in the support device according to the first embodiment. The support device 20a includes a memory unit 24a, a left door opening-closing unit 25a, a right door opening-closing unit
10 26a, an operation determining unit 23a, and a transmitting unit 27a. As compared to the support device 20, the support device 20a does not include the information interface 22 and the ATS interface 21.

[0055] The transmitting unit 27 and the transmitting
15 unit 27a are connected to a transmission path 100 that is laid across the train cars. For that reason, the train classification information 1D and the control information 2D imported by the support device 20 can be transmitted via the operation determining unit 23 to the operation
20 determining unit 23a in the support device 20a. Besides, in addition to importing the train classification information 1D and the control information 2D from the support device 20, the transmitting unit 27a can also relay that information to another train car.

25 [0056] The table 200 stored in the memory unit 24 or the memory unit 24a includes the information regarding the platform train-car capacity 205. That enables the operation determining unit 23 to compare the length of a platform of a station (train car capacity) with the length
30 of the train (number of train cars) making a stop. Then, for each train car, the operation determining unit 23 can determine whether the number of train cars is inside the train car capacity of that platform.

[0057] Fig. 8 is an exemplary flowchart explaining a flow for the case when the train crew support device 20 and the train crew support device 20a decide on the door opening side 204. Herein, as compared to the invention according to the first embodiment, the sequence of operations differs in that a step for determining the platform train-car capacity 205 is additionally performed. Meanwhile, although the following explanation is given with reference to the case of receiving the individual information 300c regarding the divergence velocity limitation, the explanation is also applicable to the case of receiving the individual information 600c regarding a stop aspect.

[0058] The support device 20 reads the control information 2D at constant intervals (Step S201). The operation determining unit 23 and the operation determining unit 23a determine whether the line code 312, the station code 313, and the track code 314 are recorded in the control information 2D. If that information is recorded (Yes at Step S202), then the operation determining unit 23 and the operation determining unit 23a call the table 200 stored in the memory unit 24 and the memory unit 24a, respectively, and identify the platform information 203 and the door opening side 204, which correspond to the station code 201 and the track code 202 in the table 200 (Step S203).

[0059] Subsequently, the operation determining unit 23 and the operation determining unit 23a determine whether the train cars are within the platform train-car capacity 205. When the car numbers in the train A are set in the ascending order (1, 2, n-1, n) from the travelling direction; if "car number" ≤ "platform train-car capacity 205" (Yes at Step S204), then the system control proceeds

to Step S205. However, if "car number">"platform train-car capacity 205" (No at Step S204), then the processing is terminated.

[0060] When the car numbers in the train A are set in
 5 the descending order (n, n-1, 2,1) from the travelling direction; if "number of train cars-car number"<"platform train-car capacity 205" (Yes at Step S204), then the system control proceeds to Step S205. However, if "number of train cars-car number"≥"platform train-car capacity 205"
 10 (No at Step S204), then the processing is terminated.

[0061] When the identified door opening side 204 is the left side (Left at Step S205) and when the crew member has pressed the switch 40 (Yes at Step S206), the operation determining unit 23 outputs the door opening-closing signal
 15 3D to the left door opening-closing device 50 (Step S207). On the other hand, when the identified door opening side 204 is the right side (Right at Step S205) and when the crew member has pressed the switch 41 (No at Step S208), the operation determining unit 23 outputs the door opening-closing signal 3D to the right door opening-closing device
 20 51 (Step S209).

[0062] Meanwhile, if the line code 312, the station code 313, and the track code 314 are not recorded in the control information 2D (No at Step S202), then the operation
 25 determining unit 23 terminates the processing.

[0063] Moreover, when the identified door opening side 204 is the left side (Left at Step S205) but when the crew member has not pressed the switch 41 (No at Step S206), then the operation determining unit 23 terminates the
 30 processing without outputting the door opening-closing signal 3D. Similarly, when the identified door opening side 204 is the right side (Right at Step S205) but when

the crew member has not pressed the switch 40 (No at Step S208), then the operation determining unit 23 terminates the processing without outputting the door opening-closing signal 3D.

5 [0064] As described above, according to the support device 20 and the support device 20a in the third embodiment, the control information 2D having the revised codes is transmitted to the support device 20a installed in each train car. Therefore, in each train car, the control
10 information 2D can be checked against the table 200. Hence, without having to install ground devices, it is possible to prevent accidental opening of doors of those train cars that are outside the train car capacity of the platform.

[0065] Fourth embodiment

15 The support device 20 according to a fourth embodiment is configured in such a way that, upon receiving the control information, the passengers in the train are notified about the side at which the doors would open.

[0066] Fig. 9 is a diagram of an exemplary configuration
20 of the train crew support device 20 according to the fourth embodiment and exemplary configurations of devices connected to the train crew support device 20.

[0067] The support device 20 is configured by additionally disposing a train information providing device
25 interface (hereinafter, simply referred to as "interface") 28 in the support device according to the first embodiment.

[0068] The support device 20a includes the memory unit 24a, the operation determining unit 23a, the transmitting unit 27a, and an interface 28. As compared to the support
30 device 20, the support device 20a does not include the information interface 22 and the ATS interface 21.

[0069] Although the switch 40, the switch 41, the left door opening-closing device 50, and the right door opening-

closing device 51 are not illustrated; each of the support device 20 and the support device 20a includes those elements in an identical manner to that in the first and the third embodiments.

5 [0070] A train information providing device 70 and a train information providing device 70a perform processing of station information and processing of expected time of arrival, and transmit the latest track information to a passenger compartment indicator 71 and a passenger
10 compartment indicator 71a, respectively. Since the information regarding train operation can also be displayed on the passenger compartment indicator 71 and the passenger compartment indicator 71a, it is possible to inform, while the train is moving, the side at which the doors would open
15 next time.

[0071] The interface 28 and the interface 28a are respectively connectable to the train information providing device 70 and the train information providing device 70a. Besides, for example, each of the interface 28 and the
20 interface 28a includes a connection port for LAN or RS422, although the configuration is not limited to those cases.

[0072] In an identical manner to the third embodiment, the support device 20a installed in each train car can import the train classification information 1D and the
25 control information 2D through the transmission path 100. Thus, in each train car, the operation determining unit 23a can determine whether the corresponding train car is within the platform train-car capacity 205 and output the determination result on the passenger compartment indicator
30 71a.

[0073] As described above, according to the support device 20 and the support device 20a in the fourth embodiment, the control information 2D having the revised

codes is transmitted to the support device 20a installed in each train car when the train A passes over the transponder 12. Thus, even if train traffic rescheduling is performed just before a train makes a stop and even if the crew member is not in a position to direct the passengers in a swift manner, the door opening side can be notified in an automatic manner.

[0074] Meanwhile, in place of the train information providing device 70 and the passenger compartment indicator 71, an indicator light can be installed on the cab for notifying the door opening side 204. By connecting the interface 28 to that indicator light, the crew member can easily determine the door opening side upon receiving the control information 2D.

15

INDUSTRIAL APPLICABILITY

[0075] In this way, the present invention is applicable to a support device for supporting train crew in performing a door opening-closing operation and is particularly suitable as an invention for obtaining information regarding the door opening side in a prompt manner without having to install ground devices.

20

CLAIMS

1. A train crew support device equipped with a door opening-closing signal output unit for controlling a door opening-closing device of a train in response to a door opening-closing operation performed by a crew member, the train crew support device comprising:
- a train classification information interface that imports, from a train number setting device, train number classification information that includes a line code indicating a travelling line of a train, a station code indicating a stop, a track code indicating a train track, platform information indicating a platform direction, a door opening-closing side, and a platform train-car capacity;
 - an ATS interface that imports, from an ATS system, ATS control information that includes the line code, the station code, and the track code;
 - a memory unit that stores the train number classification information; and
 - an operation determining unit that checks the line code, the station code, and the track code included in the ATS control information against the train number classification information, identifies a door opening side of corresponding train, and outputs a door opening-closing signal to the door opening-closing signal output unit.
2. The train crew support device according to claim 1, wherein
- the ATS control information is individual information regarding a warning aspect which incorporates the line code, the station code, and the track code.
3. The train crew support device according to claim 1,

wherein

the ATS control information is individual information regarding a stop aspect which incorporates the line code, the station code, and the track code.

5

4. The train crew support device according to any one of claims 1 to 3, wherein

the operation determining unit includes a transmitting unit for receiving the ATS control information and the
10 train number classification information through a transmission path laid across train cars, and outputs the door opening-closing signal based on a platform train-car capacity and a number of train cars.

15 5. The train crew support device according to claim 4, wherein

the operation determining unit includes a train information providing device interface that outputs information, which indicates a door opening side, to a
20 train information providing device connected to an indicator in corresponding train, and outputs the door opening-closing signal to the train information providing device interface.

25 6. The train crew support device according to claim 5, wherein

the train information providing device interface outputs the door opening-closing signal to a door opening side indicator light installed on a cab.