

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2004 (06.05.2004)


PCT

(10) International Publication Number
WO 2004/038916 A3

- (51) International Patent Classification⁷: **H03J 3/18**, B81B 3/00, H01G 5/16
- (21) International Application Number: PCT/EP2003/012399
- (22) International Filing Date: 18 September 2003 (18.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 10/278,211 22 October 2002 (22.10.2002) US
- (71) Applicant (for all designated States except MC): **INTERNATIONAL BUSINESS MACHINES CORPORATION** [US/US]; New Orchard Road, Armon, NY 10504 (US).
- (71) Applicant (for MC only): **COMPAGNIE IBM FRANCE** [FR/FR]; Tour Descartes - La Defense 5, 2, avenue Gambetta, F-92400 Courbevoie (FR).
- (72) Inventors: **CHINTHAKINDI, Anil, K.**; Seven Green Hill Dr., Apt.34E, Fishkill, NY 12524 (US). **GROVES, Robert, A.**; 27 Oak Crest Drive, Highland, NY 12528 (US). **STEIN, Kenneth, J.**; 3 Harvest Common, Sandy Hook, CT 06482 (US). **SUBBANNA, Seshadri**; 105 Coventry Lane, Brewster, NY 10509 (US). **VOLANT, Richard, P.**; 16 Fulton Drive, New Fairfield, CT 06812 (US).
- (74) Agent: **KLEIN, Daniel**; Compagnie IBM France, Direction de la Propriété Intellectuelle, F-06610 La Gaude (FR).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: MICRO-ELECTROMECHANICAL VARACTOR WITH ENHANCED TUNING RANGE



(57) Abstract: A three-dimensional micro-electromechanical (MEM) varactor is described wherein a movable beam (50) and fixed electrodes (51) are respectively fabricated on separate substrates coupled to each other. The movable beam with comb-drive electrodes are fabricated on the "chip side" while the fixed bottom electrode is fabricated on a separated substrate "carrier side". Upon fabrication of the device on both surfaces of the substrate, the chip side device is diced and "flipped over", aligned and joined to the "carrier" substrate to form the final device. Comb-drive (fins) electrodes are used for actuation while the motion of the electrode provides changes in capacitance. Due to the constant driving forces involved, a large capacitance tuning range can be obtained. The three dimensional aspect of the device avails large surface area. When large aspect ratio features are provided, a lower actuation voltage can be used. Upon fabrication, the MEMS device is completely encapsulated, requiring no additional packaging of the device. Further, since alignment and bonding can be done on a wafer scale (wafer scale MEMS packaging), an improved device yield can be obtained at a lower cost.

WO 2004/038916 A3



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:
12 August 2004

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.