

METHOD AND DEVICE FOR RELEASING A PERFUME OR SCENT

The invention relates to the field of perfumes, scents and fragrances, and more particularly a new delivery of
5 an aromatic or fragrant composition designed to perfume or scent a base product, initially contained in a package.

There is a certain number of situations in which a base
10 product cannot be perfumed before its final packaging; for example, because the base product is incompatible with the aromatic or fragrant composition, or because the mixture of the base product and the aromatic or
15 fragrant composition adversely affects the stability of the base product; or else because the aromatic or fragrant composition is unstable; or else because it is not desired that the whole of the packaged base product is perfumed or scented, for reasons that may be medical, cosmetic or quite simply for reasons of taste.

20 For example, in cosmetics, the smell of ammonia involved in the composition of hair colorants is a disagreeable smell that requires being masked. Hair colorants usually consist of two preparations that are
25 designed to be mixed extemporaneously just before use. The first preparation contains alkaline agents, such as ammonia or aminated alkaline agents, which allow the hair to swell, which helps with the penetration of the pigment; the second preparation contains oxidizing
30 agents, for example hydrogen peroxide. Particularly because of the extreme volatility of ammonia, the masking of this unpleasant smell is difficult and is the subject of much research (see for example EP1346720). Another difficulty arises from the fact
35 that the perfumes likely to mask this smell of ammonia are not always compatible with the alkalinity of the ammonia-containing composition in question, and this incompatibility makes the masking of the smell of the ammonia yet more difficult. Patent JP2004067598

proposes that the odorizing agent that is capable of masking the smell of ammonia and that is unstable in ammonia be incorporated into the hydrogen peroxide composition to be mixed extemporaneously with the ammonia-containing composition.

In agribusiness, it is often desired to scent a product in order to create or increase a pleasant aroma or to add an aroma of freshness to a product. For example, EP 1 056 660 describes a drink receptacle cap which contains a segment molded in a synthetic material impregnated with a perfume, which diffuses the perfume so that the person perceives an aroma when he drinks.

In general, the prior art recommends, to mask a smell, creating a homogeneous mixture between the composition with the unpleasant smell and the masking agent. The inventors have now shown that, surprisingly, the masking of a smell and in particular of a very volatile smell, is more effective by deceiving, particularly by saturating, the gustatory or olfactory receptors of the user with the aid of a masking agent available through its inhomogeneous mixture with the base product, rather than with the aid of the same agent mixed homogeneously with the base product.

The object of the invention is particularly to mask or modify the olfactory or gustatory sensation generated by a base product in a user.

An objective of the invention is also to make it possible to perfume or scent a desired quantity of a base product contained in a package, without perfuming the rest of the product contained in the package. Another objective of the invention is to make it possible to perfume or scent successively small quantities of a base product extracted from a package with different aromas or perfumes or fragrances.

Another objective of the invention is to make it possible to perfume and/or scent a base product with a perfume or a scent that is generally considered to be incompatible with said base product or that is unstable in the base product, or that makes the base product unstable.

A particular objective of the invention is to cover or mask the smell of ammonia of a hair formulation, preferably of a permanent hair formulation, by using a perfume that is unstable or incompatible with one and/or the other of the two bases comprising said hair composition.

Within the meaning of the present invention, "unstable" means that the homogeneous mixture of said perfume or scent with the base product results in a significant modification of the organoleptic characteristics of said mixture.

Within the meaning of the present invention, "incompatible" means that the aromatic or fragrant composition cannot coexist with the base product for chemical reasons, for example because the coexistence induces structural modifications of the aromatic or fragrant composition or of the base product, for physical reasons, for example because the coexistence induces an undesirable change of solubility or a rheological modification of the base product, and/or for organoleptic reasons, in particular because of the possible formation of damaging products that are olfactorily or gustatorily undesirable.

"Package" within the meaning of the present invention means a receptacle in which the base product can be stored, and from which it can be extracted, expressed, taken out or poured, for its use, particularly by means

of a delivery end-piece. Advantageously, the package is a bottle, in particular a flexible bottle that can be pressed in the hand to extract the product, a syringe, a tube, an aerosol or a pump. Advantageously, the package may be of the "airless" type or else a device of the type marketed under the brand SEMKIT™, or a package of the Mixpac™ System 25 type marketed by Mixpac or any package that those skilled in the art can adapt.

10

"Base product" within the meaning of the present invention means in particular a formulation to be perfumed or scented or whose smell must be masked, said formulation being able to be in fluid form, particularly cream, milk, lotion, gel, unguent, ointment, emulsion, gas, solid dispersion, liquid dispersion.

The invention therefore relates to a method for masking or modifying the olfactory or gustatory sensation generated in a user by a base product, characterized in that an aromatic or fragrant composition is released in a manner sequenced over time relative to the release of the base product, said aromatic or fragrant composition being contained in at least one breakable reservoir capable of releasing said composition at the desired moment(s). Advantageously, this reservoir comprises a breakable casing and a core comprising or consisting of said aromatic or fragrant composition; therefore, the casing encapsulates the volatile aromatic or fragrant composition and releases said composition when it is broken. Advantageously, this reservoir is a capsule, preferably as defined below.

According to a particular embodiment of the invention, the aromatic or fragrant composition forming the core and encapsulated in the casing is unstable and/or incompatible with the base product.

The release of the base product is a process that is capable of being spread over time. According to a preferred embodiment of the invention, a determined
5 quantity of the base product is released. This determined quantity may be hereinafter indicated by the word "dose".

"Release of the base product" means the extraction of
10 the base product, or of a dose of base product, from its package.

According to a first embodiment of the method according to the invention, at least one aromatic or fragrant
15 composition contained in at least one reservoir is released before the start of the release of a base product.

According to a second embodiment of the method
20 according to the invention, at least one first aromatic or fragrant composition contained in at least one reservoir is released by breaking said reservoir before the start of the release of the base product, and at least one second aromatic or fragrant composition,
25 identical to or different from the first, contained in at least one other reservoir is released by breaking said reservoir at any moment during the release of a determined quantity of base product.

30 According to a third embodiment of the method according to the invention, at least one aromatic or fragrant composition contained in at least one reservoir is released by breaking said reservoir at any moment during the release of a desired quantity of the base
35 product.

According to a fourth embodiment of the method according to the invention, a first aromatic or

fragrant composition contained in at least one reservoir is released by breaking said reservoir at any moment during the release of the base product, and at least one second aromatic or fragrant composition, identical to or different from the first, contained in at least one other reservoir is released by breaking said reservoir after the end of the release of the desired quantity of base product.

10 According to a fifth embodiment of the method according to the invention, at least one aromatic or fragrant composition is released after the end of the release of the base product.

15 Within the meaning of the present invention, "before the release of the base product" relates to a time lag preceding the start of the release of the base product, going from 0.1 to 15 seconds, preferably 0.5 to 5 seconds, very preferably from 0.8 to 2 seconds.

20 Within the meaning of the present invention, "during the release of the base product" relates to the time lag necessary for the release of some or all of a dose of the base product.

25 Within the meaning of the present invention, "after the end of the release of the base product" relates to a time lag following the end of the release of the base product, going from 0.1 to 15 seconds, preferably 0.5 to 5 seconds, very preferably from 0.8 to 2 seconds.

30 According to a first embodiment of the invention, the base product according to the invention contains at least one main active pharmaceutical ingredient, a pharmaceutical composition or a medication.

According to a second embodiment of the invention, the base product contains at least one active cosmetic

ingredient, and preferably is a cosmetic care cream, a hair product of the shampoo type or a hair coloring product, or a product for depilatory purposes of the depilatory cream type.

5

According to a third embodiment, the base product is a food, agribusiness, nutraceutical or dietetic product, preferably yogurt, sauce or drink.

10 According to a fourth embodiment, the base product is a hygiene product, in particular personal hygiene, particularly by mouth, domestic hygiene or industrial hygiene, particularly a detergent, fabric softener, a bactericide.

15

According to a fifth embodiment, the base product is an insecticide product or an active phytopharmaceutical ingredient.

20 The invention also relates to a device for applying the above method.

According to a particular embodiment, the object of the invention is a device comprising an aromatic or
25 fragrant composition contained in a reservoir, said composition being designed to perfume or scent some or all of a base product contained in a package, and any appropriate means of breaking said reservoir before the release of a desired quantity of base product, before
30 and during the release of some or all of the desired quantity of the base product, during some or all of the release of a desired quantity of base product, during and/or after the end of the release of the desired quantity of base product.

35

Advantageously, the device comprises an aromatic or fragrant composition designed to perfume or scent some or all of a base product extracted from a package, said

device being adaptable to the orifice for extraction of the base product from said package, comprising an orifice for releasing the aromatic or fragrant composition and the base product, where necessary mixed together, and comprising said aromatic or fragrant composition contained in at least one reservoir (5).

"Device that can be adapted to the orifice for extraction from a package", within the meaning of the present invention, means a device comprising adaptation means, particularly screwing, clipping, bonding, interlocking, crimping means compatible with the structure of the orifice for extraction from the package.

Advantageously, the device according to the invention is an end-piece that can be adapted to the orifice for extraction of the base product from the package, containing at least one reservoir of aromatic or fragrant composition. According to a particular embodiment, the device of the invention is characterized in that said device comprises at one of its ends a female portion that can be adapted to an orifice for extraction from the package consisting of a male end-piece and, at another distal end, an orifice for extraction of the volatile aromatic or fragrant composition and of the base product, where necessary mixed together.

Advantageously, each reservoir contained in the device of the invention comprises a breakable casing and a core comprising or consisting of said volatile aromatic or fragrant composition and the aromatic or fragrant composition is released by breaking this casing. Preferably, this reservoir is a capsule. Preferably, the casing of the reservoir is broken at a pressure greater than 1 kg, preferably lying between 1 and 2.5 kg.

Preferably, the reservoir (5) is broken either by the placing in contact of the reservoir (5) and of the base product (7) extracted from the package, or by the
5 actuation of a means for breaking the casing that may or may not be contained in the device of the invention.

According to a first embodiment, the breakage of the casing of the reservoir results from the placing in
10 contact of the reservoir and of the base product extracted from the package. In this embodiment, the casing is broken either by the product, by a chemical action, or under the effect of the passage of the product.

15 According to a second embodiment, the casing is broken manually by the user of the device; the breakage of the reservoir then results from the mechanical action applied by the user on the reservoir.

20 According to a third embodiment, the casing is broken by a means for breaking the casing, said breaking means being contained in the device of the invention. According to a particular embodiment of the invention,
25 this breaking means may be of the needle type, for example actuated by a piston, or else of the type in particular of a shearing means, preferably of the static mixer type, of a baffle, of a convergent means, of an abrasive coating, of an abutment.

30 According to one embodiment of the invention, the device of the invention can be adapted to the orifice that makes it possible to extract the base product from its package.

35 Advantageously, the device of the invention comprises a means for releasing the aromatic or fragrant composition and the base product, and optionally a

means for mixing said aromatic or fragrant composition with the base product. Advantageously, this releasing means is an extraction orifice situated at a distal end of the device relative to its end that can be adapted
5 to the orifice for extraction from the package.

According to a particular embodiment, the device of the invention is a device for sequenced release of at least one aromatic or fragrant composition and of the base
10 product, wherein the aromatic or fragrant composition is released before the start of the release of the product. In this embodiment, at least one of the reservoirs contained in the device is broken before the product is delivered to the user. This embodiment has
15 the advantage of releasing the volatile product before the user of the base product has been in contact with the smell or the scent of the base product; therefore, the first olfactory or gustatory sensation of the user is that provided by the content of the broken
20 reservoir. In a preferred variant of this embodiment, the device does not comprise a means for mixing the aromatic or fragrant composition with the base product.

According to a second particular embodiment, the
25 aromatic or fragrant composition is released before the start of the release of the product, and also during the release of the base product. In this embodiment, at least one of the reservoirs contained in the device is broken before the product is delivered to the user, and
30 at least one other reservoir is broken during the release of the base product, either by mechanical action, or by chemical action of the base product on the casing of the reservoir. In this embodiment, the first olfactory or gustatory sensation of the user is
35 that provided by the content of the first broken reservoir(s) and this sensation is prolonged during some or all of the release of the base product by the breakage of other reservoirs, thereby masking the

sensation that would have been generated by the release of said base product that is neither scented nor perfumed.

- 5 According to a third particular embodiment, the aromatic or fragrant composition is released by breaking at least one reservoir during the release of the base product, for a direct action of masking the scent or the taste of the base product. In a preferred
10 variant of this embodiment, the device comprises a means for mixing the aromatic or fragrant composition with the base product.

- According to a fourth particular embodiment, the
15 aromatic or fragrant composition is released during the release of the base product and at least one reservoir is broken after the end of the release of the desired quantity of the base product. This embodiment has the advantage of directly masking the scent or the taste of
20 the base product, and of continuing this masking action by prolonging the olfactory or gustatory sensation of the user with the aromatic or fragrant composition contained in the device.

- 25 According to a fifth particular embodiment, no reservoir is broken before or during the release of the base product, and at least one reservoir is broken after the end of the release of the desired quantity of the base product. This embodiment has the advantage of
30 modifying or masking the olfactory or gustatory sensation of the user with the aromatic or fragrant composition contained in the device. This fifth embodiment is particularly preferred for the masking of the smell of a base product containing ammonia. In this
35 embodiment, the base product is not likely to chemically break the casing of the reservoir.

According to one embodiment, the aromatic or fragrant composition is unstable and/or incompatible with said base product (7).

5 Finally, the subject of the invention is a product obtained by the method mentioned hereinabove, characterized in that it comprises an inhomogeneous, that is to say not intimate, mixture of a base product and of an aromatic or fragrant composition, the
10 aromatic and fragrant composition and the base product being compatible or incompatible.

According to a preferred embodiment of the invention, the device of the invention is a single-use device.

15

A further subject of the invention is a device placed on a package of base product, in a movable or immovable manner.

20 Finally, the subject of the invention is a method for perfuming or scenting successively a base product (7) contained in a single package with different aromatic or fragrant compositions, in which a first device (1) according to the invention, comprising a first aromatic
25 or fragrant composition, is adapted to the package, and a first dose of a base product is extracted, then at least one second device (1) according to the invention, comprising a second aromatic or fragrant composition, is adapted to said package, if necessary after removal
30 of the first device (1), and at least one second dose of said base product is extracted.

"Capsule", within the meaning of the present invention, means any device that can serve as a reservoir or a
35 means for storing a scent or an aromatic composition, irrespective of its size or shape. Advantageously, the word "capsule" relates to a device comprising a casing and a core; preferably the thickness of the casing lies

between approximately 30 and approximately 100 μm , preferably from 50 to 65 μm . Preferably the casing represents from 2 to 30% of the weight of the capsule, preferably from 2.5 to 20%, advantageously from 3 to 8%. The core of the capsule comprises a scent or an aromatic or fragrant composition, that preferably consists of a mixture of molecules that are hydrophobic or partially soluble in ethanol or molecules placed in the form of water/oil, oil/water, oil/water/oil emulsion; preferably, the core consists of aromatic compositions, particularly the aromatic, terpene-based and/or sesquiterpene-based hydrocarbons and more particularly the essential oils, alcohols, aldehydes, phenols, carboxylic acids in their various forms, ethers and aromatic acetals, nitrous heterocycles, ketones, sulfurs, aromatic disulfides and mercaptans. It may also comprise one or more molecules or extracts for cosmetic, pharmaceutical, food or other use, depending on the envisaged application. According to a particular embodiment of the invention, the core of the capsule contains a solvent comprising triglycerides, particularly caprylic and capric acid triglycerides, triglyceride mixtures of the vegetable oil type, olive, sunflower, maize, peanut, grapeseed, wheatgerm oil, mineral oils and silicone oils; the quantity of lipophilic solvent in the core of a capsule used according to the invention is of the order of 0.01 to 90% of the weight of the capsule, preferably from 25 to 75%; the core may also comprise one or more agents called weights as used in aromatic emulsions, of the damar gum type, ester gum type wood resins, saccharose acetoisobutyrate (SAIB) or brominated vegetable oils. The function of these weights is to adjust the density of the liquid core. The core may also comprise one or more sweeteners, which may be provided in the form of a solution or suspension in ethanol. Not exclusively, these include aspartame, NHDC, sucralose, acesulfame, neotame. The core may also comprise one or more

aromatic agents called sensate, which provide either a refreshing effect or a hot effect in the mouth. These include in particular as a refreshing agent, menthyl succinate and its derivatives, particularly Physcool®
5 marketed by the Applicant. Mention will be made as a hot effect agent of vanillyl ethyl ether. The present invention also includes, in the word capsule, spherical capsules and nonspherical capsules, several millimeters in diameter or several microns in diameter. The
10 capsules used according to the invention are preferably hard to the touch, and may break under the effect of a mechanical force, for example a pressure, or under the effect of a means of chemical breakage. Preferably, the capsules according to the invention have a hardness of
15 the order of 1 to 5 kg/cm². According to one embodiment, the capsule used according to the invention is spherical or substantially spherical, preferably perfectly spherical. It has a variable diameter, preferably from 1 to 7 mm in diameter. This diameter
20 will depend on the use and may be easily chosen by those skilled in the art. The weight of a capsule according to the invention is variable, it may be from 0.5 to 170 mg. In a preferred embodiment, the capsule according to the invention has a diameter of 4.5 to
25 5.5 mm, and a weight of 45 to 80 mg. According to a preferred embodiment, the capsule is as described in EP1455596, included here as reference. According to another embodiment, the capsule used in the device according to the invention is a capsule whose casing
30 contains gellan or gelatine or any appropriate material, and preferably a capsule as described in international patent application PCT/EP05/09226, and a core formed of a volatile aromatic or fragrant composition. According to yet another embodiment, the
35 capsule used in the device according to the invention is of the type of those described in international patent application PCT/EP05/09227, and in particular a humidity-resistant capsule; advantageously, the casing

of the capsule is covered with a coating of the ethylcellulose type.

The invention will be better understood on reading the following detailed examples, which illustrates in a nonlimiting manner a particular embodiment of the invention and is read with respect to figure 1.

Figure 1 represents a profile view of a device 1 according to the invention and of a package 2 of the base product.

The device 1 according to the invention, which may have any shape and is not limited to the graphic representation of figure 1, comprises reservoirs 5. In the embodiment of figure 1, these reservoirs are capsules consisting of a casing 6 and a core consisting of the aromatic or fragrant composition.

A base product 7 is situated in the package 2. This package 2 comprises an extraction orifice 3, or end-piece, capable of delivering the base product for the purpose of its use. The device 1 comprises an end 4 that can be adapted to the extraction orifice 3. The user may manually adapt the device 1 to the end-piece 3. According to a particular embodiment of the invention, not shown, the device 1 is attached to the end-piece 3 prior to the use of the base product.

When carrying out the manipulations necessary to deliver the base product, the user expresses the base product 7 from the package 2 via the end-piece 3 on which the device 1 is placed. The product expressed through the end-piece 3 comes into contact with the capsules 5. The capsules break under the mechanical action of the base product 7 that is propelled by the user into contact with the capsules 5 with sufficient pressure to break them, or under the chemical effect of

- 16 -

solubilization of the casing by the base product, or under the effect of a breaking means present in the device, or under the effect of the mechanical pressure of the user on the device. Some or all of the capsules
5 5 may break. The capsules 5 may break simultaneously or successively. When they break, they release the aromatic or fragrant composition that they contain, which can mix with the base product 7. In a particular embodiment of the invention, not shown, the device 1
10 comprises a means of mixing the base product and the aromatic or fragrant composition, said means of mixing comprising mixture elements. Depending on the number and size of the mixture elements, a more or less homogeneous mix is obtained, which allows those skilled
15 in the art to obtain the desired effect of coverage or perfuming.

Example 1:

20 A simple bayonet static mixer of the MA STATOMIX type made of polypropylene marketed by MIXPAC Systems, furnished with mixture elements, is used. The mixture elements are cut so as to be able to cause the breakable capsules marketed by MANE to enter in the
25 desired quantity, namely the sufficient quantity to obtain a dose of perfume identical to that which would be used in a commercial intimate mixture product. The identification of this dose is within the competence of those skilled in the art.

30

The hair coloring product is prepared in a flexible plastic bottle with a sectile cap of the type marketed by l'Oréal for its Excellence Crème™ products of l'Oréal Paris™, or by Henkel for Schwartzkopf Vision
35 Color Relief™, or else by Clairol for Perfect Blondes™, by Eugène Perma for Eugène Color™ or Keranove™, and by Mandom for Gatsby™. The hair coloring product is obtained by mixing the ammonia-

- 17 -

containing base on the one hand and the oxidizing portion on the other hand, then stirring the mixture. The sectile cap is cropped, and the bottle then becomes a package of the base product of which the hair coloring mixture is made. Before delivery, the static mixer furnished with the capsules is adapted to the end-piece thus opened.

The mixture of base product is expressed from the flexible plastic bottle or boiling vessel by pressure on the walls of said bottle. The mixture comes into contact in the mixer with the capsules. Under the pressure of the product, the capsules break successively when the product passes. The base product and the liquid perfume released by the capsule are sheared by the mixture elements and then expressed.

Example 2

A static mixer of the MA STATOMIX type made of polypropylene marketed by MIXPAC Systems, furnished with capsules containing an aromatic or fragrant composition, is adapted to the end-piece of a MIXPAC Systems S25 pistol furnished with 50 ml two-compartment cartridges. Each portion of the formulation is present in its compartment; it is sufficient to connect the device (twist-lock) and to install the cartridge in the pistol furnished with the button corresponding to the chosen cartridge. The pressure on the trigger of the pistol actuates the pistons which inject the two portions of the formulation into the device of the invention. The advantage provided by the use of the pistol is to be able to use products with a very viscous base.

CLAIMS

1. A method for masking or modifying the olfactory or gustatory sensation generated in a user by a base product (7) contained in a package (2), characterized in that a device (1) is placed in a removable manner on the orifice for extraction from said package (2), an aromatic or fragrant composition contained in at least one breakable reservoir (5) situated in said device is released in a manner sequenced over time relative to the release of said base product (7).
2. The method as claimed in claim 1, characterized in that said reservoir (5) comprises a breakable casing (6) and a core comprising or consisting of said aromatic or fragrant composition.
3. The method as claimed in either one of claims 1 or 2, characterized in that said reservoir (5) is a capsule.
4. The method as claimed in either one of claims 1 or 3, characterized in that said aromatic or fragrant composition is unstable and/or incompatible with said base product (7).
5. The method as claimed in any one of claims 1 to 4, characterized in that at least one aromatic or fragrant composition contained in at least one reservoir (5) is released by breaking said reservoir (5) before the start of the release of the base product (7).
6. The method as claimed in any one of claims 1 to 4, characterized in that at least one first aromatic or fragrant composition contained in at least one

- reservoir (5) is released by breaking said reservoir (5) before the start of the release of the base product (7), and at least one second aromatic or fragrant composition, identical to or different than the first, contained in at least one other reservoir (5) is released by breaking said reservoir (5) at any moment during the release of a determined quantity of base product.
- 10 7. The method as claimed in any one of claims 1 to 4, characterized in that at least one aromatic or fragrant composition contained in at least one reservoir (5) is released by breaking said reservoir (5) at any moment during the release of a desired quantity of the base product (7).
- 15 8. The method as claimed in any one of claims 1 to 4, characterized in that at least one first aromatic or fragrant composition contained in at least one reservoir (5) is released by breaking said reservoir (5) at any moment during the release of the base product (7), and at least one second aromatic or fragrant composition, identical to or different from the first, contained in at least one other reservoir (5) is released by breaking said reservoir (5) after the end of the release of the desired quantity of base product.
- 20 9. The method as claimed in any one of claims 1 to 4, characterized in that at least one aromatic or fragrant composition contained in at least one reservoir (5) is released by breaking said reservoir (5) after the end of the release of the desired quantity of the base product (7).
- 25 10. The method as claimed in any one of claims 1 to 9, characterized in that said base product (7) is in fluid form, particularly cream, milk, lotion, gel,
- 35

- 20 -

unguent, ointment, emulsion, gas, solid dispersion, liquid dispersion.

11. The method as claimed in any one of claims 1 to 10, characterized in that said base product (7) contains at least one main active pharmaceutical ingredient, a pharmaceutical composition or a medication.
12. The method as claimed in any one of claims 1 to 10, characterized in that said base product (7) contains at least one active cosmetic ingredient, and preferably is a cosmetic care cream, a hair product of the shampoo type or a hair coloring product, or a depilatory cream.
13. The method as claimed in any one of claims 1 to 10, characterized in that said base product (7) is a food, agribusiness, nutraceutical or dietetic product, preferably yogurt, sauce or drink.
14. The method as claimed in any one of claims 1 to 10, characterized in that said base product (7) is a hygiene product, in particular personal hygiene, particularly by mouth, domestic hygiene or industrial hygiene, particularly a detergent, fabric softener, a bactericide.
15. The method as claimed in any one of claims 1 to 10, characterized in that said base product (7) contains at least one active phytopharmaceutical ingredient or an insecticide.
16. A device (1) capable of being placed in a removable manner on an orifice for extraction from a package (2) comprising a base product (7), said device (1) comprising at least one aromatic or fragrant composition contained in at least one

breakable reservoir (5) and an appropriate means of breaking said reservoir (5).

17. The device (1) as claimed in claim 16, said device
5 (1) being adaptable to an orifice (3) for extraction of the base product (7) from said package, and comprising an orifice (8) for releasing the aromatic or fragrant composition and/or the base product, where necessary mixed
10 together.
18. The device (1) as claimed in one of claims 16 or 17, wherein said reservoir (5) comprises a breakable casing and a core comprising or
15 consisting of said aromatic or fragrant composition.
19. The device (1) as claimed in any one of claims 16 to 18, wherein said reservoir (5) is a capsule.
20
20. The device (1) as claimed in any one of claims 16 to 19, characterized in that the reservoir (5) is broken either by the placing in contact of the reservoir (5) and of the base product (7)
25 extracted from the package, or by a mechanical action applied by the user, or by the actuation of a means of breaking the casing contained in the device of the invention, of the type in particular of a shearing means, preferably of the static
30 mixer type, of a baffle, of a convergent means, of an abrasive coating, of an abutment.
21. The device (1) as claimed in any one of claims 16 to 20, characterized in that it comprises a means
35 for mixing said aromatic or fragrant composition with said base product (7).

22. The device (1) as claimed in any one of claims 16 to 21, wherein said aromatic or fragrant composition is unstable and/or incompatible with said base product (7).
- 5
23. The device (1) as claimed in any one of claims 16 to 22, characterized in that said base product (7) is in fluid form, particularly cream, milk, lotion, gel, unguent, ointment, emulsion, gas, solid dispersion, liquid dispersion.
- 10
24. The device (1) as claimed in any one of claims 16 to 23, characterized in that the base product (7) contains at least one main active pharmaceutical ingredient, a pharmaceutical composition or a medication; or at least one active cosmetic ingredient, for the purpose of treatment or for hair, particularly of the shampoo type or hair coloring product, or of the depilatory cream type; or the base product (7) is a food, agribusiness, nutraceutical or dietetic product; or the base product (7) is a hygiene product, in particular personal hygiene, particularly by mouth, domestic hygiene or industrial hygiene, particularly a detergent, fabric softener, a bactericide; or the base product (7) contains a phytopharmaceutical product or an insecticide.
- 15
25. The device (1) as claimed in any one of claims 16 to 24, characterized in that it is a single-use device (1).
- 20
26. A method for perfuming or scenting successively a base product (7) contained in a single package with different aromatic or fragrant compositions, in which a first device (1) as claimed in any one of claims 16 to 25, comprising a first aromatic or fragrant composition, is adapted to the package,
- 25
- 30
- 35

- 5 and a first dose of a base product is extracted,
then at least one second device (1) as claimed in
any one of claims 16 to 25, comprising a second
aromatic or fragrant composition, is adapted to
said package, if necessary after removal of the
first device (1), and at least one second dose of
said base product is extracted.
- 10 27. A product obtained via a method as claimed in any
one of claims 1 to 15, characterized in that it
comprises an inhomogeneous mixture of a base
product and of an aromatic or fragrant composition
that is unstable or incompatible with said base
product.