Device and Method for Processing of Wafers

Specification

The invention relates to a device for processing of substrates or substrate pairs, especially wafers as wafer pairs and a corresponding method.

Process systems or process devices of semiconductor technology are generally of modular structure. They conventionally consist of different chambers in which various process steps are carried out. Thus, for example for pretreatment of wafers, process steps such as wet cleaning, plasma treatment, etching or heating can be used, while for primary treatment of a wafer, bonding, lacquering, imprinting, embossing and exposure are possible. In known process systems the wafers or wafer stacks are transported with cassettes between the process systems or modules of process systems.

During transport, the contamination, damage, fouling or oxidation and thus influencing of other process steps can occur.

Contamination of the primary treatment chambers between treatments of successive wafers, therefore in loading and unloading of wafers, is also a problem.

Furthermore it is critical with respect to time that in the primary treatment large pressure differences from atmospheric pressure as far as very low pressures of 10^{-6} bar or less must be overcome.

Embodiments of this invention optimize the processing of substrates both in terms of the sequence, and also to avoid contamination, damage, fouling or oxidation as much as possible.

According to an aspect, there is provided a process system for processing substrates or substrate pairs with at least one pretreatment module and at least one aftertreatment module, the pretreatment module and the aftertreatment module coupled to a main treatment module for executing a main process including at least bonding such that the main treatment module defines vacuum-tight locks for the adjacent pretreatment module and/or the adjacent aftertreatment module.

All combinations of at least two of the features given in the specification, the claims and/or the figures also fall within the framework of the invention. At the given value ranges, values within the indicated limits will also be disclosed as boundary values and will be claimed in any combination.

Embodiments of the invention are based on the idea of coupling a primary treatment module to at least one pretreatment module and at least one aftertreatment module such that at least one of the pretreatment modules and at least one of the aftertreatment modules and/or the primary treatment module each act as vacuum-tight locks for an adjacent pretreatment module, primary treatment module or aftertreatment module. At the same time, according to one embodiment of the invention it is provided that at least one of the pretreatment modules and/or the primary treatment module and/or at least one of the aftertreatment modules can be especially exposed to pressure, a vacuum, and/or can be temperature-treated, especially can be heated independently or regardless of an adjacent module.

In this way, in spite of a flexible structure of the process system according to the device as per embodiments of the invention a time-optimized, even parallel processing of several substrates is provided within the device as per embodiments of the invention, in which based on the lock-like coupling of the individual process modules contamination, damage, fouling or oxidation by decoupling of the substrates from external effects, especially in the loading and unloading of the individual modules,

is resolved.

It is especially advantageous if the primary treatment module can be loaded and unloaded exclusively via locks or a positing system. This is achieved as per embodiments of the invention by there being both a pretreatment module which is coupled in the manner of a lock to the primary treatment module and also an aftertreatment module which is coupled in the manner of a lock to the primary treatment module. By this measure the generally especially critical primary treatment of the substrates or wafers which occurs under often extreme conditions does not take place at any instant of the processing nor during the loading and unloading of the primary treatment module with contact with the environment. The primary treatment module is accordingly completely decoupled from the environment so that contamination, damage, fouling or oxidation during the primary treatment of the substrates is essentially precluded. Furthermore, there is the advantage that the steps preparatory and subsequent to primary treatment can be moved into the pretreatment module and the aftertreatment module, especially at least partial exposure to pressure and/or temperature. In the primary treatment module as a result of this only a lower pressure difference and/or temperature difference than from the ambient/atmospheric pressure p_{ATM} need be overcome.

According to one advantageous embodiment of the invention, it is provided that the primary treatment chamber can be switched as a lock in the loading and unloading of the substrates. Thus, when the primary treatment chamber is being loaded, at the same time aftertreatment of the substrate which has been worked beforehand in the primary treatment chamber can take place. When the primary treatment chamber is being unloaded, conversely at the same time pretreatment of the next substrate which is to be worked in the primary treatment chamber can take place in the pretreatment chamber.

In another advantageous embodiment, it is provided that the pretreatment chamber and/or the primary treatment chamber and/or the aftertreatment chamber can be heated especially separately by means of a heating apparatus. It is especially advantageous here if the pretreatment chamber and/or the primary treatment chamber and/or the aftertreatment chamber are completely heat-insulated. In this way exact temperature control is possible with heat loss as low as possible.

To the extent other correspondingly made pretreatment modules can be connected upstream to the pretreatment module as locks and/or other correspondingly made aftertreatment modules can be connected downstream of the aftertreatment module as locks, the method sequence can be further subdivided so that optimization of the passage times in the process sequence arises. Here it is conceivable as per embodiments of the invention that at the same time several pretreatment modules are directly coupled to one pretreatment module via lock doors. In this way time-intensive pretreatment steps can proceed parallel and accordingly staggered in time in the upstream pretreatment modules. This applies analogously to the corresponding aftertreatment modules.

By the locks being made as pressure locks and/or temperature locks it is possible as per embodiments of the invention to control the pressure and/or the temperature by corresponding switching of the pretreatment modules and/or the aftertreatment modules.

For loading and unloading, as per embodiments of the invention there is a loading and unloading apparatus, especially at least one robot arm. The latter is used for loading and unloading of the substrates into/out of the primary treatment chamber and/or the pretreatment chamber and/or the aftertreatment chamber, and for parallel handling there can be several substrates/wafers in the process sequence, as per embodiments of the invention several robot arms. Thus for example in each pretreatment chamber and/or each aftertreatment chamber there can be exactly one robot arm which

can engage the respectively adjacent pretreatment chamber and/or primary treatment chamber for loading and unloading of the respectively adjacent chambers when the respective lock door is opened.

According to one advantageous embodiment of the invention it is provided that the primary treatment chamber can be loaded at the same time from the pretreatment chamber and can be unloaded into the aftertreatment chamber and/or the pretreatment chamber and the aftertreatment chamber can be loaded at the same time via the first lock door and unloaded via the second lock door.

Other advantages, features and details of the invention will become apparent from the following description of preferred exemplary embodiments and using the drawings.

Figure 1a shows a schematic plan view of a device as claimed in the invention with a pretreatment module, a primary treatment module and an aftertreatment module.

Figure 1b shows a schematic sectional view of the device as claimed in the invention according to cutting line A-A from Figure 1a,

Figure 2a shows a schematic plan view of a second embodiment of the device as claimed in the invention with a pretreatment module, a primary treatment module and an aftertreatment module,

Figure 2b shows a schematic sectional view of the device as claimed in the invention according to cutting line A-A from Figure 2a,

Figure 2c shows a schematic sectional view of the device as claimed in the invention according to cutting line B-B from Figure 2a,

Figure 3 shows a pressure/temperature diagram of a method as claimed in the invention for

processing of substrates and

Figure 4 shows a sectional view of the device as claimed in the invention with a pretreatment module, a primary treatment module and an aftertreatment module.

The same reference numbers for corresponding components are provided in the figures.

In the embodiment of a device 1 as claimed in the invention shown in Figure 1 a pretreatment module 9, a primary treatment module 10 and an aftertreatment module 11 are arranged linearly in a row.

The pretreatment module 9 consists of a pretreatment chamber 2 which can be exposed to a vacuum and which surrounds a pretreatment space 12. A pressurization apparatus which is not shown is connected to the pretreatment chamber 2 and can be controlled by a central control apparatus which is not shown in order to be able to control the pressure in the pretreatment space 12 with the pretreatment chamber 2 closed. Via a temperature exposure apparatus which is not shown, the pretreatment space 12 can be heated and/or cooled, the temperature exposure apparatus being controllable by the central control apparatus.

To load the pretreatment module 9 with one (or more) wafers 15, according to Figure 4 there is a first robot arm 16. The latter, controlled from the central control apparatus, can be routed through a first lock door 5 when the first lock door 5 is opened. Opening and closing of the first lock door 5 are likewise controlled by the central control apparatus.

The first lock door 5 in the embodiment according to Figure 1a and 1b is located on a first face side 18 of the device 1. The first lock door 5 can be closed pressure-tight and has heat insulation so that the pretreatment space 12 in the closed state of the first lock door 5 can be pressurized.

Furthermore, the pretreatment chamber 2 opposite the first lock door 5 jointly with a primary treatment chamber 3 of the primary treatment module 10 has a first primary lock door 6. The first primary lock door 6 is made functionally analogous to the first lock door 5. The primary treatment module 10 can be coupled pressure-tight on the first primary lock door 6 to the pretreatment modules 9, as a result of which a modular structure and a replacement of individual modules 9, 10, 11 of the device 1 can be implemented.

By controlling the first lock door 5 and the first primary lock door 6 by means of the central control apparatus the pretreatment module 9 can be used as a lock, specifically by the first lock door 5 being closed when the first lock door 6 is opened and vice versa.

The primary treatment module 10 consists of the primary treatment chamber 3 which encloses or forms a primary treatment space 13.

Opposite the first primary lock door 6 of the primary treatment chamber 3 there is a second primary lock door 7 which is included at least partially in the primary treatment chamber 3 and which is used to unload the wafer 15 from the primary treatment chamber 3 into an aftertreatment chamber 4. The second primary lock door 7 is formed at least partially by the aftertreatment chamber 4. The primary treatment space 13 can be sealed pressure-tight by the second primary lock door 7 from one aftertreatment space 14 of the aftertreatment chamber 4. Functionally the second primary lock door 7 corresponds to the first primary lock door 6, the first primary lock door 6 and the second primary lock door 7, controlled from the central control apparatus, forming a lock.

The aftertreatment module 11 for aftertreatment of the wafer 15 after primary treatment in the primary treatment module 10 consists of the aftertreatment chamber 4 which forms the aftertreatment space 14. Furthermore the aftertreatment chamber 4 has a second lock door 8 which

is located opposite the second primary lock door 7.

The wafer 15 can be unloaded via the second lock door 8 and by means of a second robot arm 17 after aftertreatment out of the aftertreatment space 14 as soon as the second lock door 8 is opened.

The aftertreatment module 11 can likewise act as a lock by the second primary lock door 7 being closed when the second lock door 8 is opened and vice versa.

The second lock door 8 is located on a second face side 19 of the device 1 so that a linear movement of the wafer 15 takes place during the entire process sequence through the pretreatment module 9, the primary treatment module 10 and the aftertreatment module 11.

The embodiment according to Figure 2a differs by the angular arrangement of the modules 9, 10, 11 so that an altered device 1' results. Only the configuration of the primary treatment chamber 3' is altered, since the second primary lock door 7 is not located opposite the first primary lock door 6, but on one side wall of the primary treatment chamber 3'.

In another embodiment of the invention, in the embodiment according to Figures 1a and 1b an additional side module (not shown) analogously to the aftertreatment module 11 in Figure 2a can be located laterally on the primary treatment module 10 in order to remove the damaged wafers which are detected during the process flow from the process sequence.

A process sequence as claimed in the invention whose pressure and temperature behavior is shown in Figure 3 proceeds as follows:

The first primary lock door 6 and the second primary lock door 7 are closed. Afterwards the pressure in the primary treatment space 13 is lowered by a pressurization apparatus which is not shown, for example a vacuum pump, especially to a pressure p_{min} less than 10^{-6} bar, preferably to a

pressure less than 10^{-9} bar. This ideally takes place only a single time during the processing of a plurality, especially more than 100, preferably more than 1000, even more preferably more than 10000 wafers or wafer pairs.

Via the opened first lock door 5 a wafer 15 or wafer pair is loaded into the pretreatment chamber by means of the first robot arm 16 and is treated there. Pretreatment can be a dry and/or wet process step, for example wet cleaning, plasma treatment, etching, heating or the like. The pretreatment especially preferably comprises an especially optical and/or mechanical alignment apparatus.

Before or after or during the pretreatment step the pretreatment space 12 can be evacuated via a separately activated pressurization apparatus.

Before opening the first primary lock door 6, in any case the first lock door 5 is closed and the pretreatment space 12 is evacuated, especially to a pressure p_V, during or shortly prior to the loading of the pretreatment chamber 3 of less than 10^{-6} bar, preferably less than 10^{-7} bar, so that the pretreatment module 9 acts as a lock for the primary treatment module 10.

The wafer 15 is loaded by an internal transport system, for example a robot arm, through the first primary lock door 6 into the primary treatment chamber 3, 3'.

Then the first primary lock door 6 is closed. During the loading of the primary treatment chamber 3, 3' the second primary lock door 7 is continually closed. The pressure is preferably further lowered to p_{min} less than 10^{-6} bar, even more preferably 10^{-9} bar.

After closing the first primary lock door 6, another wafer 15 can be loaded into the pretreatment chamber 2. At the same time the primary treatment of the first wafer 15 takes place in the primary treatment module 10. This can be for example bonding, lacquering, imprinting,

embossing and/or exposure.

After the primary treatment of the wafer 15 in the primary treatment module 10, the wafer 15 is loaded into the aftertreatment module 11 by opening the second primary lock door 7, the second lock door 8 being closed. Before opening of the second primary lock door 7 the aftertreatment space 14 is exposed to a vacuum, especially a pressure p_N of less than 10^{-6}, preferably less than 10^{-7} by a pressurization apparatus of the aftertreatment module 11 at least until the wafer 15 is loaded from the primary treatment module 10 into the aftertreatment module 11 and the second primary lock door 7 is closed again.

Then aftertreatment of the wafer 15 takes place in the aftertreatment module 11, for example cooling and simultaneous raising of the pressure by the pressurization apparatus of the aftertreatment module 11.

After completion of the aftertreatment of the wafer 15 in the aftertreatment module 11, the wafer 15 is removed via the second lock door 8 and the second robot arm 17.

Before each opening of the primary lock door 6 the pretreatment chamber 2, and before each opening of the primary lock door 7 the aftertreatment chamber 4 are exposed to a pressure p_V or p_N less than the atmospheric and/or ambient pressure p_{ATM} outside the chambers 2, 3, 4 and/or decontaminated, especially flushed with inert gas.

According to one especially advantageous embodiment of the above described invention, the wafer 15 is a wafer pair and a wafer pair is loaded into the device 1 in the above described manner by means of a holding device or handling apparatus for handling of the wafer pair, the pretreatment shown in the left-hand section in Figure 3 comprising the steps heating, evacuation, gas flushing with reducing gas, a wet chemical treatment, a plasma treatment and/or argon

bombardment.

The primary treatment takes place in a vacuum which is higher compared to pretreatment, therefore at a lower pressure p_{min} as is shown in Figure 3 in the middle section. A controlled gas atmosphere, therefore an exactly set gas pressure and an exactly controlled mixing ratio of gases are set by the pressurization apparatus of the primary treatment module 10. Then the wafer pair is brought into contact and bonded. Beforehand, the temperature which is necessary for the joining, especially T_{max}, is set to be greater than 250°C, preferably T_{max} greater than 400°C. During bonding, a force as uniform as possible is applied to the wafer pair and/or an electrical voltage is applied.

The aftertreatment which is shown in Figure 3 in the right-hand section, takes place in an nonoxidizing environment, in which cooling takes place and the pressure is raised to atmospheric pressure. Slow cooling prevents or avoids thermal stresses in the wafer pair which was bonded beforehand.

The pretreatment of the wafer pair can take place according to one embodiment such that there are a first pretreatment module for pretreatment of the first wafer or wafer pair and a second pretreatment module for pretreatment of the second wafer or wafer pair. The first and the second wafer can be loaded into the primary treatment chamber via separate lock doors.

The chambers 2, 3, 4 are preferably made of stainless steel or aluminum.

In the embodiment shown in Figure 4, the first lock door 5 is not located on the face side 18 of the pretreatment chamber 2', but on the side wall. The second lock door 8 is not located on the face side 19, but on the side wall of the aftertreatment chamber 4'.

The process flow is shown by arrows in Figure 4.

The primary lock doors 6, 7 must accordingly have high pressure tightness up to p_{min} and

are preferably made as a transfer valve which is or can be inserted in a common channel between the respectively adjacent chambers 2, 3, 4, forming a seal. The opening diameter of the lock doors 5, 6, 7, 8 is more than 200 mm, especially more than 300 mm, preferably more than 450 mm.

Reference number list

1, 1'	device
2, 2'	pretreatment chamber
3, 3'	primary treatment chamber
4, 4'	aftertreatment chamber
5	first lock door
6	first primary lock door
7	second primary lock door
8	second lock door
9	pretreatment module
10	primary treatment module
11	aftertreatment module
12	pretreatment space
13	primary treatment space
14	aftertreatment space
15	wafer
16	first robot arm
17	second robot arm
18	first face side
19	second face side

Claims:

1. A process system for processing substrates or substrate pairs with

at least one pretreatment module and at least one aftertreatment module,

the pretreatment module and the aftertreatment module coupled to a main treatment module for executing a main process including at least bonding such that the main treatment module defines vacuum-tight locks for the adjacent pretreatment module and/or the adjacent aftertreatment module.

2. The process system according to claim 1, wherein a main treatment chamber of the main treatment module can be switched to define the vacuum-tight locks during the loading and/or unloading of the substrate into/from the process system.

3. The process system according to claim 1, wherein a pretreatment chamber of the pretreatment module and/or a main treatment chamber of the main treatment module and/or an aftertreatment chamber of the aftertreatment module can be heated or cooled off by means of a temperature exposure apparatus.

4. The process system according to claim 1, wherein additional pretreatment modules are connected upstream of a first pretreatment module and/or additional aftertreatment modules are connected downstream of a first aftertreatment module.

5. The process system according to claim 1, wherein the vacuum-tight locks are formed as pressure and/or temperature locks as well.

6. The process system according to claim 1, wherein a loading and unloading apparatus is provided for loading and unloading of the substrates into/from the pretreatment module and/or the aftertreatment module.

7. The process system according to claim 3, wherein the pretreatment chamber and/or the main treatment chamber and/or the aftertreatment chamber can be heated or cooled separately.

8. The process system according to claim 6, wherein the loading and unloading apparatus is at least one robot arm.