

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
02 June 2022 (02.06.2022)



(10) International Publication Number
WO 2022/112899 A1

(51) International Patent Classification:

C10M 167/00 (2006.01) *C10N 30/00* (2006.01)
C10N 30/02 (2006.01) *C10N 40/14* (2006.01)
C10N 30/08 (2006.01)

MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

(21) International Application Number:

PCT/IB2021/060601

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

(22) International Filing Date:

16 November 2021 (16.11.2021)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

63/118,163 25 November 2020 (25.11.2020) US

Published:

- with international search report (Art. 21(3))
- in black and white; the international application as filed contained color or greyscale and is available for download from PATENTSCOPE

(71) Applicant: **CHEVRON JAPAN LTD.** [JP/JP]; Atago Green Hills Mori Tower 18F, 2-5-1 Atago Minato-Ku, Tokyo, 105-6218 (JP).

(72) Inventors: **ONOUCHI, Hisanari**; Atago Green Hills Mori Tower 18F, 2-5-1 Atago Minato-Ku, Tokyo, 105-6218 (JP).
TANAKA, Isao; Atago Green Hills Mori Tower 18F, 2-5-1 Atago Minato-Ku, Tokyo, 105-6218 (JP).

(74) Agent: **KAMEOKA, Mikio**; Tennoz Central Tower, 2-2-24 Higashi-Shinagawa, Shinagawa PO Box 73, Tokyo 140-8776 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, IT, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,

(54) Title: LUBRICATING OIL COMPOSITIONS

(57) Abstract: A lubricating oil for hybrid engine includes a major amount of an oil of lubricating viscosity; a boron-containing compound in an amount to provide 50 to 300 ppm of boron to lubricating oil composition; an overbased calcium salicylate or a mixture of an overbased calcium sulfonate and overbased calcium salicylate individually having a total base number of greater than 150 mg KOH/g, measured by the method of ASTM D-2896, present in an amount that provides 800 ppm to 1800 ppm of calcium to the lubricating oil composition; zinc dithiophosphate (ZnDTP) in an amount to bring from 100 to 800 ppm of phosphorus to the lubricating oil composition; and a non-dispersant comb polymethacrylate (PMA) viscosity index improver (VII). The boron-containing compound includes a borated dispersant. The KV at 100 °C of the lubricating oil composition is from 6 cSt to 8.5 cSt, the KV at 40 °C of the lubricating oil composition is from 25 cSt to 35 cSt, and the VI of the lubricating oil composition is greater than 200.



WO 2022/112899 A1