

LOCKING SWIVEL JOINTBACKGROUND OF THE INVENTION

This invention relates to pipe swivel joints, and more particularly to such swivel joints that are designed to withstand large external loads such as are encountered when used in the oil and gas industry.

A major advance in the completion of offshore wells in water depth at which diver assistance is uneconomical or otherwise impractical has been the design and development of diverless lay-away flowline type subsea Christmas trees for installation on subsea wellheads. These trees utilize flexibility of the flowline to make the flowline-to-tree connection at the surface prior to lowering the tree to the subsea wellhead, thereby eliminating the need to make that connection at a subsea location and also permitting pressure testing the connection in the drillship moonpool. Prior to the present invention the flowlines of a lay away system were connected to the tree in a fixed manner and extended from the tree at an angle, usually about twenty degrees from the vertical, which required more space in the moonpool than was always available, especially on drillships designed for guidelineless drilling and subsea completion systems.

One proposed solution to the problem involved connecting the lay-away flowlines to the universal guidebase by swivel joints, allowing the flowlines to hang vertically in the moonpool and then seek their final angle when they and the tree are landed on the sea floor. However, in this arrangement the flowlines cannot be run with the tree, whereby the highly desirable advantage of making up the flowline-to-tree connection at the surface is not available. Furthermore, this arrangement does not include the advantage of a flowline jettison feature, and the swivel joints employed at the guide do not have metal-to-metal seals, a feature both highly desirable and frequently required by oil and gas industry specifications where elastomer or other non-metallic

seals are inadequate.

SUMMARY OF THE INVENTION

The present invention comprises apparatus which, in a well completion system comprising a subsea Christmas tree and a pair of lay-away flowlines individually interconnected to the subsea tree by pipe swivel joints, releasably locks the flowlines against pivotal movement about the axes of their swivel joints, said apparatus comprising:-

- a) a pair of lock pins, one pin at least partially telescoped within the other pin;
- b) means for biasing said pins axially away from each other;
- c) pin operating means for moving said pins axially towards each other;
- d) support means for said swivel joints, lock pins and pin operating means, said support means adapted for rigid yet releasable connection to said Christmas tree; and
- e) receptacle means on said flowlines for receiving and holding said pins when said flowlines are in a predetermined angular attitude with respect to said Christmas tree.

A metal-to-metal sealing pipe swivel joint which may be used in combination with the apparatus of the present invention is described and claimed in our co-pending Application No. 9104187.1 (Serial No. 2242246) entitled 'Metal-to-Metal Sealing Pipe Swivel Joint', the joint comprising:-

- a) an outer tubular joint element with an inner annular metallic sealing surface;
- b) an inner tubular joint element with an outer annular metallic sealing surface, said inner element extending at least partially within said outer element;
- c) means securing together said inner and outer elements in a relatively rotatable but non-axially separable manner; and

d) an annular seal element disposed between said inner and outer joint elements, said seal element having inner and outer annular metallic sealing surfaces moveable in direct response to fluid pressure axially between an active position wherein said seal element sealing surfaces bear against said inner and outer joint element sealing surfaces to establish a metal-to-metal fluid pressure seal therebetween and an inactive position wherein said seal element sealing surfaces are not in contact with said inner and outer joint elements.

In a below described preferred swivel joint, an annular metal seal element is energized by an internal sleeve that responds to fluid pressure in the joint flow passage to move the seal element axially into a position between the relatively rotatable joint elements where inner and outer annular lips of the seal element bear against opposed annular surfaces of those joint elements in a pressure-tight interference-fit manner. In this arrangement, the metal-to-metal seal is released (de-energized) by application of external hydraulic pressure to overcome the flow passage pressure and return the seal element and sleeve to their initial positions.

A further feature of that arrangement is an alternative system to the apparatus of the present invention for locking the relatively rotatable swivel joint elements against such rotation when the seal element is in its metal-to-metal sealing position, thereby preventing movement at the interface of the seal element and the joint elements and thus assuring that a leak will not develop in the established metal-to-metal seal. This locking system comprises a first plurality of insert keys spaced circumferentially about the outer surface of the locking sleeve, a second plurality of keys on the inner surface of the outer swivel joint element that cooperate with the first set of keys in a spline-like manner when the locking sleeve is in the advanced or seal-establishing position, and a key and slot connection between the locking sleeve and the inner swivel joint element that prevents relative rotation

between the sleeve and this element at all axial positions of the sleeve.

A pipe joint formed between a pair of relatively rotatable joint elements is described herein and claimed in our copending Application No. 9317386.2 (Serial No. 2268559), entitled 'Pipe Joint', the joint including a seal element axially movable into and out of metal-to-metal sealing engagement between the joint elements, dynamic seal means being provided between the seal element and each respective joint element to maintain a fluid seal therebetween during said axial movement, the joint further comprising locking means selectively operable to prevent relative rotation between the joint elements.

The present invention may be used to ensure that the inner and outer swivel joint elements are locked against relative rotation before the seal element moves into its functional position between the opposed sealing surfaces of those joint elements, and corresponding assurance that the seal element moves out of that functional position before the joint elements are released from their locked condition.

The apparatus of the invention is ideally suited for use in situations where very high lateral loads and bending moments are imposed on the flowlines to be locked against pivotal movement, such as the catenary loads imposed by flowlines extending from a subsea Christmas tree while the tree is in a drillship moonpool during pressure tests.

Further preferred features of the present invention are in the dependent claims. An embodiment of the invention is described below by way of example and with reference to the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a side elevation of a subsea Christmas tree suspended just above a drillship moonpool and a lay-away flowline connected to the tree by a swivel joint which may be locked by apparatus according to the present invention, the flowline depending vertically from the Christmas tree, the

apparatus of the invention not being shown.

Figure 2 is a fragmentary view of the tree and flowline of Figure 1, showing how the flowline extends laterally from the tree after the tree has been installed on its subsea wellhead.

Figure 3 is a side elevation, on an enlarged scale, of the flowline hub, swivel joint and flowline of Figures 1 and 2, with the flowline shown in the Figure 2 attitude.

Figure 4 is a front elevation of the apparatus shown in Figure 3, and including a second flowline connected to the hub by a second swivel joint.

Figure 5 is an enlarged plan view, partially broken away to a horizontal section, of a swivel joint for interconnecting a tree and flowline as shown in Figures 1-4.

Figure 6 is a side elevation of the swivel joint of Figure 5.

Figure 7 is an enlarged fragmentary view of the swivel joint of Figure 5.

Figure 8 is a fragmentary view taken along the line 8-8 of Figure 7.

Figure 9 is a fragmentary view taken along the line 9-9 of Figure 7.

Figures 10-13 are fragmentary views, similar to Figure 7 but on a reduced scale, showing the swivel joint seal element and locking sleeve in their various positions during metal-to-metal seal make-up and release operations.

Figure 14 is an enlarged fragmentary view like Figure 7, showing a modified version of the swivel joint and seal elements of the preceding Figures, particularly suitable for use in conjunction with the flowline locking apparatus of the present invention.

Figure 15 is a view like Figure 14, but showing the seal element in its functional position.

Figure 16 is a front elevation, with some parts shown in vertical section of an embodiment of the invention for high flowline load applications to releasably lock a pair of flowlines in a desired attitude with respect to a subsea tree

to which they are pivotally connected by swivel joints such as shown in Figures 3 and 4.

Figure 17 is a fragmentary view, on a slightly reduced scale, of a portion of the apparatus of Figure 16, showing a locking pin released for spring-biased extension into its receptacle port upon upward pivotal movement of the flowlines from their dependent running position as seen in Figure 16.

Figure 18 is a plan view, with some parts broken away, of the flowline locking apparatus of Figure 16, showing the flowlines locked against pivotal movement through their swivel joints.

Figures 1-13

A pipe swivel joint is illustrated at 20 in Figures 5-13, and in Figures 1-4 this joint is shown as interconnecting a lay-away flowline to a subsea Christmas tree.

Referring first to Figures 5-9, the swivel joint 20 may generally comprise an outer tubular element 22, an inner tubular element 24 partially extending within the element 22, an annular metallic seal element 26 between the outer and inner joint elements 22, 24, and a sleeve 28 between the outer and inner elements 22, 24, although the sleeve 28 may be omitted where flowline locking apparatus of the present invention is employed, as shown in Figures 14 and 15 described below.

The outer element 22 has an axial bore 30 that communicates with a lateral port 32 which facilitates connecting the outer element to a pipe such as the illustrated subsea flowline 34, and the bore 30 is counterbored at 36, 38, 40 and 42 to provide annular spaces for the inner element 24, the sleeve 28, the seal element 26, and a radially enlarged portion 24a of the inner element 24, respectively. As seen in Figure 5, a washer-like annular retainer 44 surrounds the outer portion 24b of the inner element 24 and is releasably secured to the end face of the outer element 22, such as by a plurality of circumferentially spaced cap screws 46, to retain the inner and outer elements in axial position while

permitting relative rotation between them. An annular seal element 48, such as an elastomeric O-ring, functions to provide a pressure-tight dynamic seal between the inner and outer elements 24, 22, and an annular wear ring 49 of Teflon or other suitable plastic functions as a dynamic bearing between the two elements.

The inner joint element 24 has an axial bore 50 communicating with a lateral port 52, and as seen in Figure 6 a pipe 54 extends from the port 52 to connect the joint element 24 into a fluid control system such as a subsea Christmas tree of the type illustrated at 56 in Figure 1. In such use, the swivel joint 20 can be firmly secured to a suitable structure, such as a flowline hub assembly 58 which is removably connectable to the tree 56, by means of a pillow block 60 (Figures 5 and 6) that fits around the joint's outer element 22 in a manner that facilitates rotation of that element with respect to the block.

As seen best in Figure 7, the seal element 26 includes an annular base portion 62 from which extend axially an inner annular lip 64 and an outer annular lip 66. Each lip 64, 66 has an annular sealing surface 64a, 66a, respectively, with a radiused cross-section configuration, and in the seal's functional position (Figure 7) these sealing surfaces 64a, 66a bear against opposed cylindrical sealing surfaces 68, 70, respectively, of the inner and outer joint elements 24, 22, respectively, in an interference manner to establish a metal-to-metal seal between the elements 24, 22. The seal element base 62 includes inner and outer pairs of annular grooves in which are annular elastomeric seals 72 that enable the seal element to be returned axially into its non-functional position (Figures 10 and 13), that is moved to the left from the Figure 7 position, by hydraulic pressure inletted through a lateral port 74 in the outer element 22.

Again referring primarily to Figure 7, the sleeve 28 includes a body portion 28a surrounding which are a pair of outer annular elastomeric seals 76, and within which are a pair of inner annular elastomeric seals 78, these seals

functioning to provide a dynamic seal system between the sleeve and the joint elements 22, 24. An annular axial extension 80 of the sleeve body 28a protrudes into the annular space between the seal element lips 64, 66 to bear against the seal element base 62, so that when the sleeve 28 moves axially in the direction of the arrow A it forces the seal element 26 to move in a corresponding manner. At its other end the sleeve 28 includes a plurality of circumferentially spaced inner keys 82 that extend into axial slots 84 in the outer surface of the adjacent portion of the joint inner element 24, these keys and slots cooperating to prevent relative rotation of the sleeve 28 and element 24, but facilitate axial movement of the sleeve with respect to that element. On the outer surface of that same end of the sleeve 28 are a plurality of circumferentially spaced keys 86 that cooperate with a plurality of circumferentially spaced keys 88 on the inner surface of the joint outer element 22 in a spline-like manner to prevent relative rotation between the outer element and the sleeve when these keys 86, 88 are engaged as shown in figures 7-9. As seen best in Figure 9, the forward end portion of each key 86, 88 is tapered to ease axial movement of the sleeve keys 86 into meshed engagement with the keys 88.

Accordingly, when the keys 86, 88 are engaged the outer element 22 is rotationally locked to the inner element 24 through the keys 88, 86, the sleeve 28, and the keys 82 and slots 84, whereas when the keys 86, 88 are disengaged (Figures 10 and 13) the outer element 22 is free to rotate with respect to the sleeve 28 and the inner element 24. The sleeve 28 thereby functions as an alternative to the apparatus of the present invention, to lock the swivel joint elements when rotation therebetween is not desired, such as when the metal-to-metal seal between the elements has been established, and to release this locked status when the seal element 26 has been moved out of its functional position and freedom for such rotation is desirable.

In reference to Figures 10-13, movement of the seal element 26 into and out of its functional position is as

follows. From a starting position where the seal element 26 and the locking sleeve 28 are in their respective locations relative to the inner and outer joint elements 24, 22 as shown in Figure 10, the element bores 30, 50, which together comprise a flow passage for fluid to be conveyed through the joint, are subjected to fluid pressure as represented in Figure 11. As this pressure is conducted from the flow passage through one or more ports 90 in the inner element 24 into the annular space between the inner and outer elements, the locking sleeve 28 is moved axially in the direction of the arrow B until it arrives at its final or locking position shown in Figure 12. During this movement the seal element 26 is likewise moved axially from its Figure 10 position into its functional metal-to-metal sealing position shown in Figure 12. In this position the seal can be tested, as at the drillship when this swivel joint comprises the connection between a subsea tree and a flowline as depicted in Figure 1.

When a satisfactory test is achieved, the seal element 26 is returned to its initial non-functional position shown in Figures 10 and 13 by venting the joint flow passage and admitting pressure through the port 74, as indicated by arrow C in Figure 13, thereby also returning the locking sleeve 28 to its starting position and, accordingly, unlocking the joint outer element 22 for rotation about the sleeve, seal element and joint inner element 24, thereby allowing the flowline 34 to depend vertically from the subsea tree 56 to facilitate clear passage through the drillship moonpool 92. When the tree 56 has been landed and connected to its subsea wellhead, and the flowline has come to rest in its final position on the sea floor, the metal-to-metal seal can then be re-established by repressurizing the swivel joint flow passage as above.

Figures 14 and 15

These figures illustrate a modified version 98 of the foregoing pipe swivel joint for use where the means to lock the swivel joint outer element is exterior thereto such as is the case when using flowline locking apparatus of the present

invention. In this version the metallic seal element 100 is identical to the seal element 26 of the previously described swivel joint, there is no locking sleeve such as 28 and no keys such as 82, 86, 88 or slots 84, and the counterbore 38a is substantially less in axial dimension than its foregoing counterpart 38. In essentially all other design respects, this version is equivalent to the swivel joint 20, and movement of the seal element 100 between its non-functional position of Figure 14 and its functional position of Figure 15 is achieved by fluid pressure as in the foregoing swivel joint, except that said pressure acts directly on the seal element 100 in moving it in either direction without aid of a locking sleeve.

Figures 16-18

One embodiment of the invention that can be employed with the modified swivel joint 98 of Figures 14 and 15 is identified as 110 in Figures 16-18. The locking apparatus 110 comprises a pair of elongated lock pins 112, 114, the pin 114 telescoped into the pin 112, a helical spring 116 surrounding the telescoped pins 112, 114 and extending between radial flanges 118, 120 on the pins 112, 114, respectively, a pair of lock plates 122, 124 each with a tapered receptacle 126, 128, respectively, for receiving the tapered outer ends 130, 132 of the pins 112, 114, respectively, a pair of interiorly threaded sleeves 134, 136 to each of which is fixed a lateral strut 138, 140, respectively, and an operating shaft 142 threaded into the sleeves 134, 136.

The telescoped lock pins 112, 114 extend freely through supports 144, 146 that are mounted on a suitable portion of a structure to which pipe swivel joints are attached, such as the flowline hub assembly 58 of Figure 3, and the plates 122, 124 are mounted in facing relationship on a pair of flowlines such as 148, 150, respectively.

The operating shaft 142 has a reduced diameter portion 142a that rotatably resides in a support strut 152 that is also mounted on the flowline hub assembly 58. The threads

interconnecting the operating shaft 142 with the sleeve 134 are of opposite hand with respect to their counterparts that interconnect the shaft with the sleeve 136, so that as the shaft is rotated by, for instance, a wrench or other means temporarily engaged with a suitably configured shaft extension 142b, the sleeves will move axially toward or away from each other while the shaft is maintained in axial position by the strut 152. The helical spring 116 exerts a constant expanding bias against the pin flanges 118, 120 so that rotation of the shaft 142 to cause the aforesaid movement of the sleeves 134, 136 also results in telescopic axial movement of the pins 112, 114.

Figure 16 illustrates the contracted position of the pins 112, 114 wherein the flowlines 148, 150 are free to pivot by means of their swivel joints 154, 156, through their full range of movement without becoming locked in any attitude by the locking apparatus 110. When it is desired to lock the flowlines and their swivel joints against pivotal movement, the operating shaft 142 is rotated to move the sleeves 134, 136 apart until the struts 138, 140 come to rest against the pin supports 144, 146, whereby the pins 112, 114 will be biased by the spring 116 into contact with their lock plates 122, 124 as illustrated in Figure 17. As the flowlines are pivoted the lock plates are carried along until their receptacles 126, 128 come into alignment with the pins, whereupon the pins are biased further apart until their tapered ends are fully inserted into locking engagement with the receptacles as shown in Figure 18. As will be understood, reverse rotation of the operating shaft 142 will cause withdrawal of the pins 112, 114 from their locking receptacles, freeing the flowlines for pivotal movement about their swivel joint axes.

Although the best mode contemplated for carrying out the present invention has been herein shown and described, it will be apparent that modification and variation may be made without departing from what is regarded to be the subject matter of the invention, as defined in the claims.

CLAIMS

1. In a well completion system comprising a subsea Christmas tree and a pair of lay-away flowlines individually interconnected to the subsea tree by pipe swivel joints, an apparatus for releasably locking the flowlines against pivotal movement about the axes of their swivel joints, said apparatus comprising:

- a) a pair of lock pins, one pin at least partially telescoped within the other pin;
- b) means for biasing said pins axially away from each other;
- c) pin operating means for moving said pins axially towards each other;
- d) support means for said swivel joints, lock pins and pin operating means, said support means adapted for rigid yet releasable connection to said Christmas tree; and
- e) receptacle means on said flowlines for receiving and holding said pins when said flowlines are in a predetermined angular attitude with respect to said Christmas tree.

2. Apparatus according to claim 1 wherein said pipe swivel joints include a metal-to-metal sealing system.

3. Apparatus according to claim 1 or 2 wherein said biasing means comprises a helical spring surrounding said telescoped pins.

4. Apparatus according to claim 1, 2 or 3 wherein said pin operating means comprises a shaft rotatably mounted on said support means, a pair of sleeves threaded onto said shaft, one sleeve having threads of opposite hand to the other sleeve, and means interconnecting said sleeves and said pins to cause relative axial movement of said pins in response to corresponding relative axial movement of said sleeves.



5. Apparatus according to any of claims 1-4 wherein said receptacle means comprises a pair of lock plates each having at least one receptacle positioned to receive a lock pin, said plates also functioning as a stop against further axial movement of said pins away from each other in response to said biasing means until said pins and said receptacles are aligned.

6. In combination, the well completion system and apparatus according to any of claims 1-5 wherein at least one of said pipe swivel joints comprises:

- a) an outer tubular joint element with an inner annular metallic sealing surface;
- b) an inner tubular joint element with an outer annular metallic sealing surface, said inner element extending at least partially within said outer element;
- c) means securing together said inner and outer elements in a relatively rotatable but non-axially separable manner; and
- d) an annular seal element disposed between said inner and outer joint elements, said seal element having inner and outer annular metallic sealing surfaces moveable in direct response to fluid pressure axially between an active position wherein said seal element sealing surfaces bear against said inner and outer joint element sealing surfaces to establish a metal-to-metal fluid pressure seal therebetween and an inactive position wherein said seal element sealing surfaces are not in contact with said inner and outer joint elements.

