

HYDRAULIC FLUSHING SYSTEM

FIELD OF THE INVENTION

[0001] This invention relates to a hydraulic flushing system and method of flushing a downhole control line in an underwater, e.g. subsea, hydrocarbon well facility.

BACKGROUND OF THE INVENTION

[0002] Surface controlled sub-surface safety valves (SCSSVs) on production fluid wells are controlled by high pressure hydraulic fluid switched through a directional control valve (DCV). After a period of time the hydraulic fluid can deteriorate or become contaminated resulting in possible failure of the SCSSV to operate when required. In order to prevent this problem, well operators insist that the design of the hydraulic system allows for flushing of the hydraulic fluid from the hydraulic control lines right down to the SCSSV itself. However, existing methods of achieving this involve a second 'flushing' DCV and typically venting of the flushed hydraulic fluid to the sea. This creates two new problems: a) the hydraulic fluid can be contaminated with particles which can lodge in the flushing DCV causing it to fail to close resulting in total failure of the SCSSV control; and b) the hydraulic fluid, normally not a pollutant when vented to sea, can be contaminated with downhole fluids including hydrocarbons, which cause the hydraulic fluid to become a pollutant. The invention aims to overcome some of the above problems.

SUMMARY OF THE INVENTION

[0003] According to a first aspect of the invention there is provided a hydraulic flushing system comprising:

a hydraulic downhole control line that runs from a hydraulic source to a surface controlled sub-surface safety valve of an underwater hydrocarbon extraction facility, said hydraulic downhole control line having a directional control valve therein; and

a purge line that runs from the hydraulic downhole control line downstream of the directional control valve to a service line, said purge line having a fluid isolation valve therein.

[0004] According to a second aspect of the invention there is provided a method of flushing a hydraulic downhole control line, said control line comprising:

a hydraulic downhole control line that runs from a hydraulic source to a surface controlled sub-surface safety valve of an underwater hydrocarbon extraction facility, said hydraulic downhole control line having a directional control valve therein; and

a purge line that runs from the first hydraulic downhole control line downstream of the directional control valve to a service line, said purge line having a fluid isolation valve therein,

said method comprising the steps of:

closing the surface controlled sub-surface safety valve;

opening the fluid isolation valve; and

opening the directional control valve.

[0005] The fluid isolation valve could be operated by a hydraulic line which is independent of the hydraulic downhole control line. The fluid in said hydraulic line could be of relatively lower pressure than the fluid in the hydraulic downhole control line.

[0006] The service line could be an annulus service line, which in turn could vent into a well fluid production line.

[0007] The fluid isolation valve could have an internal orifice of between 1/2 inch (1.27 centimetres) and 2 inches (5.08 centimetres) in diameter.

[0008] In an embodiment of the invention, the flushing DCV in a typical hydraulic fluid flushing system, which is prone to particle contamination blockage, is replaced with a hydraulically operated fluid isolation valve (FIV), which has a much larger fluid flow path orifice, via which contaminated fluid is vented into a well service line, such as an annulus service line, rather than into the sea, which avoids potential sea pollution. The FIV is typically controlled by hydraulic operation.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Fig. 1 is a schematic diagram of a prior art flushing system for a hydraulic line; and

[0010] Fig. 2 is a schematic diagram of a flushing system according to an embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0011] Fig. 1 illustrates a typical existing method of flushing a hydraulic line to a SCSSV 1 of a subsea hydrocarbon well facility. High pressure (HP) hydraulic fluid, typically

sourced via an umbilical from a surface platform, is fed via a line 2 and a subsea Xmas tree 3, to a subsea control module (SCM) 4, housed in the tree. Reference numeral 5 designates a base plate for the SCM 4.

[0012] During normal operation, the SCSSV 1, is opened and closed by operating a DCV 6, whilst a 'flushing' DCV 7 remains closed. In order to flush a hydraulic downhole control line 8 of the SCSSV 1, the DCV 6 is closed, the DCV 7 is opened followed by the opening of DCV 6, allowing control fluid to flow through the hydraulic downhole control line 8, to the SCSSV 1, and then back up a second control line 9 (acting as a purge or flushing line), through the DCV 7, through a flow transmitter 10, if fitted (this component may be omitted in practice), a metallic check valve 11, and finally a seawater check valve 12 before being vented to sea. The orifice in a DCV such as DCV 7 in this system is typically only 3 millimetres in diameter, and is thus prone to blockage from contaminating particles.

[0013] As previously described, prior art systems such as the one shown in Fig. 1 suffer from the problem of potentially particle and chemical contaminated fluid being flushed into the sea.

[0014] Fig. 2 illustrates an embodiment of the invention which aims to remove the problems of the existing system of Fig. 1. Like reference numerals have been retained where appropriate.

[0015] As for Fig. 1, high pressure (HP) hydraulic fluid, typically sourced via an umbilical from a surface platform, is fed via line 2 and subsea Xmas tree 3, to a subsea control module (SCM) 4, housed in the tree. A hydraulic downhole control line 8 runs from the hydraulic source to a SCSSV 1 and has a DCV 6 therein. A purge line 9 runs from the hydraulic downhole control line 8 downstream of the DCV 6 to a service line 14, and has a hydraulically operated fluid isolation valve (FIV) 13 therein.

[0016] During normal operation, the SCSSV 1 is opened and closed by operating DCV 6, whilst the FIV 13 remains closed. The FIV 13 has the advantage over a DCV in that its internal orifice can be between 1/2 inch (1.27 centimetres) and 2 inches (5.08 centimetres) in diameter, and thus is not prone to blockage from contaminating particles.

[0017] In order to flush the downhole control line 8, the SCSSV 1 is closed, the FIV 13 is opened and then DCV 6 is opened, allowing control fluid to flow downhole to the SCSSV 1, and then back up the purge line 9, through the FIV 13, and into the service

line 14, such as an annulus service line. Once the required amount of fluid has been circulated through the loop, the FIV 13 is closed and normal operation can be resumed.

[0018] In the embodiment shown in Fig. 2 the FIV 13 is hydraulically operated via a low pressure (LP) hydraulic line 15 which is independent of the hydraulic downhole control line 8. The fluid of the low pressure hydraulic line 15 is of relatively lower pressure than the fluid in the line 2. In alternative embodiments the FIV 13 may be mechanically operated or electrically controlled, e.g. by a solenoid.

[0019] Purged fluid may be stored in the service line 14. On completion of the first part of the flushing activity, the FIV 13 is closed. Then pressure is applied to the service line 14 from a host facility (i.e. a surface platform, a floating production, storage and offloading (FPSO) unit, etc.) and a path opened from the service line 14 into a production line of an underwater hydrocarbon well facility, which allows the purged fluid to be pushed into the production line after which it flows back to the host facility.

ADVANTAGES OF USING THE INVENTION

[0020] The present invention may prevent the failure of the hydraulic control line flushing system from particle contamination.

[0021] The present invention may reduce the risk of pollution of the sea due to chemical contamination of flushed and vented hydraulic fluid.

CLAIMS

1. A method of flushing a hydraulic downhole control line, the method comprising the steps of:

closing a surface controlled sub-surface safety valve, wherein the hydraulic downhole control line runs from a hydraulic source to the surface controlled sub-surface safety valve of an underwater hydrocarbon extraction facility;

opening a fluid isolation valve to enable purging of a hydraulic fluid, wherein the fluid isolation valve is operated by a hydraulic line which is independent of the hydraulic downhole control line;

storing the purged hydraulic fluid in a service line; and

opening a first directional control valve;

wherein the hydraulic downhole control line comprises the first directional control valve and a purge line that runs from the hydraulic downhole control line downstream of the first directional control valve to the service line, and

wherein the purge line comprises the fluid isolation valve controlled via a second directional control valve disposed in the hydraulic line.

2. The method according to claim 1, wherein the fluid isolation valve is operated by a hydraulic line which is independent of the hydraulic downhole control line.

3. The method according to claim 2, wherein the hydraulic fluid in the hydraulic line is of relatively lower pressure than the hydraulic fluid in the hydraulic downhole control line.

4. The method according to claim 1, wherein the service line is an annulus service line.

5. The method according to claim 1, wherein the service line vents into a production line of the underwater hydrocarbon extraction facility.

6. The method according to claim 1, wherein the fluid isolation valve comprises an internal orifice, wherein a diameter of the internal orifice is between 0.5 inch and 2 inches.

7. The method according to claim 5, further comprising:

closing the fluid isolation valve; and

applying pressure to the service line to push the purged hydraulic fluid into the production line after closing the fluid isolation valve.

8. A hydraulic flushing system comprising:

a hydraulic downhole control line that runs from a hydraulic source to a surface controlled sub-surface safety valve of an underwater hydrocarbon extraction facility, the hydraulic downhole control line having a first directional control valve therein,

a purge line coupled to the hydraulic downhole control line downstream of the directional control valve and comprising a fluid isolation valve to enable purging of a hydraulic fluid, wherein the fluid isolation valve is operated by a hydraulic line which is independent of the hydraulic downhole control line; and

a second directional control valve coupled to the fluid isolation valve to control operation of the fluid isolation valve; and

a service line coupled to the purge line via the fluid isolation valve to store the purged hydraulic fluid when the fluid isolation valve is open, and to supply the purged hydraulic fluid to a production line of the underwater hydrocarbon extraction facility when the fluid isolation valve is closed.

9. The hydraulic flushing system according to claim 8, wherein the hydraulic fluid in the hydraulic line is of relatively lower pressure than the hydraulic fluid in the hydraulic downhole control line.

10. The hydraulic flushing system according to claim 8, wherein the service line is an annulus service line.

11. The hydraulic flushing system according to claim 8, wherein the fluid isolation valve comprises an internal orifice, wherein a diameter of the internal orifice is between 0.5 inch and 2 inches.