

Description

The present invention relates to color display systems using cathode-ray tubes and the electron guns of such tubes and is an improvement on earlier systems providing electrostatic convergence by the use, for example, of an asymmetric or tilted electron lens structure between beam-forming electrodes and focusing electrodes as in US-A-2957106.

Prior to development of self-converging yokes, beam convergence within a color cathode-ray tube was usually achieved by use of dynamically varied magnetic fields that were coupled to plates or pole pieces located at the output end of an electron gun. The magnetic fields were formed by electromagnetic components located outside the neck of the tube. However, the adjustments for such a dynamic convergence system were extremely complex and time-consuming. In response to this adjustment problem, a system utilizing a self-converging yoke was developed.

Although most present-day deflection yokes produce a self-convergence of the three beams in a cathode-ray tube, the price paid for such self-convergence is a deterioration of the individual electron beam spot shapes. The self-converging yoke magnetic field is astigmatic. It both overfocuses the vertical-plane electron beam rays, leading to deflected spots with appreciable vertical flare, and underfocuses the horizontal-plane rays, leading to slightly enlarged spot width.

It is desirable to avoid the astigmatism problem associated with a self-converging yoke by use of a yoke that is not self-converging. However, it is not desirable to return to use of dynamically varied magnetic fields for converging the beams.

The present invention provides therefore a color display system including a cathode-ray tube having an inline electron gun according to claim 1.

There is thus provided a system that uses non-converging yoke with an electron gun that includes means for converging the electron beams.

In the drawings:

FIGURE 1 (Sheet 1) is a plan view, partly in axial section, of a color display system embodying the invention.

FIGURE 2 (Sheet 2) is a partially cutaway axial section top view of one form of electron gun that can be provided according to the invention.

FIGURE 3 (Sheet 3) is a broken-apart perspective view of the dipole electrodes of the electron gun of FIGURE 2.

FIGURE 4 (Sheet 4) is a partially cutaway axial section top view of another electron gun.

FIGURE 5 (Sheet 3) is a sectional view of the electron gun taken at line V-V of FIGURE 4.

FIGURE 6 (Sheet 5) is a partially cutaway axial section top view of yet another electron gun.

FIGURE 7 (Sheet 3) is a diagram of three electron beams in undeflected and deflected positions, used to explain dynamic convergence.

FIGURE 1 shows a color display system 9 including a rectangular color picture tube 10 having a glass envelope 11 comprising a rectangular faceplate panel 12 and a tubular neck 14 connected by a rectangular funnel 15. The funnel 15 has an internal conductive coating (not shown) that extends from an anode button 16 to the neck 14. The panel 12 comprises a viewing faceplate 18 and a peripheral flange or sidewall 20, which is sealed to the funnel 15 by a glass frit 17. A three-color phosphor screen 22 is carried by the inner surface of the faceplate 18. The screen 22 preferably is a line screen with the phosphor lines arranged in triads, each triad including a phosphor line of each of the three colors. Alternatively, the screen can be a dot screen. A multiapertured color selection electrode or shadow mask 24 is removably mounted, by conventional means, in predetermined spaced relation to the screen 22. An improved electron gun 26, shown schematically by dotted lines in FIGURE 1, is centrally mounted within the neck 14 to generate and direct three electron beams 28 along convergent paths through the mask 24 to the screen 22.

The tube of FIGURE 1 is designed to be used with an external magnetic deflection yoke, such as the yoke 30 shown in the neighborhood of the funnel-to-neck junction. When activated, the yoke 30 subjects the three beams 28 to magnetic fields which cause the beams to scan horizontally and vertically in a rectangular raster over the screen 22. The initial plane of deflection (at zero deflection) is at about the middle of the yoke 30. Because of fringe fields, the zone of deflection of the tube extends axially from the yoke 30 into the region of the gun 26. For simplicity, the actual curvature of the deflection beam paths in the deflection zone is not shown in FIGURE 1. The yoke 30 is a non-converging type that does not converge the electron beams as does a self-converging yoke.

FIGURE 1 also shows a portion of the electronics used for exciting the tube 10 and yoke 30. These electronics are described below.

The details of one form for the electron gun 26 are shown in FIGURES 2 and 3. The gun 26 comprises

three spaced inline cathodes 34 (one for each beam), a control grid electrode 36 (G1), a screen grid electrode 38 (G2), an accelerating electrode 40 (G3), a first dipole lens electrode 42 (G4), a second dipole lens electrode 44 that is directly attached to a first main focusing lens electrode 46 (G5), and a second main focusing lens electrode 48 (G6). These electrodes are spaced in the order named. Each of the G1 through G6 electrodes has three inline apertures located therein to permit passage of three electron beams. The electrostatic main focusing lens in the gun 26 is formed by the facing portions of the G5 electrode 46 and the G6 electrode 48. The first dipole electrode 42 includes a plate 50 having semi-circular extrusions 52 and 54 around the outside halves of its two outer apertures, 56 and 58, respectively. The concave inside surfaces of the two extrusions 52 and 54 face each other. The second dipole electrode 44 includes a plate 60 having semi-circular extrusions 62 and 64 around the inside halves of its two outer apertures 66 and 68, respectively. The convex outside surfaces of the two extrusions 62 and 64 face each other, and the concave inside surfaces of the extrusions 62 and 64 face the concave inside surfaces of the extrusions 52 and 54, respectively. The center aperture 70 of the plate 60 includes a circular cylindrical extrusion 72 that extends toward the plate 50. The plate 60 of the second dipole electrode 44 is directly attached to the first main focusing lens electrode 46, so that the two electrodes 44 and 46 together may be considered the G5 electrode. The portion of the first main focusing lens electrode 46 that faces the second main focusing lens electrode 48 includes an oblong shaped leading edge 74 and an apertured portion 76 that is set back from the leading edge 74. The second main focusing electrode 48 is similarly shaped, having an oblong leading edge 78 facing the leading edge 74 and an apertured portion 80 that is set back from the leading edge 78. A shield cup 82 is attached to the electrode 48 at the exit of the electron gun. The shield cup 82 may include coma correction members 84, such as shown, or may contain coma correction members of different design.

All of the electrodes of the gun 26 are either directly or indirectly connected to two insulative support rods 86 (one shown). The rods 86 may extend to and support the G1 electrode 36 and the G2 electrode 38, or these two electrodes may be attached to the G3 electrode 40 by some other insulative means. In a preferred embodiment, the support rods are of glass which has been heated and pressed onto claws extending from the electrodes, to embed the claws in the rods.

Referring back to FIGURE 1, there is shown a portion of the electronics 100 that may operate the system as a television receiver or as a computer monitor. The electronics 100 is responsive to broadcast signals received via an antenna 102, and to direct red, green and blue (RGB) video signals via input terminals 104. The broadcast signal is applied to tuner and intermediate frequency (IF) circuitry 106, the output of which is applied to a video detector 108. The output of the video detector 108 is a composite video signal that is applied to a synchronizing signal (sync) separator 110 and a chrominance and luminance signal processor 112. The sync separator 110 generates horizontal and vertical synchronizing pulses that are applied, respectively, to horizontal and vertical deflection circuits 114 and 116. The horizontal deflection circuit 114 produces a horizontal deflection current in a horizontal deflection winding of the yoke 30, while the vertical deflection circuit 116 produces a vertical deflection current in a vertical deflection winding of the yoke 30.

In addition to receiving the composite video signal from the video detector 108, the chrominance and luminance signal processing circuit 112 may alternatively receive individual red, green and blue video signals from a computer, via the terminals 104. Synchronizing pulses may be supplied to the sync separator 110 via a separate conductor or, as shown in FIGURE 1, in association with the green video signal. The output of the chrominance and luminance processing circuitry 112 comprises the red, green and blue color drive signals, that are applied to the electron gun 26 of the cathode ray tube 10 via conductors RD, GD and BD, respectively.

Power for the system is provided by a voltage supply 118, which is connected to an AC voltage source. The voltage supply 118 produces a regulated DC voltage level $+V_1$ that may, illustratively, be used to power the horizontal deflection circuit 114. The voltage supply 118 also produces DC voltage $+V_2$ that may be used to power the various circuits of the electronics, such as the vertical deflection circuit 116. The voltage supply further produces a high voltage V_u that is applied to ultor terminal or anode button 16.

Circuits and components for the tuner 106, video detector 108, sync separator 110, processor 112, horizontal deflection circuit 114, vertical deflection circuit 116 and voltage supply 118 are well known in the art and, therefore, are not specifically described herein.

In addition to the foregoing elements, the electronics 100 includes a dynamic convergence waveform generator 122. The G4 element 42 of the electron gun 26 is provided with a dynamically varied voltage $V_m = V_{G3} - \Delta V$ where ΔV is the output from the generator 122. The generator 122 receives the horizontal and vertical scan signals from the horizontal deflection circuit 114 and the vertical deflection circuit 116, respectively. The circuitry for the generator 122 can be that as is known in the art. Examples of such known

circuits may be found in: US Patent 4,214,188, issued to Bafaro et al. on July 22, 1980, US Patent 4,258,298, issued to Hilburn et al. on March 24, 1981; and US Patent 4,316,128, issued to Shiratsuchi on February 16, 1982.

The details of another electron gun 126 that may be provided in accordance with the present invention, are shown in FIGURES 4 and 5. The gun 126 comprises three spaced inline cathodes 134, a control grid electrode 136 (G1), a screen grid electrode 138 (G2), a first main focusing lens electrode 140 (G3) that includes an electrically connected buffer plate 141, and a second main focusing lens electrode 142 (G4), spaced in the order named. Each of the G1 through G4 electrodes has three inline apertures located therein to permit passage of three electron beams. The electrostatic main focusing lens in the gun 126 is formed by the facing portions of the G3 electrode buffer plate 141 and the G4 electrode 142. The main body of the G3 electrode 140 is formed with two cup-shaped elements 144 and 146. The open ends of the two elements, 144 and 146, are attached to each other. The buffer plate 141 has three inline apertures therein. The G4 electrode 142 is cup-shaped, with its closed end facing the buffer plate 141 of the G3 electrode 140. The element 146 includes a center aperture 148 and two side or outer apertures 150 and 152. Each of these apertures includes extrusions that extend into the cup-shaped element 146. The facing portion of the G4 electrode 142 contains three corresponding inline apertures 154.

The element 146 of the G3 electrode 140 is split into two parts, 158 and 160. A central part 160 is formed by a gap extending down through the electrode at the center of the outer aperture 150, then at a right angle thereto to the center of the other outer aperture 152, and then at a right angle up through the center of the aperture 152. The center aperture 148 and the inside halves of the two outer apertures 150 and 152 are formed in the center part 160. The outer halves of the outer apertures 150 and 152 are formed in the part 158. The electrodes, including the buffer plate 141, are held by two support rods 162 (one shown). The center part 160 is held in position relative to the remaining part 158 of the element 146, by attachment to the support rods 162, to maintain the gap therebetween.

In the electron gun 126, the dynamic voltage, $V_{G3} - \Delta V$, is applied to the center part 160. The electrostatic field forming the main focusing lens forms between the buffer plate 141 and the G4 electrode 142. In this embodiment, the buffer plate 141 isolates the main focusing lens from the dipole fields formed by the parts 158 and 160.

The details of a third electron gun 226, that may be provided in accordance with the present invention, are shown in FIGURE 6. The gun 226 comprises three spaced inline cathodes 234, a control grid electrode 236 (G1), a screen grid electrode 238 (G2), a first main focusing lens electrode 240 (G3), and a second main focusing lens electrode 242 (G4), spaced in the order named. Each of the G1 through G4 electrodes has three inline apertures located therein to permit passage of three electron beams. The electrostatic main focusing lens in the gun 226 is formed by the facing portions of the G3 electrode 240 and the G4 electrode 242. The G3 electrode 240 is formed with two cup-shaped elements 244 and 246. The open ends of the two elements, 244 and 246, are attached to each other. The G4 electrode 242 is cup-shaped, with its closed end facing the closed end of the element 246 of the G3 electrode 240. The element 246 includes a center aperture 248 and two side or outer apertures 250 and 252. The facing portion of the G4 electrode 242 contains three corresponding inline apertures 254.

The element 246 of the G3 electrode 240 is split into three parts, 256, 258 and 260. One part, 256, is formed by a gap extending down through the electrode at the center of the aperture 250, and then at a right angle thereto out through the side of the electrode. Similarly, the part 260 is formed by a gap extending down through the electrode at the center of the aperture 252 and at a right angle thereto out through the opposite side of the electrode. The center aperture 248 and half of each of the side apertures 250 and 252 are formed in the center part 258. The other halves of the outer apertures 250 and 252 are formed in the parts 256 and 260, respectively. The parts 256 and 260 are attached to the part 258 by an insulating cement 262. All of the electrodes of the gun 226 are either directly or indirectly connected to two insulative support rods 264 (one shown). In the electron gun 226, the dynamic voltage, $V_{G3} + \Delta V$, is applied to the parts 256 and 260.

FIGURE 7 is a diagram of the three electron beams 28, when undeflected and deflected, similar to the showing in FIGURE 1. In the diagram, R, G and B represent the centers of the red, green and blue electron beams, respectively, in the deflection plane. Beam center-to-beam center spacing in the deflection plane is labelled s . The angle through which the electron beams are deflected is labelled θ . The distance along the central longitudinal axis of the tube from the deflection plane to the screen is labelled L . The perpendicular distance from the undeflected center beam to the intersection of the deflected center beam with the screen is labelled h . The distance along the central longitudinal axis from the deflection plane to the perpendicular plane passing through deflected center beam intersection with the mask is labelled l . The angles α are the convergence angles the outer beams R and B make with the center beam G at the screen. The angles β_R

and β_B represent the angles between the unconverged beam paths, shown in solid lines, with the desired converged beam paths, shown in dashed lines, for the outer red, R, and blue, B, beams, respectively. The following relationships hold for the diagram.

$$\tan \theta = \frac{h}{l} \quad (1)$$

$$\tan (\theta + \beta_R - \alpha) = \frac{h - s}{l} \quad (2)$$

$$\tan (\theta - \beta_B + \alpha) = \frac{h + s}{l} \quad (3)$$

The above equations can be used for estimating the magnitude of the correction angles, β_R and β_B , necessary to achieve convergence.

For a 48cm diagonal tube, such as RCA tube A48AAD10X, the pertinent dimensions are: $s = 0.508\text{cm}$ (0.200 inch), $L = 21.641\text{cm}$ (8.52 inches), $h = 20.218\text{cm}$ (7.96 inches), and, since $l = h \cot \theta$, then $l = 17.882\text{cm}$ (7.04 inches) for a deflection angle to the side of the screen of 48.5° . Since $\tan \alpha = s/L$, then $\alpha = 1.345^\circ$, and with a 48.5° deflection angle, $\beta_R = 0.629^\circ$ and $\beta_B = 0.632^\circ$.

Since β_R and β_B differ by less than 1% of their values, common voltages can be applied to both of the G3 sectioned elements 256 and 260 of the electron gun 226, to the G4 electrode at the electron gun 26 and to the center part 160 of the electron gun 126. In the above-identified RCA tube operated at an ultor voltage V_u of 25KV and a focus voltage V_{G3} of 7000V, the correction voltage ΔV required at the 48.5° deflection position is 290V. This is a value that can be readily applied to a gun electrode. Other tube voltages are cathode voltage V_K equal to 150V minus the video drive voltage, G1 grid voltage equal to zero, and G2 grid voltage equal to 600V.

Claims

1. A color display system including a cathode-ray tube having an inline electron gun (26) for generating and directing three electron beams (28), a center beam and two outer beams, along paths toward a screen (22) of said tube, said gun including electrodes (36,38) comprising a beam-forming region and electrodes (46,48; 140,142; 240,242) for forming a main focussing lens, and said system including a non-converging yoke; characterized in that between at least one of the main focussing lens electrodes and the beam-forming region there are included at least two parts (52,54,62,64; 158,160; 256,258,260) spaced laterally to the electron beam paths, one (52,54; 158; 256,260) of said parts being located outwardly from an outer beam path, and another (62,64; 160; 258) of said parts being located inwardly from an outer beam path, said outwardly and inwardly located parts forming a dipole lens structure in the path of an outer electron beam, and in that there are provided means (122) for applying to a least one (52,54; 160; 256,260) of said spaced parts a dynamic signal which is related to the deflection of the electron beams (28), whereby an electrostatic dipole field is established in the path of an outer beam that causes that outer beam to converge with the center beam for all angles of deflection.
2. A color display system according to Claim 1, characterized in that said outwardly and inwardly located parts (52,54,62,64; 158,160; 256,258,260) are segments of a cylinder surrounding an outer beam path.
3. A color display system according to Claim 1 or 2, characterised in that between said main focussing lens (46,48) and the beam-forming region there are included three separated portions (40,42,44) spaced longitudinally along the electron beam paths, the center (42) of said separated portions including said outwardly located part (52,54), and the separated portion (44) furthest from said beam-forming region including said inwardly located part (62,64).



and β_B represent the angles between the unconverged beam paths, shown in solid lines, with the desired converged beam paths, shown in dashed lines, for the outer red, R, and blue, B, beams, respectively. The following relationships hold for the diagram.

$$\tan \theta = \frac{h}{l} \quad (1)$$

$$\tan (\theta + \beta_R - \alpha) = \frac{h - s}{l} \quad (2)$$

$$\tan (\theta - \beta_B + \alpha) = \frac{h + s}{l} \quad (3)$$

The above equations can be used for estimating the magnitude of the correction angles, β_R and β_B , necessary to achieve convergence.

For a 48cm diagonal tube, such as RCA tube A48AAD10X, the pertinent dimensions are: $s = 0.508\text{cm}$ (0.200 inch), $L = 21.641\text{cm}$ (8.52 inches), $h = 20.218\text{cm}$ (7.96 inches), and, since $l = h \cot \theta$, then $l = 17.882\text{cm}$ (7.04 inches) for a deflection angle to the side of the screen of 48.5° . Since $\tan \alpha = s/L$, then $\alpha = 1.345^\circ$, and with a 48.5° deflection angle, $\beta_R = 0.629^\circ$ and $\beta_B = 0.632^\circ$.

Since β_R and β_B differ by less than 1% of their values, common voltages can be applied to both of the G3 sectioned elements 256 and 260 of the electron gun 226, to the G4 electrode at the electron gun 26 and to the center part 160 of the electron gun 126. In the above-identified RCA tube operated at an ultor voltage V_u of 25KV and a focus voltage V_{G3} of 7000V, the correction voltage ΔV required at the 48.5° deflection position is 290V. This is a value that can be readily applied to a gun electrode. Other tube voltages are cathode voltage V_K equal to 150V minus the video drive voltage, G1 grid voltage equal to zero, and G2 grid voltage equal to 600V.

Claims

1. A color display system including a cathode-ray tube having an inline electron gun (26) for generating and directing three electron beams (28), a center beam and two outer beams, along paths toward a screen (22) of said tube, said gun including electrodes (36,38) comprising a beam-forming region and electrodes (46,48; 140,142; 240,242) for forming a main focussing lens, and said system including a non-converging yoke; characterized in that between at least one of the main focussing lens electrodes and the beam-forming region there are included at least two parts (52,54,62,64; 158,160; 256,258,260) spaced laterally to the electron beam paths, one (52,54; 158; 256,260) of said parts being located outwardly from an outer beam path, and another (62,64; 160; 258) of said parts being located inwardly from an outer beam path, said outwardly and inwardly located parts forming a dipole lens structure in the path of an outer electron beam, and in that there are provided means (122) for applying to a least one (52,54; 160; 256,260) of said spaced parts a dynamic signal which is related to the deflection of the electron beams (28), whereby an electrostatic dipole field is established in the path of an outer beam that causes that outer beam to converge with the center beam for all angles of deflection.
2. A color display system according to Claim 1, characterized in that said outwardly and inwardly located parts (52,54,62,64; 158,160; 256,258,260) are segments of a cylinder surrounding an outer beam path.
3. A color display system according to Claim 1 or 2, characterized in that between said main focussing lens (46,48) and the beam-forming region there are included three separated portions (40,42,44) spaced longitudinally along the electron beam paths, the center (42) of said separated portions including said outwardly located part (52,54), and the separated portion (44) furthest from said beam-forming region including said inwardly located part (62,64).



4. A color display system according to Claim 1 or 2, characterized in that the main focussing lens electrode (140) closest to the beam-forming region comprises three separated portions (141,158,160), a first (158) of said portions including two outwardly located parts and including a centered recess therein, a second (160) of said portions located within said recess including two inwardly located parts, and a third of said portions being an apertured plate (141) located adjacent to the main focussing lens (142) furthest from the beam-forming region.
5. A color display system according to claim 1 or 2, characterized in that the main focussing lens electrode (240) closest to the beam-forming region comprises three separated portions (256,258,260), a first (258) of said portions including two inwardly located parts, a second (256) of said portions including one outwardly located part, and a third portion (260) including another outwardly located part.
6. An inline electron gun in or for a color cathode-ray tube for generating and directing three electron beams (28), a center beam and two outer beams, along paths toward a screen (22) of said tube, said gun including electrodes (36,38) comprising a beam-forming region and electrodes (46,48; 140,142; 240,242) for forming a main focussing lens, and being characterized in that between at least one of the main focussing lens electrodes and the beam-forming region there are included at least two parts (52,54,62,64; 158,160; 256,258,260) spaced laterally to the electron beam paths, one (52,54; 158; 256,260) of said parts being located outwardly from an outer beam path, and another (62,64; 160; 258) of said parts being located inwardly from an outer beam path, said outwardly and inwardly located parts forming a dipole lens structure in the path of an outer electron beam (28), whereby an electrostatic dipole field can be established in the path of an outer beam that causes that outer beam to converge with the center beam (28) for all angles of deflection.
7. An electron gun according to Claim 6, characterized in that said outwardly and inwardly located parts (52,54,62,64; 158,160; 256,258,260) are segments of a cylinder surrounding an outer beam path.
8. An electron gun according to claim 7, characterized in that between said main focussing lens and the beam-forming region there are included three separated portions (40,42,44) spaced longitudinally along the electron beam paths, the center (42) of said separated portions including said outwardly located part (52,54), and the separated portion (44) furthest from said beam-forming region including said inwardly located part (62,64).
9. An electron gun according to Claim 7, characterized in that the main focussing lens electrode (140) closest to the beam-forming region comprises three separated portions (141,158,160), a first (158) of said portions including two outwardly located parts and including a centered recess therein, a second (160) of said portions located within said recess including two inwardly located parts, and a third of said portions being an apertured plate (141) located adjacent to the main focussing lens (142) furthest from the beam-forming region.
10. An electron gun according to Claim 7, characterized in that the main focussing lens electrode (240) closest to the beam-forming region comprises three separated portions (256,258,260), a first (258) said portions including two inwardly located parts, a second (256) of said portions including one outwardly located part, and a third portion (260) including another outwardly located part.

Revendications

1. Système de visualisation en couleur comportant un tube à rayons cathodiques ayant un canon d'électrons en ligne (26) pour produire et diriger trois faisceaux d'électrons (28), un faisceau central et deux faisceaux externes, le long de trajets vers un écran (22) dudit tube, ledit canon comprenant des électrodes (36, 38) comprenant une région de formation de faisceaux et des électrodes (46, 48 ; 140, 142 ; 240, 242) pour former une lentille de focalisation principale et ledit système comportant un bobinage non convergent caractérisé en ce qu'entre au moins l'une des électrodes formant lentille de focalisation principale et la région formant les faisceaux sont incorporées au moins trois parties (52 54, 62, 64 ; 158, 160 ; 256, 258, 260) latéralement espacées par rapport aux trajets des faisceaux d'électrons l'une (52, 54 ; 158 ; 256, 260) desdites parties étant placée vers l'extérieur d'un trajet d'un faisceau externe et une autre (62,64 ; 160 ; 258) desdites parties étant placée vers l'intérieur d'un trajet d'un faisceau externe, lesdites parties placées vers l'extérieur et vers l'intérieur formant une structure



- de lentille dipôle dans le trajet d'un faisceau externe d'électrons et en ce que sont prévus des moyens (122) pour appliquer, à au moins l'une (52, 54 ; 160 ; 256, 260) desdites parties espacées un signal dynamique qui est en rapport avec la déviation des faisceaux d'électrons (28) ainsi un champ électrostatique dipolaire est établi dans le trajet d'un faisceau externe, qui force ce faisceau externe à converger avec le faisceau central pour tous les angles de déviation.
2. Système de visualisation en couleur selon la revendication 1, caractérisé en ce que lesdites parties placées vers l'extérieur et vers l'intérieur (52, 54, 62, 64 ; 158, 160 ; 256, 258, 260) sont des segments d'un cylindre entourant le trajet d'un faisceau externe.
 3. Système de visualisation en couleur selon la revendication 1 ou 2, caractérisé en ce qu'entre ladite lentille de focalisation principale (46, 48) et la région de formation de faisceaux sont incorporées trois portions séparées (40, 42, 44) longitudinalement espacées le long des trajets des faisceaux d'électrons, la centrale (42) desdites portions espacées comprenant ladite partie placée vers l'extérieur (52, 54) et la portion séparée (44) la plus éloignée de ladite région de formation de faisceaux comportant ladite partie placée vers l'intérieur (62, 64).
 4. Système de visualisation en couleur selon la revendication 1 ou 2, caractérisé en ce que l'électrode formant lentille de focalisation principale la plus proche de la région de formation de faisceaux comprend trois portions séparées (141, 158, 160), une première (158) desdites portions comportant deux parties placées vers l'extérieur et comportant un évidement qui y est centré, une seconde (160) desdites portions placée dans ledit évidement comportant deux parties placées vers l'intérieur, et une troisième desdites portions étant une plaque à ouvertures (141) placée adjacente à la lentille de focalisation principale (142) le plus loin de la région de formation de faisceaux.
 5. Système de visualisation en couleur selon la revendication 1 ou 2, caractérisé en ce que l'électrode formant lentille de focalisation principale (240) la plus proche de la région de formation de faisceaux comprend trois portions séparées (256, 258, 260), une première (258) desdites portions ayant deux parties placées vers l'intérieur, une seconde (256) desdites portions ayant une partie placée vers l'extérieur et une troisième portion (260) comportant une autre partie placée vers l'extérieur.
 6. Canon d'électrons en ligne dans ou pour un tube à rayons cathodiques couleur pour produire et diriger trois faisceaux d'électrons (28), un faisceau central et deux faisceaux externes, le long de trajets vers un écran (22) dudit tube, ledit canon comportant des électrodes (36, 38) comprenant une région de formation de faisceaux et des électrodes (46, 48 ; 140, 142 ; 240, 242) pour former une lentille de focalisation principale et étant caractérisé en ce qu'entre au moins l'une desdites électrodes formant lentille de focalisation principale et la région de formation de faisceaux sont incorporées au moins deux parties (52, 54, 62, 64 ; 158, 160 ; 256, 258, 260) latéralement espacées des trajets de faisceaux d'électrons, l'une (52, 54 ; 158 ; 256, 260) desdites parties étant placée vers l'extérieur d'un trajet de faisceau externe et une autre (62, 64 ; 160 ; 258) desdites parties étant placée vers l'intérieur d'un trajet de faisceau externe, lesdites parties placées vers l'extérieur et vers l'intérieur formant une structure de lentille dipolaire dans le trajet d'un faisceau d'électrons externe (28) ainsi un champ dipolaire électrostatique peut être établi dans le trajet d'un faisceau externe qui force ce faisceau externe à converger avec le faisceau central (28) pour tous les angles de déviation.
 7. Canon d'électrons selon la revendication 6, caractérisé en ce que lesdites parties placées vers l'extérieur et vers l'intérieur (52, 54, 62, 64 ; 158, 160 ; 256, 258, 260) sont des segments d'un cylindre entourant un trajet de faisceau externe.
 8. Canon d'électrons selon la revendication 7, caractérisé en ce qu'entre la lentille de focalisation principale et la région de formation de faisceaux sont incorporées trois portions séparées (40, 42, 44) longitudinalement espacées le long des trajets des faisceaux d'électrons, la centrale (42) desdites portions espacées ayant ladite partie placée vers l'extérieur (52, 54) et la portion séparée (44) la plus éloignée de ladite région de formation de faisceaux comprenant ladite partie placée vers l'intérieur (62, 64).
 9. Canon d'électrons selon la revendication 7, caractérisé en ce que l'électrode formant lentille de focalisation principale (140) la plus proche de la région de formation de faisceaux comprend trois



portions séparées (141, 158, 160), une première (158) desdites portions ayant deux parties placées vers l'extérieur et comprenant un évidement centré, une seconde (160) desdites portions placées dans ledit évidement comportant deux parties placées vers l'extérieur et une troisième desdites portions étant une plaque à ouverture (141) placée adjacente à la lentille de focalisation principale (142), le plus loin de la région de formation de faisceaux.

10. Canon d'électrons selon la revendication 7, caractérisé en ce que l'électrode formant lentille de focalisation principale (240) la plus proche de la région de formation de faisceaux comprend trois portions séparées (256, 258, 260), une première (258) desdites portions ayant deux parties placées vers l'intérieur, une seconde (256) desdites portions ayant une partie placée vers l'extérieur et une troisième portion (260) ayant une autre partie placée vers l'extérieur.

Patentansprüche

1. Farbbild-Wiedergabeeinrichtung mit einer Kathodenstrahlröhre, die ein Inline-Elektronenstrahlerzeugungssystem (26) zum Erzeugen von drei Elektronenstrahlen (28), einem mittleren Strahl und zwei äußeren Strahlen, und zum Richten dieser Strahlen längs Wegen auf einen Schirm (22) der Röhre enthält, welches Elektronenstrahlerzeugungssystem Elektroden (36, 38), welche einen Strahlformungsbereich umfassen, und Elektroden (46, 48, 140, 142; 240, 242) zur Bildung einer Hauptfokussierungslinse enthält, ferner mit einem nichtkonvergierenden Joch, dadurch gekennzeichnet, daß zwischen mindestens einer der Hauptfokussierungslinsenelektroden und dem Strahlformungsbereich mindestens zwei Teile (52, 54, 62, 64; 158, 160; 256, 258, 260) mit seitlichem Abstand von den Elektronenstrahlwegen angeordnet sind, wobei eines (52, 54; 158, 256, 260) der Teile außerhalb eines äußeren Strahlweges angeordnet ist und ein anderes (62, 64; 160; 258) der Teile innerhalb eines äußeren Strahlweges angeordnet ist, daß das außerhalb und das innerhalb angeordnete Teil eine Dipollinsenanordnung im Weg eines äußeren Elektronenstrahles bilden, und daß Mittel (122) vorgesehen sind, um an mindestens eines (52, 54; 160; 256, 260) der beabstandeten Teile ein dynamisches Signal anzulegen, das in Beziehung zur Ablenkung der Elektronenstrahlen (28) steht, so daß ein elektrostatisches Dipolfeld im Weg eines äußeren Elektronenstrahles erzeugt wird, das bewirkt, daß dieser äußere Strahl für alle Ablenkwinkel mit dem mittleren Strahl konvergiert.
2. Farbbild-Wiedergabeeinrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die außerhalb und innerhalb angeordneten Teile (52, 54, 62, 64; 158, 160; 256, 258, 260) Segmente eines Zylinders sind, der einen äußeren Strahlweg umgibt.
3. Farbbild-Wiedergabeeinrichtung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß zwischen der Hauptfokussierungslinse (46, 48) und dem Strahlformungsbereich drei getrennte Teile (40, 42, 44) vorgesehen sind, die longitudinal längs der Elektronenstrahlwege beabstandet sind, wobei das mittlere (42) der getrennten Teile das außerhalb angeordnete Teil (52, 54) enthält und das am weitesten vom Strahlformungsbereich entfernte getrennte Teil (44) das innen angeordnete Teil (62, 64) enthält.
4. Farbbild-Wiedergabeeinrichtung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die dem Strahlformungsbereich am nächsten benachbarte Hauptfokussierungslinsenelektrode (140) drei getrennte Teile (141, 158, 160) enthält, von denen ein erstes (158) zwei außen angeordnete Teile und eine zentrierte Vertiefung aufweist, ein zweites (160) der Teile in der Vertiefung einschließlich zweier innen angeordneter Teile angeordnet ist und ein drittes der Teile eine durchbrochene Platte (141) ist, die bei der Hauptfokussierungslinse (142) am weitesten vom Strahlformungsbereich entfernt angeordnet ist.
5. Farbbild-Wiedergabeeinrichtung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die dem Strahlformungsbereich am nächsten benachbarte Hauptfokussierungslinsenelektrode (240) drei getrennte Teile (256, 258, 260) enthält, von denen ein erstes (258) zwei innen angeordnete Teile enthält, ein zweites ein außen angeordnetes Teil enthält und ein drittes (260) ein anderes außen angeordnetes Teil enthält.
6. Inline-Elektronenstrahlerzeugungssystem für eine Farbbild-Kathodenstrahlröhre zum Erzeugen dreier Elektronenstrahlen (28), einem mittleren und zwei äußeren Strahlen, und Richten dieser Strahlen längs Wegen auf einen Schirm (22) der Röhre, mit Elektroden (36, 38), welche einen Strahlformungsbereich umfassen, und Elektroden (46, 48; 140, 142; 240, 242) zum Bilden einer Hauptfokussierungslinse,



dadurch gekennzeichnet, daß zwischen mindestens einer der Hauptfokussierungslinsenelektroden und dem Strahlformungsbereich mindestens zwei Teile (52, 54, 62, 64; 158, 160; 256, 258, 260) angeordnet sind, die mit seitlichem Abstand von den Elektronenstrahlwegen angeordnet sind, wobei einer (52, 54; 158; 256, 260) dieser Teile außerhalb eines äußeren Strahlweges und ein anderer (62, 64; 160; 258) dieser Teile innerhalb eines äußeren Strahlweges angeordnet ist; daß das außerhalb und das innerhalb angeordnete Teil eine Dipollinsenordnung im Weg eines äußeren Elektronenstrahls (28) bilden, wodurch ein elektrostatistisches Dipolfeld im Weg eines äußeren Elektronenstrahles erzeugbar ist, welches bewirkt, daß dieser äußere Strahl bei allen Ablenkwinkeln mit dem mittleren Strahl (28) konvergiert.

7. Elektronenstrahlerzeugungssystem nach Anspruch 6, dadurch gekennzeichnet, daß das außerhalb und das innerhalb angeordnete Teil (52, 54, 62, 64; 158, 160; 256, 258, 260) Segmente eines Zylinders sind, der einen äußeren Strahlweg umgibt.
8. Elektronenstrahlerzeugungssystem nach Anspruch 7, dadurch gekennzeichnet, daß zwischen der Hauptfokussierungslinse und dem Strahlformungsbereich drei getrennte, longitudinal längs der Elektronenstrahlwege beabstandete Teile (40, 42, 44) angeordnet sind, von denen das mittlere (42) das außerhalb angeordnete Teil (52, 54) enthält und das am weitesten vom Strahlformungsbereich entfernte getrennte Teil (44) das innen angeordnete Teil (62, 64) enthält.
9. Elektronenstrahlerzeugungssystem nach Anspruch 7, dadurch gekennzeichnet, daß die dem Strahlformungsbereich am nächsten benachbarte Hauptfokussierungslinsenelektrode (40) drei getrennte Teile (141, 158, 160) enthält, von denen ein erstes (158) zwei außerhalb angeordnete Teile enthält und eine zentrierte Vertiefung aufweist, ein zweites (160) der Teile, das innerhalb der Vertiefung angeordnet ist, zwei innen angeordnete Teile enthält und ein drittes der Teile eine durchbrochene Platte (141) ist, die am weitesten vom Strahlformungsbereich entfernt bei der Hauptfokussierungslinse (142) angeordnet ist.
10. Elektronenstrahlerzeugungssystem nach Anspruch 7, dadurch gekennzeichnet, daß die dem Strahlformungsbereich am nächsten benachbarte Hauptfokussierungslinsenelektrode (240) drei getrennte Teile (256, 258, 260) enthält, von denen ein erstes (258) dieser Teile zwei innen angeordnete Teile enthält, ein zweites (256) dieser Teile ein außen angeordnetes Teil enthält, und ein drittes Teil (260) ein weiteres außen angeordnetes Teil enthält.