

DESCRIPTION

TITLE

ELECTRONIC DEVICE

5 FIELD

[0001]

The present invention relates to an electronic device.

BACKGROUND

[0002]

10 Generally, an electronic device called a calculator is
provided with a display and a key input section on the top
of its housing. The key input section has multiple keys
arranged in a matrix pattern. For example, the key input
section has numeric keys, arithmetic keys, function keys,
15 etc., each including multiple keys.

[0003]

It is normally the case with a small electronic device
such as a calculator that multiple keys of the key input
section are operated with one hand while processing results
20 according to inputting of keys are presented on the display
and visually recognized.

[0004]

The electronic device is desired to be capable of
enabling accurate and quick hitting of keys of the key
25 input section, without easily causing fatigue even from use
for a long time. Conventionally, a keyboard structure with
stepped keys (a step sculpture) for mitigating a physical

burden is known. For example, Jpn. UM Appln. KOKAI
Publication No. S60-141035 (Japanese Utility Model
Application No. S59-29404, microfilm) discloses a structure
with keys having a height difference in which an elastic
sheet for supporting the keys (push-button switches) has a
shape deformed (flexed) according to the positions of the
keys. A key-to-key deformation of the key-supporting
elastic sheet in this manner, however, alters the
operability (a feel of a click) for each key and
consequently causes a sense of discomfort in the user at
key-depressing actions.

[0005]

The present invention has been formulated in view of
such problems and its objects include providing an
electronic device having multiple operation parts which
entail reduced variations in operability even if differing
in height from each other.

SUMMARY

SOLUTION TO PROBLEM

[0006]

To solve the problems, an electronic device according
to an embodiment includes a plurality of operation parts
arranged from a first-end side to a second-end side of a
housing and each including a keytop member having an
operation surface. The keytop member corresponding to a
first operation part, which is one of the operation parts
arranged on the first-end side, has a lower-end-to-

operation-surface height greater than that of the keytop member corresponding to a second operation part, which is one of the operation parts arranged on the second-end side.

ADVANTAGEOUS EFFECTS OF INVENTION

5 [0007]

According to the present invention, it is possible to provide an electronic device having multiple operation parts which entail reduced variations in operability even if differing in height from each other.

10 BRIEF DESCRIPTION OF THE DRAWINGS

[0008]

FIG. 1 is a plan view of an electronic device according to an embodiment.

15 FIG. 2 is a diagram of the electronic device according to the embodiment, viewed from the lower-side-surface side.

FIG. 3 is a perspective view of the electronic device according to the embodiment.

FIG. 4 is a diagram of the electronic device according to the embodiment, viewed from the right-side-surface side.

20 FIG. 5 is a diagram showing a first configuration example according to the embodiment, in the cross-section taken along the line A-A shown in FIG. 1.

FIG. 6 is a plan view showing an example of a rubber key according to the embodiment.

25 FIG. 7 is a diagram showing a second configuration example according to the embodiment, in the cross-section taken along the line A-A shown in FIG. 1.

FIG. 8 is a diagram showing a third configuration example according to the embodiment, in the cross-section taken along the line A-A shown in FIG. 1.

FIG. 9 is a diagram showing a fourth configuration example according to the embodiment, in the cross-section taken along the line A-A shown in FIG. 1.

FIG. 10 is a diagram showing a fifth configuration example according to the embodiment, in the cross-section taken along the line A-A shown in FIG. 1.

FIG. 11 is a diagram showing a sixth configuration example according to the embodiment, in the cross-section taken along the line A-A shown in FIG. 1.

FIG. 12 is a diagram showing a seventh configuration example according to the embodiment, in the cross-section taken along the line A-A shown in FIG. 1.

DETAILED DESCRIPTION

[0009]

Embodiments of the present invention will be described with reference to the drawings.

[0010]

FIGS. 1, 2, 3, and 4 are diagrams showing external configurations of an electronic device 10 according to an embodiment. FIG. 1 is a plan view of the electronic device 10 according to the embodiment. FIG. 2 is a diagram of the electronic device 10 according to the embodiment, viewed from the lower-side-surface side. FIG. 3 is a perspective view of the electronic device 10 according to the

embodiment. FIG. 4 is a diagram of the electronic device 10 according to the embodiment, viewed from the right-side-surface side.

[0011]

5 As shown in FIG. 1, the electronic device 10 is provided with a key input section 11 and a display section 12 on the top surface of its housing. The key input section 11 has multiple keys 14, one or more selector switches 15, and so on.

10 [0012]

 The multiple keys 14 include, for example, numeric keys, arithmetic keys, function keys, etc. The numeric keys include, for example, multiple keys corresponding to [00] and [0] to [9], respectively. The arithmetic keys include, for example, keys for use in normal calculations according to four arithmetic operations, such as keys corresponding to [+] (addition), [-] (subtraction), [×] (multiplication), [÷] (division), and [=] (execution), respectively. The function keys include, for example, an all-clear key (an [AC] key), a clear key (a [C] key), multiple memory keys ([MRC], [M-], and [M+] keys), a root key (a [$\sqrt{}$] key), and a [%] key.

20

[0013]

 The selector switch or switches 15 include, for example, a round selector and a decimal point selector.

25

[0014]

 As shown in FIG. 1, the housing top surface of the

electronic device 10 is formed in a substantially rectangular outer shape. The housing top surface includes the display section 12 on an upper side (the upper-edge side of the housing top surface) and the key input section 11 on a lower side (the lower-edge side of the housing top surface).

[0015]

In the display section 12, a display 16 is disposed on a first housing surface 12a which is a first region (the upper side) of the housing top surface. The display 16 has, for example, a horizontally long rectangular display surface and extends from a first-end side (the left-edge side in FIG. 1) of the housing to a second-end side (the right-edge side in FIG. 1) opposite the first-end side.

[0016]

In the key input section 11, multiple keys 14 (operation parts) are arranged from the first-end side to the second-end side of the housing and on a second housing surface 11a which is a second region (the lower side) of the housing top surface. The multiple keys 14 each have an operation surface 14t on their respective key tops. The multiple keys 14, in one example, are arranged at predetermined intervals (key pitches) in each of the row and column directions, with the row direction assumed to be a direction parallel to the upper edge/the lower edge of the housing top surface and the column direction assumed to be a direction parallel to the left edge/the right edge of

the housing top surface.

[0017]

In the electronic device 10 according to the embodiment, the second housing surface 11a of the key input section 11 is inclined in a direction from the first-end side to the second-end side, i.e., in the row direction of the arrangement of the multiple keys 14, at a first inclination angle (angle θ) with respect to the placement surface (the bottom surface of the housing). Also, the first housing surface 12a for the display section 12 is substantially in parallel (or substantially horizontal) to the placement surface (the bottom surface of the housing), or is inclined in the direction from the first-end side to the second-end side, i.e., in the row direction of the arrangement of the multiple keys 14, at a second inclination angle different from the first inclination angle (angle θ) with respect to the bottom surface of the housing.

[0018]

As shown in FIGS. 2 and 4, the second housing surface 11a of the electronic device 10 is formed to be inclined in the row direction, in which the keys 14 are arranged, at the angle θ with respect to the bottom surface 13 of the housing. As an example, it is preferred that the angle θ be in a range of 1° to 9° . It is further preferred that the angle θ be in a range of, for example, 1° to 3° (this will be described in more detail later).

[0019]

FIGS. 1 to 4 illustrate a configuration of the electronic device 10 which is an example where the second housing surface 11a of the key input section 11 has a rightward inclination (the left-edge side is higher than the right-edge side) as depicted in FIGS. 2 and 4. In other words, at least a portion of the operation surface 14t of the key 14 (a first operation part) on the first-end side (the left-edge side) is formed to have a greater height from the placement surface (the bottom surface of the housing) than that of at least a portion of the operation surface 14t of the key 14 (a second operation part) on the second-end side (the right-edge side). For example, the central portion (a first central portion) of the operation surface 14t of the key 14 arranged on the first-end side has a greater height from the placement surface (the bottom surface of the housing) than that of the central portion (a second central portion) of the operation surface 14t of the key 14 arranged on the second-end side.

[0020]

This realizes good operability with the multiple keys 14 and prevents the user from being easily fatigued in the instances where the user operates the electronic device 10 with the right hand (the user is a right-handed user).

[0021]

Note that, assuming that the user operates the electronic device 10 with the left hand (the user is a

left-handed user), it is also possible to adopt a configuration in which the second housing surface 11a of the key input section 11 has a leftward inclination. In other words, at least a portion of the operation surface 14t of the key 14 on the second-end side (the right-edge side) is formed to have a greater height from the placement surface (the bottom surface of the housing) than that of at least a portion of the operation surface 14t of the key 14 on the first-end side (the left-edge side).

[0022]

On the other hand, the display surface of the display section 12 is formed such that its portion on the first-end side has a height from the placement surface (the bottom surface of the housing) not greater than that of its portion on the second-end side. In the example shown in FIGS. 2 and 4, the first-end portion (the left-edge portion) and the second-end portion (the right-edge portion) of the display section 12 are aligned at the same height, and the upper-edge side of the housing top surface is raised from the boundary between the key input section 11 and the display section 12, so that the inclination in the column direction (the front-and-back direction) of the arrangement of the multiple keys 14 is formed.

[0023]

As shown in FIG. 4, the housing of the electronic device 10 is bent at the boundary between the key input section 11 and the display section 12 so that the upper-

edge side of the housing top surface is positioned higher. Accordingly, the first housing surface 12a of the display section 12 is inclined in the column direction in which the multiple keys 14 are arranged, thereby enhancing
5 viewability of the display surface of the display 16.

[0024]

Next, some examples of the configuration of the multiple keys 14 (operation parts) according to the embodiment will be described (as first to seventh
10 configuration examples) with reference to FIGS. 5 to 12.

[0025]

(1) First Configuration Example

FIG. 5 is a diagram showing an exemplary cross-section taken along the line A-A shown in FIG. 1. FIG. 5 only
15 shows, among the multiple keys 14 arranged along the line A-A, two consecutively arranged keys 14. Illustrations in FIGS. 7 to 12 are given in a similar manner.

[0026]

Note that illustrations in FIGS. 5 and 7 to 12
20 discussed below involve deformations for facilitating the understanding of the configuration of the multiple keys 14 provided for the electronic device 10, and as such, they may not perfectly conform to the configurations shown in FIGS. 1 to 4.

25 [0027]

According to the first configuration example as shown in FIG. 5, a substrate 22 is provided at the bottom portion

inside the housing of the electronic device 10, in a state parallel to the bottom surface 13 of the housing. The substrate 22 supports, inside the housing, the multiple keys 14.

5 [0028]

The keys 14 are constituted by, for example, a rubber key 21a, and key tops 14a1 and 14a2 (keytop members). The key tops 14a1 and 14a2 (the keytop members) are formed of, for example, a resin. The rubber key 21a is placed on the upper surface of the substrate 22. The rubber key 21a is formed of, for example, an elastic material such as rubber. The rubber key 21a includes dome-shaped rubber key tops 21a1 and 21a2 (rubber members) formed at positions corresponding to the respective key tops 14a1 and 14a2 of the multiple keys 14.

15 [0029]

The rubber key tops 21a1 and 21a2 are constituted by respective attachment portions 21a11 and 21a22 to which the lower ends of the key tops 14a1 and 14a2 are attached, and respective support portions 21a12 and 21a22 which support the attachment portions 21a11 and 21a21 in a state separated from the substrate 24.

20 [0030]

The attachment portions 21a11 and 21a22 are supported by the support portions 21a12 and 21a22 so that they are normally separated from the substrate 24 but are pressed downward until they contact the substrate 24 at the time of

a depressing action, in order to provide operability in response to a depressing action on the key tops 14a1 and 14a2 attached on the respective attachment portions 21a11 and 21a21.

5 [0031]

The rubber key tops 21a1 and 21a2 are standardized for providing the same operability (feel of a click) at depressing actions on the key tops 14a1 and 14a2.

In other words, the rubber key tops 21a1 and 21a2 are
10 formed from the same material (constituent), the same shape, and the same size to substantially equal each other in mass, etc.

[0032]

As used herein, a "feel of a click" refers to a sense
15 taken by the user upon recognizing a repulsion (an elastic force) produced by the rubber key top 21a1 or 21a2 squashed by the user's depressing action on the key top 14a1 or 14a2.

[0033]

20 FIG. 6 is a plan view showing an example of the rubber key 21a according to the embodiment.

[0034]

As shown in FIG. 6, the rubber key 21a has multiple rubber key tops at positions coinciding with the multiple
25 keys 14 arranged on the second housing surface 11a of the key input section 11 shown in FIG. 1. In FIG. 6, the rubber key tops 21a1 and 21a2, to which the respective key tops

14a1 and 14a2 of the two keys arranged along the line A-A are attached, are included.

[0035]

To the rubber key tops 21a1 and 21a2, the respectively
5 corresponding key tops 14a1 and 14a2 are attached via the attachment portions 21a11 and 21a22 so that their key stroke directions (sliding directions) are made perpendicular to the bottom surface 13 of the housing (the placement surface of the housing).

10 [0036]

The rubber key tops 21a1 and 21a2 (the attachment portions 21a11 and 21a22) are each provided with a conductive member at their bottoms so that the rubber key tops 21a1 and 21a2 pressed downward by the depressing
15 action on the key tops 14a1 and 14a2 will cause the conductive members to contact electrodes arranged on the substrate 22 for the detection of key depression events.

[0037]

The key tops 14a1 and 14a2 are formed to have mutually
20 different heights, each being a height from the bottom surface (the lower end) to the operation surface, according to their arrangement positions in the area from the first-end side (the key top 14a1 side) to the second-end side (the key top 14a2 side). In FIG. 5, the second housing
25 surface 11a of the key input section 11 is inclined to the right, and as such, a height Ta1 of the key top 14a1 arranged on the first-end side, i.e., the height from its

bottom surface to operation surface 14ta1, is greater than a height Ta2 of the key top 14a2 arranged on the second-end side, i.e., the height from its bottom surface to operation surface 14ta2.

5 [0038]

Accordingly, the operation surfaces 14ta1 and 14ta2 are set at the same height from the inclined second housing surface 11a so that the heights of the operation surfaces 14ta1 and 14ta2 from the bottom surface 13 of the housing
10 (the placement surface of the housing) show a stepped profile according to the inclination angle θ of the second housing surface 11a.

[0039]

While FIG. 5 shows only the two key tops 14a1 and
15 14a2, the multiple key tops arranged from the first-end side to the second-end side are formed in a similar configuration to that of the key tops 14a1 and 14a2 so that the operation surfaces of the multiple key tops are stepped according to the inclination angle θ . Basically, a constant
20 height difference is set between operation surfaces of the multiple consecutive key tops.

[0040]

The second housing surface 11a (the housing top surface) has openings corresponding to the multiple keys
25 14, respectively. The openings are each formed in such a manner that the opening wall surface is substantially perpendicular (vertical) to the bottom surface 13 of the

housing (the placement surface of the housing). The key tops 14a1 and 14a2 slidably pass through the corresponding openings, and their respective operation surfaces 14ta1 and 14ta2 are supported at levels higher than the second housing surface 11a in the normal state. As such, the side surfaces of the key tops 14a1 and 14a2 each extend substantially in parallel to the opening wall surface of the corresponding opening and face this corresponding opening wall surface with a slight clearance therebetween.

[0041]

Also, ribs 31a1 and 31a2 (slide assisting members) are formed to extend in the sliding direction of the key tops 14a1 and 14a2, i.e., the direction perpendicular to the bottom surface 13 of the housing (the placement surface of the housing), from the respective openings of the second housing surface 11a. The side surfaces of the ribs 31a1 and 31a2 facing the respective key tops 14a1 and 14a2 each extend substantially in parallel to the corresponding key top 14a1 or 14a2 and face the corresponding key top 14a1 or 14a2 with a slight clearance therebetween. The ribs 31a1 and 31a2, extending in the sliding direction of the key tops 14a1 and 14a2 from the respective openings, can prevent the key tops 14a1 and 14a2 from wobbling in such a manner as to keep them within the slight clearance during their sliding movement.

[0042]

The second housing surface 11a (the housing top

surface) is inclined at the angle θ , and the attachment portions 21a11 and 21a22 have the same height (at the same level) from the bottom surface 13 of the housing. As such, the ribs 31a1 and 31a2 are each formed to have lengths from the back of the second housing surface 11a (the inner surface of the housing) to the position abutting the flanged bottom of the key top 14a1 or 14a2 (or to the contact position in the non-operating state) such that the length on the first-end side (the key top 14a1 side) is greater than the length on the second-end side (the key top 14a2 side). In other words, the ribs 31a1 and 31a2 have lengths varying in the sliding direction of the key tops 14a1 and 14a2 (the direction perpendicular to the bottom surface 13 of the housing) according to the heights of the key tops 14a1 and 14a2.

[0043]

Therefore, with the respective ribs 31a1 and 31a2, the key tops 14a1 and 14a2 are prevented from wobbling.

[0044]

As shown in FIG. 5, the operation surfaces 14ta1 and 14ta2 (upper surfaces) of the key tops 14a1 and 14a2 are each formed to be in parallel to the bottom surface 13. In other words, in instances where the electronic device 10 is placed in a horizontal site, the operation surfaces 14ta1 and 14ta2 of the key tops 14a1 and 14a2 are horizontal. Also, heights L1 and L2 of the respective key tops 14a1 and 14a2 decrease in order from the key top 14a1 on the first-

end side and the key top 14a2 on the second-end side.

[0045]

The key tops 14a1 and 14a2 are formed in an analogous shape with a comparable stroke length defined by the movable ranges of the rubber key tops 21a1 and 21a2, and therefore, the heights L1 and L2 from the bottom surface 13 show a stepped profile according to the inclination angle θ of the second housing surface 11a as shown in FIGS. 2 and 3.

10 [0046]

In the electronic device 1 according to the embodiment as shown in FIGS. 2 and 4, the second housing surface 11a of the key input section 11 is inclined in the row direction of the keys 14 at the angle θ with respect to the bottom surface 13, and the operation surface 14t of the key 14 disposed on the first-end side is higher than the operation surface 14t of the key 14 disposed on the second-end side. This realizes good operability with the keys 14 and prevents the user from being easily fatigued.

20 [0047]

Also, the rubber key 21a (the rubber key tops 21a1 and 21a2) has a standardized configuration (material / shape (mass)) for the multiple keys 14, while the key tops 14a1 and 14a2 have mutually different heights from their respective bottom surfaces to operation surfaces 14ta1 and 14ta2. This realizes reduced variations in operability while having different heights of the operation surfaces

25

14ta1 and 14ta2 of the key tops 14a1 and 14a2 from the bottom surface 13 of the housing.

[0048]

(2) Second Configuration Example

5 FIG. 7 is a diagram showing an exemplary cross-section taken along the line A-A shown in FIG. 1.

[0049]

10 The second configuration example is basically similar to the first configuration example. More specifically, keys 14 are constituted by, for example, a rubber key 21b and key tops 14b1 and 14b2 (keytop members). The key tops 14b1 and 14b2 (the keytop members) are formed of, for example, a resin. The rubber key 21b is placed on the upper surface of the substrate 22. Similar to the rubber key 21a described
15 above, the rubber key 21b is formed of, for example, an elastic material such as rubber. The rubber key 21b includes dome-shaped rubber key tops 21b1 and 21b2 (rubber members) formed at positions corresponding to the respective key tops 14b1 and 14b2 of the multiple keys 14.

20 [0050]

25 The rubber key tops 21b1 and 21b2 are formed in a similar configuration to that of the rubber key tops 21a1 and 21a2 in the first configuration example (FIG. 5). Also, the ribs 31b1 and 31b2 are formed in a similar configuration to that of the ribs 31a1 and 31a2 in the first configuration example (FIG. 5).

[0051]

Similar to the first configuration example, the key tops 14b1 and 14b2 are formed such that a height Tb1 of the key top 14b1 arranged on the first-end side, i.e., the height from its bottom surface to operation surface 14tb1, is greater than a height Tb2 of the key top 14b2 arranged on the second-end side, i.e., the height from its bottom surface to operation surface 14tb2.

[0052]

For the key tops 14b1 and 14b2 in the second configuration example, a hollowing-out amount from components is differentiated for each key. The key tops 14b1 and 14b2, as in the first configuration example, are formed to have mutually different heights, each being a height from the bottom surface to the operation surface, according to their arrangement positions in the area from the first-end side (the key top 14a1 side) to the second-end side (the key top 14a2 side), and the key top 14b1 on the first-end side has a greater height than the key top 14b2. As such, assuming that the components are not hollow, the key top 14b1 has a greater mass.

[0053]

According to the second configuration example, a greater hollowing-out amount is adopted for components having a greater height from the bottom surface to the operation surface so that the multiple key tops arranged in the area from the first-end side to the second-end side have substantially the same mass. In the example shown in

FIG. 7, as one exemplary form, the key top 14b1 is hollowed out with support members 41b1 left inside, and the key top 14b2 is hollowed out with more support members 41b2 left as compared to the key top 14b1.

5 [0054]

Thus, at the same time as realizing unified operability with the multiple keys 14 by standardizing the configuration (material / shape (mass)) of the rubber key 21b for the multiple keys 14, the masses of the key tops themselves, i.e., the key tops 14b1 and 14b2, can be made
10 substantially equal to each other by adjusting the hollowed-out amounts from the key tops 14b1 and 14b2. Accordingly, a burden on the rubber key 21b (the rubber key tops 21b1 and 21b2) is reduced and an improved durability
15 can also be realized.

[0055]

(3) Third Configuration Example

FIG. 8 is a diagram showing an exemplary cross-section taken along the line A-A shown in FIG. 1.

20 [0056]

The third configuration example is basically similar to the first configuration example. More specifically, similar to the first configuration example, keys 14 are constituted by, for example, a rubber key 21d, and key tops 14d1 and 14d2 (keytop members). The key tops 14d1 and 14d2
25 (the keytop members) are formed of, for example, a resin. The rubber key 21d (a rubber member) is placed on the upper

surface of the substrate 22. The rubber key 21d is formed of, for example, an elastic material such as rubber. The rubber key 21d includes dome-shaped rubber key tops 21d1 and 21d2 (rubber members) formed at positions corresponding to the respective key tops 14d1 and 14d2 of the multiple keys 14.

[0057]

The rubber key tops 21d1 and 21d2 are formed in a similar configuration to that of the rubber key tops 21a1 and 21a2 in the first configuration example (FIG. 5).

[0058]

Similar to the first configuration example, the key tops 14d1 and 14d2 are formed such that a height Td1 of the key top 14d1 arranged on the first-end side, i.e., the height from its bottom surface to operation surface 14td1, is greater than a height Td2 of the key top 14d2 arranged on the second-end side, i.e., the height from its bottom surface to operation surface 14td2.

[0059]

Note that the second housing surface 11b in the third configuration example does not have ribs, unlike in the first configuration example.

[0060]

In the third configuration example, support members 34d1 and 34d2 extending in the sliding direction of the key tops 14d1 and 14d2 are formed at positions inside the respective key tops 14d1 and 14d2 of the multiple keys 14

and lateral to the respective rubber key tops 21d1 and 21d2 (the rubber members). The support members 34d1 and 34d2 are, for example, formed integrally with the housing and perpendicularly to the bottom surface 13 of the housing from, for example, above the rubber key 21d.

[0061]

The key tops 14d1 and 14s2 are provided with, at their inside, respective spaces for forming support member receivers 43d1 and 43d2 for slidably retaining the support members 34d1 and 34d2. The support member receivers 43d1 and 43d2, as one exemplary form, are each constituted by a space between the outer peripheral portion and the axial portion of the corresponding key top 14d1 or 14d2 and support the corresponding support member 34d1 or 34d2 within the space. The axial portions of the key tops 14d1 and 14d2 are each formed in, for example, a cylindrical shape, and the corresponding rubber key top 21d1 or 21d2 (the rubber member) is attached to the lower end (the bottom surface) of such a cylindrical portion.

[0062]

The key tops 14d1 and 14d2 have the respective flanges 42d1 and 42d2 at the lower ends of their outer peripheral portions. The outer peripheral portions of the key tops 14d1 and 14d2 are each formed to have a length from the operation surface 14td1 or 14td2 such that the flanges 42d1 and 42d2 are each placed at the position abutting the back of the second housing surface 11a (the inner surface of the

housing) (or at the contact position in the non-operating state).

[0063]

The support member receivers 43d1 and 43d2 (spaces)
5 are each formed to have, for example, the maximum length
(such as a length up to the vicinity of the operation
surface 14td1) according to the heights Td1 and Td2 of the
key tops 14d1 and 14d2. The support members 34d1 and 34d2
are also each formed to have, for example, the maximum
10 length according to the heights Td1 and Td2 of the key tops
14d1 and 14d2, within the range where the key tops 14d1 and
14d2 can slide by means of the support member receivers
43d1 and 43d2 (spaces). In other words, in the
configuration shown in FIG. 8, the support member receiver
15 43d1 is longer than the support member receiver 43d2, and
the support member 34d1 is longer than the support member
34d2.

[0064]

This enables the support member receivers 43d1 and
20 43d2 and the support members 34d1 and 34d2 to provide the
longest-possible support for the key tops 14d1 and 14d2 at
their sliding movement (at the stroke caused by a
depressing action). Therefore, the wobbling of the key tops
14d1 and 14d2 can be minimized.

25 [0065]

(4) Fourth Configuration Example

FIG. 9 is a diagram showing an exemplary cross-section

taken along the line A-A shown in FIG. 1.

[0066]

The fourth configuration example is basically similar to the first configuration example. More specifically, similar to the first configuration example, keys 14 are constituted by, for example, a rubber key 21e, and key tops 14e1 and 14e2 (keytop members). The key tops 14e1 and 14e2 (the keytop members) are formed of, for example, a resin. The rubber key 21e is placed on the upper surface of the substrate 22. The rubber key 21e is formed of, for example, an elastic material such as rubber. The rubber key 21e includes dome-shaped rubber key tops 21e1 and 21e2 (rubber members) formed at positions corresponding to the respective key tops 14e1 and 14e2 of the multiple keys 14.

[0067]

The rubber key tops 21e1 and 21e2 are formed in a similar configuration to that of the rubber key tops 21a1 and 21a2 in the first configuration example (FIG. 5).

[0068]

Similar to the first configuration example, the key tops 14e1 and 14e2 are formed such that a height Te_1 of the key top 14d1 arranged on the first-end side, i.e., the height from its bottom surface to operation surface 14te1, is greater than a height Te_2 of the key top 14e2 arranged on the second-end side, i.e., the height from its bottom surface to operation surface 14te2.

[0069]

The second housing surface 11b in the fourth configuration example does not have ribs, unlike in the first configuration example (and similar to the third configuration example). In the fourth configuration example, the key tops 14e1 and 14e2 have, at their respective bottom portions, flanges 45e1 and 45e2 differing in height (thickness) from each other.

[0070]

More specifically, the second housing surface 11b (the housing top surface) is inclined at the angle θ , and accordingly, the key tops 14e1 and 14e2 have mutually different heights from their bottom surfaces to the back of the second housing surface 11b (the inner surface of the housing). The flanges 45e1 and 45e2 are each formed to have a thickness that is in accordance with the height of the corresponding key top 14e1 or 14e2 from the bottom surface to the back of the second housing surface 11b (the inner surface of the housing), such that the upper surfaces of the flanges 45e1 and 45e2 are each placed at the position facing the back of the second housing surface 11b (the inner surface of the housing), that is, at the position abutting the same or at the contact position in the non-operating state. As such, the flange 45e1 formed at the key top 14e1 has a height T_{e11} which is greater than a height T_{e21} of the flange 45e2 formed at the key top 14e2 (the former is thicker than the latter).

[0071]

Therefore, even without the ribs formed at the openings of the second housing surface 11a (the housing top surface) as in the first configuration example, the key tops 14e1 and 14e2 can be stably held via the second housing surface 11b so that wobbling can be suppressed.

[0072]

(5) Fifth Configuration Example

The first to fourth configuration examples have assumed standardizing the configuration (material / shape (mass)) of each rubber key (the rubber key tops) for the multiple keys 14 and mutually differentiating the heights of the key tops from their bottom surfaces to operation surfaces so as to have different heights from the bottom surface 13 of the housing to the respective operation surfaces of the key tops. According to the fifth to seventh configuration examples, spacers are provided for the sake of different heights from the bottom surface 13 of the housing to the respective operation surfaces of the key tops.

[0073]

FIG. 10 is a diagram showing an exemplary cross-section taken along the line A-A shown in FIG. 1.

[0074]

The fifth configuration example is basically similar to the fourth configuration example. More specifically, similar to the fourth configuration example, keys 14 are constituted by, for example, a rubber key 21f, and key tops

14f1 and 14f2 (keytop members). The key tops 14f1 and 14f2 (the keytop members) are formed of, for example, a resin. The rubber key 21f is placed on the upper surface of the substrate 22. The rubber key 21f is formed of, for example, an elastic material such as rubber. The rubber key 21f includes dome-shaped rubber key tops 21f1 and 21f2 (rubber members) formed at positions corresponding to the respective key tops 14f1 and 14f2 of the multiple keys 14. [0075]

10 The rubber key tops 21f1 and 21f2 are formed in a similar configuration to that of the rubber key tops 21a1 and 21a2 in the first configuration example (FIG. 5). [0076]

15 In the fifth configuration example, in order for the heights L1 and L2 from the bottom surface 13 of the housing to the operation surfaces of the key tops 14f1 and 14f2 to have a stepped profile as in the first configuration example, the key tops 14f1 and 14f2 are formed by including respective spacers 51f1 and 52f2 differing in height from each other. While heights Tf1 and Tf2 of the key tops 14f1 and 14f2 excluding the spacers 51f1 and 52f2 are the same, heights Tf11 and Tf21 of the spacers 51f1 and 52f2 are mutually differentiated according to the difference between the heights L1 and L2.

25 [0077]

As such, the height of the key top 14f1 from its lower end to operation surface 14f1 equals Tf1 + Tf11, and the

height of the key top 14f2 from its lower end to operation surface 14f2 equals $Tf2 + Tf12$. Thus, the key top 14f21 arranged on the first-end side has a greater height than the key top 14f2 arranged on the second-end side. In other words, the lower ends of the keys 14 (operation parts) in the context of the fifth configuration example refer to the lower ends of the spacers 51f1 and 52f2.

[0078]

The spacers 51f1 and 52f2, in one example, are formed of a non-elastic material such as a resin. Thus, for the action of depressing the key tops 14f1 and 14f2 to cause the bottom surfaces of the rubber key tops 21f1 and 21f2 to contact the substrate 22, no difference in operability is produced between the key tops 14f1 and 14f2.

[0079]

As described above, the key tops 14f1 and 14f2 in the multiple keys 14 are formed by including the respective spacers 51f1 and 52f2 differing in height from each other. This allows for the standardization of the rubber key 21f and the key tops 14f1 and 14f2 while differentiating the heights from the bottom surface 13 of the housing to the respective operation surfaces of the key tops 14f1 and 14f2. Consequently, variations in operability can be suppressed while reducing the production costs of components.

[0080]

Note that the fifth configuration example is

applicable to the foregoing first to fourth configuration examples. That is, the key tops may be formed by including respective spacers differing in height as in the fifth configuration example, so as to provide mutually different heights of the operation surfaces.

[0081]

(6) Sixth Configuration Example

FIG. 11 is a diagram showing an exemplary cross-section taken along the line A-A shown in FIG. 1.

[0082]

The sixth configuration example is basically similar to the fourth configuration example. More specifically, similar to the fourth configuration example, keys 14 are constituted by, for example, a rubber key 21g, and key tops 14g1 and 14g2 (keytop members). The key tops 14g1 and 14g2 (the keytop members) are formed of, for example, a resin. The rubber key 21g is placed on the upper surface of the substrate 22. The rubber key 21g is formed of, for example, an elastic material such as rubber. The rubber key 21g includes dome-shaped rubber key tops 21g1 and 21g2 (rubber members) formed at positions corresponding to the respective key tops 14g1 and 14g2 of the multiple keys 14.

[0083]

The rubber key tops 21g1 and 21g2 according to the sixth configuration example are formed such that their attachment portions 21g11 and 21g21 enclose respective spacers 52g1 and 52g2. The spacers 52g1 and 52g2 and the

rubber key 21g are not individually formed for a subsequent bonding, etc., but the spacers 52g1 and 52g2 are enclosed at the time of molding the rubber key 21g.

[0084]

5 The rubber key tops 21g1 and 21g2 are formed to have, assuming that the spacers 52g1 and 52g2 are excluded, substantially the same masses as those of the rubber key tops 21a1 and 21a2 in the first configuration example (FIG. 5).

10 [0085]

 It will be assumed that the spacers 52g1 and 52g2 are included in the respective configurations of the key tops 14g1 and 14g2. In other words, the lower ends of the operation parts 14 in the context of the sixth
15 configuration example refer to the lower ends of the spacers 52g1 and 52g2.

[0086]

 In the sixth configuration example, in order for the heights L1 and L2 from the bottom surface 13 of the housing
20 to the operation surfaces of the key tops 14g1 and 14g2 to have a stepped profile as in the first configuration example, a height Tg11 of the spacer 52g1 and a height Tg12 of the spacer 52g2 are mutually differentiated according to the difference between the heights L1 and L2.

25 [0087]

 The spacers 51g1 and 52g2, in one example, are formed of a non-elastic material such as a resin, and the

configuration of the rubber key 21g (the rubber key tops 21g1 and 21g2) is standardized except for the spacers 52g1 and 52g2. Thus, for the action of depressing the key tops 14g1 and 14g2 to cause the bottom surfaces of the rubber
5 key tops 21g1 and 21g2 to contact the substrate 22, no difference in operability is produced between the key tops 14g1 and 14g2.

[0088]

As described above, the rubber key tops 21g1 and 21g2
10 in the multiple keys 14 are formed by enclosing the respective spacers 51g1 and 52g2 differing in height from each other. This allows for the standardization of the rubber key 21g and the key tops 14g1 and 14g2, except for the spacers 52g1 and 52g2, while differentiating the
15 heights from the bottom surface 13 of the housing to the respective operation surfaces of the key tops 14g1 and 14g2. Consequently, variations in operability can be suppressed while reducing the production costs of components.

20 [0089]

(7) Seventh Configuration Example

FIG. 12 is a diagram showing an exemplary cross-section taken along the line A-A shown in FIG. 1.

[0090]

25 The seventh configuration example is basically similar to the fifth configuration example. More specifically, keys 14 are constituted by, for example, a rubber key 21h, and

key tops 14h1 and 14h2 (keytop members). The key tops 14h1 and 14h2 (the keytop members) are formed of, for example, a resin.

[0091]

5 In the seventh configuration example, the key tops 14h1 and 14h2 are formed such that a height Th1 of the key top 14h1 arranged on the first-end side, i.e., the height from its bottom surface to operation surface, and a height Th2 of the key top 14h2 arranged on the second-end side,
10 i.e., the height from its bottom surface to operation surface, are substantially the same. That is, according to the seventh configuration example, not only is the configuration (material / shape (mass)) of the rubber key 21h (rubber key tops 21h1 and 21h2) standardized, but also
15 the key tops 14h1 and 14h2 are standardized.

[0092]

 In the seventh configuration example, a substrate 220 constituted by, for example, a flexible substrate is provided at the inner bottom of the housing of the
20 electronic device 10. The substrate 220 supports, inside the housing, the multiple keys 14.

[0093]

 The inner bottom of the housing is formed to have a stepped profile in the direction from the first-end side to
25 the second-end side in harmonization with the areas where the multiple keys 14 are provided respectively. In other words, the inner bottom of the housing is formed such that

its region (a first region) on the first-end side has a greater height from the housing bottom surface than its region (a second region) on the second-end side.

[0094]

5 In the seventh configuration example, in order for the heights L1 and L2 from the bottom surface 13 of the housing to the operation surfaces of the key tops 14h1 and 14h2 to have a stepped profile as in the first configuration example, the inner bottom of the housing is stepped. The
10 heights of the first and second regions from the bottom surface 13 of the housing are mutually differentiated according to the difference between the heights L1 and L2.

[0095]

 The substrate 220, constituted by a flexible
15 substrate, is laid over the stepped inner bottom of the housing in such a manner as to conform to the shape of the inner bottom. As such, in terms of the height from the housing bottom surface to the substrate 220, a region 220h1 (height Lh1) on the first-end side is higher than a region
20 220h2 (height Lh2) on the second-end side ($Lh1 > Lh2$).

[0096]

 The rubber key 21h is placed on the upper surface of the substrate 220. The rubber key 21h is formed of, for example, an elastic material such as rubber. The rubber key
25 21h includes dome-shaped rubber key tops 21h1 and 21h2 (rubber members) formed at positions corresponding to the respective key tops 14h1 and 14h2 of the multiple keys 14.

In other words, the rubber key top 21h1 (the key top 14h1) is arranged in the region 220h1 (the first region) on the first-end side, and the rubber key top 21h2 (the key top 14h2) is arranged in the region 220h2 (the second region) on the second-end side lower than the first region.

[0097]

The rubber key tops 21h1 and 21h2 are formed in a similar configuration to that of the rubber key tops 21h1 and 21h2 in the first configuration example (FIG. 5).

[0098]

As described above, the configuration of the rubber key 21h (the rubber key tops 21h1 and 21h2), as well as the configurations of the key tops 14h1 and 14h2, are standardized so that the variations in operability can be suppressed. Together, the inner bottom of the housing is stepped for regions where the keys 14 are arranged so that the heights from the bottom surface 13 of the housing to the respective operation surfaces of the key tops 14h1 and 14h2 can be mutually differentiated.

[0099]

Note that the seventh configuration example is also implementable with the configurations of the rubber key (rubber key tops) and the key tops according to the fifth or sixth configuration example.

[0100]

The present invention is not limited to the foregoing embodiments. For practical implementation, various

modifications may be adopted without departing from its
gist. Moreover, the foregoing embodiments involve various
aspects, and appropriate combinations of the features
disclosed herein shall permit various inventions to be
5 derived. For example, one or more of the features disclosed
in the embodiments may be omitted or combined. Provided
that such modifications can solve the intended problem and
bring the intended effects as discussed above, the
modifications should each be deemed an invention.

10

INDUSTRIAL APPLICABILITY

[0101]

15

According to the present invention, it is possible to
provide an electronic device having multiple operation
parts which entail reduced variations in operability even
if they differ in height from each other.

REFERENCE SIGNS LIST

[0102]

20

- 10 ... Electronic device
- 11 ... key input section
- 12 ... Display section
- 13 ... Bottom surface
- 14 ... Key
- 16 ... Display

CLAIMS

1. An electronic device comprising:

a plurality of operation parts arranged from a first-end side to a second-end side of a housing and each

5 including a keytop member having an operation surface,

characterized in that

the keytop member corresponding to a first operation part, which is one of the operation parts arranged on the first-end side, has a lower-end-to-operation-surface height

10 greater than that of the keytop member corresponding to a second operation part, which is one of the operation parts arranged on the second-end side.

2. The electronic device according to claim 1, characterized in that

15 the operation parts each further include a rubber member supporting the corresponding keytop member, and

the rubber members of the first operation part and the second operation part are standardized in shape, size, and material.

20 3. The electronic device according to claim 1 or 2, characterized in that

a top surface of the housing is inclined in a direction from the first-end side to the second-end side at a predetermined inclination angle with respect to a placement surface,

25 the top surface of the housing includes openings through which the keytop members slidably pass in a

direction perpendicular to the placement surface,

slide assisting members are formed at the openings of the top surface of the housing and each extend in a sliding direction of the corresponding keytop member, the slide assisting members each being configured to prevent the corresponding keytop member from sliding in a direction different from the sliding direction, and

the slide assisting members have lengths in the sliding direction which vary according to the heights of the keytop members corresponding to the respective first and second operation parts.

4. The electronic device according to any one of claims 1 to 3, characterized in that a hollowing-out amount from the keytop member corresponding to the first operation part is greater than that from the keytop member corresponding to the second operation part.

5. The electronic device according to claim 2, characterized in that

in the operation parts, support members each extending in a sliding direction of the corresponding keytop member are formed at a position inside the corresponding keytop member and lateral to the corresponding rubber member, and

the support members have lengths differing from each other according to the heights of the keytop members corresponding to the respective first and second operation parts.

6. The electronic device according to any one of

claims 1, 2, and 4, characterized in that

a top surface of the housing is inclined in a direction from the first-end side to the second-end side at a predetermined inclination angle with respect to a placement surface,

the top surface of the housing includes openings through which the keytop members slidably pass in a direction perpendicular to the placement surface,

the keytop members corresponding to the respective first and second operation parts each include a portion facing an inner surface of the housing that corresponds to the top surface of the housing, and

the keytop members corresponding to the first and second operation parts have mutually different lengths from respective lower ends to positions facing the inner surface of the housing that corresponds to the top surface of the housing.

7. The electronic device according to any one of claims 1 to 6, characterized in that

the keytop members each include a spacer, and the spacer in the first operation part is thicker than the spacer in the second operation part so that the lower-end-to-operation-surface height of the keytop member corresponding to the first operation part is greater than that of the keytop member corresponding to the second operation part.

8. An electronic device comprising:

a plurality of operation parts arranged from a first-end side to a second-end side of a housing and each including a keytop member having an operation surface; and

5 a substrate provided with the operation parts, characterized in that

the keytop member corresponding to a first operation part, which is one of the operation parts arranged on the first-end side, has a lower-end-to-operation-surface height substantially equal to that of the keytop member
10 corresponding to a second operation part, which is one of the operation parts arranged on the second-end side,

the first operation part is arranged in a first region of the substrate,

the second operation part is arranged in a second
15 region of the substrate, and

the first region has a greater height from a bottom surface of the housing to the substrate than that of the second region.

9. The electronic device according to claim 8,
20 characterized in that

the operation parts each further include a rubber member supporting the corresponding keytop member, and

the rubber members of the first operation part and the second operation part are standardized in shape, size, and
25 material.

10. The electronic device according to claim 8 or 9, characterized in that the substrate is constituted by a

flexible substrate which is bendable.