

2019-103363 U1 PCT

TEXTURED SURFACES OF EXPANDING METAL FOR CENTRALIZER, MIXING, AND DIFFERENTIAL STICKING

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to U.S. Application Serial No. 16/804,258 filed on February 28, 2020, entitled “TEXTURED SURFACES OF EXPANDING METAL FOR CENTRALIZER, MIXING, AND DIFFERENTIAL STICKING,” is commonly assigned with this application and incorporated herein by reference in its entirety.

BACKGROUND

[0002] Wellbores are sometimes drilled into subterranean formations that contain hydrocarbons to allow recovery of the hydrocarbons. Some wellbore servicing methods employ wellbore tubulars that are lowered into the wellbore for various purposes throughout the life of the wellbore. Since wellbores are not generally perfectly vertical, centralizers are used to maintain the wellbore tubulars aligned within the wellbore. Alignment may help prevent any friction between the wellbore tubular and the side of the wellbore wall or casing, potentially reducing any damage that may occur.

BRIEF DESCRIPTION

[0003] Reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:

[0004] FIG. 1 is a perspective view of a well system including an exemplary operating environment that the apparatuses, systems and methods disclosed herein may be employed; and

[0005] FIGs. 2-12 illustrate various different configurations for an expandable metal centralizer designed and manufactured according to the disclosure.

DETAILED DESCRIPTION

[0006] In the drawings and descriptions that follow, like parts are typically marked throughout the specification and drawings with the same reference numerals, respectively. The drawn figures are not necessarily, but may be, to scale. Certain features of the disclosure may be shown exaggerated in scale or in somewhat schematic form and some details of certain elements may not be shown in the interest of clarity and conciseness.

2019-103363 U1 PCT

[0007] The present disclosure may be implemented in embodiments of different forms. Specific embodiments are described in detail and are shown in the drawings, with the understanding that the present disclosure is to be considered an exemplification of the principles of the disclosure, and is not intended to limit the disclosure to that illustrated and described herein. It is to be fully recognized that the different teachings of the embodiments discussed herein may be employed separately or in any suitable combination to produce desired results. Moreover, all statements herein reciting principles and aspects of the disclosure, as well as specific examples thereof, are intended to encompass equivalents thereof. Additionally, the term, "or," as used herein, refers to a non-exclusive or, unless otherwise indicated.

[0008] Unless otherwise specified, use of the terms "connect," "engage," "couple," "attach," or any other like term describing an interaction between elements is not meant to limit the interaction to direct interaction between the elements and may also include indirect interaction between the elements described.

[0009] Unless otherwise specified, use of the terms "up," "upper," "upward," "uphole," "upstream," or other like terms shall be construed as generally toward the surface of the well; likewise, use of the terms "down," "lower," "downward," "downhole," or other like terms shall be construed as generally toward the bottom, terminal end of a well, regardless of the wellbore orientation. Use of any one or more of the foregoing terms shall not be construed as denoting positions along a perfectly vertical or horizontal axis. Unless otherwise specified, use of the term "subterranean formation" shall be construed as encompassing both areas below exposed earth and areas below earth covered by water, such as ocean or fresh water.

[0010] Referring to FIG. 1, depicted is a perspective view of a well system 100 including an exemplary operating environment that the apparatuses, systems and methods disclosed herein may be employed. For example, the well system 100 could use an expandable metal centralizer according to any of the embodiments, aspects, applications, variations, designs, etc. disclosed in the following paragraphs. The well system 100 illustrated in FIG. 1 includes a rig 110 extending over and around a wellbore 120 formed in a subterranean formation 130. As those skilled in the art appreciate, the wellbore 120 may be fully cased, partially cased, or an open hole wellbore. In the illustrated embodiment of FIG. 1, the wellbore 120 is partially cased, and thus includes a cased region 140 and an open hole region 145. The cased region 140, as is depicted, may employ casing 150 that is held into place by cement 160.

2019-103363 U1 PCT

[0011] The well system 100 illustrated in FIG. 1 additionally includes a downhole conveyance 170 deploying a downhole tool assembly 180 within the wellbore 120. The downhole conveyance 170 can be, for example, tubing-conveyed, wireline, slickline, drill pipe, production tubing, work string, or any other suitable means for conveying the downhole tool assembly 180 into the wellbore 120. In one particular advantageous embodiment, the downhole conveyance 170 is American Petroleum Institute “API” pipe.

[0012] The downhole tool assembly 180, in the illustrated embodiment, includes a downhole tool 185 and an expandable metal centralizer 190. The downhole tool 185 may comprise any downhole tool that could be positioned and/or anchored within a wellbore. Certain downhole tools 185 that may find particular use in the well system 100 include, without limitation, sealing packers, elastomeric sealing packers, non-elastomeric sealing packers (e.g., including plastics such as PEEK, metal packers such as inflatable metal packers, as well as other related packers), liners, an entire lower completion, one or more tubing strings, one or more screens, one or more production sleeves, etc..

[0013] The expandable metal centralizer 190, in accordance with one embodiment of the disclosure, includes a downhole tubular positioned on the downhole conveyance 170. The expandable metal centralizer 190, in accordance with this embodiment, additionally includes one or more wellbore centralizing elements radially extending from the downhole tubular. Further to this embodiment, at least one of the downhole tubular or the one or more wellbore centralizing elements comprises a metal configured to expand in response to hydrolysis. The expanding metal, in some embodiments, may be described as expanding to a cement like material. In other words, the metal goes from metal to micron-scale particles and then these particles expand and lock together to, in essence, lock the expandable metal centralizer 190 in place. The reaction may, in certain embodiments, occur in less than 2 days in a reactive fluid and in downhole temperatures. Nevertheless, the time of reaction may vary depending on the reactive fluid, the expandable metal used, and the downhole temperature.


[0014] In some embodiments the reactive fluid may be a brine solution such as may be produced during well completion activities, and in other embodiments, the reactive fluid may be one of the additional solutions discussed herein. The metal, pre-expansion, is electrically conductive in certain embodiments. The metal may be machined to any specific size/shape, extruded, formed, cast or other conventional ways to get the desired shape of a metal, as will be discussed in

2019-103363 U1 PCT


greater detail below. Metal, pre-expansion, in certain embodiments has a yield strength greater than about 8,000 psi, e.g., 8,000 psi +/- 50%.

[0015] The hydrolysis of any metal can create a metal hydroxide. The formative properties of alkaline earth metals (Mg - Magnesium, Ca - Calcium, etc.) and transition metals (Zn - Zinc, Al - Aluminum, etc.) under hydrolysis reactions demonstrate structural characteristics that are favorable for use with the present disclosure. Hydration results in an increase in size from the hydration reaction and results in a metal hydroxide that can precipitate from the fluid.


[0016] The hydration reactions for magnesium is:



where $\text{Mg}(\text{OH})_2$ is also known as brucite. Another hydration reaction uses aluminum hydrolysis. The reaction forms a material known as Gibbsite, bayerite, and norstrandite, depending on form. The hydration reaction for aluminum is:



Another hydration reactions uses calcium hydrolysis. The hydration reaction for calcium is:



Where $\text{Ca}(\text{OH})_2$ is known as portlandite and is a common hydrolysis product of Portland cement. Magnesium hydroxide and calcium hydroxide are considered to be relatively insoluble in water. Aluminum hydroxide can be considered an amphoteric hydroxide, which has solubility in strong acids or in strong bases.

[0017] In an embodiment, the metallic material used can be a metal alloy. The metal alloy can be an alloy of the base metal with other elements in order to either adjust the strength of the metal alloy, to adjust the reaction time of the metal alloy, or to adjust the strength of the resulting metal hydroxide byproduct, among other adjustments. The metal alloy can be alloyed with elements that enhance the strength of the metal such as, but not limited to, Al - Aluminum, Zn - Zinc, Mn - Manganese, Zr - Zirconium, Y - Yttrium, Nd - Neodymium, Gd - Gadolinium, Ag - Silver, Ca - Calcium, Sn - Tin, and Re - Rhenium, Cu - Copper. In some embodiments, the alloy can be alloyed with a dopant that promotes corrosion, such as Ni - Nickel, Fe - Iron, Cu - Copper, Co - Cobalt, Ir - Iridium, Au - Gold, C - Carbon, gallium, indium, mercury, bismuth, tin, and Pd - Palladium. The metal alloy can be constructed in a solid solution process where the elements are

2019-103363 U1 PCT

combined with molten metal or metal alloy. Alternatively, the metal alloy could be constructed with a powder metallurgy process. The metal can be cast, forged, extruded, sintered, mill machined, lathe machined, stamped, eroded or a combination thereof.

[0018] Optionally, non-expanding components may be added to the starting metallic materials. For example, ceramic, elastomer, plastic, epoxy, glass, or non-reacting metal components can be embedded in the expanding metal or coated on the surface of the metal. Alternatively, the starting metal may be the metal oxide. For example, calcium oxide (CaO) with water will produce calcium hydroxide in an energetic reaction. Due to the higher density of calcium oxide, this can have a 260% volumetric expansion where converting 1 mole of CaO goes from 9.5cc to 34.4cc of volume. In one variation, the expanding metal is formed in a serpentinite reaction, a hydration and metamorphic reaction. In one variation, the resultant material resembles a mafic material. Additional ions can be added to the reaction, including silicate, sulfate, aluminate, and phosphate. The metal can be alloyed to increase the reactivity or to control the formation of oxides.

[0019] The expandable metal can be configured in many different fashions, as long as an adequate volume of material is available for fully expanding. For example, the expandable metal may be formed into a single long tube, multiple short tubes, rings, alternating steel and swellable rubber and expandable metal rings, among others. Additionally, a coating may be applied to one or more portions of the expandable metal to delay the expanding reactions.

[0020] In practice, the downhole tool assembly 180 can be moved down the wellbore 120 via the downhole conveyance 170 to a desired location. Once the downhole tool assembly 180, including the downhole tool 185 and the expandable metal centralizer 190 reach the desired location, the expandable metal centralizer 190 may be set in place according to the disclosure. In one embodiment, the expandable metal centralizer 190 is subjected to a wellbore fluid sufficient to expand the downhole tubular or one or more wellbore centralizing elements into contact with the wellbore 120 and thereby anchor the one or more downhole tools within the wellbore 120, or alternatively seal the wellbore 120.

[0021] In the embodiment of FIG. 1, the expandable metal centralizer 190 is positioned in the open hole region 145 of the wellbore 120. The expandable metal centralizer 190 is particularly useful in open hole situations, as the expandable metal is well suited to adjust to the surface irregularities that may exist in open hole situations. Moreover, the expandable metal, in certain

2019-103363 U1 PCT

embodiments, may penetrate into the formation of the open hole region 145 and create a bond into the formation, and thus not just at the surface of the formation. Notwithstanding the foregoing, the expandable metal centralizer 190 is also suitable for a cased region 140 of the wellbore 120.

[0022] As is illustrated, the exterior surface of the expandable metal centralizer 190 may be textured. In certain instances, the textured surface has a plurality of undulations, crenellations, corrugations, ridges, depressions, or other surface variations where the radial amplitude of the surface variation is at least about 1 mm (e.g., about .04 inches). In yet another embodiment, the radial amplitude of the surface variation is at least about 1.25 mm (e.g., about .05 inches), and in yet another embodiment the radial amplitude of the surface variation is between about 1.25 mm (e.g., about .06 inches) and about 25 mm (e.g., about 1.0 inches). Any known or hereafter discovered method for creating the textured surface is within the scope of the disclosure.

[0023] In one example, axial, helical, or circumferential grooves may be placed on the outside diameter of the expandable metal, for example as described below with regard to FIG. 3. These grooves allow increased area for fluid to pass the metal. The grooves in the metal can serve as a static mixer for enhancing the mixing behavior and flow distribution of a circulated fluid. The static mixer can be a flow division process that stirs the fluid. The static mixer can be a rotational circulation that causes radial mixing of the fluid. Mixing the fluid is important in wellbore cleanup because often the low-side of a horizontal well is poorly cleaned and/or poorly cemented. Mixing minimizes the likelihood of problems. In effect, these grooves may extend radially outward from the downhole tubular or radially inward from the downhole tubular to allow the expanding metal packer to act as a mixer and as a centralizer in the time before the metal has chemically reacted.

[0024] The texture can be created by embedding components into or onto the expanding metal, as described below with regard to FIGs. 8 and 9. The embedded components can be metal, ceramic, glass, or polymer. In one case, the embedded components are an expanding metal, such as a harder expanding metal that has a slower reaction time. These components can be threaded, bonded, bolted, screwed, brazed, interference fit, tapered, epoxied, or otherwise mechanically coupled to the expanding metal. In one embodiment, steel lugs are threaded into the expanding metal, as described below with regard to FIG. 9. The lugs hold the expanding metal off of the wellbore in order to minimize differential sticking. The lugs also reduce the likelihood of

2019-103363 U1 PCT

abrasion on the expanding metal during run-in. In another example, ceramic wear buttons are affixed to the exterior surface in order to reduce abrasion during installation. In another example, a PTFE bar is affixed to the exterior surface in order to reduce friction during installation.

[0025] In another example, strips of a slower-reacting expanding metal are affixed to the outside diameter, as described below with regard to FIG. 5. In another example, the surface of the expanding metal has a waffled surface with a combination of grooves, for example as described below with regard to FIG. 11. The surface can also feature divots, treads, bumps, or ridges. The features can be square, sloped, or curved in profile with convex or concave aspects.

[0026] Turning to FIGs. 2-12, illustrated are various different configurations for an expandable metal centralizer designed and manufactured according to the disclosure. Turning initially to FIG. 2, illustrated is one embodiment of an expandable metal centralizer 200 designed and manufactured according to the disclosure. In accordance with the disclosure, the expandable metal centralizer 200 is positionable on, or positioned on as is the case in FIG. 2, a downhole conveyance 290. While the downhole conveyance 290 can be wireline, slickline, coiled tubing, work string, or any other suitable means for conveying downhole tools within a wellbore, the downhole conveyance 290 illustrated in FIG. 2 is API pipe.

[0027] In accordance with one embodiment of the disclosure, the expandable metal centralizer 200 includes a downhole tubular 210. The downhole tubular 210, in the illustrated embodiment, is positioned on the downhole conveyance 290. The expandable metal centralizer 200, in the illustrated embodiment of FIG. 2, further includes one or more wellbore centralizing elements 220 radially extending from the downhole tubular 210. In accordance with this embodiment, at least one of the downhole tubular 210 or the one or more wellbore centralizing elements 220 elements comprises a metal configured to expand in response to hydrolysis, as discussed in detail above.

[0028] In the embodiment illustrated in FIG. 2, the downhole tubular 210 and the one or more wellbore centralizing elements 220 are integrally formed with each other. Such may be the case when the downhole tubular 210 and the one or more wellbore centralizing elements 220 are formed as a single unit in a single manufacturing process. Accordingly, the downhole tubular 210 and the one or more wellbore centralizing elements 220 could comprise the same material, for example a metal configured to expand in response to hydrolysis. In certain other embodiments, as discussed below, the downhole tubular 210 and the one or more wellbore

2019-103363 U1 PCT

centralizing elements 220 are not integrally formed with each other, and thus may comprise different materials.

[0029] In one embodiment, a combined volume of the expandable metal may be sufficient to expand to anchor one or more downhole tools within the wellbore in response to the hydrolysis. For example, in one embodiment the combined volume of the expandable metal is sufficient to expand to anchor at least about 100,000 Newtons (e.g., about 25,000 lbs.) of weight within the wellbore. In yet another embodiment, the combined volume of the expandable metal is sufficient to expand to anchor at least about 200,000 Newtons (e.g., about 50,000 lbs.) of weight within the wellbore, and in yet another embodiment sufficient to expand to anchor at least about 300,000 Newtons (e.g., about 70,000 lbs.) of weight within the wellbore.

[0030] In another embodiment, a combined volume of the expandable metal may be sufficient to expand to seal an annulus between the downhole conveyance 290 and the wellbore casing or wellbore. In one embodiment, the combined volume of the expandable metal is sufficient to expand to seal at least about 1,000 psi of pressure within the annulus. In yet another embodiment, the combined volume of the expandable metal is sufficient to expand to seal at least about 5,000 psi of pressure within the annulus, and in yet another embodiment sufficient to expand to seal at least about 15,000 psi of pressure within the annulus.

[0031] In the illustrated embodiment of FIG. 2, the expandable metal centralizer 200 includes three wellbore centralizing elements 220 axially positioned along a length (L) of the downhole tubular 210. Furthermore, in the embodiment of FIG. 2 the three wellbore centralizing elements 220 are substantially equally radially spaced about the downhole tubular 210. The phrase “substantially equally radially spaced,” as used in this disclosure, requires that the wellbore centralizing elements 220 be within 30 degrees from perfectly equally radially spaced. Thus, in the embodiment of FIG. 2, the three wellbore centralizing elements 220 are radially spaced from one another by about 120 degrees $\pm$ 30 degrees. In another embodiment, the three wellbore centralizing elements 220 are ideally equally radially spaced about the downhole tubular 210. The phrase “ideally equally radially spaced,” as used in this disclosure, requires that the wellbore centralizing elements 220 be within 10 degrees from perfectly equally radially spaced.

[0032] The expandable metal centralizer 200 illustrated in FIG. 2, additionally include one or more openings (not shown) extending entirely through a wall thickness of the downhole tubular, for accepting one or more fasteners 230 for fixing the downhole tubular 210 to the downhole

2019-103363 U1 PCT

conveyance 290. The one or more openings and one or more fasteners 230 may vary in design and remain within the scope of the disclosure. Nevertheless, in the embodiment of FIG. 2, the one or more openings are threaded openings and the one or more fasteners 230 are set screws. The expandable metal centralizer 200 illustrated in FIG. 2 may additionally include electronics and/or sensors 240 positioned in one of the one or more wellbore centralizing elements 220. Those skilled in the art appreciated the different types of electronics, batteries, and/or sensors 240 that might be located in the one or more wellbore centralizing elements 220, and the purpose for including such.

[0033] Turning briefly to FIG. 3, illustrated is an alternative embodiment of an expandable metal centralizer 300. The expandable metal centralizer 300 is similar in many respects to the expandable metal centralizer 200. Accordingly, like reference numerals have been used to reference similar, if not identical, features. The expandable metal centralizer 300 differs from the expandable metal centralizer 200 in that its downhole tubular 310 and its one or more wellbore centralizing elements 320 are not integrally formed with one another. Accordingly, the downhole tubular 310 and its one or more wellbore centralizing elements 320 may be formed in different manufacturing steps, and thus comprise different materials. For example, in one embodiment the downhole tubular 310 comprises a metal configured to expand in response to hydrolysis and the one or more wellbore centralizing elements 320 do not comprise a metal configured to expand in response to hydrolysis. In another embodiment, the one or more wellbore centralizing elements 320 comprise a metal configured to expand in response to hydrolysis and the downhole tubular 310 does not comprise a metal configured to expand in response to hydrolysis. In yet another embodiment, the downhole tubular 310 comprises a first metal configured to expand in response to hydrolysis and the one or more wellbore centralizing elements 320 comprise a second metal configured to expand in response to hydrolysis. In certain of these embodiments, the first metal and the second metal are different metals configured to expand at different rates in response to hydrolysis. For example, the first metal might expand at a faster rate and the second metal at a slower rate, or vice-versa. In yet other of these embodiments, the first metal and the second metal are the same metal, and thus expand at a same rate in response to hydrolysis.

[0034] The expandable metal centralizer 300 further differs from the expandable metal centralizer 200 in that it employs four wellbore centralizing elements 320, as opposed to three.

2019-103363 U1 PCT

While general shapes have been given for the four wellbore centralizing elements 320 (and the three wellbore centralizing elements 220), many different shapes may be chosen for various different processes. As those skilled in the art appreciate, the less surface area of the centralizing element that contact any surface there around, the less friction. Accordingly, in many embodiments it is advantageous to reduce the amount of contact surface area, while still achieving their centralizing objective. In another variation, the centralizing elements 320 may have different heights so that the tubing is purposefully positioned at an axis that is offset from the centerline of the wellbore, and thus acts as a decentralizer. Thus, according to one embodiment of the disclosure a decentralizer is considered to be one form of a centralizer.

[0035] Additionally, the downhole tubular 310 illustrated in FIG. 3 includes at least two segments 310a, 310b, that connect (e.g., hinge or lock in one embodiment) with respect to each other to form the tubular. Those skilled in the art appreciate the many different configurations for connections that might be used to achieve the purpose at hand. Accordingly, the downhole tubular 310 may be installed on the downhole conveyance 290 without having to slip it over the end of the downhole conveyance 290.

[0036] Turning briefly to FIG. 4, illustrated is an alternative embodiment of an expandable metal centralizer 400. The expandable metal centralizer 400 is similar in many respects to the expandable metal centralizer 300. Accordingly, like reference numerals have been used to reference similar, if not identical, features. The expandable metal centralizer 400 includes a pair of retaining rings 410 (only one visible), for example positioned adjacent a proximal end and a distal end of the downhole tubular 310 (not visible as hidden by the retaining rings 410) for axially fixing the downhole tubular 310 on the downhole conveyance 290. In one embodiment, while the pair of retaining rings 410 axially fixes the downhole tubular 310 on the downhole conveyance 290, the pair of retaining rings 410 allows the downhole tubular 310 to spin about the downhole conveyance 290. In another embodiment, the pair of retaining rings 410 axially and rotationally fixes the downhole tubular 310 on the downhole conveyance 290.

[0037] In accordance with one embodiment of the disclosure, each of the pair of retaining rings 410 includes one or more threaded openings having one or more set screws 230 therein for axially fixing the downhole tubular 310 to the downhole conveyance 290. In one embodiment, the pair of retaining rings 410 does not comprise a metal configured to expand in response to

2019-103363 U1 PCT

hydrolysis, but in another embodiment the pair of retaining rings 410 do comprise a metal configured to expand in response to hydrolysis.

[0038] Turning briefly to FIG. 5, illustrated is an alternative embodiment of an expandable metal centralizer 500. The expandable metal centralizer 500 is similar in many respects to the expandable metal centralizer 200. Accordingly, like reference numerals have been used to reference similar, if not identical, features. The expandable metal centralizer 500 includes three individual vanes 520 extending along a length (L) (e.g., the entire length (L) in the embodiment of FIG. 5) of the downhole tubular 310. In accordance with the embodiment of FIG. 5, central axes 550 of the three individual vanes 520 are substantially parallel with a central axis 560 of the downhole tubular 310. The phrase “substantially parallel” as used herein, requires that the central axes 550 of the three individual vanes 520 be within 30 degrees of exactly parallel in all directions with the central axis 560 of the downhole tubular 310. In accordance with another embodiment, the central axes 550 of the three individual vanes 520 are ideally parallel with a central axis 560 of the downhole tubular 310. The phrase “ideally parallel” as used herein, requires that the central axes 550 of the three individual vanes 520 be within 10 degrees of exactly parallel in all directions with the central axis 560 of the downhole tubular 310. The three individual vanes 520 are illustrated in FIG. 5 as solid vanes, but in other embodiments the three individual vanes 520 could be hollow vanes or tubes.

[0039] Turning briefly to FIG. 6, illustrated is an alternative embodiment of an expandable metal centralizer 600. The expandable metal centralizer 600 is similar in many respects to the expandable metal centralizer 500. Accordingly, like reference numerals have been used to reference similar, if not identical, features. The expandable metal centralizer 600 differs from the expandable metal centralizer 500, for the most part, in that its three individual vanes 620 spiral around the downhole tubular 310. For example, in the embodiment of FIG. 6, the three individual vanes 620 each spiral around the downhole tubular 310 by approximately 120 degrees. Were only two individual vanes 620 exist, each would spiral around the downhole tubular 310 by approximately 180 degrees.

[0040] Turning briefly to FIG. 7, illustrated is an alternative embodiment of an expandable metal centralizer 700. The expandable metal centralizer 700 is similar in many respects to the expandable metal centralizer 600. Accordingly, like reference numerals have been used to reference similar, if not identical, features. The expandable metal centralizer 700 differs from

2019-103363 U1 PCT

the expandable metal centralizer 600, for the most part, in that it includes a single individual vane 720 that spirals around the downhole tubular 310. For example, in the embodiment of FIG. 7, the single individual vane 720 spirals around the downhole tubular 310 by at least 270 degrees, if not a full 360 degrees as shown in FIG. 7. In another embodiment, the single individual vane 720 is substantially parallel to the axis of the tubing and serves to decentralize the tubing.

[0041] Turning briefly to FIG. 8, illustrated is an alternative embodiment of an expandable metal centralizer 800. The expandable metal centralizer 800 is similar in many respects to the expandable metal centralizer 500. Accordingly, like reference numerals have been used to reference similar, if not identical, features. The expandable metal centralizer 800 differs from the expandable metal centralizer 500, for the most part, in that its one or more wellbore centralizing elements are a plurality of nubs 820 radially extending from and longitudinally spaced about the downhole tubular 310. In accordance with one embodiment, six or more nubs 820 radially extend from and are longitudinally spaced about the downhole tubular 310. In accordance with another embodiment, twelve or more nubs 820 radially extend from and are longitudinally spaced about the downhole tubular 310, and in yet another embodiment twenty-four or more nubs 820 radially extend from and are longitudinally spaced about the downhole tubular 310.

[0042] Turning briefly to FIG. 9, illustrated is an alternative embodiment of an expandable metal centralizer 900. The expandable metal centralizer 900 is similar in many respects to the expandable metal centralizer 800. Accordingly, like reference numerals have been used to reference similar, if not identical, features. The expandable metal centralizer 900 differs from the expandable metal centralizer 800, for the most part, in that its one or more wellbore centralizing elements are a plurality of lugs 920 radially extending from and longitudinally spaced about the downhole tubular 310. The lugs 920, in one embodiment, are steel lugs that are threaded into the downhole tubular 310, and thus may additionally be used to fix the downhole tubular 310 to the downhole conveyance 290. In other embodiments, the lugs are ceramic that are affixed with adhesive. The lugs 920 may hold the downhole tubular 310 off of the wellbore in order to minimize differential sticking. The lugs 920 may also reduce the likelihood of abrasion on the downhole tubular 310 during run-in. In accordance with one embodiment, six or more lugs 920 radially extend from and are longitudinally spaced about the downhole tubular

2019-103363 U1 PCT

310. In accordance with another embodiment, twelve or more lugs 920 radially extend from and are longitudinally spaced about the downhole tubular 310, and in yet another embodiment twenty-four or more lugs 920 radially extend from and are longitudinally spaced about the downhole tubular 310.

[0043] Turning briefly to FIG. 10, illustrated is an alternative embodiment of an expandable metal centralizer 1000. The expandable metal centralizer 1000 is similar in many respects to the expandable metal centralizers 200, 300. Accordingly, like reference numerals have been used to reference similar, if not identical, features. The expandable metal centralizer 1000 differs from the expandable metal centralizers 200, 300, for the most part, in that its one or more wellbore centralizing elements are a plurality of teeth 1020 radially extending from the downhole tubular 310. In accordance with one embodiment, six or more teeth 1020 radially extend from the downhole tubular 310. In accordance with another embodiment, twelve or more teeth 1020 radially extend from the downhole tubular 310, and in yet another embodiment twenty-four or more teeth 1020 radially extend from the downhole tubular 310. The shape of the teeth may vary greatly based upon the design of the expandable metal centralizer 1000, and thus the present disclosure should not be limited to any specific shape.

[0044] Turning briefly to FIG. 11, illustrated is an alternative embodiment of an expandable metal centralizer 1100. The expandable metal centralizer 1100 is similar in many respects to the expandable metal centralizer 1000. Accordingly, like reference numerals have been used to reference similar, if not identical, features. The expandable metal centralizer 1100 differs from the expandable metal centralizer 1000, for the most part, in that it includes a first downhole tubular 1110a having one or more first wellbore centralizing elements 1120a radially extending therefrom, as well as a second downhole tubular 1110b having one or more second wellbore centralizing elements 1120b radially extending therefrom. In fact, in the embodiment of FIG. 11, ten downhole tubulars 1110 and associated wellbore centralizing elements 1120 are stacked next to one another on the downhole conveyance. Nevertheless, any number of downhole tubulars 1110 and associated wellbore centralizing elements 1120 may be used and remain within the scope of the disclosure.

[0045] Turning briefly to FIG. 12, illustrated is an alternative embodiment of an expandable metal centralizer 1200. The expandable metal centralizer 1200 is similar in a few respects to the expandable metal centralizer 200. Accordingly, like reference numerals have been used to

2019-103363 U1 PCT

reference similar, if not identical, features. The expandable metal centralizer 1200 differs from the expandable metal centralizer 200, for the most part, in that the expandable metal centralizer 1200 includes a first downhole tubular 1210a and a second downhole tubular 1210b, and further wherein the one or more wellbore centralizing elements are one or more bow spring elements 1220a, 1220b extending between the first and second downhole tubulars 1210a, 1210b.

[0046] In accordance with one embodiment, in each of the embodiments discussed above with respect to FIGs. 2-12, the expandable metal centralizer is run-in-hole in a pre-expansion state (e.g., as a fixed geometry). Again, in accordance with this embodiment, at least one of the downhole tubular or the one or more wellbore centralizing elements comprises the metal configured to expand in response to hydrolysis. Thereafter, with the pre-expansion expandable metal centralizer positioned at a desired location, the pre-expansion expandable metal centralizer may be subjected to a wellbore fluid sufficient to expand the metal into contact with one or more surfaces (e.g., the wellbore casing in one embodiment).

[0047] Aspects disclosed herein include:

A. An expandable metal centralizer for use in a wellbore, the expandable metal centralizer including: 1) a downhole tubular positionable on a downhole conveyance in a wellbore; and 2) one or more wellbore centralizing elements radially extending from the downhole tubular, wherein at least one of the downhole tubular or the one or more wellbore centralizing elements comprises a metal configured to expand in response to hydrolysis.

B. A well system, the well system including: 1) a wellbore positioned within a subterranean formation; 2) a downhole conveyance located within the wellbore; and 3) an expandable metal centralizer coupled to the downhole conveyance, the expandable metal centralizer including: 1) a downhole tubular positioned on the downhole conveyance; and b) one or more wellbore centralizing elements radially extending from the downhole tubular, wherein at least one of the downhole tubular or the one or more wellbore centralizing elements comprises a metal configured to expand in response to hydrolysis.

C. A method for centralizing a downhole conveyance, the method including: 1) positioning a downhole conveyance at a desired location within wellbore casing located within a wellbore of a subterranean formation, the downhole conveyance having an pre-expansion expandable metal centralizer coupled thereto, the pre-expansion expandable metal centralizer including: a) a downhole tubular positioned on the downhole conveyance; and b) one or more

2019-103363 U1 PCT

wellbore centralizing elements radially extending from the downhole tubular, wherein at least one of the downhole tubular or the one or more wellbore centralizing elements comprises a metal configured to expand in response to hydrolysis; and 2) subjecting the pre-expansion expandable metal centralizer to a wellbore fluid to expand the metal into contact with the wellbore casing.

[0048] Aspects A, B, and C may have one or more of the following additional elements in combination: Element 1: wherein the downhole tubular comprises a metal configured to expand in response to hydrolysis and the one or more wellbore centralizing elements do not comprise a metal configured to expand in response to hydrolysis. Element 2: wherein the one or more wellbore centralizing elements comprise a metal configured to expand in response to hydrolysis and the downhole tubular does not comprise a metal configured to expand in response to hydrolysis. Element 3: wherein the downhole tubular comprises a first metal configured to expand in response to hydrolysis and the one or more wellbore centralizing elements comprise a second metal configured to expand in response to hydrolysis. Element 4: wherein the first metal and the second metal are different metals configured to expand at different rates in response to hydrolysis. Element 5: wherein the first metal and the second metal are the same metal configured to expand at a same rate in response to hydrolysis. Element 6: wherein the one or more wellbore centralizing elements are integrally formed with the downhole tubular. Element 7: wherein the one or more wellbore centralizing elements are three or more wellbore centralizing elements. Element 8: wherein the three or more wellbore centralizing elements are substantially equally radially spaced about the downhole tubular. Element 9: wherein the three or more wellbore centralizing elements extend along a length (L) of the downhole tubular. Element 10: wherein central axes of the three or more wellbore centralizing elements are substantially parallel to a central axis of the downhole tubular. Element 11: wherein the three or more wellbore centralizing elements spiral around the downhole tubular. Element 12: wherein the downhole tubular includes two segments that connect with respect to each other to form a tubular. Element 13: wherein the downhole tubular further includes one or more openings extending entirely through a wall thickness thereof for accepting a fastener for fixing the downhole tubular to the downhole conveyance. Element 14: wherein the one or more openings are one or more threaded openings having one or more set screws therein for fixing the downhole tubular to the downhole conveyance. Element 15: further including a pair of retaining rings positioned adjacent a proximal end and a distal end of the downhole tubular for axially fixing the

2019-103363 U1 PCT

downhole tubular on the downhole conveyance. Element 16: wherein each of the pair of retaining rings includes one or more threaded openings having one or more set screws therein for axially fixing the downhole tubular to the downhole conveyance. Element 17: wherein the pair of retaining rings allows the downhole tubular to spin about the downhole conveyance. Element 18: wherein the pair of retaining rings does not comprise the metal configured to expand in response to hydrolysis. Element 19: wherein the one or more wellbore centralizing elements radially extending from the downhole tubular is a single wellbore centralizing element that extends from and spirals at least 270 degrees around the downhole tubular. Element 20: wherein the one or more wellbore centralizing elements radially extending from the downhole tubular are six or more nubs radially extending from and longitudinally spaced about the downhole tubular. Element 21: wherein the one or more wellbore centralizing elements radially extending from the downhole tubular are six or more teeth extending from the downhole tubular. Element 22: wherein the downhole tubular is a first downhole tubular, the one or more wellbore centralizing elements are one or more first wellbore centralizing elements, and the metal is a first metal, and further including: a second downhole tubular positionable on the downhole conveyance in the wellbore; and one or more second wellbore centralizing elements radially extending from the downhole tubular, wherein at least one of the second downhole tubular or the one or more second wellbore centralizing elements comprises a second metal configured to expand in response to hydrolysis. Element 23: wherein the downhole tubular is a first downhole tubular, and further including a second downhole tubular, and further wherein the one or more wellbore centralizing elements are one or more bow spring elements extending between the first and second downhole tubulars. Element 24: wherein a combined volume of the metal is sufficient to expand to anchor one or more downhole tools within the wellbore in response to the hydrolysis. Element 25: wherein the combined volume of the metal is sufficient to expand to anchor at least about 100,000 Newtons of weight within the wellbore. Element 26: wherein a combined volume of the metal is sufficient to expand to seal an annulus between the downhole conveyance and wellbore casing. Element 27: wherein the combined volume of the metal is sufficient to expand to seal at least about 1,000 psi of pressure within the annulus. Element 28: wherein the one or more wellbore centralizing elements extend radially outward from the wellbore tubular. Element 29: wherein, wherein the one or more wellbore centralizing elements extend radially inward from the wellbore tubular. Element 30: wherein the downhole tubular

2019-103363 U1 PCT

further includes one or more threaded openings having one or more set screws therein for fixing the downhole tubular to the downhole conveyance. Element 31: further including a pair of retaining rings positioned adjacent a proximal end and a distal end of the downhole tubular, wherein each of the pair of retaining rings includes one or more threaded openings having one or more set screws therein for axially fixing the downhole tubular to the downhole conveyance. Element 32: wherein the pair of retaining rings allows the downhole tubular to spin about the downhole conveyance. Element 33: further including wellbore casing located within the wellbore, and further wherein the downhole conveyance is located within the wellbore casing forming an annulus there between, the metal expanded to engage the wellbore casing. Element 34: further including a downhole tool coupled to the downhole conveyance downhole of the expandable metal centralizer. Element 35: wherein the metal is configured to expand in response to one of magnesium hydrolysis, aluminum hydrolysis, calcium hydrolysis, and calcium oxide hydrolysis. Element 36: wherein the hydrolysis forms a structure comprising one of a Brucite, Gibbsite, bayerite, and norstrandite. Element 37: wherein the metal is a magnesium alloy or a magnesium alloy alloyed with at least one of Al, Zn, Mn, Zr, Y, Nd, Gd, Ag, Ca, Sn, and Re.

[0049] Those skilled in the art to which this application relates will appreciate that other and further additions, deletions, substitutions and modifications may be made to the described embodiments.