

RADIATING ELEMENT FOR FOCUSSED ENERGY

TECHNICAL FIELD

The present invention relates to a radiation emitter for directional energy with a device for coupling in radiation from at least one radiation generator and one radiation combination device, which combines the radiation to bundled radiation, according to the preamble of claim 1.

PRIOR ART

Based on EP 2182596 A1 from the applicant, a radiation emitter is known for directional energy, which can also be called a tactical radiation emitter or an energy weapon and, for example, can be embodied as a laser weapon.

This known radiation emitter comprises a device for coupling in radiation from at least one radiation generator and one radiation combination device, in order to combine the radiation to a high-energy combined beam. The radiation generator may represent an industrially available laser, with the use of generic laser weapons being seen in the defense against missiles, where here, via a bundled laser beam, thermal impact is applied upon the exterior skin of a missile at long distances of up to several hundred kilometers, allowing the destruction of the missile. An example is here the airborne laser weapon system Boeing YAL-1 of the U.S. Air force.

Another application of such a high energy radiation weapon is seen in the battlefield at a distance from a few hundred meters to several kilometers. Here, by using the high-energy beam, thermal effects can be applied upon weapons or ammunition rendering them ineffective.

In any case it is required, however, to provide a radiation emitter for directional energy which is capable of emitting very high radiation and directing it precisely to the target such that the radiation upon impact on the target object is still sufficiently high to cause the desired thermal effect.

For a successful defense against grenade launchers and similar targets using a high-energy laser weapon, they must be able to generate a focal point on the target with its intensity exceeding 10 kW/cm^2 at a distance from approximately one to approximately three kilometers. In order to fulfill these requirements, the laser weapon needs a laser source with a capacity exceeding 100 kW.

The development of high-energy radiation emitters, for example high energy lasers suitable for such applications, is time-consuming and costly and bears considerable risks for realization.

Lasers are already available for industrial applications, for example laser welding, showing a power of several kilowatts and an almost diffraction limited beam quality (diffraction parameter $M^2 < 1.1$). This power, which probably can be slightly increased, is far from sufficient to fulfill the requirements of a tactical radiation emitter as explained in the outset, which can apply an effective energy upon an object from over several hundred meters or even several kilometers away.

DESCRIPTION OF THE INVENTION

The objective of the present invention is to provide a radiation emitter for directional energy, which for manageable costs, allows effective energy to be applied upon a mobile object from a distance of several hundred meters to several kilometers.

In order to attain this objective, the invention shows the features stated in claim 1. Advantageous embodiments thereof are described in the other claims.

The invention further provides a radiation emitter for directional energy with a device for coupling in radiation from at least one radiation generator and one radiation combination device, which combines the radiation to bundled radiation, with the radiation combination device comprising a telescopic optic with a collimation reflector and a secondary mirror and the device being embodied for receiving directional radiation from a plurality of light conductors from at least one radiation generator.

The device for receiving directional radiation allows the coupling of high-energy radiation from one or a plurality of preferably commercially available radiation emitters, for example industrially available lasers, which are intended for processing parts and are available at low costs in large numbers. The beams radiation emitted by these radiation emitters is transferred via light conducting devices to a receiving optic of the radiation emitter according to the invention and coupled there. The collimation reflector serves, among other things, for directing the radiation bundled in this fashion to a target object; additional functions of the collimation reflector are explained in the following and the secondary mirror serves, among other things, for the focusing of the combined beam onto a target object.

The radiation emitter is preferably provided for a spatially largely coaxial coupling in of radiation from at least one high-energy laser light source. For this purpose, optic coupling devices may be provided at the telescopic optic, via which the radiation emitted by one, preferably at least two generators in the form of high-energy directional beams can be coupled in from the end sections of fiber optic conductors. Here, for example, industrial solid state lasers with a wavelength of 1.07 μm can be used as the generators of the high-energy laser beams. This arrangement allows a cost-effective application of commercially available radiation generators and energy to be coupled in the radiation emitter according to the specific energy required respectively for each application by coupling in energy from a plurality of radiation generators.

The radiation emitter according to the invention is preferably embodied to bundle radiation into a parallel beam via a parabolic mirror and for conducting radiation in individual beam axes via a beam splitter to different sub-apertures of the telescopic optic.

In order to combine radiation from several laser beams or radiation energy, the laser radiation emitted from the ends of the above-mentioned fiber optic conductors is bundled via the parabolic reflector into a parallel beam with a small diameter, typically a diameter from one to two centimeters, and directed in the individual beam axes via the beam splitter and particularly additional optic components to different sub-apertures of the telescopic optic.

The beam splitter preferably represents a deflector which is articulate in two axes, which deflects light in the beam path to Piezo tilting deflectors, preferably rapid-controlled ones tilting about two axes. For this purpose, the radiation emitter preferably comprises, in addition to the beam splitter, at least one deflector which is articulate in two axes and a beveled mirror, with the deflector being embodied to deflect radiation in the direction towards the beveled mirror and the beveled mirror being embodied to deflect radiation in the direction towards the secondary mirror.

According to the invention, it is provided that the secondary mirror is embodied in a displaceable fashion in reference to the collimation deflector along a longitudinal axis of the telescopic optic. The different sub-apertures of the telescopic optic ensure that the radiation is focused coaxially on the target object. The common focusing occurs ultimately by an axial displacement of the secondary mirror in reference to the collimation deflector along a longitudinal axis of the telescopic optic.

In order to align the radiation emitter with its telescopic optic on the target object, it is preferably provided for the radiation emitter to comprise at least a camera and a control device for analyzing image data recorded by the camera and a device for aligning the radiation emitter using a control device and the analyzed image data.

The alignment of the radiation emitter occurs, therefore, based on a camera following the target object and an allocated track electronic. In this way, preferably a first or coarsely adjusted alignment to the target object is yielded detecting the target object.

The invention further provides a laser device illuminating the target object for a fine adjustment of the radiation and/or the radiation emitter to the target object, which emits light with a wavelength different from the wavelength of the radiation of at least one radiation emitter, and that the collimation reflector and a beveled mirror are embodied for deflecting laser light reflected by the target object in the direction of the radiation paths of the radiation generator.

Using the illuminating laser, the target object can be irradiated over a relatively large area, the light emitted by the illuminating laser shows a wavelength which is different from the wavelength of the radiation emitted by the radiation generator. The light of the illuminating laser reflected by the target object is bundled via the collimation reflector and distributed via the beveled mirror and the reflector, which can tilt about two axes, into the radiation paths of the individual radiation emitters of the radiation generation device.

For a precise alignment of the radiation and/or the radiation emitter to the target object, the radiation emitter preferably comprises at least one position-sensitive detector and/or a camera for recording laser light reflected by the target object and a control device for detecting relative angular misalignments in the radiation paths based on data of the detector and/or the camera and their correction via the reflector and/or the secondary mirror.

The light of the illumination laser reflected into the radiation paths of the radiation emitter is displayed by the above-mentioned beam splitter on the position-sensitive detector and/or a camera. Here, the collimation reflector serves as a receiving optic and ensures, due to its large aperture, for high optic resolution and light intensity. This is advantageous, for example, when a camera is used for detecting positions and precise alignment, which may be provided according to the invention.

The detector and/or the camera provide data signals, based on which, via a precise tracking electronic, relative angular misalignments are determined in the individual radiation paths of the high-energy beams, and are corrected by the above-mentioned control device addressing the reflector that can tilt and the secondary mirror, also embodied as a tilting mirror. This control also allows a correction of the angular misalignments generated by atmospheric turbulence effects on the path traveled by the energy radiation to the target object.

According to the invention, at least one laser light source is provided, which emits a laser light beam coupled into the radiation path of the radiation generator, with its progression being detected by the detector and/or the camera for adjusting radiation paths of the radiation generator. For this purpose, it is provided according to the invention that the light emitted by the laser light source is different with regards to its wavelength from the wavelength of the radiation of the radiation generator and otherwise follows the radiation path of the radiation of the radiation generator. This way, the laser light used for adjusting and harmonizing individual radiation paths passes the optic path of the effective radiation.

Finally, according to the invention it is further provided that the radiation emitter comprises means for emitting a light beam, directed via a wavelength-sensitive beam splitter to a position-sensitive detector and/or a camera, which can be detected for analyzing an angular misalignment. This light beam can be displayed, similar to the reflected radiation of the illumination laser, via the wavelength-sensitive beam splitter on the position-sensitive detector and/or the camera, and angular misalignments can be calculated therefrom and corrected via tilting reflectors.

BRIEF DESCRIPTION OF THE DRAWING

It shows:

Fig. 1 a schematic illustration of an embodiment of a radiation emitter according to the present invention with a corresponding first radiation progression;

Fig. 2 a top view in the direction of the arrow II in Fig. 1 of the embodiment according to Fig. 1;

Fig. 3 a schematic illustration of an embodiment of a radiation emitter according to the present invention with a corresponding second radiation progression; and

Fig. 4 a schematic illustration of an embodiment of a radiation emitter according to the present invention with a corresponding third radiation progression.

ILLUSTRATION OF PREFERRED EXEMPLARY EMBODIMENTS

Fig. 1 of the drawing shows a radiation emitter 1 according to an embodiment of the present invention. The radiation emitter 1 represents a tactical radiation emitter provided for use in the battlefield, for example to fight grenade launchers.

The radiation emitter 1 comprises a radiation combination device 1' with a telescopic optic comprising a primary reflector or a collimation reflector 2, preferably embodied as a parabolic reflector, and a secondary mirror 3. In the embodiment shown the parabolic reflector shows a diameter from fifty centimeters to one hundred centimeters and a focal distance from one hundred to two hundred centimeters.

The secondary mirror 3 is embodied as a parabolic reflector showing a diameter from five to ten centimeters and a focal distance from ten to twenty centimeters and forms, together with the collimation reflector 2, the telescopic optic of the radiation emitter 1 according to the invention.

In general, the radiation emitter 1 comprises a jacket tube 32, in which telescopically arranged optic components are located of the radiation emitter 1 according to the invention. Overall the radiation emitter 1 shows a structure which can be aligned in two axes with high control speeds of approximately one 1 rad/s.

The secondary mirror 3 is provided at the area of the end of the jacket tube 32 opposite the collimation reflector 2, displaceable along the longitudinal axis 33 of the jacket tube 32 forming the optic axis X.

In the exemplary embodiment shown, six radiation generators 34 are provided, with Figs. 1 and 2 showing only two of them, and which represent industrial solid state lasers with a wavelength of 1.07 μm . One trained in the art clearly knows that more or less than six radiation generators 34 may be provided, as already explained above with reference to the energy requirements for the specific application. The radiation generators 34 each emit high-energy laser light, which is coupled in via only schematically shown light conducting devices 35 and an appropriate number of coupling devices 13 into the radiation emitter 1. The coupling devices 13 are provided in a housing 14 surrounding the jacket tube 32.

The light conducting devices 35 may represent, for example, light conducting fibers or another arbitrary device for coupling in and/or introducing radiation into the radiation emitter 1.

In the embodiment shown, the light conducting fibers 35 coaxially couple laser light via fiber plugs 8, shown only schematically, into the radiation emitter 1. In order to combine radiation of the respective laser beams, the laser radiation R emitted from the corresponding fiber plug 8 and/or the ends of the fibers is bundled via a parabolic reflector 7 each to a parallel beam with a small diameter from one to two centimeters and is emitted in the individual radiation axes as a radiation bundle 36 to a respective beam splitter 6.

From here, the radiation is deflected by a Piezo reflector 5, which can be tilted about two axes. From the tilting reflectors 5 the radiation is directed to a central beveled mirror 4, which is provided at the longitudinal axis 33 of the jacket tube 32, forming the optic axis X of the radiation emitter, adjacent to the collimation reflector 2. This beveled mirror 4 serves to direct the radiation to different sub-apertures A' (Fig. 2) of an emitting optic with a reference plate 10 provided with an appropriate emission aperture A, which is provided at the facial end of the jacket tube 32 facing away from the collimation reflector 2 such that the radiation S emitted is focused coaxially as effective laser beams on a target object not shown in greater detail. The number of sub-apertures A' and consequently the emission apertures A are equivalent to the number of radiation generators 34. The common focusing of the radiation occurs here via the *above-mentioned axial displacement of the secondary mirror 3.*

Fig. 2 of the drawing shows in a schematic illustration a top view from the front of the radiation emitter 1 according to Fig. 1. The secondary mirror 3 is embodied as a tilting reflector and shows the form of a parabolic reflector.

In order to direct the radiation emitter 1 on the target object, a camera 12 is provided, which analyzes image data by a control device, not shown in greater detail, in the form of a tracking electronic and serves for addressing and aligning the radiation emitter 1 to the target object via actuators, also not shown in greater detail.

The image data recorded by the camera 12 serve here for the general alignment of the radiation emitter 1 to the target object Z, while a detailed directing of the effective laser radiation shown in Fig. 1 occurs with the help of an illuminating laser 11.

The illuminating laser 11 lights the target object Z, as shown in Fig. 3, over a large area with laser light 37, namely with a wavelength which is different from the wavelength of the effective laser. In the embodiment shown, an illuminating laser is used with a wavelength of 532 nm.

The laser light 38 reflected by the target object is collected by the collimation reflector 2 and distributed via the secondary mirror 3, the beveled reflector 4, and the Piezo tilting mirror 5 in the radiation paths of the individual coupling devices 13. In the respective radiation path, the above-mentioned beam splitters 6 are arranged, which allow the laser light 38 reflected by the target Z to pass and display it on the positioning sensors 9 used for a detailed alignment.

The source signals of these positioning sensors 9 used for detailed tracking are fed to a control device, not shown in greater detail, which detects with high precision the relative angular misalignments of the individual laser beam paths and corrects the alignment of the laser beam of the respective effective laser beam in a closed control circuit via the Piezo tilting reflectors 5 and the secondary mirror 3 embodied as a tilting reflector.

This also makes it possible to correct the angular misalignment generated by atmospheric turbulences on the travel path of the effective laser beam towards the target.

The use of the collimation reflector 2 as a receiving optic is very advantageous in that its large receiving aperture yields high optic resolution and luminosity. This is particularly beneficial when quadrant detectors or cameras are used as position sensors 9.

Via a pilot laser beam 39, coupled into the beam path of the effective laser beam, in the red spectral range of 635 nm for example, which travels the same optic path as the effective laser beam, the above-described control can also be used in case of angular misalignments for adjustment and harmonizing the individual radiation paths, as shown in Fig. 4.

Retro-reflectors 41 may be inserted into the emitting apertures A, via which the respective pilot laser radiation 39 is displayed as reflected radiation 40 on the collimation reflector 2 and therefrom via the beveled reflector 4 and the Piezo tilting reflector 5 as well as the beam splitter 6 on the position sensors 9. Based on the output signals of the position sensors 9 then the angular misalignments can be determined and corrected via the Piezo tilting reflector 5.

The radiation emitter according to the invention makes it possible, in a cost-effective fashion, to apply an effective energy on a mobile object from a distance from several hundred meters to several kilometers without it here being required to invest costly developments for specifically adapted radiation generators with the corresponding development expense.

The reference characters in the claims, the description, and the drawings only serve for a better understanding of the invention and have no limiting effect upon the scope of protection.

List of reference characters

It is marked:

- | | |
|----|--|
| 1 | Radiation emitter |
| 1' | Radiation combination device |
| 2 | Collimation reflector |
| 3 | Secondary mirror |
| 4 | Beveled reflector |
| 5 | Piezo tilting reflector |
| 6 | Beam splitter |
| 7 | Off-axis parabolic reflector |
| 8 | Fiber plug |
| 9 | Position sensor, quadrant detector, camera |
| 10 | Window, reference plate |
| 11 | Illuminating laser |
| 12 | Camera |
| 13 | Coupling device |
| 14 | Housing |
| 32 | Jacket tube |
| 33 | Longitudinal axis |
| 34 | Radiation generator |
| 35 | Light conducting device |
| 36 | Radiation bundle |
| 37 | Laser light |
| 38 | Reflected laser light |

39	Pilot laser radiation
40	Reflected pilot laser radiation
41	Retro-reflectors

Claims

1. A radiation emitter (1) for directional energy with a device for coupling in radiation from at least one radiation generator (34) and a radiation combination device (1') comprising a telescopic optic, which combines radiation into bundled radiation,
characterized in that
the telescopic optic comprises a collimation reflector (2) and a secondary mirror (3), which can be displaced in reference to the collimation reflector (2) along a longitudinal axis (33) of the telescopic optic, and the device is embodied to accept directional radiation from a plurality of light conducting devices (35) from the at least one radiation generator (34).
2. A radiation emitter according to claim 1,
characterized in that
the radiation emitter (1) is embodied for the spatially largely coaxial coupling in of radiation from at least one high-energy laser light source.
3. A radiation emitter according to claim 1 or 2,
characterized in that
the radiation emitter (1) is embodied for bundling radiation to a parallel beam via a parabolic reflector (7) and for guiding the radiation in individual beam axes via a beam splitter (6) to different sub-apertures of the telescopic optic.
4. A radiation emitter according to one of the previous claims,
characterized in that
at least one reflector (5), articulate about two axes, and a beveled reflector (4), with the reflector (5) being embodied for deflecting radiation in the direction towards the beveled reflector (4) and the beveled reflector (4) being embodied for deflecting radiation in the direction of the secondary mirror (3).
5. A radiation emitter according to one of the previous claims,
characterized in that

at least one camera (12) and a control device are provided for analyzing image data recorded by the camera (12) and in a device for aligning the radiation emitter (1) via the control device and image data.

6. A radiation emitter according to one of the previous claims,
characterized in that
a laser device (11) illuminating a target object, which emits laser beams (37) with a wavelength different from the wavelength of the radiation, with the collimation reflector (2) and a beveled reflector (4) being embodied for deflecting laser light reflected by the target object in the direction of radiation paths of the radiation generator (34).
7. A radiation emitter according to one of claims 4 to 6,
characterized in that
at least one position-sensitive detector (9) and/or a camera for recording laser light reflected by the target object and a control device for determining relative angular misalignments in the radiation paths based on data of the detector (9) and/or the camera and their correction via the reflector (5) and/or the secondary mirror (3).
8. A radiation emitter according to claim 7,
characterized in that
at least one laser light source (11), emitting a laser light beam (38) coupled in the radiation path of the radiation generator (34) with its progression being detected by the detector (9) and/or the camera for adjusting radiation paths.
9. A radiation emitter according to claim 7 or 8,
characterized in that
means for emitting a light beam (39), directed via a wavelength-sensitive beam splitter (6) to a position-sensitive detector (9) and/or a camera, wherein the light beam (39) can be detected to determine angular misalignments.

Abstract

A radiation emitter (1) is provided for directional energy with a device for coupling in radiation from at least one radiation generator (34) and a radiation combination device (1'), which combines the radiation to bundled radiation, with the radiation combination device (1) comprising a telescopic optic with a collimation reflector (2) and a secondary reflector (3) and the device being embodied for accepting directional radiation from a plurality of light conducting devices (35) from at least one radiation generator (34).

(Fig. 1)