

PATENT SPECIFICATION

(11) 1 537 309

1 537 309

- (21) Application No. 28844/76 (22) Filed 12 Jul 1976
(23) Complete Specification Filed 29 Jun 1977
(44) Complete Specification Published 29 Dec 1978
(51) INT. CL.² G04B 19/02
(52) Index at Acceptance
G3T 101 PC
(72) Inventor: PIERRE-LUC GAGNEBIN

(19)



(54) A WRISTWATCH MOVEMENT

(71) We, SOCIÉTÉ SUISSE pour l'INDUSTRIE HORLOGÈRE MANAGEMENT SERVICES S.A., of 2500 BIENNE SWITZERLAND, a Company organized under the laws of Switzerland, do hereby declare the invention for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement: -

The present invention relates to a wristwatch movement particularly for wrist machines in which an electrically driven display has its basic control signals derived from a high precision frequency standard such as a quartz controlled oscillator and a frequency divider.

Timepieces of this general category have in recent years become well known and as in any new development provide many occasions to bring in improvements based on advanced technology. Thus, for example, the tendency in recent times has been to incorporate more and more details enabling complex systems of electronic controls whereby corrections which in respect of purely mechanical watches were effected by complex systems of gears and levers may now be effected in a relatively simple manner through the use of electronic circuits.

Notwithstanding the numerous features now to be found in present day electronic watches there still remains much to be done. Thus, such watches continue to exhibit a certain bulkiness and in general lack, to some extent at least, the elegance which may be associated with the finer types of purely mechanical watches. Although many improvements continue to be made, nevertheless to some extent at least, it is obvious that some basic rethinking is necessary if one is to take full advantage of the electronic possibilities and at the same time conserve the most important features of a watch while at the same time reducing

the bulk to a point where such may be incorporated in fine jewellery.

The present invention through an improved type of motionwork contributes towards reduction of volume of a watch and as will subsequently be seen provides a step of considerable importance in achieving a really small electronic wrist watch movement which at the same time will conserve certain of the features which have been found practically indispensable for modern timepieces. To this end the movement in question is provided with a motion-work taking advantage of the space saving quality of planetary gearing. The various electronic particulars of such a watch which in fact enable one to provide maximum control functions and correction functions in minimum volume through use of electronics do not form part of the present invention and will be referred to only in passing. It will be noted that among other particulars which have become superfluous by virtue of the present invention there is no need to provide a base or pillar-plate for the support of the numerous mechanical correcting arrangements often associated with the prior art type of watch movements.

The invention accordingly comprises a wristwatch movement including an electric motor arranged to transmit motion to a minute hand and an hour hand wherein the motion-work comprises:

a planetary train having a centre wheel directly driven from the motor and bearing a pair of eccentrically located coaxial planet pinions which are fixed for rotation together and arranged respectively to engage a fixed central gear and the hour wheel.

An embodiment of the invention will now be described by way of example with reference to the accompanying drawing which shows in basic outline form the mechanical motion-work arrangement as taught by this invention.

In the figure is to be found an electric motor M which preferably is in the form of an electric stepping motor such as taught for example in US Patent No. 3,845,335. Such motor will be energized from a miniature dry cell (not shown) and the timing of its energy pulses will be accomplished by means of an electronic circuit (also not shown) which may be controlled by a quartz crystal in a manner which is by now well known in the art.

In the preferred embodiment of the invention the electronic circuit is arranged so as to deliver one pulse each minute to motor M. The pulse timing, of course, will be extremely precise in nature as determined in fact by the nature of the quartz controlled oscillator which regulates the entire movement.

The motor which is described in the above mentioned US patent is designed so that at each pulse it rotates through 1/12th of a revolution. Such motion appears at motor pinion A which is arranged to mesh with a centre wheel B. In a typical execution of the invention pinion A will have 14 leaves and wheel B will have 70 teeth, thus providing a ratio of 1 to 5. Thus it will be appreciated that when pinion A rotates through 1/12th of a revolution wheel B will rotate through 1/60th of a revolution. In a well-known manner wheel B will be arranged to carry a minute hand which will thus be advanced successively through steps of 1 minute following the receipt of each motor driving pulse applied to motor M.

An important feature of the mechanism resides in the support arrangements made for the centre wheel and other mechanisms hereinafter to be described. Fitted to the motor cage of motor M is a supporting bracket H and solidly mounted therein is a support arbor G. As shown in the drawing arbor G extends upwardly to provide thereabove a reduced cross-section portion K on which is rotatably mounted the centre wheel B previously mentioned. Thus arbor G and bearing section K are held fixed by bracket H whereas wheel B is free to rotate thereon.

An enlarged section C of arbor G bears teeth thereon and in fact constitutes a fixed central gear of a planetary system. In the arrangement under consideration gear C will have 22 teeth.

Carried by wheel B is a pair of planet pinions D and E commonly mounted on a shaft L born within a bearing tube passing through the wheel B. Planet pinions D and E are fastened to shaft L and rotate together. Planet pinion D may have 24 teeth and is arranged to mesh with fixed gear C. Planet pinion E likewise has 24 teeth thereon and is arranged to mesh directly with hour wheel F. Hour wheel F likewise is provided with 24 teeth and is mounted in

the well-known manner as a hollow cannon wheel over the pipe portion of wheel B. In a well-known manner hour wheel F will carry an hour hand likewise now shown.

From the well known manner in which planetary trains operate it will be evident that as wheel B rotates planet pinion D is likewise forced to rotate by its engagement with fixed central gear C. Accordingly, planetary pinion E likewise rotates and so rotating, forces hour wheel F to rotate. The formula for the ratio of the train as shown is in accordance with the number of teeth on each of the respective gears and pinions

$$1 - \frac{22}{24} \cdot \frac{24}{24}$$

whereby the reduction appears as 1 to 12. Since, as already explained, wheel B advances at 1/60th of a revolution each minute it follows that it will effect one complete revolution each hour whereby hour wheel F will make 1/12th of a revolution each hour in accordance with the well-known arrangements of mechanical watches.

For such a type of watch movement it will be obvious that it is quite within the possibilities of electronics to provide a simple push-button control which will permit rapid corrections of minutes and rapid corrections of hours for example when traversing time zones.

It will be appreciated that in such a watch extreme simplicity has been achieved, all the motionwork in a conventional type of movement has been eliminated and the base plate has been eliminated and finally a great degree of compactness may be achieved whereby the movement is suitable for a ladies' watch smaller than heretofore achieved in electronic quartz types.

WHAT WE CLAIM IS: -

1. A wristwatch movement including an electric motor arranged to transmit motion to a minute hand and an hour hand wherein the motion work comprises a planetary train having a centre wheel directly driven from the motor, said centre wheel bearing a pair of eccentrically located coaxial planet pinions which are fixed for rotation together and one of which engages a fixed central gear and the other of which engages the hour wheel.

2. A wristwatch movement as set forth in claim 1 wherein the entire motion work is supported by the motor thereby to eliminate the conventional base plate.

3. A wristwatch movement as set forth



In the figure is to be found an electric motor M which preferably is in the form of an electric stepping motor such as taught for example in US Patent No. 3,845,335. Such motor will be energized from a miniature dry cell (not shown) and the timing of its energy pulses will be accomplished by means of an electronic circuit (also not shown) which may be controlled by a quartz crystal in a manner which is by now well known in the art.

In the preferred embodiment of the invention the electronic circuit is arranged so as to deliver one pulse each minute to motor M. The pulse timing, of course, will be extremely precise in nature as determined in fact by the nature of the quartz controlled oscillator which regulates the entire movement.

The motor which is described in the above mentioned US patent is designed so that at each pulse it rotates through 1/12th of a revolution. Such motion appears at motor pinion A which is arranged to mesh with a centre wheel B. In a typical execution of the invention pinion A will have 14 leaves and wheel B will have 70 teeth, thus providing a ratio of 1 to 5. Thus it will be appreciated that when pinion A rotates through 1/12th of a revolution wheel B will rotate through 1/60th of a revolution. In a well-known manner wheel B will be arranged to carry a minute hand which will thus be advanced successively through steps of 1 minute following the receipt of each motor driving pulse applied to motor M.

An important feature of the mechanism resides in the support arrangements made for the centre wheel and other mechanisms hereinafter to be described. Fitted to the motor cage of motor M is a supporting bracket H and solidly mounted therein is a support arbor G. As shown in the drawing arbor G extends upwardly to provide thereabove a reduced cross-section portion K on which is rotatably mounted the centre wheel B previously mentioned. Thus arbor G and bearing section K are held fixed by bracket H whereas wheel B is free to rotate thereon.

An enlarged section C of arbor G bears teeth thereon and in fact constitutes a fixed central gear of a planetary system. In the arrangement under consideration gear C will have 22 teeth.

Carried by wheel B is a pair of planet pinions D and E commonly mounted on a shaft L born within a bearing tube passing through the wheel B. Planet pinions D and E are fastened to shaft L and rotate together. Planet pinion D may have 24 teeth and is arranged to mesh with fixed gear C. Planet pinion E likewise has 24 teeth thereon and is arranged to mesh directly with hour wheel F. Hour wheel F likewise is provided with 24 teeth and is mounted in

the well-known manner as a hollow cannon wheel over the pipe portion of wheel B. In a well-known manner hour wheel F will carry an hour hand likewise now shown.

From the well known manner in which planetary trains operate it will be evident that as wheel B rotates planet pinion D is likewise forced to rotate by its engagement with fixed central gear C. Accordingly, planetary pinion E likewise rotates and so rotating, forces hour wheel F to rotate. The formula for the ratio of the train as shown is in accordance with the number of teeth on each of the respective gears and pinions

$$1 - \frac{22}{24} \cdot \frac{24}{24}$$

whereby the reduction appears as 1 to 12. Since, as already explained, wheel B advances at 1/60th of a revolution each minute it follows that it will effect one complete revolution each hour whereby hour wheel F will make 1/12th of a revolution each hour in accordance with the well-known arrangements of mechanical watches.

For such a type of watch movement it will be obvious that it is quite within the possibilities of electronics to provide a simple push-button control which will permit rapid corrections of minutes and rapid corrections of hours for example when traversing time zones.

It will be appreciated that in such a watch extreme simplicity has been achieved, all the motionwork in a conventional type of movement has been eliminated and the base plate has been eliminated and finally a great degree of compactness may be achieved whereby the movement is suitable for a ladies' watch smaller than heretofore achieved in electronic quartz types.

WHAT WE CLAIM IS: -

1. A wristwatch movement including an electric motor arranged to transmit motion to a minute hand and an hour hand wherein the motion work comprises a planetary train having a centre wheel directly driven from the motor, said centre wheel bearing a pair of eccentrically located coaxial planet pinions which are fixed for rotation together and one of which engages a fixed central gear and the other of which engages the hour wheel.

2. A wristwatch movement as set forth in claim 1 wherein the entire motion work is supported by the motor thereby to eliminate the conventional base plate.

3. A wristwatch movement as set forth



1,537,309

3

(11)

in claim 2 wherein the motor cage is provided with a bracket to which a support arbor is fixedly mounted.

5 4. A wristwatch movement as set forth in claim 3 wherein the support arbor has the central gear immovably fixed thereto and in addition provides a bearing for the centre wheel.

10 5. A wristwatch movement as set forth in claim 1 wherein a shaft bearing extends through said centre wheel and carries a shaft freely rotatable therein, a planet pinion being fixed on each end of the shaft whereby rotation of said centre wheel effects rotation of the planet pinions and the hour wheel.

15 6. A wristwatch movement as set forth in claim 1 wherein an electronic circuit con-

trolled by a quartz crystal time standard provides driving pulses to the motor.

7. A wristwatch movement as set forth in claim 6 wherein the motor comprises a stepping motor. 20

8. A wristwatch movement as set forth in claim 7 wherein the motor is stepped once per minute. 25

9. A wristwatch movement substantially as hereinbefore described with reference to and as illustrated in the accompanying drawing.

30 CLEVELAND AND JOHNSON
Chartered Patent Agents,
Chancery House,
Chancery Lane,
London, W. C. 2