

WASHING MACHINE HOSE

BACKGROUND OF THE INVENTION

The present invention relates to a drainage hose which is adapted to be attached to an electric washing machine.

5 As such a washing machine hose, generally, two kinds of hoses, that is, an internal hose which is attached to the inside of a washing machine, and an external hose which is connected to this internal hose and disposed along the outer housing of the washing machine are used. The inventor had
10 already proposed another hose the whole of which is a single, continuous, long hose in place of such two kinds of hoses used separately internally and externally, and in which the portion disposed outside the washing machine is made to have a wall in the form of a triangular corrugated wall corresponding to two
15 sides of a scalene triangle so that an inclined wall on the shorter side in the wall portion shaped into the triangularly corrugated wall can be moved into an approximately parallel posture to the inner surface side of an inclined wall on the other longer side, and can keep this moved shrinkage posture by
20 itself (for example, see Japanese Utility Model Unexamined Publication No. Hei. 5-1485).

With regard to the former of conventionally known hose of the type which uses two kinds of internal and external hoses, there is a problem that a process to connect the
25 internal hose and the external hose is required, and water is



apt to leak out of this connection portion. On the other hand,
with regard to the latter one which is a hose using a single
continuous long hose and which has been proposed as means to
solve such a problem, it is necessary to have such a structure
5 that an inclined wall on the shorter side in a wall portion
shaped into a scalene-triangular wall moves toward the inner
surface side of an inclined wall on the longer side and this
moved shrinkage posture is kept by itself. For this, it is
necessary to use a resin material which is hard to some extent,
10 and therefore the portion formed into an annularly corrugated
shape lacks flexibility if the whole of the hose is formed from
a hard resin material. This hose has therefore such problems
that overwork and damage occur easily in a bending portion
between a vertical posture for making connection to a drainage
15 pipe in a washing machine and a horizontal posture for making
extension to the outside of the washing machine, and that
vibrations of a washing tub cannot be sufficiently absorbed to
thereby give a bad influence on the washing machine body, and
so on.

20 Therefore, the inventor aimed at solving not only the
problems belonging to the former conventional washing machine
hose using two kinds of hoses, but also the problems belonging
to the latter long hose while utilizing the advantage of the
latter long hose, and considered and studied repeatedly a
25 manner how to form a continuously integrated hose by using a
hard resin material for the scalene-triangularly corrugated



portion and a soft resin material for an annularly corrugated portion. The inventor however found that it was extremely difficult to form a perfect connection portion between these materials different in hardness from each other, without causing any roughness in the materials, without any unnatural appearance in the connection portion, and without reducing strength, and particularly to carry out mass-production of such hoses continuously.

SUMMARY OF THE INVENTION

The present invention has been made to overcome all the difficulties of the conventional hoses, and an object of the invention is to provide a washing machine hose in which a scalene-triangular wall portion has a required hardness so that an shorter-side inclined wall can surely move toward the inner surface side of a longer-side inclined wall and the posture can be kept by itself easily; a corrugated wall portion has a required flexibility to be bent easily, so that the portion to be bent within the washing machine can be used for a long term without suffering from any overwork; no roughness arises in the material in a connection portion between the scalene-triangularly corrugated wall portion and the corrugated wall portion, and the connection portion can be formed perfectly without causing any unnatural appearance and without reducing strength; and particularly a structure suitable for continuous production can be obtained.

This Sheet Has Been Replaced



In order to attain the foregoing object, a washing machine hose according to the present invention comprises: a connection cylindrical portion 1 provided on one end of the hose and adapted to be connected to a drainage pipe in a washing machine; an intermediate cylindrical portion disposed in a required intermediate portion of the hose; a drainage cylindrical portion formed on the other end of the hose; an annularly corrugated wall formed entirely or almost over a portion between the connection cylindrical portion and the intermediate cylindrical portion; and a scalene-triangularly corrugated wall formed entirely or almost over a portion between the intermediate cylindrical portion and the drainage cylindrical portion. The whole of the hose is formed of a soft synthetic resin material and a hard synthetic resin material in the form of a consecutively integrated inside-outside double-layered wall in a manner so that the soft synthetic resin material is thicker than the hard synthetic resin material in the portion between the intermediate cylindrical portion and the connection cylindrical portion, while the hard synthetic resin material is thicker than the soft synthetic resin material in the portion between the intermediate cylindrical portion and the drainage cylindrical portion, so that a shorter-side inclined wall in the scalene-triangularly corrugated wall is changeable in a shrinkage posture to move to the inner surface side of the other longer-side inclined wall and this moved shrunk posture can be kept by itself.



In carrying out the washing machine of the invention, the annularly corrugated wall may be constituted by wall portions different in kind, for example, by a large-diameter annularly corrugated wall and a small-diameter annularly corrugated wall. An internal fixing cylindrical portion to be fixed to the inside of the washing machine and a washing machine-wall fixing cylindrical portion to be fixed on a wall of the washing machine may be formed in required places of the annularly corrugated wall. In addition, the intermediate cylindrical portion may have a cylindrical portion of a predetermined length which is a boundary portion between the annularly corrugated wall and the scalene-triangularly corrugated wall so as to obtain a structure having no smooth cylindrical portion of substantially a predetermined length.

In the washing machine hose according to the present invention and having such a structure as mentioned above, the portion on the drainage cylindrical portion side is disposed outside the washing machine, and the portion of the scalene-triangularly corrugated wall is brought into an extension posture or a shrinkage posture so as to change the whole length of the hose largely to thereby make it possible to drain water to a drainage hole near the washing machine or to drain water to a drainage hole away from the washing machine. In addition, when the hose is not in use, the portion of the scalene-triangularly corrugated wall is changed to a desired length so that the hose can be put along the washing machine wall and the



drainage cylindrical portion is engaged with a hose latch in a manner similarly to that in the case of a general washing machine.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a front view of a hose in a first embodiment, the intermediate portion of which is omitted partially;

 Fig. 2 is an enlarged longitudinally sectional view taken on line A-A in Fig. 1;

10 Fig. 3 is a partially transformed longitudinally sectional view of Fig. 2;

 Fig. 4 is a partially cut-off perspective view illustrating the state where the hose is attached to a washing machine;

15 Fig. 5 is a front view of a second embodiment, corresponding to Fig. 1; and

 Fig. 6 is an enlarged longitudinally sectional view taken on line B-B in Fig. 5.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

20 Preferred embodiments of the present invention will be described below with reference to the drawings.

 Figs. 1 to 4 are views illustrating a hose H as a first embodiment of the present invention: Fig. 1 is a view illustrating the whole structure of the hose H cut off partially; Fig. 2 is an enlarged view illustrating the portion



taken on sectional line A-A in Fig. 1; Fig. 3 is a view illustrating the state where the portion of a scalene-triangularly corrugated wall 5 shown in Fig. 2 is changed to a shrinkage posture; and Fig. 4 is a view illustrating the state where the hose H has been fitted to a washing machine A.

In a washing machine hose according to the present invention, a synthetic resin material, such as polypropylene system resin, which can change its hardness easily is used. Two materials, a soft material s which is rich in flexibility and another comparatively hard material h which has appropriate rigidity and elasticity are extruded in the form of two layers to form a single continuous hose in which a portion to be attached and arranged in the inside of a washing machine A and a portion to be arranged so as to project to the outside through a hose insertion hole c formed in a washing machine wall b of the washing machine A are continuously formed into one body, as shown in Fig. 4 by way of example.

As shown in Fig. 1, specifically, the hose H has such a structure that a connection cylindrical portion 1 to be connected to a drainage pipe a in the washing machine A is formed on one end side (left side in the drawing), a cylindrical portion 2 is formed in a required intermediate portion, a drainage cylindrical portion 3 is formed on the other end side (right side in the drawing). An annularly corrugated wall 4 is formed over a portion p between the connection cylindrical portion 1 and the intermediate



cylindrical portion 2, and a corrugated wall 5 shaped into a substantially triangular wave corresponding to two sides of a scalene triangle (hereinafter referred to "scalene-triangularly corrugated wall" for the sake of convenience) is formed over a portion g between the intermediate cylindrical portion 2 and the drainage cylindrical portion 3. The above-mentioned soft and hard materials s and h are arranged on the inner and outer circumferential surface sides respectively, and fused each other so that a double-layered wall composed of the soft and hard materials is formed all over the hose. Further, the respective thicknesses of the soft and hard materials s and h are varied gradually in the intermediate cylindrical portion 2 as shown in enlargement in Fig. 2 so that, with this intermediate cylindrical portion 2 as a boundary, the hard synthetic resin material h is made thinner and the soft synthetic resin material s is made thicker in the portion p on the connection cylindrical portion 1 side (left portion in the drawing) from the intermediate cylindrical portion 2 while the soft synthetic resin material s is made thinner and the hard synthetic resin material h is made thicker in the portion q on the drainage cylindrical portion 3 (right portion in the drawing) from the intermediate cylindrical portion 2.

With such a structure, the annularly corrugated wall 4 formed on the connection cylindrical portion 1 side is made to be a corrugated wall easy to bend and rich in flexibility, and the scalene-triangularly corrugated wall 5 formed on the



drainage cylindrical portion 3 side is made a corrugated wall which is appropriate in rigidity and rich in resiliency. Accordingly, if a force in the direction of the axis of the hose H is exerted to the hose H, a shorter-side inclined wall 5a constituting the triangularly corrugated wall 5 can move easily toward the inner surface side of the other longer-side inclined wall 5b by self-resilient force as shown in Fig. 3 and this moved state, that is, the shrinkage posture can be easily kept by itself.

Further, as shown in Fig. 1, the hose H of this embodiment has such a structure that a predetermined-length portion 4a formed in the portion of the annularly corrugated wall 4 adjacently to the connection cylindrical portion 1 is made to have a diameter larger a little than that of another annularly corrugated portion 4b in order to make the portion 4a to be bent easily into an L-shape so as to be connected to the drainage pipe a of the washing machine, and because this portion 4a directly receives vibrations of the drainage pipe a. Further, a in-washing machine fixing cylindrical portion 4c for fixing the hose in the inside of the washing machine A is formed between the large-diameter corrugated portion 4a and the corrugated portion 4b, and a washing machine-wall fitting cylindrical portion 4d for fixing the hose to the hose insertion hole c formed in the washing machine wall b of the washing machine A is formed in a required intermediate portion of the corrugated portion 4b.



The hose H having such a structure may have means for attaching the hose to the washing machine A in the same manner as that in a general washing machine hose, as shown in Fig. 4. A hook 11 for engagement with a hose latch d attached to the washing machine A is attached to the drainage cylindrical portion 3 of the hose H in this embodiment in practical use, as shown by a virtual line in Fig. 1.

When the hose H attached to the washing machine A in such a manner as described above is to be used, the drainage cylindrical portion 3 is first detached from the hose latch d, and inserted into a required drainage hole B. In this case, as shown in chain lines in Fig. 4, the hose can be shrunk or extended suitably to the position of the drainage hole B even if the drainage hole B is at a position B₁ near the washing machine A or at a position B₂ away therefrom so that water can be drained through the hose H in an approximately horizontally straight posture.

The washing machine hose according to the present invention may be realized with such a structure as shown in Figs. 5 and 6 as a second embodiment. That is, the intermediate cylindrical portion 2 is made to be a boundary between the annularly corrugated wall 4 and the scalene-triangularly corrugated wall 5. The respective thicknesses of the soft and hard materials s and h are varied gradually with the intermediate cylindrical portion 2 as a boundary as shown in enlargement in Fig. 6 in a manner so that the soft synthetic



resin material s is thicker than the hard synthetic resin material h in the portion p on the connection cylindrical portion 1 side (left portion in the drawing) from the intermediate cylindrical portion 2, while the hard synthetic resin material h is thicker than the soft synthetic resin material s in the portion q on the drainage cylindrical portion 3 side (right portion in the drawing) from the intermediate cylindrical portion 2, similarly to the first embodiment.

In addition, a small-diameter corrugated portion 4b is formed all over the section between the in-washing machine fixing cylindrical portion 4c and the intermediate cylindrical portion 2 in the annularly corrugated wall 4 in this embodiment, while the washing machine-wall fitting cylindrical portion 4d shown in the first embodiment is not formed. However, the attachment to the washing machine wall may be performed by use of the corrugated portion 4d at a desired place. In addition, the in-washing machine fixing cylindrical portion 4c is not always necessary, the hose may be fixed at a desired portion of the corrugated portion 4a or 4b. The drainage cylindrical portion 3 in this embodiment has a shape where a small-diameter cylindrical portion 12 is formed between two large-diameter annular portions so that the hose can be engaged with the hose latch d U-shaped in plan and attached to the washing machine A by pushing the small-diameter cylindrical portion 12 to the hose latch d.

A material forming the hose H according to the present



invention may be, not to say, any synthetic resin material such as polyethylene, polyvinyl chloride other than polypropylene mentioned in the first embodiment. Preferably, the soft synthetic resin material s and the hard synthetic resin material h are those homogeneous with each other or those which can be fused with each other easily.

Although the embodiments regarded as representatives of the present invention were described, the present invention is not always limited to the illustrated structure of these embodiments, but may be realized in an appropriate modification within a scope of providing the above-mentioned constituents according to the present invention, and attaining the object of the present invention and having the following effects.

As is apparent from the above description, the present invention has such a structure that with a desired intermediate cylindrical portion of a hose as a boundary, one side of the boundary where the hose is attached to the inside of a washing machine is made to have an annularly corrugated wall while the other drainage pipe side is made to have a scalene-triangularly corrugated wall, and that the whole of the hose is formed of a soft synthetic resin material s and a hard synthetic resin material h so as to be in the form of a consecutively integrated inside-outside double-layered wall, and with the intermediate cylindrical portion as a boundary, the soft synthetic resin material s is made thicker than the hard synthetic resin material h in a portion p on the in-washing



machine attachment side, while the hard synthetic resin material h is made thicker than the soft synthetic resin material s in a portion q on the drainage pipe side. Accordingly, the wall portion having a scalene-triangular shape

5 has a required hardness so that a shorter-side inclined wall therein can surely move toward the inner surface side of the longer-side inclined wall and the posture can be easily kept by itself, and in addition, the wall portion having an annularly corrugated shape has a required flexibility so as to be bent

10 easily so that no heavy overwork arises in the bent portion in the washing machine and the hose can be used for a long term.

The hose as a whole is formed continuously and integrally without any joint in the length direction. Accordingly, there are conspicuous effects that there arises no

15 roughness or no unnatural appearance on the material in the boundary portion between the scalene-triangularly corrugated portion and the annularly corrugated portion, the strength is not weakened, and a perfect non-joint shape can be formed both in the inner and outer surface sides of the hose. In addition,

20 there is another effect on manufacture to be suitable for continuous production.

This Sheet Has Been Replaced





WHAT IS CLAIMED IS:

1 1. A washing machine hose comprising:
2 a connection cylindrical portion provided on one end of
3 said hose and adapted to be connected to a drainage pipe in a
4 washing machine;
5 an intermediate cylindrical portion disposed in a
6 required intermediate portion of said hose;
7 a drainage cylindrical portion formed on the other end
8 of said hose;
9 a corrugated wall formed entirely or almost over a
10 portion between said connection cylindrical portion and said
11 intermediate cylindrical portion; and
12 a scalene-triangularly corrugated wall formed entirely
13 or almost over a portion between said intermediate cylindrical
14 portion and said drainage cylindrical portion;
15 wherein the whole of said hose is formed of a soft
16 synthetic resin material and a hard synthetic resin material in
17 the form of a consecutively integrated inside-outside double-
18 layered wall; and
19 wherein said soft synthetic resin material is thicker
20 than said hard synthetic resin material in said portion between
21 said intermediate cylindrical portion and said connection
22 cylindrical portion, while said hard synthetic resin material
23 is thicker than said soft synthetic resin material in said
24 portion between said intermediate cylindrical portion and said



25 drainage cylindrical portion, so that a shorter-side inclined
26 wall in said scalene-triangularly corrugated wall is changeable
27 in a shrinkage posture to move to an inner surface side of the
28 other longer-side inclined wall and its posture is kept by
29 itself.

1 2. A washing machine hose according to Claim 1, wherein
2 said corrugated wall is constituted by a large-diameter
3 corrugated wall and a small-diameter corrugated wall.

1 3. A washing machine hose according to Claim 1, further
2 comprising an internal fixing cylindrical portion to be fixed
3 to an inside of said washing machine and a washing machine-wall
4 fixing cylindrical portion to be fixed on a wall of said
5 washing machine, which are disposed at required places of said
6 corrugated wall.

1 4. A washing machine hose according to Claim 1, wherein
2 said intermediate cylindrical portion is a boundary portion
3 between said corrugated wall and said scalene-triangularly
4 corrugated wall.

This Sheet Has Been Replaced

