



## Description

### CLEANING METHOD FOR MAGNETIC TRANSFER CARRIER

#### 5 Technical Field

The present invention relates to a cleaning method for a magnetic transfer carrier on which an information signal is recorded, and more particularly to a cleaning method for a magnetic transfer carrier for performing magnetic transfer of the information signal to a magnetic record medium used in a hard disk device or a floppy disk device.

#### Background Art

Information signals such as a tracking servo signal, an address information signal and a recovered clock signal are recorded on a magnetic transfer carrier. There has been known a magnetic transfer apparatus magnetically transferring information signals recorded on a magnetic transfer carrier onto a magnetic record medium such as a hard disk or a floppy disk. For example, a magnetic transfer carrier disclosed in Japanese Unexamined Patent Publication No. 10-40544 (1998) has magnetic portions made of ferromagnetic material in a pattern for information signals on a surface of a substrate. A magnetic record medium is a sheet or a disk with a ferromagnetic thin film or a ferromagnetic powder coat layer formed thereon. A surface of a magnetic transfer carrier is put into contact with a surface of a magnetic record medium in the shape of a disk and a prescribed magnetic field is applied. With this procedure, information signals formed on the magnetic transfer carrier are magnetically transferred onto the magnetic record medium. It is important that information signals with a high density are uniformly transferred stably across all of the surface of the magnetic record medium in order to reproduce records with high precision with a magnetic



WO 03/001526

PCT/JP02/06095

head of a magnetic record reproducing apparatus. On this occasion in magnetic transfer, if tiny foreign matter exists on the surface of the magnetic transfer carrier, when both are put into contact with each other for magnetic transfer, a depression arises on the surface of the magnetic record medium by the tiny foreign matter, some times with a resultant tiny protrusion around the depression. When data record is reproduced using the magnetic head, such a tiny protrusion on the magnetic record medium is put into contact with a magnetic head with the result that the magnetic head is thrown away, for example, at the instant of the contact, which causes record reproduction performance of the magnetic head to be reduced or a life time thereof to be shorter due to physical contact thereof with the hard disk, further tending to destruction of the hard disk itself by chance. Therefore, it is very important to clean a magnetic transfer carrier prior to magnetic transfer so as to remove the above described foreign matter by the cleaning, for which there has been conventionally proposed a cleaning method cleaning a surface of a magnetic transfer carrier with a cleaning tool.

In a case of such a cleaning method, a corner of a magnetic film on a surface of a magnetic transfer carrier is scraped away in cleaning with a cleaning tool and the scraped magnetic film is in some case attached onto the cleaning tool as broken pieces. In such a cleaning method, though the above described tiny protrusion on a surface of a magnetic transfer carrier is removed by the cleaning tool, broken pieces from the magnetic film are attached as foreign matter onto the surface of a magnetic transfer carrier by way of the cleaning tool and magnetic transfer is inconveniently performed onto a hard disk, which is a magnetic record medium, with the magnetic transfer carrier having the foreign matter attached thereon.

In a conventional cleaning method, therefore, a necessity came to occur for frequent cleaning a cleaning tool itself,

WO 03/001526

PCT/JP02/06095

thereby leading to addition of an extra cleaning step, reduction in productivity for hard disks, increase in production cost of disks, further a need for expensive apparatus for cleaning a cleaning tool itself and others with a resultant high cost as a whole.

It is accordingly an object of the present invention to provide a cleaning method capable of performing cleaning of a magnetic transfer carrier at low cost with certainty, without a need for an apparatus dedicated to cleaning of a cleaning tool itself.

#### Disclosure of the Invention

According to one aspect of this invention, there is provided a cleaning method as defined in claim 1 of the appended claims. Note that shapes of the magnetic transfer carrier and the dummy carrier each are not limited to the shape of a disk.

According to the cleaning method of the present invention, in order to clean the cleaning tool, the dummy carrier has only to be placed on the rotary stage used for cleaning of the magnetic transfer carrier. Therefore, the cleaning method makes an apparatus dedicated to cleaning of the cleaning tool itself unnecessary, thereby enabling cleaning of the magnetic transfer carrier at a low cost with certainty.

In the second step of the present invention, preferably,

WO 03/001526

PCT/JP02/06095

the cleaning tool is slid toward the outer periphery from the inner periphery on the dummy carrier while rotating the dummy carrier in substantially the same direction as on the magnetic transfer carrier when being cleaned.

5           In the present invention, preferably, a shape of the at least one recess on the dummy carrier and a shape of each recess on the magnetic transfer carrier are substantially the same as each other. In such a situation, when the cleaning tool received a cleaning action by the dummy carrier, it has been already adapted  
10 to the at least one recess of the dummy carrier; therefore, when the magnetic transfer carrier having the plural recesses thereon each with the same shape as that of the at least one recess on the dummy carrier is cleaned with the cleaning tool, the cleaning can be preferably carried out with certainty and ease.

15           In the present invention, preferably, a press contact force of the cleaning tool to the dummy carrier when the cleaning tool is slid on the dummy carrier in cleaning is made substantially the same as that of the cleaning tool to the magnetic transfer carrier when the cleaning tool is slid on the magnetic transfer  
20 carrier in cleaning.

          In such a situation, when the cleaning tool received a cleaning action by the dummy carrier, it has been already adapted to the at least one recess of the dummy carrier; therefore, when the magnetic transfer carrier having the plural recesses thereon  
25 each with the same shape as that of the at least one recess on the dummy carrier is cleaned with the cleaning tool, the cleaning can be preferably carried out with certainty and ease.

          In the present invention, preferably, a relative speed of the cleaning tool to the dummy carrier when the cleaning tool is  
30 slid on the dummy carrier in cleaning is made substantially the same or almost the same as that of the cleaning tool to the magnetic transfer carrier when the cleaning tool is slid on the magnetic transfer carrier in cleaning.

WO 03/001526

PCT/JP02/06095

In such a situation, when the cleaning tool received a cleaning action by the dummy carrier, it has been already adapted to the at least one recess of the dummy carrier; therefore, when the magnetic transfer carrier having the plural recesses thereon each with the same shape as that of the at least one recess on the dummy carrier is cleaned with the cleaning tool, the cleaning can be preferably carried out with certainty and ease.

According to a second aspect of this invention, there is provided a cleaning method as defined in claim 8.

WO 03/001526

PCT/JP02/06095

According to a third aspect of this invention, there is provided a cleaning apparatus as defined in claim 16.

5        Since in the cleaning step for the cleaning tool, the cleaning tool is cleaned by sliding

10

15

20

25

30

WO 03/001526

PCT/JP02/06095

thereof on the second disk and the first disk is cleaned in the cleaning step for the first disk, the cleaning tool, which is adapted to the second disk in cleaning thereof, can clean the first disk with ease.

5       The present invention, in cleaning, preferably has a control mechanism that moves the cleaning tool across the second disk covering every part thereof to as far as outside of the outer periphery edge thereof.

10       In this case, foreign matter attached to the cleaning tool preferably loses a second chance to attach thereto since the foreign matter is sent out to outside of the second disk.

15       The present invention, in cleaning, preferably has a control mechanism that moves the cleaning tool across the first disk covering every part thereof to as far as outside of the outer periphery edge thereof.

      In this case, foreign matter attached to the first disk preferably loses a chance to remain attached thereto since the foreign matter is sent out to outside of the first disk.

20       Preferably, the present invention uses a magnetic transfer carrier, as the first disk, on which information signals are recorded, and which is used for magnetic transfer of the information signals in a state of being in contact with a magnetic record medium, and having at least one recess opening toward an outer periphery thereof from an inner periphery thereof on a  
25       magnetic transfer surface facing the magnetic record medium, and uses a dummy carrier, as the second disk, having a recess of almost the same shape as that of the at least one recess of the magnetic transfer carrier on at least one surface thereof.

30       In this case, preferably, foreign matter attached to the cleaning tool is sent out to the outer periphery of the dummy carrier with ease and simplicity when the cleaning tool is cleaned with the dummy carrier since the dummy carrier has a radial recess extending toward the periphery thereof from the inner periphery

WO 03/001526

PCT/JP02/06095

thereof, and the cleaning tool has been already adapted to the shape of the recess on the dummy carrier, so the magnetic transfer carrier can be cleaned with ease.

5 According to a fourth aspect of this invention, there is provided a dummy carrier as defined in claim 20. Preferably, the cleaning is by sliding the cleaning tool on a surface of the dummy carrier while the dummy carrier is held by a holding section of a disk cleaning apparatus.

10 According to the present invention, the cleaning tool can be preferably used in cleaning of the dummy disk. In this case, since the dummy disk has the radial recess on the surface thereof, when the cleaning tool is cleaned on the surface, foreign matter attached to the surface can be certainly removed by the cleaning  
15 tool through the recess opening toward the outer periphery thereof to outside of the dummy carrier, thereby attaining a magnetic transfer carrier easy in control of the cleaning.

20

25

30

5 One embodiment of the invention is defined in claim 21, as a result of which, with such a configuration adopted, foreign matter attached

on the surface and in the recess of the magnetic transfer carrier can be removed with ease and certainty and avoidance can be  
10 perfectly made on destruction of a magnetic head and a magnetic record medium caused by contact between the magnetic record medium and the magnetic head due to the presence of foreign matter therebetween.

In the present invention, on a surface of the magnetic  
15 transfer carrier, an area of a central portion having no part of a recess is preferably larger than an area in which the cleaning tool is in contact with the magnetic transfer carrier. This is because, when the cleaning tool is pressed into the magnetic transfer carrier prior to the start of cleaning, there occurs no  
20 contact of the cleaning tool with depressions and protrusions formed by the recess.

In the present invention, the cleaning tool is preferably  
a rotary brush rotating about a line, as an axis, in a direction  
in substantially parallel to a normal to the magnetic transfer  
25 carrier.

In the present invention, if a radius of the rotary brush  
is  $r$  (mm), a cycle of sliding repetition in sliding of the rotary  
brush driven by the sliding section is  $t$  (s), a radius of the  
magnetic transfer carrier of an almost circular shape is  $R$  (mm),  
30 and a rotation speed of the magnetic transfer carrier when being  
rotated by the holding section is  $x$  (rps) by definition, a relation  
of  $\pi t x R < r$  is preferably established. This is because cleaning  
over all of the surface of the magnetic transfer carrier can be

performed with certainty.

5 In the present invention, if a depth of a recess on the magnetic transfer carrier is M (mm) and, a press-down quantity of the rotary brush into the magnetic transfer carrier in cleaning is N (mm) by definition, a relation of  $N/M > 10$  is preferably established. This is because with such a relation established, foreign matter can be removed with more of certainty.

10 In the present invention, the recess is preferably enlarged in width toward the outer periphery from the inner periphery. This is because foreign matter can be sent out to the outer periphery side with more of certainty.

15 In the present invention, the cleaning tool is preferably slid to as far as outside of an outer periphery edge of a magnetic film on a surface of the magnetic transfer carrier on which the magnetic film is formed. This is because foreign matter can be removed with certainty, without remaining at the outer periphery edge of the magnetic transfer carrier.

20 In the present invention, preferably, the recess is of the sectional shape of a substantially circular arc, the cleaning tool pivoted around a prescribed position as a center, and a curvature radius of the circular arc and a radius of the pivoting motion of the rotary brush are almost in coincidence with each other. This is because foreign matter attached to the recess can be sent out with more of certainty.

25

30

Another embodiment of this invention is defined in  
5 claim 29, as a result of which, with such a configuration  
adopted, foreign matter attached  
on the surface and in the recess of the magnetic transfer carrier  
can be removed with ease and certainty and avoidance can be  
perfectly made on destruction of a magnetic head and a magnetic  
10 record medium caused by contact between the magnetic record medium  
and the magnetic head due to the presence of foreign matter  
therebetween.

A magnetic transfer carrier cleaned using the cleaning  
method and the cleaning apparatus described above are free from  
15 foreign matter, which has been removed, with certainty.  
Therefore, when a magnetic record reproducing apparatus is  
operated on a magnetic record medium on which information signals  
have been magnetically transferred from such a magnetic transfer  
carrier, high quality record reproduction can be enabled in which  
20 there is produced no destruction of a magnetic head and a magnetic  
record medium by contact between the magnetic record medium and  
the magnetic head caused by foreign matter present therebetween.

#### Brief Description of the Drawings

25 Fig. 1 is a view showing a state where a magnetic transfer  
carrier and a magnetic record medium are spaced apart away from  
each other in a magnetic transfer apparatus according to an  
embodiment of the present invention;

Fig. 2 is a view showing a state where the magnetic transfer  
30 carrier and the magnetic record medium are in close contact with  
each other in the magnetic transfer apparatus according to the  
embodiment of the present invention;

Fig. 3 is a perspective view of the magnetic transfer

WO 03/001526

PCT/JP02/06095

carrier of Fig. 1;

Fig. 4 is a graph showing a relationship between a time and a pressure in an internal space A of a support stage for the magnetic record medium of Fig. 1;

5 Fig. 5 is a schematic plan view of the magnetic transfer carrier of Fig. 1;

Fig. 6 is an enlarged view of a part A' of Fig. 5;

Fig. 7 is a partially sectional view of a region shown in Fig. 6;

10 Fig. 8 is an illustration showing an initialization of a magnetic record medium in magnetic transfer;

Fig. 9 is an illustration showing magnetic transfer on a magnetic record medium;

15 Fig. 10 is a sectional view showing a way of magnetic transfer;

Fig. 11 is a perspective view of a configuration of a cleaning apparatus of the embodiment;

Fig. 12 is a top view showing cleaning of Fig. 11;

20 Fig. 13 is a partially enlarged sectional view of a magnetic transfer carrier;

Fig. 14 is a perspective view of a magnetic transfer apparatus according to other embodiments of the present invention;

25 Fig. 15 is a perspective view of the magnetic transfer apparatus according to the other embodiments of a present invention;

Fig. 16 is a graph showing a cycle of movement of a pivoting brush in the magnetic transfer apparatus according to the other embodiments of the present invention; and

30 Fig. 17 is a plan view of a magnetic record reproducing apparatus according to another embodiment of the present invention.

WO 03/001526

PCT/JP02/06095

## Best Mode for Carrying Out the Invention

Referring to the accompanying drawings, description will be given of a magnetic transfer apparatus using a magnetic transfer carrier according to an embodiment in the best mode of the present invention below.

Referring to Figs. 1 to 3, a reference numeral 1 indicates a magnetic record medium such as a magnetic disk on which information signals are to be transferred; 2 a disk-shaped magnetic transfer carrier, on which the information signals are recorded to perform magnetic transfer of the information signals onto the magnetic record medium 1; 3 plural radial contact portions for contact with the disk-shaped magnetic record medium 1 in magnetic transfer, provided on one surface of the magnetic transfer carrier 2; and 4 radial recesses.

The radial recesses 4 each are depressed into the bulk of the substrate compared with the corresponding radial contact portion 3 between adjacent radial contact portions 3 and opens toward the outer periphery of the magnetic transfer carrier 2 from the inner periphery thereof. The radial recesses 4 each serve as a cleaning recess as described later and a depth thereof is preferably set to a value of the order of 5  $\mu\text{m}$ .

A reference numeral 6 indicates a support stage for supporting the magnetic record medium 1; 7 a vent hole provided for flowing of a gas into the central section of the support stage 6; 8 a passage through which a gas between the magnetic transfer carrier 2 and the magnetic record medium 1 is discharged or a gas is forcibly fed therebetween; 9 a gas discharge port for discharging a gas from the passage 8; 10 a suction pump connected to the gas discharge port 9; an 11 an exhaust valve for controlling an exhaust of the gas. A reference numeral 12 indicates a gas feed pump for forcibly feeding a gas into the passage 8; 13 a gas feed valve controlling a feed of the gas. The gas feed pump 12 is equipped with an air filter (not shown) of 0.01  $\mu\text{m}$  in pore size

WO 03/001526

PCT/JP02/06095

such that foreign matter of 0.01  $\mu\text{m}$  or more across is not forcibly fed into the passage 8.

A reference numeral 14 indicates an arm being fixedly mounted on the magnetic transfer carrier 2 to hold. The magnetic transfer carrier 2 is fixedly mounted onto the holding arm 14 by sucking a gas through the through hole provided to the holding arm 14. The holding arm 14 is freely slidably positioned at a proper position along the vertical direction by a guide member 16 by way of a boss section at the top side thereof.

Detailed description will be given of a process associated with suction/forced feed.

First of all, with reference to Fig. 1, there will be described of a moving-apart step of moving the magnetic transfer carrier 2 and the magnetic record medium 1 apart away from each other by forced feed of air, which is an example of the gas. The exhaust valve 11 is closed while the gas feed valve 13 is opened and in this state, the gas feed pump 12 is operated. With this operation, the gas is caused to flow into the passage 8. By doing so, air is forcibly fed upwardly as shown with an arrow mark A of Fig. 1 through the vent hole 7. Thereby, the air forcibly fed into the vent hole 7 pushes up the magnetic transfer carrier 2. The air is forcibly fed to the recesses 4 as shown with an arrow mark B. The air forcibly fed into the recesses 4 not only expands and advances radially toward the outer periphery of the magnetic transfer carrier 2 from the center portion thereof through the recesses 4, but are also released into the atmospheric air through clearances including the recesses 4 between the magnetic transfer carrier 2 and the magnetic record medium 1.

Fig. 4 shows a relationship between an elapsed time in the step above and a pressure in a space H interposing between the magnetic transfer carrier 2 and the magnetic record medium 1, and after elapsing 3 seconds in the figure, the pressure in the space H increases rapidly in an instant from 101.3 kpa upward and

WO 03/001526

PCT/JP02/06095

thereafter, is kept at a pressure of the order of 130 kpa for about 1 sec, which period corresponds to a state where the magnetic transfer carrier 2 and the magnetic record medium 1 stay apart away from each other.

5       The magnetic transfer carrier 2 and the magnetic record medium 1 move apart way from each other starting a state of being in close contact with each other and when the magnetic transfer carrier 2 rises by 0.5 mm in one piece with the holding arm 14, the top surface of the holding arm 14 is put into contact with  
10       the lower surface of the guide member 16. Thereby, a moving-apart distance between the magnetic record medium 1 and the magnetic transfer carrier 2 is controlled.

Referring to Fig. 2, description will be given of a close contact process in which the magnetic record medium 1 and the  
15       magnetic transfer carrier 2 are put into close contact with each other by suction of air.

The gas feed pump 12 is ceased to be out of operation and the gas feed valve 13 is closed. Then, the holding arm 14 on which the magnetic record medium 1 is fixedly mounted is moved downward  
20       by its own weight to be settled on the magnetic record medium 1. Thereafter, the exhaust valve 11 is opened and the suction pump 10 is operated.

By doing so, since the gas in the vent hole 7 is discharged downward as shown with an arrow mark C of Fig. 2, the gas in the  
25       recesses 4, that is the gas in the space H, is also discharged through a clearance between a hole defined by the inner periphery of the magnetic record medium 1 and a boss 5.

Since the recesses 4 each are of a shape to extend through the edge of the outer periphery of the magnet transfer carrier  
30       2 as shown in Fig. 3, the magnetic transfer carrier 2 and the magnetic record medium 1 are in close contact with each other along all of the periphery. For this reason, a pressure in the space H between the magnetic transfer carrier 2 and the magnetic record

medium 1 is reduced lower than the atmospheric pressure. Accordingly, the magnetic record medium 1 is pressed to the magnetic transfer carrier 2 by the action of the atmospheric pressure 15. In Fig. 4, a division of 30 kps in pressure in the space H corresponds to the above described close contact state.

Then, a magnet 17 is moved toward in the direction of an arrow mark D as shown in Fig. 2 so as to be close to the magnetic transfer carrier 2. When a distance of the magnet 17 close to the magnetic transfer carrier 2 reaches a value of the order of 1 mm, movement of the magnet 17 in the direction of an arrow mark D is ceased. Then, the magnet 17 is revolved in the circular periphery direction of the magnetic record medium 1, that is in a direction of an arrow mark E, by one revolution or more. With the revolution, a necessary magnetic field for magnetic transfer is applied to the magnetic transfer carrier 2.

Here, detailed description will be given of the magnetic transfer carrier 2 referring to Figs. 5 to 7. Fig. 5 shows a schematic plan view of one example of the magnetic transfer carrier 2. As shown in Fig. 5, a signal region 2a is formed almost radially on one major surface of the magnetic transfer carrier 2, that is a surface of the magnetic transfer carrier 1 in contact with a ferromagnetic thin film surface of the magnetic record medium 1. Figs. 3 and 5 each are a view showing a model and actually, the signal region 2a is formed on a contact portion 3 in Fig 3.

Fig. 6 schematically shows an enlarged view of part A' enclosed by a dotted line of Fig. 5. In the signal region 2a, as shown in Fig. 6, there are formed digital information signals recorded on the magnetic record medium 1, for example, a magnetic transfer information pattern constituted of magnetic portions made of a ferromagnetic thin film, corresponding to information signals at positions in conformity to preformat recording.

In Fig. 6, portions shaded by hatching show magnetic

WO 03/001526

PCT/JP02/06095

portions made of a ferromagnetic thin film. The magnetic transfer information pattern shown in Fig. 6 is a pattern with a configuration in which information signals such as a clock signal, a tracking servo signal, an address information signal, and other digital signals are arranged sequentially in the direction of a track length. The magnetic transfer information pattern shown in Fig. 6 is one example, and a configuration, arrangement and others of a magnetic transfer information pattern are properly determined according to information signals to be magnetically transferred onto the magnetic record medium 1.

For example, in a case where as in a hard disk drive, a reference signal is recorded on a magnetic film of a hard disk, which is a magnetic record medium, and preformat recording of a tracking servo signal and other signals is further performed on the basis of the reference signal, the following procedure may be adopted in which a magnetic transfer carrier according to the present invention is used to transfer record only a reference signal used in preformat recording in advance on a magnetic film of a hard disk and then the hard disk is installed into a case of the drive, followed by preformat recording of a tracking servo signal and other signals performed with a magnetic head of the hard disk drive.

Fig. 7 shows a partial section of the magnetic transfer carrier 2. The magnetic transfer carrier 2 has a substrate 2b, as shown in Fig. 7, made of a non-magnetic material such as a Si substrate, a glass substrate, a plastic substrate or the like in the shape of a disk. On one major surface of the substrate 2b, that is on a surface thereof with which a surface of the magnetic record medium 1 is in contact, there are formed plural fine recessed portions 2c corresponding to information signals in an arrangement pattern. A ferromagnetic film 2d, which is a magnetic portion, is formed in the recessed portions 2c on the substrate 2b.

As materials of the ferromagnetic thin film 2d on the magnetic transfer carrier 2, they have only to be magnetic materials capable of transfer recording a digital information signal on a magnetic record medium and no specific limitation is imposed on its nature in terms of hardness, such as hard, semi-hard or soft. As materials of the ferromagnetic thin film 2d, there can be exemplified, for example, Fe, Co, Fe-Co alloy and others. Note that a higher saturation magnetic flux density of a magnetic material is more preferably accepted in order to generate a sufficient recording magnetic field regardless of a kind of a magnetic record medium on which information signals are written. Especially in cases of a magnetic record medium with a high coercive force in excess of 200 Oe and a flexible disk with a thick magnetic layer, there arises a chance to disable sufficient recording thereon at a saturation magnetic flux density of 0.8 T or less. For this reason, there are used a magnetic material with a saturation magnetic flux density of generally 0.8 T or more and preferably 1.0 T or more.

A thickness of the ferromagnetic thin film 2d of the magnetic transfer carrier 2 is dependent on a bit length, saturation magnetization of a magnetic record medium and a film thickness of a magnetic layer. For example, in a case where a bit length is about 1  $\mu\text{m}$ , a saturation magnetization and a thickness of a magnetic layer of the magnetic record medium are about 500 emu/cc and about 20 nm, respectively, a thickness of the ferromagnetic thin film 2d has only to be of the order of a value in the range of from 50 nm to 500 nm.

In order to acquire a good quality of such magnetically transferred signals, it is desirable to uniformly excite and magnetize the ferromagnetic thin films 2d in preformat recording on the basis of an arrangement pattern of a soft magnetic thin film or a semi-hard magnetic thin film as the ferromagnetic thin film 2d provided onto the magnetic transfer carrier 2.

WO 03/001526

PCT/JP02/06095

Furthermore, it is desirable to apply uniform direct-current erase to the magnetic record medium 1 such as a hard disk prior to signal recording using the magnetic transfer carrier.

5 Description will be given of a fabrication method for the magnetic transfer carrier 2.

A resist film is formed on a surface of a Si substrate. Then, the resist film is subjected to exposure and developing to finally be patterned using a lithographic technology with a laser beam or an electron beam such as in a photolithographic method.

10 Thereafter, the resist film is etched by dry etching or the like technique to form a fine recess and protrusion profile corresponding to information signals on the resist film.

Subsequent to this, a sputtering method, a vacuum evaporation method, an ion plating method, a CVD method, a plating method or

15 the like is used to obtain a magnetic transfer carrier 2 provided with magnetic portions corresponding to information signals in a state where recessed portions are filled with a ferromagnetic thin film made of Co or the like.

No specific limitation is imposed to the above method as

20 a method for forming a recess and protrusion profile on a surface of the magnetic transfer carrier 2 and for example, a fine recess and protrusion profile is directly formed using a laser beam, an electron beam or an ion beam or alternatively, such a profile may also be formed directly by machining.

25 Then, information signals corresponding to a pattern formed on the magnetic transfer carrier 2 are subjected to transfer recording, a procedure for which will be described with reference to Figs. 8 to 10.

At first, the magnet 17 is moved close to the magnetic record

30 medium 1. In this state, the magnet 17 is rotated in parallel to the magnetic record medium 1 with a central axis of the magnetic record medium 1 as a rotation axis. Thereby, the magnetic record medium 1 is magnetized in one direction indicated by an arrow mark

WO 03/001526

PCT/JP02/06095

of Fig. 8 in advance (initialization).

Then, the magnetic transfer carrier 2 is superimposed on the magnetic record medium 1 after positioning. In this superimposed state, the magnetic transfer carrier 2 and the magnetic record medium 1 are put into uniform and close contact with each other. Thereafter, there is applied a magnetic field in a direction opposite to that in initialization. Thereby, the magnetic portions 2d of the magnetic transfer carrier 2 are magnetized. Information signals corresponding to an arrangement pattern of the magnetic portions 2d on the magnetic transfer carrier 2, as shown in Fig. 9, are magnetically transferred in a prescribed region 1b on the magnetic record medium 1 superimposed on the magnetic transfer carrier 2. Note that, an arrow mark indicated in Fig. 9 is a direction of a magnetic field of a magnetization pattern magnetically transferred onto the magnetic record medium 1.

In Fig. 10, there is shown details of a magnetization performed. As shown in Fig. 10, a magnetic field is applied to the magnetic transfer carrier 2 from outside in a state where the magnetic transfer carrier 2 is superimposed on the magnetic record medium 1 to magnetize the magnetic portions 2d on the magnetic transfer carrier 2. Thereby, information signals can be magnetically transferred to the ferromagnetic layer 1c on the magnetic record medium 1. That is, by using the magnetic transfer carrier 2 on which the magnetic portions 2d made of a ferromagnetic thin film in an arrangement pattern corresponding to prescribed information signals are formed on the non-magnetic substrate 2b, magnetic transfer recording can be performed onto the magnetic record medium 1 as a magnetization pattern corresponding to the information signals.

Note that as a method for magnetic transfer of a pattern on the magnetic transfer carrier 2 onto the magnetic record medium 1, a method is also available in which the magnetic portions 2d

WO 03/001526

PCT/JP02/06095

on the magnetic transfer carrier 2 are magnetized in advance and then in this state, the magnetic transfer carrier 2 is put into close contact with the magnetic record medium 1, thereby enabling writing of information signals, in addition to a method in which  
5 as described above, an external magnetic field is applied to the magnetic transfer carrier 2 and the magnetic record medium 1 in a state where both are in contact with each other.

Thereafter, the magnetic transfer carrier 2 and the magnetic record medium 1 again move apart away from each other  
10 as shown in Fig. 1. That is, the exhaust valve 11 is closed and the gas feed valve 13 is opened and the gas feed pump 12 is operated. Then, air is forcibly fed as shown by the arrow marks A and B and the magnetic transfer carrier 2 is moved in one piece with the holding arm 14 by the action of a force of the air forcibly fed.  
15 The magnetic transfer carrier 2 ceases its movement where the top surface of the holding arm 14 comes into contact with the guide member 16. At this time, as shown by the arrow mark B, the air is forcibly sent radially through the recesses 4 toward the outer periphery of the magnetic transfer carrier 2 from the center  
20 thereof, which state is kept on.

Here, if foreign matter exists on the contact portions 3 of the magnetic transfer carrier 2, a defect would occur on the magnetic record medium 1 by performing magnetic transfer.

Description will be given of a cleaning method with  
25 reference to Figs. 11 to 13.

Fig. 11 is a perspective view of a construction of a disk cleaning apparatus.

In Fig. 11, the disk cleaning apparatus has a dummy carrier 102. A material of the disk dummy carrier 102 is a silicon wafer.  
30 The dummy carrier 102 has plural radial recesses 4' thereon with the same shape as the radial recesses 4 on the magnetic transfer carrier 2.

A reference numeral 103 indicates a rotary stage as a

WO 03/001526

PCT/JP02/06095

holding section holding the magnetic transfer carrier 2 and the dummy carrier 102. The rotary stage 103 rotate in a direction AA while holding the dummy carrier 102 with, for example, a static chuck. The rotary stage 103 also functions as a holding section  
5 for the magnetic transfer carrier 2, which is a disk to be cleaned.

A reference numeral 107 indicates a cleaner disk and 108 a cleaning tool in the shape of a pad made of polyurethane as a material, and the cleaning tool 108 is mounted along the outer periphery of the cleaning disk 107 and faces the recesses 4' on  
10 the dummy carrier 102. A reference numeral 109 is a rotation motor for autorotation of the cleaner disk 107 in the direction of an arrow mark BB, 110 a connecting arm connected to the rotation motor 109 at one end thereof and 111 a pivoting motion motor connected to the connecting arm 110 at the other end thereof and rotatable  
15 in the direction of an arrow mark CC. A reference numeral 112 indicates an air cylinder. The rotation motor 111 is placed on the air cylinder 112 and movable in the direction of an arrow mark DD.

A reference numeral 113 indicates a micrometer adjusting  
20 a movement of the air cylinder 112 in the direction of an arrow mark DD to adjust contact between the dummy carrier 102 and the cleaning tool 108, and 114 a jet port. The jet port 114 feeds pure water passing through a filter of 0.05  $\mu\text{m}$  in pore size (not shown). The pure water is jetted between the dummy carrier 102  
25 and the cleaning tool 108.

In such a cleaning apparatus, when the air cylinder 112 is positioned at an upper side thereof (the top of the arrow DD) of Fig. 11, the dummy carrier 102 and the cleaning tool 108 are moved apart away from each other, When the air cylinder 112 is  
30 positioned at a lower side thereof (the bottom of the arrow DD) of Fig. 11, the dummy carrier 102 and the cleaning tool 108 come into contact with each other. A contact press force acting between both 102 and 108 is adjusted by the micrometer 113 disposed

WO 03/001526

PCT/JP02/06095

at the lower end of the air cylinder 112.

When the air cylinder 112 is moved downward, a press-down quantity of the cleaning tool 108 into the dummy carrier 102 is set to 0.2 mm. To be detailed, the cleaning tool 108 is positioned  
5 at 0.2 mm downward from the contact position between the cleaning tool 108 and the dummy carrier 102. The position of the cleaning tool 108 is adjusted by the micrometer 113.

The constituents 109 to 113 cause the cleaning tool 108 to slide the cleaning tool 108 on the dummy carrier 102 or the magnetic  
10 transfer carrier 2 toward the outer periphery thereof from the inner periphery thereof to thus constitute a sliding section for cleaning the cleaning tool 108 and the magnetic transfer carrier 2.

First of all, the dummy carrier 102 is placed and held on  
15 the rotary stage 103. At this time, the air cylinder 112 is disposed at the upper side thereof in the direction of the arrow DD in the figure. In this state, the dummy carrier 102 and the cleaning tool 108 are moved apart away from each other. The cleaning tool 108 is disposed at a position FF in Fig. 12, that  
20 is a position outside of the dummy carrier 102 spaced therefrom.

Then, the cleaning tool 108, in Fig. 12, is pivoted around by the pivoting motion motor 111 from the position FF in the clockwise direction as viewed from above to as far as a position EE, that is the central position of the dummy carrier 102.

25 Then, the dummy carrier 102 is slowly rotated by the rotary stage 103 in the direction of the arrow mark AA, that is in the clockwise direction as viewed from above at a low speed of 20 rpm in rotation number, while the cleaning tool 108 is rotated by the rotation motor 109 in the direction of an arrow mark BB, that is  
30 in the clockwise direction as viewed from above at a high speed of 450 rpm in rotation number. In this state, a cleaning liquid is jetted from the jet port 114 toward between the dummy carrier 102 and the cleaning tool 108.

WO 03/001526

PCT/JP02/06095

Then, the cleaning tool 108 is moved to the lower side in the direction of the arrow mark DD by the air cylinder 112. Thereby, the cleaning tool 108 and the dummy carrier 102 are relatively moved so as to be close to each other while both are  
5 rotated. After the approach, the cleaning tool 108 is ceased its vertical advance into the dummy carrier 102 at a press-down position of 0.2 mm in depth therein.

Then, the cleaning tool 108 is pivoted around by the pivoting motion motor 111 in the direction of the arrow mark CC,  
10 that is in the counter-clockwise as viewed from above. A moving speed thereof is set such that the cleaning tool 108 is pivoted around by a distance less than the diameter thereof in a period when the dummy carrier 102 is rotated one rotation by the rotary stage 103 wherein the cleaning tool 108 is eventually put into  
15 contact with all the surface of the dummy carrier 102.

With such an operation, foreign matter attached on the surface of the cleaning tool 108 is removed from the cleaning tool 108 by contact between the recesses 4' on the dummy carrier 102 and the cleaning tool 108 and sent out to outside of the dummy  
20 carrier 102 through the recesses 4'.

Then, the pivoting motion motor 111 is completely ceased out of operation when the cleaning tool 108 is at the position FF of Fig. 12, that is at a position spaced apart from the dummy carrier 102, in other words, at a position with no contact portion  
25 between the cleaning tool 108 and the dummy carrier 102. With such an operation, foreign matter attached on the surface of the cleaning tool 108 is sent out from the surface of the dummy carrier 102 to outside thereof with certainty.

Finally, after the air cylinder 112 is moved to the upper  
30 side in the direction of the arrow mark DD, the cleaning tool 108 is moved by the rotary motor 112 to its original position indicated by the arrow mark EE of Fig. 13.

By repeating such a series of cleaning related actions,

WO 03/001526

PCT/JP02/06095

foreign matter attached to the cleaning tool 108 is removed.

In the above case, an effect of adaptation of the cleaning tool 108 to the magnetic transfer carrier 2 can be enjoyed together with an effect of cleaning the cleaning tool under conditions that the recesses 4' of the dummy carrier 102 has the same shape as the recesses 4 of the magnetic transfer carrier 2; the contact press force acting between the dummy carrier 102 and the cleaning tool 108 and the contact press force acting between the magnetic transfer carrier 2 and the cleaning tool 108 are almost the same as each other; and the rotation numbers of the dummy carrier 102 and the cleaning tool 108 and the rotation numbers of the dummy carrier 102 and the cleaning tool 108, respectively, are substantially equal to each other.

The surface of the cleaning tool 108 are hardened when being left without protection. Therefore, the cleaning tool 108 is cleaned using the dummy carrier 102 in the same shape as the magnetic transfer carrier 2 prior to actual cleaning of the magnetic transfer carrier 2, which is a disk to be cleaned, in the same condition as for the magnetic transfer carrier 2. With such an operation, the cleaning tool 108 in an hardened state is rendered to be in a soft state, thereby ensuring an optimal state for the cleaning.

After cleaning of the cleaning tool 108, cleaning of the magnetic transfer carrier 2 is performed, wherein since the cleaning step is the same as the cleaning step for the cleaning step for the cleaning tool 108, the dummy carrier 102 has simply to be changed to the magnetic transfer carrier 2.

In a case where there is an abnormal part at an end of a magnetic film 2d formed on the surface of the magnetic transfer carrier 2 and thereby, for example, a burr 2e exists as shown in fig. 13, there is a fear that the end thereof is scraped into broken pieces by the cleaning tool 108 and the broken pieces are attached to the cleaning tool 108, or alternatively, to the magnetic

transfer carrier 2.

In the case of this embodiment, however, the broken pieces of the magnetic film attached to such a magnetic transfer carrier 2 are moved to outside of the magnetic carrier 2 along the recesses 4 thereon by pivoting motion and movement toward the outer periphery of the cleaning tool 108. Thereafter, when the cleaning tool 108 moves away from the magnetic transfer carrier 2, the broken pieces attached on the surface of the magnetic transfer carrier 2 are also sent out to the outside of the magnetic transfer carrier 2 since a shape of each recess on the magnetic transfer carrier 2 is in a state to open toward the outside side of the magnetic transfer carrier 2 as shown in Fig. 3.

As described above, the broken pieces of the magnetic film are certainly sent out to outside without remaining attached on the surface of the magnetic transfer carrier 2.

In this case, however, a possibility exists that broken pieces of a magnetic film stay as attached on the surface of the cleaning tool 108. In a case where the magnetic transfer carrier 2 is cleaned over plural straight times with the cleaning tool 108 or in a case where there remain many abnormal ends 2e of magnetic film as fabrication defects thereof, many broken pieces from the magnetic film have a chance to attach onto the surface of the cleaning tool 108.

Therefore, if the dummy carrier 102 is placed again on the rotary stage 103 and cleaning of the cleaning tool 108 similar to the above described way is performed, broken pieces from the magnetic film attached on the surface of the cleaning tool 108 are removed.

In such a way, in the case of this embodiment, broken pieces of a magnetic film attached on the surface of the cleaning tool 108 can be removed by a simple method without adding any special apparatus construction.

Note that the present invention is not limited to a method

WO 03/001526

PCT/JP02/06095

for alternately cleaning the dummy carrier 102 and the magnetic transfer carrier 2, each single cleaning step for the dummy carrier 102 or the magnetic transfer carrier 2 at a time, but a method may be adopted in which, for example, after the cleaning tool 108 is cleaned with the dummy carrier 12, a prescribed number of magnetic transfer carriers, for example 10 times are cleaned, followed by putting the dummy carrier 102 in place into the cleaning apparatus for the second time of cleaning of the cleaning tool 108.

It may be determined whether or not broken pieces are attached on the surface of the cleaning tool 108 by counting particles in a cleaning liquid. That is, a method may be adopted in which a publicly known in-liquid particle counter is used to count particles in a liquid and when the number of particles in the liquid exceeds a prescribed value, the dummy carrier 102 is put into a cleaning apparatus.

The present invention is not limited to one dummy carrier 102 used prior to a magnetic transfer carrier 2, but plural, for example 10, dummy carriers 102 may be consecutively used prior to the magnetic transfer carrier 2, and then an effect of cleaning the cleaning tool 108 is improved.

In the present invention, a configuration of the dummy carrier is not limited to one on which no magnetic film is formed, but for example, when a magnetic transfer carrier having a magnetic film thereon, no corner of which is chipped away by a brush, or corners of which have been sufficiently chipped away already is used, an equivalent effect can be attained.

The cleaning brush 108 of the present invention may be of the shape of a roll brush. In a case of a roll brush, the roll brush does not slide on a surface toward the outer periphery from the inner periphery, but slides by rolling. Note that the present invention includes other ways of sliding.

WO 03/001526

PCT/JP02/06095

(Other Embodiments)

Description will be given of a cleaning method for a magnetic transfer carrier relating to a second embodiment of the present invention with reference to Figs. 14 and 15. In Fig. 14, the same symbols are attached to constituents corresponding to those of Fig. 11. A configuration of an apparatus in use is such that the magnetic transfer carrier 2 made of a silicon substrate of 50 mm in diameter is held by the rotary stage 103 and rotatable at a rotation speed of 1 rpm in the direction of an arrow mark AA. A radius of the cleaning tool 108 constituted of a rotary brush is 10 mm. A radius of the cleaning tool 108 is set so as to be smaller than a radius of 13 mm of a region including the center, where no part of the recesses 4 on the magnetic transfer carrier 2 is formed.

A press-down quantity of the cleaning tool 108 into the magnetic transfer carrier 2 when the air cylinder 112 is moved downward is set to 0.20 mm. That is, the cleaning tool 108 and the magnetic transfer carrier 2 are in position adjusted by the micrometer 113 such that the cleaning tool 108 reaches a position at 0.2 mm in distance downward from a position at which the cleaning tool 108 and the magnetic transfer carrier 2 are in contact with each other.

Referring to Fig. 15, a configuration is adopted such that a curvature radius of an circular arc of each recess 4 coincides with approximately a distance between the center of the pivoting motion motor 111 and the center of the cleaning tool 108. A configuration is adopted such that the center of the pivoting motion motor 111 is positioned such that the center thereof coincides with approximately a locus of the curvature center of each recess 4 circular arc when the magnetic transfer carrier 2 is rotated.

The magnetic transfer carrier 2 is placed on the rotary stage 103 and held there by a static chuck. At that time, the

WO 03/001526

PCT/JP02/06095

air cylinder 112 is positioned at the upper side in the direction of the arrow mark DD shown in Fig. 14 and the magnetic transfer carrier 2 and the cleaning tool 108 are spaced apart from each other. The cleaning tool 108 is disposed at the position

5 indicated by the arrow mark FF in Fig. 15.

The cleaning tool 108 is pivoted in the clockwise direction as viewed from above by the pivoting motion motor 111 to be moved to the position indicated by the arrow mark EE of Fig. 15, that is to as far as a position of the center of the magnetic transfer  
10 carrier 2.

The magnetic transfer carrier 2 is rotated in the direction of an arrow mark AA by the rotary stage 103 at a rotation number of one rpm, while the cleaning tool 108 is rotated in the direction of an arrow mark BB by the rotation motor 109 at a rotation speed  
15 of 450 rpm. In this state, a cleaning liquid is jetted from the jet port 114.

The cleaning tool 108 is moved to the lower head of the arrow mark DD by the air cylinder 112. Along with the movement, the cleaning tool 108 moves close to the magnetic transfer carrier  
20 2 while rotating and ceases its vertical movement at a position where the cleaning tool 108 is pressed down into the magnetic transfer carrier 2 at 0.2 mm in depth. At this time, as shown in Fig. 15, a recess and protrusion profile of the recesses 4 have no chance to be put into direct contact with the cleaning tool  
25 108 since a radius of 10 mm of the cleaning tool 108 is set smaller than a radius of the central region where no part of the recesses 4 exists.

The cleaning tool 108 is moved in the direction of an arrow mark CC by the pivoting motion motor 111. At this time, a moving  
30 speed of the rotation motor 11 is set at a value sufficiently larger than a rotation speed of 1 rpm of the magnetic transfer carrier 2 such that the cleaning tool 108 moves substantially along each recess 4.

WO 03/001526

PCT/JP02/06095

Fig. 16 is a graph showing a cycle of movement of the cleaning tool 108 in this case. In Fig. 16, the ordinate is assigned to a position of the air cylinder 112, while the abscissa is used for plotting an elapsed time. When the air cylinder 112 is positioned at the upper side, there is shown a state where the cleaning tool 108 and the magnetic transfer carrier 2 is spaced apart away from each other, while when the air cylinder 112 is positioned at the lower side, there is shown a state where the cleaning tool 108 and the magnetic transfer carrier 2 are in contact with each other.

At an elapsed time of 0 sec in Fig. 16, the graph shows a state where the air cylinder 112 is at the upper side and the cleaning tool 108 is disposed at the position indicated by the arrow mark FF in Fig. 15. At an elapsed time of 1 sec, the graph shows a state the air cylinder 112 is at the upper side and the cleaning tool 108 moves to a position indicated by the arrow mark EE in Fig. 15. At an additional elapsed time of 0.5 sec, the air cylinder 112 moves the lower side to come into contact with the magnetic transfer carrier 2.

Thereafter, the cleaning tool 108 moves from the position indicated by the arrow mark EE to the position indicated by the arrow mark FF in Fig. 15 while keeping the position of the air cylinder 112 at the lower side thereof. That is, the cleaning tool 108 slides on the surface of the magnetic transfer carrier 2 toward the outer periphery thereof from the inner periphery thereof.

At this time, since a radius of 10 mm of the cleaning tool 108 is set smaller than the central region where no part of the recesses 4 is formed, the cleaning tool 108 can be caused to be slid toward the outer periphery from the inner periphery with certainty especially in the section where radial shapes of the recesses 4 are formed.

The position indicated by the arrow mark FF is selected at

WO 03/001526

PCT/JP02/06095

a position where the cleaning tool 108 is spaced apart away from the outer periphery edge of the magnetic transfer carrier 2 such that the cleaning tool 108 and the magnetic transfer carrier 2 do not come into contact with each other. Thereby, foreign matter  
5 does not remain at the outer periphery edge of the magnetic transfer carrier 2 and can be removed with certainty.

At an additional elapsed time of 0.5 sec, the cleaning tool 108 moves again to a position when the air cylinder 112 moves to the upper side thereof. Thereafter, a cleaning operation as  
10 described above is repeated to thereby remove foreign matter.

In this embodiment, a movement cycle of the cleaning tool 108 is set to 3 sec. In addition, a total cleaning time is set to be 5 min. Therefore, repetition of the movement of the rotary brush amounts to 100 cycles in total.

15 Since a rotation speed of the magnetic transfer carrier 2 is set to 1 rpm, and a radius thereof is set to 50 mm, the outer periphery edge of the magnetic transfer carrier 2 moves across a distance  $\pi \times 2 \times 50 \text{ mm} \times (1/60) \times 3 \text{ sec} = 15.6 \text{ mm}$  while the cleaning tool 108 operates in one cycle.

20 Since a radius of the cleaning tool 108 is 10 mm, the outer periphery edge of the magnetic transfer carrier 2 is cleaned across a length of  $10 \text{ mm} \times 2 = 20 \text{ mm}$  in one cycle of the cleaning tool 108. Therefore, since cleaning is performed in a region equal to or longer than 15.6 mm across which the magnetic transfer  
25 carrier 2 moves, all of the surface of the magnetic transfer carrier 2 is certainly put into contact with the cleaning tool 108 while the magnetic transfer carrier 2 rotates one time.

That is, if a radius of the cleaning tool is  $r$  (mm), a sliding repetition cycle in a case where the cleaning tool slides under  
30 control of the sliding section is  $t$  (s), a radius of the magnetic transfer 2 having the shape of almost a circle is  $R$  (mm) and a rotation speed of the magnetic transfer carrier 2 is  $x$  (rps) by definition, the relation of the following expression is

WO 03/001526

PCT/JP02/06095

preferably established:

$$\pi t \times R < r \Lambda \quad (1)$$

Since a moving speed of the cleaning tool 108 is sufficiently faster compared with a rotation speed of the magnetic transfer carrier 2, the cleaning tool 108 can be certainly slid toward the outer periphery of the magnetic transfer carrier 2 from the inner periphery thereof almost along the radial shape of the recesses 4 on the magnetic transfer carrier 2.

Foreign matter attached in the recesses 4 can be certainly sent out to the outer periphery side by providing a construction in which the recesses 4 are formed in a radial shape extending toward the outer periphery of the magnetic transfer carrier 2 from the inner periphery thereof on the surface thereof with the outer periphery edge in an open state outside thereof, and the cleaning tool 108 can slide along the radial shape of the recesses 4 on the magnetic transfer carrier 2 toward the outer periphery thereof from the inner periphery thereof. That is, foreign matter attached in the recesses 4 is separated from the magnetic transfer carrier 2 by the contact with the magnetic transfer carrier 2 of the cleaning tool 108 and the rotation movement of the cleaning tool 108 itself and sent out to the outer side of the magnetic transfer carrier 2 through the recesses 4 formed in the radial shape.

Since the position indicated by the arrow mark FF of the cleaning tool 108 where the cleaning tool 108 is spaced apart away from the magnetic transfer carrier 2 is set to a position where the cleaning tool 108 is in no contact with the magnetic transfer carrier 2, that is a position where perfectly no contact portion exists between the cleaning tool 108 and the magnetic transfer carrier 2, foreign matter attached to the surface of the magnetic transfer carrier 2 can be certainly sent to outside of the magnetic transfer carrier 2.

At this time, as shown in this embodiment, a width of a recess

WO 03/001526

PCT/JP02/06095

4 is preferably increased toward the outer periphery. This is because, with such a shape, foreign matter is easy to be sent out to the outside in company with sliding of the cleaning tool 108 toward the periphery from the inner periphery.

5 In addition, as shown in this embodiment, a press-down quantity of the cleaning tool 108 is preferably set to a value 10 times depth of a recess 4 or more. This is because if the press-down quantity is excessively small, an effect of removing foreign matter at the periphery edge of each of the recesses 4 is lost.

10 For example, observation with a microscope was performed in order to confirm a relationship between a press-down quantity of the cleaning tool 108 and the presence/absence of foreign matter in the recesses 4 after cleaning the magnetic transfer carrier 2 by adjusting the micrometer 113. As a result, it was confirmed that with a press-down quantity of 0.05 mm or more in a case of a depth of a recess 4 was 5  $\mu$ m, foreign matter in the recesses 4 was certainly removed.

20 As described above, it has been made clear through the experiments that foreign matter in the recesses 4 is certainly removed by setting a press-down quantity of the cleaning tool 108 to a value 10 times or more a depth of a recess 4.

25 Then, description will be given of a magnetic record reproducing apparatus with reference to Fig. 17. Fig. 17 is a view of a hard disk apparatus in a case where the magnetic disk 1 after magnetic transfer is performed using the magnetic transfer carrier 2 having been cleaned is installed in the hard disk apparatus.

30 In Fig. 17, a reference numeral 1 indicates a magnetic disk after magnetic transfer. Recording is performed onto the magnetic disk 1 by magnetically transferring information in the signal region 2a on the magnetic transfer carrier 2.

While a magnetic head 61 is scanned over the magnetic disk

WO 03/001526

PCT/JP02/06095

1, the magnetic head 61 mounted on a head suspension 62 moves along a circular arc with a rotation axis 63 of a head actuator as the center thereof, which movement coincides with a circular arc of the signal region 2a. The magnetic disk 1 rotates at a rotation speed of 5400 rpm in the counterclockwise direction as viewed from above by a spindle motor (not shown) and the magnetic head 61 is pivotable by a voice coil motor 64 in a floating state 20 nm above the magnetic disk 1.

In the hard disk apparatus mounted with the magnetic disk 1 after magnetic transfer, record reproduction was performed with the magnetic head 1 to test a data error percentage. As a result of the test, it was found that a magnetic disk after magnetic transfer was performed using a magnetic transfer carrier cleaned by the method shown in this embodiment had almost the same data error percentage as a magnetic disk on which magnetic transfer was not performed. Therefore, it is thought that cleaning was realized by which no foreign matter remained on the surface of the magnetic transfer carrier 2 and no foreign matter remained in the recesses 4 either.

According to this embodiment, as described above, a surface of a magnetic transfer carrier and recesses thereon can be cleaned by a simple method with certainty. Therefore, a high reliability magnetic record reproducing apparatus can be realized.

Note that while as a liquid for cleaning, pure water is used, no specific limitation is imposed to this, but other liquid such as IPA (isopropyl alcohol), for example, can be used with an equivalent effect.

#### Industrial Applicability

According to the present invention, application can be made to a cleaning method for a magnetic transfer carrier for use in magnetic transfer to a magnetic record medium used in a hard disk apparatus and a floppy disk apparatus.

## Claims

1. A cleaning method comprising:

a first step of placing a dummy carrier having at least one recess thereon, said recess opening toward an outer periphery thereof from an inner periphery thereof on a rotary stage used for placing a magnetic transfer carrier thereon, said magnetic transfer carrier having plural radial recesses thereon each opening toward an outer periphery thereof from an inner periphery thereof; and

a second step of sliding a cleaning tool for cleaning said magnetic transfer carrier on said dummy carrier toward said outer periphery thereof from said inner periphery thereof while rotating said dummy carrier with said rotary stage in rotation.

2. The cleaning method according to claim 1, wherein in said second step, said cleaning tool is slid on said dummy carrier toward the outer periphery thereof from the inner periphery thereof while rotating in substantially the same direction as in cleaning of said magnetic transfer carrier.

3. The cleaning method according to claim 1, wherein said dummy carrier has plural radial recesses thereon each with substantially the same shape as that of each of said plural radial recesses on said magnetic transfer carrier.

4. The cleaning method according to claim 1, wherein in said second step, a contact press force of said cleaning tool to said dummy carrier when said cleaning tool is slid on said dummy carrier in cleaning is substantially the same as a contact press force of said cleaning tool to said magnetic transfer carrier when said cleaning tool is relatively slid on said magnetic transfer carrier in cleaning.

WO 03/001526

PCT/JP02/06095

5. The cleaning method according to claim 1, wherein  
in said second step, a relative speed of said cleaning tool  
to said dummy carrier when said cleaning tool is slid on said dummy  
carrier in cleaning is substantially the same as a relative speed  
5 of said cleaning tool to said magnetic transfer carrier when said  
cleaning tool is relatively slid on said magnetic transfer carrier  
in cleaning.

6. The cleaning method according to claim 1, wherein  
10 in said cleaning, said cleaning tool is relatively moved  
as far as outside of said outer periphery edge of said dummy  
carrier.

7. The cleaning method according to claim 1, wherein  
15 said cleaning tool is a rotary brush made of polyurethane.

8. A cleaning method comprising:

a first step of sliding a cleaning tool relatively on a dummy  
carrier thereon having at least one recess opening toward an outer  
20 periphery thereof from an inner periphery thereof to clean said  
cleaning tool; and

a second step of, after said first step, sliding said  
cleaning tool relatively on a magnetic transfer carrier having  
plural recesses thereon each opening toward an outer periphery  
25 thereof from an inner periphery thereof in a state where said  
magnetic transfer carrier is held, to clean said magnetic transfer  
carrier.

9. The cleaning method according to claim 8, wherein  
30 a shape of said recess of said dummy carrier and a shape  
of said recess of said magnetic transfer carrier are substantially  
the same as each other.

WO 03/001526

PCT/JP02/06095

10. The cleaning method according to claim 8, wherein  
a contact press force of said cleaning tool to said dummy  
carrier when said cleaning tool is slid on said dummy carrier in  
cleaning is substantially the same as a contact press force of  
5 said cleaning tool to said magnetic transfer carrier when said  
cleaning tool is relatively slid on said magnetic transfer carrier  
in cleaning.

11. The cleaning method according to claim 8, wherein  
10 a relative speed of said cleaning tool to said dummy carrier  
when said cleaning tool is slid on said dummy carrier in cleaning  
is substantially the same as a relative speed of said cleaning  
tool to said magnetic transfer carrier when said cleaning tool  
is relatively slid on said magnetic transfer carrier in cleaning.

12. The cleaning method according to claim 8, wherein  
15 in said first step, a cleaning liquid is jetted in a  
direction of said cleaning tool.

13. The cleaning method according to claim 12, wherein  
20 foreign matter in said cleaning liquid is measured, and  
according to a result of said measurement, cleaning with  
said cleaning tool is performed.

14. The cleaning method according to claim 8, wherein  
25 said cleaning tool is relatively moved as far as outside  
of said outer periphery edge of said dummy carrier.

15. The cleaning method according to claim 8, wherein  
30 said cleaning tool is relatively moved as far as outside  
of said outer periphery edge of said magnetic transfer carrier.

WO 03/001526

PCT/JP02/06095

19. A cleaning apparatus comprising:

a holding section capable of holding a first carrier to be cleaned in the shape of a disk and a second carrier used as a dummy in the shape of a disk;

5 a cleaning tool disposed facing each of said both carriers held by said holding section; and

a sliding section sliding said cleaning tool relatively on

10

15

20

25

30

WO 03/001526

PCT/JP02/06095

each of said both carriers in cleaning, and

being operable according to a procedure including:

5 a step of sliding said cleaning tool with said sliding section on said second carrier relatively thereto in a state where said second carrier is held by said holding section to clean said cleaning tool; and

10 a step of sliding said cleaning tool cleaned in said previous step on said first carrier relatively thereto in a state where said first carrier is held by said holding section to clean said first carrier.

15 17. The cleaning apparatus according to claim 16, wherein in cleaning, said cleaning tool is relatively moved as far as outside of said outer periphery edge of said second carrier.

18. The cleaning apparatus according to claim 16, wherein in cleaning, said cleaning tool is relatively moved as far as outside of said outer periphery edge of said first carrier.

20 19. The cleaning apparatus according to claim 16, wherein a carrier is used, as said first carrier, on which an information signal is recorded, and which is used in magnetic transfer of said information signal onto a magnetic record medium in contact therewith, and having a recess for close contact  
25 between said first carrier and said second carrier in magnetic transfer, on a magnetic transfer surface of said carrier facing said magnetic record medium, in which said recess has a shape to open toward an outer periphery of said carrier from an inner periphery thereof and in addition, serves as a recess for cleaning,  
30 and

a carrier is used, as said second carrier, on which a recess with almost the same shape as that of said recess on said first carrier, on at least one carrier surface thereof.

WO 03/001526

PCT/JP02/06095

20. A dummy carrier, in correspondence to a magnetic transfer carrier used for magnetic transfer of an information signal with plural radial recesses thereon each opening toward an outer periphery thereof from an inner periphery thereof on a magnetic transfer surface thereof; having a radial recess extending toward an outer periphery thereof from an inner periphery thereof on at least one surface thereof, a shape of which recess is the same or substantially the same as that of each of said plural radial recesses on said magnetic transfer surface, and being used for cleaning of a cleaning tool cleaning said magnetic transfer carrier.

21. The cleaning apparatus according to any one of claims 16 to 19, wherein the apparatus is for cleaning a magnetic transfer carrier having a magnetic film corresponding to an information signal formed on a surface on a substrate, and wherein:

said magnetic transfer carrier has a recess of a radial shape thereon extending toward an outer periphery thereof from an inner periphery thereof with an edge at said outer periphery opening to outside thereof;

the cleaning tool is disposed facing a surface of said magnetic transfer carrier on which said magnetic film is formed; and

the sliding section is arranged to slide said cleaning tool on said magnetic transfer carrier relatively thereto, and wherein in cleaning, said sliding section presses said cleaning tool to said magnetic transfer carrier at a prescribed quantity of press-down and keeping this state, slides said cleaning tool toward said outer periphery from said inner periphery of said magnetic transfer carrier in conformity to said radial shape of said recess.

22. The cleaning apparatus according to claim 21, wherein on a surface of said magnetic transfer carrier, an area of

WO 03/001526

PCT/JP02/06095

a central portion having no part of said recess is larger than an area in which said cleaning tool is in contact with said magnetic transfer carrier.

5           23. The cleaning apparatus according to claim 21, wherein said cleaning tool is a rotary brush rotating about a line, as an axis, in a direction in substantially parallel to a line normal to said magnetic transfer carrier.

10           24. The cleaning apparatus according to claim 21, wherein if a radius of said rotary brush is  $r$  (mm), a cycle of sliding repetition in sliding of said rotary brush driven by said sliding section is  $t$  (s), a radius of said magnetic transfer carrier of a substantially circular shape is  $R$  (mm), and a rotation speed  
15 of said magnetic transfer carrier when being rotated by said holding section is  $x$  (rps) by definition, a relation of  $\pi t \times R < r$  is established.

20           25. The cleaning apparatus according to claim 21, wherein if a depth of said recess on said magnetic transfer carrier is  $M$  (mm) and, a press-down quantity of said rotary brush into said magnetic transfer carrier in cleaning is  $N$  (mm) by definition, a relation of  $N/M > 10$  is established.

25           26. The cleaning apparatus according to claim 21, wherein said recess is enlarged in width toward the outer periphery from the inner periphery.

30           27. The cleaning apparatus according to claim 21, wherein said cleaning tool is slid to as far as outside of an outer periphery edge of a magnetic film on said surface of said magnetic transfer carrier on which said magnetic film is formed.

WO 03/001526

PCT/JP02/06095

28. The cleaning apparatus according to claim 21, wherein  
said recess is of the shape of a substantially circular arc,  
said cleaning tool is pivoted around a prescribed position as a  
center, and a curvature radius of said circular arc and a radius  
5 of said pivoting motion of said rotary brush are substantially  
in coincidence with each other.

29. A cleaning method according to any one of claims 1  
to 15 and further being for cleaning a magnetic transfer  
10 carrier having a magnetic film corresponding to an  
information signal formed on a surface of a substrate, the  
method further comprising the steps of:

holding said magnetic transfer carrier having a recess of  
a radial shape thereon extending toward an outer periphery thereof  
15 from an inner periphery thereof with an edge at said outer  
periphery opening to outside thereof; and

sliding a cleaning tool disposed facing a surface of said  
magnetic transfer carrier on which a magnetic film is formed,  
relatively thereto, wherein

20 in cleaning, said sliding section presses said cleaning  
tool to said magnetic transfer carrier at a prescribed quantity  
of press-down and keeping this state, slides said cleaning tool  
toward the outer periphery from the inner periphery in conformity  
to said radial shape of said recess.