

IDENTIFICATION FRIEND OR FOE (IFF) SYSTEM AND METHOD

Divisional status is claimed from of Singapore patent/patent application no. 11201802341W, filed on 21 March 2018, the disclosure of which is incorporated by reference herein in its entirety.

TECHNOLOGICAL FIELD

The present invention is in the field of identification friend or foe systems and particularly relates to friend or foe identification systems which utilize optical beams for interrogating a region of interest.

5 BACKGROUND

Identification Friend or Foe (IFF) systems are used to detect and possibly identify friendly forces located in a region of interest. Identification Friend or Foe (IFF) systems typically include an interrogator module/system (hereinafter IFF interrogator) and complementary transponder module(s)/system(s) (hereinafter IFF transponder).

10 According to some known techniques, the interrogator system transmits a relatively wide, coded interrogation optical beam, whose lateral width (diameter) is in the order of several meters to several tens of meters, towards the region of interest. The optical beam, commonly generated with a laser, illuminates the entire region of interest in which friendly forces, if located therein, should be detected. If transponder module(s)

15 are located within the illumination region of the interrogating optical beam, they detect illumination of the optical beam, and, in response, transmit an RF signal acknowledging detection of the optical beam. Meanwhile, the interrogator system, after transmitting the optical beam, awaits for receipt of such acknowledging RF signals by its RF receiver/transceiver within a certain duration. The response may include the

20 interrogator's identification code transmitted by the interrogating optical beam. Consequently, upon receipt of such acknowledging signals, the interrogator module may identify whether it was transmitted by an IFF transponder module of friendly forces and whether it was transmitted in response to the same interrogation optical beam

that it had previously sent (or, for example, an interrogation by another IFF interrogator).

Such IFF systems and methods are described for example in PCT patent publications WO 2014/024196 assigned to the assignee of the present invention.

5 GENERAL DESCRIPTION

Conventional IFF systems used today require that a dedicated and specifically designed laser transmitter module be part of their IFF interrogator system. In this regard, even in cases where it is known that the IFF interrogator is going to be installed in the vicinity of other/external laser modules/transmitters, such as a laser-based range
10 finder (LRF), still the conventional IFF systems are not configured to take advantage of such readily available external lasers and include, and make use of, an additional, dedicated laser transmitter.

The inventors of the present invention found that an interrogator system
15 designed to use readily available external laser transmitters, such as an LRF, is advantageous over conventional IFF systems, in terms of size, weight and energy consumption of the interrogator system, as well as in terms of its cost effectiveness.

However, the inventors of the present invention have also noted that such
20 marriage between an IFF system and an external range finder to utilize the latter in place of a dedicated laser within the IFF system is hindered by one or more of the following difficulties: (i) independent LRFs typically do not contain interfaces for external activation; it is therefore practically impossible to interface to the external laser module from conventional IFF systems, to activate it or determine its activation; (ii)
25 LRFs typically use narrow laser beams to maximize the power of light reflected from a target towards which the range should be measured; This conflicts with the general requirement of IFF interrogators to illuminate a relatively large interrogation spot/area (illuminate/cover an interrogation spot width/diameter of several meters to tens of meters). Typically LRFs beams divergence is on the order of one mili-radian or less, so
30 that the illumination spots on the target area are on the order of a meter or less at 1Km, for example; (iii) In conventional IFF techniques the optical beam transmitted by the IFF interrogator is encoded with information indicative of the identification of the IFF

interrogator transmitting it (so that the IFF transponder detecting the laser beam can verify that the interrogation is legitimate and encode the interrogator's identification code onto the RF acknowledgement signal it sends); However, LRFs typically use a single laser pulse, which make it practically impossible to transmit the interrogator's
5 identification code over the its laser beam, thus prohibiting IFF transponder from verifying whether the interrogation is legitimate and encoding the interrogator's identification code onto the RF acknowledgement signal it sends).

The present invention provides a novel IFF system and method using novel IFF
10 interrogators and IFF transponders which are configured and operable to enable exploiting external laser transmitters for generation of the interrogating laser beam instead of a dedicated and specifically designed laser transmitter in the IFF interrogator.

According to certain broad aspects, the system and methods of the present
15 invention provide and enable interfacing to external laser transmitter(s), such as laser range finders, and use their output laser beams (which are pulsed laser beams, mostly comprising a single pulse) as IFF interrogation optical beams. Moreover, advantageously, according to some broad aspects, the system and methods of the invention are adapted to enable use of external laser transmitters which provide a
20 narrow beams, (such as range finders, for whose laser beams are typically narrower by one or more orders of magnitude than the lateral width of a typical interrogation spot size to be generated by an IFF interrogator) and use the narrow laser beam for illuminating and interrogating the region of interest. Furthermore, certain aspects of the present invention provide a novel system and method for encoding the identification
25 code of the IFF interrogator, while using an external laser module which does not necessarily provide means for modulating or encoding information on its laser beam, thereby enabling using such external laser as an IFF laser transmitter for the IFF interrogator.

30 Thus, according to a broad aspect of the present invention there is provided an Identification Friend or Foe (IFF) system including an IFF interrogator for interrogation of complementary IFF transponders. The IFF interrogator includes: an RF transceiver

module, a control system, and a laser activation interface module operable in conjunction with an independent external laser transmitter; whereby:

- 5 **(a)** the RF transceiver module is configured and operable for transmitting an RF broadcast signal to be received by an IFF transponder of the complementary IFF transponders being within the interrogation range of the IFF interrogator system and for receiving an RF response signal transmitted by the IFF transponder;
- 10 **(b)** the laser activation interface module is configured and operable for interfacing with an external laser module to determine activation of the external laser transmitter of transmission of a laser beam;
- (c)** the control system is connectable to the RF transceiver module and to the laser activation interface module, and configured and operable for carrying out IFF interrogation by:
 - 15 **i)** arming the IFF transponders for sensing laser illumination by operating the RF transceiver module to transmit the RF broadcast signal;
 - ii)** utilizing the laser activation interface to determine activation of the external laser transmitter; and
 - 20 **iii)** processing information indicative of RF signals received by the RF transceiver to identify therein an RF response signal transmitted by the IFF transponder, which is complementary to the IFF interrogation system, in response to detection of the transmitted laser beam from the external laser transmitter by the IFF transponder.

25 According to another broad aspect of the present invention there is provided an Identification Friend or Foe (IFF) interrogator system for interrogating complementary IFF transponders which are complementary to the IFF interrogation system. The interrogator system includes: an RF transceiver module and a control system. The interrogator system also includes an activation interface module operable in conjunction
30 with an independent external laser transmitter, whereby:

- (a)** the RF transceiver module is configured and operable for transmitting an RF broadcast signal to be received by an IFF transponder and for receiving an

RF response signal transmitted from the IFF transponder in response thereto;

- 5 **(b)** the laser activation interface module is configured and operable for interfacing with the external laser transmitter to determine activation and provide a synchronizing signal indicative of a time of transmission of laser beam by the external laser transmitter; and
- (c)** the control system is connectable to the RF transceiver module and to the laser activation interface and configured and operable for:
 - 10 **i)** registering time of transmission of at least one RF broadcast signal by the RF transceiver;
 - ii)** registering time of transmission of at least one laser beam transmitted by the external laser transmitter;
 - iii)** determining a time pattern associated with time intervals between the at least one RF broadcast signal and the at least one laser beam, beam
15 the time pattern representing an identification code of the IFF interrogator system;
 - iv)** obtaining information from the RF transceiver indicative of RF signals received thereby;
 - v)** processing the information to identify if the RF signals include an RF
20 response signal from a certain IFF transponder and decode the RF response signal to determine if it encodes the identification code of the IFF interrogator system which was represented by the time pattern of the at least one transmitted RF broadcast signal and at least one transmitted laser beam, and thereby determine if the certain IFF
25 transponder was interrogated by the IFF interrogator system.

According to another broad aspect of the present invention there is provided an Identification Friend or Foe (IFF) transponder (e.g. complementary to the IFF interrogator). The IFF transponder includes:

- 30 **(a)** a photo detector configured and operable for detecting light illumination in a certain wavelength band when intensity of the illumination exceeds a certain threshold;

- (b) an RF transceiver module configured and operable for receiving an RF broadcast signal transmitted by an IFF interrogation system complementary to the IFF transponder, and for transmitting an RF response signal to be received by the IFF interrogation system; and
- 5 (c) a controller connectable to the RF transceiver module and to the photo detector, the controller being adapted to:

 - i) process signals received by the RF transceiver to identify receipt of at least one RF broadcast signal from an IFF interrogation system;
 - 10 ii) process information obtained from the photo detector to identify detection of at least one interrogation laser beam by the photo detector;
 - iii) determine a time pattern associated with the time interval between receipt time of the at least one RF broadcast signal and detection time of the at least one interrogation laser beam ; and
 - 15 iv) operate the RF transceiver for transmitting the RF response signal such that the RF response signal encodes data indicative of the time pattern and wherein the time pattern representing an identification code of the interrogator to which the RF response signal is designated.

20 According to yet another broad aspect of the present invention there is provided an Identification Friend or Foe (IFF) interrogator system including:

- (a) a laser activation interface module configured and operable for interfacing an external laser module to determine activation of a laser beam by the external laser module;
- 25 (b) an RF transceiver module configured and operable for receiving an RF response signal transmitted from an IFF transponder complementary to the IFF interrogation system, in response to interrogation of the IFF transponder by an interrogation laser beam;

in this aspect of the invention the external laser module may output a laser beam
30 having a cross-section substantially smaller than a cross-sectional dimension of the area to be covered by the IFF interrogation system via illumination at a certain distance range from the external laser module, and intensity of the laser beam is substantially

higher than the minimal intensity detection threshold of a transponder system complementary to the IFF interrogation system. To this end, the IFF interrogation system is associated with a beam scattering directive providing instructions for directing the optical output axis of the external laser module towards light scattering
5 objects/surfaces in the vicinity of the distance range at which the cross sectional area should be covered, such that the cross-sectional area is illuminated by light scattered from the laser beam by the scattering objects/surfaces.

In some embodiments the beam scattering directive includes instructions for
10 sweeping the orientation of the optical axis of the external laser transmitter across a certain angular span such that the area that should be covered by the IFF interrogation system is effectively illuminate by light scattered from the laser beam during the swiping.

15 In some embodiments the beam scattering directive is at least partially implemented by an operation manual of the IFF interrogation system which includes information indicative of the instructions.

In some embodiments the beam scattering directive is at least partially
20 implemented by a beam direction module of the IFF interrogation system which is configured and operable to provide instructions for adjustment of an orientation of the optical output axis.

According to yet another broad aspect of the present invention there is provided
25 an Identification Friend or Foe (IFF) interrogation method comprising carrying out IFF interrogation by carrying out the following:

- (a) transmitting at least one RF broadcast signal suitable for receipt by a complementary IFF transponder;
- (b) registering a time of transmission of the at least one RF broadcast signal by
30 the RF transceiver;
- (c) operating a laser activation interface module adapted to interface an external laser transmitter, to determine activation of the external laser transmitter for

transmitting at least one interrogation laser beam towards an interrogation region of interest;

- (d) determining and registering a time of transmission of the at least one interrogation laser beam by the external laser transmitter;
- 5 (e) determining a time pattern associated with time intervals between transmission times of the at least one RF broadcast signal and the at least one interrogation laser beam, the time pattern representing an identification code of the IFF interrogator system;
- (f) obtaining information about RF signals received by an RF receiver;
- 10 (g) processing the information to determine whether the RF signals includes an RF response signal from an IFF transponder; and
- (h) upon detection of an RF response signal from a certain IFF transponder, decoding the RF response signal to determine whether it encodes the identification code of the IFF interrogator system which was represented by
15 the time pattern, and thereby determine whether the certain IFF transponder was interrogated by the at least one interrogation laser beam.

In yet further aspect of the invention there is provided a Friend or Foe Identification (IFF) transponding method including:

- 20 (a) process signals received by the RF transceiver to identify receipt of at least one RF broadcast signal from an IFF interrogation system, and register time of the receipt
- (b) process signals obtained from the photo detector to identify detection of at least one interrogation laser beam by the photo detector, and register time of
25 the detection;
- (c) determine a time pattern associated with the time interval between the time of receipt of the at least one RF broadcast signal and the time of detection of the at least one interrogation laser beam; and transmitting an RF response signal encoding data indicative of the time pattern; the time pattern
30 representing an identification code of the interrogation laser beam of an IFF interrogator to which the RF response signal is designated.

In another broad aspect the invention provides an Identification Friend or Foe (IFF) interrogation method for carrying out IFF interrogation. The method includes providing a beam scattering directive including instructions for directing the optical output axis of an external laser transmitter. The external laser transmitter outputs a laser beam with a cross-sectional area that is substantially smaller than a cross-sectional area to be illuminated at a certain distance range during the IFF interrogation, and intensity of the laser beam is substantially higher than the minimal intensity detection threshold of an IFF transponder system intended to respond to the IFF interrogation. Instructions for directing the optical output axis of the external laser transmitter include instructions to direct the optical output axis towards light scattering surfaces in the vicinity of the certain distance range such that the cross-sectional area is illuminated by light scattered from the laser beam by the scattering surfaces.

In some embodiments the beam scattering directive is at least partially implemented by an operation manual of the IFF interrogation system which includes information indicative of the instructions. Alternatively or additionally, in some embodiments the beam scattering directive is at least partially implemented by a beam direction module of the IFF interrogation system which is configured and operable to provide one or more of the instructions as operational instructions to directing module of the external laser system to adjust the orientation of the optical output axis.

According to some embodiments the instructions include at least one of the following:

- i) instructions for detecting a scattering surface in the vicinity of the distance range;
- ii) instructions for determining the orientation angle to direct the optical output axis towards the scattering surface;
- iii) instructions for directing the optical output axis to the orientation angle(s) θ so as to direct it towards the scattering surface;
- iv) instructions for activating, or determining activation of the external laser transmitter after the optical output axis is directed towards the scattering surface;

- 5 v) instructions for sweeping the orientation of the optical axis of the external laser transmitter across a certain angular span such that the area that should be covered by the IFF interrogation system is effectively illuminated by light scattered from the laser beam during the swiping.

Further details in the method and systems of the present invention and their implementation are described in further detail with references to the accompanying drawings, in the detailed description section below.

10 **BRIEF DESCRIPTION OF THE DRAWINGS**

In order to better understand the subject matter that is disclosed herein and to exemplify how it may be carried out in practice, embodiments will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

15 **Fig. 1** is a block diagram of a conventional IFF system;

Figs. 2A to 2C illustrate a block diagram and flow charts showing the configuration and methods of operation of an IFF system **1000** according to an embodiment of the present invention;

20

Fig. 3 is a block diagram illustrating an IFF interrogator **100** and a complementary IFF transponder **200**, according to an embodiment of the present invention which are configured for respectively communicating a code/identity of the IFF interrogator **100** in association with the interrogation optical beam **2**, and
25 determining and encoding that code in the RF response signal **3**;

Figs. 4A to 4C are block diagrams illustrating an IFF interrogator **100** according to an embodiment of the present invention comprising an activation interface **130** comprising a passive switch interface **PSI** coupled with an operating switch **320** of an
30 external laser transmitter **300**;

Figs. 5A and 5B are block diagrams illustrating in a self explanatory manner an IFF interrogator **100** with an activation interface **130** comprising a passive electromagnetic interface **PEI** electromagnetically coupled to sense activation of an external laser transmitter **300**;

5

Figs. 6A to 6B are block diagrams illustrating in a self explanatory manner of an IFF interrogator **100** according to another embodiment of the present invention, in which the passive electromagnetic interface **PEI** is electromagnetically coupled to the laser emitter **310** the an external laser transmitter **300**; and

10

Figs. 7A and 7B are a block diagram and a flow chart showing the configuration and method of operation of an interrogation system **100** adapted to be coupled to an external laser transmitter **300** outputting a narrow laser beam **2**.

DETAILED DESCRIPTION OF EMBODIMENTS

15 **Fig. 1** is a block diagram depicting a conventional identification friend or foe system **5000** configured according to the general art. The system includes an IFF interrogator (interrogation system) **10** and an IFF transponder **20**. The IFF interrogator **10** includes a controller **11** connected to RF receiver **12** and to laser emitter **13**, which is integral to the interrogation system **10**. The laser emitter **13** is configured to output a
20 optical beam, which, has relatively wide cross-section **d** (e.g. typically **d** is in the order of a few meters to tens of meters), at the desired interrogation range **R** (e.g. typically **R** is a distance in the range between tens of meters to a few hundreds of meters or a few kilometers). Accordingly, the laser emitter **13** integral to such a conventional interrogation system **10** is suitable for covering/illuminating an interrogation region
25 with a relatively wide cross-section **d** at the range **R**. The controller **11** is adapted to operate the laser emitter **13** such that the emitter **13**, whose operation is controlled by the controller **11**, encodes data indicative of the identification of the interrogation system **10** in the optical beam **14** it outputs. In turn, the IFF transponder **20** can detect the optical beam **14** of the interrogation (e.g. by photodetector **22**), decode the
30 identification code encoded in the detected laser beam **14**, and reply by transmitting an acknowledgment RF signal **24** which encodes data indicative of the identification code that was found encoded in the optical beam **14**. Finally, the interrogator **10** receiving the

acknowledgment RF signal **24**, decodes the identification code encoded therein and thereby determines (e.g. by comparing the identification code decoded from the acknowledgment RF signal **24** with the identification code it had previously encoded in the optical beam **14**) whether the acknowledgment RF signal **24** was sent in response to
5 the interrogation by laser beam **14** in which case it indicates the existence of friendly forces in the area interrogated by the interrogator **10** (e.g. covered by laser beam **14** illumination spot).

Thus, in order to achieve the task of IFF interrogation by optical/laser beam,
10 conventional IFF systems, such as **5000**, require having a specifically selected laser emitter **13** with the desired beam width to be integral with the interrogation system, such that it can be operated by controller **11** to provide/emit an encoded optical/laser beam having a desired/predetermined relatively wide width, encoding the identification code of the interrogation system **10**.

15

Reference is made together to **Figs. 2A, 3, 4A, 5A, 6A and 7A**, which are block diagrams schematically illustrating an Identification Friend or Foe (IFF) system **1000** including an interrogation system **100** (hereinafter also referred to as *interrogator*) and a complementary transponder system **200** (hereinafter also referred to as *transponder*).
20 The interrogator **100** is configured and operable to interrogate a region of interest in search of complementary transponders (e.g. transponders of friendly forces) located in the region of interest. The transponders **200** are adapted for responding to interrogation by the interrogator (typically responding by transmitting suitable RF signals detectable by the interrogator, although other response methods are possible, such as an optical
25 response signal).

According to the present invention, the interrogator system **100** includes a laser activation interface module **130** that is configured and operable for interfacing to an external laser transmitter/module **300** to determine activation of the external (e.g.
30 independent) laser transmitter **300**, for interrogating of the region of interest in conjunction with the interrogator system **100**. It should be understood that the phrase *determine activation* and similar phrases, are used herein to refer to any of the following actions: (i) activating the external laser to generate and "fire" a laser beam, e.g. toward

the region of interest (active mode of operation); and (ii) determining/sensing if the laser was fired (passive mode of operation).

The interrogator system **100** also includes a radio-frequency (RF) transceiver module **120** (i.e. being implemented as separated or combined RF receiver and transmitter module(s)). The RF transceiver **120** is configured and operable for transmitting an RF broadcast signal to be received by an IFF transponder of the complementary IFF transponders being within the interrogation range (region) of the IFF interrogator system and for receiving an RF response signal transmitted by an IFF transponder in response to detection/receipt of both the RF broadcast signal and the laser beam transmitted by the IFF transponder.

To this end, the interrogator system **100** further includes a control system **110** that is connectable to the laser activation interface module **130** and to the RF transceiver module **120**. The control system **110** may be, for example, implemented, or include a computerized system including processing unit PU (e.g. CPU/GPU) and memory for storing computer readable instructions (e.g. firmware or software) for implementing interrogation of a region of interest by carrying out the operations of method **500** illustrated in the flow chart of **Fig. 2B**. Alternatively or additionally, the control system **110** may be implemented by hardware such as analog or digital circuitry adapted to carry out one or more of the operations of method **500**.

More specifically, turning now to **Fig. 2B**, method **500**, which is carried out by the control system **110** for interrogating IFF transponders, includes the following operations:

510 - operating the RF transceiver module **120** to transmit a certain/predetermined RF broadcast signal **1** that arms (e.g. initializes) complementary IFF transponders **200** (complementary to the interrogator **100**) who receive the RF broadcast signal **1**. In this regard, it should be noted that the term *arming* is used herein to indicate that upon receipt of the RF broadcast signal **1**, the receiving IFF transponders **200** are activated and are ready for sensing laser illumination incident on their photodetection module **230**, if such illumination happens to be directed thereto. Such may

advantageously entail the transition of the optical detection modules from a low-power standby mode to the active mode; as IFF interrogations are few and on average occur at large time intervals this allows the transceivers to be mostly in the low-power standby mode, saving on their battery power.

5

520 - utilizing the laser activation interface **130** to determine activation of the external laser transmitter for transmitting the interrogation laser beam to the region of interest. As indicated above, laser activation interface **130** may include an active interface adapted for receiving operational instructions for activating the external laser transmitter **130** from the control system **110**, and upon receipt of the operational instructions, operating the external laser transmitter **300** to transmit a laser beam (e.g. towards the region of interest) to interrogate the region of interest. In this case, in **520** the control system **110** provides operational instructions to the laser activation interface **130** to operate the external laser transmitter. Alternatively or additionally, the laser activation interface **130** may include a passive interface configured and operable for sensing/detecting the activation of the external laser **300**, and upon detecting that the external laser transmitter was activated, providing a signal/data notification indicative of the activation to the control system **110**. Examples of laser activation interfaces **130** configured and operable as passive interfaces are described for example in the following in relation to **Figs. 4A to 6B**. Thus, the interrogator system may include any one or more of the active or passive activation interfaces. Accordingly, in **520** the control system **110** may either passively determine (receive indication (signal/data) that the external laser was fired, or actively trigger the laser to fire when needed (e.g. by providing suitable operational instructions).

540 - Obtain and process information (e.g. data/signal) indicative of RF signals received by the RF transceiver **120** to identify/determine if the received RF signals include an RF response signal **3** (also referred to in the following as acknowledging (ACK) signal) that was transmitted by an IFF transponder **200**, in response to detection of the transmitted optical/laser beam **2** from by the IFF transponder **200**.

30

The IFF transponder **200** includes an RF transceiver **220** (i.e. an RF transmitter and an RF receiver module or a module capable of both receiving and transmitting RF signals), a photodetection module **230** (e.g. including a photodetector, and/or any other suitable light sensor) capable of detecting an illumination/optical beam that is transmitted from the external laser transmitter **300** and incident thereon, and a controller **210** connectable to the RF transceiver **220** and the photodetection module **230**. The controller **210** may be, for example, a computerized system including processing unit PU (e.g. CPU/GPU) and memory for storing computer readable instructions (e.g. firmware or software) for responding to interrogation by the interrogator **100**, by carrying out the operations of method **600** illustrated in the flow chart of **Fig. 2C**. Alternatively or additionally, the controller may be implemented by hardware such as analog or digital circuitry adapted to carry out one or more of the operations of method **600**.

More specifically, turning now to **Fig. 2C**, method **600**, which is carried out by the controller **210** includes the following operations:

610 - obtain data indicative of RF signals received by the RF transceiver module **220**. When the IFF transponder is in standby mode, the RF transceiver module **220** may be continuously operating to receive RF signals and provide data/signals indicative thereof to the controller **210**. In turn, the controller **210**, processes the data/signals about the received RF signals, to determine if an RF broadcast signal **1** from an IFF interrogator **100** was received by the RF transceiver **220**. In this regard, determining whether RF signals received by the RF transceiver module **220** include such an RF broadcast signal from the interrogator, may be based on the wavelengths of the RF broadcast signal and/or the modulation of the RF broadcast signal and/or on data encoded in the RF broadcast signal, such that upon detection of an RF signal with wavelength/modulation/data matching predetermined criteria (e.g. stored in memory of the controller **210**) then the RF signal is identified as an RF broadcast signal **1** from the interrogator **100**. Such criteria may include use of periodically updated security code, and/or of proper encryption of the RF transmission, to ensure that third parties are incapable of interfering with, imitating or intercepting such RF broadcast signals. Upon detection of such a

legitimate RF broadcast signal, the controller **210** sets the IFF transponder in active optical detection mode, in which its photodetector is operated for sensing and/or detection of interrogating laser beam **2** from the IFF interrogator **100**.

5

620 - the controller **210** obtains and processes information (data/signals) obtained from the photodetector **230**, to determine whether an interrogation optical/laser beam from an IFF interrogator **100** was sensed/detected by the photodetection module **230** of the IFF transponder **200**. For instance, the controller **210** may process the information (data/signals) from the photodetector **230**, and upon determining that light exceeding certain illumination intensity and/or light with a certain time pattern (e.g. in cases where the external laser **300** emitters are pulsed or modulated laser beams) is sensed by the photodetector module **230**, the controller determines that an interrogation light beam **2** from an IFF interrogator **100** was detected.

15

640- Upon detection of the interrogation optical beam **2**, the controller **210** operates the RF transceiver **220** to transmit an RF response signal **3** to be received by the IFF interrogator **100**. The RF response signal **3** may be for example an encoded signal, and may, for example, encode data indicative of the identity of the IFF transponder **200**.

20

As indicated above, preferably once obtaining an RF response signal **3** from an IFF transponder, the interrogator **100** should verify that the received RF response signal **3** was transmitted from the IFF transponder **200** in response to the interrogation laser beam **2** that was sent by the interrogator **100** and not in response to detection of a stray laser beam or a laser beam from a different interrogator. Otherwise, in cases where several IFF interrogators are used in the same area, this might result in many false alarms erroneously indicating that friendly forces are in the region of interest that is interrogated by the IFF interrogator **100** (because should the IFF transponder **200** not identify the identity (code) of the IFF interrogator it to which to respond and not encode that in its RF response signal, then all the interrogators receiving the RF response signal

30

would consider it to be sent in response to their interrogation –which will raise many false alarms).

To avoid such a scenario, certain conventional techniques operate the laser to
5 encode the interrogation laser beam with a code identifying the identity of the IFF interrogator which sourced/transmitted the beam. The IFF transponder which detects the interrogation laser beam, decodes the code/identity of the interrogator and encodes it in its RF response signal, so that the IFF interrogators receiving the RF response signal will identify in response to which interrogation laser beam it was sent.

10

However, in the present case, when external laser transmitter **300** is used to transmit the interrogation laser beam **2**, it is mostly not possible, or is impractical, to encode information onto the optical/laser beam transmitted. Therefore, according to certain aspects of the present invention, the code/identity of the IFF interrogator **100** is
15 assigned and communicated in association with the interrogation laser beam **2** alleviating the need to encode the interrogation optical/laser beam **2** itself (i.e. without encoding the interrogation optical/laser beam **2**).

Fig. 3 is a block diagram exemplifying the configurations and methods of
20 operation of an IFF interrogator **100** and of a complementary IFF transponder **200**, which are configured for respectively communicating a code/identity of the IFF interrogator **100** in association with the interrogation laser beam **2**, and determining and encoding that code in the RF response signal **3**, so that an IFF interrogator receiving the RF response signal can determine whether it was sent in response to its interrogation.
25 The IFF interrogator **100** and the IFF transponder **200** of **Fig. 3** are configured and operable similarly to the IFF interrogator **100** and the IFF transponder **200** of **Fig. 2A**, except that here, in addition, the IFF interrogator **100** assigns/associates a code/identity with the interrogation laser beam **2** (e.g. the code is associated with a time delay, or, more generally, a time pattern of time intervals, between the broadcast RF signal(s) **1**,
30 and the interrogation optical/laser beam(s) **2**). Accordingly, in this implementation, the IFF transponder **200** identifies this code/identity (by recognizing the time delay, or the pattern of time intervals, between the receptions of the broadcast RF signal(s) **1**, the

interrogation laser beam(s) **2**), and encodes this code/identity in the response RF signal it transmits.

To this end, the control system **110** of the IFF interrogator is adapted to carry
5 out the operations of method **500** while carrying out additional operations (or sub-operations) as described below, in order to assign the interrogation laser beam **2** with an identifying code. The controller **210** of the IFF transponder **200** carries out the operations of method **600** described above while also carrying out additional operations (and/or sub operations) in order to determine the identifying code assigned to the
10 interrogation laser beam and encode and transmit it together with the RF response signal.

To this end, in **510** the control system **110** transmits certain/predetermined one or more RF broadcast signal(s) **1** to arm the IFF transponders **200**, and in sub-operation
15 **512** it registers (e.g. stores in memory) the time of transmission of one or more RF broadcast signal(s) **1**. In turn, in **610** the controller **210** processes signals received by the RF transceiver **220** and identifies receipt of RF broadcast signal(s) **1**, and in sub-operation **612** it registers (e.g. stores in memory) the time of receipt of the RF broadcast signal(s) **1**.

20

Accordingly in **520** the control system **110** utilizes the activation interface **230** to determine activation (e.g. activate transmission or, or determine occurrence of transmission) of an interrogation laser beam **2** by the external laser module **300**. In addition, in sub operation **522** the control system **110** registers the time of transmission
25 of the interrogation laser beam **2**. In turn, in **620**, the controller **210** process information from the photo detector **230** to determine if the interrogation laser beam(s) **2** was sensed/detected thereby, and registers a time of sensing of the interrogation laser beam **2**.

In this regard, as noted in **530**, the control system utilizes a time delay or a time
30 pattern of time interval(s) between the at least one RF broadcast signal(s) **1** and the interrogation laser beam(s) (typically one laser beam is used for interrogation) as an identification code identifying the interrogation laser beam **2**. More specifically, in some cases, the time pattern is actually a time delay between the RF broadcast signal **1**

and the interrogation laser beam **2** (i.e. the time delay between the time registered at **512** and that registered at **522**). Alternatively, more than one RF broadcast signal **1** and/or more than one interrogation laser beam may be used, and in that case the time pattern may be actually indicative of the sequence to time delays between them. In any case, in
5 **630**, controller **210** determines the time pattern of the time interval between receipt timings of the RF broadcast signal(s) **1** and the interrogation laser beam(s) **2**. Since both the RF signals and the laser beams propagate at substantially similar speeds, then the time pattern/delay determined at **630** is equivalent/substantially matching/equal to the time pattern/delay which is used in **530** to identify the interrogation laser beam(s) **2** by
10 the control system **110**.

It should be noted that in some embodiments the control system **110** is configured and operable for controlling the transmission time of the RF broadcast signal **1** and/or the transmission time of the interrogation laser beam **2** so as to adjust the time
15 delay between them (or more generally adjust a time pattern of time intervals between several transmissions of one or more RF broadcast signal(s) **1** and one or more interrogation laser beam(s) **2**). The time delay/pattern represents an identification code of the IFF interrogation system **100**. To this end, in some embodiments the time pattern/delay is a predetermined time pattern/delay (e.g. which may be stored in a
20 memory module of the control system **110**) representing a predetermined identification code of the IFF interrogation system **100**. Alternatively, the time pattern/delay may be a random/arbitrary time pattern/delay presenting a random/arbitrary name/identification code assigned to the transmission of the interrogation laser beam **2**, based on the time interval that happened to be between it and the RF broadcast signal **1**. In this case, the
25 control system **210** may assign such random/arbitrary name/identification code (based on the time delay) to each interrogation cycle (e.g. to each interrogation laser beam **2**), and store the assigned code in memory.

In **640** the controller **210** transmits an RF response signal **3** while in **642** it
30 encodes the data indicative of the time pattern in the transmitted RF response signal **3** (by any suitable encoding technology). In turn, in **540** the control system **110** obtains and processes the RF signals received by the RF transceiver **120**, and identifies the RF response signal **3** therein and decodes the time pattern encoded therein. Then in **542**, the

control system **110** determines whether the RF response signal **3** encodes the identification code of the interrogation laser beam **2**. More specifically, the control system **110** compares the time pattern decoded in the RF response signal **3** with the time pattern assigned to the interrogation laser beam **2** in **530**. If these time patterns are
5 matching/equivalent (e.g. in case the time delay between the RF broadcast signal **1** and the interrogation laser beam **2** which is registered in **530**, is about equal to the time delay decoded in the RF response signal **3**), then in **534** the control system **110** identifies the received RF response signal, as one transmitted in response to interrogation by the interrogation laser beam **2**. Otherwise, if these time patterns/delays
10 do not match, then it is understood that the RF response signal **3** received by the IFF interrogator **100** may have arrived from another source, or was issued in response to interrogation by another IFF interrogator, and therefore, in this case, it is ignored by the control system **110**.

15 Turning back to **Fig. 2A**, the activation interface **130** of the interrogation system **100** may optionally include passive and/or active interfaces, **132** and/or **134**, that are adapted for passive determination of the laser fire and/or for active triggering its fire, of the external laser transmitter **300**. In various embodiments of the present invention the activation interface **130** is implemented (configured and operable for) for interfacing
20 different modules of the external laser transmitter **300**.

For instance, in some cases the external laser transmitter **300** is expected to optionally include a controller **330** having input **tIN** and/or output **sOUT** timing ports **335** (e.g. "trigger IN" and/or "synchronizing OUT" ports) for respectively receiving
25 trigger signals for triggering laser emission by the laser transmitter **300**, and/or outputting a synchronizing signal when laser beam is emitted by the laser transmitter **300**. In such cases, the activation interface **130** of the interrogation system may be implemented with suitable electronic circuitry and/or a computerized module (optionally implemented as part of the control system **110**) that is adapted for actively
30 triggering fire of the external laser **300** by issuing a proper *trigger in* signal to the trigger input port **tIN** of port(s) **335** of the external laser **300**, and/or possibly determining the fire of the external laser **300** by detecting a *synchronizing out* signal

coming from the synchronizing output port **sOUT** of ports **335**. In this way, active **304** and/or passive **302** interfaces with the external laser **300** may be implemented (wherein *trigger in* port **tIN** in the external laser **300** allows implementation of active interface **304** and a *synchronizing out* port **sOUT** in the external laser **300** allows implementation
5 of the passive interface **302**).

It should be understood that the triggering and synchronizing ports are electronic/communication ports which can be implemented and accessed according to any suitable technique known in the art for example by wired/wireless communication
10 ports adapted to receive/output triggering/synchronizing signals and/or vial electronic I/O ports.

To this end, in some embodiments the laser activation interface **130** includes, or is implemented as, a computerized controller module including at least one of software
15 and/or hardware modules, that are configured and operable for implementing a programming interface for interfacing with a second computerized controller **330** of the external laser transmitter **300**, (e.g. the second computerized controller **330** may include ports **335** such as the triggering and/or synchronizing ports **tIn** and/or **sOut**). The computerized controller module of the laser activation interface **130** may be operable in
20 passive mode for receiving data indicative of the activation state of the external laser transmitter **300** from the second computerized controller **330** and communicating this data to the control system **110**. Alternatively or additionally, computerized controller of the laser activation interface **130** is operable in active mode for receiving from the control system **110** operational instructions for activation of the external laser
25 transmitter **300** and communicating corresponding instructions to the second computerized controller **330** to activate the external laser transmitter accordingly.

Alternatively or additionally, in certain embodiments of the present invention the activation interface **130** is configured and operable for interfacing a switch module
30 **320** of the external laser transmitter **300**, which is operable for triggering fire of the external laser transmitter **300**. The activation interface **130** may include in this case a switch interface assembly **SI** configured for coupling with the activation switch **320** of the external laser module **300**.

In this case, the activation interface **130** may implement an active interface **304**, and the switch interface assembly **SI** may include an active switch interface **ASI** implemented for example with an electro-mechanical module (e.g. Piezoelectric module) that is mechanically coupleable to the activation switch **320** of the external
5 laser **300** and adapted to receive operational instructions/signals from the control system **110** of the interrogator system **110** and mechanically operate/toggle the activation switch **320** of the external laser transmitter **300** (which may be a mechanical switch), accordingly.

10 Alternatively or additionally, in some cases the activation interface **130** may implement a passive interface **132**, and the switch interface assembly **SI** may include a passive switch interface **PSI** implemented for example with a mechanical interface **MI** that is mechanically connected/coupled to the activation switch/button **320** of the external laser **300**, and adapted to detect activation of the external laser transmitter **300**
15 when the activation button/switch **320** is operated, and provide indication (e.g. signal indication) of such activation to the control system **110** of the interrogation system **100**.

For instance, **Figs. 4A to 4C** depict a passive switch interface **PSI** being a member of the activation interface **130** of the interrogation system coupled with the
20 switch **320** of the external laser transmitter **300**. **Fig. 4A** shows the interrogation system **100** including a computerized/digital control system **110** possibly including a memory **MEM** and a user interface **UI** (e.g. a display module) and/or input/output ports **IO** configured and operable to provide data indicative of the interrogation results to a user. The control system **110** is connectable to an RF transceiver **120** capable of receiving the
25 ACK signal **3** from the IFF transponder **200**. Here, the RF transceiver **120** includes an antenna **ANT** possibly connected to an analog to digital (A/D) converter and /or amplifier (any one or both are represented by **AD** in the figure). Also the control system **110** is connectable to activation interface **130**, which is in this case a passive interface adapted for providing the control system with a signal (electric or wireless signal) upon
30 activation of the external laser **300**. In this example the activation interface **130** includes a passive switch interface **PSI** that is coupled to an activation button **320** of the external laser transmitter **300**. The activation interface **130** may include an amplifier **A** for amplifying the activation signal and possibly also digital to analog (D/A) and/or A/D in

cases where such are needed. **Figs. 4B** and **4C** show passive switch interface **PSI** in unpressed and pressed states respectively. In the pressed state the passive switch interface **PSI** is pushed/depressed by a user/operator against the activation button/switch **320** of the external laser **300**, to press/toggle it. At the same time, when pressed, passive switch
5 interface **PSI** also provides/causes provision of a signal indicating that the activation button/switch **320** is pressed to the control system **110**. To this end, in this example the activation button **320** of the external laser module is mechanical and the passive switch interface **PSI** is a mechanical interface that includes a mechanical mechanism **135** that transfers a depression action by a user onto the mechanical activation button **320**, and a
10 switch/button **133** that operates an electric circuit **137** providing the control system **110** with an indication/signal that the activation button **320** was pressed.

Alternatively or additionally, in certain embodiments of the present invention the activation interface **130** is configured and operable for detecting when the external
15 laser transmitter **300** is activated by sensing electromagnetic interference that is associated with the external laser fire and/or with the high electric currents it requires/uses on fire. For instance, **Figs. 5A** and **5B** and **Figs. 6A** and **6B** depict two embodiments of an interrogation system **100** which include a passive electromagnetic interface **PEI**, being a member of the activation interface **130** of the interrogation
20 system **100**. **Figs. 5A** and **6A** show an interrogation system **100** according to two embodiments of the present invention with modules configured similarly to those described above with reference to **Fig. 4A**. Here the control system **110** is connectable to activation interface **130**, which is in this case a passive interface adapted for providing the control system with a signal (electric or wireless signal) upon fire of the
25 external laser **300**. In this example the activation interface **130** includes a passive electromagnetic interface **PEI** including electromagnetic detection means which are implemented in this example by inductance detection circuitry **SOL** (e.g. solenoid/coil) located/wrapped in the vicinity of the laser emitter **310** (e.g. the laser emitter/diode) of the external laser transmitter **300** or in the vicinity of the electric wires/power-supply
30 **312** that are connected to the laser **310**. This laser **310** is a laser emitter such as a diode laser, a solid state laser, a fiber laser or in other forms. **Figs. 5A** and **6A** also depict illustratively a side view of the external laser transmitter **300** coupled with the passive electromagnetic interface **PEI** according to two embodiments of the present invention.

Figs. 5B and **6B** depict illustratively a front view of the external laser transmitter **300** coupled with the passive electromagnetic interface **PEI** according to these two embodiments respectively. The electromagnetic detection means **SOL** of the passive electromagnetic interface **PEI** are adapted to sense the electromagnetic interference
5 caused by the electronic power supply **312** and/or by the laser **310** upon fire of laser beam **2** from the external laser transmitter **300**. It is noted that in **Figs. 5A** and **5B** the electromagnetic detection means **SOL** are shown to include a coil wrapped around the power supply **312** of the external laser transmitter **300** and in **Figs. 6A** and **6B** the electromagnetic detection means **SOL** includes a coil wrapped around the laser **310**. In
10 any case when electric current is supplied by the power-supply **312** to the laser **310**, the electromagnetic detection means **SOL** sense the electromagnetic interference caused by this current and generate in response electric signal/indication that the external laser transmitter is activated to emit a laser beam **3**. The control system **110** receives such an indication and operates as described in method **500** above.

15

It should be noted that in some embodiments of the present invention the passive electromagnetic interface **PEI** and/or electromagnetic detection means may include a light detector (e.g. photodetector, not specifically shown), which can be located in an optical path of at least a portion of the laser output light **2** output and/or scattered from
20 an optical output port of the external laser transmitter **300**. In such embodiments the light detector senses the emitted light **2** and thereby determines/outputs a signal (e.g. photocurrent) to the control system **110** which indicates the activation state of the laser **310**. To this end, the light detector may be used instead of, or in addition to, the inductance detection circuitry **SOL** described in the embodiments of **Figs. 5A** through
25 **6B** above.

Reference is made now together to **Figs. 7A** and **7B**. **Fig. 7A** is a block diagram of an interrogation system **100** adapted to be coupled to an external laser transmitter **300** that provides/emits an optical/laser beam **2** having cross-section dimension **d** that is
30 substantially smaller than the desired cross-sectional dimension **D** of the area that should be covered by the IFF interrogation system **100** by illumination of the laser beam **2** at a certain distance (range) **R** from the external laser transmitter **300**. **Fig. 7B** is a flow chart showing method **700** for operation of the interrogation system **100** to cause

scattering of the laser beam **2** with the small cross-section **d** such that the scattered light **S** illuminates a much larger desired cross-sectional dimension **D** and thereby enables interrogation of IFF transponders **200** located within the cross-sectional area **D** at that distance range **R**. The modules of the IFF interrogation system **100** and the IFF
5 transponder **200** that are shown in **Fig. 7A** may be configured similarly to similar modules described above with reference to Figs. **2A, 3, 4A, 5A** and **6A**.

It should be noted that in order to allow utilization of the scattered light from the narrow cross-section beam **2** for interrogating the cross-sectional area **D**, the external
10 laser transmitter **300** should be adapted to provide the narrow laser beam **2** with intensity **I** of that which is substantially higher than the minimal detection threshold intensity **I_m** of the transponder system **200** (of its photodetection module **230**). More specifically, the external laser transmitter **300** should be adapted to provide a laser beam with intensity **I** (at the distance range **R**) that is in the order of $I \geq I_m \times (d/D)^2$ or higher.
15 To this end, in certain embodiments of the present invention, the interrogation system **100** is adapted to utilize external laser systems **300** such as range finders, which provide high intensity, pulsed, narrow laser beams **2**. Such high intensity pulsed narrow laser beams are indeed suitable for range finders since they need to be able to detect and measure the time of flight of light which is scattered from the laser beam **2** and returns
20 from the distance range that needs to be measured. However, for conventional IFF interrogation systems, such narrow pulsed laser beams of the range finder are less suitable, since they do not cover the entire cross-section **D** that needs to be interrogated.

The present invention solves this problem and allows utilizing narrow (possibly
25 pulsed) high intensity external laser transmitters **300** for IFF interrogation. According to an embodiment of the present invention the IFF interrogation system **100** includes, or is associated with, a beam scattering directive **140** providing instructions for directing the optical output axis **OX** of the external laser module towards light scattering objects/surfaces **LS** (e.g. ground surface) in the vicinity of the distance range **R**, at
30 which the cross sectional dimension **D** should be covered. Accordingly, the cross-sectional dimension **D** is illuminated by scattered light **S** from the laser beam **2** that is scattered from scattering objects/surfaces **LS**.

Fig. 7B is a flow chart **700** of the method/instructions provided by the beam scattering directive **140**. **710** provides instructions for determining/detecting a scattering surface **LS** in the vicinity of the distance range **R** at which IFF interrogation should be conducted by the laser beam **2**. In some embodiments the scattering surface **LS** may be detected/selected manually by an operator of the interrogation system **100**, while in some embodiments the beam scattering directive **140** includes a detector **146** (e.g. optical detector such as an imager) and is adapted to process data/imagery from the detector to detect/identify scattering surfaces near the distance range **R** and determine their location. Alternatively or additionally, a primary scattering surface **LS** that is considered, is the ground near the distance range **R**. In this case, **710** provides instructions to obtain data indicative of the magnitude and direction of the distance range **R** and the height **H** of the external laser transmitter **300** above the ground. **720** provides instructions to determine the orientation angles θ (e.g. azimuth and/or elevation) to direct the optical axis **OX** of the external laser transmitter **300** towards the scattering surface **LS**. In case the scattering surface **LS** is the ground, as indicated above, then the elevation angle to direct the optical axis **OX** is $\theta_e = \tan^{-1}(H/|R|)$. In case of other scattering surfaces **LS** (not ground), the orientation angles θ may be determined by any technique known in the art (e.g. triangulation) based on the relative displacement between the external laser transmitter **300** and the location of the scattering surface **LS**. Determining the orientation angles θ may be performed manually by an operator of the system, or the beam scattering directive **140** may include direction processor **148** (e.g. computerized system) that obtains data indicative of the location of the scattering surface **LS** relative to the external laser transmitter **300** and determines the orientation angle(s) θ accordingly, for instance in the manner described above. **730** provides instructions to direct the optical axis **OX** to the orientation angle(s) θ so as to direct it towards the scattering surface **LS**. Directing the optical axis **OX** may be performed manually, by an operator of the system directing the external laser transmitter **300**. Alternatively or additionally, in some cases the external laser transmitter **300** includes directing system **350** (e.g. motorized gimbal), and the direction processor **148** is adapted to provide/issue instructions to direct the optical axis **OX**, to the directing system **350**, such that directing of the laser beam **2** is performed automatically. **740** provides instructions to determine activation (i.e. trigger fire, or determine fire) of the

interrogation laser beam **2** by the of external laser transmitter **300** (e.g. using the laser activation interface **130**). This may be performed as described above for example with reference to operation **520** of method **500**.

5 As indicated above, one or more of the operations/instructions of method **700** which are provided by the beam scattering directive **140** may be carried out manually by an operator of the system. To this end, beam scattering directive **140** may include operational manual including information/instructions for the operator to carry out certain of the operations of method **700**.

10

 Alternatively or additionally, in some embodiments one or more of the operations/instructions of method **700** are carried out automatically by the beam scattering directive **140**. To this end, the beam scattering directive **140** may include a beam direction module **144** which may be a computerized and/or analogue system
15 implementing certain of the operations of method **700** to adjustment of an orientation θ of the optical output axis **OX**. For instance, the beam direction module **144** may include a direction processor **148** that is configured and operable for computing an orientation angle(s) θ to set/direct the optical output axis **OX** towards the scattering objects/surfaces **LS** and output data indicative of the instructions for adjusting of the
20 orientation of the optical output axis accordingly.

 In some cases a scattering surface considered is the ground surface within several meters near the distance range **R**. The beam scattering directive provides instructions for orienting elevation of the optical output axis **OX** of the external laser
25 module downwards such that it intersects this ground surface. The direction processor **148** may be configured and operable to utilize data indicative of the certain distance range **R** from the external laser module **300** and height position **H** of the external laser module **300** and process/computes an elevation angle θ of the orientation to direct of the optical output axis to intersect the ground at about the distance range such that the
30 ground scatters the laser beam.

In cases where the scattered cross-sectional dimension is insufficient to generate a large enough illumination to cover the region of interest for IFF interrogation, the orientation of the external laser transmitter may be swept across a small angle in one or two attitudes and the laser fired repeatedly to effectively illuminate the entire desired
5 region of interest. Such scanning may be performed manually or be fully automated. In the latter case the angular attitude of the external laser are motorized which serve to sweep the two angles of the laser to cover the desired region of interest.

Alternatively or additionally, the beam direction module **144** may include an
10 imager/detection module **146** capable of imaging/scanning the cross-sectional area dz at the distance range **R**. The direction processor **148** may be connectable to the imager/detection module **146** and adapted to process images/scan-data therefrom to detect/identify one or more light scattering objects/surfaces **LS** at the distance range **R**. Then, upon detection of suitable scattering object/surface **LS**, the direction processor
15 **148** computes the needed orientation θ for directing the optical output axis **OX** to the identified scattering object/surface **LS**.

In some embodiments the beam direction module **144** is connectable to a user interface **UI** and is adapted utilize/operate the user interface to display/provide the
20 user/operator with instructions to adjust the orientation of the optical output axis **OX** to θ . Alternatively or additionally, the external laser module may be associated with a directing (e.g. gimbal) system **350**, and the beam direction module **144** is configured to connect/communicate with the directing system **350** to operate it to adjust the optical output axis **OX** in the desired orientation (e.g. by providing operational directing
25 instructions for operating the directing module **350** accordingly). This enables automatic adjustment of the output optical axis **OX** towards the scattering object/surface **LS**.

Thus, the present invention provides a novel IFF system enabling to carry out IFF interrogation of a desired region of interest by interfacing and operation of an
30 external laser transmitter. The invention in some of its aspects advantageously provides a novel technique for encoding identification code of the interrogation in the temporal delay/pattern between a transmitted RF signal and transmitted interrogation laser beam. Additionally, the technique of the invention, according to some of its aspects, allows

using a relatively narrow laser beam, emitted from an external laser transmitter, to interrogate a region of interest having a wide cross-section.

Throughout this specification and the claims which follow, unless the context
5 requires otherwise, the word "comprise", and variations such as "comprises" and
"comprising", will be understood to imply the inclusion of a stated integer or step or
group of integers or steps but not the exclusion of any other integer or step or group of
integers or steps.

10 The reference to any prior art in this specification is not, and should not be taken
as, an acknowledgment or any form of suggestion that the prior art forms part of the
common general knowledge in Singapore.

CLAIMS:

1. An Identification Friend or Foe (IFF) system comprising an IFF interrogator for interrogation of complementary IFF transponders; the IFF interrogator comprises: an
5 RF transceiver module a control system and a laser activation interface module operable in conjunction with an independent external laser transmitter; whereby:
- (a) the RF transceiver module is configured and operable for transmitting an RF broadcast signal to be received by an IFF transponder of said complementary IFF transponders being within the interrogation range of
10 said IFF interrogator system and for receiving an RF response signal transmitted by the IFF transponder; and
 - (b) the laser activation interface module is configured and operable for interfacing with an external laser module to determine activation of the external laser transmitter of transmission of a laser beam ; and
 - 15 (c) the control system is connectable to said RF transceiver module and to said laser activation interface module, and configured and operable for carrying out IFF interrogation by:
 - i) arming said IFF transponders for sensing laser illumination by operating said RF transceiver module to transmit said RF broadcast
20 signal;
 - ii) utilizing said laser activation interface to determine activation of said external laser transmitter; and
 - iii) processing information indicative of RF signals received by said RF transceiver to identify therein an RF response signal transmitted by
25 said IFF transponder, which is complementary to the IFF interrogation system, in response to detection of said transmitted laser beam from the external laser transmitter by said IFF transponder.
2. The system of claim 1 wherein said laser activation interface comprises an
30 active interface configured and operable for activating said external laser module upon receipt of operational instructions for carrying out said activation from said control system.

3. The system of claim 2 wherein said active interface comprises a switch interface assembly configured for coupling with said activation switch of the external laser module and operation of said activation switch in response to said operational instructions.

5

4. The system of claim 3 wherein said activation switch is a mechanical switch and wherein said switch interface assembly includes electro-mechanical module mechanically coupleable to said activation switch and adapted to receive said operational instructions from the control system and mechanically operate said activation switch in accordance with said operational instructions.

10

5. The system of any one of claims 1 to 4 wherein said laser activation interface comprises a passive interface configured and operable for sensing activation of the external laser.

15

6. The system of claim 5 wherein said passive laser activation interface comprises a mechanical interface configured and operable for mechanically coupling with an activation button of the external laser transmitter to detect activation of the external laser transmitter when said activation button is operated and provide indication of said activation to the control system.

20

7. The system of claim 6 wherein said activation button of said external laser module includes a mechanical activation button and said mechanical interface comprises a mechanical mechanism that transfers a depression action by a user onto the mechanical activation button for activating the external laser while providing said indication.

25

8. The system of claim 5 to 7 wherein said passive interface comprises electromagnetic detection means which can be located in the vicinity of said external laser to detect the electromagnetic transmission of the external laser's electronic power supply when the laser beam is transmitted.

30

9. The system of claim 8 wherein said electromagnetic detection means comprises inductance detection circuitry configured and operable for sensing high electric currents associated with the activation of the external laser module.

5 **10.** The system of claim 8 or 9 wherein said electromagnetic detection means comprises a light detector to be located in an optical path of at least a portion of laser light output and/or scattered from an optical output port of said external laser module to thereby detect activation state of said laser.

10 **11.** The system of any one of claims 1 to 10 wherein said laser activation interface comprises a computerized controller module including at least one of software and/or hardware modules, configured and operable for implementing a programming interface for interfacing with a second computerized controller of said external laser module which is associated with activation of said external laser module.

15

12. The system of claim 11 wherein computerized controller module is operable in passive mode for receiving from said second computerized controller of said external laser module data indicative of activation state of said external laser and communicating said data to said control system.

20

13. The system of claim 11 or 12 wherein said computerized controller module is operable in active mode for receiving from the control system operational instructions for activation of said laser, and communicating corresponding instructions to said second computerized controller to activate said external laser module accordingly.

25

14. The system of any one of claims 1 to 13 wherein said computerized controller module is configured and operable for carrying out the following:

- i)** registering time of transmission of at least one RF broadcast signal by said RF transceiver;
- 30 **ii)** registering time of activation of at least one interrogation laser beam transmitted by said external laser transmitter;
- iii)** determine a time pattern associated with time intervals between said at least one RF broadcast signal and said at least one interrogation laser

beam; said time pattern representing a identification code of the IFF interrogator system;

iv) obtaining information from said RF transceiver indicative of RF signals received thereby;

5 **v)** process said information to identify if said RF signals include an RF response signal from a certain IFF transponder and decode said RF response signal to determine if it encodes the identification code of the IFF interrogator system which was represented by the time pattern of the at least one transmitted RF broadcast signal and at least one
10 transmitted interrogation laser signal, and thereby determine if said certain IFF transponder was interrogated by said IFF interrogator system.

15. The system of claim 14 wherein said control system is configured for controlling
15 transmission time of at least one of said RF broadcast signal and said interrogation laser beam and thereby adjust said time pattern of the time intervals between them, which represents the identification code of the IFF interrogation system.

16. The system of claim 15 wherein said time pattern is a predetermined time
20 pattern indicative of a predetermined identification code of said IFF interrogation system and is stored in a memory module associated with said control system.

17. The system of claim 16 wherein said time pattern is a random/arbitrary time
pattern representing of a arbitrary name code, and wherein said control system is
25 adapted to assign said arbitrary name code to the IFF interrogation system in every one or more interrogation cycles.

18. The system of any one of claims 1 to 17 wherein said external laser module
provides a laser beam having a cross-section which is substantially smaller than a cross-
30 sectional dimension of an area that should be covered by the IFF interrogation system via illumination at a certain distance range from the external laser module, and intensity of said laser beam is substantially higher than the minimal intensity detection threshold of a transponder system complementary with said IFF interrogation system; and

wherein the IFF interrogation system is associated with a beam scattering directive providing instructions for directing the optical output axis of the external laser module towards light scattering objects/surfaces in the vicinity of said distance range at which said cross sectional dimension that should be covered, so that said area is illuminated by
5 light from said laser beam that is scattered from scattering objects/surfaces.

19. The system of claim 18 wherein said scattering surfaces includes a ground surface and said beam scattering directive provides instructions for orienting elevation of the optical output axis of the external laser module downwards such that it intersects
10 the ground in the order of several meters near about said distance range.

20. The system of claim 18 or 19 wherein said a beam scattering directive comprises instructions for sweeping the orientation of the optical axis of the external laser transmitter across a certain angular span such that the area that should be covered
15 by the IFF interrogation system is effectively illuminate by light scattered from said laser beam during said swiping.

21. The system of any one of claims 18 to 20 wherein said beam scattering directive is at least partially implemented by an operation manual of said IFF interrogation
20 system which includes information indicative of said instructions.

22. The system of any one of claims 18 to 21 wherein said beam scattering directive is at least partially implemented by a beam direction module of the IFF interrogation system which is configured and operable to provide instructions for adjustment of an
25 orientation of said optical output axis.

23. The system of claim 22 wherein said beam direction module includes a direction processor configured and operable for computing an orientation angle to set said optical output axis to direct it towards said scattering objects/surfaces and output data
30 indicative of said instructions for adjusting of the orientation of said optical output axis accordingly.

24. The system of claim 23 wherein a direction processor utilizes data indicative of said certain distance range from the from the external laser module and height position of said external laser module and computes an elevation angle of the orientation to direct said optical output axis to intersect the ground at about said distance range such
5 that the ground scatters said laser beam.

25. The system of claim 23 or 24 wherein said by a beam direction module comprises an imager module for imaging said area at said distance range and wherein said direction processor is connectable to said image and is adapted to process images
10 from said imager to detect and identify one or more scattering objects/surfaces at said distance range, and computes said orientation to direct said optical output axis to at least one of said identified scattering objects/surfaces.

26. The system of any one of claims 22 to 25 wherein said beam direction module is
15 connectable to a user interface and is adapted for providing said data indicative of the instructions to adjust the orientation of said optical output axis, for display by said user interface to allow an operator of the system to adjust said optical output axis accordingly.

20 27. The system of any one of claims 22 to 26 wherein said external laser module is associated with a directing system capable of adjusting its optical output axis, and wherein the beam direction module is configured and operable for connecting to said directing system for providing operational directing instructions for operating said directing module in accordance with the desired orientation of said optical output axis,
25 thereby enabling automatic adjustment of the output optical axis of said laser beam towards said scattering objects/surfaces.

28. An Identification Friend or Foe (IFF) interrogator system for interrogating complementary IFF transponders which are complementary to the IFF interrogation
30 system; the interrogator system comprises: an RF transceiver module and a control system; and wherein the interrogator system comprises an activation interface module operable in conjunction with an independent external laser transmitter, whereby:

- (a) the RF transceiver module is configured and operable for transmitting an RF broadcast signal to be received by an IFF transponder and for receiving an RF response signal transmitted from the IFF transponder in response thereto;
- (b) the laser activation interface module is configured and operable for interfacing with the external laser transmitter to determine activation and provide a synchronizing signal indicative of a time of transmission of laser beam by the external laser transmitter; and
- (c) the control system is connectable to said RF transceiver module and to said laser activation interface and configured and operable for:
 - i) registering time of transmission of at least one RF broadcast signal by said RF transceiver;
 - ii) registering time of transmission of at least one laser beam transmitted by said external laser transmitter;
 - iii) determining a time pattern associated with time intervals between said at least one RF broadcast signal and said at least one laser beam, beam said time pattern representing an identification code of the IFF interrogator system;
 - iv) obtaining information from said RF transceiver indicative of RF signals received thereby;
 - v) processing said information to identify if said RF signals include an RF response signal from a certain IFF transponder and decode said RF response signal to determine if it encodes the identification code of the IFF interrogator system which was represented by the time pattern of the at least one transmitted RF broadcast signal and at least one transmitted laser beam, and thereby determine if said certain IFF transponder was interrogated by said IFF interrogator system.

29. Identification Friend or Foe (IFF) transponder comprising:

- (a) a photo detector configured and operable for detecting light illumination in a certain wavelength band when intensity of said illumination exceeds a certain threshold;

- (b) an RF transceiver module configured and operable for receiving an RF broadcast signal transmitted by an IFF interrogation system complementary to said IFF transponder, and for transmitting an RF response signal to be received by said IFF interrogation system; and
- 5 (c) a controller connectable to said RF transceiver module and to said photo detector, said controller being adapted to:

 - i) process signals received by the RF transceiver to identify receipt of at least one RF broadcast signal from an IFF interrogation system;
 - 10 ii) process information obtained from said photo detector to identify detection of at least one interrogation laser beam by said photo detector;
 - iii) determine a time pattern associated with the time interval between receipt time of said at least one RF broadcast signal and detection time of said at least one interrogation laser beam ; and
 - 15 iv) operate said RF transceiver for transmitting said RF response signal such that the RF response signal encodes data indicative of said time pattern and wherein the time pattern representing an identification code of the interrogator to which said RF response signal is designated.

20

30. An Identification Friend or Foe (IFF) interrogator system comprising:

- (a) a laser activation interface module configured and operable for interfacing an external laser module to determine activation of a laser beam by the external laser module;
- 25 (b) an RF transceiver module configured and operable for receiving an RF response signal transmitted from an IFF transponder complementary to the IFF interrogation system, in response to interrogation of the IFF transponder by an interrogation laser beam;

wherein said external laser module outputs a laser beam having a cross-section

30 substantially smaller than a cross-sectional dimension of the area to be covered by said IFF interrogation system via illumination at a certain distance range from the external laser module, and intensity of said laser beam is substantially higher than the minimal

intensity detection threshold of a transponder system complementary to said IFF interrogation system; and

wherein the IFF interrogation system is associated with a beam scattering directive providing instructions for directing the optical output axis of the external laser module towards light scattering objects/surfaces in the vicinity of said distance range at which said cross sectional area should be covered, such that said cross-sectional area is illuminated by light scattered from said laser beam by said scattering objects/surfaces.

31. The system of claim 30 wherein said a beam scattering directive comprises instructions for sweeping the orientation of the optical axis of the external laser transmitter across a certain angular span such that the area that should be covered by the IFF interrogation system is effectively illuminate by light scattered from said laser beam during said swiping.

32. The system of claim 30 or 31 wherein said beam scattering directive is at least partially implemented by an operation manual of said IFF interrogation system which includes information indicative of said instructions.

33. The system of any one of claims 30 to 32 wherein said beam scattering directive is at least partially implemented by a beam direction module of the IFF interrogation system which is configured and operable to provide instructions for adjustment of an orientation of said optical output axis.

34. An Identification Friend or Foe (IFF) interrogation method comprising carrying out IFF interrogation by carrying out the following:

- (a) transmitting at least one RF broadcast signal suitable for receipt by a complementary IFF transponder;
- (b) registering a time of transmission of said at least one RF broadcast signal by said RF transceiver;
- (c) operating a laser activation interface module adapted to interface an external laser transmitter, to determine activation of the external laser transmitter for transmitting at least one interrogation laser beam towards an interrogation region of interest;

- (d) determining and registering a time of transmission of said at least one interrogation laser beam by the external laser transmitter;
- (e) determining a time pattern associated with time intervals between transmission times of said at least one RF broadcast signal and said at least one interrogation laser beam, said time pattern representing an identification code of the IFF interrogator system;
- (f) obtaining information about RF signals received by an RF receiver;
- (g) processing said information to determine whether the RF signals includes an RF response signal from an IFF transponder; and
- (h) upon detection of an RF response signal from a certain IFF transponder, decoding said RF response signal to determine whether it encodes the identification code of the IFF interrogator system which was represented by the time pattern, and thereby determine whether said certain IFF transponder was interrogated by said at least one interrogation laser beam.

15

35. Friend or Foe Identification (IFF) transponding method comprising:

- (a) process signals received by the RF transceiver to identify receipt of at least one RF broadcast signal from an IFF interrogation system, and register time of said receipt
- (b) process signals obtained from said photo detector to identify detection of at least one interrogation laser beam by said photo detector, and register time of said detection;
- (c) determine a time pattern associated with the time interval between the time of receipt of said at least one RF broadcast signal and the time of detection of said at least one interrogation laser beam; and transmitting an RF response signal encoding data indicative of said time pattern; said time pattern representing an identification code of the interrogation laser beam of an IFF interrogator to which said RF response signal is designated.

25

36. An Identification Friend or Foe (IFF) interrogation method for carrying out IFF interrogation, the method comprising:

providing a beam scattering directive including instructions for directing the optical output axis of an external laser transmitter; wherein said external laser

30

transmitter outputs a laser beam with a cross-sectional area that is substantially smaller than a cross-sectional area to be illuminated at a certain distance range during said IFF interrogation, and intensity of said laser beam is substantially higher than the minimal intensity detection threshold of an IFF transponder system intended to respond to said IFF interrogation;

wherein said instructions for directing the optical output axis of said external laser transmitter comprise instructions to direct said optical output axis towards light scattering surfaces in the vicinity of said certain distance range such that said cross-sectional area is illuminated by light scattered from said laser beam by said scattering surfaces.

37. The method of claim 36 wherein said beam scattering directive is at least partially implemented by an operation manual of said IFF interrogation system which includes information indicative of said instructions.

38. The method of claim 36 or 37 wherein said beam scattering directive is at least partially implemented by a beam direction module of the IFF interrogation system which is configured and operable to provide one or more of said instructions as operational instructions to directing module of said external laser system to adjust said orientation of the optical output axis.

39. The method of any one of claims 36 to 38 wherein said instructions comprise at least one of the following:

- i)** instructions for detecting a scattering surface in the vicinity of said distance range;
- ii)** instructions for determining the orientation angle to direct said optical output axis towards said scattering surface;
- iii)** instructions for directing the optical output axis to the orientation angle(s) θ so as to direct it towards said scattering surface;
- iv)** instructions for activating, or determining activation of the external laser transmitter after said optical output axis is directed towards said scattering surface;

- v) instructions for sweeping the orientation of the optical axis of the external laser transmitter across a certain angular span such that the area that should be covered by the IFF interrogation system is effectively illuminated by light scattered from said laser beam during said swiping.