



- (51) **International Patent Classification:**
G06F 3/041 (2006.01)
- (21) **International Application Number:**
PCT/US2014/030656
- (22) **International Filing Date:**
17 March 2014 (17.03.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/798,828 15 March 2013 (15.03.2013) US
14/216,791 17 March 2014 (17.03.2014) US
- (71) **Applicant:** TACTUAL LABS CO. [US/US]; 160 Wooster Street, Penthouse B, New York, New York 10012 (US).
- (72) **Inventors:** FORLINES, Clifton; 362 Waltham Street, Newton, Massachusetts 02465 (US). LEIGH, Darren; 17615 Greenleaf Place, Round Hill, Virginia 20141 (US). WIGDOR, Daniel; 517 Newtown Road, Littleton, Massachusetts 01460 (US). SANDERS, Steven Leonard; 160 Wooster Street, Penthouse B, New York, New York 10012 (US).
- (74) **Agents:** KURTZ, Richard et al.; 450 So. Orange Ave., Suite 650, Orlando, Florida 32801 (US).
- (81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]


(54) **Title:** FAST MULTI-TOUCH NOISE REDUCTION

FIG. 1

(57) **Abstract:** A low-latency touch sensitive device provides a method for determining a location of a touch event thereon. The touch sensitive device row conductors and column conductors, the path of each of the row conductors crossing the path of each of the column conductors. Each of a set of orthogonal row signals are simultaneously transmitted on a respective one of at least some of the row conductors and an amount of each of the plurality of orthogonal row signals present on each of the plurality of column conductors is detected. A set of orthogonal column signals are simultaneously transmitted on a respective one of at least some of the column conductors. An amount of each of the orthogonal column signals present on each of the plurality of row conductors is detected. The detected amount of each of the plurality of orthogonal row signals and the detected amount of each of the plurality of orthogonal column signals is used to determine the location of a touch event on the device.

**Published:****(88) Date of publication of the international search report:**

13 November 2014

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*