

Power collector structure and method

The invention relates to a power collector structure according to the pre-characterizing part of Claim 1.

5

The invention also relates to a method for collecting power.

In many wireless devices, the acquisition of power has arisen to a central position. For vibrating items, piezoelectricity-based solutions have been developed, but their operational
10 life-time is poor. MEMS has been considered a promising solution, but the MEMS-structures' performance at collecting power, as such, is poor, due to their small size.

15 Also known are solutions for collecting power based on the RFID-technique, but in these, the hardware configuration is expensive. In car tyres, solutions for collecting power based on induction are also known, but in the mechanically extremely testing environment, the durability of these
20 solutions has been poor. In gauging the pressure of car tires, also batteries have been used in connection with an electric pressure sensor and its transmitter, but the problem with such a solution is the recurring need for battery replacement.

25

In this invention, a method is presented for collecting power, said method being particularly well suited for use with car tyres. The method is based on a pin, which is caused to vibrate, when a portion of the tyre intended to contact
30 the surface under the tyre is being bent as it hits the ground. Typically, one end of the pin is fixed to the tyre by vulcanization to the inner surface of the peripheral shell of the tyre. At the tip of the pin, there is such a MEMS

acceleration sensor or piezoelectric element, which is able to collect power under influence of the accelerations associated with the changes in the motion state of the tyre. When the part of the surface of the car tyre facing the
5 running surface makes contact with the road surface, a sudden change in angle of several tens of degrees will occur in the surface of the tyre, which change is dependent on the tyre pressure. As a result of the change in angle, the pin bends and starts vibrating. A periodical acceleration is incurred
10 in the MEMS or piezoelectric collector at the tip of the pin, until attenuation dampens the vibration.

More precisely stated, the power collector according to the invention is characterized in what is presented in the
15 characterizing part of Claim 1.

As for the method according to the invention, it is characterized in what is presented in the characterizing part of Claim 12.
20

In the power collector structure according to an embodiment of the invention, it is connected to the base so rigidly, that the intrinsic resonance frequency of the power collector structure determines the total resonance frequency to at
25 least 50%.

The power collector structure according to an embodiment of the invention comprises an electromechanical converter.

30 In the power collector structure according to an embodiment of the invention, said electromechanical converter is a MEMS converter.

In the power collector structure according to an embodiment of the invention, the base is the inner surface of the periphery of a car tyre.

- 5 In the power collector structure according to an embodiment of the invention, the base is a shoe or part of it.

The power collector in the power collector structure according to an embodiment of the invention comprises a MEMS
10 element.

The electromechanical converter of the power collector according to an embodiment of the invention is provided with bias means for providing said converter with a bias voltage.
15

According to an embodiment of the invention, said bias means are implemented by means of a piezoelectric element.

According to an embodiment of the invention, said bias means
20 are implemented by means of a suitable material couple.

According to an embodiment of the invention, the power collector comprises a piezoelectric element.

- 25 In the power collector structure according to an embodiment of the invention, gauging electronics are integrated in the power collector.

In the power collector structure according to an embodiment
30 of the invention, sending electronics are integrated in the power collector.

In the method according to an embodiment of the invention, the power collector structure being connected to the base so rigidly, that the intrinsic resonance frequency of the power collector structure determines the total resonance frequency to at least 50%.

In the method according to an embodiment of the invention, an electromechanical converter is being used as a power collector structure. In the method according to one embodiment of the invention, said electromechanical converter is a MEMS converter.

In the method according to an embodiment of the invention, the inner surface of the periphery of a car tyre is being used as a base.

In the method according to an embodiment of the invention, a shoe or a part of it is being used as a base.

In the method according to an embodiment of the invention, a MEMS element provided with a bias voltage is being used in the power collector.

In the method according to an embodiment of the invention, the bias voltage is implemented by means of a piezoelectric element.

In the method according to an embodiment of the invention, the bias voltage is implemented by means of a suitable couple of materials.

In the method according to an embodiment of the invention, a piezoelectric element is being used as the power collector.

In the method according to an embodiment of the invention, gauging electronics are integrated in the power collector.

- 5 In the method according to an embodiment of the invention, sending electronics are integrated in the power collector.

A car tyre according to an embodiment of the invention comprises a power collector according to one embodiment of
10 the invention.

A shoe according to an embodiment of the invention comprises a power collector according to an embodiment of the
invention.

15 A roller structure according to an embodiment of the invention contains a power collector according to an embodiment of the invention.

20 In a method, according to an embodiment of the invention, for manufacturing a power collector structure, it is formed by attaching to the power collector structure a component to be used presented in a method according to an embodiment of the invention.

25 In a method, according to an embodiment of the invention, for manufacturing a power collector structure, it is formed to be attached as a component of such a structure, according to an embodiment of the invention, like a car tyre, a part of a car
30 tyre, a rim, or a combination of those, a shoe, or a roller structure.

Remarkable advantages are being achieved by means of the invention.

The invention provides an inexpensive and maintenance-free
5 pressure sensor for, for instance, a car tyre. Calculations show, that then power exceeding 1 mW can easily be obtained by means of arrangements, which power is up to 10 times more than the power needed by the electronics associated with a pressure sensor. One preferable application of the method is
10 the monitoring of the tyre pressure in vehicles, but the method can be used for other applications as well. In this method, we concentrate on that, at first, energy is being stored by a spring, but, of course, it is conceivable that energy through acceleration initially is being bound to
15 kinetic energy of a mass. This opens up several application targets for the method. In addition to tyres, the functional principle of the method works in shoes and roller mats, for example, so it can be utilized in connection with, for example, snowmobile rollers for monitoring the condition of
20 the roller or the snow characteristics.

Below, the invention is being examined with the aid of the embodiment examples according to the figures, in which

25 Fig. 1, in a block diagram, shows a power collector according to the invention.

Fig. 2 shows the block diagram of Fig. 1 in more detail, and

30 Fig.3 shows an embodiment of the invention in connection with a car tyre.

According to Fig. 1, an example of an embodiment of a power collector according to the invention comprises a power collector 1 connected to electronics 2 requiring electric power.

5

According to Fig. 2, the power collector typically comprises a MEMS element 3, the equivalent circuit of which, according to one embodiment of the invention, comprises a capacitor. In practice, the capacitance of this capacitor is created by a stationary electrode and a bar vibrator located adjacent to that, forming the other electrode of the capacitor. A bias voltage is applied between these two electrodes, and then the vibrating bar of the bar vibrator generates an AC voltage between its poles. The bias voltage can be formed by means of a battery, a piezoelectric element, or a so called build-in effect, whereby a voltage will appear between two different materials. This voltage is rectified by means of a rectifier 4 and is input to the electronic circuitry 2 comprising the gauging electronics 5, including the sensor 7 and the transmission electronics 6 to which a transmission antenna 8 is connected. The sensor 7 is typically a pressure sensor.

The element 3 can also be substituted by a piezoelectric element, which can be placed either at the tip of the pin 10, described below, or around said tip of it.

According to Fig. 3, a rather short pin 10 is fixed to the tyre 12 at the inner surface 11 of the peripheral shell of the car tyre, i.e. into the pressurized interior of the car tyre 12. The pin 10 is fixed to the inner surface 11 of the peripheral shell by means of a suitable anchor 9. If the characteristic frequency of the pin 10 is sufficiently low, the mass of the pin 10 stays in place as the tyre bends, and

then a spring transfers the change energy according to the spring constant of the pin into energy stored in the spring structure. After the change, the pin 10 starts vibrating at its characteristic frequency. A MEMS power collector 1, 2 is
5 installed at the tip of the pin 10. According to one embodiment of the invention, it is also preferable for the pressure sensor 7 to be located at the tip of the pin in order to achieve a larger mass. If the Q value of the pin 10 is sufficiently large, (frequently up to 1000), power is
10 being collected in the form of electricity essentially solely via the MEMS 3. According to one embodiment of the invention, it is essential, that in the MEMS 3, there additionally is, for example, a piezoelectric element for generating the bias voltage, in order for the MEMS 3 to operate as a power
15 collector. If, however, the gap in the MEMS is very narrow, the piezoelectric element can be eliminated, since the so called build-in voltage frequently generates a voltage across the gap. A battery can also be used for generating the bias voltage, without being restricted just to a battery alone.
20 Then the battery will have very long lifetime, since the bias voltage alone, as such, will not deplete the battery at all, in practice.

In this application, the term "pin" denotes an elongated,
25 bar-like structure with a minimum diameter clearly smaller than the length of the structure.

Mathematical analysis

30 If the bending of the surface of the tyre 12 is sufficiently rapid, in a certain sense, in relation to the characteristic frequencies of the pin 10, the surface bends to the degree of an angle φ , which essentially depends on the weight of the

car and the tyre pressure. From the viewpoint of a mass at the tip of the pin, this means a displacement of x_Δ . In this case, the energy stored by means of the pin 10 is

$$5 \quad E = \frac{1}{2} k x_\Delta^2 = \frac{1}{2} m \omega^2 x_\Delta^2$$

where k is the spring constant of the pin, ω is the characteristic frequency of the pin's vibration, and m is the mass of the pin. The displacement can be expressed by means
10 of the length l of the pin and the angle φ , which depicts the change in curvature as the pertinent part of the tyre has hit the road surface. The displacement can be given in the form

$$x_\Delta = l \tan \varphi$$

15

The angle φ can be expressed by means of the track $2h$ of the tyre on the underlying surface (the part having contact between the tyre, or corresponding, and the underlying surface) and the radius r of the tyre

$$20 \quad \varphi = \arcsin \frac{h}{r}$$

i.e. yielding

$$x_\Delta = l \tan \arcsin \frac{h}{r} = l \frac{h}{r \sqrt{1 - (h/r)^2}} \approx l \frac{h}{r}$$

Now the total energy can be given in the form

$$E = \frac{1}{2} m \omega^2 \ell^2 \left(\frac{h}{r} \right)^2$$

25 The assumption being that travel from a round part of the tyre to the flat one occurs as the tyre rotates through the displacement angle φ_m . From this, the time associated with this displacement can be calculated.

$$\Delta t = \frac{r\varphi_m}{v_a}$$

Since the mass at the change phase, because of mass inertia, must resist changes in the state of motion, remaining in its momentary state, for the change energy associated with the bending of the surface of the tyre to transfer into spring energy, we arrive at a prerequisite for the mechanical resonance frequency of the pin.

$$\omega \leq 2\pi \frac{v_a}{r\varphi_m}$$

If this delimiting frequency is used, the maximum energy is obtained in the form

$$E = 4\pi^2 \frac{1}{2} m v_a^2 \left(\frac{\ell h}{r^2 \varphi_m} \right)^2$$

Energy is obtained twice per rotation, so the repetition frequency will be

$$f = \frac{v_a}{\pi r}$$

Now the average power can be expressed in the form

$$P = 4\pi \frac{v_a}{r} \left(\frac{\ell h}{\varphi_m r^2} \right)^2 \frac{1}{2} m v_a^2$$

Assuming the pin having the mass $m = 0.002$ kg (0.07 ounce), the velocity being $v_a = 50$ km/h (31 mile/h), the length of the pin $\ell = 0.01$ m (0.39 inch), the radius of the tyre $r = 0.30$ m (11.81 inch) and the total length of the track $2h = 0.1$ m (3.94 inch) and the bending angle, corresponding to the track, being $\varphi_m = 0.03$ rad (1.72 degree), the power obtained is $P = 0.4$ W. In practice there will be less power, since the resonance frequency of the pin cannot be dimensioned to be arbitrarily large. On the other hand, the MEMS element 3 is

not necessarily able to collect, in its entirety, all of the energy bound to the pin. However, the quality factor of this kind of pin or bar 10 can be up to 1000, so the MEMS element 3 constitutes a load to the vibration in such a way, that the quality factor is determined by the power collection by the MEMS. Considering that the characteristic frequency is dimensioned at about 10 times lower than the maximum frequency, the power will be about 4 mW. Typically, a sensor for the pressure in a car tyre requires about 0.1 mW of power, so the technique according to the method according to an embodiment of the invention is sufficient for that application.

The primary application of the invention is collecting power from a tyre. In applications in which there is vibration or bending of a structure, the method can be utilized. In a car tyre, also the pressure can be gauged by means of the Q-value of the pin 10, which is proportional to the pressure in the tyre 12. Regrettably, dampness also influences the result. The pendulum motion of the pin 10 must perhaps be restricted in order for the structure according to an embodiment of the invention to be durable. An advantage of the method according to an embodiment of the invention is that the bending, as such, is not depending on the speed of the car, in the same way as the acceleration. If the acceleration does not directly influence the transversal motion of the pin, the invention enables such a structural solution in which such a durable structure is achieved, which is able to collect power also at low tyre speeds.

30

The durability of the structure according to an embodiment of the invention can be improved such, that the pin 10 lightly touches a delimiter, a rubber stop, for instance, and thus

any large motion is subject to damping. The maximum amplitude can also be attenuated by this method. If the spring in the structure is stiff, the mass will follow the bending, whereby the pin is subject to less bending, which improves the

5 durability of the pin.

Patent claims:

1. A power collector structure (10) connected to a base (11) that is repetitively deformed or bent,
5 **characterized** in that:
 - the power collector structure (10) is a bar-like pin,
 - the power collector structure (10) is radially connected to the base (11) in an essentially rigid manner, and
 - 10 - a power collector (3) for converting mechanical energy to electric power is in the tip of the power collector structure (10).
2. The power collector structure according to Claim 1,
15 **characterized** in that the power collector structure (10) is connected to the base (11) so rigidly, that the intrinsic resonance frequency of the power collector structure (10) determines the total resonance frequency to at least 50%.
- 20 3. The power collector structure (10) according to any one of the preceding patent claims, **characterized** in that the power collector structure (10) comprises an electromechanical converter.
- 25 4. The power collector structure (10) according to any one of the preceding patent claims, **characterized** in that the base (11) is the inner surface (11) of the periphery of a car tyre (12).
- 30 5. The power collector structure (10) according to any one of the preceding Claims 1–3, **characterized** in that the base (11) is a shoe or a part of it.

6. The power collector structure (10) according to any one of the preceding patent claims, **characterized** in that the power collector comprises bias means for providing a MEMS element with a bias voltage.

5

7. The power collector structure (10) according to Claim 6, **characterized** in that the bias means for providing the bias voltage is implemented by means of a piezoelectric element.

10 8. The power collector structure (10) according to Claim 6, **characterized** in that the bias means for providing the bias voltage is implemented by means of a suitable material couple.

15 9. The power collector structure (10) according to any one of the preceding patent claims, **characterized** in that the power collector (3) comprises a piezoelectric element.

20 10. The power collector structure (10) according to any one of the preceding patent claims, **characterized** in that gauging electronics (2) are integrated in the power collector (3).

25 11. The power collector structure (10) according to any one of the preceding patent claims, **characterized** in that transmission electronics (6) are integrated in the power collector (3).

30 12. A method for collecting power of a base (11) that is repetitively deformed or bent, in which method a power collector structure (10) is being used, **characterized** in that in the method there is being utilized

- a bar-like pin as a power collector structure (10) connected radially and essentially rigidly to a base (11),

and a power collector (3) for converting mechanical energy to electric power in the tip of the power collector structure (10).

- 5 13. The method according to Claim 12, **characterized** in that the power collector structure (10) is so rigidly connected to the base (11) that the intrinsic resonance frequency of the power collector structure (10) determines the total resonance frequency to at least 50%.

10

14. The method according to claim 12 or 13, **characterized** in that an electromechanical converter is being used as the power collector structure (10).

- 15 15. The method according to any one of the preceding claims 12 to 14, **characterized** in that the inner surface (11) of the periphery of a car tyre (12) is being used as the base (11).

16. The method according to any one of Claims 12 to 14,
20 **characterized** in that a shoe, or a part of it, is being used as the base (11).

17. The method according to any one of the preceding claims 12 to 16 **characterized** in that a MEMS element (3) provided
25 with a bias voltage is being used as the power collector.

18. The method according to Claim 17, **characterized** in that, in the method, the bias voltage is implemented by means of a piezoelectric element.

30

19. The method according to Claim 17, **characterized** in that, in the method, the bias voltage is implemented by means of a suitable material couple.

20. The method according to any one of the preceding claims 12 to 19, **characterized** in that, in the method, a piezoelectric element is being used as the power collector (3).

21. The method according to any one of the preceding claims 12 to 20, **characterized** in that, in the method, gauging electronics (2) are integrated in the power collector (3).

22. The method according to any one of the preceding claims 12 to 21, **characterized** in that, in the method, transmission electronics (6) are integrated in the power collector (3).

23. A car tyre, characterized in that it comprises a power collector according to any one of the preceding Claims 1 to 11.

24. A shoe, characterized in that it comprises a power collector according to any one of the preceding Claims 1 to 11.

25. A roller structure, characterized in that it comprises a power collector according to any one of the preceding Claims 1 to 11.

26. A method for manufacturing a power collector structure, **characterized** in, that, in the method, the power collector structure is being formed by connecting to the power collector structure a part presented by a method according to any one of Claims 12–22.

27. The method according to Claim 26, characterized in, that
the power structure is a part of a structure according to any
one of Claims 23–25 being a car tyre, a part of a car tyre, a
rim, or a combination of such items, a shoe, or a roller
5 structure.